

CONTENTS

| | |
|---|------|
| Introduction: The Function of Boiler Water Treatment and Its Marketing | xvii |
| 1 Steam Generation | 1 |
| 1.1 Basics of Steam Generation | 4 |
| 1.2 Energy, Work, and Power | 10 |
| 1.3. Boiler Plant Efficiency | 14 |
| 2 Boiler Types and Applications | 23 |
| 2.1 Electric Boilers | 24 |
| 2.2 Fire Tube (Shell) Boilers | 29 |
| 2.3 Water Tube Boilers | 39 |
| 2.4 Nuclear Reactor Boilers | 61 |
| 3 Boiler Plant Subsystems, Appurtenances, and Auxiliaries | 67 |
| 3.1 Boiler Plant Subsystems | 69 |
| 3.2 Boiler Appurtenances | 72 |
| 3.3 Boiler Auxiliaries | 82 |
| 3.4 Balance of Plant (BOP) Equipment | 112 |
| 3.5 Boiler Plant Operational and Water Treatment Basics | 119 |
| 4 Waterside and Steamside Problems: The Basics | 131 |
| 4.1 Hot Water and Steam System Cycles | 132 |
| 4.2 The Scope of BW Treatment and Control of Steam/Waterside Chemistry | 134 |
| 4.3 Fundamental Steam–Waterside Problems and Water Treatment Objectives | 140 |
| 4.4 Deposition | 144 |
| 4.5 Corrosion | 149 |
| 4.6 Fouling | 153 |
| 4.7 Contamination | 154 |
| 4.8 Limiting the Potential for Waterside Problems | 156 |

| | | |
|---|---|-----|
| 5 | Waterside and Steamside Problems: Hot Water Heating and Low-Pressure Steam Boiler Specifics | 173 |
| | 5.1 Problems with Heating Coils | 175 |
| | 5.2 Problems Associated with the Use of Glycols | 177 |
| | 5.3 Problems of Corrosion in Hot Water and Low-Pressure Steam Heating Systems | 178 |
| | 5.4 Other Waterside Problems in Hot Water Heating and Low-Pressure Steam Systems | 180 |
| | 5.5 Waterside Problems in Medium-Temperature Hot Water and High-Temperature Hot Water Systems | 185 |
| 6 | Waterside and Steamside Problems: Pre-Boiler Section Specifics | 191 |
| | 6.1 Overview of Pre-Boiler Section Waterside Problems | 192 |
| | 6.2 Feedwater Contamination from Makeup Water | 193 |
| | 6.3 FW Contamination from Returning Condensate | 203 |
| | 6.4 Problems Associated with the Final Feedwater Blend | 206 |
| 7 | Waterside and Steamside Problems: Boiler Section Specifics | 217 |
| | 7.1 Boiler Scaling, Fouling, and Deposition | 217 |
| | 7.2 Passivation and Common Corrosion Problems | 237 |
| | 7.3 Stress and High Temperature-Related Corrosion | 254 |
| | 7.4 Other Forms of Corrosion | 262 |
| | 7.5 Corrosion in Nuclear Powered Steam Generators | 265 |
| 8 | Waterside and Steamside Problems: Post-Boiler Section Specifics | 273 |
| | 8.1 Steam Purity and Steam Quality | 275 |
| | 8.2 Corrosive Gases in Steam and Condensate Systems | 284 |
| | 8.3 Vaporous Silica and Other Steam Volatiles | 293 |
| | 8.4 Scale and Corrosion Debris Transport | 296 |
| | 8.5 Oil and Process Contamination | 298 |
| 9 | Pre-Boiler and Post-Boiler Treatment Processes | 303 |
| | 9.1 Overview of Common External Treatment Process Technologies | 306 |
| | 9.2 Basic Pretreatment Processes | 307 |
| | 9.3 Pre-Boiler Purification Technologies | 341 |
| | 9.4 Post-Boiler Condensate Conditioning | 376 |
| | 9.5 Novel Pretreatment Oxygen Removal Technologies | 382 |

| | | |
|-------|--|-----|
| 10 | Internal Treatment Programs | 385 |
| 10.1 | Outline of Internal Treatment Control and Programs | 386 |
| 10.2 | Anodic Inhibitor Chemistries | 394 |
| 10.3 | Tannin Programs | 403 |
| 10.4 | Coagulation and Precipitation Program Chemistries | 411 |
| 10.5 | Chelant Program Chemistries | 430 |
| 10.6 | All-Polymer/All-Organic Programs | 437 |
| 10.7 | Chelant-, Phosphate-, or Polymer-Based, Combination Programs | 461 |
| 10.8 | Coordinated Phosphate and Program Derivations | 464 |
| 10.9 | All-Volatile Treatment Program Chemistries | 474 |
| 10.10 | Mixed Treatment and Zero Solids Treatment | 476 |
| 10.11 | An Outline of Water Treatment for Nuclear Powered Steam Generators | 477 |
| 11 | Adjuncts and Conjunctional Treatments | 479 |
| 11.1 | Oxygen Scavenger Chemistries | 479 |
| 11.2 | Oxygenated Treatment (OT) | 506 |
| 11.3 | Ammonia and Amine Adjuncts | 510 |
| 11.4 | Alkalinity Boost Chemistries | 545 |
| 11.5 | Antifoam and Defoamer Chemistries | 548 |
| 11.6 | Multiblend Formulations | 555 |
| 12 | Control of Boiler Water Chemistry | 559 |
| 12.1 | Water Treatment Recommendation Perspectives | 560 |
| 12.2 | Tables and Supporting Notes | 566 |
| 13 | Operational Control of Waterside Surfaces | 599 |
| 13.1 | Sampling and Testing Steam and Condensate | 599 |
| 13.2 | Managing Standby and Idle Boilers | 606 |
| 13.3 | Boiler Inspections | 612 |
| 13.4 | Boiler Cleaning | 623 |
| 13.5 | Some Troubleshooting Notes | 657 |
| 14 | Control of Fireside Conditions and Surfaces | 669 |
| 14.1 | Basic Fireside Problems | 670 |
| 14.2 | Fuel Treatments/Additives | 678 |
| 14.3 | Fuel Treatment Formulations | 687 |
| 14.4 | Combustion Gas Analysis | 689 |

| | |
|------------------------|-----|
| Appendix I Useful Data | 695 |
| Appendix II Glossary | 711 |
| Bibliography | 763 |
| Index | 11 |

Table of Contents

| | |
|---|-----|
| About the Author | vii |
| Saturated steam temperatures at various boiler pressures | 2 |
| Boiler Energy and Power Units | 2 |
| Typical gross heating values of common fuels (based on approximately 80% fuel to steam efficiency) | 3 |
| Typical energy consumption and output ratings for a fire tube boiler | 4 |
| Steam tables suitable for pressure deaerators | 5 |
| Calculating Blowdown | 6 |
| Coefficients of thermal conductivity for some heat-exchanger metals and boiler deposits | 6 |
| Types of water or steam commonly employed in most HW heating and steam generating plants | 7 |
| Commonly occurring minerals in natural MU water sources | 8 |
| Specific waterside/steamside problems affecting MPH and HPHW boiler plants | 8 |
| Salt concentration indicators | 9 |

| | |
|--|----|
| Summary of waterside/steamside problems affecting LPHW and LP steam heating boiler plants | 10 |
| FW contamination from MU water | 11 |
| FW contamination from returned condensate | 12 |
| Problems associated with the final FW blend | 13 |
| Deposition of boiler section waterside surfaces by alkaline earth metal salts, other inorganic salts and organics | 14 |
| Silica and silicate crystalline scales and deposits affecting boiler section waterside surfaces | 15 |
| Iron oxide and other boiler section corrosion debris deposits | 16 |
| Boiler section corrosion problems involving oxygen, concentration cells and low pH | 17 |
| Stress and high temperature related corrosion | 18 |
| Steam purity, quality and other operational problems | 19 |
| Specification for grades of high-quality water suitable for higher pressure WT boilers | 20 |
| Practical considerations for a RW ion-exchange softener | 20 |
| Types of Internal Treatment Program | 21 |
| Carbonate Cycle Requirement Calculations | 24 |
| Phosphate-Cycle Requirement Calculations | 25 |
| A Guide to Tannin Residuals in BW | 25 |
| Carbonate-Cycle Program. BW Carbonate Reserve Requirements by Pressure and Sulfate Concentration | 26 |
| Carbonate-Cycle Coagulation and Precipitation Program. Recommended BW Control Limits for Non-Highly-Rated FT Boilers Employing Hard or Partially Softened FW | 26 |

| | |
|--|----|
| Phosphate-Cycle Coagulation and Precipitation Program. Recommended BW Control Limits for Non-Highly-Rated FT Boilers Employing Hard, Partially Softened, or Fully Softened FW | 27 |
| Phosphate-Cycle Coagulation and Precipitation Program. Recommended BW Control Limits for Non-Highly-Rated WT Boilers Employing Hard, Partially Softened, or Fully Softened FW | 27 |
| Chelant demand (ppm product) per 1ppm substrate | 28 |
| EDTA Chelant or All-Polymer/All-Organic Program. Recommended BW Control Limits for Fired WT Boilers Employing Demineralized or Similar Quality FW | 29 |
| Oxygen Solubility at Atmospheric Pressure | 30 |
| Properties of Oxygen Scavengers | 31 |
| Carbon Dioxide Evolution from FW Alkalinity | 32 |
| Amine Requirement to Reach a Stable Condensate pH | 32 |
| Amine Basicity Dissociation Constants | 32 |
| Neutralizing Amine Summary Notes | 33 |
| Some DR values for CO ₂ , NH ₃ and neutralizing amines at various pressures | 34 |
| Calculating Alkalinity Feed-Rate Requirements | 35 |
| ASME Consensus table 1: Suggested water chemistry limits. Industrial watertube, high duty, primary fuel fired, drum type Makeup water percentage: Up to 100% of feedwater. Conditions: Includes superheater, turbine drives or process restriction on steam purity | 38 |
| ASME Consensus table 2: Suggested chemistry limits. Industrial watertube, high duty, primary fuel fired, drum type | 40 |

| | |
|--|----|
| ASME Consensus table 3: Suggested chemistry limits. Industrial firetube, high duty, primary fuel fired | 41 |
| ASME Consensus table 4: Suggested water chemistry limits. Industrial coil type, watertube, high duty, primary fuel fired rapid steam generators | 42 |
| ASME Consensus table 5: Suggested water chemistry limits. Marine propulsion, watertube, oil fired drum type | 44 |
| ASME Consensus table 6: Suggested water chemistry limits. Electrode, high voltage, forced circulation jet type | 45 |
| Reduction in heat transfer efficiency with increase in deposit thickness, where A = iron oxides and silica, B = iron oxides, C = calcium carbonate | 46 |
| Notes | 47 |