

CONTENTS

Opening address	1
Prefatory note	2
The history and present day development of the autoclaved calcium silicate building products	
Industries	3
The requirements for lime used in calcium silicate brick manufacture	7
Broadening the particle size range of natural sands for calcium silicate brick manufacture	11
The effect of grading of the aggregate upon the strength of calcium silicate (sand-lime and flint-lime) bricks or blocks	18
Kaolin sandstone as a raw material for autoclaved calcium silicate building materials	34
A study of the mixing process in the calcium silicate brick industry	38
Some thermal aspects of autoclaving calcium silicate building products	54
The importance of mechanical engineering developments in the manufacture of calcium silicate building materials	59
Recent technical developments in the calcium silicate brick industry: the plant designers' viewpoint	64
Factors in calcium silicate brick manufacture to be considered when designing plant	72
Methods for improving the physical properties of calcium silicate bricks	74
The position of mechanisation and automation in the calcium silicate brick industry and possibilities of future development	80
The mechanism of the quartz-lime solution reaction at temperatures up to 500°	86
Kinetic study on hydrothermal reaction between lime and silica	92
Hydration rate of dicalcium silicate in mixes with quartz under hydro-thermal conditions	101
Influence of the composition of the mixture and the temperature of hydro-thermal treatment on the kinetics of interaction of lime and quartz	110
Investigations of stabilities of calcium silicate hydrates at elevated temperatures and pressures	114
Chemical alteration of poorly crystallised calcium silicate hydrates by hydrothermal treatment	122
The degree of condensation of the silicate anions in the dicalcium silicate hydrates A,B and C	125
High-strength calcium silicate hydrate. I. Strength tests	130
High-strength calcium silicate hydrate. II. X-ray, D.T.A., chemical and electron microscope results	134
Autoclaved blocks made from γ -Ca ₂ SiO ₄	142
The hardening of lime and silica at 175°. The relation between the structure and strength of hardened materials	148
Reducing the shrinkage of calcium silicate bricks	152
Resistance to chemical action by calcium silicate bricks	155
The within-cake variation of autoclaved aerated concrete	163

Porosity, compressive strength and volume changes of autoclaved aerated concrete	171
Moisture content and moisture migration in aerated concrete	174
The effect of environment on the strength of autoclaved aerated concrete	182
The porosity and the gas permeability of aerated concrete	188
A review of autoclaved calcium silicates	195
Examination of limes and lime-sand bricks by X-ray fluorescence	206
The load-bearing characteristics of reinforced masonry constructed from sand-lime bricks	209
Fixings to autoclaved aerated concrete building elements	216
The properties and behaviour of calcium silicate bricks in buildings and the design of structures using them in the United Kingdom	220
New applications of Siporex large size aerated concrete units	230
Some technical data concerning a new type of tongue-and-groove joints for roof slabs of cellular concrete	234
Multi-storey flat buildings in calcium silicate bricks and blocks, and the testing of wall panels and of bricks, blocks and mortar for calculated masonry	239
Finishes on aerated concrete	252
Calcium silicate thermal insulation products	259
Some problems in the manufacture and marketing of coloured calcium silicate bricks	267
AUTHOR INDEX	271
SUBJECT INDEX	273
FORMULA INDEX	277