## CONTENTS

		Page
1.	Preparation of the Fabric 1.1 Introduction 1.2 Identification of fibres 1.3 Preliminary scouring of the fabric prior to dyeing or printing	1 1 1 2
2.	Printing Procedure 2.1 Introduction 2.2 Dissolving the dyestuff 2.3 Preparation of the printing paste 2.4 Thickening agents 2.5 Printing 2.6 Drying after printing 2.7 Steaming 2.8 Final treatment	4 4 4 4 5 5 5
3.	The Different Fibres and the Dyestuffs Used in printing Them 3.1 Introduction 3.2 Fibres 3.3 Dyestuffs-Properties and notes relating to their application 3.4 Relative dyestuff strengths	12 12 12 13 14
4.	Equipment and Methods of Use 4.1 Introductory survey of methods 4.2 Block Printing 4.3 Screen Printing	15 15 17 20
5.	Thickening Agents and their Preparation for Use 5.1 Introduction 5.2 The preparation of selected thickening agents 5.3 Suitability of thickenings	32 32 33 39
6.	Fastness Properties 6.1 Introduction 6.2 Light Fastness 6.3 Washing Fastness 6.4 Depth of shade	41 41 42 42 43
7.	The Printing of Cotton and Viscose Rayon 7.1 Introduction 7.2 Procion dyestuffs 7.3 Direct dyestuffs 7.4 Acid dyestuffs printed on viscose rayon (the urea process) 7.5 Basic dyestuffs 7.6 Mordant dyestuffs 7.7 Azoic dyestuffs 7.8 Vat dyestuffs 7.9 Soledon dyestuffs 7.10 Soloxan Black SN 150 7.11 Alcian dyestuffs 7.12 Pigment printing by the Bedafin 2101 (or Bedafin 2001) process	44 44 44 55 57 59 60 65 69 79 83 85

8.	The Printing of Wool and Natural Silk	91
	8.1 Introduction	91
	8.2 Basic dyestuffs	91
	8.3 Acid dyestuffs	92
	8.4 Direct dyestuffs	94
	8.5 Procion dyestuffs	96
9.	The Printing of Cellulose Acetate	100
	9.1 Introduction	100
	9.2 Printing of cellulose acetate	100
	9.3 Printing of cellulose triacetate	103
10.	The Printing of Nylon	107
	10.1 Introduction	107
	10.2 Procinyl dyestuffs	107
	10.3 Nylomine acid P dyestuffs	108
	10.4 Procion dyestuffs	110
	10.5 Disperse dyestuffs	112
	10.6 Notes	113