

Contents

| | | |
|---------|---|----|
| 1 | Electrospinning of Polymeric Nanofibres | 1 |
| 1.1 | Introduction | 1 |
| 1.2 | Processing Condition | 2 |
| 1.2.1 | Applied Voltage..... | 2 |
| 1.2.2 | Feed Rate | 2 |
| 1.3 | Theory and Modeling | 4 |
| 1.4 | Concluding Remarks | 8 |
| 2 | Polymeric Nanofibre Fabrication via Electrospinning Process.... | 11 |
| 2.1 | Introduction | 11 |
| 2.2 | Experimental | 15 |
| 2.2.1 | Solution Preparation and Electrospinning | 15 |
| 2.2.2 | Choice of Parameters and Range..... | 16 |
| 2.2.3 | Experimental Design | 19 |
| 2.2.4 | Response Surface Methodology..... | 24 |
| 2.3 | Results and Discussion | 26 |
| 2.3.1 | Response Surfaces for Mean Fibre Diameter | 31 |
| 2.3.1.1 | Solution Concentration..... | 31 |
| 2.3.1.2 | Spinning Distance..... | 32 |
| 2.3.1.3 | Applied Voltage | 33 |
| 2.3.1.4 | Volume Flow Rate | 34 |
| 2.3.2 | Response Surfaces for Standard Deviation of Fibre Diameter | 34 |

| | | |
|---------|--|----|
| 2.3.2.1 | Solution Concentration..... | 34 |
| 2.3.2.2 | Spinning Distance | 36 |
| 2.3.2.3 | Applied Voltage | 36 |
| 2.3.2.4 | Volume Flow Rate | 38 |
| 2.4 | Conclusion | 38 |
| 2.4.1 | Mean Fibre Diameter | 39 |
| 2.4.2 | Standard Deviation of Fibre Diameter | 39 |
| 3 | Structure Formation of Polymeric Nanofibres in Electrospinning..... | 45 |
| 3.1 | Introduction | 45 |
| 3.2 | Methodology | 47 |
| 3.2.1 | Simulation of Electrospun Webs | 47 |
| 3.2.2 | Fibre Diameter Measurement | 48 |
| 3.2.2.1 | Manual Method | 48 |
| 3.2.2.2 | Distance Transform | 49 |
| 3.2.2.3 | Direct Tracking..... | 51 |
| 3.2.3 | Real Webs Treatment | 52 |
| 3.3 | Experimental | 54 |
| 3.4 | Results and Discussion | 54 |
| 3.5 | Conclusion | 63 |
| 4 | Optimisation of the Electrospinning Process..... | 67 |
| 4.1 | Introduction | 67 |
| 4.2 | Methodology | 68 |
| 4.2.1 | Measurement of Fibre Diameter | 68 |
| 4.2.1.1 | Manual Method | 69 |
| 4.2.1.2 | Distance Transform Method..... | 70 |
| 4.2.1.3 | New Distance Transform Method | 74 |

| | | |
|---------|--|-----|
| 4.2.2 | Validation of the Methods..... | 79 |
| 4.2.3 | Thresholding | 80 |
| 4.3 | Experimental | 82 |
| 4.4 | Results and Discussion | 84 |
| 4.5 | Conclusion | 91 |
| 5 | Practical Hints on the Processing Parameters and Geometric Properties of Electrospun Nanofibres | 97 |
| 5.1 | Introduction | 97 |
| 5.2 | Methodology | 98 |
| 5.2.1 | Sieving Methods..... | 101 |
| 5.2.2 | Mercury Porosimetry | 101 |
| 5.2.3 | Flow Porosimetry (Bubble Point Method) | 102 |
| 5.2.4 | Image Analysis | 103 |
| 5.2.4.1 | Real Webs..... | 104 |
| 5.2.4.2 | Simulated Webs | 105 |
| 5.3 | Experimental | 106 |
| 5.4 | Results and Discussion | 108 |
| 5.5 | Conclusion | 118 |
| 6 | Practical Hints on the Production of Electrospun Nanofibres from Regenerated Silk Fibroin..... | 121 |
| 6.1 | Introduction | 121 |
| 6.2 | Effect of Systematic Parameters on Electrospun Nanofibres..... | 122 |
| 6.2.1 | Solution Properties | 122 |
| 6.2.2 | Viscosity | 122 |
| 6.2.3 | Solution Concentration | 122 |
| 6.2.4 | Molecular Weight..... | 123 |

| | | |
|----------|--|-----|
| 6.2.5 | Surface Tension | 123 |
| 6.2.6 | Solution Conductivity | 123 |
| 6.2.7 | Applied Voltage..... | 124 |
| 6.2.8 | Feed Rate | 124 |
| 6.3 | Experimental | 124 |
| 6.3.1 | Electrospinning and Preparation of Nanofibrous Media | 124 |
| 6.3.2 | Image Analysis using Image Processing Algorithms | 125 |
| 6.4 | Results and Discussion | 126 |
| 6.4.1 | Diameter Distribution of Nanofibres..... | 126 |
| 6.4.2 | Distribution of Nanofibre Orientation | 130 |
| 6.4.3 | Porosity | 130 |
| 6.5 | Conclusions | 130 |
| 7 | Characterisation of Polymeric Electrospun Nanofibres | 133 |
| 7.1 | Introduction | 133 |
| 7.1.1 | Electrospinning Setup..... | 135 |
| 7.2 | Effect of Systematic Parameters on Electrospun Nanofibres | 139 |
| 7.2.1 | Solution Properties | 139 |
| 7.2.1.1 | Viscosity | 139 |
| 7.2.1.2. | Solution Concentration..... | 140 |
| 7.2.1.3 | Molecular Weight | 141 |
| 7.2.1.4 | Surface Tension | 141 |
| 7.2.1.5 | Solution Conductivity..... | 142 |
| 7.2.2 | Processing Condition..... | 144 |
| 7.2.2.1 | Applied Voltage | 144 |
| 7.2.2.2 | Feed Rate..... | 144 |

| | | |
|-------|--|-----|
| 7.3 | Experimental | 145 |
| 7.4 | Result and Discussion..... | 147 |
| 7.5 | Conclusion | 150 |
| 8 | Formation of Polymeric Electrospun Nanofibres | 153 |
| 8.1 | Overview | 153 |
| 8.2 | Aim of the Project..... | 153 |
| 8.3 | Experimental | 154 |
| 8.4 | Results and Discussion | 155 |
| 8.5 | Conclusion | 163 |
| 9 | Experimental Study on Electrospinning of Polymeric Nanofibres..... | 165 |
| 9.1 | Introduction | 165 |
| 9.2 | Experimental | 166 |
| 9.2.1 | Materials..... | 166 |
| 9.2.2 | Sample Preparation | 167 |
| 9.2.3 | Electrospinning | 167 |
| 9.2.4 | Characterisation..... | 168 |
| 9.3 | Results and Discussion | 169 |
| 9.3.1 | Effect of Polyaniline Content..... | 169 |
| 9.3.2 | Effect of Electrospinning Temperature..... | 172 |
| 9.3.3 | Effect of Applied Voltage..... | 177 |
| 9.4 | Conclusions | 178 |
| | Abbreviations..... | 181 |
| | Index | 183 |