

INDEX

A

- AceticaTM* process, 21–22
ALD. See *Atomic layer deposition*
Aluminophosphates (AlPO₄), chromium oxide
 activation temperature
 average activity level, 444–445
 LCB level, 448
 MW distributions, 445, 447
 three series results, polymerization test, 445–446
 copolymerization
 1-hexene comonomer response, 428–429
 HLMI response, 1-hexene L⁻¹ addition, 427–428
 MW distribution change, 430–431
 possible pathways, 1-hexene interaction, 428, 430
 coprecipitated
 broader MW distribution, 422
 catalyst and polymer properties, 422–423
 P/Al ratio, 421–422
 LCB
 film blowing, 442
 intramolecular incorporation, 443–444
 polymerization series, 441–442
 production, Cr/AlPO₄ vs. Cr/alumina, 441
 relaxation time, polymers, 442–443
 solvent-fractions analysis, 443
 metal phosphates
 MW distributions, 448–449
 titanium and zirconium, 448
 phosphate-treated alumina, 419–420
 polymerization
 average activity, 435, 439
 Cr/silica–titania activation, 870 °C, 434
 gradual decay, 435
 initiation steps, 436
 rate constants, ethylene concentration, 437–438

- reaction kinetics, 433–434, 437, 440
 stopped flow experiment, 435–436
 sensitivity, H₂
 branching profiles, 432
 hydrogenolysis *vs.* β-hydride elimination, 431
 methyl-to-vinyl chain-end ratios, 432–433
 silanes
 (CH₃)₃SiCl and (CH₃)₂Si—N—Si(CH₃)₃ reaction, 422, 424
 ²⁹Si NMR spectrum, 424
 “umbrella” crowding effect, 425
vs. SiO₂
 Cr(VI) saturation coverage behavior, 421
 structural similarities, 419–420
 total OH group density, 420
 triethylboron cocatalyst
 BEt₃, 426
 chain transfer agents, Cr/AlPO₄ *vs.* Cr/silica, 425–426
 MW distributions, 426–427
 Ashing process, 239–240
Atomic layer deposition (ALD)
 chemisorption, 104
 procedure, 105

B

- Bent ramp**
 air and gas velocity, 576
 Cr(VI) conversion, 574–575
 heat-up ramp profile, 575
 standard linear and concave ramp, 575–576
Bimodal polymer
 acidic support, P—OH group *vs.* Si—OH group, 467
 Al-associated peak, 466, 468
 coprecipitated AlPO₄, 467
 dicumenechromium(0) reaction, 471
 heating with N₂, 470–471
 mono-attached *vs.* di-attached species, 468

- Bimodal polymer (cont.)**
- MW distribution, Cr(DMPD)₂, 465–466
 - P-OH and Al-OH, 465
 - poisoning experiments, 471–473
 - polymerization activity, 473
 - reactivity determination, sites, 470
 - relative contribution, P- and Al-associated peaks, 469
 - uniform distribution, H₂, 470
- BP cativa™ process.** *See also Iridium*
- complex catalyzed carbonylation, methanol
 - elements, methanol carbonylation, 25
 - retrofitting, 24–25
- Branch distribution, α -olefins**
- average branch content, 223
 - branching, low-MW side, 220
 - deconvolution, seven Schulz–Flory components, 220–221
 - electron deficiency, 219
 - ESCR dependence, 222
 - ethylene–hexene copolymers production, 222–223
 - GPC with butyl branch profiles, 219
 - incorporation efficiency, 218–219
 - lower activation temperature, 222
 - tie molecules role, polymer failure model, 219–220
- C**
- Carbon nanotubes (CNTs)**
- EPD, 97–98
 - multiwall arrays, 104
- Carreau–Yasuda (CY)- α values**
- as indicator, LCB level, 314–319, 347
 - LCB detection, 274
 - pore volume, 306
 - as relaxation time distribution, 306
 - residence time, 321
 - selective poisoning, titania, 347
- Catalyst carrier structure**
- activity and kinetics
 - initial steps, active site formation, 233
 - “plateau rate,” 234
 - chain growth
 - basic variables, 249–250
 - MW relationship, 249
 - compacting pores
 - MW and melt indices, 253
 - polymerization test results, 251–252
 - volume distributions, 251
- copolymerization, pores influence,** 269–270
- Cr/silica manufacture**
- pore water replacement, 233
 - process, 230–231
 - silica hydrogel before drying step, 231–232
 - spray drying/flash drying, 232–233
 - suspended primary silica particles, 231
- fragmentation**
- ashing process, 239–240
 - large catalyst, plasma ashing, 239
 - polymer particle production, 238–239
 - pore volumes, recovered catalyst, 239–240
 - role, pores, 241
 - typical dimensions, 241–242
- mass transport**
- complex behavior, 246
 - MW distribution, 248–249
 - rate-decay kinetics, 247–248
 - reaction temperature, 246–247
 - soluble metallocene catalysts, 248
 - types, 245–246
- mesoporosity**
- average number of contacts and pore volume, relationship, 236–237
 - drying step, hydrogel samples, 234–235
 - measured penetration, 237–238
 - nitrogen adsorption, 235
 - pore volume distribution, 235–236
- MW distribution, pores influence,** 259–260
- network reinforcement**
- activity per unit area, 259
 - alkaline aging, 254–255
 - common silica grades, 255
 - environments, influence chain growth, 257
 - general pattern, polymer MW dependence, 257–258
- MW, sintered catalysts,** 257–258
- Oswald ripening,** 254
- polymer MW and pore diameter relationship,** 256–257
- pore diameter calculation,** 253
- pore volume distributions, Davison silicas,** 255
- silica gel coalescence,** 254
- standard silica,** 257
- particle replication growth and expansion,** 243

- PE subunits, 243
spherical Cr/alumina catalyst, 244
Ziegler catalyst, 244–245
- pore rupture and particle disintegration dependence, polymerization activity, 229–230
earliest stages, polymerization, 228–229
fragility, 228, 230
high pore volume (PV), 228
- porosity and LCB, 270
- techniques, increase pore volume
aqueous methods, drying, 267–269
hydrogel optimization, 261–263
MI potential, 260
organic methods, drying, 263–267
- Catalytic methanol carbonylation
acetic acid, 2–3
approaches, alternative
copper-containing mordenite catalysts, 37
dimethyl ether, 36
isotopic labeling, 38
Pd(II) catalyst, 38
solid-acid catalysts, 35–36
- cobalt iodide catalyst, 3
- computational investigations
migratory CO insertion, 34–35
phosphines and ligands, 35
transition state, 34
- iridium-complex
commercialization (*See* BP cativaTM process)
reaction mechanism, 27–34
- principal features, 4
- process
carbon monoxide insertion, 4
esterification, 5
low water concentration, 6
rhodium-complex-catalyzed, 5–6
- rhodium-complex
iodide salts, 9–10
phosphine ligands and derivatives, 10–20
reaction mechanism, 6–9
supported, 20–23
- Wacker process, 3
- Catalytic processing
computational methods, 34–35
description, 51
homogeneous, 20, 39
intensification, 54
ruthenium promoted, 32–33
- Catalytic wall microreactors
heat transfer performance, 72
mass transfer performance
external, 69–72
internal, 68–69
pressure drop, 64–65
residence time distribution
axial mixing, 65
continuous flow reactor, 64–65
diffusion coefficients, 66–67
dispersion, 66
flow maldistribution, 67
plug flow, 67–68
- small channel dimensions
fixed-bed reactor, 63
particle and cylindrical channel diameter, 64
- Chain architecture
branch distribution
cross-insertion, sites, 293–294
intramolecular incorporation, 294
LCB distribution, 293
low-MW preference, site population, 292–293
single-site MW distribution, 292–293
unusual characteristics, 293
- cocatalysts
BET, MW broadening, 282
reaction variables, 280–282
- Cr–Cr proximity
Arnett plot, 280–281
LCB, chromium loading, 280–281
molten polymer elasticity, 279–280
shear response, 278–279
- dehydroxylation
“Arnett plot,” 275
blow-molding process, 276–278
contradictory trends, 274–275
Cr/silica activation temperature, influence, 276–277
melt strength, 276–277
polymer grades, diverse blow molding applications, 278–279
polymer properties, increasing activation temperature, 274, 276
- detection
Janzen and Colby (JC) relationship, 272–273
melt rheology, 272
SEC–MALS, 273–274
- ethylene concentration
shear stress response, 286–287

- Chain architecture (cont.)**
- solution process, 287
 - increased vinyl concentration
 - alpha–omega dienes pathway, 299–300
 - extreme rheological changes, 298–299
 - LCB formation, 299
 - macromer insertion
 - dichromate species with Cr ions, 290
 - electron deficiency, 290
 - “frozen out,” polymer chains, 288
 - incorporation mechanism, 287–288
 - “*intramolecular*” incorporation, 289
 - LCB generation, neighboring sites, 290–291
 - LCB levels, 288–289
 - melt viscosity curve, 291
 - trigger mechanism, 289–290
 - melt elasticity
 - LCB levels, 271–272
 - polyethylene exhibit, 270–271
 - poisons
 - CO, 283
 - HLMI/MI ratio, 283–284
 - impact resistance, film, 284–285
 - melt–solution viscosity (MSV) ratio, 283
 - molten polyethylene elasticity reduction, 284
 - reaction temperature
 - Arnett plot, 285–286
 - partial solvation, 286
 - solution polymerization
 - chromium coverage effect, 297–298
 - LCB levels, varying temperatures, 295
 - reaction temperature, 295
 - research goal, Cr/silica adaption, 294–295
 - shear stress responses, 296–297
- Chemical vapor deposition (CVD)**
- ALD, 104–105
 - alumina coating, 102
 - carbon nanofibers, 103–104
 - CNTs, 104
 - Mo₂C and ZrO₂ thin films, 103
- Chromium catalyst, Phillips supported**
- activation treatments
 - anhydrous impregnation, 351–358
 - commercial practice, 364–371
 - dehydroxylation, enhanced, 358–364
 - LCB, two-step activation, 372–374
 - prereactor reduction, Cr(II), 349–351
 - AlPO₄
 - activation temperature, 444–448
 - copolymerization, 427–431
 - coprecipitated, 421–422
 - LCB, 441–444
 - metal phosphates, 448–449
 - phosphate-treated alumina, 419–420
 - polymerization, 433–441
 - sensitivity, H₂, 431–433
 - silanes, 422, 424–425
 - vs. SiO₂, 419–421
 - triethylboron cocatalyst, 425–427
 - carrier structure
 - activity and kinetics, 233–234
 - chain growth, 249–250
 - compacting pores, 251–253
 - copolymerization, pores influence, 269–270
 - Cr/silica manufacture, 230–233
 - fragmentation, 238–242
 - mass transport, 245–249
 - mesoporosity, 234–238
 - MW distribution, pores influence, 259–260
 - network reinforcement, 253–259
 - particle replication, 243–245
 - pore rupture and particle disintegration, 228–230
 - porosity and long-chain branching, 270
 - techniques, increase pore volume, 260–269
- chain architecture**
- branch distribution, 292–294
 - cocatalysts, 280–282
 - Cr–Cr proximity, 278–280
 - dehydroxylation, 274–278
 - detection, 272–274
 - ethylene concentration, 286–287
 - increased vinyl concentration, 298–300
 - macromer insertion, 287–291
 - melt elasticity, 270–272
 - poisons, 283–285
 - reaction temperature, 285–286
 - solution polymerization, 294–298
- cocatalysts**
- commercial process, 485–486
 - with cyclopentadienyl groups, 503–504
 - definition, 483–484
 - enhanced activity, 486–490
 - mechanism, 484–485
 - polymer modification, 494–503

- sensitivity, H₂, 504–508
solid, 492–494
stoichiometry, 490–492
commercial activation, Cr/silica
 bent ramp, 574–576
 Cr(VI) stability *vs.* oxygen, 580–582
 mathematical model, 573–574
 space velocity, 569–572
 temperature sensitivity, 572–573
 time dependence, 576–580
 water vapor influence, 565–569
commercial polyethylene
 comparison, 131–133
 markets, 129–131
 origin, 133–137
Cr/alumina
 activity, 400–401
 characteristics, 398–399
 copolymerization, 402–403
 fluoride-treated, 406–409
 high molecular weight (MW), 401–402
 LCB, 403–405
 metal oxides addition, 415–418
 sensitivity, H₂, 405–406
 sulfate-treated, 409–415
 two-step activation, 418–419
Cr/silica reduction
 Cr(IV), 164–165
 Cr(0) and Cr(I), 162, 164
 Cr(II) oxide, 156–157
 Cr(III) oxide, 155–156
 Cr(V) oxide, 155
 Cr(II)/silica catalyst, 157–163
 valence, active chromium species,
 154–155
Cr/silica-titania
 acidity, 323–324
 vs. Cr/titania, 347–348
 preparations, 324–325
 titania, 326–347
 uniqueness, 349
dispersion and stabilization, Cr(VI)
 bis(triphenylsilyl) chromate, 153–154
 calcination, 138–139
 chromate *vs.* dichromate, 139
 CrO₂Cl₂ adsorption and desorption,
 143–146
 mobility, 149–153
 silanol group replacement
 measurements, 140–142
 spectroscopy, 140
 surface coverage, 146–149
in situ branching
 advantages, 528–529
 cocatalyst, 518–520
 H₂, as cocatalyst, 533–535
 hydrosilanes, 529–533
 α-olefin, 509–511, 522–528
 reaction variables, 520–522
 reduction step, 512–514
 silica support, 514–518
melt elasticity and catalyst structure
 commercial applications, 311–313
 dehydroxylation *vs.* coalescence,
 308–311
 flame treatment, 316–317
 fluxing, sodium, 315–316
 hydrothermal treatment, 313–315
 materials, 320
 pore volume, 304–308
 residence time, 320–323
 silica types, 316–320
 surface area, 300–304
α-olefins copolymerization
 bimodal polymers, 223–224
 blocking, 224–225
 branch distribution, 218–223
 branch length, 225–226
 catalyst particle size, 226–228
 comonomers reactivity, 210–211
 insertion mechanism, 208–209
 molecular weight suppression, 211–218
 polymer density, 207–208
organochromium compounds
 bimodal polymer, 465–473
 bonding, 450–451
 branching, 478–479
 calcination temperature, 459–465
 chromium loading, 456–458
 chromium oxide, combined, 480–483
 fluoride effect, MW distribution,
 473–476
 initiation mechanism, 458–459
 open- *vs.* closed-ring chromocene,
 476–478
 paired Cr species, 478
 support acidity, 453–456
 types, 451–453
polyethylene manufacture
 activity *vs.* reaction temperature,
 546–547
 commercial PE process, 535–538
 density control and MW, 547–553
 H₂ influence, 558–563

- Chromium catalyst, Phillips supported (*cont.*)
 limitations, Cr/silica catalyst system, 538–540
 melting and swelling, 540–546
 MW distribution control, 553–558
 product contamination, 563–565
 polymer formation
 chain growth rate, 165–166
 chain transfer, 173–175
 comparisons, 176–177
 initiation mechanisms, 169–173
 reduction, 166–169
 site *vs.* chain initiation, 169
 surface acidity, 175–176
 promoters, Cr/silica
 alkaline earth metals, 391–393
 Cr/silica–alumina, 378–379
 Cr/silica–zirconia, 374–377
 Cr/Sn–silica, 377–378
 halides, 379–388
 lithium and sodium, 388–391
 modifiers, 398
 silica phosphate, 393–395
 silica sulfate, 395–397
 site diversity and carrier influence
 active sites, 193–197
 bonding, individual Cr atoms, 177–178
 MW distribution, 178–179
 MW-time dependence, 179–182
 radioactive labeling, 207
 site discrimination, CO titration, 182–184
 surface dehydroxylation and annealing, 184–189
 thermal treatments, 189–193
 titration by poisons, 197–207
- Chromocene
 characteristics, chromium catalysts, 452
 α -olefin copolymerization, 452–453
 open- *vs.* closed-ring
 aluminophosphate support, 477–478
 comparison, MW distributions, 476–477
 cyclopentadiene ring loss, 477
 sensitivity, H₂, 453
- Chromyl chloride (CrO₂Cl₂)
 adsorption, 143–145
 desorption, 145–146
- CNTs. *See* Carbon nanotubes
- Cocatalysts
 BEt₃, MW broadening, 282
 characteristics, 485
 commercial process
 advantages, 485
 contacting, 486
 cyclopentadienyl groups
 catalyst modification procedure, 504
 chromocene surface species, 503
 MW distributions, 503–504
 definition
 behavior, 483
 as reducing agents, 483–484
 enhanced activity
 activity improvement, Cr/
 aluminophosphate, 488–489
 average turnover numbers, 488
 CO reduction, 489–490
 induction time, 486
 maximum rate, 488
 polymerization kinetics, Cr/
 silica–titania, 486–487
 polymer modification
 AlEt₃ and BEt₃ influence, 495–496
 BEt₃ influence, 500–501
 boron alkyls, 494–495
 broad MW distributions, 498
 ESCR test, 498
 four different conditions, 498–499
 high-MW tail, MW distribution, 494
 HMWI/MI ratio, 497–498
 parison swell, 500
 performance characteristics, 501–502
 physical properties, 500
 5 ppm BEt₃ influence, 496–497
 shear thinning, 497–498
 reaction variables, 280–282
 sensitivity, H₂
 chromium species, as MW regulator, 504
 extreme shift, MW distributions, 508
 MI, polymer, 505–506
 MW distributions, 505, 507–508
 polymers characteristics, 507–508
 six ways, active-site behavior, 484–485
 solid
 Cr/silica activities, 493–494
 scavenging function, separation, 492–493
 stoichiometry
 AlEt₃ influence, 490–491
 boron alkyls, as reducing agents, 491
 Cr–O–Si bonding link, 490
 induction time, 492
 ZnEt₂ influence, 491–492
 Compacting pores, carrier structure

- MW and melt indices, 253
polymerization test results, 251–252
volume distributions, 251
Continuously operated stirred tank reactor (CSTR), 65
Continuous phase microstructured reactors
 film contactors
 components, 73–74
 falling-film devices, 73
 residence time, 74
 mesh contactor
 gas and liquid flow, 74–75
 volumetric mass transfer, 75
Convex bent ramp. *See* Bent ramp
Cr/alumina
 characteristics
 Cr(VI) concentration, 399
 “polymerization grade,” 398–399
copolymerization
 branch profiles, 403
 1-hexene incorporation, 402–403
fluoride-treated
 activities, 407
 $\gamma\text{-Al}_2\text{O}_3$ crystalline, 407–408
 aluminum oxy-fluoride (AlO_xF_y)
 supports, 406
 H_2 addition, 408
 loss, surface area, 408–409
 optimum fluoride levels, 407–408
high molecular weight
 β -hydride elimination, 401
 MW distributions, polymers, 401–402
LCB
 Arnett plot, 403–404
 dichromate species, 404
 polymer production, 405
 primary particles density, 404–405
metal oxides addition
 flexibility, 415–416
 impregnation levels, boric acid, 416
 MW distribution, 416–417
 surface silica coating, 417
 zinc, 417–418
polymerization activity
 characteristics, 400
 Cr(VI)/alumina vs. Cr(VI)/silica,
 400–401
sensitivity, H_2
 as chain transfer agent, 405
 change, MW distribution, 405–406
sulfate-treated
 ammonium and sulfate ions retention,
 411
 Cr(VI) conversion, 410
 CY relaxation time, 415
 electron-withdrawing anions, 409
 evaporation amount, 411–412
 hydrogenolysis by H_2 , 413–414
 MW distributions, 412–413
 M_w/M_n and M_z/M_w moment ratio,
 414
 polymers characteristics, 414–415
 properties, $(\text{NH}_4)_2\text{SO}_4$ treatment,
 411–412
 two-step activation, 418–419
Cr-Cr proximity
 Arnett plot, 280–281
 LCB, chromium loading, 280–281
 molten polymer elasticity, 279–280
 shear response, 278–279
Cr(VI) dispersion and stabilization
 bis(triphenylsilyl) chromate
 adsorption, 154
 characteristics, 153–154
 calcination
 Cr(III) oxidation, 138–139
 hexavalent chromium compounds, 138
 chromate vs. dichromate, 139
 chromyl chloride (CrO_2Cl_2)
 adsorption, 143–145
 desorption, 145–146
 mobility
 chromium transfer, silica particle,
 149–150
 conversion, Cr/silica and silica,
 151–153
 evaporation and redeposition, 150
 hydrolysis, Si-O-Cr bonds, 151
 redox cycling, 151
 silanol groups, involvement, 153
saturation coverage
 chromium loading, function, 147–148
 dehydration/annealing, 148–149
 thermal stability, 146
 water vapor, gas stream, 148
silanol group replacement measurements
 CO-reduction technique, 140–141
 $\Delta\text{OH}/\text{Cr}$ replacement ratio, 141–142
 spectroscopy, 140
Cr(II)/silica catalyst
 chemiluminescence emission spectrum,
 159

Cr(II)/silica catalyst (cont.)
 chemisorption behavior, 159–160
 cooling, CO and vacuum yields, 157
 CO treatment, 158
 ethylene polymerization activities, 160
 oxygen adsorption, 157–158
 site types, 161
 species characteristics, 162–163
 surface ion types, 162

Cr/silica reduction
 commercial activation
 bent ramp, 574–576
 Cr(VI) stability *vs.* oxygen, 580–582
 mathematical model, 573–574
 space velocity, 569–572
 temperature sensitivity, 572–573
 time dependence, 576–580
 water vapor influence, 565–569

Cr(IV), 164–165

Cr(0) and Cr(I), 162, 164

Cr(II) oxide, 156–157

Cr(III) oxide, 155–156

Cr(V) oxide, 155

Cr(II)/silica, 157–163
 manufacture
 pore water replacement, 233
 process, 230–231
 silica hydrogel before drying step, 231–232
 spray drying/*flash* drying, 232–233
 suspended primary silica particles, 231

valence, active chromium species, 154–155

Cr/silica-titania catalysts
 acidity
 MW and MW distribution, 323
 Ti-associated sites, 324
vs. Cr/titania
 MW distributions, 348
 as promoter, 347
 preparations
 cogelation, 325
 superior-titanated/cogelled, 325
 “titanated” catalyst, 324–325

titania
 coating, 327–330
 incorporation efficiency, 341–343
 influence, copolymerization, 333–339
 on melt elasticity, 344
 melt index (MI), 327
 MW distribution, 330–331

polymerization activity, 326–327
 on porosity, 339–341
 selective poisoning, 345–347
 thermal stability, 331–333
 uniqueness, 349

CVD. *See* Chemical vapor deposition

D

Dehydroxylation, chain architecture
 “Arnett plot,” 275

blow-molding process, 276–278

contradictory trends, 274–275

Cr/silica activation temperature, influence, 276–277

melt strength, 276–277

polymer grades, diverse blow molding applications, 278–279

polymer properties, increasing activation temperature, 274, 276

Dispersed phase microstructured reactors
 microstructured packed beds
 cyclohexene hydrogenation, 80
 silicon–glass microreactor, 81

segmented flow reactors
 flow regimes, 76
 hydrogenations, 78
 liquid–liquid mass transfer, 79–80
 mass transfer steps, gaseous reactant, 77
 microbubble column, 79
 Taylor flow, 76–77
 three-phase systems, 79

Drying techniques
 aqueous method
 anionic surfactants, 268
 pH change, hydrogel, 268–269

organic method
 azeotropic distillation process, 264–266

fractionation, 267

interfacial tension, water *vs.* heptane, 265

pore volume, silica hydrogel samples, 263–264

solvent-exchange process,
 Cr/silica-titania hydrogel, 264

thermal extraction, 267

various azeotropic compositions, 267–268

volume changes, in various stages, 265–266

E

Electrochemical deposition, 98–99

Electroless plating

copper films on silicon, 98–99

description, 98

palladium on porous alumina, 99

Electrophoretic deposition (EPD)

alumina layer, 98

CNTs, 97–98

small particles, 96

titania photocatalyst, 97

Electroplating. *See* Electrochemical deposition

Environmental stress crack resistance (ESCR)

branch length, 225–226

broadened MW distribution, 555

cocatalyst influence, polymer production, 498–499

dependence, 222

LCB levels, 313

polymer production, Cr/Silica, 188–189

EPD. *See* Electrophoretic deposition

ESCR. *See* Environmental stress crack resistance

External mass transfer, catalytic wall

microreactors

catalyst, thickness, 69

dependency, Sherwood number, 70

molecular diffusion coefficient, 72

volumetric mass transfer coefficient, 71

F

Flame combustion synthesis

chemical reactions, 105

microchannel, 106

porous catalyst deposition, 105–106

Forster's two-cycle representation, 28, 32, 34

H

Heat-up ramp profile, 575

High-density polyethylene (HDPE)

as commercial forms, PE, 129–131

density, 207

"Marlex," 136

High-load melt index (HLMI)

catalyst performance characteristics, 501

fluoride effects, 384

molten polymer response, 284

vs. relaxation time, LCB, 442

response

H₂ addition, 431

1-hexene L⁻¹ addition, 427–428

rise, sintering point, 189

silica calcination at high temperature, 190

Hydrosilanes, *in situ* branching

characteristics, 529

Cr(VI)/silica, at 600 °C, 529–530

declining activity, Cr/silica, 530–531

lowering density, 531–532

MW distribution, 532–533

olefin distribution, 533

Si–H reaction with Cr–O–Si bonds, 530

I

In situ branching

cocatalyst

characteristics, polymer, 518–519

polymer density, 518

as reducing agents, 518

Si–O–Cr linkage breaking, 519

commercial advantages, 528–529

H₂, as cocatalyst

polymer properties, 534

possible heterolytic chemisorption, 534–535

hydrosilanes

characteristics, 529

Cr(VI)/silica at 600 °C, 529–530

declining activity, Cr/silica, 530–531

lowering density, 531–532

MW distribution, 532–533

olefin distribution, 533

Si–H reaction with Cr–O–Si bonds, 530

α -olefin

coproduction, 509

distribution, 522–526

generating sites, 509–511

incorporation efficiency, 526–528

reaction variables

densities, varying ethylene concentration, 520–521

1-hexene concentration, 520

order of contacting, 521–522

reduction step

CO treatment, 512

Cr/silica-titania activation, 650 °C and 870 °C, 512

melt index, 513

polymers densities, 513–514

silica support

activation temperature influence, 516

chromium loading, 517–518

- In situ* branching (*cont.*)
 Cr(II)/silica-titania, 515
 initial temperature, 516–517
 properties production, four catalysts,
 516
 titania influence, α -olefin generation
 and incorporation, 515
- Internal mass transfer, catalytic wall
 microreactors
 effectiveness factor, 68
 temperature profile, 69
- Ir(I) complexes
 oxidative addition reactions
 H₂ and CO, 29
 HI, 28
 MeI, 27–28
- Iridium-complex catalyzed carbonylation,
 methanol
 BP Cativa™ process
 acetaldehyde concentrations, 27
 benefits, 26–27
 low water concentrations, 24
 metal compound categories, 25–26
 and rhodium catalysts, 25
 ruthenium promoter, 26
 catalyst speciation, 23
 reaction mechanism
 iodide concentration, 34
 Ir(I) complexes, 27–29
 Ir(III) methyl complexes, 29–31
 promoters, 31–32
 ruthenium-promoted catalytic process,
 32–34
 WGS reaction, 24
- Ir(III) methyl complexes
 CO-loss mechanism, 31
 CO partial pressure, 30
 flash-photolysis experiments, 30–31
 iodide loss mechanism, 30–31
 stoichiometric carbonylation, 29–30
- J**
- Janzen and Colby (JC)- α values
 vs. activation temperature, 308
 catalyst surface area, 300
 LCB levels, 308–309, 318–319, 404
 pore volume, 305
 selective poisoning, titania, 346–347
- L**
- Linear low-density polyethylene (LLDPE)
- as commercial forms, 129–131
 origin, 137
- Long-chain branching (LCB).
 activation temperature, AlPO₄, 448
 AlPO₄
 film blowing, 442
intramolecular incorporation, 443–444
 polymerization series, 441–442
 production, Cr/AlPO₄ vs. Cr/alumina,
 441
 relaxation time, polymers, 442–443
 solvent-fractions analysis, 443
- branch distribution, 293
- catalyst carrier structure, 270
- Cr/alumina, 403–405
- Cr-Cr proximity, 280–281
- CY-a values, 315
- increased vinyl concentration, 299
- macromer insertion, 288–289
- melt elasticity, 271–272
- melt elasticity and catalyst structure
 commercial applications, 313–314
 dehydroxylation vs. coalescence,
 308–310
- hydrothermal treatment, 314–315
- pore volume, 304
- residence time, 320–321
- silica, types, 319
- surface area, 300–301
- SEC-MALS, 273–274
- solution polymerization, 295
- two-step activation
 catalysts dehydroxylation, 373–374
 comonomer incorporation, 372
 vs. one-step activation, 373
 polymer contents, 372–373
- M**
- Macromer insertion, chain architecture
 dichromate species with Cr ions, 290
 electron deficiency, 290
 “frozen out,” polymer chains, 288
 incorporation mechanism, 287–288
 “*intramolecular*” incorporation, 289
 LCB generation, neighboring sites,
 290–291
 LCB levels, 288–289
 melt viscosity curve, 291
 trigger mechanism, 289–290
 “Marlex,” 136
- Mass transport, carrier structure
 complex behavior, 246

- MW distribution, 248–249
rate-decay kinetics, 247–248
reaction temperature, 246–247
soluble metallocene catalysts, 248
types, 245–246
- Melt elasticity and catalyst structure
commercial applications
alkaline aging effect, blow molding, 311–312
fundamental catalyst properties, 311
LCB influence, molding characteristics, 313–314
parison swell/layflat, 313
dehydroxylation *vs.* coalescence
calcination influence, chromium, 309–310
Cr-to-surface bonding and ligation, 311
independent causes, 308–309
LCB levels, Davison silica grades, 308–310
three series, catalysts, 309–311
flame treatment, 316–317
fluxing, sodium, 315–316
hydrothermal treatment
CY-a values, 315
LCB content, 314–315
particle coalescence, Davison silicas, 313–314
materials, 320
pore volume
average coordination number, 308
commercial silica colloids, 306–307
Cr/silica–titania compression, 306–307
CY-a value, 306
dried samples impregnation, 307
hydrogel samples, alkaline aging and drying method, 305
LCB levels variation, 304
vs. surface area, 306
residence time
CY-a values, 321
LCB content, slurry process, 320–321
mass transport limitations, 321–322
polymer yield influence, metallocene, 322–323
rigid inorganic fillers, 322
shear stress response, solution process, 321–322
“single-site” catalyst, 323
silica, types
bimodal pore distributions, 319–320
LCB levels, 319
- polymerization-grade, 316
precipitated, 318
pyrogenic/fumed, 317
surface area variations, grades, 317–318
Sylox, 318–319
- surface area
activity per unit, 304
LCB level, Davison silica grades, 300–301
Oswald ripening, 303
porosity changes, Cr/silica–titania, 302
sintering, 302
- Melting and swelling
differential scanning calorimetry, 540–541
Flory–Huggins relationship, 544
fouling, 541
“foul” zone, 545
low-density resin, 543
maximum operating temperatures, 544–545
PE grades behavior, isobutane, 542–543
temperature limits, 540
- Micropacked-bed reactors
randomly packed
advantage, 57
cross-flow design, 58
pressure drop and mass transfer, 57–58
radial-flow, 58–59
silicon, as construction material, 59
structured packed
brass wires, 60–61
catalytic filaments, 61
metallic/ceramic foams, 61–62
microstructured string, 60
and randomly packed, 59–60
“sandwiching,” 62–63
types, 56
- Microstructured catalysts
fibrous
mass transport, 82
selective hydrogenations, 83
foam, 82
prestructured reactors
posts, 81
traps, 82
- Microstructured reactors (MSRs)
characteristics, 52–53
choice and design
chemical reaction time, 54
first and second Damköhler number, 55

Microstructured reactors (MSRs) (cont.)

mass transfer elimination, 55–56
thermal behavior, 56

multiphase reactions, design

continuous, 73–75
dispersed, 76–81
hydrogenation, 72
microstructured catalysts, 81–83
types, 72–73

reaction design, gas phase reactants

catalytic wall microreactors, 63–72
micropacked bed, 56–63

surface layers preparation

gas phase deposition, coating, 101–106
liquid phase deposition, coating,
87–101
partial oxidation, 83
porous layer, 84
treatment, wall material, 84–87

Monsanto process

acetic acid manufacture, 3
catalyst stability and solubility, 6
 CO_2 emissions, 27
lithium iodide promoter, 9

MSRs. See Microstructured reactors

N

Network reinforcement

activity per unit area, 259
alkaline aging, 254–255
common silica grades, 255
environments, influence chain growth,
257

general pattern, polymer MW
dependence, 257–258

MW, sintered catalysts, 257–258

Oswald ripening, 254

polymer MW and catalyst pore diameter
relationship, 256–257

pore diameter calculation, 253

pore volume distributions, Davison
silicas, 255

silica gel coalescence, 254

standard silicas, 257

N-heterocyclic carbenes (NHCs)

catalyst degradation, 15

steric congestion, 14

O

α -Olefins copolymerization

bimodal polymers

low-MW homopolymer and high-MW

copolymer production, 224
reversing, natural branch profile,
223–224

blocking

block *vs.* isolated branching, 224
branch dispersion index (BDI), 224–225

branch distribution

average branch content, 223
branching, low-MW side, 220
deconvolution, seven Schulz–Flory
components, 220–221
electron deficiency, 219
ESCR dependence, 222
ethylene–hexene copolymers
production, 222–223

GPC with butyl branch profiles, 219

incorporation efficiency, 218–219

lower activation temperature, 222

tie molecules role, polymer failure
model, 219–220

branch length

advantages, 225

comonomers comparison, 226

dependence, physical properties,
225–226

catalyst particle size

density production, 227

vs. polymer particle size, 226–227

comonomers reactivity

incorporation efficiency, 1-hexene, 210
vs. manufacturing process, 211

insertion mechanism

1,2-insertion, comonomer, 208

reactivities, 208–209

stereo-selectivity improvement, 209

***in situ* branching**

BEt_3 concentration, 524–525

cocatalysts produced, Cr(II)/
silica–titania, 522–523

coproduction, 509

generating sites, 509–511

incorporation efficiency, 526–528

molar ratio, 1-hexene to 1-butene
incorporation, 523–524

plot, Schulz–Flory background line,
524

reaction temperature, 525

in varying ethylene concentration,
525–526

molecular weight (MW) suppression
butene isomers, 215, 217

- chain transfer, 1,2-insertion and 2,1-insertion, 211–212
density reduction and MI enhancement, 215–216
1-hexene–ethylene copolymers series, 212–213
 β -hydride transfer, 215
infrared (IR) analysis, end-groups, 213–214
isobutylene, 218
MI, Cr/silica–titania catalyst, 217
possible pathways, chain transfer, 218
unsaturation amount, 215
polymer density
 1-butene and 1-hexene, 208
 HDPE, 207
- Organochromium catalysts
acidic oxide support
 activity order, 454
 behavior, chromium oxide, 455–456
 Cr(TMSM)₄ reactivity, 454–455
 fluoride-treated alumina, 453
 reaction with nonacidic silanol groups, 455
 tetrabenzylzirconium activation, 454
- bimodal polymer
 acidic support, P-OH group *vs.* Si-OH group, 467
 Al-associated peak, 466, 468
 coprecipitated AlPO₄, 467
 dicumenechromium(0) reaction, 471
 heating with N₂, 470–471
 mono-attached *vs.* di-attached species, 468
 MW distribution, Cr(DMPD)₂, 465–466
 P-OH and Al-OH, 465
 poisoning experiments, 471–473
 polymerization activity, 473
 reactivity determination, sites, 470
 relative contribution, P- and Al-associated peaks, 469
 uniform distribution, H₂, 470
- bonding
 vs. chromium oxide catalysts, 451
 propylene release, 450
- branching, 478–479
- calcination temperature
 branched homopolymer, 465
 coordinated mono-attached species, 461–462
 dicumenechromium(0) deposition, 464
 families produced, sites, 461
- MW distributions with Cr(DMPD)₂, varying temperatures, 460–461, 463
polymer composition variation, activation temperature, 461
possible attachment, silica–titania, 464
protolysis capability, 459–460
silanol groups characterization, 459
chromium loading
 OH group population, 456–457
polymerization, Cr(II)
 trimethylsilylmethyl compound, 456–457
 tetravalent chromium alkyl compounds, 458
with chromium oxide
 Cr(DMPD)₂, 481–482
 Cr(II) alkyl with Cr(II) oxide species, reaction, 480
 diarenechromium(0) compounds, 482
 “two valent” catalyst production, 481
 unusual chromium catalysts, 482–483
fluoride effect, MW distribution
 chromium loading, 475–476
 Cr₄(TMSM)₈ deposition, 475
 GPC traces, 473–474
 very-high-MW peak, 474
- initiation mechanism
 Cr(IV) alkyl reaction with silica, 458–459
 Cr(0) compounds oxidization, 459
 “open ring,” 449–450
open-*vs.* closed-ring chromocene
 aluminophosphate support behavior, 477–478
 comparison, MW distributions, 476–477
 cyclopentadiene ring loss, 477
 paired Cr species, 478
- types
 chromocene, 451–452
 Cr compounds, 452
- Oswald ripening, 254, 261, 303
- P**
- Particle replication, carrier structure growth and expansion, 243
PE subunits, 243
spherical Cr/alumina catalyst, 244
Ziegler catalyst, 244–245
- Physical vapor deposition
 laser ablation, 102
 sputtering, 101

- "Plateau rate," 234
 Polydispersity index (PDI), 178, 220, 249
Polyethylene (PE)
 comparison
 HDPE and LLDPE production, 131
 melt viscosity *vs.* shear rate, 131–132
 MW distributions, 131–132
 Ziegler resins, 133
density control and MW
 average activity, 550–551
 1-hexene concentration, 548–549
 higher ethylene concentration, 549–550
 Langmuir–Hinshelwood mechanism, 551
 MI dependence, 547–548
 O₂ influence, fluidized-bed process, 552–553
 polymerization kinetics, Cr/
 silica–titania (871 °C), 550
 reaction rate, 550
 residence time variation, 551–552
H₂ influence
 average moments, MW distribution, 562–563
 chain termination, 561
 Cr/silica *vs.* Ziegler catalysts, 558–559
 MI rise, polymer extrusion, 560
 MW distribution, 559–560, 562
 "Zth" moment, 562
manufacture
 activity *vs.* reaction temperature, 546–547
 commercial PE process, 535–538
 limitations, Cr/silica catalyst system, 538–540
markets
 architecture, 129–130
 HDPE, 131
melting and swelling
 differential scanning calorimetry, 540–541
 Flory–Huggins relationship, 544
 fouling, 541
 "foul" zone, 545
 low-density resin, 543
 maximum operating temperatures, 544–545
 PE grades behavior, isobutane, 542–543
 temperature limits, 540
MW distribution control
 Cr/silica–titania, activation
 temperature, 554
 ESCR condition, 555
 melt fracture, 557–558
 physical properties influence, 553
 pressure generation, pipe extrusion, 556–557
origin
 commercial design, 135
 fluidized-bed technology, 137
 LDPE, 133
 licensing agreements, 135–136
 Marlex, 136
 patent, Phillips catalyst, 137
 Phillips catalyst, 133
 solution-form (SF) and particle-form
 (PF) processes, 136
 Ziegler's catalyst, 134
 Zletz's catalyst, 134–135
product contamination
 grit formation, 564–565
 intermixing, 563–564
Polymer formation
 chain growth rate, 165–166
 chain transfer
 H elimination, 173–174
 hydrogenolysis, 174
 MW distributions, 174–175
 pathways, 173
 comparisons, 176–177
 initiation mechanisms
 carbene pathway, 171
 chain initiation, hydrogen, 170
 Cr(IV) alkylidene formation, 169–170
 Cr–H reaction with silica, 172–173
 "missing H," 170–171
 proposed pathways, metallocycle, 172
 reduction
 formaldehyde detection, 166–167
 induction time, 166
 Lewis-acidic carrier addition, 167
 UHMW PE production, 167–168
 site *vs.* chain initiation, 169
 surface acidity
 Brønsted site, 175
 chain termination, 175–176
 comonomer incorporation efficiency, 176
Polymer modification, cocatalysts
 AlEt₃ and BEt₃ influence, 495–496
 BEt₃ influence, 500–501
 boron alkyls, 494–495
 broad MW distributions, 498
 ESCR test, 498

- four different conditions, 498–499
high-MW tail, MW distribution, 494
HLMI/MI ratio, 497–498
parison swell, 500
performance characteristics, 501–502
physical properties, 500
5 ppm BET_3 , influence, 496–497
shear thinning, 497–498
- Promoters, Cr/silica
alkaline earth metals
acid-base reaction, 391
Cr/silica-titania treatment, 392–393
- Cr/silica-alumina
characteristics, 379
MW distributions, 378
- Cr/silica-zirconia
characteristics, 376–377
MW distributions, 374–375
physical properties, 376
promotional influence, titania, 375
- Cr/Sn-silica
 SnO_2 and TiO_2 , 377
thermal instability, low-MW side, 377–378
- halides
fluoride addition, 381–388
silanol group replacement, 379–380
- lithium, 391
- modifiers, 398
- silica phosphate
 H_3PO_4 , 393–394
MW distribution, 394–395
- sodium
characteristics, 388–389
Cr/silica-titania activity, 650 °C, 390
influence, ethylene polymerization, 390
pore volumes and surface areas, 389
surface annealing, 391
- sulfate
MW distributions, 396–397
phosphoric vs. sulfuric acid, sintering, 395–396
- R**
- Reduction and reoxidation (R&R) activation process
calcination time, CO₂, 368–369
chromium-attachment, 364–365
clumping, 370–371
Cr(II), Cr(VI) and Cr/silica, MI values, 370
- $\alpha\text{-Cr}_2\text{O}_3$ crystallites production, 365–366
 CS_2 , 367–368
longer hold times, 369
MI potentials, two series, 367
optimum second treatment temperature, 365
- polymer, MI values, 371
redistribution, chromium, 370
titania-associated sites, 368
titania proximity, 369
- Residence time distribution (RTD)
flow maldistribution, 67
measurement, 61
molecular diffusion, 66
reactor channel, small diameter, 53, 60, 107
reactor performance, 65–66
- Residence time, melt elasticity and catalyst structure
CY-a values, 321
LCB content, slurry process, 320–321
mass transport limitations, 321–322
polymer yield influence, metallocene, 322–323
- rigid inorganic fillers, 322
shear stress response, solution process, 321–322
“single-site” catalyst, 323
- Rhodium complex-catalyzed carbonylation, methanol
- iodide salts
anhydrous process, 10–11
lower water concentrations, 9
oxidative addition, MeI , 9–10
- phosphine ligands and derivatives
chelate structure, 15–16
cisoid isomer, 18–19
degradation, 14–15
diphosphine ligands, 16–17
di-rhodium complexes, 20
 dppeO , 12
heterodifunctional ligands, 11–12
in situ HP³¹ NMR spectroscopy, 13
NHCs, 15
oxidative addition comparison, 13–14
phenyl groups, 14
reaction rate, 10
selectivity, 16
SPANphos diphosphine, 19
trans-chelating ligands, 18–19
triphos, 18
unsymmetrical ligands, 16

- Rhodium complex-catalyzed carbonylation, methanol (*cont.*)
 reaction mechanism
 acetyl complex, 8
 kinetic behavior, 7
 rate, 6–7
 tetraiodide, 9
 WGS reaction, 8–9
- supported
 carbon, 23
 covalent attachment and immobilization, 20
 ionic liquids, 22–23
 ion-pair interactions, 20–21
 leaching, 21
 thin polymer films, 22
- RTD. *See* Residence time distribution
- S**
- Schulz–Flory distribution, 178, 220, 337, 479–480, 511–512, 522–523
- Selective poisoning, titania
 CY- α values, 347
 JC- α values, 346–347
 MW distribution change, 345
 polymer properties change, 345–346
- Shear stress response
 chromium coverage effect, 297–298
 slurry process, 296
 solution process, 296–297
- Silanes
 $(\text{CH}_3)_3\text{SiCl}$ and $(\text{CH}_3)_3\text{Si}-\text{N}-\text{Si}(\text{CH}_3)_3$ reaction, 422, 424
 ^{29}Si NMR spectrum, 424
 “umbrella” crowding effect, 425
- Silanol group replacement
 bromide and iodide, 380
 fluoride addition
 Cr(VI) saturation, 383
 1-hexene incorporation, 385–386
 MI, polymer, 383–384
 MW distributions, 386–388
 polymers characteristics, 385–386
 shear stress response, 384–385
 sintering, 381–382
 silica, 379–380
- SILP catalyst. *See* Supported ionic liquid phase catalyst
- Sintered metal fibers (SMFs)
 catalyst, 62–63
 polyelectrolyte-modified, 100
- Site diversity and carrier influence, Phillips catalyst
 active sites
 Cr loading influence, 196–197
 measurements, Cr/silica, 193–195
 bonding, individual Cr atoms, 177–178
- MW distribution
 Schulz–Flory distribution and PDI, 178
 site reactivity, 178–179
- MW-time dependence
 distribution, Cr/silica, 180–181
 living vs. nonliving polymerization system, 180
 melt index (MI), 179–180
 overheating behavior, 181–182
 reaction behavior, 179–180
- radioactive labeling, 207
- site discrimination, CO titration
 Cr(VI) site reduction, 182
 MI, 183–184
 partial reduction, 182–183
- surface dehydroxylation and annealing
 advantages, 186–187
 average activity, calcination temperature, 184–185
 characteristics, chromium, 186
 color ranges, Cr/silica, 186
 drawbacks, spectroscopic techniques, 187
 ESCR, 188–189
 MW distribution, various temperature, 187–188
 polymerization behavior, 184–185
- thermal treatments
 calcination temperature variance, catalysts series, 189–191
 HLMI, cycled and virgin silica, 191–192
 MW distributions, 192–193
- titration by poisons
 classical poisoning profile curves, 198, 200
 CO, 202–204
 diethyl sulfide, 202–203
 divalent chromium, 205–206
 Hogan's estimation, 197–198
 methanol, 201–202
 MW distribution, 206–207
 oxygen, 198, 201
 various poison examples, 198–199
- Size exclusion chromatography–multiangle light scattering (SEC–MALS)
 vs. JC technique, 443–444

- LCB detection, 273–274
SMFs. *See* Sintered metal fibers
Sol-gel method
 anhydrous gelation of, 316
 preparation, 93–94
 suspensions, 96
 uses, 92
 VO_x/TiO₂ coating steps, 95–96
 washcoats, 95
Specialized activation treatments
 anhydrous impregnation
 chromium loading, 357–358
 chromium reaction with siloxanes, 355
 M1 values, two-step activation
 procedure, 352–354
 one-step *vs.* two-step point, 820 °C, 354
 organics, M1 enhancement, 355
 possible insertion, Cr(VI), 352
 reactive siloxanes, 351–352
 titanium and chromium addition, 355–356
 two-step activation, 356–357
dehydroxylation, enhanced
 CO, CS₂ and bromide/iodide replacement, 358–359
 elemental sulfur vapor, 358–359
 halide-dehydroxylation method, 361–362
 polymer properties, various chemical reactions, 359–361
 sharp drop, catalyst porosity and polymer MI, 363
 silicas extent, various gases, 359–360
 three series results, two-step activations, 362–363
LCB, two-step activation
 catalysts dehydroxylation, 373–374
 comonomer incorporation, 372
 vs. one-step activation, 373
 polymer contents, 372–373
preeactor reduction, Cr(II)
 CO-reduced catalysts, 350
 Cr(VI), 349
 Cr/silica catalysts activities, 540 and 760 °C, 350–351
 MW and branch distributions, 350
R&R activation process
 calcination time, CO, 368–369
 chromium-attachment, 364–365
 clumping, 370–371
Cr(II), Cr(VI) and Cr/silica, MI values, 370
α-Cr₂O₃ crystallites production, 365–366
CS₂, 367–368
longer hold times, 369
MI potentials, two series, 367
optimum second treatment temperature, 365
polymer, MI values, 371
redistribution, chromium, 370
titania-associated sites, 368
titania proximity, 369
Sputtering, 101
Structured supported ionic liquid-phase (SSILP) catalysis, 103
Supported ionic liquid phase (SILP) catalyst, 23
Surface dehydroxylation and annealing
 advantages, 186–187
 average activity, calcination temperature, 184–185
 characteristics, chromium, 186
 color ranges, Cr/silica, 186
 drawbacks, spectroscopic techniques, 187
 ESCR, 188–189
 MW distribution, various temperature, 187–188
 polymerization behavior, 184–185
Surface layers preparation
 anodic oxidation
 alumina layer, 84
 porous oxide layer, 84–85
 chemical treatment
 doping, 87
 skeletal metal layer, 86
 gas phase deposition, coating
 CVD, 102–105
 flame combustion synthesis, 105–106
 physical vapor deposition, 101–102
 high-temperature treatment, 85–86
 liquid phase deposition, coating
 electroless plating and electrochemical deposition, 98–99
 EPD, 96–98
 sol-gel method, 92–96
 suspensions, 88–92
 thickness, 87
 zeolite growth, 99–101
Suspensions, surface coating
 γ-Al₂O₃, 89

Suspensions, surface coating (*cont.*)

- aqueous, 97
- catalytic steam reforming, 88
- CNTs, 97–98
- deposited catalysts, 90–91
- single channel microreactor, 92

Syllox, 318–319

T**Time dependence, Cr/silica**

- activation hold time, influence, 580–581
- dehydroxylation, 576
- silica dehydration reaction, 576
- thermogravimetric analysis (TGA), 576–577
- water loss, annealing process, 577–579

Titania**coating**

- catalyst preparation, 327–328
- fluoridized and titanated data, 329–330
- melt indices (MI) and adsorption,
 - drying temperature, 328–329
- saturation coverage, 329
- titanium compound reaction, 328
- water solvent, 330
- activity enhancement, 326–327
- flame combustion synthesis, 105
- incorporation efficiency

MI potential, 342**Ti/Si 2p intensity ratios, 341–34, 343****influence on copolymerization**

- branch profiles, copolymers, 334–335
- deconvolution, GPC Curves, 336–337
- 1-hexene incorporation, inhibition, 333–334
- possible interactions, 1-hexene, 338–339
- three-dimensional plots, Schulz–Flory site distribution, 337–338

on melt elasticity, 344**melt index (MI), 327****MW distribution**

- change, increasing polymer yield, 331–332
- GPC curves, 330
- photocatalyst, 97
- on porosity
 - catalyst *vs.* virgin silica, 341
 - fluidity plot, 340–341
 - sintering, 340

surface area, silica–titania cogels, 339**selective poisoning**

- CY-a values, 347
- JC- α values, 346–347
- MW distribution change, 345
- polymer properties change, 345–346
- sol-gel method, 95
- “superhydrophilic,” 101

thermal stability

- Cr(VI) sites, 331
- MW distributions, 332–333

Titration by poisons

- classical poisoning profile curves, 198, 200
- CO, 202–204
- diethyl sulfide, 202–203
- divalent chromium, 205–206
- Hogan’s estimation, 197–198
- methanol, 201–202
- MW distribution, 206–207
- oxygen, 198, 201
- various poison examples, 198–199

Triethylboron cocatalyst

- BEt₃, 426
- chain transfer agents, Cr/AlPO₄ *vs.* Cr/silica, 425–426
- MW distributions, 426–427

U**“Umbrella” crowding effect, 425****W****Water gas shift reaction (WGSR)**

- CO through, 359
- iridium-complex catalyst, 27–28
- mechanism, 8–9
- microscale glass reactor, 59
- rhodium catalyst, 26
- silica dehydroxylation, 358–359

Z**Zeolite growth, structured surfaces**

- higher effectiveness, 99

nucleation period, 101**SMF panels, 100****ZSM-5 crystals, 100–101****“Zth” moment, 562**

INDEX

A

- Acetica® process, 117
 Acicular mullite monolith, SEM images of, 294
 Alcohols, vanadium phosphate, 201, 203, 215–216
 Allylic amination, supramolecular catalysis, 101–103
 Alumina
 coating, 276–277
 washcoat, on aluminum foam, 278–279
 Aluminum and palladium, monolithic catalysts, 291–292
 Aluminum hydroxides
 aluminum dihydroxide, 10
 aluminum methyl monohydroxide, 11, 12
 dinuclear alumoxane, 10
 metal chlorides, hydrolysis of, 10
 Aluminum oxide
 with group-4 metallocenes, 18–19
 half-metallocene group-4 metal precursors, on surfaces, 19–21
 Ammonia oxidation, 306–307
 Ammonoxidation, 235–236
 Anodization procedure, aluminum monoliths, 279
 Artificial metalloenzymes, supramolecular catalysis, 108

B

- Benzoin, 71
 BEP. *See* Brønsted–Evans–Polanyi (BEP) relationship
 Bidentate ligands, supramolecular catalysis, 103, 104
 Biomacromolecules, for supramolecular catalysis
 artificial metalloenzymes, 108
 avidin–biotin interaction, 106–107
 DNA-based catalyst, 107, 109
 enantioselective Michael additions in water, 110

- Bioreactors, 315
 Bond order conservation (BOC), 156–158, 159
 Brady–Pettit model, 135, 168
 Brønsted–Evans–Polanyi (BEP) relationship
 $\text{CH}_x\text{--CH}_y$ recombination reaction, 157–158
 CO activation, 152, 153
 Sachtler–Biloen mechanism, 139
n-Butane oxidation, vanadium phosphate materials, 191–192
 concerted reaction mechanism, 197–198
 consecutive alkenyl mechanism
 active oxygen species, 195
 furan, 194, 195
 to MA, 194
 consecutive alkoxide mechanism, 196–197
 $(\text{VO})_2\text{P}_2\text{O}_7$, (100) face of, 193
 MA, yield of, 193
 promoters, effects of, 228–230
 reactor technology for
 fixed-bed reactors, 230
 fluidized beds, 230, 231
 membrane technology, 231–233
 moving-bed reactor, 231
 redox couple mechanism, 198–199

C

- Calcium and strontium hydroxides, 7–9
 ϵ -Caprolactone, ROP catalysis, 42–43
 Carbon monoliths
 in acylation of butanol,
 performance of, 290
 applications, 285
 ceramic composites, SEM images of, 287
 CNF/monolith system, SEM image of, 287–288
 cordierite monoliths, after CNF growth, 288
 enzyme, 288–290
 free lipase and immobilized lipase, initial reaction rates, 289
 lipase, capacity of adsorption, 289–290

- Carbon monoliths (*cont.*)
 methods, for coating, 286
 textural properties of, 287
- Carbon nanofibers (CNF), 286–288
- Catalytic wet air oxidation, Taylor flow regime, 316–317
- Ceramic composites, SEM images of, 287
- Cerium, 226
- Charge relay system, supramolecular catalysis, 70
- Chemical grafting, of Lewis acid aluminum oxide with group-4 metallocenes, 18–19
 catalytically active transition metals, 17–23
- half-metallocene group-4 metal precursors, on aluminum oxide surfaces, 19–21
- heterometallic oxides, of aluminum and non-metallocene group-4 metal precursors, 21–23
- Chemical vapor deposition (CVD), carbon monoliths, 286
- Chromium, 228
- CNF. *See* Carbon nanofibers (CNF)
- Cobalt, 219, 226–227. *See also* Fischer-Tropsch catalysis
 carbonyl-bound silanetriol, 16
- Colloidal solutions, monolithic catalysts, 275–276
- Cordierite monolith
 after CNF growth, 288
 MIL101(Cr)-coated, tetralin oxidation, 297
 with nickel nitrate solution, impregnation, 281
 SEM images of, 274
- Countercurrent flow reactors
 advantages, 317
 film flow monolithic reactors, 317–318
 reactive distillation, 317
- Cucurbit[6]uril and 1,3-dipolar cycloaddition, supramolecular catalysis, 86–87
- Cyclic ketones and nitroalkenes, organocatalyzed asymmetric Michael addition of, 100, 101
- Cyclic zinc-porphyrin trimer, 82, 83
- Cyclodextrin, supramolecular catalysis
 β -cyclodextrin
 receptor, Zn-polyazamacrocycle complex, 72–73
 with thiamine analogue, 72
- α -cyclodextrin alkoxide, 69
 γ -cyclodextrin, ternary complex of, 73
- Cyclohexane oxidation, vanadium phosphate, 237
- D**
- Decarboxylative hydroformylation, catalytic cycle, 81
- Dendrimers, supramolecular catalysis, 113, 114
- Diels–Alder reactions, cyclic zinc-porphyrin trimer catalysts, 82
- Diesel exhaust gas, 303
- Dimethyl phosphine oxide, 97
- Dipcoating, carbon monoliths, 286
- Diphosphine catalyst, self-assembly of, 106
- Diruthenium ligands, supramolecular catalysis, 104, 105
- DNA-based catalyst, supramolecular catalysis, 107, 109
- E**
- Effective molarity (EM), supramolecular catalysis, 68
- Elementary surface reaction steps, Fischer–Tropsch catalysis
 CH_xCH_y recombination reaction activation energies, comparison of, 159–160
 adsorption energies, 158, 159
 BEP relationship, 157–158
 bond order conservation (BOC), 156–158, 159
 chain growth, 161
 on Co(0001) and Ru(0001) surfaces, 160
 methanation, 161
 structure sensitivity, 156–157, 158
 transition states, CH_4 activation, 163
 window, metal–carbon interaction, 161, 162
- C_1 hydrogenation reaction
 activation energies comparison, on metal surfaces and palladium atom, 164
 equilibrium distribution, 166–167
 methane activation, 164
 reaction energy diagram for, 165–166
 ruthenium surfaces, 165, 166
 transition state, 164–165

- CO activation
adsorption energies of, 151
BEP relationship, 152, 153
calculated activation energies, on
dense (111)-type surfaces of, 151
hydrogen-assisted and direct
activation, on corrugated Ru
surface, 157
nickel surfaces, activation energies
comparison, 153, 154
reaction energy paths, comparison of,
157
ruthenium, 153, 156
stepped and nonstepped ruthenium
surface, 151, 152
- Ethylene polymerization, with Lewis acid
grafted heterometallic catalysts
catalytic activity
and computational study, 29–31
half-metallocene heterobimetallic
catalysts, data, 27
MAO concentration, 28–29
metallocene-derived heterobimetallic
catalysts, data, 25
non-metallocene heterometallic
catalysts, data, 28
reaction rates, 24–28
- olefin polymerization, 24
- plastic age, 23
- transition metal, 24
- F**
- Fischer–Tropsch catalysis, mechanistic
issues
alkene/alkane molar ratio, 175
Brady–Pettit model, 135
catalyst deactivation, 172
chain growth and chain termination, 176
chain-growth reaction, C₁ species
Brady–Pettit mechanism, 168
branching mechanism, metallacycle,
171
Gaube mechanism, 169, 170
Maitlis mechanism, 168–170
- cobalt, particle sizes, 132
- computational catalysis, 130, 135, 175
- elementary surface reaction steps,
physical chemistry of, 173
- CH_x–CH_y recombination reaction,
156–163
- C₁ hydrogenation reaction, 163–168
- CO activation, 150–156
- Gaube–Maitlis model, 135
graphene formation, 176
hypothesis, 131
methanation reaction, 134
microkinetics expressions
chain growth, 182
chain-growth parameter, 179–180, 181
complete surface coverage, 180, 181
hydrocarbons, production rate of, 180
for methanation, 177–179
Pichler–Schulz mechanism
(CO insertion route), 145–150
rate expressions for, 179
- Sachtler–Biloen mechanism
(CO dissociation mechanism),
136–145
- oxygogenates formation, 176
rate of CO consumption, 174
total surface coverage, lack of dependence
of, 184
- hydrocarbon chain growth, 183
rate of CO consumption, 182
steady-state equation, 183
- Fischer–Tropsch synthesis, Taylor flow
regime, 315–316
- Fixed-bed reactors, *n*-butane
oxidation, 230
- Fluidized beds, *n*-butane
oxidation, 230, 231
- Fréchet dendrimer, hydrogen-bonding
motifs of, 115–116
- Fuels, combustion of, 305–306
- Furan, 194, 195
- G**
- Gallium hydroxides, 12–13
- Gas/liquid/liquid systems, 318
- Gas-phase reactants, monolithic catalysts
fuels, combustion of, 305–306
- low-pressure-drop applications, 300–304
- post-(finishing) reactors
ammonia oxidation, 306–307
phthalic anhydride synthesis, 307
- research and development projects, with
applications, 308, 309
- short-contact-time reactors
foams, 308
gauzes, 307–308
- Gaube mechanism, chain-growth reaction,
135, 169, 170
- Germanium(II) hydroxide, 13–14
- Glycerol, vanadium phosphate, 236

H

- 1-Heptene, hydroformylation of, 94, 95
- Heterometallic complexes, synthons for aluminum hydroxides, 9–12
gallium hydroxides, 12–13
germanium(II) hydroxide, 13–14
organic-substituted calcium and strontium hydroxides, 7–9
silanetriols, 16, 17
water, 7
- zirconium hydroxide, 14–15
- Heterometallic oxides, of aluminum and non-metallocene group-4 metal precursors, 21–23
- Hetero transition metals, bimodal catalyst, 31–37
- 1-Hexene, with oxygen-bridged heterometallic catalysts, 45–49
- Highest occupied molecular orbital (HOMO), hetero transition metals, 36–37
- Hydrocyanation reactions, supramolecular catalysis, 99, 100
- Hydrodynamics, monolithic catalysts
gas–liquid flow, in tubes, 262
Taylor flow
vs. film flow, 262
in single tube, 263, 264
- Hydroformylation catalysts, oxygen center attachment
aldehydes, preparation of, 45, 46
1-hexene, with oxygen-bridged heterometallic catalysts
CO bridging modes,
types of, 47
data for, 47–49
heterosiloxanes, 47–49
olefins, 49
silanetriols, with carbonyl clusters, 46
structure of, 47
- water-soluble biphasic olefins, with rhodium polyethylene glycolate complex, 50, 51
SHOP (Shell Higher Olefins Process), 50
- Hydroformylation process, reverse-flow adsorption, 120
- Hydrogen bonding
molecular recognition, 76, 78
motifs, of Fréchet dendrimer, 115

I

- Impregnation, monolithic catalysts, 280–282
In situ and theoretical analysis, of vanadium phosphate materials
active catalyst phase formation, dynamic processes, 221
active surface, temperatures, 220
P/V ratio, influence of, 221, 222
- Internally illuminated monolith reactor (IIMR), 315
- Ion exchange, monolithic catalysts, 282, 283
- Iron, 226–227. *See also* Fischer–Tropsch catalysis

L

- Lanthanide motif construction, for ring-opening polymerization catalysis, 39–43
- Lewis acids, 3–4. *See also* Molecular catalysts designing, with enhanced Lewis acidity
- Lipase, carbon monoliths, 289, 290
- Liquid-phase reactants
monolithic catalysts
enzymes, 312
stirred-tank reactor, with monolithic agitator, 312–313
vanadium phosphate materials, 236–238
- Lowest unoccupied molecular orbital (LUMO), hetero transition metals, 36–37
- Low-pressure-drop applications, gas-phase reactants, 300–304
- Ludox AS-40-coated cordierite monolith, SEM micrographs, 276

M

- Maitlis mechanism, chain-growth reaction, 168–170
- Maleic anhydride (MA), 191, 192, 193
- Membrane technology, *n*-butane oxidation, 231–233
- Metal dopants, vanadium phosphate materials
alkali and alkaline earth metals, 227–228
chromium, 228
iron and cobalt, 226–227
molybdenum- and cerium, 226
promoter elements, 223, 224, 229
reaction rates and surface areas, comparison of, 223, 224

- zinc, 225–226
zirconium, 224–225
- Metallic monoliths, 277–279
- Metal ligand complex, to dendrimer, 114
- Metal organic frameworks, 295–297
- Methanation reaction, Fischer–Tropsch catalysis, 134, 177–179
- Methylalumoxane (MAO), 29, 39, 41
- 3-Methyl-1-pentyn-3-ol hydrogenation, 293, 296
- Microfabricated packed bed, monolithic catalysts, 255
- Microkinetics expressions, Fischer–Tropsch catalysis
chain growth, 182
chain-growth parameter, 179–180, 181
complete surface coverage, 180, 181
hydrocarbons, production rate of, 180
for methanation
complete surface coverage, 177, 178
rate expressions for, 177
steady-state condition, 177
volcano-type dependence, 178, 179
- Pichler–Schulz mechanism (CO insertion route)
aldehyde content in, 149, 150
- Anderson–Schulz–Flory distribution of, 149
- chain-growth probability, 148
- C₁ species, generation of, 146
- energy barriers, 146–147
- homogeneous catalysis, 146
- reaction energy diagram and C–C bond formation on hcp-Co(0001) surface, 147–148
- termination reactions, 148
- rate expressions for, 179
- Sachtler–Biloen mechanism (CO dissociation mechanism)
apparent activation energy, 142, 143, 144, 145
- BEP theory, 139
- C₁ coverage intermediates, 141
- C₁ formation, 145
- chain-growth parameter, 141, 142, 143
- control parameter of C₁ coverage, 138, 139
- iron, inverse space velocity influence, 137
- M–C bond energy, 139
- methanation rate, 138, 140
- oxygen removal, 136
- reactivity index, 139
- surface concentration of, 138
- surface coverage, 143, 144
- volcano curve, 140
- Molecular catalysts designing, with enhanced Lewis acidity
- catalytic center, generation of, 5
- C–heteroatom bonds and C–C bonds, 3–4
- organometallic fluorides, of group-4 metals
- CpTiX₃/MAO activity, in toluene, 54–56
- fluorinating reagents, 52–53
- Me₃SnF, 53–54
- styrene polymerization, 54–56
- oxygen center attachment, active metal Al–O–Ln motif construction, for ring-opening polymerization catalysis, 39–43
- bridging oxygen, effect of, 50–52
- catalytically active species, investigation of, 37–39
- chemical grafting, with catalytically active transition metals, 17–23
- ethylene polymerization, with grafted heterometallic catalysts, 23–31
- heterometallic catalysts, 6
- heterometallic complexes, synthons for, 7–16
- hetero transition metals, bimodal catalyst, 31–37
- hydroformylation catalysts, development of, 45–50
- M–O–M¹ motif construction, synthetic strategy for, 16–17
- multimetallic system, 6
- olefin epoxidation catalysis, 43–44
- styrene polymerization, investigation of, 39
- synthetic strategies, 4–5
- transition metals, 3–4
- Molybdenum, 226
- Monolithic catalysts
active phase, deposition of
impregnation, 280–282
ion exchange, 282, 283
precipitation, 282–284
ready-made catalyst particles, coating of, 284–285
- agitated vessel, 251–252
- automobile exhaust gas abatement, 256, 257

- Monolithic catalysts (*cont.*)
- carbon monoliths
 - in acylation of butanol, performance of, 290
 - applications, 285
 - ceramic composites, SEM images of, 287
 - CNF/monolith system, SEM image of, 287–288
 - cordierite monoliths, after CNF growth, 288
 - enzyme, 288–290
 - free lipase and immobilized lipase, initial reaction rates, 289
 - lipase, capacity of adsorption, 289–290
 - methods, for coating, 286
 - textural properties of, 287
 - coating, with support material
 - bare cordierite monolith, SEM images of, 274
 - with colloidal solutions, 275–276
 - metallic monoliths, 277–279
 - pore filling, 274
 - slip casting and pore-filling coating, 274, 275
 - slurry coating, 277
 - sol-gel coating, 276–277
 - decoupling diffusion length and interparticle length
 - active layer coating, 260
 - advantages of, 261
 - catalyst particles/support, structure of, 260
 - characteristic timescales, in porous catalyst particles, 258
 - performance, as function of Thiele modulus, 257–258
 - structured reactors, 259
 - definition, 256
 - extrusion, 256
 - fixed-bed reactor, 252
 - heterogeneous catalysis, gas/liquid reactants, 251, 252
 - high-performance monolithic catalysts
 - α -Al₂O₃ coating, SEM images of, 292
 - aluminum and palladium for, SEM image and elemental maps of, 291–292
 - 3-methyl-1-pentyn-3-ol hydrogenation, 293
 - palladium distribution, 292, 293
 - washcoated monolith, 291
 - metal organic frameworks, 295–297
 - multiphase operation
 - hydrodynamics, 261–263
 - mass transfer rates, in Taylor flow, 263–267
 - parameters, characteristics of, 256
 - permeable walls
 - acicular mullite monolith, SEM images of, 294,
 - mean initial activities per unit silica volume, 3-methyl-1-pentyn-3-ol hydrogenation, 294–295, 296
 - palladium elemental mapping, silica-coated acicular monolith, 294, 295
 - thickness of, 294
 - practical applications, 297
 - gas-phase reactants, 300–312. *See also* Gas-phase reactants, monolithic catalysts)
 - heat effects, 298
 - with high rates, of heat conduction, 298–299
 - liquid-phase reactants, 312–313
 - module design, increased heat transport, 299–300
 - multiphase systems, 313–318
 - preparation, methods for, 273
 - reactors and reactor configurations
 - cocurrent downflow, with free gas recirculation, 268, 269
 - inlets and outlets, 270
 - loop reactors, 269, 270
 - moving-bed structure, 272
 - packed-bed reactor, 268
 - stirrer reactor design, 271
 - structured
 - fiber structures, 255
 - microfabricated packed bed, 255
 - numbers of cells per square inch, 253
 - solid foam (aluminum), 253–254
 - static mixer, 254
 - Monolithic loop reactor (MLR), 314
 - Monsanto process, supramolecular catalysis, 116, 117–118

N

Nickel surfaces, CO activation, 153, 154

O

- Oct-2-enoic acid, supramolecular catalysis, 80
Olefins, 49
epoxidation catalysis
cubic silicon–titanium μ -oxo complex, 44
tert-butyl hydroperoxide (TBHP), 44, 45
titanium catalysts, 43–44
with rhodium polyethylene glycolate complex, 50, 51
Organometallic fluorides, of group-4 metals
CpTiX₃/MAO activity, in toluene, 54–56
fluorinating reagents, 52–53
Me₃SnF, 53–54
styrene polymerization, 54–56
Oxygen center attachment, molecular catalysts designing
Al–O–Ln motif construction, for ring-opening polymerization catalysis, 39
 ϵ -caprolactone, 42–43
synthesis of, 41, 42
bridging oxygen, effect of, 50–52
catalytically active species, investigation of, 37–39
chemical grafting, of Lewis acid aluminum oxide, with group-4 metallocenes, 18–19
catalytically active transition metals, 17–23
half-metallocene group-4 metal precursors, on aluminum oxide surfaces, 19–21
heterometallic oxides, of aluminum and non-metallocene group-4 metal precursors, 21–23
electron density, 52, 53
ethylene polymerization, with Lewis acid grafted heterometallic catalysts
catalytic activity, 24–29
catalytic activity and computational study, 29–31
plastic age, 23
heterometallic catalysts, 6
heterometallic complexes, synthons for aluminum hydroxides, 9–12
gallium hydroxides, 12–13
germanium(II) hydroxide, 13–14
organic-substituted calcium and strontium hydroxides, 7–9
silanetriols, 16, 17

- water, 7
zirconium hydroxide, 14–15
hetero transition metals, bimodal catalyst advantages of, 31–32
data, 34, 35
enthalpy differences, 38
HOMO and LUMO, 36–37
trimetallic complex, 33
zirconium hydroxide, 32
zirconium, titanium, and hafnium, 34
hydroformylation catalysts, development of
aldehydes, preparation of, 45, 46
1-hexene, with oxygen-bridged heterometallic catalysts, 45–49
water-soluble biphasic, 50
main-group and transition metal hydroxides, 8
M–O–M¹ motif construction, synthetic strategy for, 16–17
multimetalloc system, 6
olefin epoxidation catalysis
cubic silicon–titanium μ -oxo complex, 44
tert-butyl hydroperoxide (TBHP), 44, 45
titanium catalysts, 43–44
styrene polymerization, investigation of, 39

P

- Palladium distribution, monolithic catalysts, 292, 293
Photoreactors, 314–315
Phthalic anhydride synthesis, 307
Pichler–Schulz mechanism (CO insertion route), 132, 133, 145–150. *See also* Microkinetics expressions, Fischer–Tropsch catalysis
p-nitrophenylcholine carbonate (PNPCC), CAChe-minimized structure of, 73–74

R

- Redox couple mechanism, *n*-butane oxidation, 198–199
Renewable feedstocks, vanadium phosphate materials, 236
Reverse-flow adsorption (RFA), supramolecular catalysis, 118, 119, 120
Rhodium
in anionic form, 117

- Rhodium (*cont.*)
 diphosphino, from pyridine-hydroxypyridine pairs, 97, 98
 hydrogenation and hydroformylation, host-guest catalysis, 75
 polyethylene glycolate complex, with olefins, 50, 51
 triarylphosphine, 79
- Ring-opening polymerization (ROP)
 catalysis, Al-O-Ln motif
 construction, 39
ε-caprolactone, 42–43
 synthesis of, 41, 42
- ROTACAT reactor, 312–313
- Ruthenium surfaces
 C₁ hydrogenation reaction, 165, 166
 CO activation, 151, 152, 153, 156, 157
- S**
- Sachtlér-Biloen mechanism (CO dissociation mechanism), 131, 136–145.
See also Microkinetics expressions, Fischer-Tropsch catalysis
- Scanning electron microscopy (SEM) image
 acicular mullite monolith, 294
 α -Al₂O₃ coating, 292
 of γ -Al₂O₃ slurry-coated cordierite monolith, 278
 aluminum and palladium for, 291–292
 bare cordierite monolith, 274
 ceramic composites, 287
 CNF/monolith system, 287–288
 of Ludox AS-40-coated cordierite monolith, 276
 vanadium phosphate materials, 200, 201, 202
- Secondary phosphine oxides (SPO)
 platinum catalysts, 94, 95
- Shell higher olefins process (SHOP), 50
- Silanetriols, 16, 17, 46
- Silica, in supramolecular catalysis
 functionalized, with binding motif, 115
 immobilized rhodium phosphine catalyst, 113
- Slurry coating, 277
- Sol-gel coating, 276–277
- Soot abatement, continuous regenerating trap, 303, 304
- Strontium hydroxides, 7–9
- Styrene
 hydroformylation of, 103, 104
- polymerization
 MAO, effect of, 39, 41
 M–O–M¹ motif, data, 40
 organometallic fluorides, 54–56
- Supramolecular catalysis
 assembling ligands, 121
 asymmetric catalysis, artificial biomacromolecules for
 artificial metalloenzymes, 108
 avidin–biotin interaction, 106–107
 DNA-based catalyst, 107, 109
 enantioselective Michael additions in water, 110
- binding site, assemblies of alkyl carboxylic acid substrate, oxidation, 77
- benzoin, 71
- charge relay system, action mode of, 70
- close to catalytic/reactive center, 68
- covalent and supramolecular catalyst-directing group, 78
- covalent nucleophilic catalysis, 70
- β -cyclodextrin receptor, Zn-polyazamacrocyclic complex, 72–73
- γ -cyclodextrin, ternary complex of, 73
- β -cyclodextrin, with thiamine analogue, 72
- decarboxylative hydroformylation, catalytic cycle, 81
- effective molarity (EM), 68
- host–guest catalysis, in rhodium-catalyzed hydrogenation and hydroformylation, 75
- molecular clips, with phosphines/phosphites, 74–75
- molecular modeling, catalyst design, 78–79
- molecular recognition, of hydrogen bonding, 76, 78
- m*-tert-butylphenyl acetate, 2-benzimidazolacetic acid and α -cyclodextrin alkoxide (α -CD), 69
- oct-2-enoic acid, reaction of, 80
- rhodium triarylphosphine, 79
- thiamine diphosphate and zwitterion–carbene resonance hybrids, of thiazolium ion, 70, 71
- vinylacetic acid, hydroformylation of, 79, 80

- Zn-cavitan and *p*-nitrophenylcholine carbonate (PNPCC), CAChE-minimized structure of, 73–74
- catalyst backbone assembly, synthesis strategies
aldehydes, hydrogenation of, 96
allylic amination, 101–103
asymmetric rhodium-complex-catalyzed hydrogenation, 106
bidentate ligands, 103, 104
chiral SPOs, 96
cyclic ketones and nitroalkenes, organocatalyzed asymmetric Michael addition of, 100, 101
dimethyl phosphine oxide, 97
diphosphine catalyst, self-assembly of, 106
diphosphino rhodium, from pyridine-hydroxypyridine pairs, 98
ditopic ligands, 104, 105
1-heptene, hydroformylation of, 94, 95
heterodimeric chelating ligands, 99
hydrocyanation reactions, 99, 100
nickel-diphosphine complex, 99
nitriles, 97
pseudoenantiomeric bisoxazoline derivatives, 102
salt formation, 104
self-assembled diphosphines, 104, 105
self-assembled transition metal-rhodium catalysts, 103
self-assembly, 100–101
SPO platinum catalysts, 94, 95
styrene, hydroformylation of, 103, 104
tris-SPO, 96
zinc complexes, 104–105
- catalyst, function of, 66
characteristics, 65–66
enzymes, 66, 67
homogeneous and heterogeneous catalysis, 65
immobilized catalyst, on solid supports
 Acetica® process, 117
 advantages, 111
 decomposition, 112
 dendrimers, 113, 114
 fluorotags, 116
 Fréchet dendrimer, hydrogen-bonding motifs of, 115–116
 guard bed, 116–117, 118
 homogeneous form, 111
- hydroformylation process, 119, 120
metal ligand complex, noncovalent attachment of, 114
- Monsanto process, reaction sequence of, 116, 117
- phosphite-containing rhodium hydrogenation catalyst, 115
reverse-flow adsorption (RFA), 118, 119, 120
- rhodium, in anionic form, 117
- silica functionalized, with binding motif, 115
- silica-immobilized rhodium phosphine catalyst, 113
- transition metal complex, disadvantages of, 111–112
- reactive species isolation, from reversible encapsulation
 anionic M₄L₆ cage and allyl ammonium ion, 92, 93
3-aza cope rearrangement, 92, 93
- cucurbit[6]uril and 1,3-dipolar cycloaddition, 86–87
- desolvation, 86
- ditopic molecule, with complementary binding groups, 88
- Fujita's self-assembled cage, exo-triamine and encapped Pd(II) ions mixing, 90–92
- molecular reaction vessel, 86–87
- phenylacetylene and phenyl azide, 89–90
- Rebek's capsule, 1,3-dipolar cycloaddition, 89–90
- self-assembly, 88–89
synthetic receptor, 88
transition state, 86
- transition state, 66
- two simultaneously complexed reagents, assemblies of
 asymmetric binding motifs, 84–85
CAChE-generated model, of exo-adduct, 82–83
- 2,2,2-cyclic zinc-porphyrin trimer, 82–83
- cyclic zinc-porphyrin trimer catalysts, for Diels–Alder reactions, 82
- matchmakers, 80–81
- pyridine-substituted dienes and dienophiles, 82
- self-replicating system, 85
- S_N2 reaction, 84

T

Taylor flow, monolithic catalysts
applications
catalytic wet air oxidation, 316–317
Fischer-Tropsch synthesis, 315–316
axial mixing, 264
bioreactors, 315
chemical reactivity per unit of reaction
volume, 266
Chilton-Colburn analogy, 267
coefficient, 265
conventional reactors, gas–liquid transfer,
265
vs. film flow, 262
hydrogenation of, 264–265
mass transfer, rate of, 263–267
monolithic loop reactor (MLR), 314
photoreactors, 314–315
single tube, 263, 264
structured monoliths, turbulent bubble
columns and agitated tanks,
comparison of, 266–267
tert-Butyl hydroperoxide (TBHP), olefin
epoxidation catalysis, 44, 45
Thiamine analogue, β -cyclodextrin, 72
Thiazolium ion, thiamine diphosphate and
zwitterion–carbene resonance hybrids
of, 70, 71
Thiele modulus, monolithic catalysts,
257–258
Titanium catalysts, olefin epoxidation
catalysis, 43–44

U

Urea decomposition, with nickel nitrate, 283,
284

V

Vanadium phosphate materials
acidity, of catalyst, 215
amorphous material, role of
alcohols, 215–216
catalyst activity and surface area,
relationship, 217
cobalt, 219
high-resolution electron micrograph,
218
in situ Raman spectroscopy, 219
spin-echo phosphorus NMR spectra,
216

supercritical antisolvent precipitation,
TEM and electron diffraction
pattern, 220
applications of
ammoxidation, 235–236
liquid-phase reactants, low-
temperature reactions with,
236–238
oxidation, 233–235
renewable feedstocks, use of, 236
n-butane oxidation, 191–192
concerted reaction mechanism,
197–198
consecutive alkenyl mechanism,
194–196
consecutive alkoxide mechanism,
196–197
(100) face, of $(VO)_2P_2O_7$, 193
MA, yield of, 193
reactor technology for, 230–233
redox couple mechanism,
198–199
improvements in, 238–239
in situ and theoretical analysis of
active catalyst phase formation,
dynamic processes, 221
active surface, temperatures, 220
P/V ratio, influence of, 221, 222
layered and ideal structure, 207
maleic anhydride (MA), 191, 192
metal dopants, influence of
alkali and alkaline earth metals,
227–228
chromium, 228
iron and cobalt, 226–227
molybdenum- and cerium, 226
promoter elements, 223, 224, 229
reaction rates and surface areas,
comparison of, 223, 224
zinc, 225–226
zirconium, 224–225
novel precursor synthesis
aerosol process, 203
cetyltrimethylammonium salts,
204–205
exfoliation and reduction processes,
205, 206
gas-phase synthesis, 203
hydrothermal synthesis, 204
supercritical antisolvent precipitation,
206–207
oxidation state

active catalysts, 210
active sites, 211–212, 213
axial HREM image, 210, 211
bright-field image, platelet, 210
evolution, of catalyst with time, 209
nanosized $(\text{VO})_2\text{P}_2\text{O}_7$ particles,
 evolution of, 212–213
one-phase hypothesis, 208–209
transmission electron micrographs, 212
 V^{5+} phases, 208
X-ray diffraction, 210, 211
paraffins, oxyfunctionalization of, 207
phosphorus/vanadium ratio, 214
standard precursor synthesis
 alcohol, 201, 203
 ion beam image of, 202, 203
SEM micrograph, 200, 201, 202
vanadium source, 200
VPA preparative route, 199, 200

VPD preparative route, 201
VPO preparation route, 200
Vinylacetic acid, hydroformylation of,
 79, 80

W

Water-soluble biphasic hydroformylation
catalyst, 50

X

XONONTM Cool Combustion technology,
 305–306

Z

Zinc, 225–226
Zirconium, 224–225
Zirconium hydroxide, 14–15, 32