

KEY: *T* refers to tables. *F* refers to figures.

A

Abbreviations, 476–478

Activity, coefficient:

- definition, 24
- rules, 451–452
- tables, 453–455

Aircraft:

- aluminum alloys in, 395
- Boeing 777, 395
- fretting corrosion, 182
- hot corrosion, 229–230
- microbiologically influenced corrosion, 388–389
- stress-corrosion cracking, 395
- titanium, 425

Aluminum, **383–398**

- anodic protection,
- anodizing, 287–288, 296
- atmospheric corrosion, 194*T*, 383, 391
- cathodic protection of, 252, 260, 261, 384, 395
- chlorinated solvents, corrosion in, 389–391
 - inhibitors for, 390
 - mechanism of, 390–391
 - water, effect of, 390*F*
- coatings, 280–281
- corrosion characteristics, 384–392
 - by microbiological constituents in fuel, 388–389
- galvanic coupling of, 392–393
- nitric acid, corrosion rates in, 392
- oxide coatings on, 287–288, 383, 386
- painting of, 296
- passivity of, 83, 383, 384, 386, 388
- soil corrosion, 208
- steam, corrosion in, 384

vapor degreasing of, 293

waters, corrosion in, 384–386

pH, effect of, 387

pitting, 98, 99

Aluminum alloys, **393–395**

- anodes in impressed current cathodic protection, 259
- clad, 384, 395
- compositions, 385*T*
- exfoliation of, 394
- intergranular corrosion, Al–Cu alloys, 393–394
- sacrificial anodes, 254–255
- stress-corrosion cracking, 384, 394–395

Amorphous alloys, 335

Amphoteric metals, 12, 47, 79, 245, 260, 279, 446

Anion, definition, 13

Anode:

- definition, 11–13
- materials, for cathodic protection, 258–260
- sacrificial, 144, 251, 252, 254–257, 263, 354, 370, 378

Anode–cathode area ratio, 56, 67–69, 71–75, 123, 132, 208–210

- magnesium, galvanic corrosion of, 402
- tantalum, 442

Anodic protection, **263–264**

- by alloying, 90–92
- of aluminum, 264, 386
- theory of, 90–92

Anodizing:

- aluminum, 287–288, 296
- magnesium, 403

Atmospheric corrosion, **191–204**

- avoiding, 201–202

comparison with seawater and soils, 195*T*
 corrosion product films, protection by, 192–195
 corrosion rates, steels, 193*F*
 alloying, effect of, 202*T*
 various metals, 194*T*
 critical humidity, 199–200
 factors influencing, 195–200
 gases in atmosphere, effect of, 197–199
 sulfur dioxide content of air, 197–198
 moisture, effect of, 199–200
 particulate matter, effect of, 196–197
 time of wetness, 199
 types of atmospheres, 192
 Automobiles, 4, 196, 295
 aluminum alloys in, 394–395
 body panels:
 electrogalvanizing, 270
 painting, 295
 phosphate coating, 287
 engines, 3
 Ford, 404
 fretting corrosion, 182
 Honda, 395
 lead in, 447
 magnesium in, 399, 404
 nickel coatings, 272
 mufflers, 2, 280
 painting, 295
 stainless steels in, 341
 Volkswagen, 399

B

Backfill, for cathodic protection, 255, 259
 Bacteria, 4, 118–120, 206–207, 279, 298, 309, 367, 388–389
 Blister, 66
 Blister cracking, 170–172
 Boiler corrosion, **323–330**
 alkali addition, effect of, 327–328
 embrittlement detector, 324–325
 inhibitors for, 328
 mechanisms of, 328–330
 oxygen, dissolved, effect of, 329
 oxygen scavengers, 318–319, 330
 Boiler water, treatment of, 326–328
 alkali addition, 327–328
 carbon dioxide removal, 326–327
 inhibitor addition, 328
 oxygen removal, 326
 phosphate addition, 328
 Brasses, **371–378**
 naval, red, yellow, 371–372
 see also Copper–zinc alloys

Bridges, 2
 cathodic protection for, 253
 steel reinforcements in, 144
 failure by stress-corrosion cracking, 153, 169–170
 painting, 290
 weathering steels for, 201
 Bronzes, 13, 252, 270, 371–372

C

Cadmium, 70–71, 168, 178, 184, 198, 231, 264, 271, 274, 276–277, 288, 314, 392–393, toxic properties of, 277, 392–393
 Catalytic properties and passivity, 108–109
 hydrogen overpotential, relation to, 65
 Cathode, definition, 11–13
 Cathodic protection, **251–267**
 anode materials for, 258–260
 backfill, use of, 255, 259
 coatings, combined use with, 255–257
 criteria of protection, 260–263
 doubtful, 262
 potential measurements, 260–262
 current, magnitude required, 77–79, 257–258
 economics of, 263
 history of, 252–253
 how applied, 253–254
 overprotection, effect of, 259–260
 pitting, used to avoid, 261–262, 354
 potential decay along pipeline, 257
 derivation of formula for, 467–469
 steel reinforcements in concrete, 144, 253
 stress-corrosion cracking, to avoid:
 in aluminum alloys, 384, 395
 in brasses, 378
 in stainless steels, 360
 in steel, 155–156, 162
 in titanium alloys,
 theory of, 77–79
 Cation, definition, 13
 Caustic embrittlement, 152
 Cavitation-erosion, **130–131**
 in diesel engine liner, 131*F*
 Cells:
 Daniell, 54–55
 galvanic, 11–12, 22, 26, 54, 68, 84, 115, 143, 157, 197, 207, 254, 280, 343, 369
 local-action, 10–11, 68, 142, 261
 passive-active, 96, 280, 352
 reference, 34–37
 calomel, 35–36
 copper-copper sulfate, 36–37
 silver-silver chloride, 36–37

- types, in corrosion reactions, 13–15
 - concentration, 13–14
 - differential aeration, 13–15, 28–30, 164, 197, 298–299, 329, 353, 370, 371, 384, 388, 430
 - differential temperature, 14–15
 - dissimilar electrode, 13
- Cement, Portland, as cause of corrosion:
 - of aluminum, 388, 391
 - of lead, 446
 - as protective coating for steel, 286
 - steel reinforcements, failure of, 143–145
 - galvanic effects of, 144
- Chromates, *see* Passivators
- Chromium–iron alloys:
 - critical composition for passivity, 100–101
 - critical current densities for passivity, 101*F*
 - oxidation, elevated temperatures, 232–235
 - effect of yttrium, 234–235
 - maximum temperatures in air, 235*T*
 - potentials of, in 4% NaCl, 101*F*
 - Flade, 88*F*
 - see also* Stainless steels
- Chromium–nickel alloys:
 - commercial alloys, composition, 413*T*
 - corrosion characteristics, 411–417
 - critical composition for passivity, 102
 - intergranular corrosion, 415
 - oxidation, elevated temperatures, 226*T*, 236–237
- Clean Air Act, 191, 198, 289, 295
- Coatings:
 - compliant, 289
 - inorganic, **285–288**
 - chemical conversion, 286–288
 - chromate, 288
 - oxide, 287–288
 - phosphate, 286–287
 - as preparation for painting, 295–296
 - Portland cement, 286
 - vitreous enamel, 285–286
 - metallic, **269–283**
 - aluminum, 280–281
 - application, methods of, 269–271
 - cadmium, 276–277
 - chromium, 279–280
 - classification, 271–272
 - lead, 274
 - nickel, 272–274
 - electroless, 273–274
 - fogging of, 273
 - thickness of, 272–273
 - tin, 277–279
 - zinc, 274–276
 - atmospheric corrosion, 198
 - seawater corrosion, 275
 - soil corrosion, 208
 - polarity reversal in hot waters, 276
 - see also* Steel, galvanized
- organic, **289–301**
 - cathodic protection, combined use with, 255–257
 - filiform corrosion, 296–299
 - pigments, inhibiting, 291–292
 - plastic, 299–300
 - prime coat, 291–292, 294, 295, 296, 299, requirements for, 291–292
 - rules for applying, 295
 - surface preparation, 293–295
 - effect on life, 295*T*
- Cobalt and cobalt alloys, **419–423**
 - cavitation-erosion, 420, 423
 - compositions, 422*T*
 - corrosion characteristics, 419–423
 - fretting corrosion, 420, 423
- Cold working, effect on corrosion:
 - iron and steel, 149–150
 - nickel, 150
 - pure iron, 150*F*
- Complexes, chemical, effect on Emf, 30–32
- Concrete, 143–145, 253, 388, 391
- Condenser tube alloys, 378–379
- Conversion factors:
 - corrosion rates, 474–475*T*
 - to current densities, 475*T*
- Copper, **367–381**
 - atmospheric corrosion, 194*T*, 195*T*, 197–199
 - blue staining, caused by, 321, 369
 - corrosion characteristics, 367–371
 - deposit attack, 370
 - hydrogen, reaction with, 231–232
 - impingement attack, 17, 368–372, 379, 411
 - inhibitor for tarnish of, 314
 - oxidation, high temperature, 230–232
 - pitting of, 369–370, 371, 378
 - seawater corrosion, 195*T*,
 - soil corrosion, 195*T*, 208, 209*T*
 - stress-corrosion cracking, 371, 374
 - waters, corrosion by, 369–371
- Copper–nickel alloys, for condenser tubes, 378–379
 - see also* Nickel alloys, copper–nickel,
- Copper–zinc alloys, **371–378**
 - dezincification, 17, 252, 334, 371–374
 - effect of Zn content, 372*F*
 - mechanism of, 334, 374
 - impingement attack, effect of Zn content, 372*F*

- stress-corrosion cracking, 374–378
 - effect of applied potential, 377*F*
 - effect of Zn content, 372*F*
 - mercurous nitrate test, 376
 - prevention, 378
- Corrosion:
 - alloying, effect of, 333–335
 - cost, 2–5
 - current and corrosion rate, 56, 475*T*
 - importance of, 2–5
 - direct and indirect losses, 2–5
 - products, protective, in atmospheric corrosion, 192–195
 - rates, calculation of, from polarization data, 71–73, 456–461
 - classification for handling chemical media, 16
 - control of, anodic, cathodic, 68–69
 - derivation of formula for, 456–461
 - polarization, influence on, 68–71
 - scientist and engineer, 1–2
 - tendency and free energy, 21–22
 - types, 15–18
- Corrosion-erosion, definition of, 17
- Corrosion fatigue, **173–180**
 - appearance of, 174 (Photo)
 - definition, 18, 173–174
 - effect of oxygen, moisture, 175
 - mechanism of, 179–180
 - minimum corrosion rate for, 178*T*
 - prevention, 178–179
 - strength, values of, 177*T*
- Crazing, 286
- Crevice corrosion, 14, 29, 99, 117, 173, 342, 350–351, 352–354, 361, 412, 416–417, 429–430, 432
- Critical pitting potential, 97–99, 160, 264, 351–354, 384–386, 421, 429, 437
- Critical pitting temperature, 99–100, 351–352
- Crystal face, effect on corrosion, 13, 149
 - effect on oxidation, 230–231, 232
- Current density:
 - critical for passivity, 85–86, 90, 117, 242, 411
 - for Cr–Fe alloys, 101*F*
 - for Ni–Cu alloys, 104*F*
 - exchange, 61
 - limiting, 58–60
 - passive, 85
 - for Ni–Cu alloys, 104*F*
- D**
- Deactivation of water:
 - definition, 317
 - by hydrazine, 318–319
 - by ion-exchange resins, 326
 - by sodium sulfite, 318, 326
- Dealloying, 17, 118, 172, 372–374
- Deaeration of water, 178, 317–319, 326, 402, 414
 - definition, 319
 - oxygen concentration, maximum allowable for steel systems, 320*T*
- Depolarization:
 - in acids, 124–125
 - by oxygen, 72, 116, 122, 124, 131–133, 139, 262, 458
- Deposit attack, 370
- Dezincification:
 - Cu–Zn alloys, 334, 371–374
 - definition, 17
 - mechanism, 374
- Diesel engines, 130, 215, 322,
- E**
- Electrochemical equivalent, 10
- Electrochemical impedance spectroscopy, 75–77
- Electrochemical mechanism:
 - of corrosion, 9–18, 22, 70–71, 143
 - for corrosion of iron and steel, 115–116
 - of passivation, 89
 - of pitting, 96, 351–353
 - of stress-corrosion cracking, 157–158, 190, 377
- Electrode:
 - copper–copper sulfate, 36–37
 - hydrogen, 24–25
 - oxygen, 28–30
 - reference, 34–38
 - standard or normal hydrogen, 24–25
- Electron configuration theory, 102–108
- Emf:
 - calculation of, 25–28
 - relation to Gibbs free energy, 22
 - Series, definition of, 30
 - Table, 31*T*
- Endurance limit, 18, 141
- Environmental Protection Agency (EPA), 191, 196, 369, 447
- Exfoliation, 394
- F**
- Faraday, value of, 22
- Faraday's law, 9–11, 56, 85, 178, 244, 259,
- Fatigue, affected by air, moisture, 175
 - limit, definition of, 18, 173
 - strength, definition of, 173
 - see also* Corrosion fatigue

- Filiform corrosion, 279, **296–299**
 photos, 297
 theory of, 298–299
- Films, oxide:
 isolation of, 94
 passive, oxidizing properties, 93–94
 thickness of:
 on aluminum, 383
 on iron, 93–94
- Flade potential:
 aluminum, 383
 definition, 86
 chromium, 279
 chromium–iron alloys, 88*F*
 iron, 47, 84–89, 93–94, 112
 nickel, 410
 nickel–copper alloys, 106
 nickel–molybdenum alloys, 412
 tantalum, 441
 titanium, 426
- Fogging, 16, 273, 411
- Fouling, marine:
 Cu^{2+} concentration to prevent, 103–105, 252, 369
 of Cu–Ni alloys, 103–105, 104*F*
 of stainless steel, 351
- Fracture mechanics, 162–166
- Fretting corrosion, **180–184**
 aircraft, 182
 automobiles, 182
 cobalt alloys, 420, 423
 definition, 17, 180–181
 equation for weight loss, 183
 derivation of, 471–474
 factors causing, of steel
 mechanism, 182–184
 nuclear reactors, 182
 prevention, 184
 railroad car wheels, 182
- Fugacity, 24
- Furnace windings, 236, 237
- G**
- Galvanic coupling:
 of aluminum, 391–393
 in aerated media, 127
 in deaerated media, 127–129
 of different steels, 141–142
 in soils, 206
 effects of, at elevated temperatures, 227–228
 hydrogen cracking of stainless steels, caused by, 357
 hydrogen embrittlement of Ta, caused by, iron–gold, 306
 in natural waters and soils, 141–142
 and passivity of stainless steels, 361
- Galvanic Series:
 definition, 32
 in seawater, 33*T*
- Galvanized steel, *see* Steel, galvanized
- Glass, cavitation–erosion, 130
 coatings, 256, 285–286
 electroless nickel coatings on, 274
 stress-sorption cracking, 160
- Glass electrode, 25
- Glassy alloys, 335
- Gmd, conversion factors of mm/y,
 474–475
 definition, 16
- Gold, 17, 22, 109, 227, 232, 269–270, 286, 334,
 372–374,
 coatings, electrical contacts, 182
 coupled to iron, 306
 fatigue, 175
- Graphitic corrosion, 138, 142, 206
- Gun barrels, protecting, 287
- H**
- Humidity:
 critical in atmospheric corrosion, 196,
 199–201
 and filiform corrosion, 298
 and growth of bacteria, 120
 and stress-corrosion cracking, 165, 376
- Hydrogen:
 cracking, 65–66, **166–172**
 and cadmium coatings, 276
 and cathodic protection, 252, 259, 267
 of cobalt alloys, 421–423
 mechanism, 167–170
 metal flaws, effect of, 170–172
 of stainless steels, 354–361
 of steel, 166–172
 of steel reinforcements in concrete,
 145
 disease, in copper, 231–232
 in silver, 203
 electrode, 24–25, 25*F*
 standard, 25
 embrittlement, 54, 158, 166–169
 of aluminum alloys, 395
 and cathodic protection, 259
 of magnesium alloys, 402
 caused by microbiologically influenced
 corrosion, 118
 caused by pickling inhibitors, 312
 of Ta,
 of ultra-high-strength steels, 357

overpotential, 60–61, 62*T*, **63–66**, 70, 80–81,
90, 116, 123, 125–129, 139, 143, 149–
150, 267, 278–279, 310, 402, 412, 448
standard scale, definition of, 25

I

Impingement attack:

of condenser alloys, 379
of copper, 368–370
of copper–tin alloys, 371
of copper–zinc alloys, 371–372
definition, 16–17
photo, 368

Inhibition efficiency, definition, 311

Inhibitors, 2, 3, **303–316**

for aluminum, 384, 390, 392
classification, 303
for corrosion fatigue, 178–179
and critical pitting potential, 97
definition, 303
for diesel-engine cylinder liners, 130
for engine cooling systems, 323
evaluation of, 73
in foods, 278
for industrial waters, 318
boiler waters, 152, 328
cooling waters, 322–323
for iron and steel, 130, 133, 143
for lead, 447
mechanism of, 304–308
nontoxic, 323
oxygen, as inhibitor in acids, 125
in phosphate coatings, 287
pickling, 310–313
applications of, 294, 312–313
concentration, effect of, 312*F*
hydrogen embrittlement, caused by, 312
pigments for paints, 291–292
slushing compounds, 313
sodium:
benzoate, 306, 384
borate, 133, 306, 322
polyphosphate, 306–307, 323
silicate, 133
for soil corrosion, 206
for stainless steels, 157, 361
pitting corrosion, 350–351
for stress-corrosion cracking, of brass, 376,
378
of steel, 152–156, 157
of stainless steels, 157
of titanium alloys, 157, 430–431
for tarnishing of copper, 314
toxicity, 303–304, 309

in vapor degreasing aluminum, 293
vapor phase, 201
see also Passivators

Insulation, stress-corrosion cracking
associated with, 355, 375

Intergranular corrosion:

in copper–zinc alloys, 156, 378
definition, 17–18
in aluminum alloys, 252, 384, 394, 395
in high purity aluminum, 384
in lead alloys, 448
in nickel-base chromium alloys, 415, 416
in stainless steels, 252, 343–350, 358
in titanium, 430–431
in zirconium, 437

Ion implantation, 270

Ionization constant of water, various
temperatures, 28*T*

ipy, conversion factors to mdd, 474–475
definition, 16

IR drop, 56–57, 63, 68, 73, 74, 88, 262–263,
456

calculation of, in electrolytes, 58
as cause of polarization, 61–63

Iron, **115–148**

acids:

citric, rates in, 71*T*, 139*T*
dissolved oxygen:
effect of, 124–125
inhibition by, 125–127
HCl + NaCl, rates in, 139*T*
velocity, effect of, 125–127
anaerobic bacteria, effect of, 118–120
anodic protection, 90, 263–264
atmospheric corrosion, 191–204
cast,

coupled to steel, 142
graphitic corrosion, 138, 142, 206
soil corrosion, 138, 206
water pipe, 286
in water, 138

composition, effects of, 138–142
heat treatment, effect of, 142–143
hydrogen cracking, 166–172
delay time and H₂ content, 168*F*
metallurgical factors, effect of, 138–143
oxidation, elevated temperatures:
in oxygen, 232–234
in steam, 323–326
effect of pH, 327*F*
oxygen, dissolved, effect of, 116–118
pH, effect of, 120–123
salts, dissolved, effect of, 131–138
seawater, rates in, 124*T*, 195*T*

soil corrosion, **205–213**

stress, effect of cold work, 149–150

stress-corrosion cracking, **151–156**

effect of:

alkalies, 151–152

carbon monoxide–carbon dioxide, 153

cold work, 153–155

illuminating gas (HCN), 153

liquid ammonia, 153

nitrites, 151–155

silicates, 152

temperature, effect of in aqueous media, 120

velocity, effect of:

in acids, 125–127

in natural waters, 129–130

wrought, 123, 124*T*, 138, 206, 209*T*

see also Steel

K

Knife-line attack, 348

L

Lead, **445–449**

and air quality, 191

atmospheric corrosion, 192, 194*T*, 198

cathodic protection of, 251, 260, 261, 262*T*,

chemical conversion coatings on, 286

coatings of, on steel, 179, 184, 271, 274

in copper alloys, 372

corrosion characteristics, 445–448

of Pb-acid battery grids, 447–448

in differential temperature cells, 15

fatigue cracks in, 174

hydrogen overpotential of, 62*T*, 65

oxidation, 231

in paints, 290, 291–292, 295*T*, 296

passivation of, 84, 92, 127

polarization of, 68

soil corrosion, 207, 208, 209*T*,

stray current corrosion, 242, 244*T*, 245

toxic properties of, 4, 393

in water, 137, 317, 321,

woods, corroded by, 446

Lead and Copper Rule, EPA, 369, 447

Liquid-metal embrittlement, 158, 160, 165

Local-action cells, 10–11, 68, 142, 261

current, 10, 259, 266

Luggin capillary, 56, 57*F*

M

Magnesium, 399–406

alloy compositions, 403*T*

coatings on, 403–404

corrosion characteristics:

alloys, 400–403, 404–404

pure magnesium, 399–400

as sacrificial anode, 254–255

efficiency of, 255

for hot water tanks, 256*F*

stress-corrosion cracking, 402–403

tolerance limit, definition of, 400

for iron, 401*F*

univalent ion, 259

mdd, conversion factors to ipy, 474–475

definition of, 16

Molybdenum, 84, 96, 108, 184, 229, 237, 341–

342, 344, 348, 350, 351, 353, 409*T*,

412, 415–417, 421

N

Nernst equation, derivation of, 22–24

Nickel, **408–411**

atmospheric corrosion, 194*T*, 198–201

corrosion characteristics, 408–411

Flade potential, 410

oxidation, elevated temperatures, 216–217,

236–237, 410

alloyed with Cr, 226*T*, 234*F*, 236–237

intergranular, 236–237, 410

Nickel alloys, **411–417**

compositions, 413*T*

critical pitting potential, 98*T*

irradiation-assisted stress-corrosion

cracking, 172

nickel–chromium, 236–237, 411–412

nickel–chromium–iron, 236, 414–415

in pressurized water reactors, 414–415

nickel–copper, 414

atmospheric corrosion, 194*T*

cupro-nickel, 103, 378–379, 411

corrosion fatigue, 177*T*

in condenser tubes, 378–379

corrosion in 3% NaCl, 103*F*

critical current densities, in 1*N* H₂SO₄, *F*

fouling of, in seawater, 105

passive current densities, 104*F*

passivity, 103–108

pitting, in seawater, 104*F*

stress-corrosion cracking, 379

nickel–molybdenum, 412, 415–416

behavior in acids,

Nitrites, *see* Passivators

Nuclear reactors, 172–173, 182, 348, 437

O

Overpotential:

definition, 60

- hydrogen, 60–61, **63–66**
 - factors affecting, 63–66
 - mechanism of, 64–65
 - values of, 62*T*
- metal deposition and dissolution, 61
 - values of, 62*T*
- oxygen, 61
 - values of, 44*T*
- Overvoltage,
 - definition, 60
- Oxidation, 215–240
 - catastrophic, hot ash, 229
 - of copper, 230–232
 - equations expressing rate, 220–223
 - galvanic effects, 227–228
 - initial, thin film, 216–218
 - internal, 231
 - iron and iron alloys, 232–233
 - iron–chromium alloys, 235–236
 - life test, ASTM, 233–234
 - nickel and nickel alloys, 236–237
 - coupled to Pt in borax, 227–228
 - reactive element effect, 215, 234–237
 - Wagner theory, 223–224
 - Zn alloyed with Al, Li, 227*T*
- Oxidation-resistant alloys, 234–237
 - Reactive element effect, 234–235
- Oxides, properties, **224–227**
 - p*-, *n*-type, 224–225
- P**
- Paints, **289–291**
 - applying, **295–296**
 - see also* Coatings, organic
- Parting, definition, 17, 334
- Passivators, **303–310**
 - applications, 308–310
 - chromates, 303–310
 - for cooling waters, 322–323
 - toxicity, 304, 322–323
 - critical concentrations of chlorides and sulfates, 310*T*
 - effect on steel, various temperatures and Cl⁻ concentrations, 308*T*
 - nontoxic alternatives, 323
 - critical concentration, 305
 - definition, 303
 - examples of, 88
 - oxygen as, 125, 306
 - sodium, benzoate, 306, 384
 - borate, 133, 306, 322
 - nitrite, 303–306, 309–310
 - corrosion of steel, effect of concentration, 309*T*
 - critical concentrations of chlorides and sulfates, 310*T*
 - polyphosphate, 306–307, 323
 - combined with chromates, 309
 - for treatment of municipal waters, 321
 - disposal, 322
 - silicate, 133, 152, 306
 - for treatment of potable waters, 321–322
 - theory of, 88–90, 304–308
 - toxicity, 303–304
 - see also* Inhibitors
- Passivity, **83–113**
 - of alloys, **100–108**
 - critical compositions, 100–102
 - breakdown of, 89, 90, 94, 96
 - catalytic properties, relation to, 108–109
 - cathodic plolarization, effect of, 108
 - chlorides, action of, 96–100
 - definitions, 84
 - film thickness:
 - on aluminum, 383
 - on iron, 93–96
 - of iron:
 - in nitric acid, 89–90
 - in sulfuric acid, 84–87
 - theories of, 92–96
 - adsorption, 92–94, 96, 99, 102, 108
 - electron configuration, 102, 108–109
 - oxide-film, 92, 96, 102
- Patina, on copper, 198–199
- pH:
 - aluminum, effect of, 387–388
 - definition, 28
 - iron, effect of, 120–123
 - measurement, 28
 - values for water at various temperatures, 28*T*
 - zinc, effect of, 274–275
- Pilling and Bedworth rule, 6, 219–220
- Pipelines, 2, 4
 - cathodic protection of, 211, 253–255, 257–263, 467–470
 - microbiologically influenced corrosion of, 120
 - hydrogen-induced cracking of, 140, 170
 - inhibitors, 309
 - pitting of, 210
 - soil corrosion of, 205, 206
 - stray-current corrosion of, 241–244, 247
 - stress-corrosion cracking of, 153, 210–211, 300
- Pitting:
 - in aluminum, 384–386
 - in condenser alloys, 378–379

- in copper, 369–370
 - critical potential for, 97–99
 - critical temperature for, 99–100
 - definition, 16
 - elongated, 352, 353*F*
 - factor, 16
 - in stainless steels, 350–354
 - theory of, 96–99, 351–353
 - Plastics, coatings, used for, 299–300
 - tetrafluorethylene, 184, 300
 - Polarization:
 - causes of, 58–63
 - activation, 60–61
 - concentration, 58–60
 - IR drop, 61–63
 - corrosion rates:
 - anode–cathode areas:
 - effect of, 73–75
 - calculation of, 71–73
 - relation to, 68–71
 - definition, 54
 - galvanostatic, for iron, 86*F*
 - how measured, 56–58
 - potentiostatic, for iron, 85*F*
 - Potential:
 - calculation of, 22–28
 - corrosion, 54
 - definition, 56
 - measurement, 66
 - critical:
 - for pitting, 97–99
 - for stress-corrosion cracking, 158–162, 355–358
 - decay along pipeline:
 - derivation of formula, 467–469
 - formula, 257
 - definition, 24–26
 - drop along soil surface by current entering pipe, 245, 469–470
 - Flade, chromium, value for, 279
 - chromium–iron alloys, 88*F*
 - definition, 86
 - iron, value for, 86
 - as calculated, 93, 112
 - in chromates, 88–89
 - nickel, value for, 410
 - passivity, relation to stability of, 87
 - pH, dependence on, 86–87
 - hydrogen, normal, 25
 - standard, 25
 - liquid-junction, 33–34
 - characteristic values, 34*T*
 - sign of, 25–28
 - standard, 31*T*, 476*T*
 - definition, 24
 - standard hydrogen, definition, 25
 - Potentiometer, 22, 26, 66
 - Potentiostat, 66–67, 85, 263
 - Potentiostatic polarization, 85, 97, 105, 242
 - Pourbaix diagrams, 43–51
 - aluminum, 47–48, 383
 - basis of, 43–44
 - copper, 367–368
 - iron, 45–47
 - lead, 445–446
 - limitations, 49
 - magnesium, 48–49, 400
 - nickel, 408–410
 - tantalum, 441–442
 - titanium, 419–420
 - water, 44–45
 - zirconium, 435–436
- R**
- Radiation damage, **172–173**
 - Reaction limit, 334
 - values, gold alloys, 334*T*
 - Reactive element effect, 215, 234–237
 - Resistivity:
 - IR drop in electrolytes, 58, 61–63
 - in soil, 206–207
 - measurement, 246
 - formula for, derivation of, 470–471
 - Ring-worm corrosion, 143
 - Risk, 5, 7–8
 - Rust:
 - composition, 116
 - definition, 1
 - iron, effect on corrosion of, 14, 15*F*,
 - protection by, in atmospheric corrosion, 192–195, 201
- S**
- Saturation index:
 - alteration of, by water treatment, 136, 321
 - calculation of, 134–136, 417*F*
 - derivation of equation for, 461–463
 - effect of temperature, 136
 - limitations of, 137–138
 - and municipal waters, treatment of, 321–322
 - Schikorr reaction, 325
 - Season cracking, 334–335
 - Seawater:
 - aluminum in, 280, 386, 392
 - galvanic coupling, 393
 - cathodic protection in, 254–256, 258*T*, 261, 272,
 - coal-tar coatings, 291

- copper-aluminum alloys in, 371
- copper-nickel alloys in, 378–379
- copper-zinc alloys in, 372
- corrosion of aircraft over, 229
- copper in, 195*T*, 369–370,
- corrosion in, 11, 14
- corrosion rate of steel in, 16
- corrosion rate of magnesium in, 19
- galvanic coupling in, 127
- galvanic series in, 32, 33*F*
- IR drop in, 58
- iron in, 118
- lead in, 446, 448
- lead alloys for cathodic protection, 446
- magnesium in, 400, 405
 - stress-corrosion cracking, 402
- microbiologically influenced corrosion in, 118–119
- nickel in, 410, 411
- nickel-chromium alloys in, 412,
- nickel-chromium-iron alloy in, 414
- nickel-chromium-molybdenum alloys in, 412, 416–417
- nickel-copper alloys in, 103, 104*F*, 408*T*, 411, 414
- stainless steel in, 208, 341, 344, 350–351, 352, 353*F*, 354, 357, 360, 362
- steel in, 123, 124*T*, 131–132, 138, 195*T*,
 - boiler corrosion, 324, 329
 - cavitation-erosion, 130
 - corrosion fatigue, 175, 178
 - deaeration, 317
 - effect of carbon content, 139
 - effect of chromium, 141, 208
 - effect of flow velocity, 129, 130*F*
 - effect of nickel, 141
 - paints for, 292
 - Portland cement coatings on, 286
- and stray current corrosion, 244
- titanium in, 98, 426, 429–430, 432
- titanium alloys in, 431
- zinc in, 195*T*, 274–275
- zirconium in, 437
- Sensitization:
 - aluminum alloys, 384, 393–394
 - stainless steels, 156, 172, 343–347, 350, 351, 359–361
- Silver, 15, 16, 17, 32, 61, 179, 184, 197, 216, 223–224, 227–228, 231, 232, 264, 269, 271, 334, 361, 400–402, 410, 447
- Slushing compounds, 313
- Soils, corrosion in, 205–213
 - avoiding, 211
 - in cinders, 208
 - depth of burial, effect on, 207
 - factors affecting, 206–207
 - pitting, 208–210
 - rates, 195*T*, 209*T*
 - resistivity measurements, 207, 246
 - stress-corrosion cracking, 210–211
- Stainless steels, **335–365**
 - anodic protection of, 90–91, 263–264
 - classes and types of, 337–343
 - cold work, 343
 - compositions, 338–340*T*
 - corrosion resistance, general, 361–362
 - crevice corrosion, 350–351
 - avoiding, 354
 - definition, 100, 335
 - galvanic coupling, 357, 361
 - heat treatment, for optimum corrosion resistance, 342–343
 - sensitizing, 343
 - austenitic, 343–345, 344*F*
 - ferritic, 349
 - history, 336–337
 - hydrogen cracking, 167, 170, 357
 - avoiding, 361
 - 18–8, cold worked, 357
 - galvanic coupling, as cause of, 167, 357
 - intergranular corrosion, **343–350**
 - austenitic types, 343–349
 - avoiding, 347–348
 - effect of carbon and nitrogen, 346*F*
 - knife-line attack, 348
 - of nonsensitized alloys, 348–349
 - theory of, 345–347
 - ferritic types, 349–350
 - theory of, 350
 - passivity, effect of alloyed Cu, Pt, Pd, 90
 - pitting, 350–354
 - avoiding, 354
 - critical potential, 97–99
 - critical temperature, 99–100
 - inhibiting against, 350–351
 - theory of, 351–353
 - soils, corrosion in, 208
 - stress-corrosion cracking, hydrogen cracking, **354–361**
 - austenitic:
 - avoiding, 360–361
 - critical potential in $MgCl_2$, 360
 - damaging ions, 354–355
 - in polythionic acids, 359–360
 - metallurgical factors, 357–359
 - nickel, effect of, 358*F*
 - nitrogen, carbon, effect of, 358, 359*F*
 - oxygen dissolved, effect of, 355, 356*F*

- ferritic and martensitic, 354, 356–357, 361
 - weld decay, 344, 345*F*
 - Steam:
 - condenser corrosion, 327
 - corrosion:
 - of aluminum in, 386
 - of iron in, 323–326
 - of zirconium in, 437–438
 - return-line corrosion, 327, 328
 - Steel:
 - atmospheric corrosion, 193*F*, 194*T*, 195*T*, 202*T*
 - Bessemer, oxygen-furnace, 138
 - carbon content, effect on corrosion, in 3% NaCl, 124*T*
 - in hydrochloric acid, 151
 - in seawater, 139
 - cold rolling, effect of, 149–150
 - composition, effects of, 138–141
 - corrosion fatigue, 173–180
 - fretting corrosion, 180–184
 - galvanic coupling, effects of, 141–142
 - galvanized, 274–276
 - corrosion of:
 - atmospheric, 198, 274, 275*T*
 - in soils, 206, 208, 209*T*
 - first patent, 252
 - painting of, 296
 - pitting of, in hot water, 276
 - heat treatment, effect on corrosion, in water, 124*T*
 - in acids, 143
 - low alloy, 138–142, 206
 - atmospheric corrosion, 193*F*, 194*T*, 201
 - copper-bearing, 124*T*, 140–141, 206
 - atmospheric corrosion, 193*F*, 202*T*
 - corrosion in aqueous media, 123, 138–142
 - corrosion fatigue, 177*T*
 - oxide coatings on, formation of, 287
 - pickling of, 294
 - reinforcements in concrete, 143–145
 - cathodic protection, 144, 253
 - soils, corrosion in, 206, 207, 208, 209*T*, 210
 - stress-corrosion cracking in, 210–211
 - stainless, *see* Stainless steels
 - weathering, 201
 - see also* Iron
 - Stepwise cracking, 140, 166
 - Stern–Geary equation, 72–73
 - derivation of, 456–458
 - general corrosion, 458–461
 - Stray-current corrosion, **241–249**
 - avoiding, 246–247
 - damage by, ac vs. dc, 241–242
 - to amphoteric metals, 245
 - quantitative values, 244
 - detection of, 245
 - pipe, inside of, 243–244
 - sources of, 242–244
 - Stress, residual, 149
 - in brass, 376
 - and corrosion fatigue, 177
 - and hydrogen-induced cracking, 170
 - in magnesium alloys, 402–403
 - in stainless steels, 357
 - and stress-corrosion cracking of steel, 151, 155, 156*T*
 - in zirconium alloys, 437
 - Stress-corrosion:
 - of aluminum alloys, 394–395
 - of bridge cable, 153
 - of copper–zinc alloys, 162, 163*F*, 374–379
 - critical crack depth, 165–166
 - definition, 18
 - initiation of, critical potentials for, 161–162
 - of iron and steel, 151–156
 - of magnesium alloys, 402–404
 - mechanisms, **156–166**
 - of pipelines, 210–211
 - rate of crack growth, 162–166
 - of stainless steels, 354–361
 - surface flaws, effect of, 166, 431
 - of titanium alloys, 431
 - Stress intensity factor, 164–166, 171–172
 - Stress-sorption cracking, 158–161, 395
 - Subscale formation, 231
 - Sulfidation, 18, 226, 230, 237, 409*T*
 - Sulfide stress cracking, 166–167, 421
 - effect of surface flaws, 171–172
- T**
- Tafel equation, 61, 64, 71, 457, 459
 - Tantalum, **441–443**
 - as alloying element, 155
 - corrosion characteristics, 436, 441–443
 - galvanic effect, 227, 228*F*
 - and glass coatings, 286
 - hydrogen embrittlement, avoiding, 441–442
 - passivity, 96, 441–442
 - Telluric currents, 241
 - Terne plate, 274
 - Thermal spraying, 270
 - Tin:
 - atmospheric corrosion, 194*T*
 - coatings, 277–279

- complexes, effect on corrosion, 30–32
 - corrosion characteristics, 279
 - Titanium, 425–434
 - alloy compositions, 428
 - corrosion characteristics, 425–432, 436
 - in alkali–hydrogen peroxide solution, 427
 - Flade potential, 426
 - hydrochloric acid, corrosion rates in
 - inhibited, 427–429, 428*F*
 - effect of alloyed Pt or Pd, 428*F*
 - nitric acid, fuming, reaction with, 427
 - pitting and crevice corrosion, 429–430
 - in bromides, iodides, 429–430
 - pitting potentials in chlorides at elevated temperatures, 430*F*
 - seawater, resistance to, 429–430
 - stress-corrosion cracking of alloys, 431
 - cathodic protection against, 431
 - inhibiting ions for, 431
 - Transition metals:
 - catalytic properties, 108–109
 - overpotential for deposition or dissolution, 61
 - passive properties, 93
 - Transpassivity, definition, 92
 - Tungsten, 96, 220, 221, 412, 421,
- V**
- Valves, corrosion of, 142
 - Vanadium, as cause of catastrophic oxidation, 229
- W**
- Wagner:
 - definition of passivity, 84
 - theory of oxidation, 223–224
 - and Traud experiment, 70
 - Wash primer, 296
- Water, treatment of, **317–332**
 - boiler, 323–328
 - cooling, 322–323
 - hot-water heating systems, 321–322
 - municipal supplies, 321–322
- Welds:
 - knife-line attack, 348
 - weld decay, 345 (Photo)
 - definition, 344
- Y**
- Yttrium, 215, 234–235, 236–237, 271
- Z**
- Zinc:
 - atmospheric corrosion, 194*T*, 195*T*, 198, 199
 - chromate coatings on, 288
 - coatings on steel, 208, 274–276. *see also* Steel, galvanized
 - electrogalvanizing, 270
 - oxidation of, in O₂, 227*T*
 - painting of, 296
 - pH, effect of, 275*F*
 - rich paints, 292, 296
 - seawater corrosion, 195*T*, 275
 - soil corrosion, 195*T*, 207, 208, 209*T*, 211
 - Zirconium, **435–440**
 - corrosion characteristics, 435–439
 - pitting in chlorides, critical potentials for, 437
 - Pourbaix diagram, 436
 - radiation, effect on, 173
 - steam, behavior in, 437–438, 439*F*
 - effect of alloyed tin, 438
 - stress-corrosion cracking, 437
 - transition point, 436, 438, 439*F*
 - water, high temperature, corrosion by, 437–439