

Index

- Abrasive wear, 234, 234f
- Absorption, of radiation, 367–368
- Absorptivity, 366
- Acids, 395, 396t–397t, 407t–408t, 415t
- Activated state, 283–284
- Activation, thermal, 302
- Activation energy
 - for creep, 277–278
 - for self-diffusion, 284
- Active coatings, 411
- Actuation
 - ferro-electric, 333–334
 - piezo-electric, 332, 332f
 - thermal, 259
- Adhesive wear, 234, 234f
- Ageing, GL2-56–GL2-58
- Airframes, 299–300
- Alcohols, 396t–397t, 407t–408t, 415t
- Aldehydes, 396t–397t, 407t–408t, 415t
- Alkalis, 395, 396t–397t, 407t–408t, 415t
- Allotropes, 266
- Alloy(s)
 - ceramic, GL2-3
 - components, GL2-3
 - concentration, GL2-3–GL2-4
 - constitution of, GL2-5–GL2-6
 - definition of, 120–121
 - ductility of, 134
 - equilibrium of, GL2-5–GL2-6
 - ferrous, 488–493, 489f–490f
 - metallic, GL2-3
 - steel, 491
 - strength of, 134
 - super, 293
- Amontons, Guillaume, 228
- Amorphous structure, 60, 61f
- Ampère, André Marie, 309, 342
- Amplifiers, 357t
- Anisotropy, 59, 354
- Annealing, 132, 482, 483f
- Anodizing, 393
- Anti-ferro magnetism, 351, 351f
- Antioxidants, 389
- Archard wear constant, 229
- Arrest points, GL2-36
- ASM Materials Handbook*, , 2
- Asperities, 233f
- Ball-bearing race, 451–453, 452f, 452t–453t
- Bar chart, 21–22, 22f
- Barrier coatings, thermal, 298–299
- Basquin's law, 191–192
- Batch size, economic, 441
- Beams
 - elastic bending of, 84–87
 - minimizing weight of, 91f, 93–96, 94t, 155t
 - plastic bending of, 144f
 - shape of, 153–155
 - vibrating, 89–90, 90f
 - yielding of, 142–145, 143f
- Bearing pressure, maximum, 230–231
- Bearings, 234–237, 236f–237f
- Bending of beams, 84–87
- Bendy design, 105–106, 106f
- Bike frames, 461–463, 462f
- Bi-metal corrosion cell, 401f
- Blades, turbine, 296–298, 297f
- Blend, of polymers, 135, 181
- Body-centered cubic atom packing, GL1-3–GL1-4, GL1-4f, GL1-4t, 60, 61f
- Body fluids, 396t–397t, 407t–408t
- Bohr, Niels Henrik David, 351
- Boltzmann, Ludwig, 251
- Boltzmann's constant, 251
- Bond coat, 299
- Bond stiffnesses, 67t
- Boriding, 239
- Boundary-layer lubrication, 235–236
- Bowden, Philip, 232
- Brakes, 237–238, 489–490, 489f
- Breakdown, dielectric, 310f, 323–324, 324f
- Breakdown potential, dielectric, 308, 312, 324

I-2 Index

- Brittle fracture, 177, 178f
- Bubble chart, 22, 23f
- Buckling, 89, 89f
- Buffers, thermal, 265–266
- Buildings, structural materials for, 102–104, 103f, 103t
- Bulk modulus, 54
- Cables, electrical, 328
- Calorimetry, GL2-35t
- Cameras, 380
- Capacitance, 311–312
- Capacitors, 310–311
- Capital cost of equipment, 440
- Capital write-off time, 440
- Carbon dioxide footprint, GL2-6
- Carbon steels, GL2-50, GL2-60–GL2-64
- Carburizing, 239
- Carnot, Sadi Nicolas, 244
- Casting, of metals, 480–481, 480f
- Cast iron, 489–490, 489f–490f
- Cathodic protection, 410f
- CD case, 39–40, 446, 447t
- Ceramic(s)
 - alloys, GL2-3
 - applications of, A-4t–A-5t
 - atom packing in, 62, 63f
 - corrosion resistance in, 404t–405t
 - creep and, 292–293
 - crystals, GL1-12–GL1-15, GL1-12f–GL1-13f
 - defects in, 120–122
 - density of, A-7t–A-8t
 - as family, 15f
 - fracture in, 177, 178f
 - fracture toughness in, A-13t–A-14t
 - glass points of, A-5t–A-6t
 - historic, 3f
 - microstructure of, 464–465, 465f
 - phase diagrams, GL2-28–GL2-33, GL2-29f
 - prehistoric, 3f
 - processing of, 493
 - properties of, 16
 - stress-strain curve for, 113f
 - tensile strength in, A-11t–A-12t
 - thermal conductivity of, A-15t–A-16t
 - thermal expansion of, A-15t–A-16t
 - yield strength in, A-11t–A-12t
 - Young's modulus in, A-9t–A-10t
- Ceramic coatings, 412t
- Change, phase, 265–266
- Chart(s)
 - bar, 21–22, 22f
 - bubble, 22, 23f
 - creep strength-density, 281–282
 - electrical properties, 314–316
 - embodied energy, GL2-7–GL2-8, GL2-13f–GL2-14f, GL2-17f
 - endurance limit, 197–198
 - fracture toughness-modulus, 174–175, 175f
 - fracture toughness-strength, 175–176, 176f
 - magnetic properties, 348–350
 - maximum service temperature, 280, 281f
 - melting point, 280
 - modulus-density, 57, 58f
 - modulus-relative cost, 57–59, 58f
 - modulus-strength, 118–119
 - optical properties, 371–372
 - reflectivity-refractive index, 371–372, 373f
 - refractive index-dielectric constant, 371, 372f
 - remanence-coercive field, 348–349, 348f
 - saturation-magnetization-susceptability, 349–350, 349f
 - strength-density, 116–118, 117f
 - strength-dielectric loss, 316
 - strength-electrical resistivity, 315
 - thermal conductivity, 248–250, 248f
 - thermal conductivity-electrical resistivity, 315
 - thermal expansion, 248–250, 248f
 - wear rate-hardness, 230–231
- Chemical properties, 8, 9f
- Chemical segregation, 180, 180f
- Classification
 - of materials, 14–17, 15f
 - of processes, 18–20, 18f
- Cleavage fracture, 177, 178f
- Climb, dislocation, 288–289, 289f
- Close packed hexagonal atom packing, GL1-4–GL1-6, GL1-4t–GL1-5t, GL1-5f, 59–60, 60f
- Clutches, 237–238
- Coarsening, precipitate, 474–475
- Coat, bond, 299
- Coatings
 - active, 411
 - application of, 413f
 - ceramic, 412t
 - metallic, 411–412, 412t
 - polymeric, 411–412, 412t

- protective, 403, 411–414
- self-generated, 411
- thermal barrier, 298–299
- Coefficient of friction, 228, 230
- Coercive field, 327, 346
- Coffin, Lou, 193–194
- Cohesive energy, 65–66
- Cold drawing, 112–114
- Color, 378–379, 379f
- Columns
 - buckling of, 89, 89f
 - yielding of, 142
- Compatibility, material, 424–426, 435
- Composites, A-4t–A-5t, 70, 498–499
- Composition gradient, GL2-45–GL2-48
- Compression, 83–84
- Compressive crushing strength, 115
- Compressive surface stress, 200–201, 201f
- Computer-aided information management, 23
- Computer-aided material selection, 99–100
- Computer-aided process selection, 442–443, 443f
- Concentrations
 - alloy, GL2-3–GL2-4
 - stress, 149–151, 150f
- Condensers, 310–311
- Conduction
 - electrons, 319
 - ionic, 317–318
- Conductivity
 - electrical, 309–310, 316–318
 - thermal, A-15t–A-16t, 247–250, 247f–249f, 254–257, 315
- Connecting rod, 215–216, 216f, 447–450, 448f–449f, 448t–449t
- Constitution point, GL2-12, GL2-12f
- Consumption
 - growth of, GL2-3–GL2-4, GL2-8f
 - of materials, GL2-3
- Contact stresses, 148–149, 149f
- Cooling rate, critical, 477–478
- Corkscrew case study, 101, 101f, 156
- Corrosion, 395
 - configuration and, 406–411
 - fatigue, 403
 - fighting, 403–416
 - geometry and, 406–411
 - inhibitors, 403, 414, 415t
 - intergranular, 402–403
 - monitoring, 403, 416
 - pitting, 402–403
 - resistance rankings, 404t–405t
 - selective, 402–403
- Corundum structure, GL1-14–GL1-15, GL1-14f, GL1-15t
- Cost
 - dedicated, 439–440
 - equipment, 440
 - minimization of, 97, 155
 - model, 438–441, 439t
 - of shaping processes, 438–441
- Coulomb, Charles Augustin, 310
- Crack tip plastic zone, 172–174, 172f
- Crash barriers, GL2-18–GL2-19, GL2-25f
- Crazing, 126f, 127
- Creep, 276
 - Creep activation energy, 277–278
 - Creep curves, 276–278, 277f
 - Creep damage, 278–279
 - Creep exponent, 276–277
 - Creep fracture, 278–279, 289–290, 291f
 - Creep mechanism, in polymers, 290–292
 - Creep modulus, 302
 - Creep relaxation, 301–302, 301f
 - Creep resistance, 292–294
 - Creep-rupture diagrams, 278–279, 279f
 - Creep strength, 281–282
 - Creep testing, 276–278, 277f
 - Crevices, corrosion and, 410f
- Critical configuration, 130
- Critical cooling rate, 477–478
- Critical strain energy release rate, 171
- Cross-linking, 135
- Crystalline imperfection, 120–122, 121f
- Crystallography, 59
- Crystal structures, GL1-2–GL1-6
- Cumulative damage, 194–195
- Curie, Pierre, 326
- Curie temperature, 326–327
- Cushions, 104–105
- Damage tolerance, 174, 174t
- Damping coefficient, 188–189
- Data, 23
- Da Vinci, Leonardo, 228
- Debye, Peter, 251
- Dedicated cost, 439–440
- Deformation mechanism diagrams, 289, 290f
- Deformation processing, 482–484

- Density, 4, 5f, 49f
 - atomic structure and, 59
 - creep strength and, 281–282
 - dislocation, 131
 - flux, 343
 - manipulation of, 70–73
 - relative, 73
 - of selected materials, A-7t–A-8t
 - units of, 48
- Dependence, temperature, 274, 275f
- Design
 - corrosion and, 403–406
 - creep and, 295–302
 - displacement-limited, 209–210, 209f
 - documentation and, 38–39
 - eco-design, GL2-10–GL2-14
 - energy-limited, 208–209, 209f
 - fail-safe, 212–215
 - for fracture, 220–222
 - fracture-safe, 207–211
 - judicious, 403
 - leak-before-break, 213
 - load-limited, 207–208, 209f
 - magnetic, 355–360, 357t–358t
 - materials and, 33–35
 - optical, 380
 - original, 30–31
 - process and, 33–35
 - process selection in, 422–424
 - ranking and, 37–38
 - redesign, 31–32
 - screening and, 37
 - for thermal stress management, 257–259
 - translation and, 36–37, 39–41
- Design-limiting properties, 8
- Design process, 30–33
- Diamond cubic structure, GL1-12–GL1-13, GL1-12f
- Dielectric
 - permittivity of, 311
 - properties, 310–314
- Dielectric, definition of, 308
- Dielectric behavior, 321–322
- Dielectric breakdown, 310f, 323–324, 324f
- Dielectric breakdown potential, 308, 312, 324
- Dielectric constant, 7–8, 7f, A-17t–A-18t, 308, 310f, 311, 371
- Dielectric loss, 322–323, 331–332
- Dielectric loss factor, 308, 312–313, 313f, 316
- Dielectric strength, 312
- Diesel engines, injectors for, 333–334, 334f
- Differential thermal expansion, 257
- Diffuse reflection, 367
- Diffusion, 282–287
- Diffusion activation energy, 284
- Diffusional flow, 287–288, 288f
- Diffusive jump, 283f
- Diffusivity, thermal, 6, 247–250, 249f, 261
- Dilatation, 52
- Dilatometry, GL2-35t
- Dipole, magnetic, 350f
- Dipole moment, 322–323, 323f
- Direction, in crystal geometry, GL1-10–GL1-11, GL1-11f
- Dislocation, 121–124, 121f–122f
- Dislocation climb, 288–289, 289f
- Dislocation density, 131
- Dislocation line, 122–123
- Dislocation strength, 133–134
- Dispersion, 130–131
- Displacement-limited design, 209–210, 209f
- Displacive transformation, GL2-60
- Dissipation factor, 313
- Documentation, 35, 38–39, 424
- Domains, 326–327, 327f, 352–354, 353f
- Domain walls, 326–327, 352, 354f
- Drawing, 126–127, 126f, 135
- Driving force, 474
- Ductile fracture, 177–179, 178f
- Ductile-to-brittle transition, 179–180
- Ductility, 4, 114, 134
- Durability
 - factors affecting, 386f
- Eco-design, GL2-10–GL2-14
- Economic batch size, 441
- Eddy currents, 355–356
- Edge dislocation, 122–123
- Einstein, Albert, 251
- Elastic bending, 84–87
- Elastic energy, 55
- Elastic extension, 83–84
- Elastic hinges, 156–157
- Elastic modulus, 5f
 - cohesive energy and, 65–66
 - definition of, 4
 - in elastomers, 17, 68
 - manipulation of, 70–73

- in metals, 16
 - in polymers, 17
- Elastic selection modulus, 143–144
- Elastomers
 - applications of, A-3t–A-4t
 - elastic moduli of, 68
 - as family, 15f
 - microstructure of, 465–466, 466f
 - processing of, 494–495
 - properties of, 17
- Electrical conductivity, 309–310, 316–318
- Electrical insulation, 329–330
- Electrical power transmission, 328
- Electrical properties, 7–8, 314–316
- Electrical resistance, 318–321
- Electrical resistivity, GL2-35t, 309–310, 309f, 315
- Electric capacitors, 310–311
- Electric field, 310–311
- Electro luminescence, 379–380
- Electromagnetic radiation, 366–371
- Electromagnetic spectrum, 367f
- Electromagnetic wave, 373f
- Electromagnets, 355–356, 357t
- Electron lenses, 355–356
- Electroplating, 413f
- Electrostriction, 313–314
- Elongation, 114
- Embodied energy, GL2-6, GL2-35t
- Embodied energy charts, GL2-7–GL2-8, GL2-13f–GL2-14f, GL2-17f
- Embrittlement, 180, 180f
- Enameling, 413f
- End-of-life potential, GL2-3
- Endurance limit, 191, 193f, 197–198
- Energy
 - cohesive, 65–66
 - creep activation, 277–278
 - demands of products, GL2-7–GL2-21
 - elastic, 55
 - embodied, GL2-6–GL2-8, GL2-35t
 - exchange, 351
 - Gibbs free, 468
 - internal, 468
 - life-cycle and, GL2-5
 - processing, GL2-3
 - product, 354
 - release in fracture, 170–172, 171f
 - self-diffusion, 284
 - surface, 170–172, 176–177, 177f
- Energy-limited design, 208–209, 209f
- Engines
 - con-rods in, 215–216, 216f
 - fuel injectors in, 333–334, 334f
- Entropy, 469
- Equilibrium
 - in alloys, GL2-5–GL2-6
 - solidification, GL2-36–GL2-48
 - thermodynamic, 469
- Equipment, capital cost of, 440
- Eutectic point, GL2-9–GL2-10, GL2-25f, GL2-28f
- Eutectic reaction, GL2-41
- Eutectic solidification, GL2-41–GL2-43
- Eutectoid point, GL2-23, GL2-25f, GL2-28f
- Eutectoid reaction, GL2-50–GL2-52
- Exchange energy, 351
- Exchangers, heat, 262–263
- Face-centered cubic atom packing, GL1-2–GL1-3, GL1-3f, GL1-3t, 59–60, 60f
- Fail-safe design, 212–215
- Faraday, Michael, 310
- Fatigue
 - compressive stress and, 200–201
 - conditions for, 189–190
 - corrosion, 403
 - in cracked components, 195–196
 - crack growth and, 195–196, 196f, 199–200, 219–220
 - damage, 199–200
 - displacement-limited design and, 209–210, 209f
 - energy-limited design and, 208–209, 209f
 - high-cycle, 190–192
 - initiation-controlled, 190
 - limit, 191, 193f, 197–198
 - load-limited design and, 207–208, 209f
 - low-cycle, 190, 193
 - material choice and, 200–201
 - propagation-controlled, 190
 - repetition and, 188
 - resistance to, 200–201, 215–216
 - strength and, 200
- Fermi, Enrico, 318, 374
- Fermi level, 318, 374
- Ferri-magnetism, 351–352, 351f
- Ferrites, 342, 345
- Ferro-electric actuation, 333–334
- Ferro-electric coefficient, 333
- Ferro-electric materials, 314, 326–327, 326f

- Ferro-magnetic materials, 345
- Ferro-magnetism, 351, 351f
- Ferrous alloys, 488–493, 489f–490f
- Ferrous metals, A-2t
- Fibers, optical, 380
- Field
 - coercive, 327, 346
 - electric, 310–311
 - magnetic, 342–345
- Field-emission electron gun, 318
- Field quantity, 287
- Flame retardants, 394
- Flame spraying, 413f
- Flammability, 387–388, 393–394
- Flashover, 393–394
- Flexural hinges, 156–157
- Flexural rigidity, 85, 86f
- Fluid trapping, 406–411, 409f
- Fluorescence, 379–380
- Fluorescent whitening agents, 389
- Fluorite structure, GL1-15, GL1-15f, GL1-15t
- Flux density, 343
- Flux lines, 343f–344f
- Flywheels, 147–148, 147f
- Foams, 72, 498
- Forensic fracture mechanics, 211–212
- Fourier, Baron Jean Baptiste Joseph, 247
- Fracture-enabling design, 220–222
- Fracture mechanics, 167–174, 211–212
- Fracture-safe design, 207–211
- Fracture toughness, 5f, A-13t–A-14t, 167–170.
 - see also* toughness
 - of ceramics, 16
 - definition of, 4
 - measurement of, 169f
- Fracture toughness-modulus chart, 174–175, 175f
- Fracture toughness-strength chart, 175–176, 176f
- Free energy of oxidation, 389
- Free-radicals, 394
- Free volume, 287
- Fresh water, 399–402
- Fresnel, Augustin Jean, 370
- Fresnel's construction, 370–371, 371f
- Friction
 - bearings and, 234–235
 - in brakes, 237–238
 - coefficient of, 228, 230
 - lubrication and, 235–236, 235f
 - materials for managing, 234–239
 - physics of, 232–233
- Fuel injectors, 333–334, 334f
- Fuels, 396t–397t, 407t–408t, 415t
- Fusion welding, GL2-46–GL2-48
- Galvanic attack, 402–403, 406–411, 409f
- Galvanizing, hot dip, 413f
- Gas phase reaction, 393
- Gibbs, Josiah Willard, 468
- Gibbs free energy, 468
- Glasses
 - applications of, A-4t–A-5t
 - atom packing in, 62–63, 63f
 - corrosion resistance in, 404t–405t
 - as family, 15f
 - fracture in, 177, 178f
 - microstructure of, 464–465, 465f
 - processing of, 493
 - properties of, 16–17
- Glass temperature, A-5t–A-6t, 244
- Goodman's rule, 193–194
- Graded joint, 258, 259f
- Gradients, thermal, 259–262
- Grain boundaries, 121–122
- Grain boundary hardening, 132–133
- Grain refinement, GL2-52
- Grains, 121–122
- Grain-size hardening, 126
- Green design, GL2-10–GL2-14
- Ground state, 283–284
- Growth, in phase transformation, 476–477, 476f, 480f
- Halite structure, GL1-13–GL1-14, GL1-14f
- Hardening
 - grain boundary, 132–133
 - grain-size, 126
 - laser, 488f
 - precipitation, 126, 134t, 484–485
 - solid solution, 126
 - solution, 128–130, 129f, 134t
 - transformation, 488, 488f
 - work, 112, 126, 131–132, 134t, 321
- Hard magnetic devices, 357–358, 358t
- Hard magnets, 347–348, 347f
- Hardness scales, 116f
- Hardness test, 115, 115f
- Headlights, 380

- Heat, specific, 245
- Heat capacity, 5–6, 245, 245f, 251, 256–257, 264–265
- Heaters, 264–265, 265f
- Heat exchangers, 262–263
- Heating, microwave, 330–331
- Heat sinks, 40–41, 330f
- Heat treatment
 - of carbon steels, GL2-60–GL2-64
 - of metals, 484–485, 484f
- Hertz, Heinrich Rudolph, 148
- HF transformer cores, 41
- High-cycle fatigue, 190–192
- High-temperature pipework, 295–296
- Hindered amine stabilisers, 394–395
- Hinge
 - flexural, 156–157
 - plastic, 141f, 143–144
 - torsional, 156–157
- Homogenisation, 481
- Hooke, Robert, 52
- Hooke's law, 52
- Hot dip galvanizing, 413f
- Hot tearing, 428
- Hybrids
 - classes of, 498f
 - as family, 15f
 - historic, 3f
 - making, 496–499
 - prehistoric, 3f
 - properties of, 17
- Hydrodynamic lubrication, 235–236
- Hydrogen standard, 400
- Hydrolysis reaction, 401
- Hydrostatic pressure, 51
- Hypo-eutectoid steels, GL2-4–GL2-5

- Ideal strength, 119–120, 119f–120f
- Imaging, pyro-electric, 332–333, 333f
- Impact test, 168f
- Impure water, 399–402
- Index of refraction, 369–370
- Induction, magnetic, 342–343, 344f
- Information storage, 358t, 359–360, 359f
- Initial elastic creep, 276–277
- Initial magnetization curve, 346
- Initiation-controlled fatigue, 190
- Injection molding, 25f
- Ink-jet printers, 332, 332f

- Inoculants, 481
- Insulation, 263–264
 - electrical, 329–330
 - thermal, 264f
- Intensity, stress, 167–170
- Intergranular corrosion, 402–403
- Intermediate phases, GL2-16–GL2-21, GL2-17f
- Internal energy, 468
- Internal reflection, 369f, 370, 380
- Interstitial solid solution, 120–121
- Interstitial space, GL1-6–GL1-7
- Ionic conduction, 317–318
- Ionization, 399f
- Ions, in solution, 398–399
- Iron, cast, 489–490, 489f–490f
- Iron-carbon diagram, GL2-23–GL2-26, GL2-24f

- Joining
 - of metals, 485–488, 487f
 - physical limits in, 436–437
 - as process, 19f
- Joint(s)
 - geometry of, 435–436, 435f
 - graded, 258, 259f
 - manufacturing constraints and, 436
 - mode of loading for, 435–436, 436f
 - secondary functionalities and, 436
- Joule, James, 170, 245
- Judicious design, 403

- Kelvin, Lord, 244
- Ketones, 396t–397t, 407t–408t, 415t
- Kinetic constant
 - linear, 390
 - parabolic, 390

- Laminates, 499
- Laminating, 355–356
- Laser hardening, 488f
- Latent heat, solidification and, GL2-36
- Lattice resistance, 126
- Leak-before-break criterion, 213
- Lenses
 - electron, 355–356
 - optical, 380
- Life-cycle, material, GL2-5, GL2-9f
- Light stabilizers, 389
- Limiting oxygen index, 388, 389t
- Limits, to size, 427–429

- Linear kinetic constant, 390
- Linear temperature dependence, 274
- Linear thermal expansion coefficient, 245–246, 246f
- Line tension, 125–126
- Liquid(s)
 - diffusion in, 287
 - environments, 396t–397t
- Load-limited design, 207–208, 209f
- Lord Kelvin, 244
- Lorentz, Hendrik Antoon, 352
- Lorentz force, 352–353
- Loss, dielectric, 322–323
- Loss coefficient, 188–189
- Loss factor, dielectric, 308, 312–313, 313f, 316
- Loss tangent, 312–313
- Loudspeakers, 357t
- Low-cycle fatigue, 190, 193
- Lubrication, 235–236, 235f
- Luminescence, electro, 379–380

- Magnetic anisotropy, 354
- Magnetic dipole, 350f
- Magnetic fields, 342–345
- Magnetic induction, 342–343, 344f
- Magnetic measurement, 345–348
- Magnetic moment, 343f
- Magnetic properties, 7–8, 342–350
- Magnetic susceptibility, 344–345
- Magnetization, 344–345
- Magnetization curve, initial, 346
- Magnets
 - hard, 347–348, 347f
 - soft, 347–348, 347f
- Maintenance, corrosion and, 416
- Manhattan Project, 318
- Martensite, GL2-60
- Material cost, minimization of, 97, 155
- Material damping, 198–199
- Materials
 - classifying, 14–17, 15f–16f
 - compatibility of, 435
 - computer-aided information management for, 23
 - consumption of, GL2-3–GL2-6, GL2-7f
 - for creep resistance, 293–294
 - design and, 33–35
 - ferro-electric, 314, 326–327, 326f
 - ferro-magnetic, 345
 - historical development of, 3f
 - life-cycle of, GL2-5, GL2-9f
 - magnetic fields in, 344–345
 - for managing friction, 234–239
 - microstructure of, 463–466
 - piezo-electric, 314, 324–325, 325f
 - process and, 17
 - properties of, 4–8
 - property charts of, 14, 21–22, 57–59
 - pyro-electric, 314, 325–326
 - radiation and, 366–371
 - shape-memory, 266
 - super-elastic, 266
- Maximum bearing pressure, 230–231
- Maximum local stress, 150
- Maximum service temperature, 4, 6f, 244, 274
- Maximum service temperature chart, 280, 281f
- Mean free path, 254–255
- Mechanical loss coefficient, 188–189, 198–199
- Mechanical properties, 4, 5f
- Melting point chart, 280
- Melting temperature, A-5t–A-6t, GL2-7, 244
- Memory, shape, 266
- Metal(s)
 - atom packing in, 59
 - casting of, 480–481, 480f
 - corrosion resistance in, 404t–405t
 - creep and, 292–293
 - defects in, 120–122
 - deformation processing of, 482–484
 - density of, A-7t–A-8t
 - dielectric constant in, A-17t–A-18t
 - as family, 15f
 - ferrous, A-2t
 - fracture toughness in, A-13t–A-14t
 - heat treatment of, 484–485, 484f
 - historic, 3f
 - joining of, 485–488, 487f
 - melting points of, A-5t–A-6t
 - microstructure of, 463–464, 464f
 - nonferrous, A-2t
 - opacity of, 374–375, 375f
 - prehistoric, 3f
 - processing of, 479–493
 - properties of, 16
 - reduction potentials of, 400, 400f
 - resistivity in, A-17t–A-18t
 - rolling of, 159–160, 159f
 - strengthening of, 127–128, 127f
 - strength-toughness tradeoff in, 180–181

- stress-strain curve for, 113f
- tensile strength in, A-11t–A-12t
- thermal conductivity of, A-15t–A-16t
- thermal expansion of, A-15t–A-16t
- yield strength in, A-11t–A-12t
- Young's modulus in, A-9t–A-10t
- Metal flame spraying, 413f
- Metallic coatings, 411–412, 412t
- Michelson, Albert A., 366
- Microchip heat sinks, 40–41
- Microchips, 330
- Microphones, 357t
- Microscopes, 380
- Microstructure, 460
 - of ceramics, 464–465, 465f
 - of elastomers, 465–466, 466f
 - evolution, GL2-34–GL2-35, 466–469
 - of glasses, 464–465, 465f
 - of materials, 463–466
 - of metals, 463–464, 464f
 - phase and, 467–468
 - of polymers, 465–466, 466f
- Microwave heating, 330–331
- Miller indices, GL1-8, GL1-9f, GL1-10–GL1-11, GL1-11f
- Miner's rule, 194–195
- Minimum service temperature, 244, 274
- Mode of loading, 48–50, 49f, 82
- Mode 1 stress intensity factor, 169
- Modulus-density chart, 57, 58f
- Modulus-relative cost chart, 57–59, 58f
- Modulus-strength chart, 118–119
- Moment, magnetic, 343f
- Moment-field interaction, 343f
- Monkman-Grant constant, 279
- Monkman-Grant law, 279

- Net flux model, 254–255
- Neutral axis, 84–87
- Nitriding, 239
- Nominal stress, 150
- Nonferrous metals, A-2t
- Nonlinear temperature dependence, 274
- Nucleation, 476–477, 476f, 480–481, 480f

- Ohm, George Simon, 309
- Oils, 395, 396t–397t, 407t–408t, 415t
- Opacity, 366–367
- Optical design, 380
- Optical fibers, 380
- Optical microscopy, GL2-35t
- Optical profilometry, 432–433
- Optical properties, 7–8, 371–372
- Organic solvents, 395, 396t–397t, 407t–408t, 415t
- Original design, 30–31
- Orowan, Egon, 122
- Oven, microwave, 330–331
- Oxidation
 - definition of, 387
 - flammability and, 387–388
 - free energy of, 389
 - measurement of, 387, 388f
 - mechanisms, 389–392
 - resistance to, 393–395
- Oxygen index, 388, 389t

- Padding, 104–105
- Paint spraying, 413f
- Panel
 - design of, 91f, 92–93, 93t, 152–153, 153t
 - sandwich, 499
 - yielding of, 142–145
- Parabolic kinetic constant, 390
- Paramagnetism, 351, 351f
- Pauli, Wolfgang Joseph, 317
- Pauli exclusion principle, 317–318
- Pearlite, GL2-51–GL2-52
- Peritectic point, GL2-24–GL2-25, GL2-28f
- Peritectoid point, GL2-27–GL2-28, GL2-28f
- Permeability of vacuum, 343
- Permittivity of dielectric, 311
- PH, 398–399, 399f
- Phase boundary, GL2-7
- Phase change, 265–266
- Phase compositions, GL2-10–GL2-14
- Phase diagrams, GL2-6–GL2-21, 467–473, 470f–471f
- Phase intermediates, GL2-16–GL2-21, GL2-17f
- Phase proportions, GL2-14–GL2-16
- Phase quantification, GL2-35t
- Phase reaction, GL2-39
- Phases, GL2-4–GL2-5
- Phase thermodynamics, 468–469
- Phase transformations, GL2-34–GL2-35, 467–468, 473–476, 473f
- Phonons, 254–255, 254f
- Phosphorescence, 379–380
- Photo-conductivity, 380

- Photodegradation, 389, 394–395
- Photons, 373–374
- Piezo-electric actuation, 332, 332f
- Piezo-electric materials, 314, 324–325, 325f
- Pinning force, 128
- Pipework, high-temperature, 295–296
- Pitting corrosion, 402–403
- Planck, Max Karl Ernst, 374
- Planck's constant, 374
- Plane bearings, 236–237
- Planes, in crystal geometry, GL1-8–GL1-9
- Plastic flow, 122–124, 126–127
- Plastic hinge, 141f, 143–144
- Plastic section modulus, 145f
- Plastic strain, 114
- Plastic zone, crack tip, 172–174, 172f
- Plate
 - buckling of, 89, 89f
 - vibrating, 89–90, 90f
- POH, 399f
- Point defects, 120–121
- Poisson, Siméon Denis, 54
- Poisson's ratio, 54
- Polarization, 311, 326
- Polar second moment of area, 145–147
- Polycrystallinity, 287–288
- Polymer(s)
 - applications of, A-3t–A-4t
 - atom packing in, 63–64, 64f–65f
 - blending of, 135, 181
 - burning of, 393–394
 - corrosion resistance in, 404t–405t
 - creep in, 290–292
 - for creep resistance, 293
 - cross-linking of, 135
 - crystals, GL1-16–GL1-19, GL1-16f–GL1-17f, GL1-16t
 - density of, A-7t–A-8t
 - dielectric constant in, A-17t–A-18t
 - drawing of, 135
 - as family, 15f
 - fibers, 495–496
 - fracture toughness in, A-13t–A-14t
 - historic, 3f
 - microstructure of, 465–466, 466f
 - molding of, 495, 496f
 - plastic flow in, 126–127
 - prehistoric, 3f
 - processing of, 494–495, 496f
 - properties of, 17
 - reinforcement of, 181
 - resistivity in, A-17t–A-18t
 - rheology, 292
 - strengthening of, 134–135
 - strength-toughness tradeoff in, 181–182
 - stress-strain curve for, 113f
 - tensile strength in, A-11t–A-12t
 - thermal conductivity of, A-15t–A-16t
 - thermal expansion of, A-15t–A-16t
 - thermoplastic, A-3t–A-4t
 - thermoset, A-4t–A-5t
 - yield strength in, A-11t–A-12t, 112–114
 - Young's modulus in, A-9t–A-10t
- Polymeric coatings, 411–412, 412t
- Polymer powder spraying, 413f
- Powder processing, 494, 494f
- Powder spraying, 413f
- Power factor, 313
- Power-law creep, 276–277, 288–289, 296–298
- Power transmission, electrical, 328
- Precipitate coarsening, 474–475
- Precipitate strengthening, 130–131
- Precipitation hardening, 126, 134t, 484–485
- Precipitation reactions, GL2-48–GL2-55
- Preferred material choices, 387, 407t–408t
- Prehistoric materials, 3f
- Pressure vessels, 211–212
- Primary creep, 276–277
- Printers, ink-jet, 332, 332f
- Process(es)
 - with ceramics, 493
 - classification of, 18–20, 18f
 - computer-aided information management, 23
 - cost estimates in, 438–441
 - definition of, 17
 - design and, 33–35
 - documentation and, 424
 - with elastomers, 494–495
 - with glasses, 493
 - joining and, 434–437
 - joining as, 19f
 - material compatibility and, 424–426
 - materials and, 17
 - with metals, 479–493
 - with polymers, 494–495, 496f
 - properties and, 20–21, 461–463
 - screening and, 424
 - selection of, in design, 422–424

- shape and, 430–432
- shaping as, 19f
- surface treatment as, 19f, 437–438
- translation and, 422–423
- tree, 17–20
- Processing energy, GL2-3
- Product, energy, 354
- Profile of properties, 14
- Proof stress, 112
- Propagation-controlled fatigue, 190
- Properties
 - of ceramics, 16
 - chemical, 8, 9f
 - in classification, 16
 - design-limiting, 8
 - dielectric, 310–314
 - of elastomers, 17
 - electrical, 7–8, 314–316
 - of glasses, 16–17
 - of hybrids, 17
 - magnetic, 7–8, 342–350
 - of materials, 4–8
 - mechanical, 4
 - of metals, 16
 - optical, 7–8, 371–372
 - of polymers, 17
 - processes and, 20–21, 461–463
 - profile of, 14
 - thermal, 4–7, 244–248
 - transport, 302
 - tribological, 228–229
- Protective coatings, 403, 411–414
- Pyro-electric materials, 314, 325–326
- Pyro-electric thermal imaging, 332–333, 333f
- Pyrolyzation, 393

- Quench cracking, GL2-61–GL2-62
- Quenching, GL2-56

- Radiation, electromagnetic, 366–371
- Radiator, 450–451, 450f, 451t
- Radomes, 331–332, 331f
- Rails, 218–219, 218f
- Random substitutional solid solution, 128
- Ranking, 35, 37–38, 98–99, 98f, 424
- Read/write head, 359f
- Recovery, in annealing, 482, 483f
- Recrystallization, in annealing, 482, 483f
- Recycling, GL2-6, GL2-11f, GL2-35t

- Redesign, 31–32
- Reduction potential, 400, 400f
- Redundant work, 159–160
- Reflection, 367, 368f–369f, 380
- Reflectivity, 366
- Reflectivity-refractive index chart, 371–372, 373f
- Refraction, 369f, 380
- Refractive index-dielectric constant chart, 371, 372f
- Reinforcement, 135, 181
- Relative density, 73
- Relative permittivity, 308
- Relaxation, creep, 301–302, 301f
- Remanence, 8, 346
- Remanence-coercive field chart, 348–349, 348f
- Remanent polarization, 327
- Repetition, fatigue and, 188
- Replacement, corrosion and, 416
- Residual stress, 260–261
- Resistance, electrical, 318–321
- Resistivity, A-17t–A-18t
- Resistivity, electrical, 309–310, 309f, 315
- Resonance, 105, 188–189
- Reynolds, Osborne, 235
- Rheology, polymer, 292
- Rigidity
 - flexural, 85, 86f
 - torsional, 88–89
- Rocksalt structure, GL1-13–GL1-14, GL1-14f
- Rolling, 159–160, 159f, 429–430
- Rolling bearings, 237, 237f
- Roughness, 432–434, 432t
- Rule of cumulative damage, 194–195
- Rule of mixtures, 69

- Salt water, 415t
- Sandwich panels, 499
- Saturation magnetization, 8, 345f, 346
- Saturation magnetization-susceptibility chart, 349–350, 349f
- Saturation polarization, 326, 327f
- Scanning electron microscopy, GL2-35t
- Scattering, of light, 377–378, 378f
- Scattering centers, 319
- Screening, 35, 37, 97, 424
- Screw dislocation, 123, 124f
- Secondary creep, 276–277
- Section thickness, 426–429
- Segregation, chemical, GL2-45–GL2-48, 180, 180f
- Selective corrosion, 402–403

I-12 Index

- Self-diffusion, 284
- Self-generated coatings, 411
- Sensing, thermal, 259
- Service temperature
 - maximum, 4, 6f, 244, 274
 - minimum, 244, 274
- Shafts
 - torsion of, 88–89, 88f, 146f
 - yielding of, 145–147
- Shape factor, 95, 96t, 430–432
- Shape-memory, 266
- Shaping
 - costs, 438–441
 - as process, 19f
- Shear banding, 126f, 127
- Shear modulus, 54
- Shock resistance, thermal, 262
- Shot peening, 200–201, 201f
- Size, limits to, 427–429
- Sliding bearings, 235–236, 236f
- Slip directions, 124
- Slip planes, 124, 125f
- S-N curve, 190–192
- Snell, Willebrord, 369
- Snell's law, 369–370
- Soft magnetic devices, 355–356, 357t
- Soft magnets, 347–348, 347f
- Soils, 396t–397t, 407t–408t, 415t
- Solenoid, 343f
- Solidification
 - equilibrium, GL2-36–GL2-48
 - eutectic, GL2-41–GL2-43
 - latent heat release on, GL2-36
- Solid lubricants, 236
- Solid solution, GL2-4, 69
- Solid solution hardening, 126
- Solubility limits, GL2-8–GL2-9, GL2-9f, GL2-11f
- Solution hardening, 128–130, 129f, 134t
- Solvents, organic, 395, 396t–397t, 407t–408t, 415t
- Space, interstitial, GL1-6–GL1-7
- Spark plug insulator, 445–446, 445f, 446t
- Specific heat, 245
- Specific stiffness, 92
- Specific strength, 152
- Specific wear rate, 229
- Spectrum, electromagnetic, 367f
- Specular reflection, 367, 368f
- Spinning disks, 147–148, 147f
- Springs, 158–159, 158f, 158t
- Stainless steel, 491–492
- Standard reduction potential, 400, 400f
- Steady-state creep, 276–277
- Stealth technology, 331
- Steel, GL2-50, 490–492
- Storage heaters, 264–265, 265f
- Strain, 52
- Strength
 - ideal, 119–120, 119f–120f
 - manipulation of, 127–135
 - specific, 152
 - toughness tradeoff, 180–182
- Strength-density chart, 116–118, 117f, 153f
- Stress, 50
 - concentration factor, 150
 - concentrations, 149–151, 150f
 - contact, 148–149, 149f
 - corrosion cracking, 403
 - intensity, 167–170, 208f
 - intensity factor, 206–207
 - maximum local, 150
 - nominal, 150
 - residual, 260–261
 - thermal, 257–259, 258f
- Stress relaxation, 301f
- Stress-strain curves, 52, 53f, 119f
- Structural materials cost, 102–104, 103f, 103t
- Structured data, 23
- Stuart, James, 1f, 2
- Substitutional solid solution, 120–121
- Super-alloys, 293
- Supercapacitor, 312
- Super-elastic materials, 266
- Surface energy, 170–172, 176–177, 177f
- Surfaces
 - diffuse, 367
 - at magnification, 233f
 - in physics of friction, 232–234
 - specular, 367, 368f
 - treatment processes for, 437–438
 - tribological properties of, 228–229
- Surface stress, compressive, 200–201, 201f
- Surface treatment, as process, 19f
- Susceptibility, magnetic, 344–345
- Tabor, David, 232
- Taylor, G.I., 122
- Tear test, 168f

- Telescopes, 380
- Temperature
- creep and, 276
 - Curie, 326–327
 - dependence, 274, 275f
 - glass, A-5t–A-6t, 244
 - gradient, 262
 - maximum service, 4, 6f, 244, 274
 - melting, A-5t–A-6t, GL2-7, 244
 - minimum service, 244, 274
- Tensile strength, 4, A-11t–A-12t
- Tensile stress intensity, 206
- Tesla, 343
- Texture, crystal, 484
- Theophrastus, 325
- Thermal activation, 302
- Thermal actuation, 259
- Thermal barrier coatings, 298–299
- Thermal buffers, 265–266
- Thermal conductivity, 5–6, 6f, A-15t–A-16t, 247–250, 247f–249f, 254–257, 315
- Thermal diffusivity, 6, 247–250, 249f, 261
- Thermal exchange, 262–263
- Thermal expansion, 5, 6f, A-15t–A-16t, 248–257, 248f, 253f
- Thermal expansion coefficient, 245–246, 246f, 258f
- Thermal gradients, 259–262
- Thermal history, 461–463
- Thermal imaging, 332–333, 333f
- Thermal insulation, 263–264, 264f
- Thermal properties, 4–7, 244–248
- Thermal property manipulation, 255–257
- Thermal sensing, 259
- Thermal shock resistance, 262
- Thermal stress management, 257–259, 258f
- Thermal walls, 263–264, 264f
- Thermoplastic polymers, A-3t–A-4t
- Thermoset polymers, A-4t–A-5t
- Thompson, Benjamin, 244
- Thompson, William, 244
- Tie-rod, 91–92, 91f, 91t, 151–152, 152t
- Ties, yielding of, 142
- Time-temperature-transformation diagrams, 477–478, 478f–479f
- Tolerance
- for cracks, 219–220
 - damage, 174, 174t
 - process and, 432–434
- Torsion, of shafts, 88–89, 88f, 146f
- Torsional hinge, 156–157
- Torsional rigidity, 88–89
- Total internal reflection, 369f, 370, 380
- Tough fracture, 177–179, 178f
- Toughness. *see also* fracture toughness
- definition of, 166
 - material property charts for, 174–176
 - origins of, 176–180
 - strength tradeoff, 180–182
 - tests for, 167, 168f
- Trains, 218–219, 218f
- Transformation hardening, 488, 488f
- Transformer cores, 41
- Transformers, 355–356, 357t
- Transient heat flow, 261–262
- Translation, 35–37, 39–41, 422–423
- Translucence, 366–367
- Transmission
- of electrical power, 328
 - of light, 368
- Transmission electron microscopy, GL2-35t
- Transmittability, 366
- Transparency, 367
- Transport properties, 302
- Trapped fluids, 406–411, 409f
- Tribological properties, 228–229
- Turbine blades, 296–298, 297f
- Ultraviolet absorbers, 394–395
- Uniform attack, 406–411
- Unit cell, 60–62, 61f
- Unstructured data, 23
- Vacuum, permeability of, 343
- Vibrating beams and plates, 89–90, 90f
- Vibration, resonance and, 105, 188–189
- Vickers test, 115, 115f
- Visco-elastic solids, 291
- Viscous flow, 274–276
- Volta, Alessandro Giuseppe Antonio Anastasio, 309
- Volume
- free, 287
 - minimization of, 155
- Walls
- domain, 326–327, 352
 - thermal, 263–264, 264f

I-14 Index

Water

- corrosion and, 395
- environments, 396t–397t
- fresh, 399–402, 415t
- impure, 399–402
- preferred materials-in, 407t–408t
- salt, 415t

Watt, James, 247

Wear

- abrasive, 234, 234f
 - adhesive, 234, 234f
 - bearings and, 234–235
 - materials for managing, 234–239
 - physics of, 232–233
 - reduction of, 238–239
- Wear constant, 229
- Wear rate, 229
- Wear rate-hardness chart, 230–231
- Welding, fusion, GL2-46–GL2-48

Wöhler, August, 188

Work, redundant, 159–160

Work function, 318

Work hardening, 112, 126, 131–132, 134t, 321

X-ray diffraction, GL2-35t

Yielding

- of beams, 142–145, 143f
- of columns, 142
- of panels, 142–145
- of shafts, 145–147
- of ties, 142

Yield strain, 118–119

Yield strength, 4, 5f, A-11t–A-12t, 112, 133–134

York Minster, 308

Young, Thomas, 52

Young's modulus, A-9t–A-10t, 52, 56