

INDEX

- Abrasive, 286, 472
 Absorption, 472
 $A_mB_nX_p$ compounds, 266, 472
 Acceleration of gravity, 466
 Acceptor, 155
 Acceptor level, 155, 472
 Acceptor saturation, 156, 472
 AC SPARK PLUG, 259
 Activation energy, 123, 472
 Addition polymer, 45, 214, 483
 Addition polymerization, 45, 214, 219, 472
 Additive properties, 349, 472
 Adsorption, 472
 Age-hardening, 378, 472
 and corrosion, 420
 Agglomerated material, 441, 472
 Aggregate, 443, 472
 AHRENS, 469
 AISI-SAE nomenclature, 330
 steel, 330, 472
 Allotropism, 77, 472
 ALCOA, 369, 376
 Alloys, 101, 169, 472
 commercial, 314
 properties of, 169
 single-phase, 169
 Alloy retardation, 368, 472
 Alloying element, 101, 169, 472
 Amorphous, 114, 272, 472
 amu, 29, 466, 472
 Analysis of phases, 307, 482
 ANDERSON, W. A., 369
 Angle, bond, 42
 Angles between directions, 81
 Angstrom, 466
 Anion, 33, 59, 472
 Anisotropic, 119, 178, 459, 472
 Annealing, 192, 374, 375, 390, 472
 full, 375
 process, 374, 483
 Annealing point, 289, 472
 Anode, 411, 472
 sacrificial, 433, 484
 Anodize, 427, 472
 APF, 71, 472
 Area, reduction of, 7, 8, 484
 ARGON, A. S., 195
 ARNOLD ENGINEERING, 4
 Arrhenius equation, 123, 128, 150, 368, 372, 472
 Asbestos, 270, 472
 ASKAY, I. A., 305
 ASKILL, J., 127
 Asphalt, 441
 ASTM grain-size, 112, 472
 Atactic, 226, 472
 Atomic disorder, 78
 Atomic mass unit (amu), 29, 466, 472
 Atomic movements, 123
 Atomic number, 29, 468, 472
 Atomic packing factor, 71, 472
 Atomic rearrangements, 123
 Atomic vibrations, 118
 Atomic weight, 29, 468, 472
 Atoms, 29
 Austempering, 393, 472
 Austenite, 320, 472
 decomposition, 326, 344, 382, 386, 473
 grain-size, 386, 389, 473
 Austenization, 375, 377, 473
 Avogadro's number, 29, 466, 473
 AX compound, 260, 473
 AX structure, 260
 CaF₂, 264
 CsCl, 261, 262, 473
 NaCl, 261, 262, 473
 NiAs, 262, 263
 noncubic, 263
 ZnS, 262, 473
 A_mX_p compounds, 264
 A_mX_p structure, 264, 473
 Axis (crystal), 68, 473
 Bainite, 393, 473
 Balsa, 458
 Band, conduction, 145, 475
 energy, 143, 477
 valence, 145, 487
 Base, 160, 473
 BATTELLE, 199
 BCC, 72, 473
 BHN, 9
 Bifunctional, 217, 219, 473
 BINDER, W. O., 432
 BOAS, W., 179
 Body-centered cubic (bcc), 72, 473
 Bohr magneton, 282, 473
 Boltzmann's constant, 120, 466, 473
 Bond, angle of, 42, 473
 covalent, 36, 475
 energy, 41, 49, 473
 intermolecular, 40
 intramolecular, 40
 ionic, 34, 479
 length, 41, 473
 metallic, 38, 480
 primary, 34, 483
 rotation, 216
 secondary, 45, 484
 Bonding, chemical, 26
 Bonding forces, 34
 primary, 34
 secondary, 45
Book of Stainless Steel, 431
 Boundary, 110, 473
 grain, 110, 478
 phase, 117, 482
 BRAGG, W., 183
 Bragg's Law, 88, 473
 Branching, 233, 247, 473
 Brass, 78, 101, 169, 170, 190, 470, 473
 beta, 185
 Bravais lattices, 70, 473
 Brazing, 473
 Brick, 470
 Brine, 300
 Brittle, 6, 473
 Bronze, 102, 169, 470, 473
 * Bronze Age, *F*
 Bubble raft, 183
 Bulk density, 445, 476
 Bulk modulus, 178, 481
 Bulk volume, 445
 Buna-S, 223
 Burgers' vector, 108, 182, 473
 BURKE, J. E., 174, 176, 192
 Butadiene-type compound, 220, 473
 Byproduct, 223
 Calcination, 473
 Capacitance, 16
 Capacitor, 16, 244
 parallel-plate, 16
 Carbide, 320, 326, 473
 eutectoid, 328
 proeutectoid, 328
 sintered, 447
 Carbon steel, 328, 355, 396, 473
 Carburization, 128, 451, 452, 473
 Carrier, charge, 15, 139, 474
 negative-type, 149
 positive-type, 149
 Case, 451, 474
 Case hardening, 451, 452, 474
 Cast iron, 322, 470, 474
 Casting, 474
 Catalyst, 474
 Cathode, 411, 474
 reaction, 416, 474

* *F* refers to the Foreword. Italicized page numbers refer to glossary terms.

- Cation, 31, 59, 474
 C-curve, 320, 474
 Cell, composition, 418, 474
 concentration, 422, 474
 galvanic, 413, 418, 430, 434, 474
 oxidation, 423, 474
 stress, 421, 474
 unit, 69, 487
 Cellulose, 457, 474
 Cement, 446, 474
 hydraulic, 446, 474
 portland, 286, 446, 474
 Cementite, 321, 474
 Center-of-gravity method, 312, 474
 Ceramics, 58, 256, 470, 474
 CERNICA, J. N., 446
 Chain silicate, 269, 485
 Charge (electron), 16, 466, 476
 Charge density, 16, 242, 474
 Charge mobility, 149
 Charpy test, 9, 474
 Chemical bonding, 26
 Chemoluminescence, 153
 Chloroprene, 220
 CHRYSLER, 346
 CINCINNATI-MILACRON, 194
Cis, 227, 474
 Clay, 259, 270, 474
 Cleavage, 270, 474
 Close-packed, cubic, 74
 hexagonal, 75, 478
 Closed pores, 444, 483
 CN, 53, 260, 475
 Coercive field, electric, 281, 474
 magnetic, 284, 474
 COHEN, M., *F*
 Coherence, 88, 380
 Cold-working, 188, 193, 474
 Cold-anneal cycles, 193
 Collector, 160, 474
 Compact, 474
 Component, design, 461, 474
 phases, 117, 299, 303, 474
 Composition, eutectic, 301, 477
 eutectoid, 324, 331, 477
 phase, 307
 Compounds, 475
 $A_m B_n X_p$, 266, 472
 AX, 260, 473
 $A_m X_p$, 264
 butadiene-type, 220, 473
 multiple, 266
 nonstoichiometric, 105, 481
 solid solutions in, 104
 vinyl-type, 220
 Compressibility, 178
 Concentration cell, 422, 474
 Concentration gradients, 124
 Concrete, 17, 441, 445, 471, 475
 Conduction electron, 148, 475
 Conductivity, 15, 475
 electrical, 60, 139, 140, 241, 350, 476
 thermal, 14, 60, 350, 470, 487
 Conductor, metallic, 140, 144, 480
 Configuration, 475
 Conformation, 217, 475
 Constants, table of, 466
 Continuous cooling transformation, 387, 475
 Conversions, table of, 466
 Cooling rate, 398, 475
 critical, 387, 475
 Coordination number (CN), 53, 260, 475
 vs. radius ratios, 55
 Copolymer, 221, 475
 Core (heat-treating), 451, 475
 CORNING GLASS WORKS, 367, 452
 Corrosion, 408, 475
 control, 428
 current, 425
 current density, 424
 galvanic, 413
 grain boundary, 421
 polarization, 425
 rate, 424
 stress, 421
 Corrosion, causes and prevention, 420
Corrosion of Metals, 432
Corrosion in Action, 421
 COSMAT, *F*
 COTTRELL, A. H., 198
 Coulombic attractions, 34
 Coulombic force, 49, 475
 Covalent bond, 36, 475
 Creep, 195, 475
 mechanisms, 196
 rate, 196, 475
 steady, 196
 Cristobalite, 307
 Critical shear stress, 181, 475
 Cross-linking, 232, 475
 CRUME, G. O., 214
 Crystal, 67, 475
 cubic, 71
 direction, 80, 475
 form, 85
 hexagonal, 75
 imperfections in, 107
 lattice, 89, 475
 molecular (polymer), 227, 481
 plane, 83, 475
 structure, 468
 system, 68, 475
 Crystallinity, 67, 229, 475
 Crystallization, deformation, 236, 476
 CsCl structure, 78, 79, 261, 263, 473
 Cubic, body-centered (bcc), 72, 473
 face-centered (fcc), 73, 477
 simple, 71, 485
 Cubic close-packed, 74
 Cubic crystal, 71
 Cubic system, 67
 CULLITY, B. D., 89, 90
 Curie point, ferroelectric, 278, 281
 magnetic, 278, 475
 Current, 158, 412, 475
 density, 159, 424, 475
 Damage, radiation, 201, 483
 Decomposition of austenite, 326, 344, 382, 386, 472
 Defect, Frenkel, 107, 108, 478
 line, 108
 point, 107, 483
 Schottky, 107, 484
 Defect semiconductor, 156, 277, 484
 Defect structure, 105, 106, 475
 Deformation, 6
 elastic, 176, 475
 high-temperature, 195
 low-temperature, 187
 plastic, 180, 234, 475
 polycrystalline, 187, 195
 viscous, 235, 236, 288
 Deformation crystallization, 236, 476
 Degradation, 245, 476
 Degree of polymerization, 214, 476
 Delocalization, 37, 38, 140, 476
 Delta iron, 321
 Density, 350, 468
 apparent, 445, 476
 bulk, 445, 476
 linear, 81
 planar, 86
 true, 445, 476
 Density change, 16, 242
 Devices, semiconducting, 158
 Diagram, phase, 303, 482
 Diamond, 79, 145
 Diamond structure, 37
 Dielectric constant, 16, 241, 276, 476
 relative, 16, 242, 476
 Dielectric strength, 276, 476
 Dielectrics, 241, 275, 476
 Diffraction, 88, 476
 x-ray, 88, 476
 Diffraction analyses, 90

- Diffraction lines, 90
 Diffusion, 124, 476
 coefficient of, 124, 127, 476
 flux, 125, 478
 self, 484
 vs. temperature, 126, 127
 Diffusivity, thermal, 14, 487
 Dipole, 45, 243, 476
 induced, 45, 244, 479
 Dipole moment, 242
 Direction, crystal, 80, 475
 vs. elastic modulus, 178
 family of, 81, 477
 slip, 181, 485
 Dislocation, 108
 edge, 108, 476
 movements, 184
 screw, 108, 476
 Dispersed phase, 357, 476
Distortion of Metal Crystals, 181
 Domains, 280, 476
 Donor, 155
 exhaustion, 156, 476
 level, 155, 476
 DOUGLAS, S. D., 214
 DP, 214, 476
 Drawing, 476
 Drawn, hard-, 478
 Drift velocity, 15, 140, 476
 Ductility, 6, 7, 476
 vs. carbon content, 355

 Edge dislocation, 108, 476
 ELAM, C., 181
 Elastic deformation, 176, 475
 Elastic modulus, 6
 Elastic strain, 7, 486
 Elasticity, 6, 176, 476
 vs. direction, 178
 modulus of, 6, 59, 176, 236, 470, 481
 vs. temperature, 178, 236
 Elastomer, 235, 476
 Electric field, 15, 140, 242, 281, 476
 Electrical conductivity, 60, 139, 241, 350, 476
 Electrical resistivity, 139, 141, 476
 Electrochemical potential, 414, 476
 Electrode, hydrogen, 414, 479
 Electrode potential, 415
 Electroluminescence, 153
 Electrolyte, 411, 476
 Electron, 29
 conduction, 148, 475
 delocalized, 39, 140
 valence, 32, 39, 148, 487
 Electron charge, 16, 139, 466, 476
 Electron hole, 140, 149, 476
 Electron-hole pair, 151, 477

Electron Microstructure of Steel, 393
 Electron transport, 136
 Electron volt, 466
 Electronegativity, 33, 477
 Electronic repulsion, 49, 477
 Electroplating, 411, 477
 Elements, properties of, 468
Elements of Physical Metallurgy, 108, 178, 368, 369, 378, 395
Elements of X-ray Diffraction, 89, 90
 Elongation, 7, 477
 Emitter, 160
 Enamel, 429
 End-quench test, 395, 477
 Endurance limit, 200, 477
 vs. surface finish, 201
 Energy, activation, 123, 472
 bond, 143, 473
 dislocation, 109
 distribution, 120, 477
 free, 371
 gap, 145, 477
 ionization, 32
 interface, 371
 levels, 31, 39
 well, 50, 477
 Engineering materials, 470
 Entropy, 240
 Equiaxial, 175, 477
 Equicohesive temperature, 196, 477
 Equilibrium, chemical, 292, 477
 Equilibrium diagram, 303, 477
 Equivalent points, 69, 477
 ERICKSON, M. A., 201
 ERNST, H., 194
 Etching, 110
 Eutectic, 301
 composition, 301, 477
 reaction, 309, 477
 temperature, 301, 477
 Eutectoid, 323, 331
 composition, 324, 331, 477
 ferrite, 327, 347, 478
 reaction, 323, 343, 477
 shift, 330, 477
 steel, 329, 348, 357, 383, 388, 486
 temperature, 324, 331, 477
 Exhaustion, donor, 156, 474
 Expansion, coefficient, 12, 121, 477
 linear, 12
 vs. melting temperature, 119
 thermal, 12, 60, 118, 470, 487
 volume, 13
 Extrinsic semiconductor, 154, 484
 Face-centered cubic (fcc), 73, 477

 Family of directions, 81, 477
 Faraday, 411, 477
 Fatigue, 199, 477
 Fcc, 73, 477
 Feldspar, 272
 Ferrite, ceramics, 266, 477
 metals, 320, 478
 Ferrite, eutectoid, 327, 347, 478
 proeutectoid, 327, 347, 478
 Ferroelectric, 280, 478
 Ferromagnetic, 284, 478
 Ferrosipinel, 266, 283
 Fiber-reinforced plastics, 454, 478
 Fiber reinforcement, 455
 Fick's First Law, 125, 478
 Field, electric, 140
 Filler, 353
 Firing, 478
 Flame hardening, 453, 478
 FLETCHER, J. F., 204
 Flow, viscous, 239
 Fluid, 114
 Fluidity, 289, 478
 Fluorescence, 154, 478
 Flux, diffusion, 125, 478
 Form, 85, 478
 Forsterite, 268, 272
 Fracture, brittle, 197, 478
 ductile, 196, 478
 Free energy, 371
 Free radical, 219
 Free space, 228
 Freezing range, 305
 Frenkel defect, 107, 108, 478
 FRITZER, G. R., 72, 73
 FRP, 454, 478
 FULRATH, R. M., 449
 Functionality, 217, 478
Fundamentals of Reinforced Concrete, 446
 Fusion, heat of, 12, 115, 478

 Gage length, 7, 478
 Galvanic cell, 413, 418, 431, 434, 478
 Galvanic protection, 433, 478
 Galvanic series, 415, 430
 Galvanization, 418, 433, 478
 Gap, energy, 145, 147, 477
 GARDNER, R. E., 111
 GARWOOD, M. F., 201
 Gas constant, 466
 GEHMAN, S. D., 236
 GENERAL ELECTRIC, F, 174, 192, 248, 447
 GENERAL MOTORS, 348, 393
 Glass, 116, 272, 471, 478
 ancient, 367
 E-, 276
 plate, 471
 silica, 471

- soda-lime, 116, 272, 485
 tempered, 288, 487
 transition temperature, 116,
 229, 235, 280, 478
 Vycor, 471
 volume changes, 116
 wool, 471
- GOLIBER, E., 447
 GORDON, M., 228
 Grading of sizes, 443
 Grading, 443, 478
 Grain, metals and ceramics, 110,
 111, 478
 wood, 458, 478
 Grain, boundary, 110, 173, 478
 area, 112, 478
 Grain growth, 173, 478
 exponent, 175
 Grain shape, 115
 Grain size, 112, 173, 478
 ASTM, 112, 472
 austenite, 386, 389, 473
 Grain-size number, 112
 GRANT, N. J., 196
 Graphite, 471
 Gravity, acceleration of, 466
 Growth rates, 175
 Gutta percha, 227
 GUY, A. G., 108, 178, 368, 369,
 378, 395
- Half-life, 202
 Hand-ball model, 49
 Hard drawn, 478
 Hardenability, 394, 478
 curve, 396, 478
 Hardening, age, 378, 472
 case, 451, 452, 474
 combined, 380
 flame, 453, 478
 induction, 453, 479
 precipitation, 378, 483
 radiation, 203
 solution, 185, 485
 strain, 189, 486
 Hardness, 7, 8, 9, 286, 478
 annealed steels, 355
 Brinell, 7, 9, 473
 vs. carbide shape, 358
 vs. carbon content, 355
 vs. phase size, 356
 Rockwell, 7, 9, 484
 tempered martensite, 357, 398
 vs. tensile strength, 9
 Vickers, 7
 Hardness traverse, 397, 478
 HARDY, H. K., 370
 Hcp, 75, 478
 HEAL, T. J., 370
 Heat, specific, 12, 350, 485
 Heat capacity, 12, 478
 Heat content, 12
 Heat of fusion, 12, 115, 478
 Heat of vaporization, 12
 Hexagonal, 68
 simple, 75
 Hexagonal close-packed (hcp), 75,
 478
 Hexagonal crystal, 75
 High polymers, 228
 High-speed steel, 399, 479
 Hole, electron, 140, 149, 476
 Homogeneous nucleation, 370
 Homogenization, 374, 376
 Hot-working, 193, 479
 House construction, F
 HREN, J. J., 368, 369, 395
 HSLA steels, 381
 HULBERT, S. F., 411
 Hydration, 446, 479
 Hydraulic cement, 446, 474
 Hydrogen bridge, 47, 479
 Hydrogen electrode, 414, 479
 Hydrostatic pressure, 178
 Hypereutectoid steel, 329, 486
 Hypoeutectoid, 329, 479
 steel, 329, 355, 486
 Hysteresis loop, electric, 281, 479
 magnetic, 284, 479
- IMBEMBO, E. A., 198
 Impact strength, 479
 Imperfections, 107
 Impressed voltage, 434, 479
 Impurities, 101
 Induced dipole, 45, 479
 Induction hardening, 453, 479
 Inhibitor, 429, 479
 Initiation, 219
 Injection molding, 57, 479
 Insulator, 144, 145, 275, 479
 Interactive properties, 353, 479
 Interatomic distance, 48
 Intercepts of planes, 94
 Interfacial stresses, 455
 Intermetallic phase, 185, 479
 Intermolecular bond, 40
 Internal structure, 5, 479
 INTERNATIONAL NICKEL, 421
 Interplanar spacing, 88, 479
 Interpolation method, 310
 Interrupted quench, 383, 390, 479
 Interstice, 103, 479
 Interstitial site, 103, 108, 261, 262,
 479
 Interstitial solid solution, 103, 485
 Interstitialcy, 107
 Intramolecular bond, 40
 Intrinsic semiconductor, 146, 484
 Introduction to Ceramics, 351, 352
 Introductory Physical Metallurgy,
 111
- Inverse lever rule, 312, 480
 Ion, 31, 33, 479
 Ion stuffing, 452, 453, 479
 Ion vacancy, 105, 479
 Ionic bond, 34, 479
 Ionic radius, 50, 468, 479
 Ionization, 32, 34, 479
 Iron, alpha, 320, 472
 cast, 322, 470, 474
 gamma, 320, 478
 Iron Age, F
 Iso, 479
 Isomer, 44, 480
 Isoprene, 220
 Isotactic, 226, 480
 Isotherm, 306, 480
 Isothermal cut (phase diagram),
 306, 482
 Isothermal precipitation, 370, 480
 Isothermal reaction, 368
 Isothermal recrystallization, 368
 Isothermal transformation, 382,
 480
 Isotropic, 119
 Izod test, 9
- Jominy bar, 395, 480
 Junction, 158, 480
 collector, 160
 emitter, 160
 p-n, 159, 482
 rectifying, 158
- KAHN, N. A., 198
 KINGERY, W. D., 351, 352
- Lattice, 69, 480
 crystal, 69, 475
 Bravais, 70, 473
 Lattice constant, 69, 72, 480
 Lever rule (inverse), 312, 480
 Light, velocity of, 466
Lignin vitae, 458
 Lignin, 458, 480
 Line, diffraction, 90
 dislocation, 109
 Linear defect, 108
 Linear density, 81
 Linear molecule, 219, 481
 Liquid-phase sintering, 447, 485
 Liquids, 114
 Liquidus, 305, 480
 Locations, unit-cell, 80
 Lone pair, 43, 480
 Long-range order, 67, 480
 Loss factor, 276
 Low-alloy steel, 328, 396, 486
 Luminescence, 152, 480
- Macromolecule, 58, 211, 480
 Macrostructure, 440, 480

- Magnet, permanent, 283, 480
soft, 283, 480
- Magnetic saturation, 282, 480
- Magnetite, 277, 282
- MAGOT, M., 247
- MARLIES, C. A., 222
- Marquenching, 391
- Martempering, 391
- Martensite, 345, 385, 480
tempered, 346, 348, 487
- MASON, C., 11
- Materials, agglomerated, 441
composite, 438, 454, 474
multiphase, 292, 338, 364
noncrystalline, 114
properties of, 470
reinforced, 454
single-phase, 167, 485
- Materials and Man's Needs, F*
- Materials balance, 311, 480
- Materials cycle, *F*
- Materials Engineering, F*
- Materials Science and Engineering, F, 460*
- Materials Science for Engineers, 125, 201*
- Matrix, 480
- McCLINTOCK, F. A., 195
- McLELLAN, G., 452
- Mean, 19, 480
- Mean free path, 141, 480
- Mechanical behavior, 5
- Mechanical Behavior of Metals, 195*
- Mechanical properties, 7, 470, 480
- Mechanical Properties of Matter, 198*
- Mechanical working, 188, 193, 480
- Median, 19, 480
- Melting, 114
- Melting temperature, 46, 59, 468
- Mer, 211, 214, 480
- Mesh, 442, 480
- Mesh number, 442
- Metallic bond, 38, 480
- Metallic conductor, 140, 144, 480
- Metals, 30, 56, 144, 166, 470, 480
cold working of, 193
grain growth in, 173
heat of fusion, 114
hot working, 193
polycrystalline, 187, 195
powdered, 442
refractory, 448
single-phase, 167
solid solution in, 101
- Metals Handbook, 304, 307, 314, 315, 316, 317, 319*
- Metastability, 346, 367, 480
- Methane, 79
- mho, 480
- Mica, 270
- MICHIGAN HIGHWAY TESTING LABORATORY, 441
- Microstructure, 172, 480
multiphase, 338, 347, 481
polycrystalline, 172
- Miller indices, 83, 481
- Miller-Bravais indices, 86
- MINDLIN, H., 199
- Mixed bonds, 39
- Mixed packing, 444
- Mixed particles, 444, 481
- Mixture, 101, 117, 299, 347, 481
- Mixture rules, 349
- Mobility, 15, 140, 149, 481
- Modulus, bulk, 178, 481
of elasticity, 6, 7, 59, 176, 470, 481
of rigidity, 178
shear, 178, 481
viscoelastic, 238, 488
Young's, 6, 176, 236, 470, 481
- Molding, 481
injection, 57, 479
- Mole, 481
- Molecular crystal, 227, 481
- Molecular length, 216, 481
- Molecular phases, 210
- Molecular weight, 213, 481
number-average, 216, 481
size distribution, 215
weight-average, 216, 481
- Molecules, 40, 481
giant, 213
linear, 217, 481
network, 217, 230, 481
polar, 46, 481
- Monel, 101, 170, 470, 481
- Monoclinic, 68
- Monomer, 211, 214, 481
- Multiphase equilibria, 292
- Multiphase materials, 292, 338, 364
- Multiphase microstructure, 338, 347, 481
- MYERS, G. L., 3
- n*-type, 154, 481
- n*-type semiconductor, 154, 484
- NaCl, 35
- NaCl-type structure, 67, 261, 481
- NATIONAL ACADEMY OF SCIENCES, *F*
- Nature of Metals, 72, 73, 111, 188*
- Network modifiers, 273
- Network molecules, 230, 481
- Network silicates, 271, 485
- Neutron, 29, 202
damage, 202
- Newton, 7
- Noble, 415, 481
- Nomenclature, AISI-SAE, 330
- Nominal stress, 9
- Nonbridging oxygen, 274, 481
- Noncrystalline materials, 114
- Nonmetals, 30, 58, 481
- Nonstoichiometric compound, 105, 481
- Normal stress, 177, 182, 481
- Normalizing, 374, 376, 481
- NORTH AMERICAN-PHILLIPS, 48
- Notch sensitivity, 287, 481
- Nuclear reactor, *F*
- Nucleation, 370, 481
- Number-average molecular weight, 216, 481
- Nylon, 223, 225, 471
- OAK RIDGE, 203
- Octahedron, 481
- Open pores, 444, 483
- Orbital, 31, 282, 468, 481
- Order, 102
atomic, 64
long-range, 67, 480
short-range, 116, 485
- Ordered crystal, 67, 102, 185, 260, 481
- Orientation (polymers), 236, 482
grain, 172
preferred, 175, 483
- ORSORT, 203
- Orthorhombic, 68, 228, 482
- OSBORN, H. B., JR., 453
- Overaging, 380, 482
- Overtempering, 399, 482
- Oxidation, 246, 482
- Oxidation cell, 423, 474
- Oxygen, bridging, 273, 473
nonbridging, 274, 481
- p-n* junction, 159, 482
- p*-type, 155, 482
- p*-type semiconductor, 155, 484
- Packing, 262, 444
- Packing factor, 71, 444, 482
- Paint, 429
- Pair, electron-hole, 151, 477
- Paraffin, 213
- Particle size, 442
- Pascal, 7
- PASK, J., 305
- Passivation, 426, 482
- Path, mean free, 141, 480
- Pauli Exclusion Principle, 143.
- PAYSON, P., 431
- Pearlite, 326, 482
formation, 344

- Periodic table, 29, 30
 Permittivity, 242, 466
 PETERSON, R. F., 200
 Phases (materials), 117, 303, 482
 analysis of, 307, 482
 composition of, 307
 dispersed, 357, 476
 intermetallic, 185, 479
 molecular, 210
 size, 356
 transition, 345, 482
 quantity fraction of, 310, 482
 Phase boundary, 117, 482
 Phase diagram, 303, 482
 isothermal cut, 306, 482
 one-phase area, 308, 310, 482
 two-phase area, 308, 310, 482
 three-phase temperature, 309, 312, 482
Phase Diagrams for Ceramists, 317
 Phase systems, 307
 Ag-Cu, 307
 Al-Cu, 316
 Al-Mg, 316
 Al-Si, 319
 Al₂O₃-SiO₂, 305
 C-Fe, 323, 325
 Cu-Ni, 304
 Cu-Sn, 315
 Cu-Zn, 314
 Fe-C, 323, 325
 Fe-O, 317
 FeO-MgO, 318
 Pb-Sn, 304
 Phenol-formaldehyde, 230, 471, 482
 Phosphorescence, 154, 482
 Photoconduction, 151, 482
 Photoluminescence, 152
 Photon, 151, 482
Physical Metallurgy, Elements of, 108, 178, 368, 369, 378, 395
 Piezoelectric, 277, 482
 Pitting, 423
 Plain-carbon steel, 328, 355, 396, 486
 Planar density, 86
 Planck's constant, 466
 Plane, crystal, 83, 475
 intercepts, 84
 slip, 181, 485
 (010), 83
 (110), 83
 (111), 84
 Plastic deformation, 180, 475
 Plastic strain, 7, 180, 486
Plasticity in Crystals, 179
 Plasticizer, 482
 Plastics, 58, 213, 482
 deformation of, 234
 fiber-reinforced (FRP), 454, 478
 Plywood, 460
 Point defect, 107, 483
 Poisson's ratio, 177, 483
 Polar group, 46, 227, 483
 Polar molecule, 46, 481
 Polarization, chemical, 425, 483
 electrical, 242, 278, 281, 483
 molecules, 46, 483
 Polyamide, 224
 Polycrystalline, 187, 195, 483
 microstructures, 172
 Polyester, 224, 483
 Polyethylene, 45, 215, 229, 230, 483
 high-density, 229, 471
 low-density, 229, 471
 Polyfunctional, 217, 483
 Polymer, 58, 471, 483
 addition, 45, 214, 483
 condensation, 223, 483
 linear, 217, 219, 483
 network, 217, 230, 483
 Polymer cement, 446
 Polymerization, addition, 219, 472
 condensation, 223, 483
 degree of, 214, 476
 Polymorph, 77, 483
 Polymorphic reactions, 341
 Polyurethane, 224
 Pores, 349, 443
 closed, 444, 483
 open, 444, 483
 Porosity, 443
 apparent, 445, 483
 true, 445, 483
 Portland cement, 446, 474
 PORTLAND CEMENT ASSOCIATION, 441
 Potential, electrochemical, 414, 476
 electrode, 415
 Powdered metal, 442
 Precipitation, isothermal, 370, 480
 reactions, 342, 483
 processes, 378
 Precipitation hardening, 378, 483
 Preferred orientation, 175, 483
 Pressure, hydrostatic, 178
 Pressure gages, 158
 Primary bond, 34, 483
Principles of High Polymers, 222
 Processing, thermal, 364
 Proeutectoid ferrite, 327, 347, 478
 Propagation, 219, 483
 Properties, 3, 468, 470, 483
 additive, 349
 generalizations, 55
 interactive, 353
 materials, 470
 Proton, 29
 PZT, 279
 Quantity fraction, 310, 312, 483
 Quartz, 272, 279, 307, 471, 483
 Quench, 390, 483
 interrupted, 383, 390, 479
 Radiation damage, 201, 247, 483
 recovery, 204
 Radical, 219, 220
 free, 219
 Radius, atomic, 50, 55, 468, 472
 critical, 371
 ionic, 50, 55, 468, 479
 Radius ratio, 54, 261, 483
 vs. coordination number, 55
 Rate (solids), 367, 483
 Reaction, cathode, 416, 474
 eutectoid, 223, 343, 477
 eutectic, 309, 477
 isothermal, 368
 polymorphic, 341
 precipitation, 342, 483
 solid-phase, 341, 485
 solution, 342
 Reaction rate, 367
 Reactive site, 221, 483
 Reactor, boiling water, *F*
 Recombination, 151, 483
 Recrystallization, 191, 368, 374, 484
 temperature, 191, 484
 Rectifier, 158, 484
 Recycling materials, *F*
 Reduction, 484
 Refractory metals, 448
 Reinforcement, 455, 484
 fiber, 455
 Reinforced materials, 454
 Relative dielectric constant, 16, 241, 276, 476
 Relaxation, 152, 239, 484
 stress, 239, 486
 time, 152, 240, 484
 Remanence, electric, 281, 484
 magnetic, 283, 484
 Repulsion, electronic, 49, 477
 Residual stress, 375, 484
 Resistivity, 15, 470, 484
 electrical, 139, 140, 476
 vs. temperature, 141
 Resistivity coefficient, solid-solution, 142, 484
 temperature, 142, 484
 Resolved shear stress, 182, 485
 Retained austenite, 386

- REYNOLDS METALS CO., *F*
 Rhombic, 75, 76
 Rhombohedral, 68
 RIEGGER, O. K., 111
 Rigidity, modulus of, 178
 Roads, stabilized, 354
 ROBINSON, G. W., 111
 ROGERS, B., 72, 73, 111, 188
 Root-mean-square length, 217, 484
 Rubber, 226, 484
 natural, 471
 synthetic, 471
 vulcanized, 233
 Rubbery plateau, 238, 484
 Rust, 417
 Rupture, stress, 196, 486
 RUSSELL, R., 275
- Sacrificial anode, 433, 486
 Saturation, acceptor, 156, 472
 magnetic, 282, 480
 SCHMID, E., 179
 Schmid's Law, 182, 484
 SCHMIDT, A., 222
 Schottky defect, 107, 484
 Scission, 246, 484
 Screens, Tyler, 442
 Screw dislocation, 108, 476
 Sea water, 300
 Secondary bond, 45, 484
 Segregation, 376, 484
 Self-diffusion, 484
 Semiconducting devices, 158
 Semiconductivity *vs.* temperature, 150
 Semiconductor, 143, 149, 484
 ceramic, 277
 compound, 148, 484
 defect, 156, 277, 484
 extrinsic, 154, 484
 intrinsic, 146, 484
 n-type, 154, 484
 p-type, 155, 484
 properties, 149
 SHANK, M. E., 195
 Shear modulus, 178, 481
 Shear strain, 178, 481
 Shear stress, 177, 484
 critical, 181, 475
 resolved, 182, 485
 Sheet silicate, 270, 485
 Short-range order, 116, 485
 SI, 5, 487
 Significant figures, 19
 Silica, fused, 276
 Silicate, chain, 269, 485
 network, 271, 485
 sheet, 270, 485
 structures, 267, 485
 Silicone, 269, 485
- Silver, Sterling, 101, 470, 486
 Simple cubic, 71, 485
 Simple hexagonal, 75
 Single-phase alloy, 169
 Single-phase material, 167, 485
 Single-phase metals, 167
 Sintering, 447, 485
 liquid-phase, 447, 485
 solid-phase, 448, 485
 Site, interstitial, 103, 108, 261, 262, 282, 479
 4-fold, 262, 282
 6-fold, 261, 282
 8-fold, 261
 Size distribution, molecular, 215
 SiO₄ tetrahedra, 54, 267, 485
 Slip, 180, 286, 485
 direction, 181, 485
 mechanism, 182
 plane, 181, 485
 system, 181, 485
 SMITH, C. O., 203
 Soaking, 376
 Soda-lime glass, 276, 485
 Solder, 302, 485
 Solid-phase reactions, 485
 Solid sintering, 448, 485
 Solid solution, 101
 dislocation movements, 184
 interstitial, 103, 485
 metallic, 101
 ordered, 102, 485
 resistivity coefficient, 142, 484
 substitutional, 101, 266, 485
 Solids, atomic disorder in, 98
 impurities in, 101
 Solid-state reactions, 341, 343
 Solid-state sintering, 448
 Solidus, 305, 485
 Solubility curve, 299
 Solubility limit, 102, 299, 302, 485
 Solute, 125, 127, 485
 Solution, 101, 299, 342, 485
 reactions, 101
 solid, 101, 485
 Solution hardening, 185, 485
 Solution treatment, 342, 378, 485
 Solvent, 125, 127, 485
 Space lattice, 69
 Spacing, *D*-, 90
 interplanar, 88, 479
 Spark plug, 58
 Specific gravity, 445, 470, 485
 Specific heat, 12, 350, 485
 SPELLER, F. N., 420
 Spheroidite, 357, 358, 485
 Spheroidization, 358, 375, 485
 SPICER TRANSMISSION, 3
 Spin (magnetism), 143, 282, 486
 Spinell, 266, 486
- Spring wood, 458
 Stainless steel, 427, 430, 486
Stainless Steels, 470
 Standard deviation, 19, 486
 Steatite, 226
 Steel, 320, 322, 470, 486
 AISI-SAE, 330, 472
 annealed, 355, 375
 carbon, 328, 355, 396, 473
 carburized, 452
 eutectoid, 329, 348, 357, 383, 387, 486
 high-speed, 399, 479
 HSLA, 381
 hypereutectoid, 329, 486
 hypoeutectoid, 329, 355, 486
 induction-hardened, 453
 low-alloy, 328, 381, 396, 486
 plain-carbon, 328, 355, 396, 470, 486
 stainless, 427, 430, 470, 486
 tool, 399, 486
 Stereohindrance, 230
 Stereoisomer, 226, 486
 Stereospecific, 37, 486
 Sterling silver, 101, 306, 470, 486
 Stone Age, *F*
 Strain, 5, 7, 486
 elastic, 7, 486
 plastic, 7, 486
 shear, 178
 true, 8, 11, 486
 Strain hardening, 189, 486
 Strain point, 289, 486
 Strength, 5, 7, 59, 486
 breaking, 9, 486
 vs. carbon content, 355
 dielectric, 276, 476
 tensile, 5, 7, 486
 ultimate, 487
 yield, 7, 8, 486
 Stress, 5, 7, 486
 cell, 421, 474
 concentration factor, 287, 486
 interfacial, 455
 nominal, 9
 normal, 177, 182, 481
 raiser, 287
 relaxation, 239, 486
 relief, 375, 486
 residual, 375, 484
 resolved shear, 182, 485
 rupture, 196, 486
 shear, 177, 485
 true, 9
 Stress-strain curve, 6
 Structure, 3, 486
 AX, 260
 A_mX_n, 264, 473
 BaTiO₃, 266, 278
 CaF₂, 264

- crystal, 67, 468
 CsCl-type, 261, 473
 defect, 105, 106, 475
 diamond, 37
 internal, 5, 479
 NaCl-type, 35, 67, 261, 481
 NiAs-type, 263
 silicate, 267, 485
 spinel, 266
 ZnO-type, 263
 ZnS-type, 262, 473
 Substitutional solid solution, 101
 random, 102
 Sugar, 299
 Summer wood, 458
 Superconductivity, 142
 Supercooling, 303, 372, 486
 Surface, 110, 486
 finish, 201
 modification, 451
 Symmetry, 486
 SYNDER, W. A., 204
 Syndiotactic, 226, 486
 Syrup, 299
 System, alloy, 307
 crystal, 68, 475
 phase, 303
 slip, 181, 485
 Système international, 5, 486

 Temper, 346, 487
 Temperature, 12
 boiling, 46, 59
 equicohesive, 196, 477
 eutectic, 301, 477
 eutectoid, 477
 glass, 116, 229, 235, 288, 478
 melting, 46, 59, 468
 recrystallization, 191, 483
 transition, 198, 487
 Temperature-resistivity coefficient, 142, 484
 Tempered glass, 288, 487
 Tempered hardness, 398
 Tempered martensite, 347, 348, 357, 487
 Tempering, 391, 487
 Tensile strength, 7, 9, 486
 vs. hardness, 9
 Tensile test, 8
 Termination, 221, 487
 Tetragonal, 68, 345, 487
 Tetrahedron, 267, 487
 SiO₄, 54, 485
 Texture, 487
 Thermal agitation, 116, 118, 487
 Thermal characteristics, 12
 Thermal conductivity, 14, 60, 350, 470, 487

 Thermal diffusivity, 14, 487
 Thermal-energy distribution, 120
 Thermal expansion, 12, 60, 118, 487
 coefficient, 13, 119, 470, 487
 iron, 342
 Thermal processing, 364
 Thermal-resistivity coefficient, 142, 484
 Thermistor, 158, 277, 487
 Thermocouple, 487
 Thermoplast, 232, 487
 Thermostat, 232, 487
 THUM, E. E., 431
 Time, relaxation, 152, 240, 484
 Tinplate, 418
 TOCCO DIVISION, 453
 Tool steel, 399, 486
 Toughness, 6, 7, 9, 487
 vs. carbide shape, 358
 vs. carbon content, 355
 Tracer diffusion data, 127
 Tracheid, 458, 487
 Trans., 227, 487
 Transducer, 278, 487
 Transformation, continuous-cooling, 387
 isothermal, 382, 480
 Transformation temperature, 198, 487
 martensite, 385
 processes, 390
 Transistor, 160, 487
 TRANSMISSION SYSTEMS, 3
 Traverse, hardness, 397
 Treatment, solution, 342, 378, 485
 Triclinic, 68
 Tridymite, 307
 Trifunctional, 217, 487
 True density, 445, 476
 True porosity, 445, 483
 True strain, 8, 11, 486
 True stress, 9
 True volume, 445
 T-T-T curves, 383
 Tyler screens, 442

 Ultimate strength, 487
 Unit cell, 69, 487
 locations, 80
 Unit mix, 450
 U.S. STEEL, 8, 10, 326, 328, 329, 345, 348, 357, 382

 Vacancy, 107, 487
 ion, 105, 479
 Valence, 32, 468

 Valence electrons, 32, 37, 148, 487
 Van der Waal's forces, 45, 487
 VAN VLACK, L. H., 125, 201
 Vaporization, heat of, 12
 Variance, 18
 Velocity, drift, 15, 140, 476
 Vickers hardness, 7
 Vinylidene, 220
 Vinyl-type compound, 220
 Viscoelastic modulus, 236, 488
 Viscoelasticity, 238, 487
 Viscosity, 236, 289, 488
 Viscous flow, 239
 Vitreous, 488
 VOLLRATH CO., 57
 Voltage, impressed, 434
 Volume, apparent, 444, 445
 bulk, 444, 445
 true, 444, 445
 Vulcanization, 233, 488
 Vycor, 471

 WALL, L. A., 247
 Warpage, 459, 488
 Water, 47
 Weight-average molecular weight, 216, 481
 Well, energy, 50, 477
 WESTERN ELECTRIC CO., 57, 279
 Wiedemann-Franz ratio, 169, 488
 Wood, 213, 457
 flour, 253
 grain, 458
 impregnated, 460
 ply-, 460
 shrinkage, 459
 • spring, 458, 488
 summer, 458, 488
 tensile strength, 460
 thermal expansion, 459
 warpage, 459
 Young's modulus, 459
 Working range (glass), 289, 488

 X-ray diffraction, 88, 488

 Yield point, 8, 488
 Yield strength, 7, 8, 486
 Young's modulus, 6, 7, 176, 470, 481

 ZAPFFE, C., 430
 ZnS structure (AX), 262, 473
 ZURBURG, H. H., 201