

## Index

- a**
- A<sub>2</sub>BB'O<sub>6</sub> 269
    - cation arrangements, perovskite-type structures 269
    - double perovskites 269
  - ab initio calculations 492, 773
  - abnormal grain growth (AGG) 9
    - triggering impurities 11
  - abnormal plate like alumina grains 9
  - ABO<sub>3</sub> perovskite
    - crystal structure 259, 260
    - polytypes, BO<sub>6/2</sub> octahedra network 264
  - accommodation processes 634, 640, 643, 648
  - Acheson furnaces 138
    - SiC furnaces 137
  - adamantine structure crystals 670
    - thermal conductivity 670, 671
  - adjacent anion sites
    - oxygen vacancy migration, curved path 284
  - aging-deaging terminology 740
  - alkaline earth metals 393
    - cations 40
  - Al<sub>2</sub>O<sub>3</sub>-Al<sub>4</sub>C<sub>3</sub> system 169
  - Al<sub>2</sub>O<sub>3</sub>-AlN system 91, 107
  - Al<sub>2</sub>O<sub>3</sub>-Y<sub>2</sub>O<sub>3</sub> additive system 680
    - thermal conductivity 680
  - Al-SiC composites alloys, development 202
  - alum, calcination 6
  - alumina 513, 615, 622, 667
    - based composites 4
    - based materials 4
    - calcia-silica system 9
    - carbothermal reduction 74
    - ceramics 535, 563
      - alumina-zirconia duplex, microcrack process zone 620
      - bending tests 563
      - strength vs. stress rate 565
      - thermal shock cracks 535
      - Weibull graph 563
    - crack
      - bridge, friction point 626
      - opening profiles 626
      - propagation 616
    - crystals, crystallographic faces 10
    - doping 681
      - co-doping 9
    - electric properties 13
    - grain boundaries
      - high-resolution transmission electron microscopy images 9
    - grain, solid-liquid interphase energies of 11
    - impurities in 516
    - interfaces 517
      - low-angle grain boundary 513
      - low-loss dielectric material 13
    - polycrystalline alumina 514
    - R-curve behavior 615
    - single crystal 13
    - strength 622
      - translucent alumina, see Lucalox<sup>TM</sup>
  - aluminum
    - compounds 155
      - grain boundary energies 510
      - metal-organic compounds 6
    - aluminum nitride (AlN) 74
      - band-gap semiconductors 75
      - ceramics 75, 679
        - alumina impurity 675
        - effect of secondary phase 674
        - lattice-purifying process 687
        - sintering 674
        - thermal conductivity 674, 676, 679

- GaN/InN
- hexagonal wurtzite-structured lattice parameters 102
- properties 75
- $\beta$ -SiC powder mixtures, CVD process 167
- SiC solid solution powders 167
- structure 74
- synthesis 74
- aluminum oxide
  - crystal structure 4
  - liquid-phase sintered (LPS) alumina 8–11
  - natural sources 5
  - polycrystalline alumina, properties 11–13
  - powders, preparation 5
  - chemical methods 6
  - high-temperature/flame/laser synthesis 6
  - mechanically assisted synthesis 6
  - solid-state sintered alumina
  - submicrometer/transparent alumina 7
- ammonia gas atmosphere
  - molecular precursor 120
  - structural transformation 116
- anion-deficient perovskites 273
- ABO<sub>3-x</sub>-type perovskites 272
- copper-containing complex compounds 274
- anomalous ultra-small angle X-ray scattering (A-USAXS) 588
- antiferroelectrics 279, 776
  - saturation voltage 776
- antiferromagnetic (AFM) 278
- AO(ABO<sub>3</sub>)<sub>n</sub> Ruddlesden–Popper phase 266
- applied moment double cantilever beam (AMDCB) techniques 359, 365
  - R-curve behaviors 366
  - specimen 359
- archetypal perovskite 257
  - CaTiO<sub>3</sub>, composition 257
- argon
  - atmosphere 148
  - gas 160
- Ashby and Verrall (A-V) model 643, 644
  - features 644
  - interface-reaction flow mechanism 645
  - principle 644
- atmospheric plasma spraying (APS) 38
- atomic force microscopy (AFM) 625, 636
- atomic resolution ultramicroscopy 496
- atomic-resolved high-resolution transmission electron microscopy 819
- Aurivillius bismuth compounds 266
- Avogadro's number 440, 483
- A<sub>x</sub>WO<sub>3</sub> bronzes, structures 271
- b**
- BaBiO<sub>3</sub>, semiconductive properties 276
- Ba-doped titania varistors
  - nonlinear exponent, variation 26
- Ba<sub>2</sub>In<sub>2</sub>O<sub>5</sub>
  - O<sup>2-</sup>-ion conductivity, Arrhenius plot 284
  - oxygen-deficient brownmillerite-structure 285
- barium titanate (BaTiO<sub>3</sub>) 261, 437, 438, 447, 454, 735
  - acceptor-doped 443, 457
  - chemical diffusivity isotherms 466
  - defect-chemical interpretation 466
  - defect structure 453
  - relaxation behavior and chemical diffusion 464
  - Al-doped 454, 455
  - electronic transference number 467
  - chemical diffusivity of oxygen 474
  - defect concentration 441
  - two-dimensional representations 445
  - defect structures 439
  - donor-doped 445, 450, 468
  - conductivity vs. time 471
  - defect-chemical interpretation 469
  - kinetic anomaly 468
  - relaxation behavior and chemical diffusion 468
  - equilibrium total electrical conductivity vs. log a<sub>O<sub>2</sub></sub> 454
  - La-doped 468
  - equilibrium conductivity 468
  - equilibrium defect structure 469
  - log a<sub>O<sub>2</sub></sub> vs. log a<sub>riO<sub>2</sub></sub>, configuration 444, 445
  - log [S] 446–449
  - vs. log a<sub>O<sub>2</sub></sub> 448, 449, 451
  - vs. log a<sub>riO<sub>2</sub></sub> 446, 447
  - majority disorder types 441, 442
  - allocation rules 443
  - numerical values 442
  - regimes 449
  - type of region 443
  - Mn-doped 744
  - multilayer ceramic capacitors (MLCC) 437
  - phase transformations 261
  - polarization directions 735
  - polycrystal 466
  - pure 439
  - tetragonal 262
  - transition 735
  - undoped 461
  - chemical diffusivity isotherms 466
  - defect-chemical interpretation 466

- relaxation behavior and chemical diffusion 464
- surface-reaction-rate constant vs. oxygen activity 465
- basal plane slip
  - log(CRSS) vs. temperature, plots 383
- Ba<sub>2</sub>Si<sub>5</sub>N<sub>8</sub>, atomic arrangement 243
- Ba<sub>1-x</sub>Sr<sub>x</sub>RuO<sub>3</sub>
  - room-temperature pressure vs. composition phase diagram 265
- Ba<sub>5</sub>Ta<sub>4</sub>O<sub>15</sub> structure, schematic projection 272
- Bayer process 6
- B<sub>4</sub>C polytypes
  - Gibbs free-energy analysis 200
  - SiC particulate composites 179
  - transition metal boride composite materials, development 181
- beryllium oxide (BeO) 396
  - wurtzite structure of 396
- BiFeO<sub>3</sub> thin films 764
  - magnetic properties 764
  - magnetoelectric effect 764
- Bi<sub>3.25</sub>La<sub>0.75</sub>Ti<sub>3</sub>O<sub>12</sub> (BLT), TEM studies 777
- Bi<sub>2</sub>MoO<sub>6</sub>, ideal structure 268
- Bi<sub>4</sub>Ti<sub>3</sub>O<sub>12</sub> (BiT) 771
  - pseudo-tetragonal unit cell of 267
  - relaxor-like behavior 771
- binary phase diagram, thermodynamic assessment 135
- binary ZrO<sub>2</sub>-Ln<sub>2</sub>O<sub>3</sub> systems, maximum conductivity 40
- biomorphous silicon carbide composites 171
- biomorphous SiSiC ceramics, SEM image 172
- bismuth
  - based layered perovskites, schematic diagram 754
  - rich phase 17
- BO<sub>6</sub> octahedrons 260, 261
- boron carbide (B<sub>4</sub>C) 131
  - acids/alkali liquids 200
  - application 207–210
  - based composites 179, 180
  - ceramics, physical properties 209
  - comparison 196
  - crystal structure 136
  - densification 177
  - electrical conductivity 195
  - gaseous hydrogen 200
  - magnesium-containing impurities 150
  - microstructure 176
  - nanostructures 151
  - oxidation 201
  - oxygen/water vapor 201
  - Poisson's ratio 200
  - powder 150, 176
  - properties 200
    - calorific properties 198
    - electrical properties 195–198
    - mechanical properties 198–200
    - neutron-absorbing capability 198
    - optical properties 194
    - thermophysical properties 198
  - room temperature isotropic elastic moduli 198
  - shock compression data analysis 200
  - sintering 174
  - submicron B<sub>4</sub>C powders 150
  - systematic doping 197
  - technical-scale production 149
  - titanium carbide, reaction 182
- boron nitride (BN) 71
  - crystallographic structures
    - cubic boron nitride 72
    - hexagonal boron nitride 71
    - wurtzitic boron nitride (w-BN) 72
  - industrial synthesis 72
  - properties 73
    - c-BN vs. w-BN 73
    - h-BN 73
  - thin films 72
- brittle materials 545, 555, 557, 627
  - application of Weibull statistics, limits for 558
  - strength 545
    - data 555
- brittle-to-plastic transition (BPT) 336
- broken bond model 481, 483, 484, 510
- broken bonds 482, 483, 486
- brookite, synthesis 23
  - crystal structures 21
- Brouwer approximation 441
- Burgers vector 321, 384, 386, 418, 422
  - cubic rare-earth sesquioxides 391
  - dissociation reaction 419
  - partial dislocations 387
  - for SrTiO<sub>3</sub> 411
- c**
- CaAlSiN<sub>3</sub>, atomic arrangement 245
- calcium aluminum silicate (CAS) intergranular films 11
- calcium silicate 30
  - intergranular films 10
- (Ca,La)<sub>0.3</sub>(Si,Al)<sub>12</sub>(O,N)<sub>16</sub> α-sialon, M cation coordination 240
- Ca<sub>2</sub>Mn<sub>2</sub>O<sub>5</sub>

- ab plane, vacancy ordering 273
- oxygen vacancies 273
- capacitance transient techniques 123
- capillarity constant concept 487, 488
- carbide-based hard materials
  - boron carbide 134
  - phase diagram 135
  - preparation 134
  - structural aspects 135–137
  - silicon carbide (SiC) 131–134
  - carborundum 131
  - phase relations 132
  - structural aspects 132–134
- carbon
  - bearing materials 140
  - carbon black 176
  - containing compounds 175
  - fiber-reinforced plastic 170
- carbon nanotubes (CNTs) 713
- carbothermal reduction and nitridation (CRN) 79
- Carnot machine, theoretical efficiency 197
- Cartesian coordinates 498
- Ca-Si-Al-O-N system, glass-forming region 248
- cation diffusion energy 653, 655
- cavitation 587, 595–597
  - creep model 595
  - density change/volume fraction 588
  - role 596
  - size distribution 590
  - TEM characterization 587
- ceramic material(s) 515, 531, 567, 578, 601, 608, 633, 657, 722, 775
  - application 568, 627
  - blades, high sensitivity 577
  - brittle fracture 541–545
  - application of Weibull statistics, limits in brittle materials 58
  - ceramic components/critical crack size, tensile strength 544
  - experimental and sampling uncertainties 553–555
  - fracture mechanics, basics 542
  - fracture statistics/Weibull statistics 545–550
  - influence of microstructure 555–558
  - probabilistic aspects 545–558
  - Weibull distribution, application 550–552
  - coarsening behavior 515
  - components 544
  - critical crack size 544
  - Griffith crack size 544
  - tensile strength 544
  - contact damage 537
  - crack growth resistance curve, influence 621
  - creep research activities 578
  - critical structural property 629
  - crystal structures 388–390
  - dislocation dissociations 391
  - slip, crystallography 388
  - slip systems 390
  - damage mechanisms, overview 538–540
  - corrosion 540
  - creep 540
  - fatigue 540
  - sub-critical crack growth 539
  - sudden, catastrophic failure 539
  - defects at failure origin 609
  - delayed fracture 558–567
  - fatigue crack growth on strength, influence 566
  - proof testing 566
  - SCCG on strength, lifetime and influence 559–565
  - dimensions 722
  - edge flakes, examples 538
  - failure modes/appearance 532–538
  - contact failure 536–538
  - thermal shock failure 534–536
  - fatigue 626–629
  - contact fatigue 627
  - cyclic fatigue crack propagation 626
  - fracture theory 531, 601–612
  - crack closure concept/superposition 609
  - fracture mirror 532
  - mechanics 531, 568
  - resistance, determination 622–626
  - stress concentration factors 608
  - surface 569
  - toughness 531, 532
  - type 533
  - functional properties 3
  - inertia 775
  - joining, micrograph 657
  - mechanical testing, standardization 531
  - penny-shaped cracks 543
  - products 537
  - statistical nature of failure 567
  - strength 532
  - microstructural mechanisms 611
  - powder processing technology 660
  - strength 609
  - structural deficiency 612
  - structural elements 352
  - structural reliability 622
  - superplasticity 633

- accommodation-controlling mechanisms 633
- accommodation processes 643–656
- applications 656–659
- future prospective in field 659
- goals 659
- grain boundaries, nature 640–643
- macroscopic/microscopic features 634–640
- systems 486, 512
- CSL boundaries 512
- toughened ceramics 612–620
- bridged interface methods for increasing fracture resistance 613–620
- toughening by crack tip process zone effects 620
- use 660, 667
- ceramic matrix composite (CMC) systems 145, 205, 634
- ceria ( $\text{CeO}_2$ ) 43, 44, 47, 705, 717
  - based ceramics
  - applications of 44
  - mechanical properties 45
  - room temperature, dependence 46
  - stabilized  $\text{ZrO}_2$  ceramic, scanning electron microscopy image 37
  - based solid electrolytes, properties 47
  - nanocrystalline, electrical conductivity 717
  - polishing powders 46
  - predominant defects 705
- cerium oxide, see ceria ( $\text{CeO}_2$ )
- cermets, fabrication 480
- charged transport processes 749
- charge neutrality equation 452
  - constraint 457
- chemical diffusion theory 463, 466
- chemical diffusivity 463, 472, 475
- chemical mechanical planarization (CMP) 43
- chemical vapor deposition (CVD) 60, 142, 330, 681
  - molecular beam epitaxy (MBE) approaches 124
  - SiC, coatings 160
  - single crystals 330
- chemical vapor infiltration (CVI) 169
- chevron-notched beam (CNB) technique 369, 371
- chromium dioxide ( $\text{CrO}_2$ ) 791, 800–802
  - $^{53}\text{Cr}$  NMR spectra 801
  - half-metallic behavior 791
  - magnetic moment 800
  - magnetoresistance (MR) 801
- chromium nitride ( $\text{CrN}$ ) 77
- coarse-grained samples 338
  - aluminas 13
  - crack-growth resistance 335
  - microstructure 191
  - SiC powder fractions 152
  - $\text{Ti}_3\text{SiC}_2$  microstructures
  - $\text{Ti}_3\text{SiC}_2$ , tensile stress-strain curves 338
- coarsening process 514
- cobalt ferrite ( $\text{CoFe}_2\text{O}_4$ ) 799
  - high coercivity 799
  - nanoparticles 800
- Cohen's analysis 735
- coincidence site lattice (CSL) model 509, 511
  - boundaries 510
  - HRTEM images 512
  - schematic illustrations 511
  - lattice 509, 510
- Cole–Cole relaxation 771
- colloidal methods 6
- colossal magnetoresistance (CMR) effect 277
  - manganites 275
  - phenomenon 278
- commercial anatase powders, morphologies 22
- complex, definition 229
- complex oxides 437
  - applications 437
  - $\text{BaTiO}_3$ , multilayer ceramic capacitors (MLCC) 437
  - defect-chemical analyses 455
  - defect structure 437–455
    - acceptor-doped case 443
    - complication, hole trapping 452
    - defect concentrations, two-dimensional representations 445–451
    - donor-doped case 445
    - kinetic aspects 438
    - pure case 439–443
    - and reality 453–455
    - sensitive properties 453
  - molecular ratio 439
  - nonstoichiometry 437
    - oxygen nonstoichiometry 456–462
    - re-equilibration 462–476
    - relaxation 437
  - $\text{TiO}_2$  438, 439
- complex Si–Al–O–N
  - lanthanum new phase 242
  - $\text{M}_1(\text{Si},\text{Al})_3(\text{O},\text{N})_5$  phases 243
  - $\text{M}_2(\text{Si},\text{Al})_5(\text{O},\text{N})_8$  oxynitrides 242
  - $\text{M}_3(\text{Si},\text{Al})_6(\text{O},\text{N})_{11}$  phases 244
  - M–Si–Al–O–N oxynitrides 238
    - JEM phase 239
    - sialon S-phase 240–242
  - $\text{MSi}_2\text{O}_2\text{N}_2$  oxynitrides 245

- sialon polytypoid phases 232
  - sialon X-phase 231
  - wurtzite oxynitrides 245
  - Y-Si-O-N oxynitrides 233–238
  - composite microstructures, thermal
    - conductivity 672
  - secondary phase effect
    - AlN ceramic 674–676
    - liquid-phase sintering of nonoxide ceramics 672–674
    - SiC ceramic 678
    - Si<sub>3</sub>N<sub>4</sub> ceramic 676–678
  - contact 536
    - blunt contact 536
    - failure 536–538
    - sharp contact 536
  - continuous fiber-reinforced SiC matrix composites 169
  - coordination number (CN) 482, 492
  - Coulombic correlations 803
  - Coulombic potential barrier 827
  - Cr<sub>2</sub>AlC
    - elastic properties 305
    - oxidation resistance 319
  - crack 603
    - bridging mechanism 163, 353, 359, 658
    - closure concept/superposition 609
    - closure force 611
      - point load closure force 612
    - deflection 146, 159, 163
    - flanks 611, 618
    - fracture, energy associated 605
    - function of length 608
    - growth
      - condition for 605
      - resistance behavior 618
      - resistance curve 621
      - resistance, effectiveness 629
    - interlinking 13
    - loading modes 607, 608
    - micro-cracking 620
    - pertinent concept of crack growth resistance 614
    - potential energy 604
    - shape 603
    - subcritical propagation 626
    - tip opening displacement measurements 625
    - wake interaction 163
    - wake toughening mechanisms 352
  - creep curves approach 594
  - creep mechanisms 577
    - resistance 658
  - critical resolved shear stress (CRSS) 380
    - deformation, kink mechanism 382–384
    - experimental observations 380–382
    - kink pair nucleation, modification 384–386
    - theory vs. experiment
      - nonstoichiometric spinel 388
      - sapphire and stoichiometric spinel 387
  - cross-head displacement (CHD) rate 340
  - cryptomelane-type MnO<sub>2</sub> nanowires 821
  - crystal 487, 489
    - equilibrium shape 491
    - fcc metallic crystals 490
    - Wulff construction 491
    - free energy 489
    - growth 499
    - kink, density 496
    - minimum symmetry segment 490
    - structures, of oxides 389
    - surfaces 496, 501
    - terrace, definition 496
    - tetragonal symmetry 487
  - crystal-field theory 792
  - crystalline boron carbide nanoparticles 151
  - crystalline oxide materials, applications 437
  - crystallographically complex 229
  - cubic perovskite structure 273
    - ABO<sub>3</sub> 273
    - transformation 264
  - cubic SrTiO<sub>3</sub>, crystal structure 411
  - cubic tungsten bronzes 270
  - cubic ZrO<sub>2</sub> matrix
    - tetragonal phase nucleated, oblate spheroids 33
  - Curie's capillarity constant concept 488
  - Curie-Weiss temperature 763, 828
  - cyclic crack propagation process 767
  - cyclic stress-strain curves
    - linear elastic solids 326
    - typical compressive 326
- d**
- damage mechanism 538
    - classes 539
    - corrosion 540
    - creep 540
    - fatigue 540
    - overview 538–540
    - sub-critical crack growth 539
    - sudden, catastrophic failure 539
  - Debye frequency 669
  - Debye length 472, 641, 702, 707, 708
    - vs. space charge potential 703
  - Debye model 669
  - Debye temperatures 315
  - defect agglomeration 770

- deformation mechanisms 579, 592, 647
  - degree of deformation 595
- de Gennes double exchange 275
- degrees-of-freedom (DOF) 505, 506
  - macroscopic, schematic illustration 505, 507
- delayed fracture 558
  - loading regions 565
  - under constant load 561
  - under general loading conditions 565
  - under increasing load 564
- dense  $B_4C$ - $TiB_2$  composite materials 180
- dense boron carbide
  - boron carbide-based composites
    - $B_4C$ -based MMCs 182
    - $B_4C$ - $SiC$  179
    - $B_4C$ - $TiB_2$  180–182
  - evaporation-condensation processes 174
  - sintered boron carbide 175
    - hot isostatic-pressed boron carbide 178
    - pressureless sintered boron carbide 175–178
    - spark-plasma-sintered boron carbide 179
- dense random packing (DRP) model 503
  - five fold rotational symmetry 503
- dense silicon carbide
  - bodies, fabrication 162
  - ceramically bonded silicon carbide 152
    - platelet-reinforced 145
      - alumina 146
    - properties 79
    - reaction-bonded silicon carbide 154
    - recrystallized silicon carbide 152–154
    - sintered silicon carbide
      - Al-B-C-based additives 159
      - AlN 167
      - $Al_2O_3$  168
      - alloying 163–172
      - $B_4C$  165–167
        - biomorphous composites 171
        - chemical/physical vapor-deposited silicon carbide 160
        - CVI, fabrication 169
        - hot isostatic-pressed SiC 160
        - hot-pressed silicon carbide 159
        - liquid-phase-sintered SiC (LPS-SiC) 156
        - LPI, fabrication 170
        - LSI, fabrication 170
        - metal matrix composites (MMCs) 172–174
        - oxide additives 157–159
        - pressure less solid-state sintered silicon carbide 154
          - silicon carbide nanoceramics 162
          - silicon carbide wafers 161
          - spark plasma sintering (SPS) 155
          - $TiB_2$  164
          - TiC 164
    - density functional theory (DFT) 109
    - deterministic design approach 551
    - dicalcium/tricalcium silicate,
      - microstructure 515
    - dielectric ceramic materials 669
    - diesel engines 204
    - diesel particulate filters (DPFs) 204
    - diffusion process 463, 514, 642
      - coefficient 649
      - controlled model 395
    - dilatation stresses 597
    - discontinuously reinforced aluminum (DRA) 202
    - dislocation theory
      - application 379
      - interactions 321
      - in oxides 392
      - particular oxides 393
      - spinel, Hornstra 392
    - dissolution-precipitation processes 673
    - 2-D nucleation process 501, 515, 651
      - energy barrier 501
    - domain-engineered crystals 731, 735
      - characteristics 735
      - domain orientation states 735
    - domain-multidomain process 743
    - domain reconfiguration process 742
    - domain wall 746
      - clamping effect 743
        - stabilization 744
        - pinning mechanism 777
        - trapping sites 746
    - dopant 445
      - mass-conservation equation 445
      - roles 633
    - doping
      - heterogeneous doping 715
      - homogeneous doping 714
    - 2-D simple rectangular system 497
      - step density, changes in 497
    - 3d transition-metal ions 794
      - electronic configurations 794
      - ground-state effective spins 794
    - Duralcan process 173
    - DWA-aluminum composites
      - manufactures 202
    - dye-sensitized solar cells (DSSCs) 704, 719–722
      - light active synthetic dyes 720

- schematic diagram 722
- structure and components 720
- Dzyaloshinskii–Moria interaction 762

**e**

- earth-doped oxynitride glasses 66
- edge energy 494
- EKasic silicon carbide laser-structure 204
- elasticity theory 408
- elastic modulus 374
- electrically active ceramics, see electroceramics
- electrical poling process 729
- electric field 765, 770
  - cyclic application 765
  - intensity 709
- electric transportation systems 668
  - parameters, summary 310
- electroceramics 3, 697
  - devices 699
  - electrically conductive, properties 697
  - electronic properties, role of interfaces 698
- electrochemical models 770
- electromechanical anisotropy 738
- electron-beam back-scattered diffraction (EBSD) analysis 507
- electron beam curing method 147
- electron beam physical vapor deposition (EB-PVD) 38
- electron energy loss spectroscopy (EELS) 62, 306
- electronic charge carriers, redistribution 702
- electronic conductor system 475
- electron paramagnetic resonance (EPR) measurements 826
- electron spin resonance (ESR) analysis 682
  - spectra 813
- electron transport dynamics 722
- electrostrictive ceramics 731
- electrostrictive effects 280
- electrostrictive transparent material 767
- Elektroschmelzwerk Kempten (ESK) process 138
- elliptical defect 602
- elliptic cylinder, schematic representation 327
- emulsion techniques 44
- energy-dispersive X-ray (EDX) analysis 252
- energy-dissipating processes 543
- energy-lowering process, see reconstruction processes
- energy-minimizing process, faceting 492
- energy-reduction process, faceting 492
- environmental barrier coatings (EBCs) 205
- equilibrium conductivity 473

- equivalent stress, definition 549
- Er-Si-O-N system 237
- ESIS reference materials 552
- ethylenediaminetetra-acetic acid (EDTA) 31
- Euler angles 507
- Euler's rotation theorem 506
- explosion boron nitride (e-BN) 71
- extreme-UV (EUV) spectral region
  - complex refractive index 195
  - space astronomy/earth sciences 194

**f**

- fabrication method 150, 180
- face-centered cubic (fcc)
  - crystal, CSL boundary 510
  - lattice 102
  - symmetry 482
- faceting 492
  - energy change 494
- Faraday constant 466
- fatigue-free systems 776
  - thin film devices 771
- fatigue process 770, 772
- Fermi energy 711
- Fermi level 113
- ferrites 797–800
  - ferrimagnetic ordering 798
  - magnetic properties 798
  - partial unit cell 798
- ferroelectric ceramics 619, 729, 750, 755
  - applications 729
  - engineering 755
  - lead zirconate titanate (PZT) 619
  - crystal domains orientation, schematic representation 619
  - poling direction 620
  - properties 750
- ferroelectricity 258, 762
- ferroelectric system 729, 735, 747, 765, 770, 775
  - acceptor defects 770
  - aging phenomenon 731
  - crystals, properties 738
  - enhanced intrinsic response 735
  - fatigue in ferroelectric materials 765–777
  - antiferroelectrics 776
  - breakdown 768
  - clamping in thin films 774
  - combined loading 775
  - defect agglomeration 770
  - domain nucleation or wall motion inhibition 773
  - domain splitting and crystal orientation dependence 774



- electrode effects 773
  - fatigue-free systems 776
  - frequency effect 769
  - macrocracking 765–767
  - microcracking 767
  - ferroelectricity and magnetism 756–764
  - hardening-softening transitions 747
  - hysteresis loops 741, 748
  - comparison 749
  - relaxation 748
  - lead-zirconate-titanate, image of stresses 766
  - materials 730, 742, 745
  - applications 730
  - piezoelectric properties 742
  - properties, rate dependencies 730, 769
  - V-potential 745
  - memory devices 765
  - perovskites 734, 749, 750, 760
  - PZT/BaTiO<sub>3</sub> 749
  - phase transition 281
  - polarizations 764
  - properties 729
  - extrinsic properties, hard and soft ferroelectrics 739–750
  - intrinsic properties, anisotropy of properties 731–739
  - random access memory 760
  - single crystals 730
  - spontaneous polarization 739
  - stress-strain relationships 766
  - textured ferroelectric materials 750–756
  - HTGG 753
  - OCAP 752
  - RTGG 754–756
  - TGG 753
  - use 765
  - variety 733
  - ferromagnetism 258
  - fiber-reinforced SiC matrix composites
    - mechanical and physical data 158
  - fibrous grains 358, 373
    - schematic presentation 370
  - fibrous  $\beta$ -reinforcing grains 359
  - fibrous  $\beta$ -seed crystals, use 353
  - fibrous  $\beta$ -silicon nitride grains 365
  - field-cooled (FC)/zero-field-cooled (ZFC) susceptibility curves 811, 825
  - field effect transistor (FET) devices 92, 203
  - fine-grained material 621
    - microstructure 162
    - yields materials 351
    - Ti<sub>3</sub>SiC<sub>2</sub> samples, cyclic-fatigue study 334
  - finite element (FE) stress analyses 549
  - finite-temperature Lanczos method (FTLM) 812
  - first law of thermodynamics 438
  - first nearest neighbor interactions (FNNs) 483, 485
    - interactions 491
  - first-principle stress (FPS) criterion 549
  - flexure method, surface crack 625
  - forsterite, Mg<sub>2</sub>SiO<sub>4</sub>
    - crystal structure of 417
    - high-temperature creep deformation 418
  - Fourier transform infrared (FTIR) spectroscopy 115
  - fractography 558
  - fracture 546, 615
    - energy strength, comparison of 375
    - probability 546
    - resistance, determination 622–626
    - advantages 623
    - indentation fracture toughness 622
    - intrinsic toughness, determination 625
    - significance 622
    - single-edge notched beam 623
    - surface crack in flexure 625
    - statistics 546
    - strain 376
    - strength 373
    - porosity dependence 372
    - dependencies 373
    - theory 601–612
    - crack closure concept/superposition 609
    - fracture toughness vs. strength for ceramic materials 602
    - stress concentration factors 608
  - free carbon content
    - four-point bending strength vs. sintering temperature 199
  - French process 16
  - Frenkel disorder 701
  - Friedel–Fleischer statistics 428, 430
  - functional gradient material (FGM) 659
- g**
- gadolinium-doped ceria (GDC) 714
  - gallium arsenide 112
  - gallium nitrate, thermal treatment of 115
  - gallium nitride (GaN) 93, 112
    - anion-substituted 108
    - bulk single crystals 100
    - films
      - crystallinity 99
      - oxidation 108
    - (Ga,Al,In)N solid solutions, properties 101
    - GaN-Ga<sub>2</sub>O<sub>3</sub> system 109

- phase separation 118
- metal-oxide-semiconductor (MOS) capacitors 123
- phase 93
- description 94–98
- powder 96
- solubility of oxygen 111
- substrates, optoelectronic materials 91
- molecular precursors, pyrolysis of 117
- thermally activated transformation 115–117
- synthesis routes 99
- bulk gallium nitride, synthesis 99
- chemical precursor routes, synthesis 101
- thin film, synthesis of 100
- system 94
- gallium oxide nitride 111
- films 123
- sensor properties 114
- materials 113
- phases, synthesis 117
- gallium oxides
- based materials 104
- $\beta$ -gallium oxide displays 94
- GaN solid solutions 121
- GaN system 108, 110
- $\beta$ -Ga<sub>2</sub>O<sub>3</sub> phase
- Raman spectra 105
- X-ray diffraction patterns 105
- $\beta$ -Ga<sub>2</sub>O<sub>3</sub> polymorph 94
- $\epsilon$ -Ga<sub>2</sub>O<sub>3</sub> polymorph 107
- growth techniques, synthesis 106
- phase description and properties 102–106
- system 104
- phase transformations/synthesis temperatures 103
- thin films 94
- gallium oxonitrides 107
- compounds, syntheses 114, 116
- gallium oxide nitride phases 110–114
- Ga-O-N materials, nomenclature issues 108
- growth techniques, synthesis 114
- crystalline phases 118–121
- precursor approach 115–118
- photoluminescence measurement 119
- potential applications 122–124
- spinel
- phase 118
- properties of 109
- structure 118
- theoretical predictions 108–110
- gallium tris(tert-butoxide) dimethylamine adduct 117
- Ga/N/O atoms
- secondary ion mass spectroscopy profiles 113
- Ga<sub>2.8</sub>N<sub>0.64</sub>O<sub>3.24</sub>
- spinel-type structured, Rietveld refinement 119
- Ga-O-N films, useful production 92
- Gaussian distribution 553, 554
- curve 555
- Ga<sub>x</sub>O<sub>y</sub>N<sub>z</sub> phase
- diffraction pattern 121
- solid-state compounds 108
- Gibbs dividing surface 481
- Gibbs free energy 458
- function 737
- Gibbs–Helmholtz equation 458
- glass
- grain interfacial energy 10
- pockets, triple grain junctions
- energy-dispersive X-ray spectra 366
- transition temperatures 66
- glassy-phase ceramics 649
- accommodation processes 649
- layers 655
- global positioning system (GPS) 202
- goethite  $\alpha$ -FeOOH nanowires 797
- scanning electron microscopy image 797
- superparamagnetic behavior 797
- Goss grains 519, 520, 523
- exclusive growth 519
- microstructural evidence 521, 522
- optical microscopic images 522
- sub-grain boundaries 520
- Gouy–Chapman model 718
- boundary conditions 704, 707
- vs. Mott–Schottky 706, 707
- grain 614
- alignment 364
- crack bridging, examples 614
- crack growth resistance behavior 616
- morphologies 365
- grain boundary(ies) 7, 11, 47, 368, 480, 508–510, 516, 519, 595, 633, 700
- coincident site lattice (CSL) boundaries 507
- crystal phase 351
- energies, anisotropy 521
- glass 11
- corrosion resistance 13
- glassy phase 686, 688
- microscopic grain boundary 507, 508
- mobility 517
- schematic illustration 518
- molecular dynamics (MD) simulations of 10

- nature 640–643
  - sub-grain boundary, schematic illustration 519
  - thickness 595
  - viscosity 596, 597
  - grain boundary sliding (GBS) 594, 633, 635, 636
  - accommodation process 646
  - advantage 657
  - mechanism 645
  - point defects 635, 636
  - strain rate controlling 648
  - grained sialon, equiaxed/elongated 628
  - scanning electron microscopy images 628
  - Green's function technique 757
  - Griffith analysis 543, 544, 603, 606
    - mechanical energy release rate 604
    - stressed plate/through-thickness crack 603
    - stress element, cartesian/polar coordinate 606
  - Griffith–Irwin fracture criterion 543
- h**
- H<sup>+</sup> ions
    - binding force 286
    - conductivity, masses 287
  - Hall coefficient 310
  - hardening mechanisms 423
  - hardening-softening concept 740
  - hard sphere model 482, 500
  - heat-exchanger systems 204
  - Heisenberg model 813, 815
  - Helmholtz free energy 487
  - Hertzian cone cracks 531
  - Hertzian ring crack 536, 538
  - heterotemplated grain growth (HTGG) 752, 753
  - hexagonal BN (h-BN) 71
    - functions 71
  - hexagonal gallium nitride 120
  - hexagonal/rhombohedral polytypes 421
  - hexagonal wurtzite structure 96
  - high-energy milling 14
  - high-pressure nitrogen solution growth (HPNSG) method 99
  - high-resolution electron energy loss spectroscopy (HREELS) 112
  - high-resolution scanning electron microscopy (HRSEM) 625
  - high-resolution synchrotron X-ray diffraction 736
  - high-resolution transmission electron microscopy (HRTEM) 106, 134, 504, 642, 678, 820, 825
    - images, technological advancements 512
    - high-strain rate superplasticity (HSRS) 659
    - hole trapping, trapping factor 452
    - hollow microsphere templated thin films 715
    - homogeneous uniaxial stress field 547, 548
    - arbitrarily oriented cracks, Weibull distribution 547, 548
    - HOMO–LUMO separation 709
    - hot isostatic pressing (HIP) 8, 160, 178
    - hot-pressed silicon carbide 159, 203
    - hot-wall horizontal quartz tube reactor 142
    - Hugoniot elastic limit (HEL) 200
    - Hund's correlation energy 793
    - Hund's rule 803
    - hydrocarbon combustion 47
    - hysteresis 745, 746
      - ascending/descending branches 750
      - loops 740
- i**
- ideal perovskite ABO<sub>3</sub> structure, presentations 258
  - IKB
    - critical resolved shear stress (CRSS) 328
    - formation 327
  - incident photon-to-electron conversion efficiency (IPCE) 721
  - indium tin oxide (ITO) 697
  - injection laser diode, synthesis processes 100
  - in-situ scanning electron microscopy (SEM) 365
    - insulating gallium oxide nitride layers 92
    - interface anisotropy, role 515
    - intergranular amorphous phase 365
    - intermediate-temperature solid oxide fuel cells (IT-SOFCs) 41
    - intra-atomic electron-electron coulomb energies 275
    - intrinsic electronic excitation, pseudo-equilibrium constant 458
  - ion-beam-assisted deposition 60
  - ion beam-deposited boron carbide 194
  - ionic and mixed conducting materials 707, 714
    - interfaces in 714–718
  - ionic conductivity 47, 285, 716
    - Arrhenius plot 716
  - ionic solid, electrical conductivity 714
  - ionic systems 699, 700
    - potential barriers 700
    - space charge formation 699
  - iron oxides 793–797
    - arrays 793
    - hematite ( $\alpha$ -Fe<sub>2</sub>O<sub>3</sub>) 794, 796

- magnetic moment 794
- magnetic properties 794–797
- magnetite ( $\text{Fe}_3\text{O}_4$ ) 794, 796
- structural properties 795
- structures 793
- Ising model 499

**j**

- Jahn–Teller-active ions 808
- Jahn–Teller effect 763, 802
- Jahn–Teller phonons 803
- JEM phase, crystal structure 240
- J-phase
  - monoclinic cells 236
  - structure 236
  - unit cell volume vs. ionic radius 237

**k**

- Kagomé layers 389
  - basal dislocations 391
  - Shockley-like quarter partials 391
- kink
  - band formation, scheme 325
  - behavior, analysis of 421
  - boundaries 337
  - formation energy 384
  - nucleation model 384, 385, 388
  - modification 385
  - pair nucleation, diagrams 386, 413, 419
- Knoop hardness anisotropy 199, 400, 401
- Kosterlitz–Thouless transition 499

**l**

- $\text{LaMnO}_3$  276
  - Mn vacancy migration 288
- Landau–Ginsburg–Devonshire (LGD) theory 733
- Landolt–Börnstein tables 379
- Langmuir equation 711
- lanxide, see Primex process
- large fibrous grains
  - alignment 371, 374
  - crack interacting, in situ observations 367
- large-scale solar cell 720
- large  $\beta$ -seed crystals, incorporation of 360
- laser-heated diamond anvil cell (LH-DAC) 118
- laser-heated diamond cell methods 118
- laser scanning systems 207
- $\text{La}_4\text{Si}_2\text{O}_7\text{N}_2$ 
  - crystal structures, [0 1 0] projections of 237
- lattice dislocation model 509
- lattice molecule 439, 443, 445, 450
- lattice wave propagation 669

- lead-lanthanum zirconate-titanate (PLZT) 730
  - electro-optic properties 730
- lead zirconate titanate (PZT) ceramics 731, 774, 781
- least squares method 593
- Le Châtlier's principle 450
- Legendre transformation 497
- ligand-field theory 792
- light-emitting diodes (LEDs) 161
- light-emitting nitride 80
- linear elastic fracture mechanics framework 543
- Lipschitz-mechanism, grain switching, scheme 635
- liquid crystal displays (LCDs) 697
- liquid phase
  - advantage of 157
  - sintered aluminas 4
  - sintered EKasic T 193
  - sintered materials 11
  - sintered silicon carbide (LPS-SiC) 156
  - tailored properties of 203
- liquid-phase sintering (LPS) mechanism 157, 246, 480, 514, 517, 671
- lithium-ion
  - battery materials 718
  - conductor 715
  - $\text{Al}_2\text{O}_3$  system 716
  - densification theory 514
  - realistic model 514
- lithium sialon system
  - $\alpha$ -sialon stability, region 239
- local-density-approximation (LDA) calculations 109, 814
- Lodgering factor 755
- log(CRSS)-T law 382
- longitudinal piezoelectric coefficient 736, 737
  - orientation dependence 736
- long-range ordering (LRO) transition 808, 810
  - antiferromagnetic 812
- low-energy electron diffraction (LEED) methods 112
- low-Z rare earth sialon systems 249
- $\text{Lu}_2\text{O}_3$ - $\text{SiO}_2$  sintering additives
  - seeded 369
  - tape-cast silicon 369
- Lucalox<sup>TM</sup> 514
- lutetium, role 596

**m**

- macrocracking 765
- magic angle spinning nuclear magnetic resonance (MAS-NMR) spectroscopy 116, 231

- magnesia, see magnesium oxide (MgO)
- magnesium acetate 14
- magnesium oxide (MgO) 13, 14, 516
  - addition 11
  - crystal structure 14
  - crystals, work hardening 423–424
  - spinel 424–426
  - Fe<sup>3+</sup> dopant, yield stress 430
  - MgO-doped alumina 516, 517
  - pore mobility 517
  - natural sources and production 14
  - polycrystalline magnesia 15
  - powders, sinterability 14
  - role 517
  - single-crystal, physical properties 14
  - slip systems, log(CRSS) vs. temperature 380
- magnetic anisotropy 796
- magnetic frustration, manifestation 807–815
  - defect spinel  $\lambda$ -MnO<sub>2</sub>, frustrated magnetism 813–815
  - layered  $\alpha$ -NaMnO<sub>2</sub> compounds, magneto-elastic coupling 811–813
  - geometric frustration 813
  - magnetic susceptibility 812
  - mixed-valence hollandite ( $\alpha$ -MnO<sub>2</sub>), magnetic properties 810
  - pyrolusite ( $\beta$ -MnO<sub>2</sub>), helical order 808–810
- magnetic nanoparticles 821
- magnetic recording technology 800
- magnetic semiconductor 801
  - schematic densities 801
- magnetic spiral order sets, conditions 762
- magnetic susceptibility 823, 824
  - Curie–Weiss dependence 823
- magnetization 822
  - temperature-dependence 823
- magnetoelectric devices 756
- magnetoelectric effect (ME) 756, 757
  - challenge 760
  - comparison 759
  - product property 757
  - sources 756
- magnetoelectric voltage coefficient 758, 759, 760
- manganese oxide 802, 804
  - crystallographic summary 805
  - frameworks 807
  - hollandite-type 811
  - layered forms 807
  - layered structures 807
  - birnessite ( $\delta$ -MnO<sub>2</sub>) 807
  - magnetic behavior 808
  - magnetism 802
    - one-dimensional structures 804–807
    - hollandite ( $\alpha$ -MnO<sub>2</sub>) 806
    - pyrolusite ( $\beta$ -MnO<sub>2</sub>) 804
    - ramsdellite (R-MnO<sub>2</sub>) 804–806
    - phases 802–821
    - crystal structures, polyhedral presentations 806
    - magnetic properties 807–815
    - manganese dioxide nanoparticles, magnetic properties 821
    - manganese oxide structures 804–807
    - MnO<sub>2</sub> nanostructures, synthesis 815–821
    - samples, scanning electron microscopy image 826
    - three-dimensional structures 807
    - spinel  $\lambda$ -MnO<sub>2</sub> 807
- manganese dioxide nanostructures 815, 821
  - crystalline phases/precursors/synthesis conditions/morphologies 816, 817
  - magnetic properties 821–828
  - $\alpha$ -MnO<sub>2</sub> (hollandite) 824–828
  - $\beta$ -MnO<sub>2</sub> (pyrolusite) 821–824
  - synthesis 815–821
  - in crystallographic phases 821
  - $\alpha$ -MnO<sub>2</sub> nanostructures, synthesis 815–818
  - $\beta$ -MnO<sub>2</sub> nanostructures, synthesis 818
  - $\gamma$ -MnO<sub>2</sub> nanostructures, synthesis 819
  - $\lambda$ -MnO<sub>2</sub> nanodiscs, synthesis 820
- March–Dollas function 755, 756
- mass-action law 440
- mass conservation constraint 452
- materials 731
  - chemistry 479
  - electromechanical responses 731
  - fatigue, degree 776
  - imperfections 479
  - interfaces 479–513
  - anisotropy 523
  - energies, anisotropy in 480
  - kinetics of surface migration 499–502
  - roughening transition 495–499
  - solid/liquid interfaces 502–506
  - solid/solid interfaces 506–513
  - surface energy 480–486
  - Wulff plot 486–495
  - microstructures 479
  - practical implications 513–523
  - properties 479
- MAX phases 300
  - compressive stresses 329
  - cyclic stress-strain loops 328
  - discovery of 304
  - electrical conductivities 307

- electronic properties 312
- experimental vs. theoretical bulk, comparison 306
- kink bands (KBs) 321
- mechanical properties 320
- MX carbides 329
- nanolaminate nature of 324
- partial DOS 304
- Raman modes 307
- rutile-forming 319
- Si/Ge-containing 313
- Sn-containing 305
- TECs, summary 317
- temperature-dependence 309
- thermal conductivities 314, 315
- thermal expansion coefficients (TECs) 316
- thermal shock-resistant 333
- thin films 299
- $\text{Ti}_3\text{SiC}_2$  320
- transport parameters 312
- unit cells 301
- Vickers indentation 333
- Young's modulus/shear modulus/Poisson ratio 305
- mechanically coupled magnetoelectric composites 758
- mesoporous random nanoparticle  $\text{TiO}_2$  films 722
- metal/silicon nanowire Schottky barrier 709
  - electron density 710
  - energy band bending 709
- metallic systems, secondary recrystallization 519
- metal matrix composites (MMCs) 172
  - advantage of 182
  - discontinuously reinforced 173
  - whiskers, use 145
- metal-organic chemical vapor deposition (MOCVD) 101
- metal oxide 642
  - nanostructures, electronic properties 713
  - metal-oxygen binding energies 283
- methyltrimethoxysilane (MTMS) 140
- $\text{MgO}_n\text{Al}_2\text{O}_3$  385
  - mechanical properties 413
  - spinel 385, 411
  - stacking fault energy of 416
- $\text{MgSiN}_2$ , crystal structure of 245
- microcracking 31, 767, 768
- microcrystalline ceria 45
- microelectromechanical systems (MEMS) 714
- micromechanical mechanisms, development 626
- micro-mechanical models 580
- microstructural elements, types 351
- microwave hydrothermal (MH) synthesis 22
- Miller indices 488, 490, 496, 505
- mixed ionic electronic conductivity (MIEC) 697
- $\text{M}_{n+1}\text{AX}_n$  phases 299
  - bonding and structure 300–303
  - elastic properties 303–307
  - electronic transport 307–313
  - list of 302
  - machinability 342
  - mechanical properties 299
    - compressive properties 336–338
    - creep 338–341
    - dislocations and arrangements 320
    - hardness and damage tolerance 329–333
    - high-temperature properties 336
    - incipient kink band microscale model 325–329
    - plastic anisotropy, internal stresses, and deformation mechanisms 321–325
    - quasi-single crystals/polycrystals, compression behavior of 329
    - R-curve behavior and fatigue 334
    - solid-solution hardening and softening 341
    - tensile properties 338
    - thermal shock resistance 333
      - properties 299
      - thermal properties
        - chemical reactivity and oxidation resistance 318
        - thermal conductivities 313–316
        - thermal expansion 316–318
        - thermal stability 318
    - tribological properties 342
- mobile dislocation walls (MDWs) 322, 326
- molecular beam epitaxy (MBE) 716
- monoclinic  $\beta\text{-Ga}_2\text{O}_3$ , crystal structure of 103
- monolithic SiC-plate heat exchanger 205
- Monte-Carlo simulations techniques 553, 810
  - 3-D microstructure, cross-section 519, 520
  - steps 519
- morphotropic phase boundary (MPB) 282, 733, 734
  - vicinity, intermediate phases 734
- Mott–Schottky model 705, 717
  - approximation 702
  - conditions 708
  - electrons/holes, space charge profiles 705
- $\text{MSi}_2\text{O}_2\text{N}_2$  oxynitrides 245
- M-Si-Al-O-N systems 248

- oxynitrides 230
- M-Si-O-N liquid phases 247
- multianvil pressure apparatus (MAP)
  - synthesis 61
- multi-axial stress field, Weibull
  - distribution 549
- multiferroics 763
  - magnetoelectric properties 763
- multilayer ceramic capacitors (MLCC) 437
- multilayer ionic conductors 717
- multiwalled carbon nanotubes (MWCNTs)
  - 149
- n**
- NaCl 484
  - single crystal, equilibrium shape 498
  - structure 486, 491
  - surface energy 486
  - type ceramics 484
  - unit cells, clinographic view 484, 485
- nanocrystallines 78, 719
  - anatase 22
  - B<sub>4</sub>C 151
  - gallium oxide nitride ceramic 120
  - MgO 15
  - YSZ ceramics 40
- nanodimensioned ceramics 723
  - physical and chemical properties 723
- nanofiber, preparation 713
- nanometer-thin glass grain boundary films
  - crystallization of 11
- nanometric boron carbide particles
  - CVD 151
- nanometric carbon black 151
- nanoporous SnO<sub>2</sub> elements 712
- nanostructured ceramics 697
  - case study 710–722
  - dye-sensitized solar cells 719–722
  - ionic/mixed conducting materials, interfaces 714–718
  - lithium-ion battery materials 718
  - nanostructured sensor films 710–714
  - charge carrier distributions, nanostructure influence 708–710
  - electrical conduction, introduction 697
  - introduction 697–699
  - observed conductivity, space charge profiles effect 707
  - semiconducting Ceramic Materials, Space Charge Layers 699–707
- nanostructures 698
  - 1-D/2-D/ 3-D systems 698, 699
  - hierarchy 699
  - schematic depiction 698
  - sensor films 710–714
  - Y<sub>2</sub>O<sub>3</sub> 518
  - microstructure evolution 518
  - by two-step sintering 518
- nano-TiO<sub>2</sub> coating
  - hydroxyapatite layer formation, cross-sectional view of 27
- nanowires, synthesis 819
- National Institute of Advanced Industrial Science & Technology 689
- natural plants
  - morphology 171
- Nd<sub>2</sub>CuO<sub>4</sub>, T'-tetragonal structure 268
- Nd<sub>2</sub>O<sub>3</sub>-Yb<sub>2</sub>O<sub>3</sub>
  - thermal conductivity 38, 39
- neutron diffraction 274
  - spectra 316
- nierite (Si<sub>3</sub>N<sub>4</sub>) 62
  - unit-cell parameters 62
- nitric oxide (NO) reduction 104
- nitride-based structures 230
- nitride compounds 91
  - development 229
- nitrogen atmosphere 152, 167
- nitrogen pyroxene MgYSi<sub>2</sub>O<sub>5</sub>N
  - atomic arrangement 252
- nitrogen-rich M-Si-Al-O-N oxynitrides 230
- noise equivalent power (NEP) 123
- nonagglomerated powders 47
- nonmetallic crystal 669
  - high thermal conductivity 669
- nonmolecularity 439, 441, 444, 445, 447, 449–451, 455, 469
- nonoxide ceramic materials 668
  - intrinsic thermal conductivities 668
  - sintering 672
  - thermal conductivity 679, 693
- nonoxide ceramics 642
- nonstoichiometric spinel 388
- nonstoichiometry 437, 438, 442, 444
  - re-equilibration 462–476
  - defect diffusivities 475
  - donor-doped BaTiO<sub>3</sub> 468–475
  - undoped/acceptor-doped BaTiO<sub>3</sub> 464–468
  - relaxations 464
- nonstoichiometry re-equilibration process 462
- no poling process 773
- novel  $\gamma$ -Si<sub>3</sub>N<sub>4</sub> phase, synthesis 61
- NT 154 579–582
  - cavitation creep model 593
  - cavity size distribution evolution 591
  - creep-controlling process 580

- creep rates 583
  - creep resistance 579
  - tensile creep curves 582
  - volume fraction of cavities 589
  - n-type semiconductor 437, 703
  - nuclear/electron configurations
    - features 261
  - nuclear magnetic resonance (NMR) spectra 137
  - measurements 801
  - nucleation process 653
- o**
- on-site electron-electron coulomb energies 276
  - orientation distribution function (ODF) 755
    - integrations 755
  - oriented consolidation of anisometric particles (OCAP) technique 752
  - Orowan's equation 650
  - orthorhombic  $\text{CaZrO}_3$ 
    - inter-octahedra proton, dynamical simulations 286
  - Ostwald's rule 132
  - oxalate coprecipitation method 45
  - oxide-ion conductors
    - BIMEVOX family 267
  - oxide perovskites 271, 292
  - oxonitride compounds 91
  - oxygen 461
    - activity 462
      - conductivity relaxation 471
      - thermodynamic situation/expected diffusion profiles 472
      - vs. defect diffusivities 477
      - vs. reciprocal temperature 462
      - vs. thermodynamic factors 476
    - deficient compounds 267
    - nitrogen exchange 290
    - nitrogen disorder 110
    - partial molar enthalpy 462
      - vs. nonstoichiometry for undoped  $\text{BaTiO}_3$  463
  - oxygen nonstoichiometry 456–462, 469
    - vs.  $\text{BaTiO}_3$  456
    - chemical diffusivity vs. oxygen activity 465
    - control 456
    - experimental reality 460–462
    - in general 457–460
    - vs. oxygen activity 461
    - vs. partial molar enthalpy of component 459
  - oxygen vacancies 771
    - accumulation 771
    - oxygen vacancy agglomeration model 771
    - oxynitride 108, 231
      - field 231
      - glass ceramics 248, 249
        - B-Phase 249, 250
        - Iw Phase 250
        - Nitrogen Pyroxenes 251, 252
        - U-Phase 250, 251
        - W-Phase 251
      - properties 290
      - structures 230
    - oxynitride glasses 66, 246–248
      - feature 247
    - oxynitride phosphors 80, 81
- p**
- paraelectric state 279
  - partially stabilized zirconia (PSZ) 32
    - Ca-PSZ 34
    - Mg-PSZ 32–34
    - plasma-sprayed zirconia 38
    - Y-PSZ 34
  - particle-matrix interface 174
  - particular oxides, dislocations 392
    - aluminum oxide
      - basal slip 406
      - Castaing law 406
      - deformation twinning 408–410
      - dipoles and climb dissociation 407, 408
      - dislocation-dissociation 406
      - prism-plane slip 406, 407
      - stacking fault energy 408
      - Verneuil crystals 405
    - climb vs. glide dissociation 422, 423
    - fluorite structure, oxides
      - dislocation-dissociation 401, 402
      - uranium oxide 400, 401
      - zirconia 398–400
    - forsterite 417
      - crystal structure 417
      - water-weakening/dislocation-dissociation 418, 419
    - $\text{MgO-Al}_2\text{O}_3$  spinel single crystals
      - dislocation-dissociations 415–417
      - mechanical properties 413
      - slip planes 414, 415
    - non-oxide ceramics
      - silicon carbide 421
      - silicon nitride 422
    - oxides
      - cubic rare-earth sesquioxide structure 420
      - garnet structure 420, 421
      - slip systems 419
      - YAG 420, 421



- perovskite structure, oxides 410
- SrTiO<sub>3</sub>, inverse brittle-to-ductile transition (BDT) 410, 411
- strontium titanate, dislocation-dissociation 411–413
- rock-salt structure, oxides
- magnesium oxide 393
- stoichiometry, effect 393–396
- transition metal oxides 393–396
- rutile structure, oxides
- titanium oxide 402
- silicon oxide
- dislocation-dissociation 404, 405
- hydrolytic weakening 403, 404
- polymorph 402
- Wurtzite structure, oxides
- BeO, dislocation dissociation 397, 398
- beryllium oxide 396, 397
- zinc oxide 398
- particulate/liquid hybrid mixtures 140
- Pauling's rules 235, 251
- Pb-based ferroelectric thin films 753
- Pb-containing perovskites 292
- Peierls barrier 383
- Peierls stress 382, 393
- perfect single crystal 773
- polarization 773
- perovskiteABO<sub>3</sub> structure 262
- perovskite catalysts
- designing strategy 291
- Perovskite crystal structure 732
- perovskite families
- characterization 289
- perovskite oxides
- B-site vacancies 271
- electrostatic Madelung energy, ionic compounds 274
- metallic conductivity 275
- thermal stability 291
- perovskites 761
- chemical/catalytic properties 289–292
- synthesis 292
- crystal chemistry 259
- ionic transport, computer modeling 288
- physical properties 281
- spectroscopic studies 282
- structural family 264
- perovskites, crystal structure
- ABO<sub>3</sub> perovskite 259
- AO<sub>3</sub> layers, polytypes 264, 265
- cation ordering 269, 270
- ideal perovskite structure 259, 260
- nonstoichiometry
- anion-deficient perovskites 272–274
- anion-excess nonstoichiometry 274
- A-site vacancies 270, 271
- B-site vacancies 271, 272
- vacancy-ordered structures 272–274
- perovskite intergrowth structures
- aurivillius phases 266, 267
- ruddlesden-popper (RP) phases 266
- perovskite-related copper oxide structures 267–269
- structural distortions and phase transitions 260–264
- perovskites, physical properties 274
- ABO<sub>3</sub> ionic transport
- computer modeling 288
- thermal stability 290
- applications 289
- cation transport 287, 288
- ferroelectricity 279, 280
- ion conductivity
- oxide-ion conductivity 283–285
- proton conductivity 285–287
- morphotropic phase boundary (MPB) compositions 282
- optical properties 282, 283
- physical properties 274–277
- A-site/B-site cations 275
- colossal magnetoresistance (CMR) phenomenon 277–279
- relaxor ferroelectrics 280–282
- perovskites containing 276
- perovskites demonstrate relaxational properties 280
- perovskites exhibit 280
- perovskite structure 257, 259
- BO<sub>3</sub> array 270
- direct cation-cation interaction 274
- perovskite-type oxide structure
- periodic table, metallic elements 260
- persistent photoconductivity (PPC) 123
- phase-controlled synthesis 821
- ε phase transforms 77
- phenolic resin, pyrolysis 176
- phenomenological approach 745
- photocatalysts, redox catalysis 290
- photoelectrochemical water splitting 282
- physical vapor deposition (PVD) methods 92
- SiC
- novel applications 161
- techniques 107
- piezoelectric anisotropy
- vs. dielectric anisotropy 738
- piezoelectric ceramics 619, 752
- groups 752
- poling 619

- piezoelectric effects 258, 730
  - converse piezoelectric effect 730
  - direct piezoelectric effect 730
- piezoresponse force microscopy (PFM) 774
- plane-plane interactions 420
- plane-strain condition 373
- plasma-assisted reaction process 151
- plasma-enhanced CVD (PECVD) 151
  - boron carbide nanostructures, morphologies 152
- plastic anisotropy 321
  - brittle-to-plastic transition 321
- plastic anisotropy 331
- plastic deformation 162, 403, 421, 422, 538
- plastic-to-brittle transition 336
- plastic yield stress 531
- plate-like  $\alpha$ -SiC particles 145
- platinum electrodes 773
- PMN-PT ceramics 504, 507, 739
  - as-sintered surface 504
  - fractured surface 504
  - high-field strain response 740
  - longitudinal piezoelectric coefficient 739
  - optical micrograph 508
  - texturing 739
- Pnma perovskite structure 283
- Pnma phase 263
- point defects 437, 772
  - role 772
- Poisson's equation 702
- Poisson's ratio 618
- Poisson–Boltzmann differential equation 702
- Poisson–Schrödinger equations 710
- poly(ethylene glycol) (PEG) 820
- polycarbosilane (PCS) 141
- polycrystalline (Pb,Sr)TiO<sub>3</sub>-films 769
  - breakdown 769
- polycrystalline  $\alpha$ -SiC fibers 148
- polycrystalline alumina 4, 7, 8, 11, 12, 13, 50
  - characteristic properties of 12
  - corrosion of 13
- polycrystalline boron carbide
  - hardness 199
- polycrystalline ceramics 667
  - applications 667
  - preparation of 25
  - thermal conductivity 672
- polycrystalline ferroelectric materials 773
- polycrystalline films 141, 717
- Polycrystalline materials 750
  - functionality 750
- polycrystalline samples
  - Raman spectra 308
- polycrystalline silicon carbide 133
- polycrystalline silicon nitride
  - materials, properties 67
  - mechanical properties 67
  - microstructure 65
- polycrystalline titanium dioxide ceramics 24
  - physical properties of 25
- polycrystalline yttria ceramics 49
  - fracture toughness of 49
- polymer-pyrolysis-derived fibers (PP-fibers) 146
  - silicon carbide fibers 147
- polytypes, proportions 134
- poly vinyl pyrolidone (PVP) polymer 818
- pore-boundary separation 515, 516
  - tendency 517
- porous biocarbon monoliths
  - preparation 171
- porous silicon nitride 370, 373
  - fracture energy 372, 374
  - porosity dependence 374
  - fracture strength, porosity dependence 373
  - fracture surface 372, 375
  - microstructures 371
- positive-temperature coefficient resistor (PTCR) 437, 729
  - performance 437
- positive thermal coefficient (PTC) component 569
  - thermal shock cracks 535
  - thermistors 698
- post-HIPed composites, TEM images 182
- post-HIP process 177
  - boron carbide materials, mechanical properties 198
- Potts model 772
- power-law model 593
- Pr<sub>6</sub>O<sub>11</sub>-doped varistors 19
- Preform infiltration 173
- preparation of submicrometer-grained aluminas 6
  - pressureless sintered
    - flexural strength 166
  - pressureless sintered boron carbide 175
- pressure-pulsed-CVI (P-CVI) 170
- Primex process 173
- principle of independent action (PIA) criterion 549, 552
- prism plane slip
  - log(CRSS) vs. temperature, plots 383
- probability 545
- projected surface free energy 497
- 0001 projection, schematic representation 323

- p-type conductivity 455
- pure metallic system, principal surfaces 482
- pure rutile, synthesis of 23
- pyrocarbon (PyC) 170
- pyrochlore phase 18
- pyroelectric behavior 282
- pyroelectric materials 729
  - ferroelectrics 729
- PZT 733, 736, 758, 768, 771, 772. see also lead zirconate titanate ceramics
  - compositions 772
  - Fe-doped 746
  - fluorine doping 750
  - hardening-softening 740
  - IrO<sub>x</sub>-electrode system 771
  - longitudinal piezoelectric coefficients 739
  - nucleation 753
  - softening treatment 748
- q**
- quartz 137. see also silicon oxide
- quartz deformation 402
  - stress-strain curves 404
- β-quartz phase field 405
- quasi-1-D metal oxide nanostructures 713
- r**
- Rachinger grain boundary sliding 636
- Rachinger mechanism 635
- Raman active phonon spectra 136
- Raman microspectroscopy 137
- Raman spectroscopy 118, 180, 617
- Raman spectrum 200
- rare-earth (RE) oxides 596, 685
  - role 596
- rate controlling mechanism 637, 645, 650, 651
- rate-independent process 745
- Rayleigh coefficient 750
- Rayleigh model 746
- Rayleigh-type polarization 749
  - hysteresis loop 750
- R-curve measurements 352, 353
  - self-reinforced silicon nitrides 353
- reaction-bonded silicon nitride (RBSN) 689, 690
  - post-sintering 690
  - sintering 689
- reaction bonding (RB) process 689
  - benefits 689
- reactive templated grain growth (RTGG) 752, 754–756
- reciprocal reticular density 488
- reconstruction processes 492
  - missing row reconstruction 492
  - type 492
- reference coordinate system 506
- relaxation processes, origin 492
- relaxation time 501
- relaxor ferroelectrics 280
- relaxor materials 281
- ReO<sub>3</sub>-type framework 259
- residual porosity 8
- resistance, schematic diagram 707
- rock-salt structure 393, 394
- rutile powder, micrograph 23
- s**
- Sapphire (α-Al<sub>2</sub>O<sub>3</sub>) 405. see also aluminum oxide
  - critical resolved shear stress 429
  - crystal structure of 5
  - deformation 405
  - deformation twinning 408
    - basal twinning 410
    - rhombohedral twinning 408
  - dislocation-dissociation 406, 407
  - experimental and theoretical fault energies 409
  - faulted dipole, formation 408
  - gemstone 405
  - prism-plane slip 406, 407
  - stacking fault energy 408
  - stress-strain curves 426, 427
  - structure 390
  - work hardening 426
    - basal plane slip 426, 427
    - prism plane slip 427, 428
- sapphire single crystals 513
- SAXS data 590
- Scandia-stabilized zirconia (ScSZ) 41
  - electrolyte sheets 41
  - possesses 35
- scanning electron microscopy (SEM) 94, 625, 636, 819, 827
- Schottky barriers 17
- Schottky diode 699
- screw dislocation 502
  - successive stages 502
- ScYSi<sub>2</sub>O<sub>4</sub>N<sub>2</sub> glass ceramic
  - fine-grained microstructure 252
- secondary ion mass spectroscopy (SIMS) 113
- second nearest neighbor (SNN) interactions 491
- Seebeck coefficients
  - dependence 197
  - values 309
- Seebeck effects 197

- seeded silicon nitride
  - fracture toughness and strength 355
  - fracture toughness and strength 357
  - microstructure 356
  - R-curve behaviors 358, 359
- selected area diffraction (SAD)
  - techniques 109
- selected area electron diffraction (SAED) 62
- self-propagating high-temperature synthesis (SHS) 181
- semiconducting ceramics 704
- semiconducting metal oxides (SMOs) 710
  - n-type 711
  - sensitivity 712
- semiconducting systems, space charge
  - formation 699
- semiconductor 711
  - doping 195
  - electronic properties 711
- sensor response model 712
- sensors, class 730
- shear stress 646
- Shockley-type partials 402
- short-circuit diffusion 422
- short-range ordered (SRO) fraction 799
- [(Si,Al)(O,N)<sub>4</sub>] tetrahedral 3-D interlinked
  - arrangement 240
- [(Si,Al)<sub>2</sub>(O,N)<sub>7</sub>]-type units 242
- Si-(Al)-Y(Ln)-O-N oxynitride glasses 367
- Si<sub>2</sub>N<sub>2</sub>O, potential applications 71
- Si<sub>3</sub>N<sub>4</sub>-4(AlN)-4(YN)-2(Y<sub>2</sub>O<sub>3</sub>)-2(Al<sub>2</sub>O<sub>3</sub>)-3(SiO<sub>2</sub>)
  - system
    - Jänecke prism 68
- α-sialon 238
  - forming area 69
  - fracture surface 69
  - JEM phase, typical microstructure 241
  - materials 70
  - mechanical properties 69
  - solid solutions 69
- sialon ceramics 655
  - compressive superplastic deformation 655
  - mechanical properties 70
  - strain rate vs. stress plots 656
- sialon polytypoid phases
  - base-shared tetrahedral, undulating
    - layers 234
- sialon S-phase 240
- Si-Al-O-N system
  - aluminum nitride 232
  - phase relationships 232, 234
- sialon U-phase
  - [1 1 0] projection 250
- sialon W-phase
  - acicular microstructure 251
- sialon X-phase
  - crystal structure, projection 233
- Si-based ternary nitrides
  - luminescent properties 80
- SiBN<sub>3</sub>C, fibers produced 147
- SiCNTs, potential applications 149
- silane (SiH<sub>4</sub>)
  - gas-phase reactions 60
  - NH<sub>3</sub>, laser-induced CVD 60
- silica
  - carbon mixtures 140
  - carbothermal reduction 138
  - heat-treating a mixture 139
  - oxynitride 81
  - principles 230, 231
  - polymorphs 230
- silicon 495
  - infiltration 154
  - scanning tunneling microscopy image 495
  - vicinal surface, schematic illustration 495
- silicon atoms, nitrogen linked 244
- silicon-based ternary nitrides 78
- silicon carbide (SiC) 131, 138, 187
  - Al<sub>2</sub>O<sub>3</sub> solid solutions 168
  - alloying 163
  - AlN materials 167, 168
  - AlN system 168
  - anisotropic tribological behavior 188
  - application 202–207
  - B<sub>4</sub>C composite materials 165
  - chemical properties 186, 187
  - continuous silicon carbide fibers 146
  - polymer pyrolysis-derived silicon carbide
    - fibers (PP-Fibers) 147, 148
  - sintered powder-derived α-silicon carbide
    - fibers (SP-Fibers) 148
  - substrate-based fibers (CVD) 146, 147
  - densification 159
  - iron pair 188
  - Ohm's law 184
  - oxidation 164, 186
  - physical properties
    - electrical properties 184
    - mechanical properties 184–186
    - optical properties 183
    - thermal and calorific properties 184
  - post-densification 160
  - reaction bonding 154
  - β-SiC filaments 146
  - β-SiC nanoceramics
    - preparation 162
    - α-SiC whisker 144
    - properties, Comparison 144

- silicon carbide nanofibers 148
- silicon carbide nanotubes (SiCNTs) 149
- silicon carbide platelets 145, 146
- $\beta$ -silicon carbide powder
  - silica, carbothermal reduction 138–141
  - synthesized submicron  $\beta$ -SiC powder 141, 142
  - vapor phase, deposition 142
- $\alpha$ -silicon carbide, technical-scale production 137, 138
- silicon carbide whiskers 142
  - vapor-liquid-solid process 143
  - vapor phase formation and condensation 144
  - vapor solid reaction 144, 145
- sintered 193, 205
- SEM image 193
- submicron/nanosized powders 140, 142
- substrate material 194
- synthesis 141
- thin films 161
- TiB<sub>2</sub> composite 164, 165
- types 165
- TiC system 164
- toughened alumina 146
- transition metal diboride 164
- tribological properties 187
  - sintered  $\alpha$ -SiC ceramics 187–190
  - sliding wear application, material development 190–194
  - unlubricated friction 189
  - whisker growth 142
  - routes 143
  - VLS process 143
- silicon carbide ceramics 184, 668
  - applications 668
  - composite materials 163
    - fabrication 163
  - densification 674
  - microstructure 153, 192
  - physical properties 185, 206
  - solid-state sintering 674
  - synthetic polymers, advantage 141
- silicon carbide fibers
  - mechanical characteristics 146
  - preparation 141
- silicon carbide nanoceramics, fabrication
  - liquid-phase sintering 162, 163
  - solid-state sintering 162
- silicon carbide nanofibers 148, 155
  - synthesis 148
- silicon carbide nanotubes (SiCNTs) 149
- silicon carbide polytypes
  - crystal structures 133
  - transformation 155, 168
- silicon carbide powders, formation 160
- silicon carbide roll, ESD facility 138
- silicon carbide shapes 152
- silicon carbide single crystal 687
  - lattice 687
  - thermal conductivity 687
- silicon-carbon system 133
  - binary phase 132
  - phase diagram 132
- silicon compact 689
  - microstructures, scanning electron microscopy images 689
- silicon nitride 60, 62, 67, 356, 541, 577, 628, 692
  - AMDCB techniques, R-curve behaviors 361
  - amorphous silicon nitride ( $\alpha$ -Si<sub>3</sub>N<sub>4</sub>)
    - crystal structures 61
    - molecular dynamics (MD) calculation 63
    - tensile strength 63
    - $\beta$ -silicon nitride
      - hexagonal prisms 353
      - seed crystals 371
  - cavitation processes, Phenomenological model 594
  - compressive specimens 590
  - creep cavities, classification 588
  - creep data 582
  - creep mechanisms in commercial grades 577
    - creep behavior 582
    - creep of silicon nitride 578–580
    - experimental data, discussion 581–592
    - material characterization 580
    - motivation 577
    - NT 154 582
  - creep performance 579
  - creep research activities 578
  - creep-resistant grades 579
  - creep-strained, SAXS study 591
  - crystallographic modifications 60
  - deformation 592
  - extensive microstructural analysis 587
  - fabrication procedure, schematic illustration 356
  - fracture origin 533, 541
  - fracture toughness and strength 364
  - $\gamma$ -Si<sub>3</sub>N<sub>4</sub>
    - hardness 64
    - thermal expansion coefficient 64
  - grades 577
  - grain boundaries 596
  - grain-growth behavior 692

- Hertzian contact zone 628
- mechanical behavior 65
- microstructures 354, 360
- models of creep 592–596
- cavitation creep model in NT 154/SN 88 593–595
- lutetium, role in viscosity of glass 596
- noncavitation creep 595
- NC 132 silicon nitride 580
- properties 62
- single crystal grains 66
- solution-precipitation (S-P) 594, 597
- structural phases 60
- structural reliability 578
- superplastic deformation 361
- silicon nitride body, original formed 364
- silicon nitride ceramic 59, 60, 352, 551, 596, 638, 668
- bending strength test 551
- $\beta$ - $\text{Si}_3\text{N}_4$  crystal 668, 692
- lattice defects in grains 680–682
- lattice oxygen contents vs. thermal resistivities 683
- thermal conductivity 672, 673, 677, 678
- two dimensional microstructure 677
- comparative strain rate vs. stress plot 638
- crack velocity vs. stress intensity curve 559
- experimental data 654
- experimental temperature compensated strain rates vs. stress plots 639
- lattice defects in SiC grains 687
- lattice-purifying process 687
- mechanical behavior 67
- microstructure 684
- oxygen content 682
- polycrystalline ceramic materials 66
- processing strategy 668
- seeded/tape-cast, microstructure 693
- strength distribution 554
- strength test results 552
- tensile/compressive strain rates 639
- tensile creep 596
- tests on 560
- textured, Scanning electron microscopy images 692
- thermal conductivity 682, 688, 693
- improvements in 682–688
- of  $\text{MgSiN}_2$ -doped 586
- variation 684
- with sintering time 683
- thermal resistivity, lattice oxygen content effect 685
- silicon nitride fabricated
- microstructure 368
- silicon nitride grains 248
- silicon nitride seeds
- fibrous crystals 354
- silicon nitride single crystals
- mechanical properties
- $\gamma$ - $\text{Si}_3\text{N}_4$  63, 64
- silicon oxide
- activity 686
- chemical sensors 712
- polymorph 402
- silicon oxynitride 70
- silicon tetrachloride 142
- Si-melt infiltration 171
- Si-N bondlength 230
- $\text{SiN}_4$  tetrahedra 61
- single crystal  $\alpha$ -alumina, properties of 5
- single-crystal MgO, physical properties 14
- single-crystal seeding 355
- single-crystal ZnO, physical properties of 16
- single-crystal  $\text{ZrO}_2$ , physical properties 29
- single-edged notched beam (SENB) test method 623, 625
- single-edge precracked-beam (SEPB) method 357
- single-edge-V-notched-beam (SEVNB) fracture toughness 363
- single-walled carbon nanotubes (SWCNTs) 149
- sintered powder-derived  $\alpha$ -silicon carbide fibers (SP-Fibers) 148
- sintered reaction-bonded silicon nitrides (SRBSN) 690
- preparation 690
- scanning electron microscopy images 691
- sinter forging 371, 657
- sinter-HIP techniques 8
- sintering process 513, 514
- sintering techniques
- development of 3
- $\text{SiO}_4$  tetrahedra chains 251
- Si-Si bonds 421
- SiSiC
- seal rings 203
- slip-cast, combustion tubes 204
- Slater–Stoner–Wolfarth band-type 802
- {111}{110} slip
- dissociated screw dislocations cross-slip 381
- stoichiometric spinel, Log(CRSS) vs. temperature 382
- stoichiometries, Log(CRSS) vs. temperature 381
- slip casting 178
- SiSiC, combustion tubes 204

- slip planes
  - Kagomé layer 415
  - oxides, spinel structure 414
- slip systems
  - in oxides 391
- $\text{Sm}_3\text{Si}_6\text{N}_{11}$ 
  - atomic arrangement 244
- small-angle X-ray scattering 590
- SMO wire 712
  - conductive pathway 721
- SN 281 581, 585
- SN 88 581, 583
  - cavitation creep model 593
  - cavity formation 595
  - creep asymmetry 585
  - creep behavior 586, 587
  - multigrain junction cavities 588
  - strain rates 584
  - stress-strain rate dependence 586
  - tensile and compressive creep curves 583, 584, 287
  - tensile creep cavities 592
  - two-grain junction cavities 589
  - volume fraction of cavities 589
- sodium silicate
  - water, leaching 30
- sole transitional process 748
- sol-gel method, see colloidal methods
- sol-gel synthesis routes 102
  - nanostructured SiC, morphologies 148
- solid/liquid interfaces 502
  - features 502
  - first layer, structure 503
  - type 502
- solid/solid interfaces 505
  - fundamentals 505
  - structure and energy 508
  - symmetry dividing plane 506
- solid oxide electrolyzer cells (SOECs) 283
- solid oxide fuel cells (SOFCs) 258, 697
  - oxide electrodes 288
- solid-state diffusion 438
- solid-state electrochemistry 697
- solid-state-sintered 186
  - aluminas 4
- solution hardening
  - oxides
    - aliovalent cations 429, 430
    - isovalent cations 428, 429
- solution-precipitation process 650, 652
  - schematic representation 651
- solution-precipitation processes 683
- space charge barrier 699
- space charge density 709
  - space charge layers, schematic diagram 718
- space charge models 699, 707
  - applicability 707
- space charge potential 700, 701
- spark-plasma-sintered boron carbide 179
- spark plasma sintering (SPS) 15, 74, 155
- sphalerite structure 396
- S-phase, orthorhombic structure
  - atomic arrangement 241
  - $[(\text{Si},\text{Al})_{10}(\text{O},\text{N})_{25}]$  structural unit 242
- spinel crystals
  - stress-strain curves 425
  - work hardening 424–426
  - work softening 424–426
- spinel grains 18
- spinel-structured gallium oxonitride 120, 121
- spin-spin interactions 275
- spray deposition process 173
- spray gun, aluminum alloy 173
- $\text{Sr}_3\text{Ln}_{10}\text{Si}_{18}\text{Al}_{12}\text{O}_{18}\text{N}_{36}$ 
  - schematic representation 246
- sintered reaction-bonded silicon nitrides (SRBSN) 690
  - thermal conductivity 690
- short-range ordered (SRO) 810
- $\text{SrTiO}_3$  crystals
  - perovskite structure 259
  - yield stress vs. temperature 412
- stacking of {111} planes
  - in spinel viewed 389
- stoichiometric boron carbide
  - densification 175
- stoichiometric spinel 381
- strain rate
  - vs. stress, summary log-log plot 340
- strain transient dip tests (STDTs) 340
- stress intensity factor 542, 607, 612, 615, 617
  - expression 609–611
  - fracture toughness, defined 543
- stress-strain behavior 172
- stress tensor, components 543
- structural ceramics 621. see also silicon nitride
- structural elements
  - ceramics 352
  - fibrous grain-aligned porous silicon nitrides
    - dense silicon nitrides 375, 376
    - porous silicon nitrides 370
    - sinter-forging technique 374, 375
    - tape-cast porous material 371–374
  - fibrous grain-aligned silicon nitrides
    - large grains 355–361
    - small grains 361–364

- grain boundary phase control
  - fracture resistance 365–367
  - heat resistance 368–370
  - self-reinforced silicon nitrides 352–355
  - well-organized control 351
  - sub-critical crack growth (SCCG) 544, 560, 567
  - consequences on fracture 561
  - crack length vs. time 562
  - crack velocity vs. stress intensity curve 559
  - exponent 560, 561, 562, 565
  - lifetime and influence 559
  - submicrometer aluminas 7
  - submicrometer-grained aluminas 7
  - submicron boron carbide powder 178, 181
  - submicron-sized microstructure 155
  - superhard compounds 131
  - superplastically deformed silicon nitride 362, 363
  - superplastically sinter-forged body 364
  - superplastic forging
    - schematic illustration 362
  - superplasticity 633, 649, 659
    - accommodation processes 643–656
    - GBS accommodated by diffusional flow 643–648
    - GBS accommodated by dislocation motion 648
    - shear-thickening creep 655
    - solution-precipitation model for creep 649–655
    - applications 656–659
    - creep mechanism 649
    - definition 633, 634
    - macroscopic/microscopic features 634–640
    - multiscale nature 659
    - research in 660
    - strain rate 633
    - stress exponent 659
  - surface energy 480–486, 493, 501
    - atomic configuration, Schematic illustrations 482
    - calculation 484
    - enthalpic aspect 495
    - origin 486
    - plot 493
    - reduction of anisotropy 504
  - surface-related phenomena 481
  - surface work 481
  - symmetrical tilt grain boundaries (STGBs) 507
  - synchrotron X-ray data 774
- t**
- tantalum mononitride (TaN) 77
  - tape-casting process 752, 753
    - schematic 752
  - tape-cast silicon nitride 357, 368
    - fracture toughness and strength 357
    - microstructure 356
    - R-curve behaviors 358
  - TbMnO<sub>3</sub> 762
    - magnetic and dielectric properties 762
    - magnetic field 763
    - polarization reversal 764
    - magnetocapacitance effect 763
    - spin frustration effect 761
  - templated grain growth (TGG) 752, 753
    - heterotemplated grain growth 753
    - microstructure evolution, Schematic 753
    - reactive grain growth 753
  - tensile stresses 542
    - flaws 542
    - stress concentration 542
  - tentative SiC-AlN phase diagram 168
  - ternary nitrides 78
    - schematic drawing 92
    - ternary silicon nitrides
      - alkaline earth silicon nitrides 79
      - LaSi<sub>3</sub>N<sub>5</sub> 79
      - lithium silicon nitride (LiSi<sub>2</sub>N<sub>3</sub>) 80
      - MgSiN<sub>2</sub> 78, 79
  - terrace-step-kink (TSK) model 495
  - TETRABOR boron carbide
    - venturi blast nozzle, cross-sectional area 208
  - tetragonal zirconia polycrystals (TZP)
    - typical properties of 36
    - ceramics 35
  - tetrahedral 3-D interlinking 242
  - textured materials, advantages 739
  - texture engineering, aspects 750
  - theoretical density (TD) 145
  - thermal barrier coatings (TBC) 35, 39
    - thermal conductivity 351, 667
    - of dielectric ceramics 668–671
      - in adamantane compounds 669–671
      - of nonmetallic crystals 668
      - β-Si<sub>3</sub>N<sub>4</sub>, thermal conductivity, estimate 671
    - high-thermal conductivity nonoxide ceramics' 672–688
      - of composite microstructures 672–679
      - improvement via purification of grains during sintering 679–688
  - introduction 667



- $\text{Si}_3\text{N}_4$  ceramics, mechanical properties 688–693
- anisotropic thermal conductivity in textured  $\text{Si}_3\text{N}_4$  692
- thermal conductivity/mechanical properties, harmonic improvement 688–692
- temperature dependence 669
- thermal conversion 117
- thermal expansion anisotropy, correlation 318
- thermal expansion coefficient 198
- thermal shock 534
  - cracks 534
  - failure 534–536
- thermal stresses 534
- thermodynamically stable phase 94
- thermodynamic approach 737
- thermodynamic factor 466, 467
- thermoelectric devices
  - materials, suitability 197
- thermoreflectance microscopy 671
- thin film 774
  - clamping in 774
  - glassy film 7
  - PVD deposition 76
- third-generation solar technology 720
- third-order Birch–Murnaghan equation 110
  - parameters 110
- three-dimensional corner-sharing tetrahedral lattice 814
- threshold stress 640, 646
- $\text{Ti}_2\text{AlC}$  compounds 304
  - cyclic compressive stress-strain curves 325
- $\text{Ti}_3\text{GeC}_2$  samples
  - post-quench four-point flexural strength 333
- $\text{Ti}_3\text{SiC}_2$  339, 341
  - basal planes 342
  - bulk moduli 341
  - creep parameters, Summary 339
  - cycle, fine-grain sample 337
  - engineering stress-strain curves 330
  - fine-grained microstructures 338
  - grain, load-displacement curve 332
  - loaded tension/compression 338
  - oxidation 319
  - polycrystalline samples, crack fatigue behavior 334
  - response
  - stress-strain curves 324
  - tensile stresses 338
- time-of-flight (ToF) neutron diffraction 755
- titania single crystals
  - physical properties of 24
- titanium, oxychlorides 23
- titanium dioxide ( $\text{TiO}_2$ ) 20, 701, 721
  - anatase 26
  - applications of 25–27
  - biocompatibility of 27
  - concentration of electrons 721
  - crystal structure 20, 21
  - mesoporous dye-sensitized 721
  - natural sources and production 22
    - anatase, synthesis of 22, 23
    - brookite, synthesis of 23, 24
    - rutile, synthesis of 23
  - n-type semiconductor 26
  - polycrystalline titania 24, 25
  - polymorphs 20
    - anatase 20
    - brookite 20
    - properties of 24
    - rutile 20
  - relative permittivity 704
  - single-crystal, properties of 20, 21
  - space charge properties 701
  - surface area 721
- titanium nitride ( $\text{TiN}$ ) 75
  - characteristic properties 76
  - powders 76
  - properties 76
  - structure 75
  - synthesis 75, 76
  - thin film 75
- titanium-oxygen interstitial defect 429
- ( $\text{TM}$ ) $\text{O}_6$  octahedron 792
  - octahedral and tetrahedral environment 793
    - 3d one-electron levels, Crystal-field splitting 793
  - symmetries 792
  - valence-band orbitals 792
- toughened ceramics 612–620
  - bridged crack wake methods 612
  - bridged interface methods for increasing fracture resistance 613–620
    - crack bridging by second phase 616
    - crack growth resistance toughening 614–616
    - ferroelastic toughening 619
    - grain bridging 613
    - phase transformation/dilatant zone toughening 617–619
  - frontal wake methods 612
  - microstructural design methods 613
  - toughening by crack tip process zone effects 620

- toughening mechanisms 365
- transition metal nitrides 77
- transition-metal oxides (TMOs) 791
  - applications 791, 792
  - chromium dioxide 800–802
  - 3d orbitals, properties 792
  - ferrites 797–800
  - iron oxides 793–797
  - magnetic properties 791, 794–797
  - structures 793
  - manganese oxide phases 802–821
  - magnetic properties 807
  - manganese dioxide nanoparticles, magnetic properties 821
  - manganese oxide structures 804–807
  - MnO<sub>2</sub> nanostructures, synthesis 815–821
  - oxygen defects 394
  - single crystals, Plastic deformation 393
- transmission electron microscopy (TEM) 62, 181, 320, 580, 767, 818, 820
- tribological applications
  - SiC ceramics, physical properties 192
- triglycine sulfate (TGS) 743
- trimethylgallium 101
- triple junction wetting 521
  - 2-D section parallel 521, 742
- u**
- ultrafine-grained titania powders
  - preparation of 22
- ultraviolet (UV) emitters 93
  - wavelengths 102
- UO<sub>2+x</sub>, dislocation structure 401
- v**
- vanadium on a magnesium oxide support (V/MgO) 14
- vanadium oxyhydroxide 828
  - magnetization 828
- van der Waals forces 71
- vanVechten predicted phase transitions 95
- vapor-liquid-solid (VLS) process 143
  - whisker 143
- vapor phase formation 144
- varistor-forming oxides (VFOs) 19
- VC 504
  - adsorption 504
  - effect 504
  - role 504
- Verneuil method 106
- Verwey transition 796
- Vickers hardness 162, 182, 331
- Vickers indentations 358, 624, 625
  - loads 331
- Vickers indenter 621
  - diamond-tipped 622
  - on glass 623
  - rows 624
- virtual charge transfers 808
- volatile organic compounds (VOC) 20
- voltage-current characteristics (VCC) 20
- w**
- Wakai's model 646, 651
  - cation diffusion energy 653
  - creep equation 652
  - creep laws 646
  - equations 651
  - free energy 653
  - modification 653
  - stress exponent vs. applied stress 652
  - apparent values 654
- WC crystal 504
  - coarsening rate 504
  - grain growth behavior 504
  - scanning electron microscopy images 505
- weakest-link hypothesis 545
- wedge effects 370
- Weibull analysis 554
- Weibull distribution function 550, 552
  - application 550
- Weibull equation 556
- Weibull material 555, 558
  - bimodal flaw size distribution 557
  - flaw sizes, relative frequency 556
- Weibull modulus 357, 359, 547, 548, 550, 553, 564, 568
  - confidence intervals in 554
- Weibull statistics 357, 545, 546
- Weibull theory 558
- white light-emitting diode (LED)
  - schematic function 80
- Wiedmann–Franz law 313
- Wiener's model 674, 676
  - two-phase systems 675
- Wiener method 682
- Willis defects 401
- Wulff plot 486
  - equilibrium shape 487
- Wulff theorem 489
  - analytical version 498
  - graphical interpretation 489
- wurtzite crystal structure 16, 95, 167
  - stacking fault energy 397, 398
- wurtzite-structured GaN 123
  - O/N substitution 123, 124
- wurtzitic boron nitride (w-BN) 72

**x**

- X-ray absorption spectroscopy (XRAS) 106
- X-ray diffraction (XRD) analysis 133, 581, 755, 825
  - amorphous phase 319
  - intensity 768
  - symmetry-dependent reflections 756
- X-ray photoelectron spectroscopy (XPS) 179
  - spectra 112
- X-ray specular reflectivity (XRSR) 771

**y**

- $\text{Yb}_2\text{Si}_2\text{O}_7$  591
  - distribution 591
  - scattering 591
  - size distribution 592
- YN- $\text{Si}_3\text{N}_4$  system 236
- Young's modulus 12, 373, 622
- Y-Si-Al-O-N system 249, 250
  - B-phase produced 249
- $\text{Y}_2\text{Si}_4\text{N}_6\text{C}$ , atomic arrangement 238
- $\text{Y}_2\text{Si}_3\text{O}_3\text{N}_4$ ,  $^{29}\text{Si}$  MAS-NMR spectrum of 235
- yttria
  - ceramics, use 49
  - Poisson ratio 50
  - powder
    - morphology 49
    - ultra-fine-grained 49
- yttria-stabilized tetragonal zirconia polycrystal (YTZP) ceramic 634, 638, 640, 644
  - absorption free energy 648
  - as-received/tensile-deformed specimens 635
  - borosilicate-doped 642
  - deformation 636
  - dislocation cores 647
  - grain boundary sliding, microstructural invariance 637
  - layers 657
  - segregation energy 648
  - submicron-sized 641
  - superplastic behavior 645
  - superplasticity 636
- yttria-stabilized zirconia (YSZ) 35, 658, 697, 714
  - bicrystal 512
  - disadvantages 39
  - layer 39
  - nanostructured thin films 41
- yttria tetragonal zirconia ceramics 640
  - strain rate vs. stress 640
  - polycrystals, dislocation driven model 646
- yttrium-aluminum-garnet (YAG) 48, 420
  - powder 157

yttrium-aluminum ratios 365

- yttrium atoms 641
  - segregation 641, 647
- yttrium-iron-garnets 48
- yttrium oxide 48
  - ceramic material 48
  - microstructure 50
  - optical ceramic 50
  - thin economical layer 51
  - $\text{SiO}_2$  additive ratios 685
  - stabilized  $\text{ZrO}_2$ 
    - plastic deformation 399
    - single crystals 399

**z**

- Zener drag effect 518
- Zener polarons 278
- zincblende (zb)
  - gallium nitride crystallizes 96
  - phase 97
  - structured GaN, experimentally/theoretical investigations 97
  - structures 95, 96
  - type phase 112
- zinc oxalate dihydrate, thermal decomposition 16
- zinc oxide (ZnO) 15, 516
  - applications
    - ceramics 19
    - varistors 17–19
  - based diluted magnetic semiconductors (DMS) 20
  - crystals
    - properties 16
    - structure 16
  - nanocolumns, scanning electron microscopy images of 20
  - nanocrystals 16
  - nanowire sensitivity 713
  - natural sources and production 16
  - n-type semiconductor 17
  - pure/ $\text{Bi}_2\text{O}_3$ -doped 516
  - SEM/TEM images 516
- zirconia 617, 619
  - aging-related nucleation 42
  - based ceramics 27
  - based materials 34
    - surface monoclinic phase fraction vs. exposure time 36
  - biomedical-grade 42
  - chlorination 29
  - crack growth resistance curves 617
  - electrolytes 40, 258
  - fuel cell, schematic diagram of 41

- melting temperature 32
- metastability 42
- orthorhombic 33
- particles, microcrack formation 31, 32
- phase transformation 31, 42, 619
- polymorphs, lattice parameters of 28
- Raman spectroscopy, monoclinic phase content 618
- single crystals, physical properties of 29
- thermal decomposition 29
- yttria 34
- zirconia-toughened alumina (ZTA) 4, 31, 37
- zirconium oxide 27–28
- ZrO<sub>2</sub> polymorphs, crystal structures 28
- ZrO<sub>2</sub>-Y<sub>2</sub>O<sub>3</sub> single crystals, yield stresses 400