

Index

Note: Page numbers followed by “b”, “f”, and “t” indicate boxes, figures, and tables respectively.

A

- American Physical Society, 10
- Aramid fibers
 - Kevlar®, 59
 - properties, 58–59, 61t
 - sleeve and tapes, 58–59, 59f
 - stress–strain curves, 59, 60f
 - Twaron®, 59
- Arc discharge, 104, 104f–105f
- Armchair nanotube, 81, 81f

B

- Bismaleimides, 57

C

- Carbon allotropes, 74–75, 74f
 - Carbon fibers, 58, 59f, 61t
 - Carbon nanotubes (CNTs)
 - advantages, 209–213
 - applications, 119
 - Adidas adizero shoes, 192, 192f
 - antibody functionalized single-walled carbon nanotubes, 196–197, 196f
 - artificial muscles, 194, 194f
 - bicycle with frame, 190, 192f
 - catalytic materials, 199, 199f
 - CNT-based organic solar cells, 197–198, 198f
 - drug delivery systems, 196–197
 - Easton baseball bat, 190, 191f
 - electrochemical supercapacitor electrodes, 197, 197f
 - electromagnetic interference shielding, 201, 201f
 - electrophoretic display (EPD) e-paper, 194–195
 - hard tissue engineering, 194–195
 - hockey sticks, 190, 191f
 - hydrophilic microbiosensor, 192–194, 193f
 - hydroxyapatite formation, collagen composite, 195, 196f
 - lithium-ion battery, 199–201, 200f
 - paper-thin cylinder, 199, 200f
 - printed CNT transistors, 201–202, 202f
 - sail boat, 190, 191f
 - Samsung display, 194–195, 195f
 - sound frequency electric currents, 199
 - synthetic gecko tape, 194, 195f
 - tennis racket, 190, 190f
 - thermo-acoustic effect, 199
 - water molecules, 198, 198f
 - wind turbine blades, 192, 193f
 - chemical fibers and yarns, 228
 - cost, 213, 214t
 - and production capacity, 106–107
 - vs. property analysis, 220–221
 - covalent functionalization, 94, 97f
 - double-walled carbon nanotube, 75–76, 76f
 - electrical conductivity, 88, 88t
 - fiber composites, micromechanics modeling
 - critical length, 218–219
 - effective fiber, 218–219
 - fiber volume fraction, 218
 - Halpin–Tsai equations, 217
 - hybrid composites, 219–220
 - materials cost, 219–220
 - nanotube reinforced composites, 217
 - single reinforcing phase, 218
 - strength efficiency factor, 219
 - tensile strength, 218–219
- fitting experimental data, 241–244, 242f–243f
- graphene sheet, 75–76
- hollow carbon fibers, 77, 78f
- Halpin–Tsai model, 217
- health risk and safe disposal
 - asbestos fibers, 109
 - electrolyte imbalance, water consumption, 109
 - environmental precaution, 110–111
 - glove box, 110, 111f
 - granulomas, 109–110, 110f
 - MSDS, 111–119, 111b
 - toxicological effects, 110
- hybrid composites, 222
- impurities, 89
- material selection process, 220
- mechanical properties, 85t
 - arc discharge, 84
 - covalent bond, 83
 - density and price, 223, 224t
 - nanocomposite materials, 208, 210t
 - SEM, 84, 84f
 - single-walled carbon nanotubes, 86–87, 86f
 - specific resistance value, 83–84
- models development, 235–240, 236f
- multi-walled carbon nanotube, 75–77, 76f, 79f

- Carbon nanotubes (CNTs) (Continued)**
- non-covalent functionalization
 - adsorption models, 94, 96f
 - block copolymers, 94, 96f
 - single-walled carbon nanotube, polyethylene polymer chain, 94, 95f
 - patents and published articles, 77, 80f
 - polymer matrix composites (*see* Polymer matrix composites)
 - production methods
 - adaptations and improvements, 103–104
 - arc discharge, 104, 104f–105f
 - carbon monoxide conversion, 106, 108f
 - CVD, 105–106, 106f–108f
 - laser ablation, 104–105, 105f
 - properties, 213, 214t, 222, 222t
 - published articles and patents, 208, 209f
 - purification and oxidation
 - characteristics, 89–90, 92
 - hydrochloric acid, 90, 90f
 - metal oxides, 90
 - oxidation temperature, MWCNTs, 92f, 92b
 - oxidation time, MWCNTs, 93f, 93b
 - single-walled carbon nanotube defects, 90, 91f
 - solvents and polymer matrices, 93
 - reinforcement efficiency
 - applications, 234
 - 3D network, 234
 - epoxy system, elastic modulus, 234, 235f
 - percolation threshold, 234
 - properties, 234
 - semiconductor carbon nanotubes, 87, 87f
 - series and parallel
 - composite modulus, 237
 - filler volume fractions, 237–238
 - large-diameter CNT bundles, 236
 - nano-filters, 236
 - percolation threshold, 238
 - switching function, 237–238
 - three-phase composite system, 236, 237f
 - single-phase reinforced epoxy composites, 222
 - single-walled carbon nanotube, 75–76, 76f–77f
 - stiffness, 223–226, 226f–227f
 - structure
 - armchair nanotube, 81, 81f
 - C–C bond length, 79
 - chiral vector, 78, 80f
 - graphene sheet, 74f, 77–78
 - SWCNT, 82b
 - van der Waals attractions, 82
 - zigzag hexagonal lattice, 78
 - surface modification, 213
- Takayanagi model, 238–240
- elastic modulus, 240–241, 240f
 - tensile strength, 209–213, 213f, 223, 226f–227f
 - thermal conductivity, 88–89, 89t
 - tight-binding, superposition energy, 88
 - types, 75–76
 - Young's modulus and break up elongation, 209–213, 213f
- Ceramic matrix composites (CMC), 50**
- Ceramics, 61**
- Chemical vapor deposition (CVD)**
- apparatus, 105, 106f
 - nanotube synthesis, 105–106, 108f
 - structures growth, 105–106, 107f
- Composites**
- advantages and disadvantages, 61, 62t
 - applications, 69
 - Boeing aircraft structure, 64
 - Boeing 787 Dreamliner, 65, 66f
 - Bulletproof vest, 65–68, 67f
 - concrete columns, 68, 68f
 - Enertia, electric bike, 65, 67f
 - F-22A Raptor fighter aircraft, 63, 64f
 - Mercedes CLK Cabriolet, body components, 65, 66f
 - plastic bridge, 68, 69f
 - polymer composite biomaterials, 68–69, 70f
 - Super Jumbo Airbus A380, 65, 65f
 - wind generator with blades, 68, 69f
 - bamboo and timber, 46, 47f
 - classification, 50f
 - CMC, 50
 - fiber composites, 51, 52f
 - MMC, 50
 - particulate composites, 51, 51f
 - PMC, 51
 - structural composites, 52, 53f
 - criteria for, 45
 - definitions, 45–46
 - engineering materials
 - advantages, 45
 - ceramics, 41
 - characteristics, 38
 - metals, 38–41
 - per capita usage, 41–45, 46f
 - polymer-based composites, 41–45
 - polymers, 41, 42t
 - properties, 38, 39t
 - fiber length, fiber composites, 62–63, 63f
 - matrix phase, 46, 47f
 - function, 48
 - performance characteristics, 48

- properties, 46, 53
 reinforcements, 48–49, 49f
 aramid fibers, 58–59, 59f–60f, 61t
 carbon fibers, 58, 59f, 61t
 ceramics, 61
 functions, 49, 50f
 glass fibers, 57–58, 58f, 61t
 phase, 46, 47f
 polyester fibers, 60
 polyethylene, 60
 quartz, 60
 types, 57
 resins, 53
 bismaleimides, 57
 epoxy, 55, 55f, 56t
 ester cyanates, 57
 phenolic resins, 56–57
 polyamides, 57
 polyester, 54, 54f, 56t
 polyurethanes, 57
 silicones, 57
 thermoplastics and thermosets, 53–54
 vinyl ester, 55–56, 56f, 56t
 snail shell, 46, 47f
 teeth, 46, 47f
- CVD. *See* Chemical vapor deposition (CVD)
- D**
- Double-walled carbon nanotubes (DWCNTs), 75–76, 76f
 modified Halpin–Tsai model, 149–150
- Dual asymmetric centrifuge (DAC), 182–183, 184f–185f
- E**
- Einstein equation
 aspect ratio, 134, 135f
 vs. Guth model, 134, 135f
 reinforced elastomers, 133–134
 suspension viscosity, 133–134
 Young's modulus, 134
- Epoxy resins, 55, 55f, 56t
- Ester cyanates, 57
- F**
- Fiber composites, 51, 52f
 fiber length, 62–63, 63f
 micromechanics modeling
 critical length, 218–219
 effective fiber, 218–219
 fiber volume fraction, 218
 Halpin–Tsai equations, 217
- hybrid composites, 219–220
 materials cost, 219–220
 nanotube reinforced composites, 217
 single reinforcing phase, 218
 strength efficiency factor, 219
 tensile strength, 218–219
- G**
- Glass fibers, 57–58, 58f, 61t
 Gold and silver nanoparticles, 13–14, 16f
- H**
- Halpin–Tsai model, 139–142, 140f, 142f
 Hatta model, 158, 159f
- Health risk and safe disposal
 asbestos fibers, 109
 electrolyte imbalance, water consumption, 109
 environmental precaution, 110–111
 glove box, 110, 111f
 granulomas, 109–110, 110f
 MSDS, 111–119, 111b
 toxicological effects, 110
- High-shear mixer
 applications, 178–180
 oil emulsions, 177–178
- PU matrix composites, 178b, 179f
 rotor types, 177–178, 178f
- K**
- Kelly–Tyson approximation, 129–130
- L**
- Laser ablation, 104–105, 105f
 Lycurgus cup, 13, 15f
- M**
- Material Safety Data Sheets (MSDS), 111–119, 111b
 Matlab® simulation
 Halpin–Tsai code, 104
 mixtures, code rule, 103–106
- Metal matrix composites (MMC), 50
- Modified Halpin–Tsai model
 DWCNTs and MWCNTs, 149–150
 effective fiber modulus, 149
 fibrous composites, 147
 vs. Halpin–Tsai model, 151, 151f
 mechanical properties, 150, 150t
 micromechanics-based models, 147–148
 nanotube–matrix interface, 147
 tensile strength, 149
 Young's modulus, 148, 148f

- Molecular nanotechnology, 11
- Moore's law
- chip development, 15
 - computing power evolution, 17–18, 21f
 - integrated circuit transistors, 18, 21f
 - transistor, 15, 20f
 - transistor investors, 15, 20f
- MSDS. *See* Material Safety Data Sheets (MSDS)
- Multi-walled carbon nanotubes (MWCNTs),
- 75–77, 76f, 79f
 - modified Halpin–Tsai model, 149–150
 - oxidation temperature, 92f, 92b
 - oxidation time, 93f, 93b
- N**
- Nan model, 157, 158f
- Nanoscience and nanotechnology
- applications
 - air pollution and water, 28–29, 29f
 - aviation and space, 22, 23f
 - broken bone, healing process, 23–24
 - energy, 27–28, 28f
 - flexible color display monitor, 26, 26f
 - in food industry, 25–26, 25f
 - integrated circuit fabrication, 27
 - magnetic random access memory (MRAM), 27
 - micro and nano robots, 24–25, 24f
 - nanocapsules, 22–23, 24f
 - nano-silver crystals, 22–23
 - quantum dots, 22–23
 - sports, 30, 32f
 - textiles, 29–30, 31f
 - history, 1–2, 4–10, 12f, 14, 18f
 - American Physical Society, 10
 - atom rearrangement, 13
 - biological system, 9
 - computing machines, 11
 - electron microscopes, 8–9
 - gold and silver nanoparticles, 13–14, 16f
 - high school competition, 15–18
 - lubrication problems, 10
 - Lycrus cup, 13, 15f
 - molecular nanotechnology, 11
 - NNI, 12
 - scanning tunneling microscope, 11, 11f
 - small scale atoms, 13–15
 - timeline with events, 15, 19t
 - tiny factories, 17–18
 - Moore's law
 - chip development, 15
 - computing power evolution, 17–18, 21f
 - integrated circuit transistors, 18, 21f
- transistor, 15, 20f
- transistor investors, 15, 20f
- nano-abacus, 30, 32f
- nanofabrication, 33
- nanoparticles
- electromagnetic properties, 9–10
 - mechanical properties, 10
 - optical properties, 10
 - sinterization, 8–9
 - size effect, 8
 - thermal properties, 9, 9f
- nanoscale
- area/volume ratio, 6
 - atom density, 7
 - atoms alignment, 1–2, 2f
 - copper atom mass, 8
 - definition, 1–2
 - gold cube, specific surface area, 5–6, 5f
 - International System of Units, prefixes, 1–2, 2t
 - material outer surface, 7, 7f
 - number of atoms, 4
 - objects vs. natural organisms size, 2, 3f
 - properties, 6, 6t
 - specific surface area, 8
- SWCNTs, 31
- types, 13, 14f
- National Nanotechnology Initiative (NNI), 12
- Nielsen model, 142–145, 143t, 144f, 144t, 159–161, 160f
- P**
- Particulate composites, 51, 51f
- Periodic table, 47f
- Phenolic resins, 56–57
- Polyamides, 57
- Polyester fibers, 60
- Polyester resins, 54, 54f, 56t
- Polyethylene, 60
- Polymer matrix composites (PMC), 51
- DAC, 182–183, 184f–185f
 - electrical conductivity
 - advantages, 161
 - composite filler, 162
 - conduction path, 164, 165f
 - conductive fillers, 161
 - contact resistance, 162
 - factors, 164–167
 - percolation threshold, 161–162, 162f–163f
 - high-shear mixer, 177–180, 178f, 178b, 179f
 - magnetic stirring, 175–177, 176f
 - manufacture of, 172, 173f
 - mechanical properties

aspect ratio, 130
 constituents density, 131
 Cox model, 137–138, 138f–139f
 critical length, 128–129
 Einstein equation, 133–134, 135f
 elastic modulus, nanocomposites, 133
 elastic properties, 151
 fractions and concentrations, 131, 131t
 Halpin–Tsai model, 139–142, 140f, 142f
 Kelly–Tyson approximation, 129–130
 modified Halpin–Tsai model, 147–151, 148f, 150t
 Nielsen model, 142–145, 143t, 144f, 144t
 polymers and density, 128, 129t
 series and parallel models, 136–137, 136f–137f
 SWCNTs, 130, 130f
 tensile strength, nanocomposites, 145–147, 146f
 mechanical stirring, 177, 177f
 melt processing, 172–174, 174f
 nanosized reinforcements, 172
 preparation methods, 172
 properties
 chemical modification, 127
 molecular chemical bonds, 127, 128f
 nano-fillers aggregation, 126, 127f
 van der Waals interactions, 126
 reaction processing/in situ polymerization, 174–175, 175f
 single-screw extruder, 185–187, 186f–187f
 solution processing, 172, 174f
 sonication, 180–182, 181f–183f
 thermal conductivity
 geometric model, 154–157, 155f

glass and organic fibers, 152, 153t
 Hatta model, 158, 159f
 Nan model, 157, 158f
 Nielsen model, 159–161, 160f
 parallel model, 152–154, 154f
 series model, 153–154, 154f
 two-phase composites, 152
 three-roll mill (calender), 184–185, 186f

Polyurethanes, 57

Q

Quartz, 60

S

Silicones, 57
 Single-walled carbon nanotubes (SWCNTs), 31, 75–76, 76f–77f, 130, 130f
 defects of, 90, 91f
 mechanical properties, 86–87, 86f
 polyethylene polymer chain, 94, 95f
 Sonication
 advantages, 181
 cavitation, 180, 182f
 industrial sonicators, 182
 sodium carbonate, milling process, 180–181, 183f
 ultrasonic bath and probe, 180, 181f
 Structural composites, 52, 53f

T

Takayanagi model, 238–240
 elastic modulus, 240–241, 240f

V

Vinyl ester, 55–56, 56f, 56t