

Index

A

Abrasion resistance, of HNBR materials, 97
 Accelerators, types of, 15-17
 Acetone-diphenylamine (ADPA), 472
 Acetylene process, 3-4
 Acetyl methyl ricinoleate, 390, 395
 Acetyl tributyl citrate, 390, 393, 395
 Acid acceptor, for epichlorohydrin
 compounds, 259-262
 ACN, 481
 Acrylic elastomers-ACM, 404, 453-454
 air oven aging of
 formulations, 458-459
 soap and sulfur-cured compounds, 460
 TCY-cured compounds, 460
 compounds extracted in IRM 901 oil
 before air oven aging, 461-464
 formulations and properties, 456-457
 processing aids incorporation
 in, 484, 486-488
 Acrylic elastomers (ACMs and AEMs), 98
 Acrylonitrile-butadiene-isoprene
 (ACN/BR/IR) elastomer,
 terpolymer of, 51
 Acrylonitrile-butadiene rubber (Buna N
 and Perbunan), *see* NBR
 Adkizer RS-735, 393
 AEM, 404, 473
 processing aids incorporation in, 487
 Aerosil[®] P-972, 144-145
 Aflas[®] 100 series, 140
 AGERITE MA, 413
 AGERITE RESIN D, 413
 AgeRite Stalite S, 172
 Aging stabilizers, for HNBR, *see*
 Hydrogenated Nitrile-Butadiene
 Rubber (HNBR)
 Alkylated chlorosulfonated polyethylene,
 335-337
 Alkylphenol disulfide, 416
 ALTAX (MBTS), 420
 Aluminum trihydrate (ATH), 362

Aminox, 445
 Ammonium benzoate cured compounds, 178
 Anti-drain back valve, 189
 Antioxidants
 and comparative study, 18
 in Gechron 2000 ECO, 262
 solubility in heptane, 446
 volatility of, 445
 Antiozonants, 17-19
 in Gechron 2000/100, 263
 API TR 6JI Elastomer Life Estimation Test
 Procedures, 515
 Aranox, 445-446
 Armeen 18D, 212, 479-480, 484, 487
 Aromatic process oils, 390, 393, 398
 Arrhenius plot, of EVM insulation
 compound, 359
 Arrhenius' theory of the thermal
 acceleration, 515
 Ascium, 302
 ASTM D2000 compounds, 383
 classification system, 96, 135
 elastomers comparison, 97
 ASTM D1418 designations, 246
 ASTM 901 Oil, 445, 449
 Avoid this mistake (ATM), 389, 394, 397,
 402-404, 406
 Axel Int 216, 172

B

Bayer, 105
 Benzoates, 394
 4,4'-Bis (a-dimethylbenzyl)diphenylamine,
 440
 Bisphenol A, 420
 A, α' -Bis(t-butylperoxy)-diisopropyl
 benzene, 410, 472
 1,1-Bis(t-butylperoxy)-3,3,
 5-trimethylcyclohexane, 410
 Black thiokol FA printing rollers, 380
 Blanc Fixe, 144

Brittle point, of a specific elastomer, 500
 BR 9151 or ETP, 144
 Butadiene process, 3–4
 Butadiene Rubber (BR), 15, 397, 406, 439
 Butyl acrylate group polyacrylate elastomers, 156
 Butylated hydroxytoluene, 440
 Butyl benzyl phthalate (BBP), 390, 395, 407
 Butyl oleate (BO), 23, 390, 392, 394–395
 Butyl tallate, 394

C

Calendering, of AEM compounds, 217
 Carboxylated NBR polymers
 from Lanxess, Trade Name Krynac, 52
 liquid NBR (Nipol DN601), 52
 by Zeon Chemicals, 52
 standard grades of
 Nipol 1072, 1072CGX, Krynac X740 and X750, 82
 from Zeon Chemicals LLC, Trade Name Nipol, 52
 Carboxylated nitrile rubber (XNBR), 404, 418–419
 calendering, 481
 comparison of peroxides in, 86
 compounding XNBR rubber, 82
 process safety in, 83
 extrusion, 481
 fillers for, 85–86
 carbon black in, 87
 non-black fillers in, 88
 milling, 481
 molding, 481–485
 processing aids incorporation in, 481–485
 zinc oxide and zinc peroxide study in, 83–84
 zinc oxide/zinc peroxide compatible comparison, 85
 Carboxyl grades, low
 Nipol DN 631 and Krynac X146 and X160, 82
 Castor oil-based factice, 394
 Chemical list, 287
The Chemical Resistance Guide, 140
 Chemlok 250, 8500, 8560, 182
 Chemraz[®], 135
 Chlorinated polyethylene (CPE), 406
 applications for, 296

 chemical structure influences, 289, 290
 chlorine content role, 290
 saturated backbone of, 290
 viscosity of products, 290
 commercial grades for elastomer applications, 291
 comparison of
 peroxides in with coagents, 412
 thiadiazoles and accelerators in, 422
 compounding and factors involved, 292–293
 compounding ingredients for
 choice of CPE, 293–294
 chlorine content of, 294–295
 CPE viscosity, 293–294
 curatives choice, 295
 degree of residual crystallinity, 295
 fillers and plasticizers, 295–296
 compounds and applications, 296–298
 effect of increasing chlorine content, 292
 Chlorination process, 289
 Chloroprene (CR) rubber and compounds
 applications, 29–36
 availability in market, 11–14
 and carbon black and mineral fillers, 19
 compounding and processing principles, 14
 blends and elastomers, 14
 grades selection, 14
 division of grades, 11
 fillers and, 19–21
 influence of antiozonants on weather resistance of, 21
 and plasticizers effects, 21–22
 polymerization and copolymerization, 3–4
 processing involved, 24
 production facilities for, 3
 and resistance to fluids, fungi, bacteria, 29
 role of accelerators, 15–17
 Chlorosulfonated PE-CSM, 406
 Chlorosulfonated polyethylene (CSM)
 alkylated, 335–337
 applications
 ACSM timing belts, 341–342
 extra heavy duty mining cable jackets, 339–340
 hoses, 337
 industrial roll cover, 337–339
 uncured roofing, 340–341
 characteristics of various grades of, 305

- comparison with other elastomers, 304
 - compounding of
 - fillers, 308–313
 - plasticizers and process aids for, 313–316
 - selection of CSM, 305–308
 - cross-index of grades, 302–303
 - properties, 307
 - saturated nature of, 304
 - selection guide, 307
 - structure of, 303
 - Chrysler MSEA 235, 273
 - CM, processing aids incorporation in, 488
 - Coagents
 - comparison of peroxides in
 - CPE with, 412
 - EPDM without, 412
 - effect in peroxide cure of HNBR, 414
 - types, 414
 - Cold polymerization, *see* NBR
 - Colorable bearing seal, 182
 - Compliant seals, 497
 - Compounding ingredients, *see* specific compounding ingredients
 - resins as, 24
 - stearic acid, 23
 - Compression molding, 181
 - Conductive blacks (XC-72, N472), 144
 - Conductive roll formula, 286
 - CO, processing aids incorporation in, 487–488
 - CPE, *see* Chlorinated polyethylene
 - CR; *see also* Polychloroprene-CR
 - CR grades
 - Mercaptan-Modified (M-Grades), 8
 - (M/XD) typical accelerator systems for, 18
 - precrosslinked grades, 10
 - sulfur-modified grades, 10
 - vs.* compound/vulcanizate properties selection, 14, 15
 - XD-grades, 8–9
 - Critical oxygen index (COI), 362
 - Crosslinking mechanism
 - and factors influencing, 16, 17
 - CR vulcanizates
 - and flame retardance, 28
 - M-type vulcanizates
 - and heat resistance, 26–27
 - properties of, 25
 - and protection by antiozonants and antioxidants, 17
 - Crystallization resistant grades, 8
 - CSM (Chlorosulfonated polyethylene), 391, 397
 - calendering, 490–491
 - extrusion, 491
 - milling, 490–491
 - molding, 491
 - processing aids incorporation in, 490–491
 - CTFE (chlorotrifluoroethylene), 137
 - Cumar P-10, 479, 481
 - Curatives, for polyepichlorohydrin elastomer, 258–259
 - Cure cycle, for ACM compounds, 181
 - Cured Vamac, 212
 - Cure systems, for ACM
 - ammonium benzoate cured compounds, 178
 - for chlorine/carboxyl cure-sites, 175–177
 - for chlorine cure-site ACM, 173, 174
 - dithiocarbamates cure system, 179
 - diuron cure system, 175
 - for epoxy cure sites, 178
 - HyTemp NPC-25/SC-75175
 - Nipol AR12, AR14, and AR22, use of, 179
 - peroxide curable HyTemp PV-04, 179
 - zeonet system, 178
 - Cyclic enole derivatives, 18
 - Cyclic oxidation process, 437
- ## D
- DBEEA, 394, 402, 405
 - DBEEA (TP-95, 4226), 390, 392
 - DBEEF, 394
 - DBEEF (TP-90B, 4221), 390, 392
 - DBEP, 394
 - DBES, 394
 - DBP number, of polymers, 529
 - Diacrylate, 414
 - Diaryl-p-phenylenediamines, 440
 - Diatomaceous Silica (Celite[®] 350), 144
 - Dibutoxyethoxyethyl adipate, 116, 395
 - Dibutoxyethoxyethyl formal, 395
 - Dibutyl phthalate (DBP), 390, 392, 394, 407
 - Dibutyl sebacate (DBS), 390, 392, 395
 - Dicumyl peroxide, 106, 472
 - DIDA, 401–403

Diesel engine oil cooler O-ring
 and HNBR, 119
 Diester plasticizers, 396
 Diethyl thiourea (DETU), 17
 1,2-dihydro-2,2,4-trimethyl quinoline
 (Agerite
 Resin D, Flectol H, and Naugard Q), 114
 (see also Aging stabilizers, for
 HNBR)
 Diisobutyl adipate, 390, 395
 Diisodecyl phthalate (DIDP),
 390, 394, 401–403
 Diisononyl phthalate (DINP), 390,
 394, 401–402, 406
 Dilauryl thiodipropionate (DLTDT),
 439, 444
 2,5-Dimethyl-2,5-di(t-butylperoxy)hexane,
 410
 2,5-Dimethyl-2,5-di(t-butylperoxy)hexyne-3,
 410
 Dioctyl adipate (DOA), 390, 392,
 395, 401–402, 406
 Dioctyl azelate (DOZ), 390, 392,
 395, 401–402
 Dioctyl phthalate (DOP), 23, 116, 390, 394,
 402–403, 405–407
 Dioctyl sebacate (DOS), 390, 392,
 395, 402
 Diphenyl-*p*-phenylene diamine, 420
 Diphenyl thiourea (DPTU), 17
 Dipolymers, vulcanization
 systems for, 214
 Dipropylene glycol dibenzoate, 395
 Distearyl thiodipropionate
 (DSTDP), 444
 Dithiocarbamates cure system, 179
 Dithiodicapro lactam (DTDC), 416
 Dithiodimorpholine, 416
 4,4'-Dithio dimorpholine, 472
 Diuron cure system, 175
 Dough processes, 25
 DSC-curves, 349
 DTDM (4,40 dithio-bis-morpholine or
 Sulfasan R), 259
 Dual chlorine/carboxyl cure sites,
 of polyacrylate elastomers, 157–158
 DuPont Performance Elastomers'
 designation, 141
 Durazone 37, 445–446
 Dynamic or shaft seals, 182

E

Einstein equation, of particle reinforcement
 of liquids, 528
 Elastic response, of rubber, 522–524
 Elastomers
 degradation caused by oxidation,
 434–437, 439
 effects of
 fatigue, 436–437
 heat, 435
 light and weathering, 436
 metals, 436
 oxygen, ozone and shear, 435
 evaluations of antioxidants
 in, 445–472
 ethylene-acrylic elastomer, 455, 460,
 465–472
 HNBR, 445–455
 polyacrylic elastomer, 453–464
 inhibition of degradation, 439–444
 amines, 441–442
 phenolics, 440–441
 phosphites, 442–443
 primary antioxidants, 440
 secondary antioxidants, 442
 thioesters, 443–444
 ozone degradation, 430–434
 antiozonants, 431–433
 nonstaining triazine based antiozonants,
 433–434
 waxes and polymer antiozonants, 434
 polymeric degradation, 437–439
 selection of proper antioxidant,
 444–445
 Elastomers vulcanization agents, 409–427
 composition and trade name, 424–425
 metal oxides cross-linking, 417–420
 multifunctional cross-linking
 agents, 420–423
 peroxide cross-linking, 409–410,
 417, 419
 compounding with peroxides,
 413–415
 peroxide reactions, 410
 selection of peroxide, 410–415
 sulfur cures, 417–419
 sulfur donor cures, 415–417, 419
 suppliers, 426–427
 Emulsion-polymerized material, 346

- Energized seals, 497
- Energy industry elastomers, 496–498
- EPDM, 406, 434–435, 439
 - comparison of peroxides in without coagent, 411–412
 - cure time in, 411
 - effect of antioxidants in peroxide cure of, 413
 - scorch time in, 411
 - temperature for 10 min cure in, 410
- Epichlorohydrin-ethylene oxide copolymer (ECO), 247
- Epichlorohydrin, cure systems in, 423
- Epichlorohydrin elastomers, 248; *see also* Polyepichlorohydrin elastomer
 - autoxidation mechanism of, 252
 - extrusion of, 264–265
 - formula for, 250
 - service life of an, 251–252
- Epichlorohydrin-ethylene oxide-allyl glycidyl ether terpolymer (GECO), 247
- Epichlorohydrin-ethylene oxide elastomers (ECO), 404–405, 422
 - processing aids incorporation in, 487–488
- Epichlorohydrin homopolymer, 423
- EPM, 439
- Epoxidized octyl tallowate, 390, 395
- Epoxidized soybean oil (ESO), 390 (G-62), 393
- Epoxy side cure sites, of polyacrylate elastomers, 156
- Ethyl acrylate group polyacrylate elastomers, 156
- Ethylene/acrylic (AEM) elastomers
 - benefits of, 195
 - chemical composition, 194–195
 - commercial grades, 195–196
 - compound design
 - fillers, carbon black and mineral fillers, 204–206
 - plasticizers, 206–209
 - polymer selection, 200–201
 - release system, 201
 - stabilizer(s), 201–204
 - development of polymers, 220
 - mixing of AEM compounds
 - internal mixers, 215–216
 - roll mill mixing, 216–217
 - processing of AEM compounds
 - calendering, 217
 - extrusion, 217
 - molding, 217–220
 - product lines, 195
 - shelf stability of, 196
 - starting formulation for specific applications
 - cellular vamac, closed cell, 236–237
 - CVJ boots, 234–236
 - dampers, torsional dampers, 226–228
 - high performance automotive hoses, 225–226
 - low smoke flooring and extruded edging, 239–243
 - oil field applications, 239
 - O-rings, 234
 - roll covers, 237–239
 - seals, gaskets, and general molded applications, 221–225
 - wire and cable, 228–234
 - Vamac product line, 195
 - vulcanization, 209–215
 - vulcanized properties
 - dry heat resistance, 196
 - general fluid and chemical resistance, 197
 - low-heat performance, 196–197
 - other, 199
 - physical properties, 197–199
 - vibration damping, 197
- Ethylene-acrylic elastomer (EAM), 445, 472
 - air oven aging of formulations, 467–468
 - cell oven aging of compounds, 471
 - compounds extracted in IRM 901 oil before air oven aging, 469–470
 - formulations and properties, 465–466
- Ethylene dimethacrylate (EDMA), 355
- Ethylene-octene copolymer (EOM), comparative rheometer cure curves in, 415
- Ethylene-Propylene-Rubber (EPDM), 15
- Ethylene thiourea (ETU), 17, 258
- Ethylene Vinyl Acetate elastomers, 344–346
 - applications in, 358
 - blend component, 366
 - flame-retardant noncorrosive applications, 361–364
 - heat- and oil-resistant molded goods, 364

high-temperature insulation compounds, 358–360

classification of, 346

compounding process in

- antioxidants, 356
- curing system, 355
- fillers and plasticizers, 356

crystallinity of, 352

heat of combustion (DHc) of, 349

polymerization reaction for, 345

processing of

- calendering and fabricating, 357
- LCM salt bath curing, 358
- mixing and extrusion, 357
- molding, 358
- steam curing, 358

structure and property relationships

- crystallinity, 348–355
- glass transition temperature, 348–355
- oil resistance, 354
- polymerization and production processes, 344–346

2-Ethylhexyl diphenyl phosphate, 390, 392, 395

ETP or BR 9151

- FKM and FEPM designation, 141

ETP-S series, 140

ETU lead oxide cure system, 422–423

EVM, *see* EVM elastomers

EVM, as insulation compound

- electrical properties of, 361
- maximum service temperature, 358–359
- resistance to radiation, 360–361
- resistance to UV light, weathering, and ozone, 359–360

EVM/CM blends, in light-colored compound, 367

EVM copolymers

- thermo gravimetric measurements in nitrogen atmosphere, 348

EVM grades, 347

EVM/HNBR blends, in black filled compound, 368

EVM injection molding compound, 365–366

EVM, processing aids incorporation in, 490

Extos, 302

Extrusion and calendering, of black filled ACM compounds, 181

Extrusion, of AEM compounds, 217–218

F

Factice, *see* Vulcanized vegetable oil (Factice)

Failure life data, defined, 516–517

Fast, safe cure system, for terpolymers, 213

FEPM materials, 135

- relative oil resistance of, 140

FFKM compounds, 135

Finite Element Analysis, 517

FKM families

- and base resistance grades of, 140
- low temperature measurement methods on, 142
- major process aids for FFKMs, 145
- permeation of *vs.* NBR, HNBR, and FVMQ, 142
- plasticizer, Dai-EI[®] Γ-101, 146
- relative fuel resistance *vs.* low temperature flexibility of, 141
- relative oil resistance of, 140

Flame-Resistant Noncorrosive Compound (FRNC)

- influence of ATH amount on critical oxygen index in EVM, 362
- influence of vinyl acetate content on limiting oxygen index in EVM, 363

Flame-retardant noncorrosive applications, *see* EVM

Fluorocarbons (FKM), 98, 496; *see also* FKM families

Fluoroelastomers, 134

- advantages of using, 135
- base-resistant grades of FKM, 140
- chemical resistance
 - of FFKMs *vs.* other elastomers, 136
 - of major FKM families, 137
- choice of pigments, 145
- compounding for purposes, 146
 - compression set resistance, 148
 - for elongation at break, 146–147
 - hardness, 146
 - for tensile strength, 146–147

- compression set resistance vs. other elastomers, 135
 - curing with
 - Bisphenol AF and metal oxides, 143
 - peroxide curing systems, 143
 - fillers used in
 - effect of filler level on compression set and physical properties, 149
 - MT and SRF black fillers, 144
 - white fillers, BaSO₄, 144
 - FKM, 406
 - cross-linking agents for, 421
 - processing aids incorporation in, 483–484
 - history and suppliers of, 134–135
 - low-temperature flexibility as weak point, 141
 - major differentiators for good, 139
 - molecular structure of, 137–139
 - consists of fluorinated monomers and dipolymers VF2 and CTFE, 137
 - Mooney viscosity of, 138
 - polymer structure in, 138
 - problems and solutions during compounding, 150–151
 - process aids for, 145–146
 - process involved in production, 139
 - resistant to chemical and heat, 134
 - selection steps for, 139
 - base resistance grades of FKM, 140
 - end use and processing, 142–143
 - fuel resistance or permeation, 140–141
 - low-temperature flexibility requirement, 140–141
 - trademarks for, 152–153
 - unique properties for, 143
 - used extensively in O-rings, 135
 - vulcanization, 139
- Fluoropolymer micropowder, 145
- Fluorosilicone (FVMQ) materials, 98
- Ford M2D241A fuel and oil resistant tubing
 - recommended formula, 278–280
- FRNC compound
 - flame tests of, 364
- Fuel permeation, of epichlorohydrin, 255
- G**
- Glycol esters, 394
- Glycol ether adipate, 395
- GM 6148, 273–274
- GM 289M Hose, 275–277
- Green strength, 47
- H**
- HAF N330, 144
- Hexamethylene diamine carbonate (HMDC), 472
- Highly Saturated Nitrile, for oil fields, 496
- High-pressure polyethylene process (LDPE), 346
- HNBR properties
 - and influence of acrylonitrile content and amount of unsaturation, 104
- Highly Saturated Nitrile (HSN), *see* Hydrogenated Nitrile Butadiene Rubber (HNBR)
- Hydrin 3105, 259
- Hydrin Terpolymer 3105 cure systems study, 260–261
- Hydrocarbon process oils, 397–399
 - aromatic process oils, 398
 - ASTM D 2226 classification, 398–399
 - naphthenic process oils, 398
 - paraffinic process oils, 398
 - producers, 398–399
- Hydrogenated Nitrile-Butadiene Rubber (HNBR)
 - air oven aging of, 452–453
 - applications in
 - automotive air conditioning O-rings (green), 122, 125
 - chemically resistant, low hysteresis roller for paper mills, 129, 130
 - high-pressure resistant O-ring for oil drill bits, 130, 131
 - for power steering pump output, 127, 128
 - high-temperature
 - abrasion-resistant joint boot, 118–120
 - differential shaft seal, 124, 126
 - long life automotive serpentine belt, 122, 123
 - oil cooler O-ring seal, 118
 - oil field high pressure well packer, 120–121
 - ozone resistant and abrasion-resistant hose cover, 128, 129

short power steering system
 hose, 126, 127
 water pump mechanical seal protective bellows (orange), 122, 124

calendering, 481

cell oven aging of, 455

commercial polymers properties, 100–103

compounding process
 aging stabilizers, 114
 blending with EPDM, 117
 carbon black fillers, 110–113
 non-black fillers, 113–115
 plasticizers used in, 116–117
 polymer selection, 99
 tackifiers, internal lubricants in, 117
 vulcanization systems, 106

compounds extracted in IRM 901 oil
 before air oven aging, 454

effect of coagent in peroxide cure of, 414

extrusion, 481

formulations and properties, 447–448

influence of variable acrylonitrile content and cross-linking on compression set of, 105

manufacturing process, 96

milling, 481

molding, 481–485

peroxide and coagent interaction and influence study in, 108–110 (*see also* Vulcanization, for HNBR)

peroxide-cured compounds, 446, 449

physical properties of, 96

polymer structure of, 95

processing aids incorporation in, 481–485

produced from hydrogenated acrylonitrile butadiene copolymer elastomers, NBR, 94

regression analysis of antioxidant effects in, 450–451

semi-EV and EV sulfur cure systems for, 107

study of post-cure effects in, 111–112

technology involved in, 94

Zinc Methacrylate modification of, 105

Hypalon 20, 302

HYPALON chlorosulfonated polyethylene (CSM), 419

Hypalon[®] S-1, 302

HyTemp AR-72LF non-black bearing seal, 185

HyTemp NPC-25 cure system, 175

HyTemp PV-04, 159

HyTemp SC-75 cure package, 175

I

IIR, 397, 406, 439

IISRP Worldwide Rubber Statistic 2001, 3

Internal mixers/procedures, for AEM compounds, 215–216

Isodecyl diphenyl phosphate, 390, 395

Isopropyl triphenyl, 394

K

Kalrez[®], 135

L

Lead oxides, 16

Levapren EVM grades, from Bayer, 347–348

Life prediction, of oil field elastomers, 512, 515–518

Limiting oxygen index (LOI), 362

Linear phthalate, 390, 395

Linear trimellitate, 390, 393, 395

Lip Seal, 182
 for GM 8645003-C, 184

Liquid NBR (Nipol DN601)
 major advantage of, 52
 from Zeon Chemicals LLC, Trade Name Nipol, 53

Liquid polysulfide, 370

Low mold-fouling NBR polymers
 from Zeon Chemicals LLC, Trade Name Nipol, 49–50

Low molecular weight polyethylene (LMWPE), as processing aid, 478, 488, 491

“LS” designation, of Vamac products, 195

LT suffix, 141

Luperc[®] 101XL, 144

M

Marching modulus characteristics, 15

Mercaptan-Modified (M-Grades), 2, 8
 and influence of
 crystallization tendency on, 8–9

- Mooney viscosity, 8–9
 - tensile strength-Mooney viscosity relationship of XD-grades, 10
- 2-Mercaptotoluimidazole (MTI), 453, 472
- Metal oxides cross-linking, in elastomers, 15–17, 417–420
- Methoxy ethyl acrylate (MEA) group polyacrylate elastomers, 156
- Methyl acetyl ricinoleate (P4), 392
- 4,4'-Methylenebis (cyclohexamine) carbamate, 420
- Methyl mercapto benzimidazole (MMBI system), 17
- A-Methylstyrenated diphenylamine, 445, 472
- Microtalc, 21
- Millable polysulfide, 370
- Mineral oils, 397–399
- Molding defects, in fluoroelastomers, 150–151
- Molding, of AEM compounds, 217–220
- Molecular structure, key factors responsible, 5
- Mooney viscosity elastomer, 497
- M-Phenylene-bis(maleimide) (MBM), 414, 472
- MT N990 Black filler, 144
- Multifunctional cross-linking agents, for elastomers, 420–423
- N**
- Naphthenic process oils, 390, 393, 398
- Natural Rubber (NR), 15
- Naugalube 635, 445–446
- Naugard 445, 172, 413, 445–446, 449, 453
- Naugard BHT, 440
- Naugard J, 445–446
- Naugard PANA, 445–446
- Naugard Q, 445–446
- N-BBSA, 394
- NBR, 15, 40, 401–403, 415, 435, 439
 - ACN Content and effects, 46
 - calendering, 481
 - carbon black masterbatches
 - advantages of, 53
 - from Zeon Chemicals, 53–54
 - chemical configuration of
 - butadiene isoprene ACN terpolymer NBIR, 42
 - carboxylated XNBR polymer, 42
 - comparison of
 - peroxide and sulfur donor cures in, 417
 - regular and sulfur less cure systems in, 418
 - sulfur, sulfur donor and peroxide cure systems in, 419
 - compound design and considerations
 - carboxylated nitrile rubber, 82
 - curing of standard NBR, 72
 - fillers, 63–65
 - NBR selection, 58–62
 - plasticizers, 65–66
 - extrusion, 481
 - grades and types of NBR, 42–46
 - history of, 39–40
 - HNBR, 403, 415, 481–485
 - influence of variable acrylonitrile content and cross-linking on compression set of, 104
 - milling, 481
 - molding, 481–485
 - Mooney viscosity of, 47
 - NBR/PVC blends
 - advantages of using, 86–87
 - disadvantages of, 89
 - with and without plasticizer, 86–89
 - from Zeon Chemicals LLC, 55–57
 - for oil fields, 495–496
 - performance of peroxide vs. sulfur cures in, 80
 - and plasticizer-extended NBR, 86
 - polymerization process of, 95
 - polymerization temperature and stabilizers role, 47–48
 - polymer structure, 94
 - processing aids incorporation in, 481–485
 - protection by antioxidants and antiozonants, 81–82
 - specific gravity of, 48
 - structure of standard NBR, 41
 - suppliers, worldwide, 40–41
- NBR curing
 - comparison of EV, semi-EV, and peroxide with and without SR-297 cure system, 81
 - EV efficient vulcanization cures, 77–78
 - sulfur-less, 74
 - performance of peroxide versus sulfur cures in, 80

- peroxide curatives in, 74, 79
 sulfur cures systems in, 72–74
 sulfur donor or semi-EV cures, 73–76
- NBR grades and polymers**
 carboxylated polymers, 50–51
 from Lanxess, Trade Name Perbunan/
 Krynac, 45–46
 low mold-fouling grades, 48
 polymer structure of, 94
 precrosslinked grades of, 48
 types of Butadiene addition in formation of
 polymer, 94
 from Zeon Chemicals LLC, Trade Name
 Nipol, 43–44
- NBR manufacturers; see also Hydrogenated
 Nitrile Butadiene Rubber (HNBR)**
 Goodyear, Bayer, Nippon Zeon, and
 Polysar, 95
- N*-Butyl-4,4-bis(*t*-butylperoxy)valerate, 410
- N110 carbon black (SAF), 529
- N*-(Cyclohexylthio) Phthalimide, 472
- N*-(1,3-dimethylbutyl)-*N'*-phenyl-*p*-
 phenylenediamine (6PPD), 431–432
- Neoprene GN, 2
- Neoprene W, Thiokol ST blends of with, 378
- Nickel di-*n*-butyldithiocarbamate
 (Naugard NBC), 439
- Nipol 1312, 389
- Nipol AR-12, 159, 169–170
 AR14, and AR22, 179
- Nipol AR14, 159
- Nipol AR22, 159
- Nipol AR53, 158
- Nipol NX775, 419
- NIPOL 1001, Thiokol ST blends
 of with, 377
- Nippon Oil Seal, 169
- Nitrile cure systems, 419
- Nitrile (NBR) group
 NBR, 401–402, 415, 481–485
 NBR/PVC, 402–403
- Nitrile PVC blends, 55
- Nitrile rubber, *see* NBR
- N,N'*-bis-(1,4-dimethylpentyl)-*p*-
 phenylenediamine (77PD), 432–433
- N,N'*-diphenyl-*p*-phenylenediamine
 (Naugard'J), 440, 472
- Non-black static-dissipative formula, 285
- Nonpolar elastomers-NR, 406
- NORSOK M 710 Rev. 2 “Qualification of
 Non-metallic Sealing Materials and
 Manufacturers”, 515
- N*-Phenyl- α -naphthylamine (PANA), 472
- N*-Phenyl-*N'*-(*p*-toluenesulfonyl)-*p*-
 phenylenediamine (TPPD), 445, 472
- O**
- Octamine, 440, 445–446
- Octylated diphenylamine (ODPA),
 17, 440, 472
- Octyl oleate (AO), 390
- Oil field elastomers
 chemical changes, 504–506
 commercial Ram Packers, 507–511
 in sour environment, 505–508
 life prediction, 512
 materials, 495–496
 physical changes, 498–504
 at elevated temperatures, 499–500
 explosive decompression in Freon
 134A, 503
 at glass transition temperatures, 501
 and high differential pressures,
 501–502
 in low temperature environments, 501
 storage temperature, 501
 swelling, 502–503
 qualification tests, 512
 used in the energy industry, 496–498
 well-bore fluids, 506–511
- Oil field packer and HNBR, 121
- Oil pan gasket compound, 187
- Oil-resistant elastomers
 in automotive transmission fluid,
 comparison of, 98
 in engine oil, comparison of, 97
 pound-volume cost comparisons
 of, 99
- O-rings, 234
- Ozone degradation, 430–434
 antiozonants, 431–433
 nonstaining triazine based antiozonants,
 433–434
 waxes and polymer antiozonants, 434
- Ozone resistance, of polyepichlorohydrin
 compounds, 253
- Ozonolysis, 431

P

- Packers, for oil fields
 - blow-out-prevention (BOP), 497–498
 - down-hole, 497
 - inflatable, 498
- Paint and lacquer spray can gaskets, 381–382
- Paint hose inner liner, 382–383
- PANA *N*-Phenyl- α -naphthylamine, 472
- Paraffinic process oils, 390, 393, 398
- Paraffin wax, as processing aid, 478
- Pariser's mechanism, 17
- Perfluoroelastomers, 135
- Peroxide cross-linking
 - in elastomers, 409–410, 417, 419
 - compounding with peroxides, 413–415
 - peroxide reactions, 410
 - selection of peroxide, 410–415
- Peroxide curable fluoroelastomer, 415
- Peroxide Curable HyTemp PV-04, 179
- Peroxide cure mechanism, for Vamac, 213–214
- Petrolatum, as processing aid, 478
- Phenyl- α -naphthylamine (Naugard PANA), 445
- Phthalates diesters, 394
- Plasthall 7050 (glutarate), 390
- Plasticizer-extender NBR
 - EV cure systems *vs.* sulfur and semi-EV in, 90
 - grades, 89
 - from Lanxess, Trade Name Krynac, 55
 - from Zeon Chemicals LLC, Trade Name Nipol, 55
- Plasticizer oils, effects on the viscosity of rubber, 532–533
- Plasticizers, 21–23, 171–172
 - acrylic elastomers, 404
 - applications and compounding, 401–407
 - chlorinated polyethylene-CPE, 406
 - chlorosulfonated PE-CSM, 406
 - definitions, 389–394
 - diester, 396
 - environmental considerations, 407
 - epichlorohydrin elastomers, 404–405
 - fluoroelastomers-FKM, 406
 - high-temperature performance, 389
 - hydrocarbon process oils, 397–399
 - low-temperature improvement, 389
 - molecular weight and high-temperature permanence, 392–393
 - monomeric types, 389
 - nitrile rubber, 401–403
 - nonpolar elastomers, 406
 - polarity, 389, 394
 - polychloroprene, 405–406
 - polyesters, 397
 - polymeric types, 389
 - rubber process oil, 408
 - styrene block copolymers, 404
 - styrene butadiene rubber, 403–404
 - synthetic plasticizers, 389, 391–397, 407–408
 - viscosity and low temperature, 390–391
 - vulcanized vegetable oil, 399–401, 408
- Pluoriol E4000, 479–480, 491
- Polyacrylate elastomers
 - antioxidants, 172
 - applications, 156, 182–191
 - ASTM D2000/SAE J200 designations of, 156
 - commercially available grades, 158, 159
 - compounding
 - filler selection, 169–171
 - polymer selection, 159–169
 - cost effectiveness, 155
 - cure systems, 172–179
 - fillers for
 - carbon black, 169, 170–171
 - non-black, 171
 - influence of ACM composition on properties, 157
 - plasticizers, 171–172
 - process aids, 172
 - processing properties
 - internal mixing procedures, 179–180
 - mill mixing procedures, 180–182
 - reactive cure sites of, 157
 - structure and types, 156–159
- Polyacrylic elastomer (ACM), 421, 445, 472–473
- Polychloroprene, applications of
 - belting, 33–34
 - extruded profiles, 34
 - hoses, 29–31
 - molded goods, 32–33
 - wire and cables, 34

- Polychloroprene-CR, 389, 391,
397, 405–406
processing aids incorporation in, 488–490
- Polychloroprene polymers
and crystallization process, 6
and tensile strength—Mooney viscosity
relationship of, 10
- Polychloroprene rubber
applications of
belting, 33–34
extruded profiles, 34
hoses, 29–31
molded goods, 32–33
and chloroprene monomer production, 3
compounding and processing
of, 14, 24–25
accelerators, 15–16
antioxidants and antiozonants, 17–18
blending with other elastomers, 14
chloroprene rubber grades selection, 14
compounding ingredients used, 23
fillers, 19–20
plasticizers, 21–22
CR rubbers, commercially available, 11
historical background of, 2–3
monomer synthesis by father Nieuwland, 2
polymerization and copolymerization of, 3
properties of, 25–26
aging and heat resistance, 26
flame retardance, 28
low-temperature flexibility, 27
resistance to fluids, fungi
and bacteria, 29
relationship between precrosslinking and
properties, 11
structure and properties
general purpose grades, 8–9
precrosslinked grades, 10
sulfur-modified grades (S-Grades), 10
structure and structural variables, 4
crystallization process, 6
Glass transition temperature (T_g) and
melt temperature (T_m) of, 7
modifications of, 7
polymerization and isolation of, 5
structural units in chain, 6
- Polyepichlorohydrin-allyl glycidyl ether
copolymer (GCO), 247
- Polyepichlorohydrin elastomer
acid acceptors, 259–262
applications
air conditioning, 282
air ducts, 267–268
curb pump hose, 281–282
dynamic components, 282–283
electrical conductivity, 285
fuel hose, 268–281
other, 287
pimer bulb, 285–287
static dissipation, 283–285
classes, 246
commercial, 248–249
corrosion resistance, 254–255
curatives, 258–259
dynamic properties, 251
effect of reversion on, 252
electrostatic properties, 255–257
extrusion, 264–265
formulation design, 257
fuel resistance, 255
grades, 250
heat and oil resistance, 251–253
history, 247–248
molding, 265–266
ozone resistance, 253
permeability, 255
physical properties, 249–251
polymer selection, 257–258
processing section
internal mixing process, 264
milling, 263–264
protective agents, 262–263
uses, 246
- Polyester adipate, 396
Polyester glutarate, 396
Polyester sebacate, 396
Polyesters plasticizers, 397
Polyethylene, 346, 389
Poly(ethylene co-vinyl acetate),
feature of, 346
Polymeric adipate, 391
(G-50, P-6310), 393
(P-6320), 393
Polymeric sebacate, 391
(G-25), 393
Polymerized 2,2,4-trimethyl-1,
2-dihydroquinoline (TMQ), 472
Polymer molecular weight averages, 526
Polymer selection, of polyacrylate elastomer
compression set resistance, 161, 167–169

- cure-site selection
 - chlorine cure sites, 161–163
 - dual chlorine/carboxyl active cure site, 161, 165–166
 - epoxy cure sites, 161, 164–165
 - Polysulfide; *see also* Thiokol FA; Thiokol ST
 - applications, 380–383
 - paint and lacquer spray can gaskets, 381–382
 - paint hose inner liner, 382–383
 - composition, 370
 - compounding, 373–374
 - internal lubricant, 374
 - plasticizing and softening, 374
 - vulcanization agent, 373–374
 - elastomer blends, 375–378
 - fillers, 375–376
 - problems in processing and product performance, 384
 - processing, 376–380
 - Thiokol FA, 376, 379
 - Thiokol ST, 379–380
 - properties, 371–373
 - test formulations, 371
 - p*-Phenylenediamines, 18, 431, 440
 - Practical rules of thumb (PROT), 389, 402–403, 405, 407
 - Precrosslinked grades, 10
 - NBR Grades, from Lanxess, Trade Name Krynac, 51
 - Precursors, 395
 - Processing aids, 478–480
 - bloom and migration, 480
 - incorporation of, 481–491
 - in ACM, 484, 486–488
 - in AEM, 487
 - in CM, 488
 - in CR, 488–490
 - in CSM, 490–491
 - in ECO and CO, 487–488
 - in EVM, 490
 - in FKM, 483–484
 - in NBR, XNBR and HNBR, 481–485
 - melting and softening temperatures of, 478–480
 - surface tack, 480
 - Processing Guide for Viton from DuPont
 - Performance Elastomers, 149
 - Proprietary processing aids, 478–480
 - substitutes, 480
 - Propylene glycol dibenzoate, 390
 - PVC, 402–403
- ## Q
- Qualifying tests, for oil field elastomers, 512
 - Quinone dioxime, 420
- ## R
- Radiation effect, of EVM compound, 361
 - Rapeseed oil-based factice, 394
 - Rocker cover gasket, 186
 - Roll mill mixers/procedures, for AEM compounds, 216–217
 - Rubber, antioxidants protection, 440
 - Rubber industry, blends used in, 15
 - Rubber process oils, 394, 408
- ## S
- Santicizer 148, 394
 - Saret SR-206 coagent, 84
 - SBR-NBR blends, 403–404
 - S-B-S polymers, 404
 - 70 shore A O-ring compounds, 188
 - Silicone (VMQ), 415
 - Sodium ethylhexyl sulfate (SDPA), 472
 - Solid factice, 394
 - Solid polysulfide elastomer, *see* Polysulfide
 - Soybean oil-based factice, 394
 - Specialty elastomers, *see* Elastomers
 - vulcanization agents
 - effects of compounding variables, 526–534
 - effects of process variables, 524–526
 - elasticity, 522–524
 - flow related issues, 539–541
 - problems in compression, transfer, or injection molding, 534–538
 - sudden dimensional shift in finished part, 538–539
 - viscosity, 520–522
 - SRF carbon black, study in Thiokol FA, 375
 - SRF N762, 144
 - Static seals, 171
 - Stearic acid, 172
 - Strukrez 160, 479–480
 - Struktol HM 97, 479, 488, 491

- Struktol HPS 11, 479, 481, 483–484, 488–490
 Struktol 60 NS, 479–481
 Struktol PE 1–1–100, 480
 Struktol PE H-100, 479, 491
 Struktol TR 121, 479–480, 491
 Struktol TR 131, 479–480, 491
 Struktol TR 141, 479–480, 491
 Struktol WA 48, 480–481, 483–484, 488
 Struktol WA 48A, 479
 Struktol WB 42, 479–480, 487
 Struktol WB222, 172
 Struktol WB 222, 479–484, 486–491
 Struktol WB 280, 484
 Struktol WS 180, 479, 487, 490
 Struktol WS 280, 479, 483–484, 486–487
 Struktol WS-280, 172
 Struktol ZP-1014, 84
 Styrenated diphenylamine (SDPA), 17, 472
 Styrene block copolymers, 404
 Styrene butadiene rubber (SBR), 15, 389, 391, 397, 403–404, 434–435, 439
 Sulfonamides, 394
 Sulfur cures, in elastomers, 417–419
 Sulfur donor cures, in elastomers, 415–417, 419
 Sulfur-modified grades (S-Grades), 10–11
 Surface tack, in processing aids, 480
 Surface treated fillers, 145
 SynPro RD-50, 84
 Synthetic plasticizers, 389, 391–397, 407–408
 equivalent products and producers, 395–396
 monoesters, 391, 394
 precursors, 395
- T**
- TEG-CC, 394
 TEG-2EH, 394
 TEP, 394
 TE80 paste, 172
 Terpolymer NBR
 from Zeon Chemicals LLC, Trade Name Nipol, 53
 Terpolymers, vulcanization of copolymers (Vamac D, Vamac DLS), 213–215
 dipolymers, 214
 fast diamine/peroxide cure systems, 212–213
 Vamac G, HG, and GLS, 209–212
 Tetra(3,5-di-*t*-butyl-4-hydroxy hydrocinnamate) methane (N-10), 472
 TFE (tetrafluoroethylene), 138
 Therban XT VP KA 8889 carboxylated HNBR, 106; *see also* Hydrogenated Nitrile Butadiene Rubber (HNBR)
 Thermal acceleration techniques, in life prediction of elastomers, 516–517
 Thermofluctuational theory, 516
 Thiadiazole, 420
 B-thiodipropionic acid, 443
 Thioester stabilizers, 439
 Thiokol A, 369
 Thiokol FA, 369
 formulations, 373
 permeability, 372–373
 physical properties, 371
 processing, 376, 379
 SRF carbon black study in, 375
 Thiokol FA Hose Liner, 382–383
 Thiokol FA Paint Can Gasket, 382
 Thiokol LP, 369
 Thiokol ST, 369
 ASTM D2000 compounds based upon, 383
 blends of with
 Neoprene W, 378
 NIPOL 1001, 377
 fillers in, 376
 formulations, 373
 physical properties, 371
 processing, 379–380
 Thiuram disulfide, 416
 Thiuram hexasulfide, 416
 Thixon 718/719 adhesive, 182
 TINTM, 394
 TIOTM, 394
 Titanium dioxide or TiO₂ (TiPure[®] P960), 144
 TQA Acron's products 800 series, 159
 Toacron 840 shaft seal compound, 183
 Toluimidazole, 446
 TP-759 (4426), 392
 TPP, 394
 TP-759 (4426, RS-700), 390
 Transmission oil cooler hose, 190–191

- Trialkyl phosphates, 394
Triallyl cyanurate (TAC), 355, 414
Triallyl-iso-cyanurate (TAIC), 355, 414
Triallyltrimellitate (TATM), 414
Triaryl phosphates, 390, 394, 396
Tributoxyethyl phosphate (TBEP), 390, 394, 395
Tributyl phosphate, 395
Tributyl phosphate (TBP), 390, 392, 394
Triethylene glycol butyl adipate, 395
Triethylene glycol caprate-caprylate, 395
Triethylene glycol dioctate, 390, 392, 395
Trimellitates, 394
Trimethyl dihydroquinoline (TMQ), 17
Trimethylolpropane trimethacrylate (TMPTMA), 355, 414
Triocetyl phosphate, 395
Triocetyl trimellitate (TOTM), 390, 393, 394, 401, 403, 406
1,11-(3,6,9-Trioxaundecyl)-bis-3-(dodecylthio) propionate, 472
2,4,6-tris-(*N*-1,4-dimethylpentyl-*p*-phenylenediamino)-1,3,5-triazine (TAPTD), 433–434, 445, 472
Tris(nonylphenyl) phosphite (TNPP), 439, 443, 472
Trithiocyanurate cure system, 453
Trithiocyanuric acid, 420
1,3,5-Trithiocyanuric acid (TCY), 472
TyPly BN adhesive, 182
- U**
- Unsaturated terpolymers (GECO), 423
- V**
- Vamac compounds, design for fillers for, 204–206
plasticizers, 206–208
polymer selection, 200–202
release system, 201, 203
use of stabilizer(s), 201–204
Vamac elastomers, *see* Ethylene/acrylic (AEM) elastomers
Vamac terpolymers, 194
VANAX 808 amine, 422
VANAX 882B, 421–422
VANAX DPG, 420
VANAX MBM, 414
VANAX 829 thiadiazole, 421–422
VANCHEM DMTD, 421
VANOX ZMTI, 413
VAROX 130, 410–411, 414
VAROX 230, 410–413
VAROX 231, 410–412
VAROX 802, 410–411
VAROX DBPH, 410–411, 414
VAROX DCP, 410–414
Varox Dicap 40C from R.T. Vanderbilt, 106
VDE 0207/part 20 type 401, 358
VF2 (vinylidene fluoride), 137
Vinyl acetate, 345
content, influence on oil swelling, 363
Viscosity
defined, 520–521
Power Law and Cross models for, 522
shear rate behavior for rubber, 521
temperature effects on, 524
Viton[®], 137
VP KA 8796, 105
Vulcanizate properties, comparison of CR, NBR, NR, and SBR, 26
Vulcanizates, of unextended Vamac elastomers, 196
Vulcanization agents, for specialty elastomers, 409–423
Vulcanization, for HNBR and coagents used
N-*NO*-*m*-phenylenedimaleimide (VanaxMBM), 106
triallyl isocyanurate (TAIC), and triallyl cyanurate (TAC), 107
sulfur and organic peroxide, 106 (*see also* Hydrogenated Nitrile-Butadiene Rubber (HNBR))
Vulcanization systems, for dipolymers, 214
Vulcanized properties, of AEM elastomers
dry heat resistance, 196
general fluid and chemical resistance, 197–198
low-temperature performance, 196
other properties, 199
physical properties, 197–199
vibration damping, 197
Vulcanized vegetable oil (Facticc), 399–401, 408
modifiers, 400
producers, 400
vulcanizing agents, 399

W

Well-bore fluids and oil field elastomers,
506–511

White fillers with MT Black,
comparison of, 148

White Thiokol FA Rolls, 381

Wollastocoat[®] 10,022, 10,014, 10,012, 145

Wollastonite[®] (Calcium metasilicate), 144

www.dupontelastomers.com, 140

X

Xanthogen-Disulfide Grades(XD-grades),
2, 8

processing behavior and vulcanizate
properties, 8–9

tensile strength—Mooney viscosity
relationship of M-grades, 10

XNBR rubber, *see* Carboxylated Nitrile
Rubber

XQ 536, 105

Z

Zeon Chemicals' 4000 number series of
elastomers, 159

Zeonet system, 178

Zetpol PBZ-123, 106

Zetpol ZSC 2295, 105

Zinc diacrylate, 414

Zinc dimethacrylate, 414

Zinc di-*n*-butyldithiocarbamate (ZDBC), 472

Zinc 2-mercaptotoluimidazole (ZMTI), 446,
449, 453, 472

Zisnet cure system, 422–423

Zisnet F-PT cure system, 182, 254, 259

Zonyl[®] MP, 145