

# INDEX

---

- Barrage components, 31
  - powerhouse, 38
  - sluiceway, 36
  - access dyke, 36
  - closure dyke, 92
- Bathymetric data, 20
- Caisson projects, 72
  - Hibernia, 73
  - Kislaya Guba tidal power station, 74
  - Murray prefabricated steel powerhouse, 76
  - Scheldt Estuary control works, 73
  - St. Petersburg storm-surge barrier, 74
- Concrete caisson design, 82
  - foundation considerations, 77, 81
  - hydraulic considerations, 77
  - stability assessment, 81
  - stability forces, 82
  - maximum water levels, 77
  - minimum water levels, 79
  - tidal currents, 80
  - wave climate, 78
  - wave runup, 79
- Construction “in the dry,” 76, *see also*
  - La Rance Station, 195 and Annapolis Station, 204
- Construction “in the wet,” 69,
  - advantages, 76, *see also* Caisson projects and Concrete caisson design
- Database for planning, 47, 166
  - continuous tide level data, 50
  - estuarial ecosystems, 58, 176, 192
  - estuary topography/bathymetry, 42
  - geological characteristics of estuary, 171
  - input for modeling tidal regime, 56
  - sedimentation characteristics of estuary, 55
  - seismicity of estuary region, 50
  - tidal currents, 54
  - wave climate, 54

- Development schemes, 45  
*see also* Retiming tidal energy  
 single-basin single-effect, 35–39
- ebb generation, 36–39
- flood generation, 36–39
- pumping capability, 41, 44
- Bay of Fundy studies, 41–42, 44
- La Rance tidal power plant, 41  
 single-basin, double-effect, 36  
 pumping capability, 41, 44
- linked basins, 42
- paired basins, 45
- Dykes, 87–95  
 access dykes, 89–92  
 alternative construction methods, 89  
 closure dykes, 92–95  
 water velocities, 90, 92  
 construction materials, 95  
 cost, 87  
 design factors, 88, 98
- Economic analysis, 155–160, *see also*  
 Sensitivity analysis  
 basic assumptions, 155  
 benefit/cost ratio, 164  
 cost parameters, 152  
 cost of capital, 155–56  
 fossil fuel costs, 155–57, 164  
 labor costs, 152, 162  
 discount rate, 151–52, 155–56
- Electrical equipment, 114, *see also*  
 Turbogenerating equipment
- Environmental aspects, 171–74  
 agricultural, 174–75  
 benthic environment, 172  
 biological responses, 167, 174  
 regional climate changes, 170  
 erosion and sediment regimes, 171  
 fisheries, 177  
 floods and drainage, 174–75  
 planktonic environment, 172  
 recreation and tourism, 178  
 transportation, 179  
 water quality, 169–71  
 waterfowl, 179
- Estuary numerical models, 62–67  
 calibration, 60
- Factors influencing project economics, 20–21  
 external factors, 20–21  
 internal factors, 20
- Feasibility studies, 22  
 Severn Estuary, 24, 255–59  
 Bay of Fundy, 30–32, 215–22
- Finite grid element, definition, 64–65  
 grid sizes used for Bay of Fundy–Gulf of Maine model, 64
- Mathematical model for barrage closure activities, 69
- Modeling barrier effects, 67
- Modeling techniques for tidal estuaries, 59, 63  
 finite difference method, 63–64  
 finite element method, 63–64  
 hydraulic models, 55, 59–62  
 numerical models, 52, 54, 59–60, 62–63, 65, 67  
 hybrid models, 59, 61, 67
- Modeling plant output  
 Bay of Fundy Tidal Power  
 Reassessment Study, 121  
 one-cycle dynamic programming model, OCDPM, 122  
 maximum energy operation, 122–23  
 single-tide optimization model, STOM, 121, 123
- Operation for maximum energy, 122
- Optimizing plant output, 117  
 cost-related, 118  
 operating, 117–119  
 principal variables, 117
- Origin of tides, 9–12
- Plant output  
 factors determining output, 16  
 optimization, 117–24, 127–28  
 effect of varying numbers of sluices and turbines, 119  
 operation simulation, 120  
 optimum combination of turbine and sluiceway capacities 118–19
- Plant operational modes, 34–38, 124  
 double-effect operation, 36, 38–39

- single-effect operation, 35, 37–39
  - complex modes of operation, 124
- Potential tidal power sites worldwide, 209
  - factors influencing exploitation, 221
- Powerhouse caissons, 81, 84, 222, 241,
  - see also* Concrete caisson design
- Project economics, 20, 21, 199, *see also*
  - Economic analysis
- Retiming tidal energy, 44, *see also* Tidal
  - energy storage options
- Risk assessment, 157, 160
- Sensitivity analysis, 155, 160, *see also*
  - economic analysis
  - nuclear penetration in system, 155–56
- Simulation models to analyze viability of
  - alternative generation expansion programs, 141, 145
- Chronological Absorption of Tidal
  - Output (CATO), 145
  - Optimum Mix (OPTMIX), 146
  - Production Cost (PROCOX), 145
  - Tidal Capacity Correction (TCC), 145
- Site investigations, 81–82
- Site potential, 17
  - annual energy production, 18, 22–24,
    - 109, 121, 126, 215, 226
  - gross energy potential, 17
- Site selection, 15, 20, 22, 24, 223
  - criteria, 21, 24, 54, 78–79, 86, 88, 92,
    - 113, 142–43, 146, 266
  - short listing of sites, 24
    - assessment factors, 31, 48
- Socioeconomic impacts, 161
- Sluiceway caissons, 61, 81, 85, 87–88, 244,
  - see also* Concrete caisson design
- Sluiceway gates, 17, 86, 178
  - design criteria, 21, 57, 86, 88, 92
  - radial gates, 86–87
  - vertical lift gates, 86–87
- Sustainability, 6
- System generation expansion, 129, 140,
  - 145, 149, 153, 155–56
  - lead times to commissioning, 141
  - market analysis, 143–44
  - system simulation, 136–37, 142, *see also*
    - Simulation models
- Tidal ebb and flow energy, 1
- Tidal currents, construction effects on, 95
- Tidal-electric power plants in operation,
  - 181, *see also* Tidal ranges in estuaries
  - Annapolis, 5, 102–103, 105, 177,
    - 181–83, 198–206, 264, 266, 268
  - Jiangxia, 5, 183, 194–95, 226
  - Kislaya Guba, 73–74, 195–96, 234–35,
    - 238, 264
  - La Rance, 4–5, 41, 72, 102, 178–79,
    - 181–85, 187–89, 191–93, 195, 226,
      - 253, 264–65, 269–70
- Tidal energy absorption, 136, 267
  - dynamic absorption capability of
    - system, 135
  - load-following capability, 135–36, 143
  - “must-run” generation, 136, 143, 146
  - raw tidal energy asorption, 136, 267
  - static absorption capability of system,
    - 143
    - system load allocation, 141
- Tidal energy storage options, 137
  - see also* Development schemes
  - auxiliary capacity, 137, 138
  - compressed-air energy storage, 45,
    - 137, 139–40
- coordinated operation with river hydro,
  - 137
  - pumped storage, 40, 137–39, 162, 165,
    - 218, 268, 272
- Tidal mills, 2–5
  - operation, 1–3
  - Woodbridge Tide Mill, Deben
    - Estuary, England, 3
  - Slade’s mill, Chelsea, Mass., 3
  - mill in La Rance estuary, France, 72
- Tidal range in estuaries, 18
  - barrage effect, 13, 23, 67
  - Bay of Fundy, 5, 10, 13, 19, 30–32,
    - 41–42, 44, 52, 56, 59, 64, 66–69,
      - 76, 83–84, 90–92, 94, 98, 105,
        - 109–10, 121–22, 126–27, 130, 136,
          - 140, 144, 159, 166, 170, 175–76,
            - 198, 206, 215–17, 221 224, 237,
              - 245, 256, 262–67, 271, 275
    - Annapolis Basin, 5
    - Cobequid Bay, 13, 51, 110, 222

- Cumberland Basin, 13, 42, 67, 92, 138, 170, 219–20, 222, 263
- Minas Basin
- Coriolis effect, 13, 64, 256
- Jiangxia Inlet, 5
- Kislaya Guba, 73–74, 195–97, 235, 238, 264
- La Rance estuary, 4–5, 41, 72, 102, 178–79, 181, 183–85, 187–89, 191–93, 195, 226, 253, 264–5, 269–70
- resonance effect, 12–13, 48, 67, 170, 257
- Tidal range in oceans, 18, 222, 243
- Tidal stream, 7, 266
- Tide coefficients, 19, 62, 123, 127
- Tide types, 9, 19, 56, 172
  - anomalistic tide, 9–11, 19
    - anomalistic month, 9
    - apogee, 9, 11
    - perigee, 9, 11, 19
  - declinational tide, 9, 11, 19
    - diurnal, 8, 12, 19, 22, 51, 85, 121–24, 223, 257, 259–60
    - diurnal inequality, 12, 19, 22, 121–24, 232
    - semidiurnal, 7, 12–13, 15, 42, 51, 67, 188, 208, 231, 259–60
  - mixed tide, 9
  - synodic tide, 9, 19
    - synodic month, 9
  - spring tide, 92, 129, 188–89, 191, 211, 237
    - neap tide, 10, 41, 188–89, 191
- Transmission to remote and local markets, 114
- Turbines, 5, 8, 20–21, 23–24, 34–44, 61, 68, 75, 79, 84–85, 97–101, 103, 106, 109–12, 118–20, 122–27, 131, 140, 156, 163, 177–78, 180, 184, 188–95, 197, 202, 212, 222, 230, 232–33, 235, 237–38, 241, 243, 245, 248, 250, 252, 257, 265
  - Straflo, 5, 102–06, 194, 198, 202, 206, 210–11, 222, 264, 266, 270
  - bulb, 5, 75, 99–103, 110–14, 184, 187, 191–95, 210–12, 215, 230, 232–33, 238, 265
  - tubular, 99–100, 203
  - vertical Kaplan, 99, 101
- Turbine output regulation, 45, 101, 104, 106, 109, 132
  - double regulation, 101, 106, 109
  - adjustable runner blades, 106, 257
  - fixed runner blades, 107–109
  - variable guide vanes, 106, 108
- Turbine specific speed, 99, 112
- Turbine runner diameter, 99, 112–23, 127
- Turbine generator, 106, 140, 241, 243
- Turbogenerating equipment, 97, 117
  - see also* Turbines and and Turbine generator
  - percent of project cost, 121
  - project design factors, 52, 105, 113, 160, 167, 195, 199, 214–15, 219, 234, 239, 240, 242, 272