

INDEX

A

- ABO₃ formula, 307
- Absolute value, inclusion, 128
- AC/DC converter, usage, 349f
- Activation barrier, 76f
 - catalytic electrode, impact, 89–90
 - decrease, 89–90
 - size, 78–79
 - symmetry, 84–85
- Activation energy
 - impact, *see* Reaction rates
 - modification, 104f
- Activation impedance loop, decrease, 248
- Activation kinetics, simplification, 91–93
- Activation losses, 18
 - accounting, 209
 - contributions, 94f
 - plotting, 235f
 - curve, concentration losses (impact), 173–174
 - increase, 169
 - inference, 249
 - usage, 172
- Activation overpotential, representation, 423
- Activation overvoltage, 86
 - changes, calculation, 172
 - effect, *see* Fuel cells
 - explanation, 87
 - requirement, *see* Forward current density
- Activation process, effective resistance (decrease), 249
- Active catalyst area coefficient, 253
- AD, *see* Anaerobic digestion
- ADG, *see* Anaerobic digester gas
- Aeromonas hydrophilia, 276
- AFC, *see* Alkaline fuel cell
- AFM, *see* Atomic force microscopy
- Aftercooler, hot stream placement, 410
- Air blower
 - power consumption, 445, 446
 - specifications, 443t
- Air pollution
 - external costs, environmental impact (quantification), 473–476
 - financial costs, 475t
 - health effects, 474t
 - environmental impact, quantification, 473
 - hydrogen, contributor, 472–473
- Air pollution, emissions (relationship), 472–476
- Air supply, usage, 434–435
- Alkaline-based direct alcohol fuel cells, 274
- Alkaline-based direct-methanol fuel cells, investigation, 273
- Alkaline fuel cell (AFC), 9, 261
 - advantages, 267
 - aqueous potassium hydroxide electrolyte, usage, 266
 - carbon dioxide, presence, 267
 - cathode activation overvoltage, 266
 - concentrated aqueous KOH electrolytes, usage, 127
 - disadvantages, 268
 - explanation, 266–268
 - hydrogen reduction reaction, 96
 - UTC Fuel Cells, Inc. AFC, 267f
- Ammonium borohydride (NH₄BH₄), usage, 275
- Anaerobic digester gas (ADG), 384
 - contaminants, removal, 385
 - renewable fuel, consideration, 385
- Anaerobic digestion (AD), 372, 384–385
 - components, 384–385

- Anode Galvani potential, sacrifice, 85f
- Anode-membrane interface
 hydrogen/water concentration, calculation, 211
 hydrogen/water concentrations, solutions, 209
- Anodes
 activation, 245
 kinetics, 247
 losses, 238
 carbon monoxide tolerance, 262–263
 current densities, limiting, 169
 degradation, 322
 hydrogen concentrations, 208–209
 materials, 316–337
 overvoltage, 104f
 oxidation, relationship, 14
 reaction kinetics, ignoring, 204
 structure, surface area, 271
 thickness, 209
 water concentrations, 208–209
- Anode supported MEA, 312
- Anode-supported SOFCs, 204
- Aqueous alkaline electrolyte, 279
- Aqueous electrolytes/ionic liquids, ionic conduction, 127–129
- Aqueous solutions, ionic mobility, 129t
- AR, *see* Autothermal reforming
- Area-normalized reaction rates, 74
- Area-specific resistance (ASR), 119–120, 318
 calculation, 120
 usage, 120–121
- Arrhenius conductivity equation, deployment, 426, 430
- Aromatic hydrocarbon membranes, 289
- Asiplex™ (Asahi Chemical Industry), 288
- Atomic force microscopy (AFM), 256
- Atoms
 barrier height, 155
 characteristics, 5
- Autothermal reforming (AR), 372, 379–383
- Avogadro's number, usage, 44
- B**
- Back-diffusion water fluxes, balance, 200
- Backward flux, 147–148
- Banded designs, 335f
- Barrier heights, *see* Atoms
 calculation, 155–156
- Batteries, schematic comparison, 9f
- BET, *see* Brunauer-Emmett-Teller
- BIMEVOX-based materials, usage, 306
- Binary diffusion, Fick's law, 206
- Binary diffusion model, 206
- Biological fuel cells, 261, 272
 explanation, 276–277
- Bipolar plates
 design, 336
 examples, *see* Fuel cells
 stacking, 332–333
- Bipolar plate/seal degradation, 321
- Bismuth oxides, 306
 conductivity, 306
- Black body surface, resemblance, 391
- Blocking electrode, 242–243
- Boltzmann's constant, 27, *see also* Exponential Boltzmann factor
 usage, 79
- Bond enthalpy calculations, 35
- Bonding energy, *see* Hydrogen-hydrogen bonds
- Bonds, energy (relationship), 5
- Bottleneck processes, identification, 477–478, *see also* Gasoline vehicle supply chain
- Boundary conditions, 208–209
 explanation, 426–430
 usage, 429–430
- Brunauer-Emmett-Teller (BET) surface area
 determination, 255
 measurement, 228
- Built-in voltage, occurrence, 55
- Bulk reactant (flow channel), 164
- Butler-Volmer (B-V) equation, 83–88, 172
 application, 95
 consideration, 86
 derivation, 87
 description, 422
 functional form, 86f
 modifications, requirement, 887
 Nernst equation, connection, 101–105
 size, 91
 usage, 89
 values, relationship, 86f
- BYZ, *see* Yttrium doped barium zirconate
- C**
- Calcium-doped LaCrO₃, electrical conductivity, 319
- Capacitive double-layer impedance, 242
- Capacitors
 impedance response, 240
 placement, 240–241
- Carbon cloth, 295–296
 usage, *see* Polymer electrolyte membrane fuel cell
- Carbon content, 467t
- Carbon dioxide (CO₂)
 CO, selective oxidation, 388–389
 emissions, 470
 environmental impact, quantification, 466–468
 production, 276
- Carbon-fiber paper materials, production, 296
- Carbon monoxide (CO)
 clean-up, 372, 387–390
 cleanup reactor, 401
 concentrations, increase, 388
 CO-passivated Pt surface, poisoning, 95
 production, 39
 selection oxidation, 388–389
 selective methanation, 387–388
 tolerance, 273, *see also* Anodes providing, 298
 yield, reduction, 385–386
- Carnot cycle, usage, *see* Heat/expansion engine
- Carnot equation, 61
- Carrier-gas-based fuel-processing subsystems, complexity, 345
- Carrier hydrogen storage systems, comparison, 342t
- Carriers
 concentration, 123, 142
 contrast, *see* Intrinsic carriers
 mobility, 123
 description, 142–143
 system, effectiveness (calculation), 342

- Catalyst-electrode design, 97–98
- Catalyst layers, 164
 - assumptions, 204
 - reactant
 - concentration, 168
 - depletion, 171–172
 - reactant/product concentrations, 161
 - requirements, 294
 - components, 294
 - thinness, 186
 - x*-direction oxygen profile, 188
- Catalysts, 208
 - choice, 90
 - deactivation, 386
 - discovery, 98–99
 - materials, development, 295
 - surface area, 254
- Catalytic electrode, impact, *see* Activation barrier
- Catalytic fuel reformer, exothermic operation, 361
- Cathode Galvani potential, sacrifice, 85f
- Cathode-membrane interface, 212
 - oxygen/water concentrations, 211
- Cathodes
 - activation, 245
 - losses, 238
 - overtoltage, *see* Alkaline fuel cell
 - catalyst, unit surface area, 299
 - current densities, limiting, 169
 - degradation, 322–323
 - impedance, *see* Hydrogen-oxygen fuel cell
 - mass transfer, 245
 - process, assumption, 246–247
 - materials, 317–318
 - overtoltage, 104f
 - results, 204
 - oxygen concentration, 220f, 221f
 - oxygen profile, 209
 - oxygen reduction proceeds, 273–274
 - reduction, relationship, 14
- Cathode supported MEA, 311–312
- Cathode-supported SOFCs, 204
- Cathodic overtoltage
 - comparison, 217
 - computation, 215
- CellTech Power, 281
- Ceramic electrolytes, ionic conduction, 141–144
- Ceramic interconnects, 319
- Ceria, *see* Doped ceria; Gadolinia-doped ceria
- Ceria-based anodes
 - materials, 314–315
 - performance, 315
- CFD, *see* Computational fluid dynamics
- CFD-ACE+®, 418
- CGO10, ionic/electronic conductivities, 305f
- Characterization, importance, 19
- Charged species, types, 111
- Charge flux, 112
 - calculation, 154
 - generation, voltage gradient (usage), 154
- Charges
 - amount, 73–74
 - carriers
 - atomistic diffusivity, 152
 - concentration, conversion, 123
 - conservation, 202
 - explanation, 422
 - simplified form, 418
 - movement, 111–114
 - transfer mechanisms, illustration, 124f
 - transfer reactions, activation energy, 76–78
 - transport, electrical driving forces (impact), 153–154
- Charge transport
 - electrical driving forces
 - impact, 114
 - summary, 115f
 - illustration, 115f
- Chemical bonds, *see* Hydrogen
- Chemical determinations, 228
 - explanation, 256
- Chemical energy
 - representation, 26f
 - transformation, 3
- Chemical free energy difference, 82f
- Chemical potential
 - concentration, relationship, 50
 - concept, 49–50
 - definition, 50–51
 - measurement, 49
- Chemical reaction, molar basis, 51
- Chemisorbed hydrogen charge transfer reaction
 - energetics, schematic, 78f
 - schematic, 77f
- CHP, *see* Combined heat and power
- Chromium-based metallic interconnects, 323
- Circuit diagram, 241f, *see also* Parallel RC; Porous bounded Warburg element; Simple fuel cell impedance model; Warburg element
- Climate change, 460
 - mitigation, 465–466
- Closed system, internal energy (change), 27
- Coal gasification plant
 - greenhouse gas emissions, 384
 - supply chain, 477f
- Cold streams
 - identification, 398–401
 - minimum temperature difference, selection, 403–404
 - temperature-enthalpy diagram, 405f, 406f, 408f, 411f
 - temperature profiles, 400f
 - thermodynamic data, *see* Fuel cell systems
- Cold *T-H* diagram, shift, 406
- Combined heat and power (CHP), 351
 - explanation, 353
 - fuel cell system, process diagram, 352f, 399f
 - subsystems, function, 354
 - overall efficiency, 353
 - systems, case study, *see* Stationary combined heat/power systems
- Combustion
 - engines
 - chemical factories, analogy, 3
 - schematic comparison, 9f
 - reaction, schematic, *see* Hydrogen-oxygen combustion reaction
- Compressed hydrogen, usage, 340–341
- Compression force, 234
- Computational fluid dynamics (CFD), 218
 - basis, *see* Fuel cells
 - fuel cell model
 - equations, 419t

- Computational fluid dynamics (CFD)
 (*cont.*)
 list, 427t–428t
 physical properties, 219t
 resource-intensiveness, 433
 model
 performance enhancement, 220
 permission, 219
 solutions, 432
 modeling, 176
 relaxation parameters, 430
 software, 418
 packages, components, 425
 usage, 424
 usage, *see* Fuel cells
- COMSOL Mutlyphysics[®], 418
- Concentration cells, 54–56
- Concentration gradient, 154
- Concentration losses, 18
 accounting, 209
 activation effects, impact, 174f
 calculation, 175
 cause, 172
 explanation, j - V curve (usage),
 172–173
 impact, *see* Activation losses
 implication, 171
 Nernstian effects, impact, 173f
 illustration, 174f
- Condenser heat, usage, 407
- Conduction, *see* Electronic conduction;
 Ionic conduction
- Conductivity, 147–153
 determination, 123
 diffusivity, relationship, 150–153
 expression, 128
 logarithmic plot, 156f
 mobility, relationship, 123
 physical meaning, 123–126
- Conductors
 contrast, *see* Electronic conductors
 resistance, 116
 structural differences, 124
- Conservation laws, 202
- Constant-current-density assumption,
 usage, 188
- Constant flow rate condition, *see* Fuel
 cells
- Constant-flux Sherwood number, 188
- Constant-pressure process, enthalpy
 expression, 34
- Constant stoichiometric operation,
 preference, 64
- Constant stoichiometry, 63
 condition, *see* Fuel cells
- Consumption rate, 166
- Contact resistance, 121
 association, 121–122
 variations, 122
- Convection
 diffusion, contrast, 162
 illustration, 162f
 dominance, 186
 usage, *see* Forced convection
- Convective-dominated flow,
 diffusive-dominated flow (dividing
 line/boundary), 164
- Convective fluid transport, 162f
- Convective forces, dominance, 163
- Convective heat-transfer coefficient,
 391
- Convective mass transport process,
 description, 187
- Convective transport, 176–194
 ignoring, 202–203
- Cooling requirements, 336
- Cooling systems, effectiveness ratios,
 337
- Copper concentration cell, 57f
 reaction, occurrence, 57–58
- Copper ions, concentration, 56–57
- Coulombic effect, 304–305
- Coupling coefficients, 113
 description, 114
- Cross-membrane interconnections, 334
- Crystalline electrolyte, carrier
 concentration, 126
- Crystalline ion conductors, 129–130
- Crystalline solid electrolyte, ion
 conductivity, 125–126
- Cubic fluorite-type crystal structure,
 306
- Cu/GDC/YSZ composites, usefulness,
 315
- Current
 electrochemical variables, 229–230
 interrupt, characteristics, 250
 interrupt measurement, 227
 defining, 230
 explanation, 250–252
 interrupt technique, idea, 250
 production, 81
 rate, 72–73
 response, 253f
- Current density, 200, *see also* Exchange
 currents; Low current densities;
 Reverse current density
 importance, 74
 limiting, 169–170
 profile, 432
- Current-voltage (j - V) curve,
 low-current-density regimen, 235f
- Current-voltage (j - V) measurement,
 227
 examination, 232–234
 interpretation, 234
 taking, 232
- Current-voltage-power relationships,
 example, *see* Step-down converter;
 Step-up converter
- Cyclic voltammetry (CV), 228, 230
 explanation, 252–254
 measurement, 252
 waveform, schematic, 253f
- D**
- Darcy's law, 420
- DC-DC converter
 account losses, 444
 output voltage, delivery, 443
 specification, 442, 444t
 usage, 435
- DC/DC converter
 fluctuating DC fuel cell voltage,
 usage, 347
- types, 347
- Dead zones, 220
- Decay rate, 79
- Dependent variables, relationship, *see*
 Thermodynamics
- Dielectric breakdown, 121
- Differentiation, chain rule, 152
- Diffusion
 atomistic view, 148f
 coefficient, 151–152
 contrast, *see* Convection
 electrochemical reaction, impact,
 164–168
 flux, 168
 layer
 schematic, 163f
 thickness, 244
 macroscopic picture, 148f

- Diffusive mass transport, dominance, 186
- Diffusivity, 114–115, 147–153
atomistic origins, 147–150
calculation, 125, *see also* Effective diffusivity
explanation, 429
information, *see* Intrinsic hopping rate
relationship, *see* Conductivity
- Dilute solution (ideal solution), species activity, 50
- Direct alcohol fuel cells, 297–298
- Direct borohydride fuel cells, 261, 272
- Direct electro-oxidation, 343
application, 345
- Direct ethanol fuel cells, investigation, 273–274
- Direct flame fuel cell, schematic illustration, 281f
- Direct-flame SOFCs, 261, 272
advantages, 280–281
explanation, 280–281
- Direct formic acid fuel cells, 261, 272
- Direct hydrocarbon fuel cells,
high-temperature internal reforming, 39
- Direct hydrogen storage systems,
comparison, 340t
- Direct liquid-fueled fuel cells, 273–276
- Direct methanol fuel cells (DMFCs), 261, 272
methanol usage, 46
systems, *see* Prototype portable DMFC systems
- Direct sodium borohydride fuel cells, theoretical open cell voltages, 275
reactions, 275
- Disorder, measure, 27
- DMFCs, *see* Direct methanol fuel cells
- Dopant ions, oxygen vacancies (interaction), 304
- Doped carbon, 301
- Doped ceria, 303–305, *see also* Gadolinia-doped ceria
advantage, 304
ionic conductivity, maximization, 315
materials, disadvantages, 305
- Doped ceria-based materials,
advantage, 314–315
- Double-layer capacitance, 239
- Dual-layer approach (gas-diffusion layer/catalyst approach), *see* Polymer electrolyte membrane fuel cell
- Durability, importance, 320–323
- Dynamic equilibrium, example, 147
- E**
- Earth, near-surface temperature, 463f
- Edge tabs, usage, 334
- Effective diffusivity
calculation, 167–168
explanation, 429
increase, 168
obtaining, 205–206
- Effective porosity, 254
- Effective resistance, decrease, *see* Activation process
- Efficiency, power density (trade-off), 436–437
- Efficiency axis, 18
- Efficiency loss, sources, 391–392
- EIS, *see* Electrochemical impedance spectroscopy
- ELAT, *see* Electrode Los-Alamos Type
- Electrical efficiencies, *see* Fuel cell systems; Net electrical efficiencies
example, 363t
- Electrical potential, 42
- Electric field force, 127–128
- Electricity
electrochemical generation, 15f
generation, supply chain, 477f
generators, emission factors, 456t
production, alternative, 4–5
supply management, usage, 359–360
- Electric power
plants, operation, 470–471
scenarios, 476–479
- Electric wall conditions, application, 429–430
- Electrocatalysis, relationship, *see* Exchange currents
- Electrochemical characterization techniques, 227
- Electrochemical equilibrium, 56–58
thermodynamic statement, 81
- Electrochemical half reactions, 6
- Electrochemical impedance spectroscopy (EIS), 227–228, 230
basics, 234–237
characterization, *see* Fuel cells
circuit modeling, equivalence, 238
data, 249
examination, 234–250
fuel cells, relationship, 237–238
Nyquist plot, 237–238
power, 248–249
- Electrochemical potential, 55
definition, 152
- Electrochemical processes,
heterogeneity, 72
- Electrochemical processing plant, 350
- Electrochemical reactions, 15
chemical reactions, contrast, 72
components, 45
electrons, transfer, 112
equivalence, 239
explanation, 16, 422–423
heterogeneity, 72f
HOR, comparison, 72
hypothetical situation, 92f
interface, physical representation/proposed equivalent circuit model, 240f
kinetics, 16
modeling, 239
parameters, 93
participation, 63
rate, finite characteristic, 75–76
- Electrochemical systems, 242
- Electrochemical variables, 229–230
- Electrode/catalyst degradation, 321
- Electrode-electrolyte interface, *see* Perfectly smooth electrode-electrolyte interface
impact, 315
schematic, 97f
- Electrode/electrolyte microstructure, 254
- Electrode Los-Alamos Type (ELAT), 296
- Electrode potentials, 75, *see also* Standard electrode potentials
concept, illustration, 43t
manipulation, 75f
- Electrodes
attachment, 293
kinetics, introduction, 71–76

- Electrodes (*cont.*)
 layers, 205–206
 materials, selectivity, 280
 structure transport, flow structure
 transport (contrast), 162–164
 tortuosity, 168
 transport, 164–176
- Electrode surface
 hydrogen, surface, 76
 smoothness, 91
- Electrolytes, 207
 carbon dioxide degradation, 274
 cell, anode/cathode identification, 14
 degradation, 322
 membrane, ohmic losses, 203–204
 resistance, dominance, 122–123
 stability requirement, 126
 thickness, 207
- Electrolyte supported MEA, 311
- Electrolyte-supported SOFCs, 204
- Electronic conduction, 16
- Electronic conductivity, 426
 values, calculation, 125
- Electronic conductors, ionic conductors
 (contrast), 123–124
- Electrons
 conductivity, *see* Metal
 energy, potential (impact), 74–75
 hole, formation, 146
 mobility, 125
 orbitals, evolution, 99f
 passage, 279
 release, 277
 stoichiometric coefficient, 58
 theft, 276
 transfer, 76
- Electro-osmotic drag, 135
 balance, 200
 coefficient, knowledge, 135
- Electro-osmotic water drag, impact, *see*
 Water
- Emission data
 application, environmental impact
 (quantification), 470–472
 control volume, 471–472
- Emission factor, usage, 471
- Endothermic reaction, HC fuel/steam
 combination, 375
- Endothermic reactors, 362
- Endothermic SR+WGS reaction,
 calculation, 380
- Energy
 accumulation, absence, 41
 buffers, usage, 351
 changes, *see* Negative energy change
 calculation, 32–33
 conservation
 equation, solving, 421
 explanation, 421
 law, 27
 conversion device, *see* Fuel cells
 creation, 64–65
 definition, 7
 density
 comparison, 10f
 explanation, 7
 Ragone plot, 366
 dumping, 29
 explanation, 7
 landscape, 155
 necessity, 31
 noble form, 28
 power/time equation, 7
 process, carbon dioxide emissions
 (impact), 466
 release/absorption, 5
 source, conversion, 13
 transfer, 27
 transit, 28
- Enthalpy (H), 26, 31, *see also* Reactant;
 Reaction enthalpy
 calculations, *see* Bond enthalpy
 calculations
 computation, *see* Formation enthalpy
 differential expression, 34
 temperature dependence, 36–37
 values, usage, *see* Standard enthalpy
 values
- Entropy
 change, 29
 concept, 27
 demonstration, 28f
 losses, 217–218
 meter, 30
 variables, 29–30
 variation, 36
- Environmental impact, quantification,
see Carbon dioxide
- Equivalent circuit elements, impedance
 summary, 245t
- Equivalent circuit fuel cell model,
 245–250
- Equivalent circuit models, 238
- Equivalent circuit models, proposal,
 240f
- Equivalent weight, 137
- Exchange currents
 density, 81
 concentration density, 86
 explanation, 426
 electrocatalysis, relationship, 88–91
- Exothermic POX reaction, calculation,
 380
- Exothermic reactors, 362
- Exponential Boltzmann factor, 156
- Ex situ characterization techniques, 227
 explanation, 254–256
 methods, 228
- External heat transfer, 400
- External reformers, examples, 344f
- External reforming, usage, 343
- Extrinsic carriers, 144
 contrast, *see* Intrinsic carriers
- F**
- Faradaic resistance, 239
- Faraday's constant, 44
 necessity, 73
 usage, 123, 126, 129
- Faraday's law, 72
- Feedback loop, implementation, 350
- Fermi level, 74–75
- Feynman, Richard, 25–26
- Fick's diffusion equation, 420
- Fick's law, 187, *see also* Binary
 diffusion
- Final state-initial state, form
 (computation), 35
- Fixed-flow-rate condition, 234
- Fixed stoichiometry condition, 234
- Flemion™ (Asahi Glass Company), 288
- Flip-flop designs, 335
- Flow channels
 design, 176
 diffusive transport, 203
 geometries, 191f
 mass transport, 182–185
- Flow field plates, usage, 15–16
- Flow rate, impact, 234
- Flow-rate condition, 234
- Flow structures, 226
 design, 189–192
 impact, 176

- geometry, interaction, 195
- transport, 176–192
- Fluent[®], 418
- Fluid enthalpy, 421
- Fluid mechanics, 176–181
- Flux, 111–112, *see also* Backward flux;
 - Charge flux; Forward flux; Molar flux; Net flux
 - balance, *see* Fuel cells
 - principle, 200
 - schematic, 112f
 - types, 112–113
- Forced convection, usage, 336
- Formation enthalpy, 36
 - computation, 35
- Formic acid (HCOOH), 275
 - fuel cells, *see* Direct formic acid fuel cells
- Forward activation barriers, changes, 85–86
- Forward current density (increase),
 - activation overvoltage (requirement), 88
- Forward flux, 147–148
- Forward hop, activation barrier, 150–151
- Forward reaction, 80
- Fractional vacancy concentration, 143
- Free energy, 26
 - curves, 89–90
 - difference, *see* Chemical free energy difference
 - maximum, overcoming, 77–78
- Fuel
 - availability, problems, 8
 - crossover, 121
 - delivery/processing subsystem, 331
 - explanation, 339–345
 - summary, 345
 - heat potential, 34–37
 - partial oxidation, 377
 - processing subsystem
 - complexity, 371–372
 - design, 371
 - example, 373f
 - processors
 - control volume analysis, 357
 - reactor design, 392
 - subsystem, 354–357
 - reformers
 - efficiency, description, 356
 - reactor design, 392
 - reforming, 372
 - overview, 372–385
 - utilization
 - efficiency, 63
 - losses, 61
 - work potential, 37–46
- Fuel cells, *see* Alkaline fuel cell;
 - Phosphoric acid fuel cell; Polymer electrolyte membrane fuel cell; Solid-oxide fuel cell
- activation overvoltage, equilibrium state, 105
- advantages, 8
- application, fuel/fuel system choice (qualitative summary), *see* Mobile fuel cell application; Stationary fuel cell application
- behavior, 174–175
- bipolar plates, examples, 337
- bipolar stack, 3D view, 333f
- catalysis, understanding, 98–101
- catalysts, function, 99
- cathode, 100
 - outlet, 215
- characterization, 225
 - defining, 226–227
 - techniques, overview, 227–228
- charge transport, 111, 114
 - resistance, characteristics, 118–123
- comparison, 282–283
- composite membranes,
 - incorporation, 291
- concentration loss, summary, 174–176
- concept, *see* Hydrogen-oxygen fuel cell
- constant flow rate condition, 63
- constant stoichiometry condition, 63
- control system, 350
 - schematic, 350f
- cross-section, 15f
- current
 - density, 208–209
 - load (500 mA), 251–252
 - steady-state value, 229
 - supply, 17
- CV curve, 253f
- definition, 3–5
- design
 - computational fluid dynamics, usage, 417–433
 - equations, usage, 418–423
- diffusion models, 206–207
- disadvantages, 8–9
- efficiency, 59–64, *see also* Real fuel cell efficiency
 - constant stoichiometry/constant flow rate conditions, contrast, 64f
 - ideal, *see* Reversible fuel cell efficiency
- EIS characterization, 248f
- electrodes, 165–166
 - porosity, 419
- electrolyte
 - classes, review, 126–147
 - materials, doping, 144
 - resistance, minimization, 121
- energy conversion device, 64–65
- environment, relationship, 20–21
- environmental impact, 451
- example, 6–7
- explanation, 272–282
- factory analogy, 8
- flooding, 16
- flow channels, gas flow (smoothness), 179
- flux balance, 200–202
- fuel supply, 66
- galvanostatic techniques, 229
- GDL, gas/electron transport, 295f
- geometric design guidelines, usage, 418
- geometry, construction, 424
- H₂-utilization, impact, 354, 356
- heat generation, 66
- heat recovery, importance, 400
- high-voltage requirements, 332
- impedance model, *see* Simple fuel cell impedance model
- innovations, acid test, 226
- i*-*V* curve
 - power density curve, combination, 18f
 - schematic, 17f
- j*-*V* curve, shape, 64
- j*-*V* performance behavior, 174
- laptop, DC power (usage), 347

- Fuel cells (*cont.*)
- LCA, 454–459
 - losses, 19
 - mass balances, 64–67
 - mass transfer losses, 175
 - mass transport, 161
 - model, 217–218
 - basics, 195–199
 - CFD basis, 218–221
 - geometry, construction, 424–425
 - modeling, 195
 - monitoring system, 350
 - net current
 - extraction, 85f
 - production, 92
 - operation, 13–16, 180
 - operational sweet spot, 332
 - parameters, 217
 - performance, 17–19
 - activation overvoltage, effect, 87f
 - concentration loss, impact, 175f
 - ohmic loss, effect, 118f
 - test conditions, 233–234
 - understanding, 227
 - physical property, calculation, 430, 432
 - planar anode-electrolyte-cathode structure, 13f
 - planar structures, 13
 - platinum electrodes, usage, 6
 - potentiostatic techniques, 229
 - power
 - conditioning, tasks, 345, 347
 - density curve, 17–18
 - density information, usage, 363
 - product removal, 15
 - properties, 226
 - reactant delivery (transport), 15
 - reaction
 - impact, *see* Kinetics
 - kinetics, 71, 96
 - kinetics, facility, 242
 - surfaces, providing, 13
 - real efficiency, calculation, 62
 - real voltage output, 19
 - relationship, *see* Electrochemical impedance spectroscopy
 - resistance, 118–119
 - additivity, 121–122
 - properties, 118–119
 - reversible thermodynamic efficiency, 62–63
 - reversible voltage, prediction (non-standard-state conditions), 46–59
 - schematic comparison, 9f
 - sealing method, example, 334f
 - sizing, case study, *see* Portable fuel cell
 - stacking, 19–20
 - steady-state galvanostatic measurement, 229
 - steady-state properties, 230
 - structures, 217
 - subsystems, 357–359
 - example, 358f
 - function, 354
 - gross/net efficiency, 359f
 - net electrical efficiency, 357
 - technology, 19–20
 - temperature, 441
 - test stations, 232
 - requirements, 230–232
 - thermal balances, 64–67
 - example, 66f
 - thermodynamically predicted voltage output, 19
 - thermodynamics, 25
 - equation, 52
 - total ohmic resistance, 122f
 - transport model, schematic, *see* Two-dimensional fuel cell transport model
 - types, 9–11
 - comparison summary, 283t
 - contrast, 11
 - description, 12t
 - overview, 261
 - vehicles
 - adoption, example, 475–476
 - annual hydrogen consumption, 459f
 - on-board fuel processor R&D, DOE discontinuation, 345
 - voltage, *see* Nonreversible fuel cell voltage; Reversible fuel cell voltages
 - description, Nernst equation (usage), 101–102
 - efficiency, 62–63
 - instantaneous rebound, 251–252
 - maintenance, difficulty, 18
 - obtaining, 209
 - profile, 117f
 - profile, shape, 83f
 - translation, 42
- Fuel cell stacks (subsystems), 331
- cooling, importance, 337–338
 - design, requirements, 332
 - electrical power output, 403
 - explanation, 332–335
 - hot stream placement, 410
 - requirements, 232–233
 - estimates, 436
 - usage, 434
 - voltage, generation, 446
- Fuel cell systems
- components, specification, 442–445
 - configuration, selection, 436
 - design, 417, 441
 - case studies, 351–367, 433–447
 - hot/cold streams, thermodynamic data, 402t
 - j*-*V* performance curves, 446
 - review, 445–447
 - electrical efficiency, 362
 - heat management, 397
 - in-use time, maximization, 365
 - iterative process, 433
 - neutral water balance, achievement, 356
 - optimization, 365f
 - overview, 331
 - resizing, 362
 - schematic, 332f
 - simplified equivalent circuit, 251f
 - size/operation lifetime comparison, 367f
 - slow-scan *j*-*V* curve measurements, acquisition, 233
 - thermal management subsystem, design, 409
- Fuel-processing subsystem
- example, 355f
 - function, 354
- Fuel-rich flame, proximity, 280–281
- Fuel species, electron movement, 5
- Fuel storage, availability, 8
- Full PEMFC model, description, 203t

G

Gadolinia-doped ceria (GDC), 144
advantages, 305, *see also*

Yttria-stabilized zirconia
electrolytes, conductivity, 145f
GDC10, 304–305
electronic/ionic conductivities,
305
GDC40, 315

ionic conductivity, increase, 302
SOFC electrolyte material,
candidate, 301–302

Gadolinium-doped ceria (GDC), 279

Galvanic cell, anode/cathode
identification, 14

Galvani potential, 81–83

Galvanostatic techniques, 229

Gas diffusion layer (GDL), 98
carbon cloths, usage, *see* Polymer
electrolyte membrane fuel cell
chemical surface oxidation, 321
electrode materials, 295–297
materials, 296–297
requirements, 294–295

Gas/electron transport, *see* Fuel cell
GDL

Gases

constant, 126
critical properties, 167t
depletion, effects, 215–217
flow
rates, 231f
turbulence, 179
fluids, equivalence, 177
heat capacity, 440t
kinetic theory, usage, 178
mixtures, usage, 179
permeability, 228, 255
pressures, impact, 205–206
transport
dominance, 162
modes, 192f

Gasification, 372, 383–384

Gasifiers, efficiencies, 384

Gasoline vehicle supply chain,
bottleneck processes
(identification), 457

Gaussian (computational tool), 99

GDC, *see* Gadolinia-doped ceria;
Gadolinium-doped ceria

GDL, *see* Gas diffusion layer

Generalized mass-transfer driving
force, 175

Geometric design guidelines, *see* Fuel
cells

Gibbs free energy (G), 30–31
calculation, 37–39
differential expression, 46, 48
electrical work, relationship, 39–40
impact, *see* Reversible voltage
reaction spontaneity, relationship, 42
relationship, *see* Reversible fuel cell
voltages
representation, 37
reversible fuel cell voltage,
relationship, 52
usage, 60
voltage, relationship, 42–43

Global warming, 461–462
emissions, relationship, 460–472
evidence, 462–463
external costs, environmental impact
(quantification), 469–470
fuel cell vehicles, impact, 464
hydrogen, contribution, 463–465
impacts, 469

Global warming potential (GWP), 466
values, 468

Gore-Select™ (W.L. Gore and
Associates, Inc.), 288

Gravimetric energy density (specific
energy), 7
calculation, 339

Gravimetric power density (specific
power), 7

Gravimetric Ragone plots, *see* Portable
power solutions

Greenhouse gases, concentrations, 462f

GWP, *see* Global warming potential

H

HC, *see* Hydrocarbon

Heat

absorption/release, 217
availability, 407
capacity effects, 36
delivery, 361
energy, chemical reaction (impact),
41
engine, operation, 40f
generation/heat balance, 226
generation rate, 440

management, 435
potential, *see* Fuel
relationship, *see* Work
release, 4
transfer, *see* External heat transfer;
Internal heat transfer

Heat exchangers

definition, 398
economic trade-off, 391
function, explanation, 398, 400
incorporation, impact, 405
network, redesign, 409
orientation, scenario analysis, 398
conducting, 409
performance, 401
specifications, 443t

Heat/expansion engine (description),
Carnot cycle (usage), 60

Heat recovery, 338, 361
amount, 338
efficiency, 362–363
calculation, 338
example, 363t
importance, *see* Fuel cells
subsystem efficiency, 361–362

Helmholtz free energy (F), 31

Heteropoly acid catalysts, 302

HHV, *see* Higher heating value

High-current-density region,
consideration, 171

High-energy reactant bonds, movement,
4–5

Higher heating value (HHV)

calculation, 458
efficiency, 60–61
yield, *see* Reversible HHV
efficiency

heat recovery efficiency, 478
usage, 356

High-frequency intercept, 242

High-potential-energy initial state, 34

High-power-density automotive stacks,
active liquid cooling
(requirement), 336

High-temperature fuel cells, 337

heat, supply, 343

High-temperature oxidizing
environments, 317

High-temperature WGS processing,
387

Honda Clarity (2008), rendering, 265f

- Honda FCX (2005) fuel cell car power train, 265f
- Honda Home Energy Station, 344f
- Hopping activation barrier, linear voltage gradient (impact), 150f
- Hopping mechanisms, usage, 16
- Hopping model, *see* Solid-state ionic conductor
- Hopping process
- atomistic view, 149f
 - attempt frequency, 125–126
 - physical picture, 149f
- Hopping rate
- exponential activation, 149
 - expressions, 151
- Hopping-type mechanisms, 147
- HOR, *see* Hydrogen oxidation reaction
- Hot reformate stream, temperature range, 401
- Hot streams
- identification, 398–401
 - minimum temperature difference, selection, 403–404
 - temperature-enthalpy diagram, 405f, 406f, 408f, 411f
 - temperature profiles, 400f
 - thermodynamic data, *see* Fuel cell systems
 - transfer, 441–442
- Hot *T-H* diagram, shift, 406
- Hot water heating system, heat delivery, 361
- Hydrocarbon-fueled fuel cell
- performance, improvement, 312
- Hydrocarbon (HC) fuel, usage, 371
- Hydrocarbon polymers, 289
- Hydrogen
- absorption, 76
 - peaks, 253f
 - adsorption, 252
 - atoms
 - chemical bonds, 26
 - separation, 100 - carriers
 - effectiveness, comparison, 341–342
 - usage, 339, 341–345 - charge transfer reaction, 90
 - combustion, 3–4
 - combustion reaction, splitting, 6
 - compression, 455
 - concentration cell, 54f, 56
 - components, 54–55
 - concentrations, *see* Anodes
 - profile, 432
 - desorption peaks, 253f
 - direct usage, 339
 - economy dream, schematic, 20f
 - flux, 200
 - fuel cells
 - operation, 343
 - platinum, usage, 297
 - STP, 65–66
 - vehicle fleet, supply chain, 455f - gas, mass transport, 76
 - generators, emission factors, 456t
 - ions, mass transport, 77
 - macroscopic energy, absence, 26f
 - molecule, separation, 76
 - reactants, 35
 - reduction reaction, 96
 - stoichiometric number, 216
 - storage, 339–341
 - efficiency, 340
 - methods, 339–341
 - systems, comparison, *see* Direct hydrogen storage systems - supply, 434
 - yield
 - calculation, 381
 - limitation, 390
- Hydrogen-fueled PEMFCs, 297
- Hydrogen-hydrogen bonds
- bonding energy, internuclear separation (contrast), 5f
 - breakage, 4
- Hydrogen oxidation reaction (HOR), 14, 76
- comparison, *see* Electrochemical reactions
 - electro-catalyst, 297
 - kinetics, speed, 94
 - standard-state exchange current densities, 95t
 - surface-limited reaction, 72f
- Hydrogen-oxygen (H₂-O₂) AFC, schematic, 266f
- Hydrogen-oxygen (H₂-O₂) combustion reaction, schematic, 4f
- Hydrogen-oxygen (H₂-O₂) fuel cell
- anode, cathode (contrast), 94f
 - cathode impedance, 247f
 - concept, 4f
 - example, 6f
 - model, equations, 423
 - protons/electrons, accumulation, 113f
 - reaction, 33, 42–43
 - reversible HHV efficiency, comparison, 61, 62f
 - standard-state potential, 45
- Hydrogen-oxygen (H₂-O₂) MCFC, schematic, 268f
- Hydrogen-oxygen (H₂-O₂) PAFC, schematic, 262f
- Hydrogen-oxygen (H₂-O₂) PEMFC, schematic, 264f
- Hydrogen-oxygen (H₂-O₂) SOFC, schematic, 271
- Hydrogen-oxygen PEMFC, 113–114
- Hydrogen-pump-mode configuration, 252
- Hydronium atom, formation, 100
- illustration, 100f
- Hydroperoxy (.OOH) radicals, 320–321
- Hydrophobicity, increase, 296
- Hydrophobic treatment, 296
- Hydroscopic oxide, inclusion, 290–291
- Hydroxide (OH)
- compounds, ionic conductivity, 128–129
 - groups, interactions, 101
- Hydroxide (ˉOH)
- concentration, 267
 - zinc oxidization, 279
- Hydroxy (.OH) radicals, 320–321
- I**
- ICE, *see* Internal combustion engine
- Ideal gas, species activity, 50
- Impedance
- behavior, 243
 - calculation, 241–242
 - component, 242
 - data, plotting, 236–237
 - measurements, 235–236
 - confinement, 237f
 - requirement, 248f
 - response, 236
 - measurement, 247–248
- Incremental voltage loss, calculation, 170–172

- Independent variables, relationship, *see* Thermodynamics
- Industrial Revolution, changes, 462–463
- Inertial forces, viscous forces (ratio), 177
- Infinite Warburg behavior, 244–245
- Infinite Warburg element, equation, 243
- Infinite Warburg impedance element, Nyquist diagram, 244
- Ink deposition, 293
- Ink formulation, 293
- Inlet condition, 429
- Inlet gases, preheating, 337
- Input voltage, increase, 347–348
- In situ electrochemical characterization techniques, 228–254
- Interconnect degradation, 323
- Interdigitated flow, 191f, 192
- Interfaces, impact, 204
- Interfacial potential, buildup, 81–82
- Intermediate-strength bond, usage, 90
- Intermediate-temperature SOFC design, 272
- Internal combustion engine (ICE) vehicles, supply chain, 452f
- Internal energy (U), 26, 31
change, 27, *see also* Closed system
- Internal fluid friction, measure, 177
- Internal heating, examples, 338
- Internal heat transfer, 400
- Internal reforming, usage, 343, 345
- Internuclear separation, *see* Hydrogen-hydrogen bonds
- Interstitials, 124
- Intrinsic carriers, 144
extrinsic carriers, contrast, 143
- Intrinsic hopping rate, diffusivity information, 149
- Ionic charge
carriers, 11, 142
transport, difficulty, 116
- Ionic conduction, 15
explanation, 16
- Ionic conductivity, 121
creation, 290
explanation, 426, 429
representative examples, 304f
- Ionic conductors, contrast, *see* Electronic conductors
- Ionic resistance, domination, 122–123
- Ionic transport, 130–132
occurrence, 317
- Ions
conduction, quantum
mechanics-based simulation, *see* Oxide electrolytes
- conductivity
addition, 271–272
characterization, 302
- conductors, usage, 153–154
- diffusivities, 126
- mobility, 125–126
- Iron oxidation reaction, standard-state potential, 45
- Irreversible reaction process, 91–92
- Isothermal reaction, computation, 37
- i-V* curve, schematic, *see* Fuel cells
- J**
- Jump attempt frequency, 149–150
- K**
- Kinetic energy, representation, 26f
- Kinetic Monte Carlo (KMC)
techniques, 156, *see also* Quantum-KMC technique
- Kinetic performance, improvement, 88–91
- Kinetic properties, 226
- Kinetics (production), fuel cell reactions (impact), 94–97
- KMC, *see* Kinetic Monte Carlo
- KOH aqueous solution, conductivity (calculation), 129
- KOH electrolyte solution, calculation, 129
- L**
- Laminar flow
computation, 181
conditions, micro-scale
channel-width dimensions (necessity), 278
turbulent flow, contrast, 180f
- LAMOX (La₂Mo₂O₉), materials
basis, 306–307
development, 307
- Lanthanum gallate (LaGaO₃), 307
LaGaO₃-based materials, disadvantages, 308
- Lanthanum strontium cobalite ferrite (LSCF), 272
- Lanthanum-strontium cobalite (LSC), 272
- Lanthanum-strontium ferrite (LSF), 272
- Lanthanum strontium gallium magnesium (LSGM)
conductivity, 307–308
ionic conductivity, 307, 308
- Lanthanum Strontium Manganite (LSM), 145–147, 279, *see also* Strontium-doped LSM
- LSM+YSZ, mixed interfacial layer, 311
- LSM-YSZ cathodes, MIEC alternatives, 318
- LSM-YSZ composite cathodes, formation, 318
- LSM-YSZ composite materials, oxidative degradation/secondary reaction, 322–323
phases, 311–312
reliance, 317–318
- Law of conservation of energy, *see* Energy
- Lawrence Livermore National Laboratories (LLNL), vehicle use (hybrid cryocompressed gas storage option), 340
- LCA, *see* Life cycle assessment
- Le Chatelier's principle
example, 49
usage, 375, 386
- Legendre transform, 30
- LHV, *see* Lower heating value
- Life cycle assessment (LCA), 451–459, *see also* Fuel cells
conducting, 470
emissions, 460
example, 457–458
methodology, 452–453
scenario analysis, 476–479
stages, 452
tool, 452–454
- Lifetime
importance, 320–323
issues, 226
- Linear Tafel fit, usage, 93
- Liquid-fueled portable power fuel cell system, battery system (comparison), 367f

- Liquid fuels, direct operation, 273
- Liquid-gas transport models, 204
- Liquid hydrogen, usage, 341
- Liquid-tin anode SOFCs (LTA SOFCs), 261, 272
 explanation, 281–282
 operating principles, 282f
 operation, 281–282
 power densities, level, 282
- Liquid water product, standard-state conditions, 43
- LLNL, *see* Lawrence Livermore National Laboratories
- Log-scaled j - V curve, 235f
- Lone pair substitution (LPS), 307
- Low carbon fuels, usage, 465–466
- Low current densities, 234
- Low-current-density j - V curve regimen, 234
- Low-energy associations, formation, 303
- Low-energy product bonds. movement, 4–5
- Lower heating value (LHV), 61
- Low-potential-energy final state, 34
- Low-power portable PEMFC systems, cooling (absence), 336
- Low pressure equation, Nernst equation (indication), 54
- Low-temperature acidic fuel cells, 97
- Low-temperature fuel cells, 336
 systems, heat production, 400
- Low-temperature methanol fuel cells, Pt basis, 273
- Low-temperature WGS processing, 387
- LPS, *see* Lone pair substitution
- LSC, *see* Lanthanum-strontium cobalite
- LSCF, *see* Lanthanum strontium cobalite ferrite
- LSCV-YSZ composites, 316
- LSF, *see* Lanthanum-strontium ferrite
- LSGM, *see* Lanthanum strontium gallium magnesium
- LSM, *see* Lanthanum Strontium Manganite
- LTA-SOFCs, *see* Liquid-tin anode SOFCs
- M**
- Man-made sources, U.S. emissions, 468t
- Mass balance, 437–442
 calculation, 433
 usage, 438–439
- Mass conservation, 202
 explanation, 419
 simplified form, 418
- Mass flow controllers, 230
- Mass storage efficiency, calculation, 340
- Mass transport, 243–245, *see also* Flow channels
 low frequencies, 247
 model, *see* Two-dimensional mass transport model
 properties, 226
 schematic, 165f
- Material, importance, 320–323
- Matrix material, fuel cell usage, 127
- Maxwell-Stefan equation, 420–421
- Maxwell-Stefan model, 206–207
- MCFC, *see* Molten carbonate fuel cell
- MEA, *see* Membrane electrode assembly
- Mechanical integrity, 121
- Mechanical stability, addition, 271
- Mediator-free approach, bacteria usage, 276
- Membrane degradation, 320–321
- Membrane electrode assembly (MEA), 264
 fabrication, *see* Polymer electrolyte fuel cell
 membrane fuel cell; Solid-oxide fuel cell
 manufacturing, 321
- Membraneless fuel cells, 261, 272
 design, Y-shaped micro-fluidic channel configuration basis, 277f
 explanation, 277–278
 simplicity/compactness, 278
- Mercury, injection, 254–255
- Meta
 macrocycles, 300
- Metal
 carrier concentration, calculation, 125
 electrodes, 114
 electron conductivity, 125
 interconnects, 319
- Metal-air cells, 261, 272
 explanation, 278–279
 zinc/aluminum/magnesium, usage, 278
- Metal-based GDL materials, 297
- Metal hydride
 cylinder
 attention, 443–444
 specification, 444t
 tank, 442
 usage, 341
 volumetric storage capability, 344
- Metallic electron conductor,
 free-electron model, 124
- Metal surfaces
 chemisorption, 77
 standard-state exchange current densities, 95t
- Methane (CH₄)
 carbon monoxide, selective methanation, 387–388
 consumption, *see* Reformer presence, 353
- Methanol (CH₃OH)
 combustion reaction, calculation, 35–36
 electro-oxidation kinetics, 274
 reaction, 273–274
 fuel system, equivalence, 342
 oxidation, 264
- Microporous layers, 296
- Microstates, 28–29
 availability, 29
- MIEC, *see* Mixed ion-conducting and electronically conducting
- MIECs, *see* Mixed ionic-electronic conductors
- Migration energy barrier, illustration, 156f
- Minimum temperature difference, selection, 403–404
- Mixed ion-conducting and electronically conducting (MIEC)
 ceramic material, 271–272
- Mixed ionic-electronic conductors (MIECs), 144–147, 317
 ceramic materials, 145–146
 conduction, 145

- development, 146–147
- prototype, 145–146
- SOFC cathode electrode, 146f
- Mixture
 - density, 181
 - molecular weight, 181
 - viscosity, 181
- Mobile fuel cell application, fuel/fuel system choices (qualitative summary), 346t
- Modeling, importance, 19
- Molar concentration, conversion, 187
- Molar diffusion flux, conversion, 166
- Molar flow rate, 73
- Molar flux, 112
- Molar input/output flow rate, *see* Species
- Molar quantities, 32–33
 - usage, 40
- Molar reaction quantities, 47, 48
- Molar-weighted reactant, differences, 35
- Moles, number (representation), 35
- Molten carbonate fuel cell (MCFC), 9, 261
 - advantages, 270
 - disadvantages, 270
 - electrolyte, usage, 268
 - example, 338
 - explanation, 268–270
 - high operating temperature, 270
 - molten (K/Li)₂CO₃, usage, 127
 - nickel-based electrodes, 270
 - operating temperature, 268
 - system, photograph, *see* Pressurized MCFC system
 - temperatures, operation, 371–372
- Momentum conservation, 420
- Multicomponent gas diffusion, 206–207
- N**
- Nafion, 288–289
 - chemical structure, 131
 - conductivity
 - local change, 135
 - water content, impact, 133–135
 - equivalent weight, 137
 - free volumes, aggregation, 131–132
 - ionic conductivity
 - temperature, contrast, 134f
 - water content, contrast, 134f
- membranes
 - behavior, *see* Polymer electrolyte membrane fuel cell
 - calculated properties, 140f
 - conductivity profile,
 - determination, 214
 - restriction, 288–289
 - water content, linear increase, 212
 - water fluxes, existence, 207
- sulfonic group, valence, 137
- water, absorption, 132–133
- water content, water activity (contrast), 132f
- water diffusivity, 138–140
 - constancy, 212–213
 - illustration, 138f
- Nafion, ionic transport, 130–132
- Nafion-based fuel cell system, 288–289
- National Emission Inventory (NEI), 469–470
- Natural desulfurized gas fuel,
 - composition, 353t
- Natural gas fuel, 353
 - processing, 455
- Natural greenhouse effect, 460
- Natural logarithm function, application, 103
- Negative energy change, 32–33
- NEI, *see* National Emission Inventory
- Neosepta-FTM (Tokuyama), 288
- Nernst equation, 49–54
 - application, 52
 - Butler-Volmer equations, relationship (understanding), 102
 - connection, *see* Butler-Volmer equation
 - derivation, 56–57
 - indication, *see* Low pressure equation
 - logarithmic form, 89
 - modification, 53
 - rederivation, 56
 - relationship, *see* Pressure usage, 105, *see also* Voltage
- Nernstian concentration losses,
 - consideration, 173
- Nernstian losses, 164–165
- Nernst voltage
 - concentration, impact, 170–171
 - decrease, 169
 - value usage, 170
- Net electrical efficiencies, 362–363
- Net flows, environmental impacts, 453
- Net flux, 151
- Net reaction rate, 80
- Neutral system water balance, 356
 - explanation, 356–357
- Neutral water balance, achievement, *see* Fuel cell systems
- nF*, usage, 44
- Nickel (Ni) agglomeration,
 - acceleration, 314
- Nitrates (NIT), impact, 461–462
- Nitrogen consumption, absence, 216
- Nitrogen flux, 209
- Ni-YSZ advantage, 314
- Ni-YSZ anode-based SOFCs, 314
- Ni-YSZ anodes, YSZ electrodes (matching), 313
- Ni-YSZ cermet
 - anode materials, 312–314
 - electrical conductivity, 313f
- Ni-YSZ ratio, impact, 314
- Nominal diffusivity, calculation, 167
- Nonideal gas, species activity, 50
- Nonideal solution, species activity, 50
- Nonlinear electrochemical systems, 237
- Nonplatinum ORR catalysts, 300–301
- Nonpolar gases, final parameters, 167
- Nonreversible fuel cell voltage, 33
- Nonspontaneous reaction, 38
 - temperature, 39
- Nonstandard fuel cell types, 272
- Non-steady-state conditions, 229
- Nonstoichiometry, 305
- Nonuniformities, 121
- No-slip condition, 178
- Nyquist impedance plot, *see* Resistor-capacitor series
- Nyquist plot, 241f, *see also* Electrochemical impedance spectroscopy; Parallel RC; Porous bounded Warburg element; Resistors; Simple fuel cell impedance model; Warburg element
 - example, 238f
 - generation, values (summary), 247t
- O**
- Ohmic activation losses, 238
- Ohmic conduction process, 239

- Ohmic losses, 18, 116, 245, *see also*
 Electrolytes
 effect, *see* Fuel cells
 Ohmic overvoltage, membrane
 resistance (impact), 139
 Ohmic properties, 226
 Ohmic resistance, 239
 Ohmic voltage losses, 120
 determination, 207
 Ohm's law, 234
 voltage loss, impact, 116
 OM, *see* Optical microscopy; Organic
 matter
 On-board fuel processor R&D, DOE
 discontinuation, *see* Fuel cells
 One-dimensional (1D) fuel cell model,
 199–218
 assumptions, 202–205
 considerations, 217–218
 examples, 208–217
 geometric effects, 220–221
 governing equations, 205–208
 One-dimensional (1D) PEMFC
 flux details, 201f
 model example, 210–215
 One-dimensional (1D) SOFC model
 example, 208–210
 flux details, 201f
 modification, 215–217
 One-phase AC power, requirement,
 349
 Open solid oxide fuel cell (no-chamber
 solid oxide fuel cell), 280
 Operating temperature, selection,
 437
 Optical microscopy (OM), 256
 Optimal λ , selection, 216
 Organic matter (OM), enhancement,
 461
 ORR, *see* Oxygen reduction reaction
 Orthorhombic tungsten bronze (OTB)
 crystal structure, 316–317
 Outlet condition, 429
 Oxidant species, electron movement, 5
 Oxidation, 14
 reaction, standard-state potential, *see*
 Iron oxidation reaction
 Oxide electrolytes, ion conduction
 (quantum mechanics-based
 simulation), 155–157
 Oxide ions, diffusing species, 155
- Oxygen
 concentration changes, 188
 concentration profile, 432
 deficiency, 378
 density
 increase, 189
 profile, 189f
 electro-reduction, 317–318
 flux, consumption, 187
 molar ratio, 67
 reactions, 35
 stoichiometric amount, 378
 stoichiometric number, 216
 supply rate, 189
 vacancy
 formation, 146
 hydration, 309
 y-direction mass transport, 187
 Oxygen-deficient perovskites, 316
 Oxygen-ion-conducting LaGaO₃,
 308f
 Oxygen-ion-conducting Perovskite
 oxides, 307–308
 Oxygen-oxygen bonds, breakage, 4
 Oxygen reduction reaction (ORR), 14
 catalysts, *see* Nonplatinum ORR
 catalysts
 complication, 94–95
 platinum, activity, 298
 standard-state exchange current
 densities, 96t
- P**
 Pacific Northwest National Laboratory
 microfuel processor, 344f
 PAFC, *see* Phosphoric acid fuel cell
 Palladium membrane, H₂ yield, 390
 Palladium membrane separation, 387
 explanation, 389–390
 Parallel flow, 191, 191f
 Parallel RC, circuit diagram/Nyquist
 plot, 243f
 Parallel serpentine flow, 191f
 Parasitic nonelectrochemical reactions,
 180
 Parasitic power, 357
 Partially humidified air, 133
 Partial oxidation (POX), 372
 fuel reformer, 378–379
 reactions, 377t
 reforming, 377–379
- Passive cooling, usage, 336
 PBI, *see* Phosphoric acid doped
 polybenzimidazole;
 Polybenzimidazole
 PCU, *see* Power control unit
 PEEK, *see* Polyaryletherketone
 PEMFC, *see* Polymer electrolyte
 membrane fuel cell
 Perfectly smooth electrode-electrolyte
 interface, 240
 Perfluorinated polymers, 288–289
 Permeability (K), 426, *see also* Gases
 Perovskite anode materials, 316
 Perovskite oxide, proton conductivity,
 308–309
 Perovskites, proton conduction, 309
 Perovskite structure, 308
 Persulfonated polytetrafluoroethylene
 (PTFE), 130, 131
 Phase-shifted current response, 236
 Phosphoric acid doped
 polybenzimidazole (PBI), 290
 impurities, sensitivity, 371–372
 membranes, conductivity, 290
 Phosphoric acid fuel cell (PAFC), 9, 97,
 261
 advantages, 263
 disadvantages, 263
 explanation, 262–263
 optimal performance, 262
 schematic, 262
 PHosphotungstic acid, 291
 Physical picture, *see* Simple fuel cell
 impedance model
 Pinch point analysis
 definition, 398
 multiple scenarios, evaluation,
 409–412
 steps, overview, 398–412
 Pinch point temperature, level, 412
 Planar anode-electrolyte-cathode
 structure, *see* Fuel cell
 Planar concentration, conversion, *see*
 Volume
 Planar connection designs, exploration,
 334
 Planar fuel cell, cross-sectional view,
 15f
 Planar series interconnection, 335f
 Planck's constant, usage, 79
 Plates, flow, 177–178

- Platinum-electrolyte-platinum membrane structure, usage, 54–55
- Platinum-free catalysts, outlook, *see* Polymer electrolyte membrane fuel cell
- Platinum (Pt)
alloys, 297–298
catalysts, complications, 300
usage, 299–300
atoms, hydrogen molecule approach, 99f
interaction, 99–100
catalyst surface, oxygen molecule (approach), 101f
current Pt/C catalysts, optimization, 299
expense, 297
Pt-particle-size deactivation effect, 299
usage, 298–299
- Poisoning, impact, 386
- Poly-2,2'-m-(phenylene)-5,5'-bibenzimidazole, *see* Polybenzimidazole
- Polyaryletherketone (PEEK), 289–290
structure, *see* Sulfonated PEEK
- Polybenzimidazole (PBI)
(Poly-2,2'-m-(phenylene)-5,5'-bibenzimidazole), 290f
- Polymer
chains
ion transport, schematic, 130f
sulfonation, 290
free volume, 130
ion conductor, 130
structure, density, 130
- Polymer electrolyte membrane fuel cell (PEMFC), 9, 97, 261, *see also* Hydrogen-oxygen PEMFC
acidic environment, 300
advantages, 264
anode catalysts, 297–298
applications, 130
cathodes
catalysts, 298–301
costs, reduction, 298
platinum-free catalysts, outlook, 301
construction, 263–264
disadvantages, 266
dual-layer approach (gas-diffusion layer/catalyst approach), 293–295
electrode/catalyst materials, 291–301
electrode structures, 292
electrolyte materials, 288–291
environments, 100
explanation, 263–266
GDL applications, carbon cloths (usage), 295–296
geometry, 186
impurities, sensitivity, 371–372
materials, 287
durability/lifetime issues, 320–321
MEA fabrication, 292–293
explanation, 293
process, 292f
membrane resistance, ohmic overvoltage, 214–215
model
challenge, 211–212
results, comparison, 199f
Nafion membranes, behavior, 135
PEMFC-based direct alcohol fuel cells, attractiveness, 298
physical properties, 213t
platinum, usage, 98
polymer membrane, usage, 11, 264
power density, 264
serpentine flow channels, 218
stacks
configuration, 333
usage, 265f
start-up/shutdown local cathode potential, 321
test station, 231f
volume conditions, 427f
- Polymer electrolytes, ionic conduction, 129–141
- Polymer ion conductors, 129–130
- Polymer-ionic composite membranes, 290–291
- Polytetrafluoroethylene (PTFE), *see* Teflon
- Pore size distributions, 254–255
- Porosity, 426, *see also* Effective porosity
definition, 254
determination, 228
explanation, 254–255
- Porous bounded Warburg element, circuit diagram/Nyquist plot, 245f
- Porous bounded Warburg model, 244
- Porous electrode geometries, impact, 15–16
- Porous structure, porosity, 168
- Portable fuel cell
sizing, case study, 363–367
system, 332f
optimization, 364–365
- Portable power solutions, gravimetric Ragone plots, 366f
- Portable SOFC system
design, 434–437
schematic, 435f
- Post-WGS reactor, 411
- Potassium hydroxide (KOH), concentration, 266
- Potential
gradient, 152
impact, *see* Electrons
rate, relationship, 83–88
- Potential energy
reaction progress, relationship, 4f
representation, 26f
- Potentiostatic techniques, 229
- Power
conditioning devices, usage, 359
definition, 7
electronics subsystem, 331, 359–360
example, 360f
explanation, 345–351
function, 354
explanation, 7
inversion, 345, 348–350
regulation, 345, 347–348
supply management, 351
- Power control unit (PCU), electrical power output management, 265f
- Power density
comparison, *see* Technologies
curve, *see* Fuel cells
combination, *see* Fuel cells
explanation, 7
- POX, *see* Partial oxidation
- Preheater, heat delivery, 361
- Pre-leached Pt-alloy catalysts, poisoning rates (reduction), 300
- Pre-leaching process, introduction, 300

- Pressure
gauges, usage, 230
impact, 233–234
temperature/Nernst equation, relationship, 53
- Pressure-swing absorption, 387
- Pressure swing adsorption (PSA), 389
- Pressurized MCFC system, photograph, 269f
- Primary fuel reforming reactions, chemical reaction characteristics (comparison), 374t
- Primary H₂ production methods, advantages/disadvantages, 375t
- Processor efficiency losses, 390–392
- Product
concentration, 165–166
profile, 166f
formation enthalpies, difference, 35
surface concentration, 80
- Product/reactant species, 52
- Product removal, 16, *see also* Fuel cells
- Products-reactants, impact, 35
- Proton conducting BaZrO₃, 308f
- Proton-conducting Perovskites, 308–309
- Proton-conducting polymer electrolyte membrane, usage, 263–264
- Proton conducting polymer (Nafion), conductivity, 302f
- Protons
accumulation/depletion, 114
conduction, occurrence, 290
flux, 200
introduction, 309
release, 277
water, relationship, 135
- Prototype portable DMFC systems, 274f
- PSA, *see* Pressure swing adsorption
- Pt-based catalyst, usage, 97
- Pt catalyst, effectiveness (maximization), 293
- PTFE, *see* Persulfonated polytetrafluoroethylene
- Pulse-width voltage modulation, DC transformation, 349f
- PureCell™ 200 power system, photograph, 263f
- Pure LaCrO₃, conductivity, 319
- Pure resistors, representation, 242
- Pyrochlore-type oxides, mixed ionic/electronic conductivity, 317
- Q**
- Quantum-KMC technique, 156–157
- Quantum mechanics, 98–101
- R**
- Radial frequency, relationship, 235–236
- Raw material production, supply chain, 454
- Reactants
concentration, 165–166
changes, 232–233
decrease, 89, 173
effects, inclusion, 90
increase, 89
consumption rate, 65
convective mixing, 165f
crossover, 127
flux, 168
fuel, enthalpy, 65
surface concentration, 80
time dependence profile, 166f
transport, 15–16
- Reaction
current per unit area, 90–91
enthalpy, 34–37
calculation, 34–36
input, electrical power output (difference), 65–66
interface, Galvani potential, 84
reduction, 84f
kinetics
description, Butler-Volmer equation (usage), 171
Tafel simplification, 241
writing, 102–103
losses, 165
increase, 169
net rate, calculation, 79–80
potential, equilibrium, 81–83
sites, increase, 90–91
spontaneity, relationship, *see* Gibbs free energy
- standard-state molar free-energy change, 51–52
surface area, maximization, 97
variation, treatment, 87
- Reaction rates, 75–76, *see also* Net reaction rate
activation energy, impact, 78–79
concentration, impact, 171–172
equilibrium, 81
formula, 80
theory, 149
- Real fuel cell efficiency (practical fuel cell efficiency), 61–64
- Redox active dye molecules, 276
- Reduction, 14
- Reformate stream, 354
CO, chemical removal, 388t
- Reformer
efficiency
description, *see* Fuel losses, 390–392
example, *see* External reformers; Internal reformers
exothermic operation, *see* Catalytic fuel reformer
methane consumption, 376–377
reaction, 275–276
- Reforming processes, H₂ yields (variation), 372
- Relaxation parameters, *see* Computational fluid dynamics
- Resistance, definition, 119
- Resistance scales
area, inclusion, 119–120
thickness, inclusion, 120–121
- Resistive Faradaic impedance, 242
- Resistor-capacitor series, Nyquist impedance plot, 241
- Resistors
circuit diagram, 239f
Nyquist plot, 239f
- Results analysis, *see* Solution process/results analysis
- Reverse activation barriers, changes, 85–86
- Reverse current density, 81
- Reverse reaction, 80
activation barrier, 80
rate, 81
- Reversibility, 33

- Reversible fuel cell efficiency, ideal, 60–61
- Reversible fuel cell voltages, 33
decrease, 47
temperature, increase, 47–48
defining, 47
Gibbs free energy, relationship, 47, 49
variation, 59
pressure, relationship, 49
- Reversible HHV efficiency
comparison, *see* Hydrogen-oxygen fuel cell
yield, 60
- Reversible thermodynamic efficiency, 62, *see also* Fuel cells
- Reversible thermodynamic engine, diagram, 40f
- Reversible voltage
computation, 43–46
magnitude, Gibbs free energy (impact), 42–43
prediction, non-standard-state conditions, *see* Fuel cells
pressure, relationship, 49
temperature, contrast, 48f
variation
concentration, relationship, 49–54
pressure, relationship, 48–49
temperature, relationship, 46–48
- Reynolds number, 177
- Right-hand side (RHS), 420–421
- Rotational diffusion transfer
mechanisms, reliance, 291
- Rotationally mobile tetrahedral oxy-anion groups, 291
- Ruthenium
consideration, 273
effectiveness, 298
- S**
- Salt bridge, connection, 58
- Salt water battery, components, 54
- Samaria-doped ceria (SDC), 304
- Scanning electron microscopy (SEM), 256
- SDC, *see* Samaria-doped ceria
- Sealant degradation, 323
- Sealing material, *see* Solid-oxide fuel cell
selection, 321
- Sealing method, example, *see* Fuel cells
- Secondary-ion mass spectrometry (SIMS), 256
- Selective oxidation reactor, hot stream
placement, 410
- Self-heating effects, impact, 336
- SEM, *see* Scanning electron microscopy
- Semi-empirical expression, usage, 179
- Serpentine flow, 191, 191f
channel fuel cell model, isometric view, 218f
channel model, cell j - V curves, 219f
channels, *see* Polymer electrolyte membrane fuel cell
- Seven layer MEA, 296
- Shear force, impact, 177
- Shell, usage, 3
- Sherwood number, *see* Constant-flux Sherwood number
- Shewanella putrefaciens, 276
- Shorting, 121
- Siemens-Westinghouse SOFC/micro 220-kW gas-turbine system, 271f
- Siemens-Westinghouse SOFC systems, 335
- Siemens-Westinghouse tubular SOFCs, photograph/end-on detail, 336f
- Signal voltage perturbation, application, 237f
- Silicotungstic acid, 291
- Silp boundary conditions, usage, 178
- Simple fuel cell impedance model
physical picture/circuit diagram/Nyquist plot, 246f
- Simplified PEMFC model, description, 205t
- SIMS, *see* Secondary-ion mass spectrometry
- Single-chamber flow structure, making, 176
- Single-chamber SOFCs, 261, 272
designs, advantages, 279–280
explanation, 279–280
operating principle, 280f
platinum electrodes, usage, 279
- Single channel fuel cell geometry, 425f
- Single-phase inverter solution, example, 349–350
- Sintering, impact, 386
- Sinusoidal current response, 236f
- Sinusoidal voltage perturbation, 235–236
equations, 240
illustration, 236f
- Size sensitivity, 51
- SOFC, *see* Solid-oxide fuel cell
- Solid acid membranes, 291
- Solid-electrolyte ionic conductivity
values, 126
YSZ, usage, 270
- Solid-oxide fuel cell (SOFC), 9, 261
advantages, 272
anode electrocatalyst material, 308
anode materials, usage, 270–271
assumptions, 204
BOP components, design parameters (initial values), 438t
catalyst/electrode materials, requirements, 310
cathode
electrode, 146f
materials, usage, 270–271
ceramic membrane, usage, 11
CO, impact, 95–96
current density, 210
design, *see* Intermediate-temperature SOFC design
end/side views, *see* Tubular SOFC design
disadvantages, 272
dual-layer approach, 310
electrode/catalyst materials, 309–320
electrode structures, 145
electrolytes
applications, 307–308
conductivity, 143–144
dopants, usage, 143
materials, 301–309
explanation, 270–272
fabrication stack materials, exposure, 322
flux balance, 202
hydrogen reduction reaction, 96
interconnect materials, 318–319
materials, 287
durability/lifetime issues, 322–323
MEA fabrication, 310–312
approaches, 311f
model, gas depletion effects, 217
one-dimensional model, 199

- Solid-oxide fuel cell (SOFC) (*cont.*)
 operating temperature, 272
 operation stack materials, exposure, 322
 oxygen (O^{2-}) flux, impact, 207
 performance, enhancement, 313
 physical properties, 210t
 polarization curve, 437f
 sealing issues, 334–335
 sealing materials, 319–320
 solutions, 431f–432f
 stack
 design parameters, initial values, 438t
 specification, 445t
 structure, modeling assumptions, 204
 system
 flow rates, 439t
 specification, 445t
 thermal balance parameters, 442t
 temperatures, operation, 371–372
 test station, elaboration, 232
 volume conditions, 427t–428t
- Solid-state ion-conducting materials, 130
- Solid-state ionic conductor, hopping model, 124
- Solution convergence rate, 430
- Solution process/results analysis, 430–433
- Spatial separation, achievement, 6
- Species
 chemical potential, 55–56
 concentration, 102
 conservation, 202
 explanation, 420–421
 simplified form, 418
 consumption/production, 163
 flux, 113
 molar input/output flow rate, 66–67
 mole fraction, 205–206
 transport, effectiveness, 243–244
 types, *see* Charged species
 Warburg coefficient, 243
 z-profile, calculation, 207
- Specific energy, *see* Gravimetric energy density
- Specific power, *see* Gravimetric power density
- Spontaneous processes,
 nonspontaneous processes
 (separation), 29
- Spontaneous reaction, 42
- SR, *see* Steam reforming
- Stability, importance, 320–323
- Stacks, *see* Fuel cell stacks
- Standard electrode potentials, 43–46
- Standard enthalpy values, usage, 35
- Standard state conditions, 33
- Standard-state exchange current
 densities, *see* Hydrogen oxidation reaction; Metal surfaces; Oxygen reduction reaction
- Standard-state potential, *see* Hydrogen-oxygen (H_2 - O_2) fuel cell
- Standard-state voltage, production, 43
- Standard temperature and pressure (STP), 33, *see also* Hydrogen maximum likely diffusive O_2 flux, 162
- STAR-CD[®], 418
- State-initial state, 32–33, *see also* Final state-initial state
- Stationary combined heat/power systems, case study, 351–363
- Stationary fuel cell application, fuel/fuel system choices (qualitative summary), 346t
- Stationary residential-scale fuel cell system, 332f
- Steady-state condition, 187
- Steady-state j - V measurement, 229
- Steady-state operation, 40
- Steady states, 232–233
- Steady-state system, requirement, 232–233
- Steam generator, heat delivery, 361
- Steam reformer, design, 376
- Steam reforming (SR), 372, 375–377 reactions, 376t
- Steam-to-carbon ratio, 377
 estimation, 379–380
 value, 379
- Step-down converter, 347
 current-voltage-power relationships, example, 348t
- Step-up converter, 347–348
 current-voltage-power relationships, example, 348f
- Stoichiometric number, 216
 concept, 215–216
- Stoichiometry factor, 65
- Stokes's law, 127–128
- Storage device, fuel cell system charging, 360
- STP, *see* Standard temperature and pressure
- Streams, thermal data determination, 401
- Strontium-doped LSM, 272
- Structure determinations, 228
 explanation, 256
- Subsystems, *see* Fuel cell stacks
- Sulfates (SULF), impact, 461–462
- Sulfonated hydrocarbon polymers, 289–290
- Sulfonated PEEK, structure, 289–290
- Sun energy, infrared (IR) radiation, 460
- Sunlight, absorption, 461f
- Supply chain, *see* Internal combustion engine
 energy/polluting portions, identification, 454–455
 environmental performance, 453
 research and development (R&D), 476–477
 sketching, 454, 477
- Supply management, usage, *see* Electricity
- Surface-to-volume ratios,
 maximization, 13
- Sutherland's law, 178
- Symmetry condition, 430
- T**
- Tafel equation, 91–93
 combination, 188
- Tafel fit, usage, *see* Linear Tafel fit
- Tafel-like kinetic process, calculation, 241–242
- Tafel slope, 92
- TEC, *see* Thermal expansion coefficient
- Technologies, power density comparison, 10f
- Teflon (polytetrafluoroethylene) (PTFE), 130–131, 296
 backbone
 hydrophobic nature, 132
 usage, 288–289

- TEM, *see* Transmission electron microscopy
- Temperature
- changes, 232–233
 - dependence, 138
 - effects, 93–94
 - excursions, 391–392
 - impact, 233
 - increase, 90
 - profile, 432
 - relationship, *see* Pressure
 - sensors, usage, 230
- Temperature dependence, *see* Enthalpy approximation, 38
- Temperature-enthalpy diagrams (*T-H*)
- construction, 398, 404–407
 - usage, 408
- Ternary anodes, composition, 315
- Test conditions, 233–234
- Tetragonal tungsten bronze (TTB)
- crystal structure, 316–317
- Theoretical open cell voltage, *see* Direct sodium borohydride
- Thermal balance, 437–442
- calculation, 433
 - usage, 439–442
- Thermal conductivity, 318
- explanation, 429
- Thermal data, identification, 401–403
- Thermal expansion coefficient (TEC), 318
- matches, 318
 - difficulty, 335
- Thermal expansion compatibility, 271
- Thermal management subsystem, 331, 360–362
- design, 397
 - example, 361f
 - explanation, 336–338
 - functions, 354
 - representation, 351
- Thermodynamic engine
- operation, constant temperature/pressure, 40–41
 - steady state, 41
- Thermodynamic equilibrium, 117f
- Thermodynamic plots, evaluation, 404–409
- Thermodynamic potentials, 29–32
- defining, 31, 50
 - pictorial summary, 32f
- Thermodynamics, *see* Fuel cells
- definition, 25–26
 - dependent variables, independent variables (relationship), 30
 - equilibrium, 81
 - first law, 27
 - review, 25–32
 - second law, 27–29, 41
- Thermodynamic voltage, decrease, 169
- Thin solid acid membranes, fabrication, 291
- Three-phase AC power, requirement, 349
- Time, electrochemical variables, 229–230
- Time-dependent RC, 250–251
- Time-dependent
- voltage/time-dependent current, ratio, 235
- Time-invariant techniques, 230
- Tortuosity, 168
- explanation, 429
- Total air supply, calculation, 439
- Total charge transport flux, 152–153
- Total concentration loss, generalization, 172
- Total ohmic resistance, *see* Fuel cells
- Total viscosity, calculation, 180–181
- TPBs, *see* Triple phase boundaries
- Transfer coefficient, 84–85
- explanation, 426
- Transmission electron microscopy (TEM), 256
- Triple phase boundaries (TPBs), 97
- sites, 310
- Triple-phase zone, concept, 145
- Triple phase zones, 97, 293
- TTB, *see* Tetragonal tungsten bronze
- Tubular geometries, usefulness, 335
- Tubular SOFC design, end/side views, 335f
- Turbulent flow, contrast, *see* Laminar flow
- Two-dimensional (2D) fuel cell model, geometric effects, 220–221
- Two-dimensional (2D) fuel cell transport model, schematic, 186f
- Two-dimensional (2D) mass transport model, 185–186
- Two-phase flow models, 204
- U**
- Uncharged species, transport, 161
- Unstructured grids, disadvantage, 425
- Upstream chemical reactions, 337
- U.S. electric power, derivation, 457
- V**
- Vacancies, 124
- concentration, 142, *see also* Fractional vacancy concentration
- van't Hoff isotherm, 52
- Vaporization, latent heat, 60–61
- Vehicle emissions, EPA tabulation, 469
- Vertical stacking, 332–333
- Vertical stack interconnection, 333f
- Viscosity, 114–115, *see also* Mixture calculation, *see* Total viscosity parameters, 179t
- characteristic, 177
 - explanation, 429
 - pressure dependence, 179
- Viscous drag interaction, 420
- Volatile organic compounds (VOCs), 461–462
- nonmethane organic compounds, 472
- Voltage
- building, 332
 - current, ratio, 234
 - determination, Nernst equation (usage), 55
 - development, 55
 - drop, 154
 - efficiency, *see* Fuel cells
 - electrochemical variables, 229–230
 - gradient, 152–153
 - direction, 116
 - effective strength, 153–154
 - modification, 151
- losses, 61, 116
 - charge transport, impact, 114–118
- rebound process, 250–251
 - relationship, *see* Gibbs free energy

- Volume
concentration, planar concentration (conversion), 147–148
conditions
 explanation, 426–430
 physical properties, 426
storage density, calculation, 340
variables, 29–30
Volumetric air flow rate, 439
Volumetric power density, 7
 calculation, 339
 Ragone plot, 366
Vulcan XC-72, 294
- W**
- Wall condition, 429
Warburg circuit elements, 243
Warburg coefficient, *see* Species
Warburg element
 circuit diagram/Nyquist plot, 244f
 equation, *see* Infinite Warburg element
Warburg model, *see* Porous bounded Warburg model
Warm-up, usage, 233
Water
 back diffusion, 136
 concentrations, *see* Anodes
 diffusivity, 136
 flux balance, 200–201
 flux/charge flux, ratio, 201–202
 flux existence, *see* Nafion
 gas shift reaction, 372
 liquid presentation, 199
 molecules, dragging, 139
 movement, electro-osmotic water drag (impact), 136
 phase changes, 217
Water gas shift (WGS) processing, *see* High-temperature WGS processing; Low-temperature WGS processing
Water gas shift (WGS) reaction, 383
 calculation, 375
 examination, 385–387
 increase, 376
Water gas shift (WGS) reactors, 385–387
 hot reformat stream, exit, 398
 usage, 354
Water vapor
 activity, quantification, 133
 emission, source location, 464
 form, 186
 quantity, calculation, 465
 saturation pressure, 133
WGS, *see* Water gas shift
Work
 heat, relationship, 28
 nobility, 28
 potential, *see* Fuel
- X**
- X-ray diffraction (XRD), 256
X-ray photoelectron spectroscopy (XPS), 256
- Y**
- Yttria-stabilized zirconia (YSZ), 141f
 advantages, 305
 conductivity, 142f
 dopants, usage, 143
 electrolytes, conductivity, 145f
 GDC advantages, 305
 ionic conductivity, 155
 mixing, 311–312
 SOFC electrolyte material, candidate, 301–302
 thermal expansion, 308
 usage, 303, *see also* Solid-oxide fuel cell
 vacancies, availability, 303
 YSZ-based SOFCs, 317–318
Yttrium doped barium zirconate (Y:BaZrO₃) (BYZ), 309
- Z**
- Zero-cost cathode catalyst, volumetric catalytic activity, 300
Zinc-air cell, schematic diagram, 278f
Zirconia, yttria (addition), 141
Zirconium cations (Zr⁴⁺), replacement, 303