

-
- AC energy meters *see* energy meters
 acceleration signals 36–7
 alternators 165–75
 bearing failure 166–70, 172
 under leakage current 174–5
 current flow through bearings 171
 design features 166, 168–70
 dimensional accuracy of bearings 170
 lubricants 167–8, 174
 magnetic flux density 165, 170, 172–4
 shaft voltages 170, 171
 stray voltage development 165, 173–4
 axial forces 149–53
 determination of 152
 under load conditions 149, 150
 measurement technique 150–2
 under no-load conditions 149, 150
 unbalanced magnetic pull 149
 axial length 134, 136
 Bakelite linings 162–3
 balancing trials 158
 barium ferrite 219
 bearing failure
 in alternators 166–70, 172, 174–5
 detection 2–3
 and electric current 85, 100–2
 leakage current 174–5
 localized current 79–80
 in electric power equipment 63
 bearing impedance 94–6, 181
 bearing inductance 181–2
 bearing resistance 74
 bearing turbulence and oil grade 117–20
 cage and roller slip 40–55
 comparison of bearings 51–2
 in DDHPB 230–1
 defect frequencies 41, 43–4
 energy levels 43–4, 50–1
 experimental procedure 41–2
 negative slip 40, 49
 oil film thickness 50
 positive slip 40, 49
 spectral analysis technique 42
 capacitance 95–6, 181
 centrifugal forces in DDHPB 239
 charge accumulation 95–6
 clearance ratios *see* oil grades and
 clearance ratios
 coefficient of friction 233
 constant moment of friction 132, 133
 corrugated pattern formation 90–2
 current flow
 through bearings 56–7, 63, 67–9, 171
 through nuts and bolts 61
 cycles/revolutions for crater formation
 182–3, 184
 damping characteristics of bearings 156
 DDHPB 228–40
 cage and roller slip 230–1
 centrifugal forces 239
 coefficient of friction 233
 concept 229–30
 frictional torque 231–2, 237–8
 operation 229–30
 performance evaluation 232–3
 rotational speed 230, 231–2, 238
 stress distribution 239
 temperature rises 235–8
 test conditions 233–5

- defect frequencies 2–3, 7–9
 - in cage and roller slip 41, 43–4
- deteriorated lubricant 177, 180, 184
- dimensional accuracy of bearings 170
- dye-penetration tests 159
- eccentricity ratio 114, 115
- elastohydrodynamic film thickness 23
- electric current 84–102
 - bearing failure 85, 100–2
 - capacitance accumulation 95–6
 - charge accumulation 95–6
 - contact temperature and stresses 96–8
 - corrugated pattern formation 90–2
 - electro-adhesion forces 92–4
 - flow of current
 - through bearings 56–7, 63, 67–9, 171
 - through nuts and bolts 61
 - grease resistivity 86–9, 93, 98–9
 - impedance responses 94–6, 181
 - insulation 60–1, 64–5, 84
 - leakage effects 64, 92–4, 98–9, 174–5
 - magnetic flux development 85, 92–4
 - repeated machine starting and stopping 99–100
 - shaft voltages 85
 - threshold voltages 94–5
 - see also* localized electrical current
- electric power equipment 56–65
 - bearing arrangement 57
 - failed bearing analysis 63
 - flow of current
 - through bearings 56–7, 63, 67–9, 171
 - through nuts and bolts 61
 - grease leakage 60
 - grease pipe outlet 58–60, 63
 - grounding brushes 60
 - instrumentation cables 60, 63
 - insulation damage 60–1, 64–5
 - leakage current 64
 - lubricant analysis 58, 64
 - magnetic flux density 63, 65
 - seals 60
 - shaft voltages 56–7, 58, 61–2
 - spectrum analysis 58
 - vibration levels 58, 62
 - see also* electric current
- electrical pitting 184
- electro-adhesion forces 92–4
- energy levels 7–9, 10–11
 - in cage and roller slip 43–4, 50–1
 - of inductive circuit 181–2
- energy loss 23
- energy meters 214–27
 - jewel bearings 214, 215
 - magnetic suspension bearings 215–27
 - rotating system 214–15, 222
- envelope detection system 5–7
- excitation forces 155–6
- field strength 75
- flow of current
 - through bearings 56–7, 63, 67–9, 171
 - through nuts and bolts 61
- flux density *see* magnetic flux density
- four-ball tests 141, 146
- friction 30–3
 - coefficient 233
 - constant moment 132, 133
- frictional torque studies 222–7, 231–2, 237–8
 - speed-based 223
 - time-and-revolutions to standstill 224
- grease leakage 60
- grease pipe outlets 58–60, 63
- grease resistivity 86–9, 93, 98–9
- grounding brushes 60, 71
- guide pin assembly 220, 222
- high-frequency resonance technique (HFRT) 1–19, 24
 - bearing malfunction detection 2–3
 - defect frequencies 2–3, 7–9
 - energy levels 7–9, 10–11
 - envelope detection system 5–7
 - performance comparisons 12–19
 - recording system 4
 - resonance detection 4–5
 - resonant frequencies 3
 - vibration signature 4, 7
- homopolar flux 68, 171
- hydrodynamic journal bearings 130–8
- impedance responses 94–6, 181
- induced voltage 73–4
- inductance 181–2
- instrumentation cables 60, 63
- insulation 60–1, 64–5, 84

- jewel bearings 214, 215
- journal and bearing contact width 181
- kurtosis values 24, 28–9, 36–7
- leakage current 64, 92–4, 98–9, 174–5
- life prediction of bearings 37
- life prediction of oil 139–48
- localized electrical current 67–80
 - bearing arrangement 69–70
 - bearing failure 79–80
 - bearing resistance 74
 - field strength 75
 - grounding brushes 71
 - induced voltage 73–4
 - magnetic flux density 75–6
 - potential difference 77–8, 80
 - residual flux density 78
 - shaft voltage causes 67–9
 - speed of rolling elements 73
 - theoretical model 72–5
 - time span of flute appearance 76, 79
 - see also* electric current; electric power equipment
- lubricants
 - in alternators 167–8, 174
 - in electric power equipment 58, 64
 - grease leakage 60
 - grease pipe outlets 58–60, 63
 - grease resistivity 86–9, 93, 98–9
 - in synchronous condensers 178, 180, 184
 - use of deteriorated lubricant 177, 180, 184
 - see also* oil
- magnetic flux density
 - in alternators 165, 170, 172–4
 - effect on bearings 173
 - and electric current 85, 92–4
 - in electric power equipment 63, 65
 - and localized electrical current 75–6
 - origins 173–4
 - residual flux density 78
- magnetic suspension bearings 215–27
 - construction 221–2
 - design 216–20
 - frictional torque studies 222–7, 231–2, 237–8
 - speed-based 223
 - time-and-revolutions to standstill 224
- guide pin assembly 220, 222
- magnet material 218–19
- magnet to disc fixing 220
- manufacturing requirements 220
- mechanical requirements 220–1
- size of magnets 226
- motor starting temperature 160, 163
- negative slip 40, 49
- noise causes 200
- nomographs 112–14, 134–5
- non-bonding of bearing liners 161
- oil
 - flow in bearings 107
 - four-ball tests 141, 146
 - life estimation 139–48
 - oxidation 139–40
 - stickiness of film 156
 - thickness of film 50
 - see also* lubricants
- oil grades and clearance ratios 106–28
 - bearing turbulence 117–20
 - eccentricity ratio 114, 115
 - functional nomographs 112–14
 - performance of bearings 114–16
 - and safe load-carrying capacity 125–6
 - and temperature 107–8, 116–17, 125
 - and transition speed 117–20, 120–5
 - viscosity coefficients 106, 107–12
 - viscosity integral 106, 112–14, 120–5
 - viscosity-temperature relationship 109
 - oxidation of oil 139–40
- performance tests 22–39
 - acceleration signals 36–7
 - comparison of performance 12–19, 38
 - of DDHPB 232–3
 - energy loss 23
 - kurtosis values 24, 28–9, 36–7
 - life prediction of bearings 37
 - and oil grades 114–16
 - procedures 26–7
 - shock pulse levels 24, 28, 33–5
 - temperature of bearings 23, 27–8
 - friction effects 30–3
 - test rigs 25–6
 - vibration 24, 29, 37
 - velocity calculation 36
 - see also* reliability analysis

- positive slip 40, 49
- potential difference 77–8, 80
- pump-rod joints 212
- radius calculations 133–4, 136
- RBOT (rotating bomb oxidation test) 139–48
- real-time analysers (RTA) 42
- reciprocating pump performance 205–9
- recording systems 4
- reliability analysis 1–19
 - bearing defects 1, 2–3
 - experimental procedures 3
 - performance comparisons 12–19
 - see also* performance tests
- repeated machine starting and stopping 99–100
- repulsion-type bearings *see* magnetic suspension bearings
- residual flux density 78
- resonance detection 4–5
- resonant frequencies 3
- revolutions for crater formation 182–3, 184
- rotating system in energy meters 214–15, 222
- rotational speed of DDHPB 230, 231–2, 238
- rotor bearings 211–12
- rotor instability investigations 162–3
- safe load-carrying capacity 125–6
- samarium cobalt 219
- seals 60
- shaft bend 156
- shaft voltages 85
 - in alternators 170, 171
 - in electric power equipment 56–7, 58, 61–2
 - and localized electrical current 67–9
 - in synchronous condensers 180–1
- shock pulse levels 24, 28, 33–5, 193–9
- sleeve bearing clearance 156
- spectral analysis technique 42
- spectrum analysis 58
- speed-based frictional torque studies 223
- spherical seatings 130–8
 - axial length 134, 136
 - constant moment of friction 132, 133
 - design parameters 130–2
 - nomographs 134–5
 - outer diameter to inner diameter ratio 136
 - radius calculation 133–4, 136
 - starting and stopping machines 99–100
 - stray voltage development 165, 173–4
 - stress distribution in DDHPB 239
 - sump layout and construction 187–8
 - swivel box bearings 209–11
 - synchronous condensers 177–85
 - bearing impedance 181
 - bearing inductance 181–2
 - capacitance 181
 - cycles/revolutions for crater formation 182–3, 184
 - damage measurement 179–80
 - design features 178
 - energy of inductive circuit 181–2
 - experimental procedure 178–9
 - journal and bearing contact width 181
 - lubrication system 178, 180, 184
 - shaft voltage 180–1
 - temperature 23, 27–8
 - contact temperature and stresses 96–8
 - friction effects 30–3
 - motor starting temperature 160, 163 and oil grades and clearance ratios 107–8, 116–17, 125
 - rises in DDHPB 235–8
 - viscosity-temperature relationship 109
 - threshold voltages 94–5
 - time-and-revolutions to standstill torque studies 224
 - torque studies 222–7, 231–2, 237–8
 - speed-based 223
 - time-and-revolutions to standstill 224
 - TOST (turbine oil stability test) 139–48
 - transition speed 117–20, 120–5
 - transmission system in windmills 205
 - turbulence and oil grade 117–20
 - turntable in windmills 204
- unbalanced magnetic pull 149
- vertical pump-motor sets 187–202
 - bearing design 199–200
 - bypass valves 191
 - causes of noise 200
 - shock pulse values 193–9
 - sump layout and construction 187–8

- system behaviour 189–91
- system layout 188–9
- vibration spectra 191–3
 - at 1156Hz frequency 199
 - at 16Hz frequency 193–8
- vibration 4, 7, 154–64
 - balancing trials 158
 - damping characteristics of bearings 156
 - diagnosis of causes 156–7
 - in electric power equipment 58, 62
 - examination of bearings 159
 - excitation forces 155–6
 - and motor starting temperature 160, 163
 - non-bonding of bearing liners 161
 - oil film stickiness 156
 - performance tests 24, 29, 37
 - rotor instability investigations 162–3
 - shaft bend 156
 - sleeve bearing clearance 156
 - sources of 155–6
 - and system design 157–8
 - velocity calculation 36
 - in vertical pump-motor sets 191–3
 - at 1156Hz frequency 199
 - at 16Hz frequency 193–8
- vibration signature 4, 7
- viscosity coefficients 106, 107–12
- viscosity integral 106, 112–14, 120–5
- viscosity-temperature relationship 109
- voltage-controlled oscillators (VCO) 42
- windmills 203–13
 - design features 204
 - pump-rod joints 212
 - reciprocating pump performance 205–9
 - replacement of bearings 209–12
 - rotor bearings 211–12
 - swivel box bearings 209–11
 - transmission system 205
 - turntable 204
- zinc additives 64, 92, 174