

Index

Note: *f.* indicates a figure; *t.* indicates a table.

- Air entrainment and removal, 43
- Air-Release, Air/Vacuum, and Combination Air Valves* (M51), 133
- Air-release valves, 133, 135*f.*
- Air/vacuum valves, 133, 135*f.*
- American Gas Association, 145
- American Petroleum Institute, 145
- Anchor blocks, 71*f.*
- Anchor rings, 132, 197, 197*f.*, 198*t.*
- Anchors, 168
- Annealing, 5
- Aqueducts, 42
- ASTM A370, 25
- Atmospheric corrosion, 147
- AWWA C200, 25, 111, 121, 131
- AWWA C203, 153
- AWWA C205, 153
- AWWA C206, 112, 116, 164
- AWWA C207, 115, 132
- AWWA C208, 121, 133, 135, 136
- AWWA C209, 154
- AWWA C210, 154
- AWWA C213, 154
- AWWA C214, 154
- AWWA C215, 154–155
- AWWA C216, 155
- AWWA C217, 155
- AWWA C218, 155
- AWWA C221, 117
- AWWA C222, 155
- AWWA C224, 155
- AWWA C225, 155
- AWWA C512, 134
- AWWA C602, 156

- Barlow formula, 46
- Bedding and backfill, 171
 - backfill above pipe zone, 172
 - densification, 171
 - hydraulic consolidation, 171–172
 - interior bracing of pipe, 172
 - mechanical compaction, 171
 - See also* Pipe-laying schedule, Trenching
- Bell-and-spigot joints with rubber gaskets, 111, 112*f.*, 165
- Biochemical corrosion, 143, 144–138
- Blowoff connections, 133–134
 - design, 202, 211*f.*
- Bolted sleeve-type couplings, 113, 114*f.*
 - pipe layout, 113
- Bolts
 - hole position, 130
 - installation, 165–166
 - torque requirements, 166–167, 169*t.*, 170*t.*
 - torque sequence (in gasket installation), 168–169, 166*f.*
 - torque values, 169
- Boussinesq equations, 65
- Brittle fracture, 13–15
 - Charpy V-notch impact test, 16–17, 17*f.*
 - conditions causing, 15–16
 - and steel selection, 17
- Buckling
 - allowable buckling pressure, 63–64
 - failure (Stewart formula), 49
 - and normal pipe installations, 64

- Casing spacers, 134–135
- Cathodic protection, 147–149
 - current required, 148
 - design of systems, 148
 - galvanic anodes, 148, 149*f.*
 - joint bonding, 148, 149*f.*
 - rectifiers, 147, 148*f.*
- Cement–mortar linings and coatings, 149, 154
 - and hydrostatic field test, 172
- Charpy V-notch impact test, 16–17, 17*f.*
- Check analysis, 24–25
- Circumferential fillet welds, 218–220
- Coal-tar coatings and linings, 153
- Cold working, 13
- Collapse-resistance formula, 48–49
- Collars, 179–180
 - multiplier (*M*-factor), 180
 - plate design, 180–181
 - reinforcement type, 180
- Concentration cells, 137
- Concrete anchors, 100
- Concrete piers, 99–100
- Constrained soil modulus, 63
- Controlled finishing-temperature rolling, 6
- Controlled rolling, 5–6
- Corrosion, 137
 - atmospheric, 147
 - biochemical, 137, 143–144
 - concentration cells, 137
 - crevice, 144
 - electrochemical cells, 137
 - electrolytic, 137, 143, 143*f.*, 145*f.*
 - electrolytic cells, 137
 - fatigue, 144
 - galvanic, 137–140, 139*f.*, 139*t.*, 140*f.*, 141*f.*, 142*f.*

galvanic cells, 137, 138*f*.
 internal (in steel pipe), 146–147
 severity of, 146
 soil, 145, 145*f*., 146*t*.
 stress, 144
 surveys, 149
 tuberculation, 146
 Corrosion allowance, 48
 Corrosion control, 146
 cathodic protection, 146–148, 148*f*., 149*f*.
 galvanic anodes, 147, 148*f*.
 inhibitive coatings, 147
 joint bonding, 148, 149*f*.
 protective coatings, 147. *See also*
 Protective coatings and linings
 rectifiers, 147, 148*f*.
 Crevice corrosion, 144
 Crosses, 129
 Crotch plates. *See* Wye branches

 Darcy-Weisbach formula, 39
 Depolarization, 138
 Diameter, economical, 42–43
 Discharge, 33
 Distribution systems, 42
 Double submerged arc weld process, 23*f*.
 Ductility, 6–7
 and cold-forming operations, 13
 importance in design, 12–13
 Ductility transition temperature, 17

 EFW. *See* Electric fusion welding
 Elasticity, modulus of, 61
 Elbows, 122–125
 angle computation method and formulas,
 125, 126*f*.–130*f*.
 recommended dimensions, 123*f*.–124*f*.
 tangent-type layout, 125*f*.
 wall thickness calculation, 122–125
 Electric fusion welding (EFW), 21, 24*f*.
 Electric resistance welding, 21, 22*f*., 23*f*.
 Electrochemical cells, 137
 Electrolytic cells, 137
 Electrolytic corrosion, 137, 143, 143*f*., 144*f*.
 stray currents, 143
 Entrance head loss, 33
 ERW. *See* Electric resistance welding
 Expansion joints, 71*f*., 100, 102
 aboveground, 116–117, 117*f*., 118*f*.
 underground, 116
 External loads, 59
 buckling, 63–64
 computer programs, 68
 constrained soil modulus, 63
 extreme conditions, 65–67, 66*t*., 67*f*.
 formula, 59–60
 influence coefficients for rectangular
 areas, 66*t*.
 Iowa deflection formula, 60–61, 67
 live-load effect, 61, 63*t*.

Marston theory, 59–60
 modulus of elasticity, 61
 modulus of soil reaction, 61, 62*t*.
 normal pipe installations, 64
 unified soil classification, 62*t*.

Fabricated pipe bend, 176, 177*f*.
 Fatigue corrosion, 144
 Field-welded joints, 112, 164–165
 Fillet welds, 220–222
 Fittings, 121, 135
 bolt hole position, 130
 collars, 179–181
 connecting dissimilar pipe materials, 131
 crosses, 129
 designator of, 121–122
 elbows, 122–125, 123*f*.–124*f*., 125*f*.,
 126*f*., 127*f*.–131*f*.
 flow through, 39–42, 40*f*., 41*f*.
 and frictional resistance between soil and
 pipe, 130
 laterals, 129
 miter end cuts, 122, 123*f*.
 recommended dimensions, 122*f*.
 reducers, 129, 131
 reinforcement of, 176–180, 179., 179*t*.
 tees, 129
 testing, 130
 and unbalanced thrust forces, 130
 wrappers, 179, 182–183
 wye branches, 129, 183–191
 Flanges, 113
 connections, 131
 gaskets, 115
 pressure ratings, 115
 steel ring, 115
 Flow
 equivalents, 35*t*.
 through fittings and valves, 39–42, 40*f*., 41*f*.
 through pipe, 31–33
 Fracture transition temperature, 17
 Freezing in pipelines, 204–206
 conduction heat-transfer values, 214, 216*t*.
 emissivity factors, 214, 217*t*.
 exposed pipes, 213–218
 heat balance, 213, 214*f*., 215*t*.
 heat loss, 213–214, 215*t*., 216*t*.
 underground pipes, 212*f*., 213
 wind velocity factors, 214, 217*t*.
 Friction head loss, 33
 Fusion-bonded epoxy coating, 154

 Galvanic cells, 137, 138*f*., 146
 with dissimilar electrolytes, 1402*f*.
 on embedded pipe without protective
 coating, 140*f*.
 pitting action, 140*f*.
 Galvanic corrosion, 137, 139, 139*f*.
 caused by cinders, 141*f*.
 caused by differential aeration of soil, 142*f*.

- caused by dissimilar metals, 141*f*.
- caused by dissimilar metals in contact on buried pipe, 141*f*.
- caused by dissimilar soils, 142*f*.
- caused by dissimilarity of surface conditions, 142*f*.
- caused by mixture of different soils, 142*f*.
- depolarization, 138
- and dissimilar electrolytes, 140*f*.
- on embedded pipe without protective coating, 140*f*.
- galvanic series of metals and alloys, 139*t*.
- pitting action, 140*f*.
- polarization, 139
- Gaskets
 - for bell-and-spigot joints, 111, 112*f*., 165
 - bolt torque sequence, 166–167, 166*f*.
 - for flanges, 115
 - installation procedure, 165–167, 166*f*.
- Gradient of support elevations to prevent pocketing, 76
- Grooved-and-shouldered couplings, 115, 116*f*.
- Ground friction, 117–118
- Harnessed joints, 195, 196*f*.
 - lugs, 197, 203*t*., 205*f*.
 - tie bolts, 197, 199*t*.–202*t*., 203*t*., 204*t*.
- Hazen-Williams formula, 29
 - graphical solution, 28*f*.
 - multiplying factors, 28*t*.
- Head, for different pressures, 37*t*.
- Head loss
 - entrance, 33
 - for fittings and valves, 39–42, 40*f*.
 - friction, 33
 - minor, 33
 - velocity, 33
- Hencky–Mises theory of failure, 77
 - equivalent stress diagram, 79, 80*f*.
- Hooke's law, 6, 9
- Hoop stress, 45, 48
 - and saddle supports, 69
- Hydraulics, 27
 - Darcy-Weisbach formula, 39
 - entrance head loss, 33
 - flow equivalents, 35*t*.
 - flow through fittings and valves, 39–42, 40*f*., 41*f*.
 - flow through pipe, 31–33
 - friction head loss, 33
 - Hazen-Williams formula, 28*f*., 28*t*., 29
 - head for pressures, 37*t*.
 - Manning formula, 31, 32*f*., 32*t*.
 - minor head loss, 33
 - pressure, 31–33
 - pressure equivalents, 38*t*.
 - pressure for heads, 36*t*., 38*t*.
 - Scobey formula, 29–31, 30*f*., 30*t*.
 - slope conversions, 34*t*.
 - symbols, 27
 - total head, 31–33
 - velocity head loss, 33
- Hydrostatic field test, 172
 - air venting, 172
 - allowable leakage, 173
 - bulkheads, 172
 - field testing cement–mortar-lined pipe, 172
- Hydrostatic test, 25
- Insulating joints, 132
- Iowa deflection formula, 60–61, 67
- Joints, 111, 118
 - bell-and-spigot with rubber gasket, 111, 112*f*., 167
 - bolted sleeve-type couplings, 113, 114*f*.
 - expansion (aboveground), 116–117, 117*f*., 118*f*.
 - expansion (underground), 116
 - field coating, 171
 - flanges, 113–115
 - grooved-and-shouldered couplings, 115, 116*f*.
 - insulating, 134
 - welded, 112, 112*f*.
- Ladle analysis, 24
- Laterals, 125*f*., 130
- Line tension, 117–118
- Liquid epoxy coating, 154
- Mains
 - checklist for pumping, 54–55
 - tapping, 202, 212*f*.
- Manholes, 132
 - design, 202, 210*f*.
- Manning formula, 31
 - graphical solution, 32*f*.
 - multiplying factors, 32*t*.
- Manufacture
 - double submerged arc weld process, 23*f*.
 - electric fusion welding (EFW), 21, 24*f*.
 - electric resistance welding (ERW), 21, 22*f*., 23*f*.
 - spiral-seam pipe, 21, 24*f*.
 - straight-seam pipe (plate pipe), 21, 24*f*.
- Marston theory, 59–60
- Minor head loss, 33
- Miter end cuts, 120, 121*f*.
- Modulus of elasticity, 61
- Modulus of soil reaction, 61, 62*t*.
- National Bureau of Standards (NBS), 145
- National Institute for Science and Technology. *See* National Bureau of Standards (NBS)
- Normalizing, 5
- Nozzle outlets, 130–131
- PDV. *See* Pressure-diameter value (PDV)
- Penstocks, 42

- Pipe deflection as beam, 73–75
 calculating deflection, 75–76
- Pipe installation
 assembly, 163–164
 bell-and-spigot rubber-gasket joints, 167
 bolts, 167–168, 169*t.*, 170*t.*
 field-welded joints, 164–165
 flanged joints, 165
 gasket installation, 165–167, 166*f.*
 handling and laying, 163
- Pipe joints. *See* Joints
- Pipe wall thickness
 Barlow formula, 46
 collapse-resistance formula, 48–49
 corrosion allowance, 48
 determining (working pressures for allowable unit stress), 224*t.*–232*t.*
 and external pressures, 48–49
 factors affecting, 45
 and hoop stress, 45, 48
 and internal pressure, 45–46, 46*f.*
 minimum-thickness formulas, 50
 pressure limits, 48
 Stewart formula (buckling failure), 49
 and tension stress, 46–48, 47*t.*
 and yield strength, 46–48
See also Buckling, External loads, Water hammer
- Pipe-laying schedule, 178, 180*t.*
- Pipelines
 freezing in, 202–204
 freezing in exposed pipes, 213–218, 214*f.*, 215*t.*, 216*t.*, 217*t.*
 freezing in underground pipes, 212*f.*, 213
 layout, 175–176
 standards, 153–156
 submarine, 220–222, 222*f.*
- Pocketing, prevention of, 76
- Poisson's ratio, 63, 73, 99
- Polarization, 138
- Polyamid coating (two-layer nylon-11-based), 155
- Polyolefin coatings, 154–156
- Polyurethane coatings, 155
- Pressure, 31–33
 equivalents, 38*t.*
 for heads, 36*t.*, 38*t.*
- Pressure surge. *See* Water hammer
- Pressure-diameter value (PDV), 177, 180, 182, 183
- Protective coatings and linings, 151, 156
 cement-mortar, 153, 156
 coal-tar, 153
 coating application, 156
 coating selection, 152
 cold-applied petrolatum tape and petroleum wax tape, 155
 cold-applied tape, 154
 epoxy-based polymer concrete, 156
 for exterior of aboveground pipe, 155
 extruded polyolefin, 154–155
 fused polyolefin, 155
 fusion-bonded epoxy, 154
 heat-shrinkable cross-linked polyolefin, 155
 lining selection, 152–153
 liquid epoxy, 154
 polyurethane, 155
 requirements, 151
 special sections, connections, and fittings, 156
 standards, 153–156
 tape, 154
 testing procedures, 151–152
 two-layer nylon-11-based polyamid, 155
- Quenching and tempering, 5
- Reducers, 129, 131
- Relief-valve manifolds, 202, 211*f.*
- Restrained joints, 194–196, 195*f.*
- Ring girders, 69, 71*f.*, 79
 assembling pipe, 102
 bending stress resulting from ring restraint, 79, 81*f.*
 concrete anchors, 100
 concrete footings, 101
 concrete piers, 99–100
 construction for low-pressure pipe, 100–101, 101*f.*
 design example, 82–99
 distance calculations, 86–87
 equivalent stress diagram, 79, 80*f.*
 expansion joints, 102
 installation of spans, 101–102, 102*f.*
 moments and moment calculations, 84–86, 84*f.*, 85*t.*
 stiffener ring calculations, 87–92
 stiffener ring coefficients (equal and opposite couples), 81*f.*
 stiffener ring coefficients (radial load supported by two reactions), 81*f.*
 stiffener ring coefficients (transverse earthquake), 81*f.*
 stiffener ring stresses for half-full condition, 92–99, 94*f.*, 100*t.*
 stress summary, 79, 82*f.*
 stresses at support rings, 90*t.*
- Rubber gaskets, 111, 112*f.*, 115
- Saddle supports, 69–72, 70*f.*
 and hoop stress, 69
 safe spans for pipe in 120° contact saddles, 73, 74*t.*
 and stress formulas, 72–73
- Scobey formula, 29–31
 graphical solution, 30*f.*
 multiplying factors, 30*t.*
- Slope conversions, 34*t.*

- Soil
 frictional resistance between soil and pipe, 130
 and galvanic corrosion, 142*f.*
 standard density tests, 163*t.*
 unified classification, 62*t.*
See also Bedding and backfill, Trenching
- Soil corrosion, 145
 corrosion rate in various soils, 145
 and soil resistivity, 146*t.*
 soils in order of corrosive action on steel, 146*t.*
 tests, 145
- Soil modulus, constrained, 63
- Soil reaction, modulus of, 61, 62*t.*
- Spangler's formula, 67
- Specials, 176, 177*f.*
 connections, 202, 206*f.*, 207*t.*, 208*t.*
- Spiral-seam pipe, 21, 24*f.*
 stress evaluation, 18, 18*f.*
- Spiral-welded pipe, 18, 18*f.*
- Standard for Air Release, Air / Vacuum, and Combination Air Valves for Waterworks Service*, 133
- Standard for Cement-Mortar Lining of Water Pipelines—4 In. (100 mm) and Larger in Place*, 156
- Standard for Cement-Mortar Protective Lining and Coating for Steel Water Pipe—4 In. (100 mm) and Larger—Shop Applied*, 153
- Standard for Coal-Tar Protective Coatings and Linings for Steel Water Pipelines—Enamel and Tape—Hot-Applied*, 153
- Standard for Coating the Exterior of Aboveground Steel Water Pipelines and Fittings*, 155
- Standard for Cold-Applied Tape Coatings for the Exteriors of Special Sections, Connections, and Fittings for Steel Water Pipelines*, 154
- Standard for Dimensions for Fabricated Steel Water Pipe Fittings*, 119
- Standard for Extruded Polyolefin Coatings for the Exterior of Steel Water Pipelines*, 154–155
- Standard for Field Welding of Steel Water Pipe*, 112, 164
- Standard for Fused Polyolefin Coating Systems for the Exterior of Steel Water Pipelines*, 155–156
- Standard for Fusion-Bonded Epoxy Coating for the Interior and Exterior of Steel Water Pipelines*, 154
- Standard for Heat-Shrinkable Cross-Linked Polyolefin Coatings for the Exterior of Special Sections, Connections, and Fittings for Steel Water Pipelines*, 155
- Standard for Liquid Epoxy Coating Systems for the Interior and Exterior of Steel Water Pipelines*, 154
- Standard for Polyurethane Coatings for the Interior and Exterior of Steel Water Pipe and Fittings*, 155
- Standard for Steel Pipe Flanges for Waterworks Service—Sizes 4 in. Through 144 in. (100 mm Through 3,600 mm)*, 113
- Standard for Steel Water Pipe 6 In. (150 mm) and Larger*, 25, 121
- Standard for Tape Coating Systems for the Exterior of Steel Water Pipelines*, 154
- Standard for Two-Layer Nylon-11-Based Polyamid Coating System for the Interior and Exterior of Steel Water Pipe, Connections, Fittings, and Special Sections*, 155
- Steel, 2
 annealing, 5
 casting, 4
 chemical composition, 3–4
 controlled finishing-temperature rolling, 6
 controlled rolling, 5–6
 effects of alloying elements, 3*t.*
 heat-treated, 3, 5–6
 hot-rolled, 3, 4, 5–6
 killed, 4–5
 normalizing, 5
 quenching and tempering, 5
 semikilled, 4–5
 stress relieving, 5
- Steel pipe
 calculation of angle of fabricated pipe bend, 176, 177*f.*
 economical diameter, 42
 expansion and contraction, 116
 in filtration plant gallery, 2*f.*
 history, 1–2
 installation. *See* Pipe installation
 moment of inertia values, 103*t.*–109*t.*
 section modulus values, 103*t.*–109*t.*
 specials, 176, 177*f.*, 202, 206*f.*, 207*t.*
 transportation and handling of coated pipe, 159–160
 uses, 2–3
- Stewart formula (buckling failure), 49
- Stiffener rings, 71*f.*
 coefficients, 78*f.*
- Straight-seam pipe (plate pipe), 21, 24*f.*
- Strain, 7
 analysis based on, 11, 12*f.*, 12*t.*
 importance in design, 9–11, 17–18
- Strain aging, 13, 14*f.*
- Strain hardening, 13, 14*f.*
- Stray currents, 143, 143*f.*, 144*f.*
- Stress, 7
 actual, 9, 10*f.*
 actual and apparent, 9, 10*f.*

- calculated vs. measured, 9–10
- calculating for pipe with saddle supports, 72–73
- change in longitudinal stress due to temperature change, 118
- design considerations, 17
- evaluation in spiral-welded pipe, 18, 18*f.* and span length, 76–77
- Stress corrosion, 144
- Stress relieving, 5
- Stress–strain diagrams, 7–9
 - for carbon steel, 9*f.*
 - and cold-forming operations, 13
 - plastic and elastic strains, 9*f.*
 - for steel, 8*f.*
 - true curve for steel, 8*f.*
- Submarine pipelines, 220
 - lay barges, 222
 - pipe laying, 220
 - pipe pulling, 220–221, 221*f.*, 222*f.*
- Supports, 69
 - anchor blocks, 71*f.*
 - brackets, 69
 - concave rollers, 69
 - concrete anchors, 100
 - concrete piers, 99–100
 - and expansion joints, 71*f.*, 100, 102
 - gradient of support elevations to prevent pocketing, 76
 - hangers, 69
 - moment of inertia values, 103*t.*–109*t.*
 - pipe deflection as beam, 73–76
 - ring girders, 69, 71*f.*, 79–103
 - saddles, 69–73, 70*f.*, 74*t.*
 - section modulus values, 103*t.*–109*t.*
 - span lengths and stresses, 76–77
 - stiffener rings, 71*f.*, 78*f.*
- Surge. *See* Water hammer
- Tape coatings, 154
- Tees, 131
- Tension stress, 46–48, 47*t.*
- Testing
 - check analysis, 24–25
 - of chemical properties, 24–25
 - of dimensional properties, 25
 - hydrostatic test of straight pipe, 25
 - ladle analysis, 24
 - of physical properties, 25
- Thrust blocks, 168, 191
 - calculation of size, 194
 - horizontal bends, 192*f.*
 - typical configurations, 194
 - vertical bends, 193*f.*
- Thrust forces, 130, 191, 192*f.*
 - formula, 191
- Thrust restraint, 191
 - harnessed joints, 196, 196*f.*
 - restrained joints, 194–196, 195*f.*
 - thrust blocks, 191–194, 192*f.*, 193*f.*, 195*f.*, 196*f.*
 - welded joints, 196, 196*f.*
- Total head, 31–33
- Transient pressure. *See* Water hammer
- Transportation and handling, 159–160
- Trenching. *See also* Bedding and backfill, Pipelaying schedule
 - bottom preparation, 161
 - depth, 160
 - overexcavation, 161, 162*f.*
 - regulations, 161
 - standard density tests, 163*t.*
 - subgrade densification, 161, 162*f.*
 - width, 160
- Tuberculation, 146
- Unified soil classification, 62*t.*
- Valves
 - air-release, 132, 134*f.*
 - air/vacuum, 133, 134*f.*
 - connections, 131
 - flow through, 39–42, 40*f.*, 41*f.*
 - relief-valve manifolds, 202, 211*f.*
- Vaults, 202, 209*f.*, 210*f.*
- Velocity head loss, 33
- Water hammer, 51
 - allowance for, 56
 - checklist for pumping mains, 54–55
 - pressure rise calculations, 56
 - surge studies at design stage, 55–56
 - surge-wave theory, 51–54, 53*f.*, 53*t.*
- Welded joints, 112, 112*f.*, 196, 196*f.*
 - circumferential fillet welds, 218–220
- Wrappers, 179
 - multiplier (*M*-factor), 182
 - plate design, 182–183
 - reinforcement type, 182
- Wye branches, 129, 184*f.*
 - N* factor curves, 187*f.*
 - nomograph use in design of, 183–191, 186*f.*, 187*f.*
 - plan and layout, 189*f.*
 - Q* factor curves, 187*f.*
 - three-plate design, 190–191
 - top depth, 188*f.*
 - wye depth and plate thickness, 185
- Yield strength, 6–7, 8*f.*
 - and cold-forming operations, 13
 - and pipe wall thickness, 46–48
- Young's modulus, 54, 63