

- Accelerated gravity separation:
 analysis of, 241-242
 description of, 241
- Acquired immune deficiency syndrome (AIDS), 92
- Activated biofilter process, 637-639
- Activated carbon, 314-324
 adsorption, analysis of, 318, 751-753
 Freundlich isotherm, 318
 Langmuir isotherm, 318
 adsorption from mixtures, 320
 classification of: granular activated carbon (GAC), 315
 powdered activated carbon (PAC), 315
 contactors: for dechlorination, 506
 expanded-bed contactors, 316, 752
 fixed-bed contactors, 316, 752
 moving-bed contactors, 316
 for odor control, 517
 for wastewater treatment, 751-755
 description of, 314-315
 powdered activated carbon treatment (PACT), 753
 process analysis, 321-323
 breakthrough capacity, 322
 carbon adsorption capacity, 322
 estimation of breakthrough time, 323-324
 mass-transfer zone (MTZ), 321
 powdered activated carbon, 323
 production of, 315
 regeneration of, 317
 treatment: with granular carbon, 315
 with powdered carbon, 316
- Activated sludge, 379-400, 531-604
 aeration systems, 556-578
 diffused air, 556-569
 high purity oxygen, 574-578
 mechanical, 569-574
 (See also Aerators)
 aeration tanks, 578-580
 air diffusers, 579
 baffles in, 579
 cross section, typical, 578
 dimensions of, 574, 579
 drains in, 579
 freeboard, 579
 hydraulic detention time, 534, 550
 aerators (see Aerators)
 air: application rates, 536
 blowers, 563-566
 diffusers, 556-563
 piping, 566-569
 required for mixing, 573
 complete-mix with recycle, 385-388
 description of process, 379
 design considerations, 531-539
 control of filamentous organisms, 537
 effluent characteristics, 538
 food-to-microorganism ratio, 533-534
 hydraulic retention time, 550
 loading criteria, 532-534
 mean cell residence time, 533
 nature of wastewater, 532
 nutrient requirements, 536
 organic (BOD) loading, 534, 550
 oxygen requirements, 535

- Activated sludge, design considerations (*Cont.*):
 oxygen-transfer, 562, 572
 reactor selection, 531
 safety factor in design, 536
 selector for control of filamentous organisms, 538
 sludge production, 534
 sludge wasting, 534
 solids separation facilities, 580–591
 effects of inhibitory pollutants, 163
 efficiency of BOD removal, 548–549
 effluent characteristics, 538–539
 example of process analysis, 389–392
 factors affecting performance, 171
 final tanks (*see* Solids-separation facilities, design of *below*)
 flow distribution, 580
 food to microorganism ratio (F/M):
 definition of, 389
 typical values, table of, 550
 froth control, 580
 hydraulic retention time: definition of, 386
 typical values, table of, 550
 kinetic analysis of process: complete-mix with recycle, 385–388
 performance and stability of, 392–393
 plug flow with recycle, 393–396
 process control relationships, 388–389
 kinetic coefficients for, table of, 394
 mean cell residence time (θ): definition of, 386
 typical values, table of, 550
 microorganisms, involved, 384–385, 537, 553–556
 mixed liquor suspended solids (MLSS), 379, 550
 mixed liquor volatile suspended solids (MLVSS), 375, 390, 533
 mixing, energy requirements for, 573
 nutrient requirements, 536
 observed yield: definition of, 377, 388
 typical values of, 394
 operational problems, 537, 553–556
 bulking sludge, 396–398, 553, 557
Nocardia foam, 556
 rising sludge, 555
 pH and alkalinity effects, 532
 plug flow with recycle, 393–396
 process description, 379
 process design and control, 388–389, 539–553
 dissolved oxygen control, 542
 oxygen uptake rates, 553
 return activated sludge control, 545–551
 sludge wasting, 551–553
 process design examples, 591–604
 complete-mix, 592–600
 sequencing batch reactor, 601–604
 process microbiology, 384–385
 process modifications, 539–542
 complete-mix, 540, 543
 contact stabilization, 540–544
 continuous-flow stirred-tank (*see* Complete-mix)
 conventional plug-flow, 540, 542
 deep shaft reactor, 542, 546
 design parameters, 550
 extended aeration, 541
 high-purity oxygen system, 540, 544
 high-rate aeration, 541
 Kraus process, 541
 modified aeration, 540
 operational characteristics, 548
 oxidation ditch, 541, 545
 sequencing batch reactor, 541
 step-feed aeration, 540, 543
 tapered aeration, 540
 process safety factor, 393
 reactor selection, 531, 532
 effect of cost, 532
 effect of environmental factors, 532
 effect of reaction kinetics, 531
 effect of wastewater characteristics, 532
 oxygen transfer requirements, 531
 return sludge control, 545–551
 settling tanks (*see* Solids-separation facilities, design of *below*)
 shock loads, 532
 sludge wasting, 551–553
 solids-separation facilities, design of, 580–591
 circular tanks, 581
 density currents, 581, 591
 flocculating clarifier, 590
 flow distribution, 589
 for high-purity oxygen systems, 588
 intrachannel clarifiers, 582, 586
 lamella settlers, 582
 overflow rates, 587–588
 rectangular tanks, 581
 scum removal, 591
 settling characteristics of sludge, 584–587
 sidewater depth, 588
 sludge blanket, 587
 sludge collectors, 581
 sludge volume index (SVI), 587

- solids loading rates, 587-588
- surface loading rates, 587
- tank inlets, 589
- tank outlets, 591
- tank types, 581-584
- tray clarifiers, 582, 585
- tube settlers, 582, 586
- weir placement and loading, 590
- specific growth rate, 370
- specific substrate utilization rate, 388, 392
- temperature effects, 372-373
- Activation energy, 331
- Acute toxicity, 104, 1197
- Acute toxicity units (TU_a), 106
- Adsorption, activated-carbon, 314-324, 751
 - analysis of, 318, 751-753
 - Freundlich isotherm, 318
 - Langmuir isotherm, 318
 - breakthrough, 322
 - capacity, 322
 - description of, 314-315
 - flow diagrams for, 688, 1179-1184
 - of mixtures, 320
 - process analysis, 321-323
 - production of, 315
 - regeneration of, 317
- Advanced wastewater treatment, 663-759, 1174-1184
 - biological removal of phosphorus, 726-731
 - chemical oxidation, 755
 - combined removal of nitrogen and phosphorus by biological methods, 731-735
 - control of nutrients, 691-694
 - nitrogen removal by various processes, table of, 692-693
 - phosphorus removal by various processes, table of, 695
 - conversion of ammonia by biological nitrification, 694-711
 - definition of, 2
 - need for, 664
 - reclamation technologies, 1174-1184
 - removal of dissolved inorganic substances, 756-759
 - removal of nitrogen by biological nitrification/denitrification, 711-726
 - removal of nitrogen by physical and chemical methods, 735-741
 - removal of phosphorus by chemical addition, 741-749
 - removal of residual suspended solids:
 - by granular medium filtration, 666-689, 1177-1179
 - by microscreening, 689-690
 - removal of toxic compounds and refractory organics, 749-755
 - treatment technologies, 666-670
 - classification, 666
 - process performance data, 666
 - treatment levels, table of, 670
 - typical process flow diagrams, 668-669
 - unit operations and processes, table of, 667
- (*See also individual listings*)
- Advection, 1199-1200
- Aerated channels:
 - advantages of, 471
 - air requirements, 471
 - use of incinerator exhaust gas, 783
- Aerated grit chamber, 460-464
- Aerated lagoons, 399-400, 604-614
 - analysis of, 399-400
 - description of, 604
 - design considerations: 604-611
 - BOD removal, 604-605
 - cold weather operations, 607
 - effluent characteristics, 606
 - oxygen requirement, 606
 - process design example, 605-611
 - temperature, 606
 - mean cell residence time, 605
 - solids separation, 611-614
 - algal growth control, 612
 - design example, 612-614
 - odor control, 612
 - volatile solids reduction, 611
- Aerated static pile sludge composting, 845-847
- Aeration:
 - in activated sludge, 556-578
 - in aerated lagoons, 604
 - in aerobic digesters, 837, 839
- Aeration tanks:
 - design of, 578-580
 - dimensions for mechanical aerators, 574
 - geometry for diffused air, 579
 - (*See also Activated sludge: aeration tanks*)
- Aerators:
 - aspirating, 557, 561
 - diffused-air: alpha factors, 563
 - coarse bubble diffusers (*see Nonporous diffusers below*)
 - diffuser cleaning, 563

Aerators (*Cont.*):

- diffuser efficiency, 562
- diffuser fouling, 562
- diffuser performance, 561–562
- energy requirements for mixing, 573
- fine-pore diffusers (*see* Porous diffusers *below*)
- fouling factors, 563
- nonporous diffusers, 557, 561
- performance evaluation, 282
- porous diffusers, 557, 559–561
- swing diffusers, 578
- transfer efficiency, 562
- typical performance information, 561–563
- jet, 557–561
- mechanical:
 - alpha factors, 573
 - disk aerator, 571
 - efficiency, 572
 - energy requirement for mixing, 573
 - horizontal axis, 571
 - Kessener brush, 571
 - oxygen solubility correction factor, 573
 - performance, 571
 - performance correction for field conditions, 572
 - rating conditions, 571–572
 - submerged turbine, 570
 - surface aerators, 570–571
 - tank dimensions for surface aerators, 574
 - typical performance information, 571–572
 - vertical axis, 569–571
 - static tube, 557–558, 561
 - U-tube, 557, 561
- Aerobacter, 93
 - (*See also* Indicator organisms)
- Aerobic-anaerobic (facultative) stabilization ponds, 436–438, 648–650
 - (*See also* Stabilization ponds)
- Aerobic bacteria, 363
- Aerobic cycle in nature, diagram of, 382
- Aerobic sludge digestion, 401–403, 835–842
 - conventional air aerobic digestion:
 - design criteria, 837
 - energy requirements for mixing, 839
 - environmental conditions, 837
 - oxygen requirements, 837, 839
 - process description, 402
 - process design example, 839–841
 - process operation, 839
 - solids reduction, 837–839
 - tank volume, 838
 - cryophilic aerobic digestion, 842
 - dual digestion, 842
 - high-purity oxygen aerobic digestion, 402
 - process microbiology, 403
 - thermophilic aerobic digestion, 402
 - typical BOD and SS concentrations in recycle flows, table of, 893
- Aerobic stabilization ponds, 434–436, 642–648
 - (*See also* Stabilization ponds)
- Aggregation, particle, 311–313
- Air, solubility in water, 1255–1256
- Air diffusers, 556–563
 - (*See also* Aerators: diffused air)
- Air flotation, 243
- Air mixing, 219
 - in activated sludge process, 573
 - description of, 219
 - power requirements for, 219
- Air piping, 566–569
 - adiabatic temperature rise in, 566
 - design air temperatures, 566
 - friction loss in, 567
 - headloss example, 568
 - materials of construction, 566
 - velocities in headers, 566
 - velocity head, 567
- Air pollution control, 890
- Air pollution control regulations, 891
- Air stripping of ammonia, 735–738
 - air requirements, 738
 - application, 737
 - lime requirements, 738
 - operational problems, 738
 - temperature, effect of, 738
- Algae:
 - blooms, 91
 - description of, 91
 - effect of: on dissolved oxygen, 438, 1204
 - on pH, 438
 - in facultative pond effluent, 651
 - nuisance, 91
- Algal-bacterial symbiosis, 435–436
- Algal photosynthesis, 1204, 1208
- Algal respiration, 1204, 1208
- Alkalinity:
 - definition of, 85
 - importance of: in ammonia stripping, 738
 - in anaerobic digestion, 821
 - in chemical precipitation, 304–308
 - in nitrification, 698, 711
 - typical values in wastewater, 109
- Alpha (α) factor in aeration:
 - definition of, 286
 - for diffused air systems, 563
 - for mechanical aerators, 573

- Alum:
 characteristics of, 303
 dosages for: improved suspended solids removal in primary sedimentation, 304
 phosphorus removal, 308
 reactions involving, 304, 308, 742
 sludge characteristics, 769
 uses, 303, 306
- Amines, 57
- Ammonia conversion of by biological nitrification:
 classification of processes, 696
 comparison of nitrification processes, 711
 operating considerations, 710
 operating and environmental variables, table of, 700
 process description, 431, 695
 separate stage nitrification, 706-710
 single stage carbon oxidation and nitrification, 697-706
- Ammonia nitrogen:
 comparison of treatment methods, 727, 737
 removal of: by air stripping, 735, 737-738
 by breakpoint chlorination, 737-740
 by ion exchange, 740-741
 by nitrification-denitrification, 711-726
 solubility in water, 1255-1256
 typical values: in septage, 110
 in wastewater, 109
- Ammonia stripping, 735, 737-738
 (See also Air stripping of ammonia)
- Anaerobic bacteria, 363
- Anaerobic biological process:
 application, table of, 381
 classification of: attached growth, 378
 suspended growth, 378
 definition of, 377
 process variations: anaerobic contact, 427
 anaerobic filter, 429
 anaerobic ponds, 439, 650
 dual digestion, 842
 expanded bed, 429
 Imhoff tank, 1029-1030, 1079
 typical reactor configurations for, 421
- Anaerobic contact process, 427
- Anaerobic cycle in nature, diagram of, 383
- Anaerobic filter process, 429
- Anaerobic sludge digestion: application of, 420-427, 813-834
 digester gas, 823-826
 collection, 825
 heating value, 826
 production, 825
 utilization, 826
- digester heating, 830-834
 analysis of heat requirements, 830
 heat-transfer coefficients, table of, 832
 heating requirements example, 833-834
- digester mixing, 826-830
 advantages and disadvantages of various types, 828-829
 description of, 826-827
 typical design information, 830
- digestion tanks: covers, types of, 825
 heat requirements, 830-831
 mixing, 826-830
 sludge addition, 816
 types of, 823-825
 history of, 823-25
 operating temperatures, 425
 process analysis and design, 425-427, 817-823
 kinetic coefficients, 426
 loading factors, 820-821
 mean cell residence time, 818-819
 methane gas conversion, example of, 426-427
 population basis, 822
 typical design criteria, 823
 volatile solids reduction, example of, 821-822
 volume reduction, 822
- process description, 420-421, 814-817
 high-rate digestion, 420, 814
 separate-stage digestion, 816
 standard-rate digestion, 420, 814
 two-stage digestion, 421, 816
- process kinetic coefficients, 426
- process microbiology, 423-425
 acid forming bacteria, 424
 hydrolyzing bacteria, 423
 methane forming bacteria, 424
- tank design, 823-824
 cylindrical, 823
 egg-shaped, 823-824
 waffle bottom, 824
- thermophilic, 834
- typical BOD and SS concentrations in recycle flows, table of, 893
- Anaerobic stabilization ponds, 439, 650
 (See also Stabilization ponds)
- Anaerobic treatment processes, figure of, 421
- Analytical results, expression of, 51
- Animals (microorganism), 90, 92
- Anoxic biological process:
 application, table of, 381
 definition of, 377

- Anthracite, 679, 681
 A/O process, 729
 A²/O process, 731
 Aquaculture, 938
 Arbitrary flow reactor, 171-172
 Artificial media sludge drying beds, 874-875
 description of, 875
 typical cross-section, 875
 Assimilative capacity of receiving waters, 1195
 Atomic numbers and atomic masses (*see inside of back cover*)
 Attached growth treatment processes:
 aerobic processes: definition of, 377-378
 nitrification, 431-432, 705-706, 909-910
 packed-bed reactors, 420
 roughing filters, 418
 rotating biological contactors, 418-420
 trickling filters, 403-418
 types, table of, 380
 (*See also individual listings*)
 anaerobic processes: anaerobic filter, 429
 definition of, 377-378
 expanded bed, 429
 rotating biological contactor, 719, 724
 types, table of, 381
 anoxic denitrification: definition of, 377-378
 types, table of, 381
 facultative processes, definition of, 377-378
 Autotrophic microorganisms:
 chemosynthetic, 361
 definition of, 361
 photosynthetic, 361
 Axial dispersion:
 in plug flow reactors, 1271
 in pond systems, 644
 in rivers and estuaries, 1214-1216
 Backwashing, filter, 680-683
 (*See also Filtration, granular medium*)
 Bacteria:
 cell chemical composition, table of, 365
 chemical structure, 364
 classification by ability to utilize oxygen:
 aerobic, 363
 aerotolerant, 364
 anaerobic, 363
 facultative, 363
 classification according to carbon and energy source: autotrophs, 361
 chemotrophs, 361
 heterotrophs, 361
 phototrophs, 361
 classification, general, 90
 coliform organisms, 91
 pathogenic, 93-94
 pH ranges, 366
 reproduction, 91
 size, 91
 streptococci, fecal, 95
 temperature ranges, table of, 365
 Bacterial die-off, 1206
 Bacterial growth:
 conversion reactions: for endogenous respiration, 379
 for oxidation and synthesis, 379
 general growth patterns in pure cultures, 367
 based on bacterial mass, 368
 based on bacterial numbers, 367
 in mixed cultures, 369
 phases of, 368
 Bacterial yield:
 definition of, 371
 effect of endogenous respiration on, 372
 (*See also Activated sludge, observed yield; Yield coefficient, bacterial*)
 Bacteriological tests for coliform organisms:
 completed test, 95-96
 confirmed test, 95-96
 membrane filter technique, 99-100
 most probable number (MPN), 97-99
 MPN tables, 1261-1263
 multiple tube fermentation, 96-97
 presumptive test, 95-96
 Bar racks and screens, 200-203, 445-454
 hand-cleaned, 447, 448
 characteristics of, 447
 design information, 448
 typical rack, 449
 headloss computation, 203
 mechanically-cleaned, 448-451
 design information, 448
 typical installations, 450
 screenings: disposal, 454
 quantities, 453
 screens: headloss through, 453
 types of, 202, 452
 Bardenpho process:
 four-stage, 714-715
 five-stage, 732
 Barge transport of sludge, 917
 Batch reactor:
 definition of, 172, 1265
 mass balance for, 370, 1265-1267

- Belt filter press, 864-868
 design considerations, 866
 design example, 866-868
 process description, 865
 sizes, 866
 system operation and performance, 865-866
 typical performance data, 866
- Beneficial use, in water reuse, 1139
- Beneficial use of sludge, 903-915
 (See also Land application of sludge;
 Sludge, beneficial use of)
- Beta (β) factor in aeration, 286
- Bingham plastic, 791
- Bioassay toxicity tests:
 application of test results, 105-106
 example of, 106-108
 protection against acute toxicity, 106
 protection against chronic toxicity, 106
 evaluation of test results, 104
 organisms used, 102-103
 testing, 102
 toxicity units, 104
 uses of, 101-102
- Biochemical oxygen demand (BOD), 71-82
 applications, 71
 carbonaceous biochemical oxygen demand,
 (CBOD), 77
 definition of, 71
 determination of K and L: by daily-
 difference method, 77
 by Fujimoto method, 77-79
 by least squares, 77
 by method of moments, 77
 by rapid-ratio method, 77
 by Thomas method, 77
 formulation of first stage, 72-73
 kinetics of, 72-76, 1201-1202
 limitations of BOD test, 80
 method of determination, 71-72
 nitrification in BOD test, 76
 oxidation, 1201
 seeding, 71
 sustained mass loading curve, 161
 temperature effects, 75
 typical K values, 75
 typical values in wastewater, 75
- Biofilter-activated sludge process, 641
- Biological characteristics of wastewater,
 90-108
 (See also Wastewater characteristics,
 biological)
- Biological denitrification (see Nitrogen
 removal by biological denitrification)
- Biological growth kinetics, 369-377
 (See also Kinetics of biological growth;
 Activated sludge, kinetic analysis of
 process)
- Biological nitrification/denitrification
 (see Nitrogen removal by nitrification/
 denitrification)
- Biological nutrient removal, 429-434,
 694-735
 combined nitrogen and phosphorus
 removal, 434, 731-735
 nitrogen removal, 432-433, 711-726
 phosphorus removal, 433-434
 (See also Nutrient removal)
- Biological odor control, 518
- Biological unit processes:
 activated sludge, 379-398, 531-604
 aerated lagoons, 398-400, 604-614
 aerobic digestion, 401, 835-842
 anaerobic contact, 427
 anaerobic digestion, 420-427, 813-834
 anaerobic filter, 429
 definition of, 377
 denitrification, 432-433, 711-727
 expanded bed, 429
 nitrification, 431, 694-711
 nitrification/denitrification, 714-718
 packed bed reactor, 420
 phosphorus removal, 433, 726-731
 rotating biological contactor (RBC),
 419, 628-636
 roughing filter, 418
 sequencing batch reactor (SBR), 400
 stabilization ponds, 434-439, 641-655
 trickling filter, 403-418, 614-628
 upflow anaerobic sludge-blanket, 427
 (See also individual listings)
- Biostimulants (see Nutrients)
- Blowers, 563-566
 centrifugal, 563-565
 effects of temperature, 565
 surging, 564
 turndown, 564
 noise control, 563, 566
 positive-displacement, 564
 power requirements, 565
 temperature rise, 566
 types, 563
- BOD (see Biochemical oxygen demand)
- Bomb calorimeter test, 882
- Break-point chlorination, 334-337, 738-740
 acid generation, 336
 application of, 739

- Breakpoint chlorination (*Cont.*):
 buildup of TDS, 336
 theory of, 334–335, 739
- Breakthrough in carbon adsorption, 322
- Bromine chloride, disinfection with, 347–348, 506
 (*See also* Disinfection with bromine chloride)
- Buchner funnel test for sludge, 851
- Bulking sludge:
 causes of, 553–554
 control of: methods of, 396
 by selector, 538
 by temporary measures, 555
 description of, 396
 types of, 553
- Bulrush, 934, 936
- Butanol wheel for odor measurement, 60
 (*See also* Odor)
- Cadmium, 944
- Calcium hydroxide:
 characteristics of, 303
 chemical reactions involving, 304–305
 thermal regeneration of, 745
- Calcium hypochlorite, 496
- Carbohydrates, 65–66
- Carbon, total organic, 82
- Carbon adsorption, 314–324
 (*See also* Activated carbon, adsorption)
- Carbon analyzer, 82
- Carbon contactor, 752–753
 (*See also* Activated carbon, contactors)
- Carbon dioxide:
 in biological treatment, 361, 379
 carbon source for algae, 438
 in natural cycles: aerobic, 382
 anaerobic, 383
 in nitrification, 382, 696
 solubility in water, 1255–1256
- Carbonaceous biochemical oxygen demand (CBOD):
 application of, 77
 definition of, 77
 use in EPA effluent discharge requirements, 123
- Carver-Greenfield process, 878–880
 (*See also* Multiple-effect evaporator)
- Cascade post aeration, 509–511
- Catalytic incineration, 522
- Cattails, 934, 936–937
- CBOD (*see* Carbonaceous biochemical oxygen demand)
- CCC (*see* Criterion continuous concentration)
- Cell yield coefficient (*see* Yield coefficient, bacterial)
- Center-pivot irrigation system, 953, 956
- Centrifugal pumps for sludge pumping, 786
- Centrifugation, 805–806
 applications of: for sludge dewatering, 860–862
 for sludge thickening, 805–806
 cake solids, table of, 863, 893
 centrate, table of, 862, 893
 description of, 805–806
 odor, 862
 performance data, 863
 types of, 805, 860
 (*See also* Sludge thickening; Sludge dewatering)
- Centrifuge dewatering:
 description of: imperforate basket, 862
 solid bowl centrifuge, 860, 862
 design considerations, 862–864
 typical performance, 863
- Centrifuge thickening, 805–806, 809–810
 description of, 805–806
 operational variables, 810
 performance of, 809
- CFSTR (*see* Continuous flow stirred-tank; Complete-mix reactor)
- Channels, aerated, 471
- Chemical applications in wastewater collection, treatment, and disposal, table of, 353
- Chemical characteristics of wastewater, 64–90
 (*See also* Wastewater characteristics, chemical)
- Chemical composition:
 of bacteria, table of, 365
 of septage, table of, 110
 of wastewater, table of, 109
 (*See also* Wastewater characteristics, chemical)
- Chemical conditioning of sludge, 850–854
 (*See also* Sludge conditioning)
- Chemical feed systems, 492–494
- Chemical fixation of sludge, 915
- Chemical oxidation:
 applications of, 353, 755
 dosages for: BOD reduction with chlorine, 755
 COD reduction with ozone, 755
 for septage treatment, 1098
 for sludge stabilization, 811
 table of applications, 353

- Chemical oxygen demand (COD):
 BOD₅/COD ratios, 83
 definition of, 82
 typical values in wastewater, 109
- Chemical precipitation, 302–314, 486–494
 chemicals used, table of, 303
 design of storage, feeding, piping,
 and control systems, 492–494
 for dissolved inorganics removal, 756
 for improved sedimentation-tank
 performance, 303, 488
 for independent physical–chemical
 treatment, 488
 for phosphorus removal, 488, 741–749
 coprecipitation, 307, 743–745
 postprecipitation, 748
 preprecipitation, 307, 742–743,
 745–748
 strategies for, 306
 summary of advantages and
 disadvantages, table of, 750
- reactions involving: alum, 304
 ferric chloride, 306
 ferric chloride and lime, 306
 ferric sulfate and lime, 306
 ferrous sulfate and lime, 305
 lime, 304
 phosphate removal, 306, 742
- sludge quantities, estimation of, 489–491
- surface loading rates for, 488
- theory of, 310–314
 electrical double layer, 312
 hydrolysis products, 313–314
 metal salt polymer formation, 313–314
 nature of particles, 310
 particle aggregation, 311–312
 polyelectrolytes, 311
 polymers, 311–313
 surface charge, 310–311
 zeta potential, 311
- (*See also* Chemical treatment, phosphorus
 removal)
- Chemical treatment:
 applications: improved BOD removal, 303
 improved SS removal, 303
 nitrogen removal, 735
 phosphorus removal, 308–310,
 741–749
 in physical–chemical treatment,
 488–489
 in wastewater collection, treatment,
 and disposal, 353
 chemicals used, 303
 sludge quantities, estimation of, 489–492
- Chemical unit processes:
 adsorption, 314–324
 breakpoint chlorination, 738–740
 carbon adsorption, 751–753
 chemical precipitation, 302–314
 dechlorination, 343–345
 definition of, 301
 disinfection:
 with bromine chloride, 347–348
 with chlorine, 332–343
 with chlorine dioxide, 345–346
 with ozone, 349–351
 with ultraviolet light, 351–352
 electro dialysis, 759
 ion exchange, 740, 756
 oxidation, 751, 755
 for phosphorus removal, 741–749
 sludge stabilization with lime addition,
 811–813
 thermal reduction, 881–885
 (*See also individual listings*)
- Chemostat, 375
- Chemotrophic organisms, 361
- Chick's law, 328–329
- Chloramines:
 formation of, 334
 effectiveness in disinfection, 338
- Chlorides:
 importance of, 84
 as tracers, 85
 typical values: in septage, 110
 in wastewater, 109
- Chlorination:
 application of: dosages, 495
 uses, 494
 breakpoint reaction, 334
 chlorine chemistry, 332–334
 reactions with ammonia, 333
 reactions in water, 332
 chlorine compounds, 332, 494–497
 calcium hypochlorite, 332, 496
 chlorine dioxide, 496
 chlorine gas, 332, 495
 sodium hypochlorite, 332, 497
 equipment and dosage control,
 497–500
 for chlorine, 497
 for chlorine dioxide, 499
 for hypochlorite feeders, 499
 germicidal efficiency: of chlorine, 338
 of chlorine compounds, 338
 mixing and contact, 501–504
 of return sludge for bulking control,
 555

- Chlorinators, 497–499
 capacity, 497
 evaporators, 497
- Chlorine:
 chemistry of: with ammonia, 332
 in water, 332
 hydrolysis reaction, 332
 ionization reaction, 332
 combined available, 334–335
 compounds: calcium hypochlorite, 332, 496
 chlorine dioxide, 496
 chlorine gas, 332, 495
 sodium hypochlorite, 332, 497
 containers, 495
 demand, 335
 evaporators, 497
 free available, 333
 hydrolysis and ionization reaction, 332–333
 residuals: definition of, 334–335
 toxicity of, 343
 safety measures, 495–496
 storage and handling, 497
 (*See also* Disinfection with chlorine)
- Chlorine contact basins, 502
 design, 502–505
 residual measurement, 505
 solids transport velocity, 505
- Chlorine dioxide, 345–46, 496, 499
 (*See also* Disinfection with chlorine dioxide)
- Chlorine feeders, 497–499
 (*See also* Chlorinators)
- Chlorine oxidation of sludge, 811
- Chromium, 88
- Chronic toxicity, 104, 1197
- CID (*see* Critical initial dilution)
- Clarification (*see* Sedimentation;
 Sedimentation tanks)
- Clean Water Act (CWA), 123
- CMC (*see* Criterion maximum concentration)
- CMR (*see* Complete-mix reactor)
- Coarse screens, 452
- Co-composting with solid wastes, 850
- COD (*see* Chemical oxygen demand)
- Coefficient of rigidity for sludge, 792–793
- Coefficient of soil permeability:
 definition, 1047
 determination of, 1049
 typical values of, 1048
- Coincineration of sludge, 889
- Coliform organisms:
 classification of, 93
 completed test, 95–96
 confirmed test, 95–96
 estimation of, 97–99
 membrane filter technique, 99–100
 determination of most probable number
 (MPN), 97–99.
 MPN tables, 1261–1262
 presumptive test, 95–96
- Colloids:
 coagulation of, 303
 size range, 51
- Color, 64
- Combined aerobic treatment processes,
 637–641
 activated biofilter, 637
 biofilter activated-sludge, 641
 roughing-filter activated sludge, 640
 trickling filter-solids contact, 639–641
 typical design information, 639
 typical flow diagrams, 638
- Combined available chlorine, 334
- Combined sewers:
 definition of, 1103
 flow regulators for, 1106–1109
 outlets for, 1111
- Combined sewer flowrates, 1112–1117
 calculation of, 1116–1117
 computer modeling, 1116
 model calibration, 1117
 storm water management model
 (SWMM), 1116
 verification, 1117
 measurement of, 1113
- Combined sewer overflows (CSOs):
 control of, 1125–1129
 collection system controls, 1125
 list of methods for, 1126
 off-line storage, 1128
 source controls, 1125
 storage, 1128
 surface storage, 1128
 in-system storage, 1128
 first flush effect, 1119
 management of: current situation, 5
 future directions, 5, 1131–1132
 treatment of, 1129–1131
 biological treatment, 1129
 chemical (disinfection), 1130
 physical treatment, 1129
 wastewater characteristics, 1117
 calculation of characteristics, 1119
 comparative quality data, 1117
 comparison with other wastewaters, 1120
 variations in quality, 1117
- Combined sewer system, 1105–1112
 components of, 1105–1112
 flow regulators, 1106

- outlets, 1111
- pipe network and interceptor, 1106
- computer modeling of, 1116
- Combustion:
 - complete, 881–883
 - calculations for, 882
 - heating value of sludge, 882
 - oxygen requirements, 882
 - process applications, 885–889
 - definition of, 881
 - pyrolysis, 883–884
 - starved air, 884
 - wct, 884
- Comminution, 454–456
 - application and design, 456
 - description of, 455
 - function, 454
 - grinders, 456
 - headloss, 456
 - operating problems, 454
 - types of, 455
- Complete-mix activated sludge, 540
 - (*See also* Activated sludge)
- Complete-mix reactor (CMR):
 - analysis with recycle, 385–389
 - applications to activated sludge process, 385–392
 - bench scale, 1276
 - in biological treatment, 385
 - description of, 172
 - kinetic analysis of: complete-mix reactor
 - with first-order conversion reaction, 1267–1269
 - complete-mix reactors in series with first-order conversion reaction, 1270–1271
 - with recycle, 173
- Completed test for coliforms, 95–96
- Composition of septage, 110
- Composition of wastewater:
 - constituents in, 109
 - mineral increase during usage, 111
- Compost filter for odor control, 518
- Composting, sludge, 842–850
 - cocomposting with solid waste, 850
 - composting systems, 844
 - aerated static pile, 844
 - in-vessel, 845–847
 - windrow, 844
 - design considerations: important parameters, 847
 - table of, 848
 - process description, 844
 - process microbiology, 843
- Compression settling (type 4), 221, 240
- Conditioning of sludge, 850–854
 - (*See also* Sludge conditioning)
- Confirmed test for coliforms, 95–96
- Conservation of mass equation, 1208
- Constants, physical (*see inside of back cover*)
- Constructed wetlands, 992–1002
 - design parameters, 995
 - preapplication treatment, 993
 - site evaluation and selection, 992
 - types of wetlands: free water surface (FWS) 937, 998
 - subsurface flow system (SFS), 937, 998
 - vector control, 1002
 - vegetation selection and management, 994
 - (*See also* Natural treatment systems)
- Construction cost index, 134
- Contact basin, chlorine, 502–505
- Contact-stabilization activated sludge, 540
 - (*See also* Activated sludge)
- Contactors, carbon, 752
- Contaminants in wastewater, 49
- Continuous BOD, determination of, 79–80
- Continuous flow stirred-tank reactor (CFSTR), 172
 - (*See also* Complete-mix reactor)
- Conventional plug-flow activated sludge, 540
 - (*See also* Activated sludge)
- Conversion factors:
 - for design parameters, 1247
 - metric (SI) to U.S. customary units, 1244–1246
 - U.S. customary to metric (SI) units, 1241–1243
- Conveyance of sludge and solids, 915–918
 - by barge, 917
 - environmental considerations, 918
 - by pipeline, 917
 - by rail, 918
 - by truck, 917
- Cooling towers:
 - cycles of concentration, 1160
 - operating problems, 1160
 - water balance for, 1159
- Corrosion, metallic, 1161
- Cost considerations, 133–135
 - construction cost, 134
 - cost comparisons, 134
 - operations and maintenance, 134
- Criterion continuous concentration (CCC), 106
- Criterion maximum concentration (CMC), 106
- Critical initial dilution (CID), 106

- Crops for natural treatment systems:
 for slow rate, 948–949
 for overland flow, 992
 (*See also* Natural treatment systems)
- Cryogenic air separation for oxygen generation, 576
- Cryophilic aerobic digestion, 842
- Cryptosporidium*, 92, 94
- CSOs (*see* Combined sewer overflows)
- CFSTR (*see* Complete-mix reactor; Continuous flow stirred-tank reactor)
- CWA (*see* Clean Water Act)
- Cycles of concentration, 1160
- Cyclone degritter, 466, 796–798
- DAF (*see* Dissolved air flotation; Flotation, dissolved air)
- Darcy's law, 1047
- DBC (*see* Downflow bubble contactor)
- Death phase, bacterial, 368
- Decay:
 of bacteria in biological systems, 372
 of coliforms in ocean, 1206
 of organic matter, 1201
- Dechlorination:
 analysis of: with activated carbon, 345
 with sulfur dioxide, 344
 design considerations: for activated carbon, 506
 for sulfur dioxide, 506
 typical design information, 507
 toxicity of chlorine residuals, 343
- Decomposition of organic matter, 382–383
- Deep shaft activated sludge reactor, 541
 (*See also* Activated sludge)
- Definition of terms:
 for biological treatment, 377–378
 for reclamation, 1139–1140
- Denitrification, biological, 432–433, 719–726
 (*See also* Nitrogen removal by biological denitrification)
- Density:
 of wastewater, 64
 of water, 1251–1253
 in SI units, 1253
 in US customary units, 1252
- Density currents:
 in lakes, 1212
 in settling facilities, 589–590
- Deoxygenation of rivers:
 due to organic matter, 1201
 due to plant respiration, 1204
 due to sludge deposits, 1203
- Deoxyribonucleic acid (DNA), 365, 375
- Design:
 conceptual, 138
 final, 139
 preliminary, 139
 special studies, 139
- Detention time, hydraulic, 386, 550
- Detergents, 67
- Dewatering of sludge, 855–877
 (*See also* Sludge dewatering)
- Diamines, 57
- Diaphragm pumps for sludge and scum pumping, 787
- Die-off, bacterial, 1206
- Diffused-air aeration, 556–569
 air piping, 566–569
 blowers, 563–566
 diffuser performance, 561–563
 diffusers, 556–561
 for post-aeration, 512
 (*See also* Aerators: diffused air)
- Diffuser:
 for chlorine injection, 502–503
 for ocean outfall, 1228–1232
 for river outfall, 1223–1224
- Diffusion:
 eddy, 1200–1201
 of wastewater in ocean, 1233
- Digester gas:
 characteristics of, 823
 collection and storage of, 825
 composition of, 823
 heating value of, 826
 production of, 825
 safety considerations, 826
 specific gravity of, 825
 use of, 826
 volume based on BOD conversion, 426–427
- Digester heating, 830–834
 analysis of heat requirements, 830
 heat loss computations, 833–834
 heat transfer coefficients, 831–832
 heating methods, 830
- Digester mixing:
 aerobic, 837, 839
 anaerobic, 826–830
- Digesters (*see* Aerobic sludge digestion; Anaerobic sludge digestion)
- Digestion, aerobic, 401–403, 832–842
 (*See also* Aerobic sludge digestion)
- Digestion, anaerobic, 420–427, 813–834
 (*See also* Anaerobic sludge digestion)

- Dilution:
 achieved with ocean outfalls: initial,
 1228-1232
 farfield, 1232-1233
 achieved with river outfalls: computation
 of, 1225
 initial, 1224
- Direct injection, 1168
- Discrete particle settling (type 1), 222-226
- Diseases, waterborne, 94, 324
- Disinfection (general theory of), 324-332
 disinfectants: comparison of properties, 326
 types of, 326-327
 factors influencing the action of
 disinfectants, 327-331
 concentration of chemical agent, 330
 contact time, 328
 intensity and nature of physical agent,
 330
 nature of suspending liquid, 331
 number of organisms, 331
 temperature, 330
 type of chemical agent, 330
 types of organisms, 331
 mechanisms of disinfectants, 325-327
 methods and means of, 324-325
 by chemical agents, 324
 by mechanical means, 325
 by physical agents, 325
 by radiation, 325
 by various treatment processes, 328
- Disinfection of sludge:
 by chemical addition, 811-813
 by composting, 842-850
 by heat treatment, 813
 by long-term storage, 855
 by pasteurization, 855
- Disinfection with bromine chloride, 347-348,
 506
 bromine chloride chemistry: reactions
 with ammonia, 347
 reactions in water, 347
 effectiveness of bromine chloride,
 348-349
 by-product formation, 348
 environmental impacts, 348
 flow diagram for, 508
- Disinfection with chlorine, 332-343,
 494-505
 breakpoint reaction, 334
 acid generation, 336
 buildup of total dissolved solids, 336
 chlorine chemistry, 332-334
 reactions with ammonia, 333
 reactions in water, 332
 chlorine compounds: calcium hypochlorite,
 332, 496
 chlorine dioxide, 496
 chlorine gas, 332, 495
 sodium hypochlorite, 332, 497
 dechlorination, 343-345, 506
 with activated carbon, 345, 506
 with sulfur dioxide, 344, 506
 factors that affect disinfection efficiency
 of chlorine, 337-343
 breakpoint reaction, 339
 characteristics of microorganisms, 342
 characteristics of wastewater, 341
 contact time, 340
 germicidal efficiency of chlorine, 338
 germicidal efficiency of chlorine
 compounds, 338
 initial mixing, 339
 toxicity of chlorine residuals, 343
 (*See also* Chlorination)
- Disinfection with chlorine dioxide,
 345-346, 496
 chlorine dioxide generation, 345
 dechlorination of chlorine dioxide, 346
 effectiveness of chlorine dioxide: by-
 product formation, 346
 environmental impacts, 346
 flow diagram for, 499
- Disinfection with ozone, 349-351, 507-508
 effectiveness of ozone: environmental
 impacts, 350
 other benefits, 351
 flow diagram for, 509
 ozone chemistry, 349
 ozone generation, 349
- Disinfection with ultraviolet (UV) light,
 351-352, 508
 effectiveness of UV radiation:
 environmental impacts, 352
 optimizing performance of, 352
 flow diagram for, 509
 source of UV radiation, 351
- Dispersion:
 coefficient, 1214
 in pond systems, 644
 in rivers and estuaries, 1214-1216
- Disposal:
 of effluent (*see* Effluent disposal)
 of sludge (*see* Sludge disposal and
 reuse; Sludge disposal methods)
- Disposal beds or pits, 1034
- Disposal fields for septic tank effluent:
 assimilative capacity of site, 1047
 biomat formation, 1032
 degree of treatment, 1062

- Disposal fields for septic tank effluent (*Cont.*):
 description of, 1029
 design criteria: based on most conservative criterion, 1058
 based on percolation testing, 1056
 based on soil characteristics, 1057
 design example, 1061
 dosing: intermittent gravity-flow, 1029
 periodic application, 1033
 pressure dosed, 1064–1070
 percolation testing, 1044
 site criteria, 1043
 sizing and layout, 1059
 flowrates, 1019–1020, 1059
 layout, 1059
 soil acceptance rate, 1049
- Dissolved air flotation (DAF), 243, 804
 (*See also* Flotation, dissolved air; Flotation thickening)
- Dissolved inorganic substances, removal
 of, 756–759
 chemical precipitation, 756
 electro dialysis, 759
 ion exchange, 756–757
 reverse osmosis, 757–759, 1181–1184
 ultrafiltration, 757, 1184
- Dissolved oxygen (DO):
 concentration in water, 1258–1259
 as a function of temperature and barometric pressure, 1259
 as a function of temperature and salinity, 1258
 demand of wastewater (*see* Biochemical oxygen demand)
 factors controlling solubility, 89, 277–281
 importance of aerobic cycle: in nature, 382
 in receiving waters, 1201–1205
 in treatment, 535
 limits in receiving waters, 1196
 in oxygen sag analysis, 1216–1218
 solubility in water, 1255–1256
 surface reaeration, 1202–1203
- Dissolved solids:
 classification of, 50
 definition, 50
 typical values in wastewater, table of, 109
- Distribution:
 in intermittent sand filters and pressure dosed disposal fields, 1064–1070
 in trickling filters, 619–620
- DNA (*see* Deoxyribonucleic acid), 365
- DO (*see* Dissolved oxygen)
- Domestic wastewater:
 definition, 15
 sources and flowrate data, 26–29
- Domestic water use data, 17–19
 commercial facilities, 18
 institutional facilities, 19
 recreational facilities, 20
 residential, 17
- Dosing pump for septic tank, 1034
- Dosing rate for trickling filters 616–619
- Dosing siphon for septic tank, 1034
- Downflow bubble contactor (DBC), 577
- Draft in trickling filters, 623
- Drag, equation for, 218
- Drag force:
 in flocculation, 218
 in sedimentation, 222
- Dryers, 877–881
 (*See also* Heat drying of sludge)
- Drying beds, sludge, 870–876
 (*See also* Sludge drying beds)
- Dual digestion, 842
- Duckweed:
 characteristics of, 1005
 harvesting of, 1007
 use in wastewater treatment systems, 1006
- Dynamic forced-choice triangle olfactometer, 60–61
- EC (*see* Electrical conductivity)
- ED₅₀, 59
- Eddy diffusion:
 coefficient of: determination by field methods, 1215
 mathematical formula, 1214, 1221
 in oceans, 1221
 in rivers and estuaries, 1214
- Efficiency:
 of treatment processes: activated sludge, table of, 548–549
 advanced, table of, 670
 for nitrogen removal, 692–693
 for phosphorus removal, 695
 primary sedimentation, 473
 trickling filters using plastic media, 640
 of waste stabilization, defined, 389
- Effluent characteristics:
 from advanced wastewater treatment, 670
 aerated lagoons, 645
 from natural treatment systems, table of, 932
 from rotating biological contactors:
 for ammonia removal, 707
 for BOD removal, 634
 from stabilization ponds, 645

- Effluent disposal:
 into estuaries, 1213-1225
 into lakes and reservoirs, 1209-1213
 on land (*see* Natural treatment systems)
 into the ocean, 1225-1236
 options for small communities, 1089
 new directions and concerns, 11
 (*See also individual listings*)
- Effluent disposal into estuaries, 1213-1225
 dispersion coefficient, 1214
 dissolved-oxygen sag analysis, 1216-1220
 general description of, 1213-1216
 mixing zone, 1221-1223
 tidal action, 1220
- Effluent disposal into lakes and reservoirs,
 1209-1213
 analysis of, 1209-1211
 eutrophication, 1213
 stratification, 1212
- Effluent disposal into oceans, 1225-1236
 density of seawater, 1226
 initial mixing, 1228-1232
 multipoint discharges, 1229
 vertical single-point discharges, 1228
 farfield modeling, 1232-1236
 with complex current patterns, 1234
 mixing analysis example, 1234
 with spatially uniform current, 1232
 transition region, 1232
 general description of, 1225-1227
 outfall design, 1228-1232
 outfall design example, 1231-1232
- Effluent disposal into rivers, 1213-1225
 deoxygenation: due to organic matter, 1201
 due to sludge deposits, 1203
 due to respiration of plants, 1204
 oxygen sag analysis, 1216-1220
 critical dissolved oxygen deficit, 1217
 critical distance, 1217
 critical time, 1217
 general equation, 1217
- Effluent filter vault for septic tanks,
 1026-1027
- Effluent filtration, 666-689, 1177-1178
 (*See also* Filtration, granular medium)
- Effluent reuse, 1137-1189
 (*See also* Wastewater reclamation and reuse)
- Effluent standards, 1197-1198
- Egg-shaped anaerobic digester, 823
- Electrical conductivity (EC):
 definition of, 1145
 importance of, 1145
 relationship to total dissolved solids
 (TDS), 1145
- Electrical double layer, 312
- Electrodialysis, 759
- Electrolysis cell for BOD measurement,
 79-80
- Electron acceptors in bacterial reactions,
 table of, 363
- Elutriation, 854
- Endogenous metabolism, 372
- Endogenous phase in bacterial growth, 368
- Energy dissipation in mixing, 213
- Energy reactions:
 for aerobic oxidation, 379
 for nitrification, 695-696
- Energy requirements:
 for activated sludge mixing, 573
 for aerobic digester mixing, 839
 for anaerobic digester mixing, 830
 for blowers, 565
 for mixing and flocculation: paddle
 mixers, 217-219
 pneumatic mixing, 219-220
 propeller and turbine mixers, 215-217
 static mixing, 219
- Environmental-impact assessment, 135, 1195
- Epilimnion, definition of, 1212
- Equalization, flow, 203-212, 468-470
 (*See also* Flow equalization)
- Error function, computation of, 1221
- Escherichia coli* (*E. coli*):
 decay in salt water, 1206
 in filamentous growth, 385
 inorganic composition, table of, 538
 occurrence of, 93
 tests for: completed, 95-96
 confirmed, 95-96
 presumptive, 95-96
 use as indicator organism, 93-95
- ESP (*see* Exchangeable sodium percentage)
- Estuaries, effluent disposal in, 1213-1225
- Eucaryotic cell, 90
- Eutrophication, 1213
- Evapotranspiration rates for selected
 geographical locations, table of, 951,
- Excess activated-sludge wasting, 551-553
- Exchangeable sodium percentage (ESP), 945
- Expanded bed process, 429
- Expanded bed reactor, 172
 application of, 421, 429, 719, 725
 description of, 172
- Explosion hazards, 826
- Extended-aeration activated sludge, 541
 (*See also* Activated sludge)
- Facilities planning, 137
- Facultative bacteria, 436

- Facultative ponds, 436-438, 648-650
(*See also* Stabilization ponds)
- Facultative process:
 application of, 436-438
 definition of, 371
- Fall turnover in lakes, 1212
- Farfield mixing in ocean disposal,
 1232-1236
- Fate processes in the environment,
 1198-1209
 conservation of mass equation,
 1208-1209
 transformation processes, 1201-1208
 adsorption, 1206
 BOD oxidation, 1201
 photosynthesis and respiration, 1204
 sediment oxygen demand, 1203
 solids deposition, 1205
 surface reaeration, 1202
 volatilization, 1207
 transport processes, 1199-1201
 advection, 1199
 diffusion, 1200
- Fats in wastewater, 66
- Fecal coliform to fecal streptococci, ratio
 of, 100-101
- Fecal coliforms:
 determination of, 95-100
 importance of, 93
 inorganic composition, 538
 sources of, 93
 use as indicator organism, 93
- Fecal streptococci, 93-94
- Fermentation metabolism, 363
- Ferric chloride, 303, 306
- Ferric sulfate, 303, 306
- Ferrous sulfate, 303, 306
- Fertilizer:
 value of commercial products, 772
 value of sludge, 772
- Filamentous organisms:
 occurrence, 396-398, 537-538
 prevention and control of, 538
(*See also* Bulking sludge)
- Film process, attached (*see* Attached
 growth treatment processes)
- Filter presses for sludge dewatering, recessed
 plate:
 application, 868
 design considerations, 869-870
 types of, 868-869
 fixed-volume, 868
 variable-volume, 869
 typical performance data, 892-893
- Filter vault for septic tanks, 1026-1027
- Filtering materials (*see* Filtration, granular
 medium)
- Filters:
 anaerobic, 429
 expanded-bed, 429
 granular medium (*see* Filtration, granular
 medium)
 intermittent sand (*see* Intermittent sand
 filter)
 pressure, 680
 trickling (*see* Trickling filters)
- Filtration, granular medium, 248-276,
 666, 671-689
 analysis of filtration operation, general,
 263-265
 equation of continuity, 264
 rate equation, 265
 analysis of pilot plant data, example
 of, 271-276
 analysis of wastewater filtration, 265-269
 clear water headloss computation,
 example of, 267-268
 equation of continuity, 264
 generalized rate equation, 266
 headloss computation, table of equations
 for, 268
 headloss development, 267-271
 rate equation, 265
 application of, 671
 characteristics of filtering materials,
 678-679
 classification of filtration systems, 254-257
 direction of flow, 255
 filtration driving force, 256
 flow control, 256-257
 types of filter beds, 255
 description of filter operation, 248-249
 continuous, 249
 semi-continuous, 248
 effluent filtration with chemical addition,
 687-689
 effects of wastewater characteristics, 688
 operating ranges for alum coagulation,
 688
 use of organic polymers, 687
 filter appurtenances, 683-685
 surface washers, 685
 underdrain systems, 683
 washwater troughs, 683
 filter backwashing systems, 680-683
 combined air-water, 682
 water with air auxiliary scour, 681
 water with auxiliary surface wash, 680

- filter bed options, 673-678
 - dual- and multi-medium, 678
 - mono-medium unstratified, 676
 - shallow mono-medium stratified, 674
 - stratified, 673
 - unstratified, 673
- filter instrumentation and control systems, 685
- filter problems, summary table of, 686
- filtration process variables: filter medium characteristics, 260
- filtration rate, 260
- influent characteristics, 257-260
- table of, 259
- flow control, 256-257
 - constant rate, 257
 - variable rate, 257
- number and size of filter units, 671-672
- operational characteristics, table of, 251
- particle removal mechanisms, 260-263
 - pictorial representation, 262
 - summary of methods, table of, 261
- physical characteristics, table of, 250, 674-675
- pilot plant studies, need for, 271
- process variables: filter medium characteristics, 260
- filtration rate, 260
- influent characteristics of, 257
- selection of type of filter, 672-678
- performance characteristics of different types of filters, 672
- types of filters: illustration of, 252-254, 677-678, 680
- table of, 250, 674-675
- Financing, 142-144
 - leasing, 143
 - long-term municipal debt, 142
 - non-debt financing, 142
 - privatization, 143
- Fine screens, 486-487
- First flush effect, 1119
- First-order reaction, 1201
- Fish:
 - dissolved oxygen levels for, 1196
 - used in bioassay tests, 103
- Fixed film processes (*see* Attached growth treatment processes)
- Fixed screen, inclined, 202, 452
- Fixed solids;
 - suspended, 52
 - total, 52
- Flash dryers, 878
- Floating aquatic plant treatment systems, 1002-1013
 - design criteria, 1008
 - design parameters, 1007
 - mosquitos and their control, 1011
 - plant harvesting and processing, 1012
 - plant selection, 1005
 - duckweed, 1005
 - pennywort, 1005
 - water hyacinths, 1005
 - preapplication treatment, 1003
 - site evaluation and selection, 1003
 - types of systems, 1006
 - duckweed, 1006
 - water hyacinth, 1006
 - (*See also* Natural treatment systems)
- Floating digester covers, 825
- Flocculant settling (type 2), 226-228
 - analysis of, 226
 - definition of, 226
- Flocculation:
 - design information, 471
 - function, 471
- Flotation:
 - air, 243
 - applications, 242, 486, 802, 804
 - chemical additives, 242
 - description of, 242
 - dissolved-air: air-to-solids ratio, 246
 - analysis of, 245-246
 - design example, 246
 - recycle flow, 246
 - solids loading information, 809
 - theory of, 245-246
 - of sludge, 804-805, 809
 - test apparatus for, 245
 - of untreated wastewater, 486
 - vacuum, 243
- Flotation thickening:
 - description of, 804-805
 - typical polymer dosages for, 810
 - typical solids loading for, 809
- Flow diagrams for treatment processes:
 - for activated-sludge processes: complete mix, 194, 543, 894
 - contact stabilization, 544
 - conventional plug flow, 542
 - deep shaft, 546
 - oxidation ditch, 545
 - step aeration, 543
 - for advanced treatment, 668-669, 1181-1184
 - for ammonia removal by zeolite exchange, 741

- Flow digrams for treatment processes (*Cont.*):
- for anaerobic digester, egg-shaped, 824
 - for anaerobic wastewater treatment, 421
 - for biological removal of phosphorous, 435, 728
 - for biological treatment processes, typical, 530
 - for carbon adsorption, 752
 - for chemical feed systems (dry and wet), 493
 - for chemical fixation, 916
 - for combined removal of nitrogen and phosphorous, 733
 - for complete wastewater recycle, 1039
 - definition of, 182
 - for disinfection with: bromine chloride, 508
 - chlorine/sulfur dioxide dechlorination, 498
 - chlorine dioxide, 499
 - hypochlorination/dechlorination, 500
 - ozone, 509
 - ultraviolet (UV) light, 509
 - for dissolved-air flotation, 244
 - for filter operation, 252-253
 - for independent physical-chemical treatment of wastewater, 490
 - for lime post treatment of sludge, 813
 - for operation of sequencing batch reactor, 401
 - for nitrogen removal in onsite systems, 1063
 - for nitrogen removal, biological two-stage, 721
 - for nitrification/denitrification, combined stage, 715
 - for onsite wastewater disposal, 1024
 - for phosphorus removal with chemicals, 743
 - for phosphorus removal with lime:
 - single-stage, 749
 - two-stage, 749
 - for powdered activated carbon treatment (PACT), 754
 - for recirculating sand filter, 1080
 - for removal of residual suspended solids, 1178
 - for reverse osmosis, single stage, 758
 - for rotating biological contactor (RBC), 630-631
 - for secondary treatment, typical: with biological means, 894
 - with physical/chemical means, 490
 - for septage treatment, 1091
 - for single-stage lime treatment, 749
 - for sludge pasteurization, 856,
 - for sludge processing and disposal (generalized), 780-781
 - for treatment processes, definition of, 182
 - for treatment of sludge with: biological methods, 782
 - nonbiological methods, 783
 - for trickling-filter processes, 410, 617
 - for two-stage lime treatment, 749
 - for ultrafiltration and reverse osmosis, 758
 - for vacuum filtration, 860
 - for VOC gas phase adsorption, 520
 - for VOC treatment in off gases: by incineration, 523
 - by steam assisted flare, 523
 - by thermal incineration, 522
 - for wastewater treatment with water hyacinths, 1004
 - for wet air (Zimpro) oxidation process, 853
- Flow equalization, 153, 203-212, 468-470
- analysis of: in-line or off-line, 205
 - location, 205
 - volume required, 206-207
 - application of, 204
 - basin construction: appurtenances, 469
 - basin geometry, 468
 - construction materials, 468
 - description of, 204
 - example of volume determination, 207-212
 - mixing and air requirements, 469
 - pumps and pump control, 470
- Flow measurement, 195-200
- application of, 196-197
 - characteristics of flow metering devices, 199
 - maintenance of flow measuring devices, 198
 - selection criteria, 196
 - types of flow-metering devices, 196
 - for closed conduits, 196
 - for open channels, 196
- Flow models, hydraulic for combined sewer systems, 1116-1117
- Flowrates, 15-43
- (*See also* Wastewater flowrates)
- Flow reduction, devices and appliances, table of, 42
- Flow regulators for combined sewer overflows, 1106-1109
- description of, 1107
 - types, 1106
- Fluid classification:
- Newtonian, 788
 - Non-Newtonian, 788
- Fluidized-bed incineration, definition of, 886

- description of, 886–887
 - bubbling bed, 887
 - circulating bed, 888
 - recycle flows, 888
- Fluidized-bed reactor for denitrification, 724–725
- Foaming:
 - in aeration tanks, 580
 - in digesters, 825
- Food-to-microorganism ratio:
 - application of, 532–534, 538, 550
 - definition of, 389, 532
 - design parameters, table of, 550
 - typical values for activated-sludge processes, 534
- Forest land sludge application, 913
- Fouling in cooling towers, 1162
- Free vortex, 241–242
- Freezing for sludge conditioning, 854
- Freundlich adsorption isotherm, 318
- Friction factors, Moody diagrams, 1282–1283
- Froth-control systems, for activated sludge process, 580
- Fungi, 91

- G (velocity gradient):
 - definition of, 213–214
 - equation for, 213
 - typical values: for flocculation, 215
 - for initial mixing, 215
- GAC (*see* Granular activated carbon)
- Gambusi affinis*, 1002, 1011
- Garbage grinders (effects on unit loading factors), 165–166
- Gas, digester, 823–826
 - (*See also* Digester gas)
- Gas solubility:
 - factors affecting, 1255
 - Henry's law, 1255
 - Henry's law constants, 1256
 - for several gases, 1256
 - (*See also* Gas transfer)
- Gas stripping for VOC removal, 288
- Gas transfer:
 - analysis of, 277–282
 - description of, 276–277
 - evaluation of aerator performance, 282–285
 - factors affecting oxygen transfer, 285–287
 - correction factors, 287
 - mixing intensity, 286
 - tank geometry, 286
 - temperature, 286
 - wastewater characteristics, 286
 - Henry's law, definition, 289–290
 - Henry's law, constants, table of, 291
 - mass transfer coefficient, $K_L a$: definition of, 280
 - temperature correction, 286
 - oxygen transfer devices, 279
 - transfer coefficient, 286
 - two-film theory, 277
- Gases in wastewater:
 - ammonia, 430
 - dissolved oxygen, 89
 - hydrogen sulfide, 89
 - methane, 89
- Gaussian distribution, 1215, 1233
- Giardia lamblia*, 92, 94
- Granular activated carbon (GAC), 315
 - (*See also* Activated carbon)
- Granular medium filtration
 - (*see* Filtration, granular medium)
- Gravity belt thickening, description of, 806–807
- Gravity filtration, 253
 - (*See also* Filtration, granular medium)
- Gravity thickening of sludge, 802–804
 - application of, 808–809
 - description of, 802–804
 - solids loadings, 808
 - typical solids concentrations, 808
- Grease:
 - accumulation in sludge piping, 795
 - content of sludge, 771
 - forms of, 66
 - importance of, 66
 - typical values: in septage, 1022
 - in wastewater, 109
- Grease and oil interceptor tanks, 1028–1029
- Grinder pumps for pressure sewers, 1073
- Grinders:
 - in-line, 456
 - screenings, 454
- Grit:
 - characteristics, 456
 - definition, 456
 - disposal of, 466
 - quantity of, 466
 - separation and washing, 467
- Grit chambers, 457–466
 - aerated, 460–464
 - design example, 463
 - design information, 462
 - flow pattern, 462
 - grit removal equipment, 461, 463
 - release of VOCs, 463
 - application, 457

- Grit chambers (*Cont.*):
 horizontal flow, 458–460
 design information, 458
 rectangular, 458
 settling area curves, 460
 square, 459
 location, 457
 vortex, 464–466
 design information, 466
 types, 464
- Grit removal, 456–468
 from aerated grit chambers, 461
 from horizontal-flow grit chambers, 459
 from plant, 467
 from sludge, 465, 796–798
 from vortex-type grit chambers, 464
- Grit washer, 467
- Groundwater:
 effect on mineral increase, 111–112, 164
 effect on wastewater quality, 164
 infiltration into sewers, 29–32
 definition, 29
 description of, 31–32
 quantities of, 31
- Groundwater recharge with reclaimed wastewater, 1166–1172
 fate of contaminants in groundwater, 1169
 dissolved, 1168
 particulate, 1169
 pathogen removal, 1171
 preapplication treatment requirements, 1168
 recharge guidelines, 1171
 recharge methods, 1166–1168
 direct injection, 1168
 surface spreading, 1166
- Growth coefficients (*see* Kinetics of biological growth; Kinetic coefficients for bacterial growth)
- Growth cycles, bacterial:
 aerobic, diagram of, 382
 anaerobic, diagram of, 383
- Growth kinetics, biological, 369–373
 (*See also* Kinetics of biological growth)
- Growth rate, specific, 370
- Half velocity constant, 370
- Harvesting:
 of duckweed, 1007
 of water hyacinths, 1012
- Headloss:
 across treatment units, 188
 in air piping, 566–569
 through bar racks, 448
 through comminutors, 456
 in granular medium filtration, 267–271
 clearwater, 267–268
 wastewater, 267, 269
 through screens, 453
 in sludge pumping, 787–794
 sludge pumping example, 794
- Heat drying of sludge, 877–881
 air-pollution and odor control, 880
 drying options:
 flash dryers, 878
 multiple-effect evaporators, 878
 multiple hearth dryer, 878
 rotary dryers, 878
 spray dryers, 878
 theory of, 877
- Heat for disinfection, 854–855
- Heat treatment of sludge:
 for conditioning: description of, 852–853
 schematic diagram for, 853
 for stabilization, 813
- Heating, digester, 830–834
 analysis of heat requirements, 830–831
 heat loss computations, 833–834
 heat transfer coefficients, 831–832
 heating methods, 830–831
- Heating value of sludge, table of, 883
- Heavy metals:
 importance of, 88
 removal of, 756
 in septage, 110
 sources of, 88
- Hedstrom number, 793
- Helminths (worms):
 description of, 92
 pathogenic types, 94
- Henry's law:
 application, 289, 1256
 constants for various gases, 1256
 definition of, 1255
- Herbicides, 69–70
- Heterotrophic organisms, 361
- High-pressure piston pump for pumping sludge, 787
- High-purity oxygen:
 activated sludge, 541
 aerobic digestion, 841
 dissolution of, 576–578
 dissolution time, 576
 by downflow bubble contactor, 576
 energy consumption, 578
 by U-tube contactor, 577
 generation of, 574–578
 by cryogenic air separation, 576
 by pressure-swing adsorption, 574

- High-rate aeration activated sludge, 541
(*See also* Activated sludge)
- Hindered settling (type 3), 229-240
- HRT (*see* Hydraulic retention time)
- Hydraulic detention time, 386, 550
- Hydraulic profiles, 188
- Hydraulic retention time (HRT), definition of, 386
- Hydrogen ion concentration (pH), 84
- Hydrogen sulfide:
characteristics of, 89
corrosion caused by, 87-88
formation of, 89
odor problems, 85
removal of, 514-515, 517
solubility in water, 1255-1256
- Hydrolysis products, 313-314
- Hydroxylapatite, 308
- Hypochlorite:
application methods of, 496-497, 500
germicidal efficiency of, 338-340
- Hypochlorite compounds:
calcium, 332, 486
sodium, 432, 497
- Hypolimnion, definition of, 1212
- (I/I) (*see* Infiltration inflow)
- Imhoff cone, 50, 53
- Imhoff tank:
description of, 1029, 1078
design criteria, 1079
- Imperforate basket centrifuge, 805, 862
- Incineration:
applications, 885-888
combustion calculations, 882
of sludge, 885-888
(*See also* Combustion; Thermal reduction of sludge)
- Incinerators:
fluidized-bed, 886-888
multiple hearth, 885-886
(*See also individual listings*)
- Indicator organisms:
definition of, 93
of human pollution, 93, 95-96
used to establish performance criteria for various water uses, 96
- Indirect potable reuse of wastewater, 1173
- Industrial cooling water reuse, 1157-1166
cooling tower make-up water, 1157
cycles of concentration, 1160
problems in cooling tower systems, 1160-1162
biological growth, 1161
fouling, 1162
metallic corrosion, 1161
scaling, 1162
water quality requirements for steam and cooling in heat exchangers, 1163
water and salt balances in cooling towers, 1158
- Industrial wastewater:
definition of, 16
typical flowrate design values, 27
- Industrial water use, 19, 21, 1157
- Infectious agents in wastewater, table of, 94
- Infiltration:
computation of, 32
definition, 29
sources of, 31
- Infiltration/inflow (I/I), 29-33
computation of, 32
cost-effectiveness analysis, 30
definition of, 16, 29
effects on peak flowrates, 153
- Inflow:
computation of, 32
delayed, 30
direct, 29
steady, 29
total, 30
- Initial dilution in ocean outfalls, estimation of, 1228-1232
- Initial mixing:
in chlorination, 502-504
methods, 502
mixing chamber, 504
typical diffusers, 503
typical injector mixers, 504
in ocean outfalls, 1228-1232
- Injection, chlorine, 502-503
- Inorganic matter in wastewater, 83-88
alkalinity, 85
chlorides, 84, 109
heavy metals, 88
nitrogen: forms of, 85-86
pathways in nature, 86
pH, 98
phosphorus, 86-87
sulfur, 87-88
toxic compounds, 88
- Interceptor sewers, 1106
- Intermittent sand filter:
description of, 1035-1036
design criteria, 1066
design example, 1068
typical performance data, 1040
- In-vessel sludge composting, 845
- Ion exchange:
for removal of ammonia, 740-741
flow diagram for, 741

- Ion exchange, for removal of ammonia
(*Cont.*):
 regenerants, 740-741
 types of resins, 740
for removal of inorganic substances,
 756-757
 application rates of wastewater, 757
 description of, 756
 regenerants, 756-757
- Iron as a nutrient, 537
- Irradiation:
 for bacterial control, 351-352, 508, 509
 for sludge conditioning, 854
- Irrigation:
 early practice, 928
 for overland-flow systems, 984-985
 for slow-rate systems, 953-957
(*See also* Surface application methods
 for wastewater)
- Irrigation return water, 966
- Isotherms, adsorption, 318-320
 definition of, 318
 example use of, 319-320
 Freundlich, 318
 Langmuir, 318
- Jet aerator, 559, 561
- Jet mixing, turbulent, 502, 504
- Kessener brush aerator, 571
- Kinetic coefficients for bacterial growth:
 for activated sludge process, table of, 394
 for anaerobic digestion, table of, 426
 for denitrification, table of, 721
 for nitrification, table of, 701
- Kinetics:
 of adsorption, 1206-1207
 of biochemical oxygen demand test,
 72-76
 of biological growth (*see* Kinetics of
 biological growth)
 of biological treatment, 374-377
 of disinfection, 329-331
 of gas transfer, 280-281
 of sludge digestion, 426
 of VOC removal, 288-293
(*See also* Activated sludge, kinetic
 analysis of process)
- Kinetics of biological growth, 369-377
 application of growth and substrate
 kinetics to biological treatment,
 374-377
 effluent microorganisms and substrate
 concentration, 376-377
 microorganism and substrate balances,
 374-376
 cell growth, 370
 cell growth and substrate utilization, 371
 effects of endogenous metabolism, 372
 substrate limited growth, 370
- Kjeldahl nitrogen, 85
- Kraus process activated sludge, 541
(*See also* Activated sludge)
- Laboratory studies:
 anaerobic treatment, 1276
 biological treatment, 375
 complete-mix reactors, 1276
 flotation, 245
 sludge filterability, 851
- Lag growth phase, bacterial, 368
- Lagoons:
 aerated 604-614
 (*See also* Aerated lagoons)
 aerobic, 642-648
 aerobic-anaerobic, 648-650
 anaerobic, 650
 sludge, 876, 920
(*See also* Stabilization ponds)
- Lakes:
 effluent disposal in, 1209-1213
 eutrophication of, 1213
 stratification of, 1212-1213
- Land application of sludge, 903-914
 application methods, 912-914
 for dewatered sludge, 914
 for liquid sludge, 912-914
 loading rates, 908-910
 example of, 910-912
 land requirements, 910
 for nitrogen, 909
 for phosphorus, 910
 for pollutants, 908
 nutrient levels,
 in commercial fertilizers, 772
 in wastewater sludge, 772
 regulated pollutants for, 778
 regulatory requirements, 904-905
 site evaluation and selection, 905-907
 slope limitations, table of, 906
 sludge characteristics affecting,
 903-904
 soil limitations, table of, 906
 typical application rates, 905
 typical metal content in sludge, 772
- Land treatment (*see* Natural treatment
 systems)
- Langmuir adsorption isotherm, 318
- Lateral diffusion coefficient, 1214, 1221

- LC₅₀, 104, 1198
 Leachfield (*see* Disposal fields for septic tank effluent)
 Lewis-Whitman two-film theory, 277
 (*See also* Gas transfer)
 Lime:
 addition: for air stripping, 735, 738
 for chemical precipitation, 303–305
 for sludge conditioning, 851
 for sludge stabilization, 811
 characteristics of, 303
 dosages for untreated wastewater, 738
 (*See also* Calcium hydroxide)
 Lime stabilization, 811–813
 lime pre-treatment, 811–812
 lime post-treatment, 812–813
 temperature increase using quicklime, 812
 typical dosages, 811
 Limiting nutrient, 1213
 Loading criteria:
 for activated carbon contactors for wastewater treatment, 753
 for activated sludge process, 532–534, 550
 for aerobic digesters, 837
 for anaerobic digesters, 820, 823
 for attached growth processes for nitrification, 706
 for combined aerobic treatment processes, 639
 for constructed wetlands, 995, 999–1000
 for disposal fields, 1056–1059
 for dissolved air flotation units, 809
 for floating aquatic plant systems, 1008, 1010
 for gravity thickeners, 808
 for intermittent slow and recirculating sand filters, 1066
 for land application of sludge, 908–910
 for microscreens, 690
 for open sludge drying beds, 873
 for overland flow systems, 989–972
 for package treatment plants, 1084–1085
 for rapid infiltration systems, 969–972
 for rotating biological contactors, 630, 632
 for secondary clarifiers, 588
 for sedimentation tanks for chemical treatment, 488
 for slow rate systems, 958–962
 for stabilization ponds, 645
 for trickling filters, 615
 Loading data for treatment plants, analysis of, 156–163
 average mass loadings, 159
 flow-weighted average, 157
 simple average, 157
 sustained peak mass loadings, 159–161
 LOEC (*see* Lowest observable effect concentration)
 Log-mean temperature, 623
 Longitudinal dispersion:
 in estuaries, 1221
 in oceans, 1233
 in pond systems, 644
 in rivers, 1214
 Lowest observable effect concentration (LOEC), 104
 Magnetic flow meter, 196, 197
 Mass balances:
 application to: activated sludge, 387
 cooling towers, 1160
 effluent disposal, 1208
 estimation of sludge quantities, 891–902
 reactor analysis, 1269–1270
 return sludge pumping, 547, 551
 for batch reactor, 1265–1267
 for complete-mix reactor, 1267–1269
 for complete-mix reactors in series, 1270–1271
 example of solids balance, 894–903
 for non-ideal plug-flow reactor, 1271–1273
 for plug-flow reactor, 1269–1270
 preparation of, 891
 Mass concentration of microorganisms, 370
 Mass loadings, sustained:
 definition of, 159–160
 curves for BOD, SS, nitrogen, and phosphorus, 161
 Mass loadings for treatment plants, 153–166
 analysis, 156–160
 mass loading curves, 161
 unit waste-loading factors, 166
 Mass transfer:
 in aeration, 283–284
 coefficient for gas transfer, 280
 in stream transport, 1202
 of VOCs, 290
 Mass transfer rates for VOCs, 288–290
 Mass transfer zone (MTZ), 321
 Materials balance equations (*see* Mass balances)
 Maturation stabilization pond, 438
 MBAS (*see* Methylene blue active substances)
 MCRT (*see* Mean cell residence time)
 MDTOC (*see* Minimum detectable threshold odor concentration)
 Mean cell residence time (MCRT):
 for activated sludge, 533–534
 for anaerobic digestion, 818–819
 definition of, 386
 minimum values, 393

- Mean cell residence time (MCRT) (*Cont.*):
 typical values: for activated sludge, 550
 for anaerobic digestion, 818
 (*See also* Complete-mix reactor)
- Measurement of flowing water, 195–200
 (*see also* Flow measurement)
- Measurement of organic content of
 wastewater, 70–83
- Mechanical aerators, 569–574
 (*See also* Aerators, mechanical)
- Mechanical dewatering (*see* Sludge
 dewatering)
- Membrane filter technique, 99
 for coliforms, 99–100
 for suspended solids, 51, 53
- Mercaptans, 42
- Mesophilic anaerobic digestion:
 temperature range, 425
 typical design criteria for, 823
- Mesophilic organisms, 366
- Methane:
 solubility in water, 1255
 sources, 80–90
 uses, 826
 (*See also* Digester gas)
- Methanol, use in denitrification, 720
- Methylene blue active substances
 (MBAS), 67
- Metric (SI) conversion factors to U.S.
 customary units, 1244–1246
- Microbial metabolism:
 nutritional requirements for growth,
 360
 carbon and energy sources, 361
 microbial nutrition and biological
 treatment processes, 362
 nutrient and growth factors, 361
 types of metabolism: fermentative, 363
 respiratory, 363
 (*See also* Bacterial growth)
- Microorganisms:
 algae, 91, 367
 bacteria, 91, 364–366
 cell composition, 365
 cell structure, 364
 environmental requirements, 365
 classification, general, 90
 archaeobacteria, 90
 eubacteria, 90
 eucaryotes, 90
 classification of: by ability to utilize
 oxygen, 363
 by sources of energy and carbon, 361
 by temperature, 365
 found in wastewater, table of, 110
 of importance in biological treatment:
 algae, 367
 bacteria, 364–366
 fungi, 366
 protozoa, 366
 rotifers, 366
 pathogenic, 93
 pathogenic, table of, 94
 protozoa, 92, 366
 temperature ranges, table of, 94
 in treatment processes: activated sludge,
 384–385
 anaerobic digestion, 423–424
 denitrification, 432
 nitrification, 431
 trickling filter, 404, 406
 viruses, 92–93
- Microtrainers, 689–690
 application, 689
 description of, 689
 functional design of, 690
 typical design information, 690
- Mineral increase due to water use, 112
- Minerals required for bacterial growth,
 537
- Minimum detectable threshold odor
 concentration (MDTOC), 59
- Mixed-liquor suspended solids (MLSS),
 547, 550, 587, 592
- Mixed-liquor volatile suspended solids
 (MLVSS), 390, 534, 592
- Mixed-medium filtration (*see* Filtration,
 granular medium)
- Mixers:
 power requirements for, 215–220
 types of, 214
- Mixing:
 analysis of using propeller and turbine
 mixers, 215–217
 laminar conditions, 216
 turbulent conditions, 216
 application: in activated-sludge aeration
 tanks, 836, 837
 in aerated lagoons, 611
 in aerobic digesters, 839
 in anaerobic digesters, 826–830
 in chemical conditioning of sludge,
 852
 in chlorination, 502, 504
 in effluent disposal, 1221–1224
 in flocculation, 471
 in sludge blending, 799
 definition sketch for turbine mixer, 217
 description of, 213
 energy dissipation, 213

- importance of, 212
- methods of, 214
- power requirements for, 215–220
 - paddle mixers, 217–219
 - pneumatic mixing, 219–220
 - propeller and turbine mixers, 215–217
 - static mixing, 219
- theory of, 213–215
- times: for flocculation, 215
 - for mixing, 215
- velocity gradients (G): for flocculation, 215
 - for mixing, 215
- vortexing in, 217
- Mixing zone, 1221, 1228–1232
- MLSS (*see* Mixed-liquor suspended solids)
- MLVSS (*see* Mixed-liquor volatile suspended solids)
- Modified aeration activated sludge, 540
 - (*See also* Activated sludge)
- Moisture content:
 - of composting mixture, 848–849
 - of various sludges, table of, 774
- Molecular diffusion coefficient for oxygen, 1203
- Monod equation:
 - application, 700, 723
 - definition, 370
- Moody diagrams for fluid flow, 1282–283
- Mosquitofish, 1002, 1011
- Mosquitos and their control, 1002, 1011
- Most probable number (MPN):
 - application, 98–99
 - definition of, 96–97
 - determination of, 96–97
 - tables of, 1261–1263
- Mound system, 1037
- MPN (*see* Most probable number)
- MTZ (*see* Mass transfer zone)
- Mudball formation in filtration, 686
- Multimedia filtration:
 - application, 666–689
 - theoretical analysis, 248–276
 - (*See also* Filtration, granular-medium)
- Multiple-effect evaporator, 878–880
 - description of, 878
 - schematic diagram of, 880
 - (*See also* Carver-Greenfield process)
- Multiple hearth dryer, 878
- Multiple hearth incineration, 885–886
 - ash handling, 886
 - description of, 885
 - particulate discharges from, 886
 - sludge loading rates, 885
- Multipoint diffusers:
 - for river outfalls, 1229
 - for ocean outfalls, 1224
- National pollution discharge elimination system (NPDES), 123, 1197
- Natural treatment systems, 928–938
 - aquacultural, 938–944
 - bacteriological agents, 943
 - characteristics and objectives, 929
 - crop quality, 944
 - groundwater quality, 944
 - historical review, 928
 - public health issues, 943
 - site characteristics, companion of, 930
 - steps in the design of, table of, 946
 - treatment mechanisms, 938–943
 - types of systems: floating aquatic plants, 937
 - overland flow, 934
 - rapid infiltration, 932
 - slow rate, 929
 - wetlands (natural and constructed), 934–937
 - (*See also individual listings*)
- Natural wetlands, 925
- Newtonian fluids, 788
- Newton's law for gravity settling, 222
- Nitrification, biological:
 - in BOD test, 76
 - microorganisms involved in, 431
 - in natural systems, 939–940
 - process application, 431–432
 - process description, 431
 - processes for: single-stage combined
 - with carbon oxidation, 542, 689–706
 - comparison of, table of, 711–712
 - separate stage, 542, 706–711
 - stoichiometry, 431
- Nitrification/denitrification (*See* Nitrogen removal by biological nitrification/denitrification)
- Nitrogen:
 - cycle, 87
 - forms in wastewater: ammonia, 85
 - Kjeldahl, 85
 - nitrate, 86
 - nitrite, 86
 - organic, 85
 - importance of, 85
 - pathways in nature, 86
 - in proteins, 85
 - requirements for cell tissue, 537
 - solubility of gas in water, 1255–1256
 - sources of, 85

- Nitrogen (Cont.):**
 transformations in biological treatment processes, figure of, 430
 transformations in natural systems, 940
 typical values: in septage, 110
 in wastewater, 109
- Nitrogen and phosphorus, combined removal of, 731-735**
 A²/O process, 731
 Bardenpho process (five-stage), 732
 comparison of processes, table of, 735
 UTC process, 734
 VIP process, 735
- Nitrogen removal by biological assimilation, 430**
- Nitrogen removal by biological denitrification, 432-433, 719-726**
 attached growth process for, 723-726
 comparison of denitrification alternatives, table of, 727
 process application, 433
 process description, 432
 stoichiometry, 720
 suspended growth, 720-723
- Nitrogen removal by biological denitrification in natural treatment systems, 941**
- Nitrogen removal by biological nitrification/denitrification:**
 classification of, 713
 combined carbon oxidation, nitrification/denitrification (single-sludge) system, 714-716
 Bardenpho four stage, 714-715
 oxidation ditch, 715
 process design, 716-718
 comparison of processes, 727
 definition of, 432
 kinetic coefficients for, 721
 microorganisms involved, 432
 operation and environmental variables, table of, 723
 process analysis: attached-growth processes, 433
 suspended growth processes, 433
 process application, 433
 process description, 711-713
 process microbiology, 432
 rate of, 712-713
 separate-stage (separate-sludge), 719-726
 attached growth, 723-726
 effect of operational and environmental variables, 723
 stoichiometry, 720
 suspended-growth, 720 722
 typical design parameters, 722
 typical kinetic coefficients, 721
- Nitrogen removal by physical and chemical methods, 735-741**
 air stripping of ammonia, 735, 738
 breakpoint chlorination, 334 337, 738
 (See also Breakpoint chlorination)
 ion exchange, 740
- Nitrogen removal from sludge applied to land, 909-910**
- Nitrogen removal from wastewater:**
 by biological denitrification, 432-433, 719-726
 by biological denitrification in natural treatment systems, 941
 by biological nitrification/denitrification, 711-726
 by physical and chemical methods, 735-741
 (See also individual listings)
- Nitrogen transformations:**
 in biological treatment, figure of, 430
 in natural treatment systems, figure of, 940
- Nocardia foam, 556**
- NOEC (see No observable effect concentration)**
- NOECL (see No observable effect concentration level)**
- Nonlog centrifugal pump for sludge pumping, 784, 786**
- No observable effect concentration (NOEC), 104**
- No observable effect concentration level (NOECL), 104**
- Nonideal plug-flow reactor, analysis of, 1271-1279**
- Non-Newtonian fluids, 788**
- NPDES (see National pollution discharge elimination system)**
- NRC (National Research Council) trickling filter equations, 409-411**
- Nutrient removal:**
 nitrogen and phosphorus, combined removal of, 731-735
 nitrogen removal by biological nitrification/denitrification, 711-726
 nitrogen removal by physical and chemical methods, 735-741
 phosphorus removal by biological methods, 433-434, 726-731
 phosphorus removal by chemical addition, 306-310, 741-749
 (See also individual listings)
- Nutrients:**
 for biological systems, 536-538
 in commercial fertilizers, 772

- control of, 691–694
 - control and removal of nitrogen, 691
 - control strategies, 691
 - removal of phosphorus, 694
 - importance of, 86, 1196
 - nitrogen, 85–86, 1204
 - phosphorus, 86–87, 1204
 - requirements for biological growth:
 - inorganic ions, 537
 - nitrogen, 1204
 - phosphorus, 1204
 - uptake rates for selected crops, table of, 950
 - in wastewater sludge, 772
- Ocean disposal of effluent, 1225–1236
- description of, 1225–1228
 - estimation of initial dilution, 1228–1232
 - outfall design, 1228–1232
- Odor:
- causes of, 55
 - characterization of, 60
 - control methods (*see* Odor control)
 - detection of, 57
 - effects of, 57
 - errors in sensory detection, 60
 - measurement of, 60–62
 - with butanol wheel, 60
 - with dynamic forced-choice triangle olfactometer, 60–61
 - with scentometer, 61–62
 - minimum detectable threshold odor concentration (MDTOC), 59
 - threshold odor number (TON), 60
- Odor control, 512–518
- activated carbon adsorbers, 517
 - approach to, 512–514
 - buffer distances, 513
 - methods to control odorous gases, 514–518
 - soil-compost bed, 518
 - for sludge storage, 779
 - wet scrubbers, 515–517
 - removal efficiencies, 517
 - typical systems, 516
- Odor thresholds of odorous compounds in untreated wastewater, table of, 58
- Odorous compounds in wastewater, table of, 57
- Odorous gases, removal by wet scrubbers, 517
- Oils, 66
- Olfactometer, dynamic forced-choice triangle, 60–61
- One dimensional modeling, 1213
- Onsite systems, 1024
- components, 1024
 - disposal bed or pits, 1034
 - disposal field, 1029–1034
 - gray water system, 1038
 - grease and oil interceptor tanks, 1028
 - Imhoff tank, 1029
 - intermittent sand filter, 1035
 - mound system, 1037
 - recirculating sand filter, 1035
 - recycle treatment system, 1038
 - septic tank, 1025–1028
 - shallow sand-filled pressure-dosed disposal field, 1037
 - performance of, 1039–1041
 - selection and design of, 1041–1070
 - analysis of site assimilative capacity, 1047
 - degree of treatment, 1062
 - design criteria for physical facilities, 1062
 - detailed site evaluation, 1042
 - flow distribution in pressure-dosed systems, 1064
 - preliminary site evaluation, 1041
 - selection of design criteria, 1056
 - selection of systems for evaluation, 1054
 - sizing and layout of disposal fields, 1059
- Onsite wastewater management district (OSWMD), 1070–1071
- functions, 1071
 - requirements, 1071
 - types, 1071
- Operations and maintenance manual, 141
- Organic carbon, total (TOC):
- definition of, 82
 - typical values in wastewater, 109
- Organic matter in wastewater:
- agricultural chemicals, 70
 - carbohydrates, 65
 - fats, 66
 - grease, 66
 - measurement of, 70–83
 - oils, 66
 - pesticides, 70
 - priority pollutants, 67–68
 - proteins, 65
 - removal in natural systems, 939
 - size ranges of, 54
 - surfactants, 66
- Organic nitrogen, 85
- Organisms (*see* Microorganisms)
- OSWMD (*see* Onsite wastewater management districts)
- OTE (*see* Oxygen transfer efficiency)

- OTR (*see* Oxygen transfer rate)
- OUR (*see* Oxygen uptake rate)
- Outfall, ocean, 1228–1232
(*See also* Ocean disposal of effluent)
- Outlets, combined sewer, 1111
- Overflow rates for sedimentation tanks:
for primary clarifiers, 475
for secondary clarifiers, 588
- Overflows, combined sewer (*see* Combined sewer overflows)
- Overland-flow systems, 982–992
cover crop selection, 992
design parameters, 986
distribution methods, 984
land requirements, 990
preapplication treatment, 983
site evaluation and selection, 982
storage requirements, 990
system layout, 992
(*See also* Natural treatment systems)
- Oxidation (*see* Chemical oxidation)
- Oxidation ditch activated sludge, 541
(*See also* Activated sludge)
- Oxidation ponds, 641–655
(*See also* Stabilization ponds)
- Oxygen (*see* Dissolved oxygen)
- Oxygen demand:
biochemical, 71–82
chemical, 82
theoretical, 82
- Oxygen dissolution:
dissolution time, 576
downflow bubble contactor, 576
U-tube contactor, 577
- Oxygen generation:
by cryogenic air separation, 575–576
by pressure swing adsorption, 574
- Oxygen sag curve, 1216–1220
application, 1217–1220
critical deficit, 1217
critical time, 1217
mathematical development, 1216–1217
- Oxygen solubility in water, 1255–1256
- Oxygen transfer:
in activated sludge process, 561–563
in clean water, 283
coefficient, definition of, 282
efficiency of, 562
theory of, 278–287
in wastewater, 283
(*See also* Gas transfer)
- Oxygen transfer efficiency (OTE), 562
- Oxygen transfer efficiency, standard (SOTE), 561–562
- Oxygen transfer rate (OTR), 287
- Oxygen uptake rate (OUR), 539, 553
- Ozone:
for disinfection, 349–351, 507
(*See also* Disinfection with ozone)
for odor control, 353
as an oxidizing agent, 353
- PAC (*see* Powdered activated carbon)
- PACT (*see* Powdered activated carbon treatment)
- Package treatment plants, 1080–1088
design criteria for, 1084–1085
design and operational issues, 1081
improving performance of, 1086
selection of, 1087
types, 1081–1086
contact stabilization, 1082
extended aeration, 1081
physical-chemical treatment, 1083
rotating biological contactor, 1083
sequencing batch reactor, 1083
- Packed-bed reactor:
application, 420
description of, 172
- Paddle mixer, 217–219
- Particle aggregation, 311–313
definition, 311
modes of aggregation, 312
- Particle sizes:
in settled wastewater, 256
in wastewater, 56
- Pasteurization of sludge:
description of, 855
schematic diagram for, 856
- Pasteurizing of BOD samples, 77
- Pathogenic organisms:
removal in recharge systems, 1171
sources, 93
table of, 94
- Paved sludge drying beds, 873–874
area requirements, 873
description of, 873
view of, 874
- Peaking factors:
for flowrates, 149–153
from flowrate data, 150
from published data, 151
for mass loadings, 149, 161
- Pennywort, 1005
- Percolation test:
application, 1056
description of, 1044, 1046

- Pesticides, 70
- PFR (*see* Plug-flow reactor)
- PFRP (*see* Processes to further reduce pathogens)
- pH:
- algae, effect of, 438
 - definition of, 84
 - effect of: on ammonia removal, 735
 - on anaerobic digestion, 435
 - on biological treatment, 532
 - on denitrification, 723
 - on disinfection with chlorine, 332-333, 338
 - on microorganisms, 365-366
 - on nitrification, 700
 - on phosphorus removal, 308, 743, 745
 - measurement of, 84
 - national standards for, 123
- Phoredox, 732
- Phosphorus:
- forms of, 86-87
 - importance of, 86
 - requirements for bacterial growth, 537
 - typical values: in septage, 110
 - in wastewater, 109
- Phosphorus removal by chemical addition,
- 306-310, 741-749
 - comparison of processes, 748-750
 - estimation of sludge volumes, 746
 - factors affecting choice of chemicals,
 - table of, 741
 - operations and processes, 306, 742
 - precipitation reactions: with alum, 308, 742
 - with iron, 308, 742
 - with lime, 308, 742
 - to primary sedimentation facilities, 307, 742-743
 - to secondary sedimentation tanks, 743-745
 - to secondary treatment, 743-744
 - strategies for removal: coprecipitation, 307, 745
 - post-precipitation, 307
 - pre-precipitation, 307, 745
 - by tertiary lime coagulation, 748
 - typical chemical dosages for, 745
 - typical flow diagrams, 307, 749
 - using lime, 745-748
 - addition to primary sedimentation tanks, 745-746
 - following secondary treatment, 748
 - using metal salts and polymers, 742-745
- Phosphorus removal by natural systems, 941
- Phosphorus and nitrogen, combined removal
- of, 731-735
 - A²/O process, 731
 - Bardenpho process (five-stage), 732
 - comparison of processes, table of, 735
 - UTC process, 734
 - VIP process, 735
- Phosphorus removal by biological methods,
- 433-434, 726-731
 - A/O process (mainstream phosphorus removal), 729
 - comparison of biological phosphorus removal processes, 730, 732
 - PhoStrip (sidestream phosphorus removal), 730
 - process description, 433
 - role of VFAs, 433
 - sequencing batch reactor, 730
- Phosphorus removal from wastewater:
- by biological methods, 433-434
 - by chemical methods, 306-310
 - combined with nitrogen removal, 731-735 (*See also individual listings*)
- Photosynthesis, 1204-1205
- by algae, 1204
 - definition of, 438
 - effects on oxygen resources: in ponds, 1213
 - in rivers, 1208
- Phototrophic organisms, 361
- Physical characteristics of wastewater, 50-64 (*See also* Wastewater characteristics, physical)
- Physical constants (*see inside of back cover*)
- Physical properties of water, 1251-1254
- in SI units, 1253
 - in U.S. customary units, 1252
- Physical unit operations:
- accelerated gravity separation, 240-242
 - air stripping: for ammonia removal, 735-738
 - for VOC removal, 751
 - definition of, 193
 - dewatering, 855-877
 - filtration, granular-medium, 666-689
 - flotation, 242-248
 - flow equalization, 203-212
 - flow metering, 195-200
 - heat drying, 877-881
 - microstraining, 689
 - mixing, 212-220
 - reverse osmosis, 757
 - screening, 200-203
 - sedimentation, 220-240
 - sludge pumping, 779-795

- Physical unit operations (*Cont.*):
 thickening, 801-810
 ultrafiltration, 757
 vacuum filtration, 857-861
 (*See also individual listings*)
 Pilot plant studies, 139, 271
 Pipeline transport of sludge, 917
 Piping, sludge, 795
 Plain sedimentation, 220-226
 (*See also Sedimentation*)
 Planning, facilities, 137
 Plans and specifications, 140
 Plant harvesting in aquatic treatment systems, 1012
 Plant layout:
 definition of, 184
 examples of, 185, 187, 708
 Plants for natural treatment systems:
 constructed wetlands, 994-995
 floating aquatic plant systems, 1005-1006
 overland flow, 992
 slow rate, 948-949
 Plants (microorganisms), 90, 92
 Plate and tube settlers:
 analysis of, 229
 applications: in sedimentation tanks, 586
 in septic tanks, 1078
 description of, 228
 Plug-flow reactor (PFR):
 description of, 172
 kinetic analysis of with first-order reaction conversion, 1269-1270
 nonideal, analysis of, 1271-1273
 process analysis with recycle, 393-395
 with recycle, 173, 393
 Plume, outfall, 1227
 dilution at centerline, 1228, 1232
 width, 1232
 Plunger pumps for pumping sludge and scum, 779
 Pneumatic mixing, 219
 Pollutants:
 loading rates for land application of sludge, 908
 priority (*see* Priority pollutants)
 regulated for sludge disposal or reuse, 778
 in wastewater, 49, 109
 Polyelectrolytes (*see* Polymers)
 Polymers:
 applications: in effluent filtration, 687-688
 in phosphorus removal, 742
 in sludge dewatering, 865
 in sludge thickening, 810
 classification of, 312
 metal salt polymer formation, 313-314
 mode of action, 312-313
 Ponds, 641-655
 (*See also* Stabilization ponds)
 Population equivalent loading factors:
 for septage, 1092
 for wastewater, 165, 166
 Post aeration, 508-512
 cascade aeration, 509-511
 diffused-air aeration, 512
 mechanical aeration, 511
 Potable water reuse, 1173-1174
 indirect reuse, 1173
 reuse criteria, 1173
 POTW (*see* Publicly owned treatment works)
 Powdered activated carbon (PAC), 316, 323
 Powdered activated carbon treatment (PACT), 753
 Power requirements (*see* Energy requirements)
 Praeration, 470-471
 aerated channels, 471
 typical design information, 471
 Preapplication treatment for natural systems:
 for constructed wetlands, 993
 for floating aquatic plant treatment systems, 1003
 for overland-flow, 983
 for rapid infiltration, 968
 for slow-rate systems, 951
 Prechlorination, 353, 495
 Precipitation:
 chemical (*see* Chemical precipitation)
 of phosphorus (*see* Phosphorus removal by chemical addition)
 sedimentation (*see* Sedimentation)
 Preengineered treatment plants, 1080-1088
 (*See also* Package treatment plants)
 Preliminary treatment operations:
 comminution, 454-456
 flocculation, 471
 flow equalization, 203-212, 468-470
 grit removal, 456-468
 praeration, 270
 screening, 200-203, 445-454
 Preparation of solids mass balances, 891-902
 Preservation of samples, 113
 Pressure filter, 680
 Pressure sewers, 1073-1075
 description of, 1073
 typical design data for, 1076
 Pressure-swing adsorption for oxygen generation, 574

- Presumptive test for coliforms, 95–96
- Primary sedimentation tanks, 472–485
 - basis of design, 473–476
 - circular, 481–484
 - design information, 475
 - detention time, 473
 - dimensions, 477
 - inlets and outlets, 477, 481
 - overflow rates, 474
 - purpose of, 472
 - rectangular, 476–481
 - removal efficiencies, 473
 - scour velocity, 475
 - scum removal, 479, 481
 - sludge collection in, 477, 481
 - sludge density, 485
 - sludge removal in, 477, 481
 - sludge volume estimation, 484
 - as storm water tanks, 473
 - surface loading rates, 474
 - temperature effects, 474
 - type, size, and shape of, 476–483
 - weir rates, 475
- Primary treatment, definition of, 2
- Priority pollutants:
 - definition of, 67
 - typical compounds, 68–69
- Privatization, 143
- Procaryotic cell, definition of, 90–91
- Processes to further reduce pathogens (PFRP), 904
- Processes to significantly reduce pathogens (PSRP), 904
- Progressive-cavity pump, 786
- Propeller mixer:
 - analysis of, 215–217
 - examples of, 214
- Proteins:
 - composition of, 65
 - occurrence of, 65
 - synthesis of, 65
- Protista definition of, 90
- Protozoa, 92, 94
 - classes of, 92
 - cryptosporidium*, 92, 94
 - description of, 92
 - giardia lamblia*, 92, 94
 - importance in activated sludge, 366
 - importance in biological treatment, 92
 - pathogenic types, 94
- PSRP (Processes to significantly reduce pathogens), 904
- Psychoda fly in trickling filters, 614
- Psychophilic bacteria, 366
- Public health issues:
 - in agricultural and landscape irrigation, 1155
 - in natural systems: bacteriological agents, 943
 - crop quality, 944
 - groundwater quality, 944
 - in wastewater reuse applications, 1143
- Public law 92–500, 4, 123
- Publicly owned treatment works (POTW), 124
- Pulsed-bed filter, 253, 677
- Pump-in test, shallow trench, 1049
- Pumping of sludge, 779–796
- Pumps, sludge and scum, 779–795
 - (See also Sludge and scum pumping)
- Pyrolysis for sludge processing, 883
- Quadrupole mass spectrometer, 61
- Quality of effluent:
 - from activated-sludge process, 548–549
 - from advanced waste treatment processes, 670
 - from aerated lagoons, 645
 - from natural treatment systems, table of, 932
 - from rotating biological contactors, 634, 707
 - from stabilization ponds, 645
 - from trickling filters using plastic media, 640
- Quantity of wastewater (see Wastewater sources and flowrates)
- Racks (see Bar racks)
- Radiation for disinfection, 351–352, 508
- Rail transport of sludge, 918
- Rapid-infiltration systems, 967–982
 - distribution methods, 968
 - effluent recovery system, 979
 - hydraulic-loading rate and operating cycle, 969
 - land area requirements, 973–975
 - layout of infiltration area, 977
 - preapplication treatment, 968
 - site evaluation and selection, 967
- Rapid sand filtration (see Filtration, granular medium)
- Reactor:
 - definition of, 170
 - process selection: flow regimes and reactor combinations, 173
 - mass balance analysis, 174–176

- Reactor, process selection (*Cont.*):
 performance comparisons, 176
 reaction rate expressions, 174
 types of, 171–173
 description, 171
 table of, 171
- Reaeration:
 coefficients of, 1203
 computation, 1203
 surface, 1202
- Recharge, groundwater, 1166–1172
 (*See also* Groundwater recharge with reclaimed wastewater)
- Recirculating granular medium filter:
 description of, 1037
 design criteria, 1066
- Recycling, wastewater, 1140
 (*See also* Wastewater reclamation and reuse)
- Reduction of flow, devices, and appliances, 42
- Regulations:
 for air pollution control, 891
 for the reuse and disposal of sludge, 777–779
 trends in, 1202, 1203
- Reliability concept in wastewater treatment and plant design, 178–181
- Renovation, wastewater (*see* Wastewater reclamation and reuse)
- Reoxygenation in rivers, 1202
- Residential water use, 17–19
- Residual chlorine, 500
- Residual constituents in wastewater, table of, 665
- Residue on evaporation, 50
- Respiration, 1204
- Return activated sludge:
 flowrates: methods of determining, 546–551
 typical, by process, 550
 importance in process control, 545
- Reuse of reclaimed wastewater, 1142–1174
 (*See also* Wastewater reuse applications)
- Reverse osmosis:
 for removal of total dissolved solids (TDS), 757–759
 for wastewater reclamation, 1181–1184
- Reynolds number:
 in mixing, 216
 in sedimentation, 222–223
 in sludge headloss computations, 791
 values in Moody diagram, 1282
- Rheology, in sludge headloss computations, 791–795
- Ribonucleic acid (RNA), 365, 375
- Rising sludge, 555
- River outfalls, 1223–1224
- RNA (*see* Ribonucleic acid)
- Rock filter for solids separation, 651
- Rotary drum screen, 202, 452
- Rotary drum thickener, 807
- Rotary-lobe pumps for sludge pumping, 787
- Rotating biological contactors, 418–420, 628–636
 design of physical facilities, 632–633
 drive systems, 633
 enclosures, 633
 media, 632
 settling tanks, 633
 shafts, 632
 tankage, 633
 factors affecting performance, 171
 operating problems, 633
 process description, 419
 process design, 628–632, 635, 726
 effect of temperature, 635
 effluent characteristics, 630
 loading criteria, 630
 process design curves, 634, 726
 sizing, 635
 staging, 628
 process design example, 635–636
 process performance analysis, 419
 typical design information, 632
- Rotifers:
 description of, 366
 function in aerobic biological processes, 366
- Roughing filter-activated sludge process, 640
- Roughing filters:
 analysis of, 418
 description of, 418
 microbiology of, 418
 (*See also* Trickling filter)
- Safety:
 chlorine handling, 495–496
 digester gas, 826
 explosion hazards, 826
- Salinity:
 definition of, 1145
 effects, of, 1145
- Sample analysis, specialized tests, 109
- Sample preservation, 113
- Sampling, 111–113
 equipment, 112
 intervals, 112
 locations, 111
 sample preservation, 113

- Sand drying beds for sludge, 870–876
 area requirements, typical, 873
 construction of, 871–872
 depth of wet sludge applied, 871
 loadings, 873
 underdrains, 872
- Sand filtration, intermittent, 1035–1036
 (See also Intermittent sand filter)
- SAR (see Sodium adsorption ratio)
- SBR (see Sequencing batch reactor)
- Scale-up factors for settling tanks, 228
- Scale-up for mixers, 216
- Scaling, 1161
- Scentometer for odor measurement,
 61–62
- Scour velocity:
 computation, 476
 in treatment tanks, 475
- Screening, 200–203
 analysis of: bar racks, 203
 fine screens, 203
 description of: bar racks, 200
 screens, 200
 typical screening devices, 202
- Screenings:
 characteristics, 447
 disposal of, 454
 grinding of, 454
 quantities, 453
- Screens:
 coarse, 452
 description of, 201
 fine, 203
 headloss through: bar racks, 203
 fine screens, 203
 microscreens, 689–690
 racks, 447–451
 (See also Bar racks)
 types of, 202
- Scum:
 control of, in digesters, 823, 824
 pumping, 779
 sources of, 768
- Scum pumps (see Sludge and scum
 pumping)
- Scum removal:
 in primary sedimentation tanks, 479, 481
 in secondary settling tanks, 591
- Sediment oxygen demand (SOD), 1203
- Sedimentation, 220–240
 compression settling (type 4), analysis
 of, 240
 (See also Sludge thickening)
 description of, 220–221
 detention time, 224
 discrete particle settling (type 1), analysis
 of, 222–226
 drag coefficient, 222
 drag force, 222
 laminar flow, 223
 Newton's law, 222
 overflow rate, 223
 removal efficiency, 224–225
 Stokes' law, 222
 terminal velocity, 223–224
- flocculant settling (type 2), analysis
 of, 226–229
 analysis of settling column data, 227–228
 description of, 226
 removal efficiency, 227–228
 scale up from settling tests, 228
- hindered settling (type 3), analysis
 of, 229–240
 applications of solids flux analysis,
 238–240
 area requirement based on batch
 test results, 230–233
 area requirement based on solids
 flux analysis, 233–240
 description of, 229–230
 (See also Activated sludge)
- plate and tube settlers, analysis of, 228
 definition sketch, 228
 description of, 228
- Sedimentation tanks:
 for activated-sludge process, 581–584
 (See also Activated sludge)
 for aerated lagoons, 611–614
 for primary treatment, 472–485
 (See also Primary sedimentation tanks)
 for trickling-filter process, 624
 typical design information for secondary
 clarifiers, table of, 588
- Selective withdrawal from lakes, 1212
- Selector for control of filamentous organisms:
 contact time, 538
 food-to-microorganism ratio, 538
- Separate stage nitrification, 542
- Septage:
 characteristics of, 110, 1090–1091
 definition of, 108
 disposal of: co-disposal with solid
 waste, 1096
 land application, 1093
 quantities of, 1092
 receiving stations, 1093
 treatment of: by biological treatment, 1096
 by chemical oxidation, 1098
 by composting, 1098
 by lime stabilization, 1098

- Septage, treatment of (*Cont.*):
 typical flow diagrams for, 1097
 with wastewater, 1093
- Septic tank:
 appurtenances, 1028
 description of, 1025–1028
 design criteria, 1063
 dosing pumps for, 1034
 dosing siphons for, 1034
 effluent filter vault, 1026–1027
 materials of construction, 1025
 sludge removal, 1028
- Septic tank disposal systems (*see* Onsite systems)
- Septic tank effluent pumping (STEP) system, 1073
- Sequencing batch reactor (SBR):
 operating sequence for, 401
 operating strategies for carbon, nitrogen, and phosphorus removal, 731
 for phosphorus removal, 730
 process description, 400, 541
 process design example, 601–604
- Settleable solids:
 definition of, 50
 determination of, 52
 typical values in wastewater, 109
- Settling (*see* Sedimentation)
- Settling column analysis, 227
- Settling curves, 227
- Settling tanks (*see* Sedimentation tanks)
- Settling tests for flocculant suspensions, 223
- Settling velocity, 223, 1205
- Sewage (*see* Wastewater)
- Sewers:
 combined, 1106
 conventional gravity flow, 1072
 outlets for, 1111
 pressure, 1073–1075
 regulators for, 1106–1109
 separation, 1127
 small-diameter variable slope, 1072
 vacuum sewers, 1074–1076
- Shear velocity, 1214
- Shrimp, used in bioassay, 103
- Single stage nitrification, 542
- Skatole, 57
- Slow-rate treatment systems, 945–967
 crop selection, 948
 design hydraulic-loading rate, 958
 distribution methods, 952, 954–955
 land area requirements, 963
 preapplication treatment, 951
 site evaluation and selection, 945
 storage requirements, 964
 surface runoff control, 966
 underdrainage, 965
 (*See also* Natural treatment systems)
- Sludge:
 activated (*see* Activated sludge)
 age (*see* Mean cell residence time)
 application on land, 903–914
 (*See also* Land application of sludge)
 regulated pollutants in, 778
 sources of, table of, 768
 specific resistance of, 851
- Sludge and scum pumping, 779–795
 application of pumps, table of, 788–789
 headloss determination, 787
 application of rheology for long pipelines, 791–795
 simplified determinations, 789
 sludge piping, 795
 types of pumps: centrifugal, 786
 diaphragm, 787
 high-pressure piston, 787
 plunger, 779
 progressive cavity, 786
 rotary-lobe, 787
 torque flow, 785
- Sludge, beneficial use of:
 application on land, 903–914
 (*See also* Land application of sludge)
 chemical fixation, 915
 distribution and marketing, 915
- Sludge beds (*see* Sludge drying beds)
- Sludge blending, 798
- Sludge bulking, 553–555
 (*See also* Bulking sludge)
- Sludge centrifuges:
 for dewatering, 860–864
 for thickening, 805–806, 809 810
- Sludge characteristics, 766–777
 chemical composition and properties, table of, 771
 comparison of nutrient levels, 772
 description of, 769–770
 heating values, table of, 883
 metal content, table of, 772
 physical characteristics, table of, 773
 quantities of, 772–777
 specific gravity, 773, 775–776
 typical concentrations from operations and processes, table of, 774
 volume-weight relationship, 775–776
- Sludge composting, 842–850
 (*See also* Composting, sludge)
- Sludge concentration, 801–810
 (*See also* Sludge thickening)

- Sludge conditioning, 850–54
 by acidification, 854
 by chemical addition, 850–852, 854
 chemicals used, 850
 dosage, typical, 851–852
 factors affecting, 850
 polymer addition, table of, 852
 mixing, 852
 by elutriation, 854
 by freeze-thaw, 854
 by heat treatment, 852–853
 by irradiation, 854
 by solvent extraction, 854
- Sludge conveyance methods, 915–918
 by barge, 917
 environmental considerations, 918
 by pipeline, 917
 by rail, 918
 by truck, 917
- Sludge degritting:
 description of, 796–797
 grit removal efficiencies, 798
- Sludge deposits, oxygen consumed by, 1203
- Sludge dewatering, 855–877
 by belt filter press, 864–868
 by centrifugation, 860–864
 comparison of methods, 858–859
 on drying beds, 870–876
 by filter press, 868–870
 in lagoons, 876–877
 typical BOD and SS concentrations
 in recycle flows, table of, 893
 typical solids capture values, table of, 892
 typical solids concentration values,
 table of, 893
 by vacuum filtration, 857–860
 (*See also individual listings*)
- Sludge digestion:
 aerobic, 401–403, 835–842
 (*See also Aerobic sludge digestion*)
 anaerobic, 420–427, 813–834
 (*See also Anaerobic sludge digestion*)
- Sludge disinfection, 854–855
 by chemical fixation, 915
 by composting, 842–850
 by lime stabilization, 811–813
 by long-term storage, 855
 by pasteurization, 855
 processes to further reduce pathogens
 (PFRP), 904
 processes to significantly reduce pathogens,
 (PSRP), 904
 (*See also individual listings*)
- Sludge disposal and reuse:
 current status, 8
 new directions and concerns, 9
- Sludge disposal methods:
 lagooning, 920
 land application, 903–914
 landfilling, 919–920
 for landfill cover and land reclamation,
 915
 number by facility, 9
- Sludge drying, 877–881
 air-pollution and odor control, 880
 flash dryers, 878
 multiple-effect evaporators, 878
 multiple hearth dryer, 878
 rotary dryers, 878
 spray dryers, 878
 theory of, 877
- Sludge drying beds, 870–876
 area requirements for: conventional
 sand, 873
 paved, 873–874
 classification of: artificial media, 874–875
 paved, 873–874
 sand, 870–873
 vacuum-assisted, 875–876
 (*See also individual listings*)
- Sludge elutriation, 854
- Sludge gas, 823–826
 (*See also Digester gas*)
- Sludge grinding:
 description of, 796
 operations or processes requiring, 797
- Sludge headloss determinations, 787–795
 multiplication factors, 790
 simplified methods, 789
 using rheology, 791
- Sludge incineration:
 ash disposal, 886
 fluidized-bed, 886–888
 multiple hearth, 885–886
 (*See also Combustion; Thermal reduction
 of sludge*)
- Sludge lagoons, 876–877, 920
- Sludge piping, 795
- Sludge processing and disposal methods:
 flow diagrams for, 780–783
 table of, 130, 767
 typical sludge concentrations from, 774
- Sludge pumps, 779–789
 (*See also Sludge and scum pumping*)
- Sludge regulations for reuse and disposal,
 777–779, 904–905
- Sludge reuse, 903, 915
- Sludge sources, 766, 768

Sludge stabilization:

- by aerobic digestion, 835-842
 - by anaerobic digestion, 813-834
 - by chlorine oxidation, 811
 - by composting, 842-850
 - by heat treatment, 813
 - by lime addition, 811-813
 - purpose of, 810
- (See also individual listings)

Sludge storage:

- after digestion, 855, 918
- before treatment, 799
- computation of volume requirements, 799-801
- purpose of, 799
- long-term, for disinfection, 855

Sludge storage basins, 918

(See also Sludge lagoons)

Sludge storage pads, 918

Sludge thickening:

- application, 801-802
- chemical aids, 809-810
- description of equipment: 802-807
 - centrifuge, 805-806
 - flotation, 804-805
 - gravity, 802-804
 - gravity belt, 806-807
 - rotary drum, 807
- (See also individual listings)
- design of thickeners, 808-810
 - centrifuge, 808
 - flotation, 809
 - gravity, 808
- performance, 808, 892-893
- polymer addition, 810
- sludge concentrations for gravity thickeners, 808
- solids loadings: dissolved-air flotation, 809
- gravity, 808
- typical BOD and SS concentrations in recycle flows, table of, 893
- typical solids capture values, table of, 892
- typical solids concentration values, table of, 893

Sludge volume index (SVI), 587

Sludge volume ratio (SVR), 809

Sludge volume-weight relationships, 775-776

Sludge wasting, 551-553

Small wastewater management systems:

- centralized without septic tanks, 1077
- systems with individual septic tanks, 1077

SOD (see Sediment oxygen demand)

Sodium adsorption ratio (SAR):

- adjusted value, computation of, 1115, 1153

- adjusted value, definition of, 1148, 1150
- definition of, 1148

Sodium hypochlorite, 487

Soil:

- classification (U.S. Dept. of Agriculture), 1045
- textural classes, 1044

Soil adsorption system, 1029

(See also Disposal fields for septic tank effluent)

Soil bed for odor control, 518

Solid bowl centrifuge, 805, 860-862

Solids:

- content of sludge, 773-774
- deposition, 1205
- total per capita per day, 166
- type of: dissolved, 51, 55
- suspended, 52, 55
- total, 50, 55

typical values: in septage, 110

in wastewater, 109

Solids flux analysis of settling data:

- application, 238-240, 596-599
- description of, 234
- theory of, 234-237

Solids loadings:

- definition of, 234
- loading criteria (see Loading criteria)

Solids mass balance, 891

definition, 891

preparation, 891-892

basis for, 891

example of, 894-902

performance data, 892-893

Solids retention time (see Mean cell residence time)

Solubility of gases in water, 1255-1266

SOTE (see Standard oxygen transfer efficiency)

SOTR (see Standardized oxygen transfer rate)

Specific growth rate, 370

Specific heat of sludge, 882

Specific ion toxicity, 1148

Specific oxygen uptake rate (SOUR), 553

Specific utilization rate, 388, 534

Specific weight of water:

definition of, 1251

table of values, 1252-1253

Sphaerotilus, 406

SS (see Suspended solids)

Stabilization of sludge, 810-850

(See also Sludge stabilization)

Stabilization ponds, 434-439, 641-655

aerobic, 434-436, 642-648

process analysis, 436

- process description, 434
- process microbiology, 435
- aerobic-anaerobic (facultative), 436-438, 648-650
 - process analysis, 438
 - process description, 436
 - process microbiology, 437
- anaerobic, 650
- application, 641-643
- classification, 642
- design of physical facilities, 651-655
 - bottom construction, 655
 - dike construction, 653
 - freeboard, 654
 - inlet and outlet structures, 651
 - liquid depth, 654
 - sealers and liners, 655
 - slope protection, 654
 - surface runoff control, 655
 - transfer lines, 652
- facultative, 648-650
- pond systems, 650
- recirculation, 651
- rock filter, 653
- solids separation, 651, 652
- Standard oxygen transfer efficiency (SOTE), 561-562
- Standardized oxygen transfer rate (SOTR), 287
- Standards:
 - effluent, 1197-1198
 - receiving-water, 1197
 - secondary treatment, table of, 123
- Static screen, inclined, 202, 452
- Static mixers, 219
- Static tube aerator, 561
- STEP (*see* Septic tank effluent pumping system)
- Step-feed aeration activated sludge, 540, 543 (*See also* Activated sludge)
- Stem potential, 312
- Stokes' law for gravity settling, 222
- Storage of sludge (*see* Sludge storage)
- Storm water, definition of, 16
- Storm water management model (SWMM), 1116-1117
- Storm water overflows (*see* Combined sewer overflows)
- Stratification:
 - in digesters, 820
 - in lakes, 1212-1213
 - in oceans, 1227, 1229
 - due to salinity in estuaries, 1213
- Stream standards (*see* Water pollution control)
- Streeter-Phelps oxygen sag analysis, 1216-1220
- Streptococci, fecal, 93-94
- Stripping, air:
 - for ammonia removal, 735-738
 - for VOC removal, 288
- Submerged wastewater field, example computation of, 1231
- Substrate:
 - definition of, 360
 - effluent concentration, 376
 - limited growth, 370
 - mass balance, 374-376
 - utilization, 371
- Sulfur:
 - bacterial conversion products, 87
 - importance of, 87
 - sources of, 48
- Sulfur dioxide for dechlorination, 506
- Surface aerators:
 - with horizontal axis, 571
 - oxygen transfer rate, 285-287
 - with vertical axis, 569-576
 - performance, 571-572
 - testing of, 283
 - (*See also* Aerators)
- Surface application methods for wastewater:
 - for overland-flow systems: fan sprays, 985
 - gated pipe, 984
 - sprinklers, 985
 - for rapid-infiltration systems: spreading basins, 968
 - sprinkling, 968
 - for slow-rate systems: conditions recommended
 - for use of, table of, 954-955
 - drip, 953, 955
 - surface distribution, 933, 953
 - sprinkler, 933, 953
 - typical design information, 957
- Surface charge:
 - development of, 310-311
 - importance of, 311
- Surface reaeration:
 - definition of, 1202
 - rate of, 1202
- Surface spreading for groundwater recharge, 1166
- Surfactants, 66-67
- Suspended growth treatment processes:
 - aerobic processes: activated sludge, 379-398
 - aerated lagoons, 398-400
 - aerobic digestion, 401-403
 - definition of, 377-78
 - sequencing batch reactor, 400-401

- Suspended growth treatment processes (*Cont.*):
 anaerobic processes: anaerobic contact, 427
 anaerobic digestion, 420–427
 definition of, 377–378
 denitrification, 432–433, 720–723
 upflow anaerobic sludge blanket, 427
 anoxic processes: definition of, 381
 denitrification, 377
 facultative: definition of, 377–378
 stabilization ponds, 436–438
 (*See also* Attached growth treatment processes; *individual listings*)
- Suspended solids (SS):
 definition of, 50
 determination of, 50, 53
 fixed, 52
 importance of, 49
 typical values: in septage, 110
 in wastewater, 109
 volatile, 52
- Suspended solids, removal of:
 by precipitation (*see* Chemical precipitation)
 by flotation (*see* Flotation)
 by sedimentation (*see* Sedimentation)
- Suspended solids, removal of residual
 by granular medium filtration
 (*see* Filtration, granular medium)
- Suspended solids, removal of residual
 by microscreening, 689
 description of, 689
 design information, table of, 690
 functional design, 690
- Sustained mass loadings:
 definition of, 159–160
 curves for BOD, SS, nitrogen, and phosphorus, 161
- SVI (*see* Sludge volume index)
- SVR (*see* Sludge volume ratio)
- SWMM (*see* Storm water management model)
- Symbiotic relationship in stabilization ponds, 435–436
- Synthetic detergents, 67
- Syntrophic relationship in anaerobic digestion, 424
- Tapered aeration activated sludge, 540
 (*See also* Activated sludge)
- TDS (*see* Total dissolved solids)
- Temperature:
 log-mean, 623
 of wastewater, 62
- Temperature coefficients:
 for aeration, 286, 572
 for biochemical oxygen demand, 76
 for conventional biological treatment processes, 373
 for denitrification, 712
 for nitrification, 700
 for reaeration, 1203
 van't Hoff-Arrhenius relationship, 75
- Temperature effects:
 on aerated lagoons, 606
 on aeration, 286
 on aerator performance, 286–287
 on aerobic digestion, 836, 842
 on air flow in pipes, 567
 on air flow in trickling filters, 622
 on ammonia stripping, 738
 on anaerobic digestion, 818
 on aquatic life, 62–63
 on bacterial die-off in sea water, 1206
 on bacterial kill, 330
 on bacterial species, optimal ranges, 366
 on biochemical oxygen demand, 75
 on biological growth, 372
 on biological reaction rates, 372–373
 on biological treatment processes, 373
 on bromine chloride reactions in water, 347
 on chlorination, 332–333, 338
 on chlorine reactions in water, 332–333
 on composting, 843
 on denitrification process, 712
 on digester heating, 830
 on disinfection, 330
 on dissolved air flotation, 246
 on dissolved oxygen concentration in water, 1258–1259
 on molecular diffusion coefficient for oxygen, 1203
 on nitrification process, 700
 on physical properties of water: in SI units, 1252
 in U.S. customary units, 1253
 on post-lime stabilization, 812
 on reaeration, 1202–1203
 on receiving waters, 1226–1227
 on sediment oxygen demand, 1203
 on sedimentation rates, 222
 on sedimentation tank performance, 226
 on sludge storage times, 855
 on solubility of gases in water, 1255–1256
 on thermal stratification: in lakes, 1212
 in oceans, 1227, 1229
 on thermophilic digestion, 834
 on trickling filter process: for nitrification, 710
 for organic carbon removal, 413
 on unit operations and processes, 168
 on viscosity of water, 1251–1253
 in SI units, 1252
 in U.S. customary units, 1253
 on VOC mass transfer rates, 290
 on water use, 23

- Tertiary maturation stabilization ponds, 438
(*See also* Stabilization ponds)
- Tertiary treatment (*see* Advanced wastewater treatment)
- Theoretical oxygen demand (THOD), 82–83
- Thermal incineration, 521
- Thermal reduction of sludge, 881–891
air pollution control, 890–891
process fundamentals, 881–885
complete combustion, 881–883
pyrolysis, 883–884
starved air combustion, 884
wet combustion, 884–885
thermal reduction processes, application of, 885–890
co-incineration, 888–889
fluidized bed incineration, 886–888
multiple hearth incineration, 885–886
wet-air oxidation, 889
wet oxidation in a vertical deep-well reactor, 889–890
- Thermal stratification in lakes, 1212
- Thermocline, definition of, 1212
- Thermophilic digestion:
aerobic, 841–842
anaerobic, 834
- Thermophilic organisms, 366
- Thickeners:
centrifugal, 805–806, 808
flotation, 804–805, 809
gravity, 806–807, 808
gravity belt, 806–807
rotary drum, 807
- Thickening, 801–810
(*See also* Sludge thickening)
- THOD (*see* Theoretical oxygen demand)
- Thomas method for analysis of BOD data, 77
- Threshold odor:
definition of, 59
determination of, 59–62
(*See also* Odor)
- Threshold odor number (TON), 60
- TKN (*see* Total Kjeldahl nitrogen)
- TL_m (*see* LC_{50})
- TOC (*see* Total organic carbon)
- TON (*see* Threshold odor number)
- Torque flow pumps for sludge pumping, 785
- Total dissolved solids (TDS):
definition of, 50
relationship to electrical conductivity, 1145
typical values: in septage, 110
in wastewater, 109
- Total Kjeldahl nitrogen (TKN):
definition of, 85
typical values: in septage, 110
in wastewater, 109
- Total organic carbon (TOC):
BOD₅/TOC ratio, 83
definition of, 82
typical values in wastewater, 109
- Total solids:
components of, 50–55
definition of, 52
typical values: in septage, 110
in wastewater, 109
- Toxic compounds and refractory organics,
removal of, 749–755
carbon adsorption, 751
chemical oxidation, 755
powdered activated carbon treatment (PACT), 753
treatment methods, table of, 751
- Toxicity:
acute, 104
of chlorine residuals, 343
chronic, 104
in digesters, 425
of heavy metals, 88
test for, 102–104
- Toxicity tests, 101–108
application of results, 105
evaluation of results, 104
testing, 102–104
toxicity units, 104
- Toxicity units:
acute (TU_a), 104
chronic (TU_c), 104
- Trace elements:
recommended maximum concentrations in irrigation waters, table of, 1149
required for biological growth, 88
toxicity to plants, 88
in wastewater, 88
- Tracers, for measuring eddy diffusion, 1215
- Transport processes, 1199–1201
advection, 1199
diffusion, 1200
- Transportation of sludge, 915–918
by barge, 917
environmental considerations, 918
by pipeline, 917
by rail, 917
by truck, 917
- Traveling-bridge filter, 253, 677
- Treatment kinetics (*see* Kinetics of biological growth)
- Treatment plant design:
critical design factors, table of, 178
sizing criteria, table of, 178
- Treatment plant loading data, analysis of, 156–162
average mass loadings, 159

- Treatment plant loading data, analysis
of (*Cont.*):
 flow-weighted average, 157
 simple average, 157
- Treatment plants, package, 1080–1088
(*See also* Package treatment plants)
- Treatment-process flow diagrams (*see*
 Flow diagrams for treatment processes)
- Triangle olfactometer, 60–61
(*See also* Odor)
- Trickling filter, 403–418, 614–628
 analysis of: formulations for plastic
 media, 412–414
 mass balance approach, 407–409
 NRC equations for rock and slag,
 409–411
 BOD removal for plastic media, 640
 classification of: 614–616
 high-rate, 616
 intermediate-rate, 616
 low-rate, 614
 roughing, 616
 super high-rate, 616
 two-stage, 616
 design, 616–628
 airflow, 622–624
 distributors, 619
 dosing rate, 616–619
 draft, 623
 media selection, 620–622
 settling tanks, 624
 underdrains, 622
 factors affecting performance, 171
 mass transfer limitations: definition of, 417
 air flow in filters, 622–624
 draft in filters, 623
 process description, 404
 process design, 624–628
 BOD removal, 624
 treatability constants, 625
 process design example, 625–628
 process microbiology, 404
 recirculation, 410, 415, 617
 solids separation facilities, 417, 624
 typical design information, 615
 typical flow diagrams, 410, 617
- Trickling filter-activated sludge process, 641
- Trickling filter, roughing:
 process analysis, 418
 process description, 418, 616
 process microbiology, 418
- Trickling filter–solids contact process, 638–640
 BOD removal, 640
 typical design information, 639
- Truck transport of sludge, 917
- Tube and plate settlers:
 analysis of, 229
 applications: in sedimentation tanks, 586
 in septic tanks, 1028
 description of, 228
- Turbidity:
 effect on disinfection, 341–342
 in wastewater, 64
- Turbine aerator, 278–279
- Turbine mixer, 215–217
 analysis of, 215–217
 definition sketch of mixer in baffled
 tank, 217
 examples of, 214
- Two-film theory of oxygen transfer, 277,
 280–281
(*See also* Gas transfer)
- Two-stage anaerobic digestion, 816
(*See also* Anaerobic sludge digestion)
- Two-stage trickling filters, 409–412, 616–617
- UASB (*see* Upflow anaerobic sludge
 blanket process)
- Ultimate BOD, 73
- Ultimate disposal:
 of screenings, 454
 of septage, 1092–1098
 of sludge, 903, 915, 919–920
- Ultrafiltration:
 description of, 757
 application in wastewater reclamation, 1184
- Ultraviolet (UV) light, disinfection with,
 351–352, 508
(*See also* Disinfection with ultraviolet light)
- Underdrains:
 for granular-medium filters, 683
 for sludge drying beds, 871–872
 for trickling filters, 405, 622–623
- Underflow:
 in settling tanks, 231, 234–237
 in thickeners, 802–804
- Unit loading factors:
 for septage, 1092
 for wastewater, 165–166
- Unit operations:
 definition of, 2
 degree of treatment achieved by, 170
(*See also* Physical unit operations)
- Unit processes:
 definition of, 2
 degree of treatment achieved by, 170
(*See also* Biological unit processes;
 Chemical unit processes)

- Unit waste-loading factors, 165–166
- Units of expression for analytical measurements, 51
- Upflow anaerobic sludge blanket (UASB) process, 427
- Upflow filter, granular medium, 252–253, 255
- Urea, 65
- U.S. customary units, conversion factors to metric (SI) units, 1241–1243
- UV, disinfection with, 351–352, 508
- UTC process, 734
- U-tube:
 - aerator, 557, 559
 - contactor for high purity oxygen, 577
 - deep shaft activated sludge process, 546
- Vacuum-assisted sludge drying beds, 875–876
 - description of, 875
 - sectional view of, 876
- Vacuum filtration, 857–861
 - cake solids, 861
 - principles of operation, 857
 - system operation and performance, 857–860
 - typical diagram for, 860
 - typical performance data, 861
- Vacuum flotation, 243
- Vacuum sewers, 1074–1076
 - description of, 1075
 - typical design data for, 1076
- van der Waals forces, 311
- van't Hoff-Arrhenius temperature relationship, 75
- Vapor phase adsorption, 520
- Variations in wastewater flowrates, 33–35
(See also Wastewater sources and flowrates)
- Vector control:
 - in water hyacinth treatment systems, 1011
 - in wetlands, 1002
- Vegetation for natural treatment systems:
 - for constructed wetlands, 943, 994–995
 - for floating aquatic plant systems, 937, 1005–1006
 - need for, 931
 - for overland flow systems, 992
 - for rapid infiltration, 968
 - for slow rate systems, 948–949
- Velocity gradient (G):
 - definition of, 213–214
 - equation for, 213
 - typical values: for flocculation, 215
 - for initial mixing, 215
- Ventilation in trickling filters, 417, 622–624
- Vertical mixing in ocean outfalls, 1228–1230
- VFAs (see Volatile fatty acids)
- VIP process, 735
- Viruses:
 - classification of, 92
 - description of, 92
 - importance of, 92, 94
 - pathogenic types, 94
- Viruses, removal of:
 - in advanced wastewater treatment, 1178–1179
 - by chlorination, 343
 - in groundwater recharge, 1171
- Viscosity of water:
 - in SI units, 1253
 - in U.S. customary units, 1252
- Volatile fatty acids (VFAs):
 - role in anaerobic digestion, 425
 - role in phosphorus removal, 433
- Volatile organic compounds (VOCs):
 - control of, 518–524
 - control strategies for, 518
 - off gas treatment, 519–524
 - stacks for atmospheric release, 524
 - definition of, 67
 - emission of, 287
 - gas stripping, 288
 - mass transfer from aeration processes, 290, 292–293
 - mass transfer rates, 288–290
 - physical properties of, 291
 - sources and methods of release, 289
 - strategies for control of, table of, 519
 - treatment of off gas containing VOCs, 519–524
 - volatilization of, 288
- Volatile solids:
 - definition of, 52
 - total (TVS), 52
 - suspended (VSS), 52
 - destruction in digesters: aerobic, 837–839
 - anaerobic, 816
 - loading factors for anaerobic digesters, 820, 823
 - typical values: in septage, 110
 - in wastewater, 109
- Volatile toxic organic compounds (VTOCs), emission from treatment facilities, 4
- Volatilization:
 - definition of, 288
 - rate of, 1207
 - vaporization constant, 1207
- Volume-weight relationships for sludge, 775–776
- Volume of wastewater (see Wastewater sources and flowrates)
- Vortex, free, 241–242

- Vortex separator:
 for combined sewer overflows, 1130
 for wastewater, 240-242, 464-465
- Vortexing in mixers, 217
- VSS (*see* Volatile solids, suspended)
- Waffle-bottom anaerobic digester, 823-824
- Waste activated sludge (WAS), 551-553
- Wastewater:
 components of total solids, 164
 composition of, 108-111
 condition of, 64
 flowrates, 15-43
 (*See also* Wastewater flowrates)
 mineral increase due to usage, 111
 strength of, 109
 threshold concentrations of pollutants, 163
 variation: in composition, 109
 in concentration, 154-156
 in flowrates, 33-35
- Wastewater analyses:
 analytical methods, 49
 expression of analytical results, 51
 methods for analyses, 49
- Wastewater characteristics:
 biological, 90-108
 algae, 91
 bacteria, 91
 coliform organisms, 91, 95-96
 fecal coliform to fecal streptococci,
 ratio of, 100-101
 fungi, 91
 indicator organisms, 93, 95
 pathogenic organisms, 93
 protozoa, 92
 toxicity test, 101-108
 viruses, 92-93
 (*See also specific organisms*)
 chemical, 64-90
 agricultural chemicals, 70
 alkalinity, 85
 ammonia, 88
 biochemical oxygen demand, 71-82
 carbohydrates, 65
 chemical oxygen demand, 82
 chlorides, 84
 detergents, 67
 dissolved oxygen, 89
 fats, 66
 gases, 88-90
 grease, 66
 heavy metals, 88
 herbicides, 70
 hydrogen sulfide, 89
 inorganic matter, 85
 Kjeldahl nitrogen, 85
 methane, 89
 nitrogen, 85
 oils, 66
 organic matter, 65
 pesticides, 70
 pH, 84
 phosphorus, 86-87
 priority pollutants, 67-69
 proteins, 65
 sulfur, 87
 surfactants, 66
 theoretical oxygen demand, 82
 total organic carbon, 82
 toxic inorganic compounds, 67
 volatile organic compounds, 67
 (*See also individual listings*)
 physical, 50-64
 colloidal solids, 51
 color, 64
 dissolved solids, 51
 odors, 55-62
 settleable solids, 50, 53
 suspended solids, 50-51, 53
 temperature, 62-63
 total solids, 50
 turbidity, 64
 typical composition, 109
 volatile solids, 52
 (*See also individual listings*)
- Wastewater collection systems for small communities, 1072-1076
 conventional gravity, 1072
 pressure sewers, 1073
 small-diameter variable-slope, 1072
 vacuum sewers, 1075
- Wastewater disposal:
 new directions, 11, 1196
 by reuse, 1143
 of treated effluent: current status, 11
 in lakes and reservoirs, 1209-1213
 on land (*see* Natural treatment systems)
 in oceans, 1225-1236
 in rivers and estuaries, 1213-1225
- Wastewater flow metering (*see* Flow measurement)
- Wastewater flowrate reduction, 41-43
- Wastewater flowrates:
 analysis of, 35-41
 flowrates for design, 36
 statistical analysis, 37-41
 components of, 15
 estimating from water supply data, 16-25
 municipal water use, 16-22
 proportion reaching collection system, 25

- evaluation and selection of, 148-153
 - application of flowrate factors, 149
 - average flowrates, 148
 - minimum flowrate factors, 150
 - peak flowrate factors, 151
- reduction of, 41-43
- upstream control of peak flowrates, 153
- (*See also* Wastewater sources and flowrates)
- Wastewater management:
 - elements and engineering tasks, table of, 12
 - financing, 142-144
 - leasing, 143
 - long-term municipal debt, 142
 - non-debt, 142
 - privatization, 143
 - options for small wastewater systems, 1021-1024
 - for rural sewered areas, 1022
 - for rural unsewered areas, 1021
 - program implementation, 137-144
 - construction, 140
 - design, 138
 - facilities planning, 137
 - startup and operations, 141
 - value engineering, 140
- Wastewater metering, 195-200
- Wastewater reclamation and reuse, 10, 1137-1142, 1184-1189
 - current status, 10
 - definition of terms, 1139-1140
 - historical perspective, 1138
 - new directions and concerns, 10
 - planning considerations, 1184-1189
 - monetary analysis, 1186-1188
 - other planning factors, 1188
 - planning basis, 1185-1186
 - planning report, 1189
 - potential and status, 1140
- Wastewater reclamation technologies, 1174-1184
 - advanced reclamation process combinations, 1179-1184
 - suspended solids and turbidity removal, 1177-1179
 - treatment process reliability, 1174-1177
 - unit processes and operations, table of, 1175
- Wastewater reuse applications, 1142-1174
 - agriculture and landscape irrigation, 1144
 - categories of reuse, 1143
 - groundwater recharge, 1166
 - industrial water reuse, 1157
 - (*See also* individual listings)
- Wastewater sources and flowrates, 26-35
 - domestic flowrate data, 26
 - commercial facilities, 28
 - institutional facilities, 28
 - recreational facilities, 29
 - residential, 27
 - flowrate variations, 33-35
 - industrial, 35
 - seasonal, 34
 - short-term, 33
 - infiltration/inflow, 29-33
- Wastewater treatment:
 - current status, 2-4
 - definition of terms, 377-378
 - new directions and concerns, 4-8
 - operations (*see* Physical unit operations)
 - processes (*see* Biological unit processes; Chemical unit processes)
 - role of microorganisms in, 360
 - typical flow diagrams for secondary treatment: with biological methods, 894 with physical and chemical methods, 470
- Wastewater treatment plant design:
 - application of treatment methods, 126-129
 - advanced, 128
 - for combined sewer overflows, 129
 - conventional secondary, 128
 - nutrient removal or control, 128
 - preliminary, 128
 - primary, 128
 - toxic or specific contaminant removal, 129
 - classification: biological unit processes, 126 chemical unit processes, 125 physical unit operations, 125
 - constituent removal efficiency, 170
 - cost considerations, 133-135
 - design considerations, 136
 - energy and resource requirements, 136
 - equipment availability, 136
 - personnel requirements, 136
 - design period, 182
 - environmental considerations, 135
 - flowrates, 148-153
 - mass loadings, 153-162
 - objectives and regulations, 122-125
 - current regulations, 122-124
 - safety requirements, 125
 - sludge regulations, 124, 777-779
 - trends in regulations, 124
 - plant hydraulics, 184-189
 - plant layout, 184
 - preliminary sizing, 183
 - process design, 181-189
 - process flow diagrams, 130-137, 182
 - process selection, 166-181
 - based on kinetic analysis, 170-176
 - based on empirical relationships, 177
 - factors affecting selection, 168, 169
 - impact of flowrates and loadings, 178

- Wastewater treatment plant design, process selection (*Cont.*):
- reliability considerations, 177-81
 - systems approach, 167
 - solids balance, 184
 - startup and operations, 141
- Water:
- dissolved oxygen concentration, 1258-1259
 - physical properties, 1251-1254
 - solubility of gases in, 1255-1256
 - used for public supplies, 16-25
(*See also* Water use data)
- Water conservation devices, 41-43
- description, 42
 - effects on interior water use, 41
 - typical flowrate reduction, 42
- Water hyacinths, 1005
- characteristics of, 1005
 - harvesting of, 1012
 - use in wastewater treatment systems, 1006
- Water pollution control:
- Clean Water Act (CWA), 123
 - national standards for secondary treatment, 123
 - receiving water standards, 1196
- Water Quality Act of 1987 (WQA), 124
- Water quality, irrigation, 1144-1157
- adjusted sodium adsorption ratio, 1148
 - health and regulatory requirements, 1155
 - nutrients, 1153
 - physical and chemical, 1144
 - salinity, 1145
 - sodium adsorption ratio (SAR), 1148
 - specific ion toxicity, 1148
 - water infiltration rate, 1148
- Water quality criteria:
- acute toxicity units (TU_a), 106
 - criterion continuous concentration (CCC), 106
 - criterion maximum concentration (CMC), 106
 - lowest observable effect concentration (LOEC), 104
 - no observable effect concentration (NOEC), 104
 - no observable effect concentration level (NOECL), 104
- Water use data, 16-25
- by commercial facilities, 18
 - domestic, 17-19
 - effects of water conservation devices, 41
 - estimating from water supply records, 20-22
 - factors affecting water use, 23
 - fluctuations in community systems, 25
 - industrial (nondomestic), 19
 - by industries, 21
 - by institutional facilities, 19
 - proportion reaching collection system, 25
 - public service and system maintenance, 19
 - by recreational facilities, 20
 - typical interior use, 17
 - typical per capita use, 17
 - unaccounted system losses and leakage, 20
 - by various devices and appliances, 23
- Wehner and Wilhelm equation, 644
- Weir loadings:
- for activated-sludge settling tanks, 591
 - for primary sedimentation tanks, 475
- Wet-air oxidation:
- for heat treatment, 813
 - for thermal reduction, 889-890
(*See also* Zimpro process)
- Wet oxidation in a vertical deep-well reactor:
- description of, 889-890
 - schematic diagram of, 890
- Wet scrubbers for odor control, 515-517
- Wetlands treatment of wastewater:
- definition of, 934
 - types of: natural, 935
 - constructed, 992-1002
(*See also* Constructed wetlands)
- Windrow sludge composting, 844-845
- Yield, vacuum filter, 860
- Yield coefficient, bacterial:
- definition of, 371
 - determination of, 1275-1279
 - effect of endogenous metabolism, 372
 - observed values of: in bacterial growth, 372
 - in activated sludge process, 377, 388
 - typical values for: activated sludge process, 394
 - anaerobic digestion process, 426
 - nitrification process, 701
 - denitrification process, 721
- Yield stress of sludge, 791-793
- Zeolite, 740
- Zero-order reaction, 1267
- Zeta potential, 311-312
- Zimpro process:
- description of, 813
 - for heat treatment, 852-853
 - schematic diagram of, 853
 - for thermal reduction, 889
(*See also* Wet-air oxidation)
- Zinc:
- inorganic nutrient, 361
 - in wastewater, 88
- Zone settling, 221, 229-240
(*See also* Hindered settling)