

INDEX

- 2-D composition, 194
- absorption-based optical sensors, 39
- absorption-based sensors, 39
- absorption fiber optic chemical sensors, 39
- acetonitrile (ACN), 198–202
- ACN. *See* acetonitrile
- acoustic wave propagation, 27, 29
- acoustic wave sensor, 24, 27, 29, 30
- active and passive filters, 355
- active surface area, 131, 134, 139, 140, 142
- ADFETs. *See* adsorption-based FETs
- adsorption, 9, 17, 20, 24, 32, 70, 71, 75–77, 79–85, 88, 90, 94, 96, 98, 105, 112, 119, 120, 121, 124, 129, 132, 135, 136, 186, 259, 260, 262, 263, 315, 320, 322, 326, 327, 332, 344, 348, 350, 356, 361, 363, 364, 365, 367
- adsorption ability, 64, 129
- adsorption-based FETs (ADFETs), 12
- adsorption/desorption parameters, 79, 80–82, 315
- adsorption processes, 64, 76, 81
- adsorption properties, 70, 124, 315
- aerosol phase, 245, 246, 248, 249, 252
- AFM. *See* atomic force microscopy
- Ag, 90, 171, 172, 174, 218, 260, 265, 332, 345, 346, 348–350
- agglomerate, 131, 140–142, 144, 219, 227, 229, 257, 318, 319, 324, 326
- agglomerated, 140–142, 257, 258, 278, 285, 318, 319
- agglomeration, 23, 121, 131, 140, 142, 144, 257, 269, 271, 282, 283, 285, 288, 318, 319, 321, 324, 347, 365
- Al₂O₃, 66–68, 71–73, 76, 79, 85, 89, 90, 93, 109, 111, 112, 143, 188, 196, 218, 229, 233, 238, 239, 242, 243, 254, 260, 271, 282, 283, 325, 338, 345, 346, 356, 357, 364
- alcohol condensation, 273, 274
- alloy, 83, 131, 161, 217, 220, 231, 241, 242, 351, 352
- amperometric sensor, 2–4
- analyte, 2, 3, 8, 9, 17, 21–26, 33, 34, 36–39, 42, 44, 64, 74, 84, 111, 127, 177, 180, 182, 184, 186, 192, 194, 197–199, 201
- aqueous solutions, 259, 260, 262, 272, 290, 351
- atomic force microscopy (AFM), 32, 174, 327, 360
- atomization techniques, 248
- Au nanoparticles, 127, 171, 174
- band gap, 9, 69–71, 74, 106–109, 169, 342
- baseline sensor drift, 24
- biological sensors, 32, 51, 169
- bridging oxygen, 103, 317
- bulk stoichiometry, 321
- calcination, 135, 188, 277, 278, 284, 333, 336
- calorimetric sensors, 48
- cantilever, 9, 32, 33, 83, 177, 179, 180
- capacitance sensors, 8, 9
- carbon-containing species, 320

- carbon nanotubes, 21, 330
- catalyst, 19, 20, 23, 45, 46, 47, 82, 83, 105, 124, 125, 127, 128, 131, 161, 186, 188, 202, 253, 260, 267, 274, 276, 291, 314, 320, 332, 337, 347, 351, 352, 353, 357, 358, 368
- catalytic activity, 64, 70, 82, 84, 87, 88, 101, 105, 121, 127, 186, 215, 317, 331, 334, 339, 340, 349, 350, 356, 358
- catalytic activity of sensing materials, 84
- catalytic bead, 19
- catalytic sensors, 19
- cationic site, 75
- CBD. *See* chemical bath deposition
- CdS, 78, 271
- CdSe, 165–168
- CFS. *See* combustion flame synthesis
- CH₄, 40, 96, 121, 339, 350, 355, 356, 362, 368
- charging agent, 270
- chemFET, 1, 12, 15
- chemFET-based sensors, 15
- chemical activity, 92, 93, 235, 346
of metal oxides, 93
- chemical bath deposition (CBD), 259–262, 264, 265, 269, 271, 272
- chemical polymerization, 289, 292, 293
- chemical precursor, 237, 241, 244, 284, 299
- chemical sensitization, 349
- chemical sensor, 1, 17, 19, 25, 31, 32, 33, 34, 36, 37, 38, 39, 45, 52, 63, 64, 65, 69, 70, 78, 80, 84, 88, 90, 92, 94, 95, 96, 97, 103, 106, 107, 109, 110, 112, 113, 120, 144, 215, 216, 224, 229, 231, 245, 246, 267, 272, 275, 276, 279, 288, 289, 292, 294, 298, 301, 327, 328, 329, 330, 332, 336
- chemical stability, 92, 229, 243
- chemical vapor condensation (CVC), 280, 282–284
- chemical vapor deposition (CVD), 189, 235, 236, 237, 238, 239, 241, 242, 243, 244, 245, 247, 253, 282, 289, 292, 294, 295, 298, 299, 300, 314, 322, 326, 346
- chemical warfare agents (CWAs), 200
- chemiluminescence, 33, 34, 35
- chemisorption, 21, 22, 69, 76, 77, 79, 80, 88, 96–98, 101–103, 121, 124, 238, 315, 317, 318, 344, 361, 364
- cladding-based chemical fiber-optic sensors, 37
- Clark oxygen sensor, 3
- CO, 3, 9, 40, 70, 79–84, 87, 96, 98, 103, 111, 127, 128, 133, 135, 136, 139, 142, 188, 190, 191, 238, 323, 327, 339, 341, 349–353, 355, 356, 362, 368
- coating design and tooling, 295
- colorimetric sensors, 39
- combinatorial experimentation, 165
- combinatorial library, 163, 195
- combinatorial materials screening, 160, 184
- combinatorial screening, 160, 172, 177, 183, 186, 188, 196, 198, 200, 202
- combinatorial technologies, 160, 165, 202
- combustion flame synthesis (CFS), 280, 281, 283–285
- complexant, 260, 261
- composite, 101, 105, 186, 187, 215, 216, 232, 235, 288, 289, 291, 292, 297
- conducting polymer, 110, 111, 169, 184, 245, 290, 292
- conductivity, 1, 4, 5, 20, 21, 23, 24, 27, 28, 46, 47, 48, 64, 70, 74, 79, 80, 82, 92, 95, 96, 97, 98, 99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 114, 115, 128, 131, 169, 188, 226, 250, 252, 265, 320, 334, 339, 341, 343, 344, 356, 362
- conductivity type, 101, 102
- conductometric sensor, 4, 20–23, 107, 109, 196, 202
- conjugated organic monomers, 169
- corona spray pyrolysis, 250
- CoTiO₃, 191
- counter electrode, 3, 4, 250, 265
- Cr_{2-x}Ti_xO₃, 103
- cracking effect, 276
- crystal faceting, 318
- crystallite, 88, 95, 98, 113, 115, 116, 118, 119, 120, 121, 128, 132, 135, 136, 139, 141, 142,

- 186, 219, 226, 227, 229, 254, 256, 257, 269,
314, 315, 318, 319, 321, 324, 325, 326, 332,
333, 336, 338, 341, 354, 358, 364, 366
- crystal shape, 120
- crystal structure, 65, 67, 103, 104, 120, 226, 234,
241, 283, 313, 338, 341
- CVC. *See* chemical vapor condensation
- CVD. *See* chemical vapor deposition
- CWAs. *See* chemical warfare agents
- DC and RF sputtering, 222
- Debye length (L_D), 114
- dendrogram, 167
- deposition from aerosol phase, 245
- deposition parameters, 226, 232, 239, 240, 254,
257, 315, 323
- deposition process, 16, 124, 217, 218, 223, 231,
235, 239, 242, 245, 246, 249, 253, 265, 269,
270, 293, 295
- deposition rate, 220–225, 232, 234, 237, 239, 241,
242, 252, 253, 264, 267, 270, 284, 294, 298,
300
- deposition technology, 121, 215, 293, 297
- desorption, 77, 79–82, 98, 119–121, 186, 238,
315, 322, 332, 334, 351, 352, 364, 365
- detection mechanism, 38, 116, 361
- device application, 358
- dielectric constant, 8, 9, 43, 106, 112, 114, 186
- diffusion, 18, 20, 26, 67, 96–98, 100, 103, 120,
124, 131, 132, 138–142, 192, 196, 225, 227,
233, 236, 237, 239, 245, 252, 261, 313, 335,
353, 356, 359, 365
- diffusion-layer thickness, 196
- dimension effect, 114, 115
- discrete arrays, 165, 166
- dissociation, 18, 44, 75, 89, 105, 124, 138, 221,
236, 260, 345, 357, 360, 361
- dissociative chemisorption, 124, 317
- doping, 13, 23, 82, 105, 116, 126, 127, 130, 138, 169,
188, 191, 291, 314, 331, 333–342, 361, 364
- doping process, 342
- droplet size, 246–248
- ED. *See* electroless deposition
- EDOC. *See* electrochemical deposition under
oxidizing conditions
- electrical energy transduction, 183, 184
- electrical energy transduction sensors, 183
- electrochemical cell, 2–5, 98
- electrochemical deposition, 259, 264, 267, 270
- electrochemical deposition under oxidizing
conditions (EDOC), 259, 267, 269
- electrochemical polymerization, 288–291, 297
- electrochemical sensors, 1–3, 38, 64, 94, 105, 110
- electroconductivity, 69, 70, 74, 95, 107, 109, 110,
141, 342, 344, 351
- electroless deposition (ED), 259, 260, 265, 269,
272
- electrolyte, 2–5, 16, 95, 98, 169, 200, 266–268,
290, 297, 298, 300
- electron-beam evaporation, 216, 234
- electron configuration, 68, 69, 74, 87
- electron exchange, 186, 332, 334, 340
- electronic “nose,” 368
- electronic properties, 71–73, 77, 78, 96, 186
of metal oxide surfaces, 77
- electronic sensitization, 349
- electronic structure, 68, 70, 74, 106, 129, 351
of metal oxides, 68, 70, 106
- electrophoretic deposition (EPD), 270–272, 300
- electrophysical properties, 68, 97, 113, 215
of sensing materials, 97
- electrostatic spray deposition (ESD), 250–252
- electrostatic spray pyrolysis. *See* electrostatic spray
deposition
- environmental conditions, 358, 361
- EPD. *See* electrophoretic deposition
- ESD. *See* electrostatic spray deposition
- ethanol (EtOH), 198, 199
- EtOH. *See* ethanol
- evaporation rate, 216, 281
- Fe₂O₃, 66, 68–70, 72, 73, 78, 85, 87–91, 93, 105,
108, 111, 131, 238, 254, 260, 277, 331, 345,
346, 350

- Fermi level, 9, 77, 78, 109, 130, 315
- Ferrite plating, 269, 272
- FET. *See* field-effect transistor
- F* (flat) faces, 317
- fiber, 34–39, 41, 109, 110, 112, 169–171, 173, 272, 273, 292, 294–297
- fiber Bragg gratings, 39
- fiber coating, 294, 296
- fiber optic chemical sensor, 36–39
- fiber optic sensor, 36, 38
- field-effect transistor (FET), 11–15, 51, 94
- field-effect transistor sensors, 12
- filament thermistor, 48
- film agglomeration, 324
- film deposition, 128, 216, 218–220, 224, 225, 232, 233, 239, 245, 247, 248, 250, 253, 260, 264, 269, 271, 290, 291, 294, 321, 324, 325, 340
- by thermal evaporation, 218
- film microstructure, 233
- film texture, 23, 127–129, 256
- film thickness influence, 128, 337
- finely dispersed fraction, 118, 358
- flame ionization detector, 49
- flame ionization sensor, 49, 50
- flammable gas, 19, 140
- flexural plate wave (FPW), 25, 31
- fluorescence-based optical chemical sensor, 38
- fluorescence fiber optic chemical sensors, 38
- fluorescent chemical sensors, 34
- FPW. *See* flexural plate wave
- Ga_2O_3 , 19, 66, 71–73, 85, 87, 89, 93, 98, 100, 102, 104, 109, 229, 243, 328, 334, 345, 356, 364
- GaAs, 19, 78, 94, 95, 108, 111, 112
- GaN, 19, 95, 108
- gap plasmons, 177
- gas condensation, 280
- gas processing condensation (GPC), 280, 283
- gas-sensing effect, 63, 79, 80, 115, 121, 123, 131, 140, 142, 318, 344, 347, 357, 358, 365
- gas-sensing properties, 114, 115, 121, 129, 137, 188, 314–316, 319, 322, 334, 337, 339, 344, 354, 367
- of metal oxides, 314, 315, 316, 348
- of multicomponent metal oxides, 337
- gas sensor, 2, 9, 11, 13, 14, 18, 21–24, 27, 31, 45, 63, 64, 69, 70, 74, 77–79, 81, 82, 84, 87, 90, 92, 94–101, 103, 106, 107, 109–113, 116, 119–121, 123, 124, 127, 130, 132, 134, 135, 138, 139, 165, 167, 172, 225, 227, 243, 250, 270, 272, 276, 285, 313, 314, 315, 318, 322, 323, 325, 326, 329, 334, 337–339, 341, 343, 348, 351–353, 356, 358–361, 364, 365, 367–370
- GCS. *See* grating coupler sensor
- gelation, 276
- GPC. *See* gas processing condensation
- gradient arrays, 166, 192
- gradient sensor material, 192
- grain, 21–23, 88, 97, 98, 100, 107, 113–121, 127–135, 141–144, 188, 219, 225–227, 234, 238, 255, 256, 264, 271, 277, 278, 286, 287, 314–316, 318, 319, 321, 323–328, 333–338, 341, 343, 345, 347, 354–356, 358–367
- grain boundary, 22, 98, 100, 115, 120, 121, 128, 188, 334–336, 338
- grain faceting, 121
- grain-growth inhibitors, 367
- grain size, 23, 113–121, 129, 131–135, 142–144, 225–227, 234, 238, 255, 256, 271, 277, 278, 286, 287, 315, 316, 318, 319, 321, 324, 326–328, 333, 334, 336–338, 345, 358–365, 367
- grain-size growth, 256, 277
- “grains” model, 113, 115
- grating coupler sensor, (GCS), 35
- growth directions, 328
- H_2 , 5, 70, 76, 81, 83, 87, 88, 90, 111, 117, 119, 124, 133, 134, 137–139, 142, 188, 190, 191, 238, 327, 338–340, 348, 350, 352, 353, 355–357, 359, 360–363, 368
- H_2S , 3, 92, 105, 238, 341, 345, 350, 357, 358, 366, 368

- heat of formation of the most stable oxide, 88
humidity, 9, 24, 37, 39, 41, 48, 49, 64, 94, 96, 97, 99,
101–103, 106, 109, 111, 112, 119, 121, 131,
139, 180, 200, 313, 343, 355, 361, 363, 364
hybrid materials, 279, 280
hydrolysis, 97, 117, 135, 237, 242, 260, 261, 264,
273, 274, 276, 277, 279, 280, 292
hydroxyl groups, 77, 119, 269, 364
- IBAD. *See* ion-beam–assisted deposition
IDTs. *See* interdigital transducers
 In_2O_3 , 66, 72, 73, 74, 85, 89, 93, 96, 98, 101, 102,
109, 115–117, 119, 128, 129, 134, 136, 137,
139, 188, 190, 225, 226, 229, 238, 239, 243,
254, 255, 260, 265, 271, 276, 277, 325–328,
331, 333, 334, 339–345, 351–353, 357,
359–365, 367
indium tin oxide (ITO), 373
initial reduction temperature, 88, 90
InP, 19, 94, 95, 108, 111, 112
interglomerate contact, 141, 142, 144, 318, 319
interdigital transducers (IDTs), 27, 29–31
interdigitated electrode, 8, 23, 186, 187
intergrain contact, 115, 315, 343
ion-beam–assisted deposition (IBAD), 233–235
ionic drift, 95
ionosorption, 74
ion-selective electrode (ISE), 5–7
ion-sensitive field-effect transistor (ISFET), 12,
15, 16
IR spectroscopy, 39–41, 76, 111
ISE. *See* ion-selective electrode
ISFET. *See* ion-sensitive field-effect transistor
ITO. *See* indium tin oxide
- Kelvin probe, 10, 11
kinetics of sensor response, 324, 364
K (kinked) face, 334
K-nearest-neighbor (KNN) cluster analysis, 167,
168
KNN. *See* *K*-nearest-neighbor cluster analysis
Knudsen cell, 217
Lamb wave sensors, 30
Langmuir-Blodgett (LB) films, 51, 52
Langmuir-Blodgett (LB) sensors, 1, 50
Langmuir-Blodgett (LB) technique, 292
laser ablation, 21, 229, 230, 232, 299, 300
lattice oxygen, 88, 103, 105, 106, 338, 344
LB. *See* Langmuir-Blodgett
Lewis acidity, 70
Lewis basicity, 71, 76
LFD. *See* liquid flow deposition
liquid flow deposition (LFD), 269, 272
liquid-phase deposition (LPD), 188, 259, 260,
264, 272, 297
long-term stability, 25, 64, 91, 94, 95, 97, 99,
142, 160, 180, 188, 275, 358
Love-mode acoustic wave sensors, 30
lower explosive limit (% LEL), 20
LPD. *See* liquid-phase deposition
- magnetron sputtering, 196, 222–224, 245, 252,
296, 298, 324, 326
MAPLE. *See* matrix-assisted pulsed laser
evaporation
mass-sensitive chemical sensors, 31
material selection, 182
materials engineering, 23, 313, 368
matrix-assisted pulsed laser evaporation
(MAPLE), 293, 294
mechanical energy transduction, 177
mechanical energy transduction sensors, 177
mechanical milling, 124, 142–144, 280, 285–287
melting temperature, 67, 88, 91, 94, 216, 217,
219, 237, 286, 326, 336
membrane, 2, 3, 5–7, 9, 15, 16, 30, 31, 36, 47,
88, 101, 110, 196, 197, 355–357, 368
MEMS. *See* microelectromechanical systems
mesoporous materials, 216, 330
metal-ion coordination numbers, 65
metal-organic chemical vapor deposition
(MOCVD), 242, 243, 245, 253, 299
metal-organic precursor, 237, 243, 275, 282,
283

- PECVD. *See* plasma-enhanced chemical vapor deposition
- pellistor, 19, 20, 48, 140
- peripheral measuring device, 103, 368
- phase modification, 332, 334, 343
of metal oxides, 331, 332, 343
- photoacoustic sensors, 45
- photo-assisted chemical vapor deposition (PACVD), 244, 245, 299
- photochemical deposition (PCD), 271
- photochemical polymerization, 288, 289, 291
- photolytic mechanism, 244
- photothermal mechanism, 244
- pH sensor, 2, 6, 272
- physical sputtering, 220
- physical vapor deposition (PVD), 232–235, 239, 294, 296, 298–300
- piezoelectric material, 24, 28
- plasma-enhanced chemical vapor deposition (PECVD), 241, 242, 299
- plasma polymerization, 288, 291
- plasmonic nanostructure, 171
- plasticizer, 169, 171, 172, 198, 200–202, 276
- PLD. *See* pulsed laser deposition
- point defect, 65–68, 97, 98, 107, 315, 326
- polycrystalline film, 129, 141, 243, 318, 319, 363
- polymer, 8, 9, 21, 24, 30, 34, 36, 37, 47, 91, 92, 94, 97, 108, 110–112, 161, 166–173, 176, 180–183, 185–187, 192, 193, 200, 202, 224, 245, 259, 261, 262, 276, 288–294, 296, 297
- polymer film, 9, 94, 166, 186, 187, 276, 288, 292, 293
- polymerization, 94, 107, 161, 166, 169, 184, 245, 252, 273, 275, 280, 288–293, 297
- polymer sensor, 94, 97, 110
- polymer synthesis, 186, 288
- polymer technology, 288
- polypyrrole (PPY), 94, 108, 112, 245, 289, 291
- porosity, 23, 121, 128, 131–135, 137–139, 142, 225, 227, 229, 272, 274, 276, 280, 318, 319, 324, 334, 338, 341, 345, 356, 360, 365
- porosity and active surface area, 131, 134
- postdeposition annealing, 326
- post-transition-metal oxides, 68, 69, 74
- potentiometric sensor, 3, 5, 6, 95
- powder, 40, 116–118, 132, 133, 135, 136, 139, 140, 143, 215, 236, 250, 262, 264, 270–273, 278, 280–289, 292, 298, 338, 346, 351, 359, 364
- powder technology, 280, 287
- PPY. *See* polypyrrole
- pressure of the saturated vapor, 216
- pre-transition-metal oxides, 68
- principal-components analysis (PCA), 182, 200
- Pt, 13, 18–20, 23, 47, 82, 90, 91, 96, 109, 117, 125–127, 133, 138, 139, 189, 192–194, 196, 218, 238, 244, 253, 265–268, 271, 290, 332, 345–348, 350, 352, 355–358, 365, 368
- pulsed laser deposition (PLD), 229–232, 293
- pulsed magnetron sputtering, 223, 224
- PVD. *See* physical vapor deposition
- pyroelectric effect, 46
- pyroelectric sensor, 47
- pyrolysis, 21, 116, 119, 121, 129, 137, 140, 141, 237, 242, 243, 246–251, 253–259, 273, 280, 283, 288, 289, 292, 293, 298, 300, 315, 316, 321–325, 339–341, 347, 349, 353, 360–362
- pyrolysis temperature, 119, 243, 256, 259, 321–324, 361, 362
- QCM. *See* quartz crystal microbalance
- QCM crystal, 25, 26
- quartz crystal microbalance (QCM), 25, 26
- radiant energy transduction, 165
- radiant energy transduction sensor, 165
- radio-frequency identification (RFID) sensor, 196, 198–202
- rate of sensor response, 365
- reaction chemistry, 237
- reactivity of elements toward oxygen, 90
- reagent, 37, 38, 41, 82, 92–94, 165, 192–194, 202, 259, 263, 264, 274, 276, 289, 290, 346
- recovery time, 1, 80, 81, 99, 117, 128, 129, 139, 140, 142, 165, 180, 329, 365, 368

- “redox” mechanism, 101, 361
 redox reaction, 10, 74, 368
 reduction, 3, 28, 69, 74, 88–90, 95, 98, 102, 103,
 120, 121, 125, 127, 129, 135, 186, 224, 237,
 263, 267, 269, 270, 276, 281, 317, 332, 333,
 339, 344, 358
 reference electrode, 2, 6, 7, 15, 16, 37, 95, 290
 refractive index, 34–37, 39, 43, 44, 71, 111, 134,
 172, 176, 296
 refractometric fiber optic chemical sensors, 39
 refractometric optical sensors, 39
 reothaxial growth and thermal oxidation
 (RGTO), 126, 131, 227, 229
 response time, 44, 63, 98–100, 116, 128, 135, 137,
 139, 140, 144, 186, 276, 324, 329, 345, 357,
 361–363, 365
 Rayleigh sensor. *See* surface acoustic wave (SAW)
 or Rayleigh sensor
 RFID. *See* radio-frequency identification sensor
 RF sputtering, 222, 231
 RGTO. *See* reothaxial growth and thermal
 oxidation

 Sauerbrey equation, 25, 27
 SAW. *See* surface acoustic wave sensor
 scanning light pulse technique (SLPT), 194, 195
 Schottky barrier, 17, 18, 78
 Schottky diode, 1, 16–18, 19
 Schottky diode–based sensor, 16
 screen printing, 21, 166, 292, 300
 Seebeck effect, 45
 selective ion-layer adsorption and reaction
 (SILAR), 259, 260, 262
 self-lithography, 244
 semiconducting metal oxides, 96, 100, 186, 196
 sensing film, 11, 141, 167, 177, 188, 192–194,
 197–202, 244
 sensing layer, 21, 22, 24, 31, 132, 135, 225, 276,
 318, 325
 sensing material, 38, 46, 63, 65, 77, 79, 84, 87, 88,
 92, 94, 97, 101, 102, 107–112, 115, 130–134,
 138, 140, 144, 159–166, 169–172, 177, 180,
 181, 183, 185, 186, 188, 191–193, 196–200,
 202, 203, 231, 244, 254, 274, 276, 295–297,
 318, 330, 361, 367
 sensing properties, 21, 70, 114, 115, 121, 129,
 137, 188, 276, 314–316, 319, 322, 334, 339,
 344, 354, 367
 sensitivity, 1, 12–14, 16, 18, 21–25, 27, 28, 30,
 32, 34, 37–40, 44, 46, 63, 64, 78, 79, 81, 84,
 86–88, 91, 92, 94–96, 98, 99–102, 104–106,
 109–112, 115–117, 119, 124, 125, 127, 129,
 131–134, 137–139, 142, 144, 166, 169,
 172, 177, 183, 185, 186, 188–190, 194, 200,
 202, 313–315, 319, 320, 324, 327, 329, 330,
 338–342, 344–352, 355–359, 361, 362,
 364–366, 368–370
 to air humidity, 102, 119, 131
 sensor array, 99, 177, 180–184, 188, 190, 192,
 196, 199, 244
 sensor parameters, 95, 96, 119, 129, 140, 279,
 280, 328, 366, 369
 sensor response, 17, 18, 24, 28, 80–84, 86, 88,
 114–117, 121, 123, 126, 128, 129, 131, 134–
 137, 140–144, 192, 193, 196, 198, 200, 201,
 314, 315, 318, 322–324, 327, 337, 340, 342,
 345, 347, 348, 350, 353, 356, 364, 365, 367
 control of, 331, 344
 selectivity of, 198, 200, 367
 sensor stability, 95, 195
 serial scanning analysis, 165
 SERS. *See* surface-enhanced Raman
 spectroscopic sensor
 SH-APM. *See* shear-horizontal acoustic plate
 mode (SH-APM) sensor
 shear-horizontal acoustic plate mode (SH-APM)
 sensor, 29
 shear-horizontal surface acoustic wave (SH-SAW)
 sensor, 29, 30
 SH-SAW. *See* shear-horizontal surface acoustic
 wave (SH-SAW) sensor
 Si, 19, 46, 72, 78, 90, 94, 95, 108, 111, 112, 196,
 242, 243, 274, 279, 325, 332, 346, 347, 367
 SiC, 14, 15, 19, 89, 95, 108, 112

- SILAR. *See* selective ion-layer adsorption and reaction
- SILD. *See* successive ionic-layer deposition
- sintering, 21, 66, 115, 128, 134–136, 274, 275, 278, 282, 285, 298, 300, 334, 338
- SLPT. *See* scanning light pulse technique
- SnO₂, 11, 23, 66, 68, 69, 72–74, 77–82, 85–87, 89, 91–93, 95, 96, 98, 101–105, 109, 111, 112, 115–119, 121–124, 126, 127, 129–144, 188, 189, 196, 225–227, 229, 233, 234, 238, 239, 242–244, 254, 256–262, 270, 271, 277, 278, 282, 315–329, 331, 333–345, 347–355, 357, 358, 360–366
- crystallographic planes, 121
- SnO₂-CuO, 92, 341, 342
- sol-gel method, 116, 140, 245, 246, 275–278, 333, 339
- sol-gel polymerization, 275
- solid electrolytes, 95, 298, 300
- solid-state gas sensor, 63, 64, 78, 81, 87, 90, 95–98, 106, 113, 119, 121, 124, 130, 285, 313, 314, 322, 323, 334, 358, 359, 364, 365, 367–370
- space-charge region, 115
- specific-ion electrodes, 6
- SPR. *See* surface plasmon resonance
- spray nozzle, 246, 248
- spray pyrolysis, 298, 300
- spray pyrolysis deposition, 255, 341
- sputtering, 21, 196, 217, 219–226, 231, 233, 234, 245, 252, 291, 293, 296, 298, 300, 314, 324, 326, 347, 355
- rate, 220, 223, 224
- techniques/technology, 219, 221, 224, 324
- SrF₂O₃, 100
- stability, 21, 23–25, 44, 64, 69, 76, 78, 88–92, 94–97, 99–102, 109, 111, 113, 118, 119, 121, 123, 129, 131, 134, 140, 142, 160, 162, 167, 169, 180, 186, 188, 192–195, 200, 229, 243, 270, 271, 275, 293, 313, 314, 323, 326, 328, 329, 336, 338, 345, 346, 348, 353, 356, 358, 359, 361, 364, 366, 367, 369
- structural engineering, 119, 314, 319, 321, 322, 327, 334, 337, 359, 369
- structural properties, 21, 100, 134, 333
- successive ionic-layer deposition (SILD), 142, 144, 259, 260, 262–264, 272, 319, 349
- surface acoustic wave (SAW) or Rayleigh sensor, 25, 27–30, 83, 84, 110, 196, 198, 294
- surface additive, 355, 357
- surface catalysis, 22, 96, 340, 348
- surface charge, 15, 46, 79, 80, 129, 271
- surface clustering, 125
- surface clusters, 125, 349, 350, 353
- surface diffusion, 124, 131, 353
- surface-enhanced Raman spectroscopic (SERS) sensor, 171, 172, 174
- surface geometry, 23, 123–125
- surface modification, 23, 103, 125, 231, 245, 264, 323, 326, 345–352, 354–357, 367
- of metal oxides, 264, 344, 346, 350, 356
- surface morphology, 124, 172, 234, 241, 354
- surface plasmon, 1, 35, 43, 44, 111, 171, 178
- surface plasmon resonance (SPR), 1, 43–45, 111, 171, 177
- surface plasmon resonance sensor, 43
- surface plasmon resonance technique, 43
- surface poisoning, 82, 103
- surface processes, 70, 369, 370
- of sensing materials, 77
- surface properties, 70, 77, 79, 94, 95, 118, 130, 139, 195, 296, 337, 338, 343, 367
- surface reaction, 23, 83, 88, 98, 103, 121, 124, 270, 317, 339, 348, 364, 366
- surface segregation, 334–336
- surface solubility, 335
- surface state, 63, 74, 77–80, 121, 130, 186, 315, 332, 342, 345, 346
- surface stoichiometry, 130, 131, 342, 345, 346
- disordering, 129
- swelling, 8, 24, 184
- technology readiness level (TRL), 162, 163
- temporal drift, 95, 98

- thermal conductivity, 1, 47, 48
thermal conductivity sensor, 47, 48
thermal evaporation, 216–219, 221, 224, 227,
233, 280, 282, 294
thermalization, 224, 225
thermally activated CVD, 241, 242, 245
thermal program reduction (TPR), 88–90
thermal stability, 78, 89, 91, 94, 102, 131, 134,
293, 326, 336, 345, 348, 359, 366
thermodynamic stability, 64, 88–90
thermoelectric effect, 45
thermoelectric sensor, 45, 46
thick film, 118, 119, 138, 139, 188, 290, 359,
365
thick-film sensor, 21, 134, 140
thickness shear mode (TSM) sensor, 25, 27,
180–183, 196, 198
thin film, 21, 23, 28, 47, 50, 109, 116, 118, 119,
123, 141, 166, 196, 197, 219, 221, 229,
231–233, 242, 245, 246, 251, 259, 262, 264,
271–273, 275, 282, 290, 293, 300, 314, 324,
347, 359, 365
thin-film sensor, 21, 129, 144, 368
threshold voltage, 12–16
TiO₂, 66, 68, 69, 72–76, 78, 85, 87, 89, 90, 93, 95,
98, 102, 104, 108, 111, 112, 125–128, 131,
226, 238, 242, 243, 254, 260, 265, 271, 277,
281, 297, 328, 331, 333, 334, 336
TPR. *See* thermal program reduction
transducer, 25, 27, 29, 45, 162, 177, 184, 341,
350, 358
transition-metal oxide, 66, 68–70, 74, 87, 106,
127, 265, 331, 334, 345, 357
transmittance, 40–42
TRL. *See* technology readiness level
TSM. *See* thickness shear-mode sensor
ultrasonic agitation, 271
ultrasonic atomizer, 246
UV absorption, 42
UV irradiation, 94, 173, 291, 293, 346
UV spectroscopy, 42
vacuum deposition, 216, 293
vacuum evaporation, 216–218, 245, 293, 346
vacuum polymerization, 289, 293
van der Waals interaction (force), 24, 177, 180
vapor pressure, 198, 200, 216, 217, 221, 236, 237,
281, 291, 298
water adsorption, 119, 124, 363, 364
water condensation, 139, 273, 274
WE. *See* working electrode
Wheatstone bridge, 5, 19
wireless technologies, 196
WO₃, 66, 69, 70, 72, 84, 85, 89, 93, 98, 100–102,
108, 111, 112, 115, 124, 260, 277, 331, 361
work function, 1, 9, 10, 11, 13, 15, 17, 18, 77, 78,
106, 194, 346
work-function sensor, 9, 84, 88, 109
working electrode (WE), 2–4
ZnO, 30, 66, 68–70, 72–74, 78, 85, 87, 89, 90, 93,
102, 109, 111, 112, 127, 128, 130, 131, 225,
226, 229, 242, 243, 254, 260, 265, 269, 271,
328, 331, 345, 364
ZnS, 78
ZrO₂, 66, 72, 73, 76, 78, 85, 89, 90, 93, 98, 108,
111, 112, 126, 127, 218, 238, 242, 243, 260,
277, 281, 283, 356

INDEX

- AAO. *See* anodic aluminum oxide
- absorption spectroscopy, 96, 158
- activated tunneling model, 172
- activation energy, 172, 173, 249, 323, 324
- adsorbed oxygen, 51, 237, 321
- adsorptivity, 311, 322
- aerogel, 340
- Ag. *See* silver
- air quality, 291
- ammonia (NH₃), 54, 58, 59, 65, 66, 101, 102, 104, 105, 133, 175, 221, 228, 244, 245, 251, 266, 268, 269, 321, 322, 324, 325, 327, 342, 348, 349, 356
- amperometric, 71, 127, 294, 327, 354, 361
- analyte, 53, 70, 104–108, 121, 133, 134, 149–153, 158, 159, 165–167, 169–176, 178–181, 183, 185, 186, 188–190, 228, 234, 236, 242, 243, 245, 268, 269, 275, 311, 319, 321–324, 342, 346–349, 354, 356, 360
- anodic aluminum oxide (AAO), 44–47
- anodic etching, 205, 209, 210
- anodization process, 215
- Au. *See* gold
- auxiliary phase, 316
- back gate, 47, 48, 95, 96, 112, 132
- band gap, 4, 5, 52, 88, 89, 94, 220, 323, 340
- BET (Brunauer-Emmett-Teller) surface area, 299
- biocompatibility, 151, 203
- biocompatible CNT, 101
- biological molecule, 54, 72, 98, 99, 101, 133, 188
- biomolecule, 22, 23, 70, 71, 98, 111, 112, 142, 151, 158, 159, 181, 183, 336, 344, 347
- biosensor, 53, 70, 112, 114, 123, 127, 128, 141, 142, 167, 181, 187, 188, 318, 339, 347, 349, 354
- block co-polymer, 299, 301
- Bohr radius, 47
- bottom-up method, 15–17, 22, 30, 31, 68, 72, 145
- Bragg mirror, 239, 240
- Brust-Schiffrin method, 143
- buckminsterfullerene (C₆₀), 7, 87, 88, 90, 91, 98, 132–134
- bulk doping, 40
- bulk material, 6, 7, 10, 13, 14, 19, 36, 142, 209, 225
- C₆₀. *See* buckminsterfullerene
- cadmium oxide (CdO), 54, 58, 66
- cantilever, 269, 271, 272
- capacitance-type sensor, 226, 228, 229
- capacitive sensor, 318
- capillary condensation, 204, 227–229, 236, 238, 240, 265, 292
- capillary effect, 227
- capping layer, 183
- carbon, 2, 3, 5, 7, 14, 18, 47, 53, 59, 68, 87–95, 98–101, 103, 108, 110, 114, 116, 123, 124, 126–128, 131, 133, 134, 143, 145,

- 169, 181–183, 220, 261, 266, 267, 291,
302, 303, 321, 324, 336–338, 342, 344,
347–350, 352–357, 360
- carbon monoxide (CO), 2, 4, 20, 34, 54, 57–60,
66, 67, 69, 70, 89, 91–93, 96, 97, 100, 103,
104, 111, 113, 124, 125, 143, 144, 148,
149, 175, 93, 181, 233, 244, 245, 250, 251,
253, 254, 266, 268, 269, 291, 294, 295,
298, 302, 303, 319, 321, 322, 324, 342,
343, 347, 355
- carbon nanotube (CNT), 2, 5, 7, 18, 47, 53,
68–70, 87–90, 92–105, 108–110, 115–117,
124, 126–134, 337, 342, 348–350, 352–356,
358, 359, 361
- carrier concentration, 40, 48–51, 247, 248
- carrier mobility, 48, 50, 52, 63
- cataluminescence, 327
- catalysis, 20, 181, 294, 326, 336, 360
- catalytic action, 344
- catalytic activity, 4, 10, 12, 20, 311, 326–328,
355, 358
- catalytic oxidation, 294, 295, 327
- CdO. *See* cadmium oxide
- cetyltrimethylammonium bromide (CTABr), 299
- CgA. *See* chromogranin A
- C_h. *See* Hamada vector
- CH₄. *See* methane
- charge carrier, 35, 40, 50, 51, 63, 207, 209, 220,
225, 249, 297, 323, 324
- chelating ligand, 297
- chemical composition, 3, 31, 147, 152, 226,
292, 313, 314
- chemical selectivity, 68, 108, 152, 159, 166, 169,
188, 190
- chemical sensing, 23, 30, 41, 70, 107, 133, 142,
147, 148, 151–153, 185, 269, 311, 316,
360
- chemical sensitivity, 61, 142
- chemical sensor, 9, 12, 14, 20, 23, 29, 53–56,
59–62, 65, 66, 68, 71–73, 87, 105, 141,
147, 148, 151–153, 185, 188, 210, 230,
240, 243, 265, 269, 311, 312, 316, 324,
328, 335, 339, 341, 346, 347, 349, 353,
355, 359, 361
- chemical vapor deposition (CVD), 31, 33–35,
36, 38, 39, 43, 47, 50, 91–93, 101, 103,
106, 118, 119, 130, 131, 212, 298
- chemicapacitor, 105, 107, 108
- chemiresistor, 104, 105, 107, 144, 149, 170,
171, 173–180, 186, 189, 291–293, 349
- chromium atoms, 130, 131
- chromogranin A (CgA), 111–114
- clinical diagnosis, 361
- CMOS. *See* complementary-metal-oxide
semiconductor device
- CNT. *See* carbon nanotube
- CNT sensor, 101, 133, 134
- CO. *See* carbon monoxide
- Co₃O₄, 303, 342
- colloid, 155, 159, 345, 350, 357
- colometric pH meter, 189
- complementary-metal-oxide semiconductor
(CMOS) device, 134, 271
- condensation, 32, 204, 227–229, 236, 238, 240,
247, 265, 292, 297–298
- conducting polymer, 44, 346, 347, 349, 353–
355, 357, 358, 360
- conduction band, 50, 51, 57, 94, 95, 154
- conductivity, 7, 13, 18, 41, 49–51, 63, 69, 94,
98, 99, 101, 105, 112, 133, 169, 171–173,
175, 176, 178, 180, 183, 185, 187, 209,
213, 243, 247–250, 255, 258, 261, 263,
270, 273, 313, 318, 323–325, 346, 347,
352–354, 359, 360
- conductometric detection, 57
- conductometric glucose biosensor, 114
- conductometric sensor, 244, 246, 247, 262, 323,
325
- conductometric-type gas sensor, 243
- contact barrier, 56, 63
- contact formation, 50, 53
- contact potential difference (CPD), 257, 258, 266
- core–shell structure, 347
- covalent functionalization, 100, 350

- CPD. *See* contact potential difference
crystallinity, 31, 59, 90, 303
crystallite size, 1, 6, 13, 297, 303
CTABr. *See* cetyltrimethylammonium bromide
cubic nanoparticle, 149, 176–178
CV. *See* cyclic voltammetry
CVD. *See* chemical vapor deposition
cyclic voltammetry (CV), 72, 124, 126, 127, 319
- dark conductivity, 249
Debye length, 10, 13, 47, 53, 54, 62, 275, 297
density-gradient ultracentrifugation (DGU), 93, 94
detection of biomolecules, 159, 183
DGU. *See* density-gradient ultracentrifugation
dielectric constant, 48, 108, 157, 173, 174, 178, 228, 234, 247
dielectrophoresis, 55
differential pulse voltammetry (DPV), 124–126
diffusion, 12, 13, 31, 33, 56, 107, 108, 122, 127, 150, 227, 246, 254, 293–296, 303, 319, 326, 341, 346, 355
diffusion coefficient, 254, 293, 295, 296
diffusivity, 122, 294–296
dimethyl methylphosphonate (DMMP), 54, 58, 60, 61, 104–108
dip coating, 298
distributed Bragg reflector, 239, 240
DMMP. *See* dimethyl methylphosphonate
DNA, 2, 96, 99, 101, 104, 105, 108–110, 122–126, 133, 134, 144, 148, 150, 151, 159–162, 166–168, 183–185, 187–188, 347, 348, 354, 356, 359, 360
DNA hybridization, 108–110, 122–124, 126, 133, 134, 167, 168, 184, 188, 354
doping, 35, 40, 41, 50, 51, 95, 98, 100, 109, 114, 211, 213, 215, 225, 271, 275, 292, 340, 346
double cell, 211
DPV. *See* differential pulse voltammetry
drain (D), 48, 63, 95, 96, 109, 111, 112, 114, 115
drop casting, 145, 149
drug delivery, 17, 101
electric arc discharge, 90, 92
electrical contact, 21, 53, 55, 56, 63, 111, 211, 247
electrical percolation, 353
electrical properties, 47, 51, 133, 151, 244, 247, 275, 341, 361
electrical transport properties, 47, 48, 50
electrochemical etching, 208, 211, 216, 221, 226
electrochemical etching cell, 211
electrochemical sensor, 53, 120–123, 126, 180, 181, 183, 185, 189
electrodeposition, 44–46, 126
electroless, 44, 45, 214, 221, 223, 224, 266, 268, 269
electroluminescence, 52, 99, 169, 240
electroluminescence sensor, 169
electrolyte, 44, 126, 178, 179, 181, 186, 187, 205, 206, 210–215, 217, 220–222, 225, 226, 244, 265, 325–327
electromechanical resonator, 130
electronic nose, 68, 70, 73, 152, 167, 185, 189
electropolishing, 205, 211, 218, 219, 224
electropolymerization, 354
electrospinning, 338
ellipsometric parameter, 238
endohedral doping, 98
environmental monitoring, 153, 169, 205, 361
enzyme electrode, 361
ethanol (EtOH), 213, 215, 235, 266
EtOH. *See* ethanol
ethyl alcohol. *See* ethanol
exohedral functionalization, 99, 352
explosive, 291
extrinsic doping, 50
- Fabry-Pérot resonator, 226
Fermi level, 50, 51, 94, 98, 100
FET. *See* field-effect transistor
field-effect transistor (FET), 18, 47–52, 55, 63–66, 95, 96, 101, 108, 110, 111, 113, 247

- field-emission sensor, 128, 134
- film deposition, 145, 146, 340
- film morphology, 174, 175, 215, 264
- filter, 19, 128, 129, 204, 239, 241, 242, 269, 273, 294, 295, 311, 315, 316, 319, 321, 327, 328
- fluorescence, 6, 70, 97, 108, 119, 121–123, 134, 153, 163, 164, 168, 169, 188, 316, 317
- fluorescence spectroscopy, 97
- fluorescent MCNP sensor, 162
- fluorophore, 100, 118, 120, 121, 134, 162, 317
- formation mechanism, 206
- freeze-drying, 220
- fullerene, 7, 87–90, 92, 98, 100, 132–134
- functional (sensitive) phase, 322
- functional coating, 18
- functional material, 17, 19, 44, 311, 359
- functionality, 22, 171, 312, 319, 325, 347
- functionalization, 7, 23, 36, 66, 98–100, 114, 116, 134, 144, 147, 160, 267, 350, 352
- Ga_2O_3 . *See* gallium oxide
- GaAs, 39, 47, 220–226, 250, 251, 253–255
- gallium oxide (Ga_2O_3), 40, 42, 47, 50, 51, 58, 226, 295
- GaN, 36–38, 220, 221, 223, 225, 250, 251, 253, 276
- GaP, 4, 5, 7, 39, 52, 88, 89, 94, 219–222, 224, 225, 270, 271, 273, 323, 341
- gas density, 128, 134
- gas diffusion, 293, 303, 355
- gas selectivity, 258, 293–295, 303
- gas sensitivity, 59, 62, 254, 264, 293, 302, 303
- gas sensor, 54, 57, 59, 60, 63, 67, 68, 70, 72, 73, 103, 181, 189, 203–205, 220, 221, 226, 228, 232, 238, 239, 241, 243–245, 247, 248, 250, 251, 254–261, 263–265, 268, 269, 273–276, 291–294, 296–299, 303, 316, 320, 322, 325, 327, 341, 344, 353, 355, 361
- gas sensor platform, 273
- gas-sensing characteristic, 256, 264, 265, 274
- gate refreshing, 66
- gating effect, 48, 63, 102, 112
- gel, 298, 299
- glucose, 71, 72, 108, 114, 115, 120–122, 126–128, 134, 318, 342, 347, 348, 354, 356, 360, 361
- glucose oxidase (GOx), 71, 72, 114, 115, 126, 127, 318, 348, 354, 356, 360
- glucose sensing, 114, 120, 121, 126
- gold (Au), 2–4, 20, 23, 31, 32, 34, 35, 38, 39, 44, 47, 55, 56, 66, 67, 72, 96, 104, 105, 111, 112, 115, 116, 126, 127, 131, 134, 142–146, 148–151, 154–165, 167, 169, 171–175, 178–184, 186–188, 212, 219, 245, 250–255, 262, 266, 268, 269, 294, 319, 325–327, 347, 348, 354–360
- gold–platinum (Au–Pt) nanoparticles, 126
- GOx. *See* glucose oxidase
- grain boundary, 6, 12, 19, 60, 61, 296, 339
- grain size, 6, 12, 21, 45, 60, 296, 297
- granular metal theory, 172
- growth direction, 22, 34–36, 40, 41, 43
- growth method, 15, 31, 33, 41, 43, 47, 143, 156
- growth parameters, 35
- H_2 . *See* hydrogen
- H_2O_2 . *See* hydrogen peroxide
- H_2S . *See* hydrogen sulfide
- H63D polymorphism, 109
- Hamada vector (C_h), 89
- heavy-metal ion, 159, 189, 317
- hemochromatosis, 108, 110
- Her1/EGFR, 118
- Her2/neu, 118
- heterojunction, 37–39, 247, 256, 343
- heterostructure, 38, 39, 204, 250, 251, 255, 256
- HF, 131, 205, 206, 209–216, 220–223, 225, 226, 244, 246, 265, 270, 302
- HFE gene, 108, 110
- hierarchical structure, 37
- HiPco (high-pressure carbon monoxide), 93, 96, 119, 122
- hole, 51, 65, 66, 94–96, 98, 100, 112, 114, 206,

- 207, 210, 213, 214, 236, 259, 261, 263,
271, 361
- host material, 316
- hotplate, 269, 270, 273, 274
- humidity sensing, 226, 227, 229, 318
- hybridization, 23, 88, 108–110, 122–126, 133,
134, 150, 161, 167, 168, 184, 188, 354
- hydrogen (H_2), 18, 21, 35, 39, 54, 57–59, 62,
66, 67, 69, 70, 91, 99, 103, 104, 114,
124–127, 146, 175, 181, 205, 206, 209,
212, 244, 245, 247, 248, 250–257, 260,
261, 266, 268, 294, 296, 298, 299, 302,
318, 321, 342, 357, 361
- hydrogen peroxide (H_2O_2), 114, 126, 127, 214,
217, 222, 223, 261, 263, 318, 342, 348,
356, 357, 360
- hydrogen sulfide (H_2S), 54, 58, 104, 181, 268,
294, 342, 343
- hydrolysis, 90, 114, 132, 133, 167, 168, 297
- hydrophobic surface, 294
- hydrothermal, 42
- hysteresis, 229, 230, 262, 266
- IEC. *See* ion-exchange chromatography
- immobilization, 23, 108, 111, 112, 125, 167,
181, 316, 317, 347, 354, 358, 360
- impedance measurement, 178, 249
- In_2O_3 . *See* indium oxide
- indium oxide (In_2O_3), 35, 38, 41, 42, 45, 47, 48,
50, 54, 57–59, 63, 70, 72, 298, 303, 304,
321, 339, 343
- inorganic–inorganic nanocomposites, 337
- InP , 5, 38, 39, 220–222, 224, 225
- InP nanodot, 5
- integrin $\alpha_v\beta_3$, 118, 119
- intrinsic doping, 50
- ion-exchange chromatography (IEC), 93
- ionic conductivity, 247, 323, 325
- ionization gauge, 128
- KIT-6, 304
- Knudsen diffusion, 227, 293, 295, 296
- Langmuir-Blodgett (LB) method, 146
- Langmuir-Schaefer method, 146
- LB method. *See* Langmuir-Blodgett method
- laser ablation, 39, 92, 143, 340
- layer-by-layer (LbL), 114, 115, 146, 150, 321,
354
- LbL. *See* layer-by-layer
- ligand, 119, 142–148, 150, 151, 159, 160, 166,
169, 171, 173–175, 178, 183, 187, 189,
297
- ligand substitution, 144, 146
- lithography, 14, 15, 54, 56, 131, 270, 358
- “lock-and-key” sensor, 152, 189
- macropore, 206, 292
- mask technology, 212
- MCNP film, 142, 144, 145, 170, 173, 174, 186,
189
- MCNP-based chemiresistor, 170, 176, 178, 179
- MCNP. *See* monolayer-capped nanoparticle
- mean free path, 6, 47, 154, 164, 293
- mechanical percolation, 353
- medical diagnostics, 112, 151
- membrane, 19, 44, 45, 60, 72, 111, 113, 117,
121, 122, 152, 181, 218, 219, 244–246,
269–274, 291, 294, 295, 303, 315, 316,
337, 344, 347, 360, 361
- mesopore, 208, 216, 292, 293, 295, 298, 299,
302, 303, 312
- mesoporosity, 292, 295, 302
- mesoporous metal oxide, 297, 303
- mesoporous silica, 301, 302, 317, 321, 322
- metal core, 172, 173, 357
- metal-core nanoparticle, 357
- metal ions, 143, 159, 183, 189, 243, 317, 357
- metal nanoparticle, 88, 92, 93, 103–105, 116,
142, 144, 153, 164, 338, 354, 355, 357–359
- metal oxide, 7, 29, 30, 34, 37, 44, 47, 50–58,
60, 66, 68, 70, 72, 102–104, 171, 204,
205, 249, 256, 263, 265, 275, 291–293,
297–299, 302–304, 336, 338–344, 346,
347, 352, 353, 355, 357

- metal-oxide nanowire sensor, 57
- metal oxide–based nanocomposite, 338–341, 357
- metal salt reduction, 143
- metallic, 4, 6, 17, 45, 46, 88, 89, 94, 95, 97, 103, 122, 123, 141, 143, 144, 147, 152, 171, 175, 181, 188, 189, 211, 243, 352, 358
- metalloprotein, 354
- metal oxide, 30, 179, 204, 254
- methane (CH₄), 41, 93, 103, 104, 118, 179, 244, 255, 268, 291, 294–296, 298, 302, 303, 361
- micelle, 96, 143, 301, 315, 339, 358
- micro hotplate, 269, 270, 274
- microemulsion, 339
- micromachining, 203, 269–272, 274
- micropore, 205, 208, 227, 293, 299, 315, 326
- microstructure, 6, 10, 210, 221, 238, 246, 254, 265, 339
- mixed-potential sensor, 327
- molecular recognition element, 103
- molecular sieve, 93, 293, 294, 315
- monodisperse, 43, 297
- monolayer, 23, 108, 141, 142, 145–147, 152, 164, 174–176, 183, 184, 187, 239, 259, 357
- monolayer-capped nanoparticle (MCNP), 142–147, 149–153, 158, 160, 162, 164, 166, 167, 169–178, 181, 184–186, 188–190
- morphology, 4, 31, 35, 44, 62, 143, 174, 175, 205, 206, 208, 215, 217, 224, 225, 227, 230, 264, 297, 321, 337, 338
- “multicolored” Raman probe, 117, 118
- multiwalled nanotube (MWNT), 87, 88–93, 100, 101, 124–126, 348, 349, 353, 354, 356, 361
- MWNT. *See* multiwalled nanotube
- Nafion, 99, 104, 105, 124, 127, 342, 356, 361
- nanocasting, 302
- nanocluster, 2, 6, 7, 32, 34, 104, 337
- nanocomposite, 17, 335–349, 352–361
- nanocrystalline, 7, 18, 19, 335, 343
- nanodot, 5
- nanoelectronic device, 17, 18, 30, 349
- nanofiller, 336, 337, 355
- nanomaterial, 1–3, 5–8, 10–15, 17–23, 29–31, 35–37, 44, 45, 52, 53, 55–58, 60, 66, 72, 98, 114, 141, 335, 337–339
- manufacturing, 14, 15
- properties, 12, 13
- nanoparticle (NP), 1–3, 6, 7, 10–12, 16–21, 34, 35, 41, 66, 67, 87, 88, 92, 93, 103–105, 115, 116, 119, 121, 124, 126, 127, 134, 141–151, 153–184, 186–190, 268, 298, 321, 335–339, 344–348, 354–361
- nanophotonics, 18
- nanopore, 44, 241, 242
- nanoporosity, 292
- nanoporous membrane, 19
- nanorod, 3, 18, 29, 46, 66, 147, 155–158
- nanoscale material, 22, 23, 338, 341
- nanoscience, 7, 22
- nanoshell, 149, 156–158
- nanosphere, 154–156, 159
- nanostucture, 1, 3, 7–10, 13, 14, 16–19, 22, 23, 29–31, 35, 36, 38, 41, 42, 47, 52, 57, 58, 62, 67, 70, 71, 154, 157, 186, 187, 243, 261, 292, 336–339, 341, 343, 344, 349, 354, 358, 359
- nanotechnology, 1, 7, 8, 17–19, 21–23, 190
- nanotools, 17
- nanotube, 2, 5, 7, 14, 17, 18, 29, 30, 44–47, 53, 54, 56, 57, 59, 68, 72, 87–101, 103, 105–108, 110, 114, 116–118, 120, 122–124, 128, 130–134, 335–337, 344, 349, 350, 352, 353, 355, 360, 361
- nanotube field-effect transistor (NTFET), 95–97, 101, 105, 108, 110–114, 133
- nanotube resonator, 130–132, 134
- nanowire, 2, 3, 5, 7, 13, 17, 18, 21, 23, 29–57, 59–73, 117, 335, 336, 339, 361
- diameter, 35, 48, 60
- nanowire field-effect transistor, 47
- nanowire sensor, 56, 57, 59, 60, 63, 68–71

- network, 56, 68, 95, 100, 104–110, 130, 181, 208, 225, 249, 296–299, 338, 357
- network sensor, 68
- NH₃. *See* ammonia
- nitrogen dioxide (NO₂), 57–61, 63–66, 69, 70, 101–105, 133, 134, 232, 233, 235, 236, 244, 245, 250–252, 256, 258–263, 266, 268, 298, 303, 321, 327, 342, 343, 353
- nitric oxide (NO), 17, 20, 22, 23, 35, 68, 87, 93, 100, 103–106, 112–114, 123, 125, 126, 132, 133, 165, 167, 168, 174, 175, 211, 216, 219–221, 225, 228, 233–236, 240, 244, 248, 250, 251, 253, 254, 258, 266, 268, 270, 271, 275, 316, 319, 324, 327, 339, 345
- NO. *See* nitric oxide
- NO₂. *See* nitrogen dioxide
- noble metal, 338
- noble metal–based nanocomposite, 355
- noise, 127, 133, 169, 176
- noncovalent interactions, 99, 122, 160
- NP. *See* nanoparticle
- NTFET. *See* nanotube field-effect transistor
- n*-type semiconductor, 51
- O₂. *See* oxygen
- “OFF state,” 95
- ohmic contact, 50, 247
- oligomer, 144, 347
- oligonucleotide, 144, 148, 150, 160, 163
- “ON state,” 95
- optical characteristics, 47, 204
- optical glucose sensing, 120, 121
- optical measurement, 237, 239, 241
- optical properties, 5, 30, 41, 50, 52, 98, 118, 134, 141, 144, 153, 154, 164, 170, 209, 238, 344, 346
- optical sensing, 154, 157, 158, 161, 164, 169, 237, 317
- optical sensor, 53, 120–122, 134, 153, 159, 169, 188, 189, 237–240, 243, 323, 327
- organic ligand, 142, 143, 151, 159, 169, 171, 189
- organic–organic nanocomposite, 337
- oxidizing gas, 57
- oxidizing reagent, 211
- oxygen (O₂), 2, 4, 18, 21, 35, 41, 49–51, 54, 57, 58, 60, 62, 63, 66, 67, 91, 94, 102–105, 127, 217–219, 235–237, 244, 245, 250, 253–255, 257, 260, 266, 291, 294, 312, 316, 317, 319, 321, 324, 327, 340, 357
- oxygen deficiency, 54
- P123, 299
- PANI, 338, 346–349, 354, 356, 357, 360
- Pd, 3, 66, 67, 93, 104, 106, 143, 144, 148, 175, 183, 245, 247, 250, 251, 254–257, 266, 268, 292, 295, 356, 357, 360, 361
- pentane drying, 220
- peptide, 96, 101, 112, 118, 160
- performance enhancement, 63
- pH test, 162
- photolithography, 14, 30, 56, 111, 114, 272
- photoluminescence, 5, 6, 52, 70, 118, 210, 216, 226, 232–237, 240, 258, 260, 261, 267, 318
- photoluminescence quenching, 232–234, 236, 267
- photoresist, 55, 212, 219
- physisorption, 99, 103, 292, 293
- piezoelectric MCNP sensor, 188
- piezoelectric sensor, 185, 186
- plasma etching, 205, 272
- plasmonic coupling, 158
- platinum (Pt), 3, 20, 60, 61, 66, 67, 70, 104, 124, 126, 127, 143, 144, 148, 149, 169, 171, 175, 177, 205, 211, 214, 221, 223, 250, 251, 255, 256, 273, 292, 294, 295, 315, 319, 325–327, 342, 348, 355–358, 360, 361
- PLD. *See* pulsed laser deposition
- polarization interferometry, 243
- poly(ethyleneimine) (PEI), 99, 104, 105
- poly(metaphenylenevinylene) (PmPV), 99
- poly{(5-alkoxy-*m*-phenylenevinylene)-*co*-

- [(2,5-dioctyloxy-*p*-phenylene)-vinylene]
(PAmPV), 100
- polymer, 7, 13, 16, 18, 44, 46, 53, 66, 68, 96,
98–100, 103–105, 107, 110, 133, 134,
144, 160, 175, 184, 187, 267, 298, 299,
317, 318, 336–338, 344–350, 352–355,
357–361
- polymer-based nanocomposite, 337, 338, 344,
345, 347, 357
- polystyrene sulfonate (PSS), 99, 114
- polyvinyl pyrrolidone (PVP), 99, 349
- pore, 44, 47, 59, 93, 204–210, 213, 215–218,
220, 221, 224, 225, 227–230, 237, 238,
240, 241, 243, 247, 253–256, 261, 264,
265, 268, 272, 275, 292–299, 302, 303,
315, 316, 323, 326, 327
- porogen, 298, 299, 302
- porosification, 205, 206, 210–214, 216, 218,
220, 221, 225, 226, 240, 265, 267, 272, 275
- mechanism, 206
- porosity, 60, 204, 205, 207–210, 212–221, 240,
246, 249, 250, 264, 265, 275, 292–298,
303, 311, 312, 328, 339, 344
- porous films, 150, 205, 215, 221, 264, 293
- porous layer, 205, 207, 211, 213, 216–221,
224–227, 229, 241, 243, 246, 247, 249,
258, 261, 262, 264, 265, 275, 295
- porous material, 204, 208, 210, 220, 237, 243,
245, 248, 249, 255, 256, 258, 259, 261,
264, 265, 274–276, 292, 293, 298, 302, 328
- porous membrane, 303
- porous semiconductor, 203–205, 208, 209,
220, 221, 226, 227, 229, 237, 238, 245,
246, 250, 254, 255, 259, 261, 264, 265,
274–276
- porous semiconductor gas sensor, 259
- porous silicon (PSi), 203–213, 215–220,
226–230, 232–252, 255–276
- humidity sensor, 228–230
- luminescence, 260
- microcavity, 240
- oxidation, 268
- surface modification, 267
- thermal conductivity, 209
- porous silicon layer, 204, 208, 210, 212, 213,
215, 216, 229, 238–240, 242, 243, 247
- PPy, 348, 353, 354, 356–358, 360
- precipitation, 145, 150, 176, 188, 297, 298
- processability, 344, 347
- protein detection, 110, 118, 134
- protein, 99, 101, 108, 110–112, 114, 117, 118,
121, 133, 134, 148, 151, 160, 163, 166,
181, 235, 347, 359, 361
- PSi. *See* porous silicon PSS. *See* polystyrene
sulfonate
- Pt. *See* platinum
- p*-type doping, 51
- p*-type semiconductor, 100, 112, 325
- pulsed laser deposition (PLD), 31, 340
- PVP. *See* polyvinyl pyrrolidone
- Q1D. *See* quasi-one-dimensional
- Q1D nanomaterial, 30, 44, 53, 57, 58, 60
- Q1D nanostructure, 29–31, 35, 36, 41, 42, 52,
57
- Q1D structured sensor, 70
- QCM. *See* quartz crystal microbalance
- QCM biosensor, 187
- QCM sensor, 185–187
- quantum dot, 5, 7, 17, 18, 29, 117, 121
- quantum effect, 13, 142
- quartz crystal microbalance (QCM), 161,
185–189
- quasi-one-dimensional (Q1D), 29–31, 35–38,
40–42, 44–58, 60, 68, 70, 72
- quenching effect, 235–237
- Raman scattering, 115, 117, 118, 170
- Raman sensor, 115
- Raman spectroscopy, 70, 98, 118–121, 134, 209
- recovery time, 65, 68, 102, 103, 105, 107, 108,
230, 237, 244, 250, 257, 267, 353
- redox, 23, 124, 126, 181, 183, 186, 188, 319,
343, 357

- reducing gas, 57, 103
refractive index, 70, 116, 157, 158, 165–167,
169, 204, 216, 218, 237, 239–243, 258
replication, 302–304
resistance, 6, 56, 57, 59–62, 70, 72, 103, 106,
170–176, 178, 179, 209, 211, 225, 246,
249, 254–256, 261, 264, 268, 343, 347,
349
resistive gas sensor, 291–293, 296, 299, 303,
319, 320
resistivity measurement, 102
reverse micelle, 143, 339, 358
ripening, 297
RNA, 151, 160, 167, 168, 359
Rugate filter, 241, 242
- sacrificial layer, 270–273
SAW. *See* surface acoustic wave
SB. *See* Schottky barrier
SBA-15, 295, 318
scanning probe electrochemical method, 338
scanning tunnel microscope (STM), 4, 8, 9
Schottky barrier (SB), 62, 66, 95, 97, 250, 251,
253–255, 275
Schottky barrier–type junction, 66
Schottky barrier–type sensor, 250, 253, 255
Schottky contact, 250, 254, 255
Schottky diode, 254, 255
Schottky diode sensor, 250
SEC. *See* size-exclusion chromatography
selective gas sensing, 293
selectivity, 20, 57, 63, 66, 68–70, 72, 103, 108,
110, 112, 114, 126, 127, 133, 134, 142,
147, 152, 159, 166, 169, 171, 183, 188,
190, 233, 243, 253, 254, 258, 263, 268,
271, 274, 275, 293–296, 302, 303, 315,
316, 319, 320, 327, 341, 361
self-assembled monolayer, 23, 183, 184, 187
self-assembly, 16, 17, 22, 31, 43, 132, 146, 147,
150, 160, 174, 299, 338
semiconducting, 5, 7, 44, 49, 57, 70, 88, 89,
93–97, 101–103, 109, 114, 122, 123, 207,
291, 293, 298, 299, 303, 319–321, 323,
352
semiconductor, 1, 5, 7, 14, 16, 22, 30, 35, 39,
41, 44, 50, 51, 54, 70, 94, 95, 100, 103,
112, 203–210, 213, 220–222, 224, 226,
227, 229, 237, 238, 240, 245, 246, 250,
251, 253–255, 257–259, 261, 264, 265,
274–276, 292, 297, 319, 321, 325, 337,
339–341
semimetallic, 88, 89, 94
sensing behavior, 57–59, 65, 69, 70, 174, 175,
304, 360
sensitivity, 20, 23, 56, 59–64, 66–68, 70, 72,
102–105, 108, 110, 112, 115, 118, 123,
124, 126, 127, 130, 132–134, 142, 147,
149, 152, 157, 158, 160, 162, 164, 166,
169–171, 176, 183, 185–189, 226, 228–
230, 232, 236–238, 240, 241, 243–248,
250, 253–257, 259–261, 264–268, 275,
293, 295, 297, 302, 303, 318, 321, 327,
339, 340, 343, 344, 347, 349, 353, 354,
361
sensor array, 23, 69, 70, 73, 104, 105, 134, 152,
171, 185, 189, 273, 274
sensor device, 55, 71, 325
sensor recovery, 65
sensor refreshing, 230
sensor sensitivity, 59, 232
SERS. *See* surface-enhanced Raman scattering
SiC. *See* silicon carbide
silicon carbide (SiC), 220, 221, 223, 225, 228,
265, 276
silica, 149, 156, 157, 171, 294, 295, 301–304,
315, 317, 318, 321, 322, 337, 342, 350,
351, 356, 360, 361
silicon porosification, 210, 213, 214
silver (Ag), 18, 66, 104, 115, 116, 124, 126, 127,
134, 143, 144, 145, 148, 154, 155, 156,
158, 164, 169, 184, 185, 247, 254, 321,
322, 342, 357, 358, 360
simultaneous monitoring, 258
single cell, 211

- single-stranded DNA (ssDNA), 99, 104, 105, 108, 122, 124, 125, 160, 348, 356
- single-MCNP optical sensor, 169
- single-nucleotide polymorphism (SNP), 109, 110
- single-walled carbon nanotube (SWCNT), 88, 89, 92, 93, 337, 353, 354
- single-walled nanotube (SWNT), 5, 69, 70, 88, 89, 92–112, 114, 115, 118–123, 131, 342, 348–351, 353, 356
- sintering, 297, 298, 352
- SiO₂, 38, 47, 49, 52, 55, 56, 60, 95, 96, 102, 106, 108, 111, 112, 114, 131, 217, 240, 262, 268, 294, 301, 302, 342, 356, 358, 360
- size control, 35
- size effects, 13, 48, 52
- size-exclusion chromatography (SEC), 93
- size-dependent properties, 2, 355, 358
- size-dependent thermal melting, 3
- SnO₂. *See* tin oxide
- SNP. *See* single-nucleotide polymorphism
- sol, 45, 297–299, 302
- sol-gel, 45, 296–299, 337, 340, 342, 350
- method, 45, 296, 297, 337
- synthesis, 298, 299
- solid–solid interface, 296
- solution-phase growth, 30, 41, 43, 72
- sonication, 345, 350
- source (S), 48, 63, 95, 96, 109, 111, 112, 114, 115
- specific surface area, 10, 19, 209, 267, 292, 293, 299, 302, 353
- spectroscopic properties, 96, 122, 134
- spin coating, 145, 149, 298, 302, 345
- SPR. *See* surface plasmon resonance
- spray coating, 149
- spray pyrolysis, 298, 340
- ssDNA. *See* single-stranded DNA
- stability, 9, 14, 17, 36, 63, 67, 68, 72, 105, 127, 128, 142, 144, 151, 180, 187, 190, 233, 234, 255, 260, 262–264, 266–268, 270, 274, 275, 298, 318, 337, 339–341, 345, 347, 354, 359–361
- stabilization, 10, 21, 262, 263, 267, 268, 350
- standard semiconductor, 220, 222, 250
- starch, 99, 104, 105
- stepwise self-assembly, 146, 147
- STM. *See* scanning tunnel microscope
- structure director, 298, 299
- structure matrix, 302, 303
- structure replication, 302–304
- substitutional doping, 98, 100
- substrate, 23, 33, 36, 37, 41, 43, 47, 49, 55, 56, 60, 91, 92, 95, 101, 103, 106, 108, 111, 112, 130, 131, 145–147, 158, 167, 174, 189, 204, 205, 209, 211–215, 217–219, 221, 226, 228, 247, 270, 271, 273, 298, 338, 347, 353, 357, 358, 360
- supercritical drying, 216, 220, 298, 340
- superlattice, 39, 70, 145
- supramolecular aggregate, 299, 302
- supramolecular structure direction, 302
- surface acoustic wave (SAW), 132–134, 185, 189, 322
- surface acoustic wave (SAW) device, 132, 134
- surface area, 10, 18, 19, 38, 56, 68, 71, 72, 94, 124, 127, 166, 176, 180, 204, 208, 209, 241, 243, 267, 292, 293, 299, 302, 311, 312, 321, 337, 339, 353, 360
- surface atom, 10
- surface-enhanced Raman scattering (SERS), 115–117, 119, 170
- surface functionalization, 7, 144, 147, 352
- surface passivation, 51, 52
- surface plasmon, 6, 116, 142, 153–155, 158, 164–166, 169, 358
- surface plasmon resonance (SPR), 116, 142, 154, 155, 164, 165, 358
- biosensor, 167
- imaging, 166–168
- sensor, 164–167, 170, 188
- surface reaction, 237, 241, 248, 297
- surface-to-volume ratio, 3, 30, 47, 53, 56, 61, 103, 147, 187, 204, 217, 292, 293, 303
- surfactant, 42, 43, 93, 94, 110, 111, 122, 143, 213, 299, 318, 338, 344, 350, 352

- SWCNT. *See* single-walled carbon nanotube
SWNT. *See* single-walled nanotube
synthesis, 7, 8, 14–17, 20, 23, 29–31, 33–35, 38, 40–42, 55, 72, 89–93, 100, 141–144, 147, 150, 156, 176, 291–293, 296–299, 302–304, 315, 316, 318, 321, 338, 339, 341, 344, 345, 349–351, 357
synthetic polymers, 99
- Taguchi sensor, 292
- TEM. *See* transmission electron microscopy
temperature, 2, 3, 6, 9, 19, 34, 35, 38, 41, 42, 45, 46, 49, 53, 54, 59–61, 69, 87, 92–94, 102, 103, 105, 122, 133, 146, 153, 154, 160, 171, 172, 179, 180, 188, 204, 209, 212, 213, 217, 219–221, 227, 228, 230, 234, 245, 247, 249, 250, 253, 254, 256, 257, 259, 260, 264, 270, 272–274, 292, 297–299, 302, 303, 322–325, 339, 341, 343, 345, 352, 353, 361
template, 30, 31, 43–47, 60, 70, 93, 160, 298, 299, 302–304, 315, 316, 321, 338, 339, 344, 354, 357, 358, 360
synthesis, 338
template-based growth, 31, 43
thick film, 267, 295, 298
thin film, 7, 18, 29, 103, 115, 133, 167, 171, 238, 241, 298, 302, 323, 343, 346, 354
three-dimensional structure, 204
threshold voltage, 48, 63, 64, 108, 112
tin oxide (SnO₂), 36–38, 41, 43, 48, 50, 54, 57–62, 66, 67, 69, 70, 72, 255, 256, 292, 294, 295, 298, 299, 302, 319, 321, 322, 339, 342–344, 347, 355, 356
TiO₂. *See* titanium oxide
titanium oxide (TiO₂), 4, 42, 44–46, 52, 54, 57–59, 69, 240, 251, 298, 337–339, 342, 343, 346–348, 354, 356, 360
top-down method, 14–16, 22, 30
toxic organic vapor, 132, 134
transmission electron microscopy (TEM), 3, 31, 32, 34, 35, 39, 42, 43, 149, 154, 155, 225, 298, 304
triode sensor, 128
- valence band, 94, 95
van Hove singularity, 94, 96
vapor deposition technique, 358
vapor–liquid–solid (VLS), 31, 33, 35, 37, 38
vapor–solid (VS), 31, 41, 62, 63, 129, 222
vapor–solid growth, 41
VLS. *See* vapor–liquid–solid
VS. *See* vapor–solid
- WO₃, 42, 44, 45, 59, 294, 299, 303, 339
work function, 50, 56, 95, 175, 257
- x-ray diffraction (XRD), 298, 341
XRD. *See* x-ray diffraction
zeolite-modified electrode (ZME), 321
zeolitic framework, 313
zeolites, 6, 294, 299, 300, 311–328, 344
 adsorptivity of, 311
 applications based on, 325
 as conductometric sensors, 324
 as filters, 311, 315, 319, 327, 328
 as high-surface templates, 316
 as host materials, 316
 as humidity sensors, 318
 as preconcentrators, 321
 catalytic activity of, 326
 chemical sensors based on, 311, 312
 classification of zeolite-based chemical sensors, 312
 in mixed potential sensors, 327
 ionic conductivity of, 323
 lattice, 313, 324
 membrane, 315
 properties of, 312
zinc oxide (ZnO), 5, 8, 18, 21, 30, 34–38, 40–43, 45–58, 61, 63–68, 70–72, 292, 302, 303, 321, 339, 342, 344
ZME. *See* zeolite-modified electrode
ZnO. *See* zinc oxide

INDEX

- actinides, 139, 142
- air–fuel ratio, 294, 310, 311, 315
- alkali metal ion, 134, 135, 137, 138, 147, 158, 292
- alkaline earth metal ion, 133, 134, 136
- alumina, 19, 36, 37, 105, 233, 296, 356
- β -aluminas, 291, 332, 333, 336, 337, 343
- Na β -alumina, 296, 332–337, 339, 340, 343
- Sr β -alumina, 296, 332, 336, 337, 339–341, 344
- aluminum, 9, 26, 44, 316, 319, 324–331, 339
- amine, 7, 8, 31, 38, 43, 81, 144, 153, 167, 176–178, 210, 234, 242, 276
- ammonia gas sensor, 34
- amperometric sensor, 18, 19, 45, 156, 204, 211, 214, 293, 294, 313, 314, 353
- antibody, 9, 77, 84, 98, 204, 206, 212, 221, 223, 226, 229, 231–233, 239, 243, 244
- aqueous solution, 10, 96, 98, 127, 139, 150, 206, 216, 245, 246, 268, 281, 336, 355
- artificial cell membrane, 206
- artificial receptor, 96, 219
- β -aluminas, 291, 332, 333, 336, 337, 343
- bacteria, 34, 90, 91, 93, 95, 206–209, 212, 221, 226, 230, 232, 234, 236, 247
- bilayer lipid membrane, 213
- bioelectronics, 239
- biological membrane, 213, 219
- biological system, 4, 84, 161, 232, 234, 247
- biomaterials
- antibody, 204, 206, 212, 221, 223, 226, 229, 231–233, 239, 243, 244
- DNA, 203, 221, 223, 225, 227–229, 232, 233, 236, 238–241, 243
- lipid, 207, 209, 213–222, 226, 229, 231, 234, 236, 241, 242, 244–247
- lipid bilayer, 213, 214, 216, 218, 220, 222, 229, 236, 241, 244
- protein, 207, 211, 215, 220–224, 230, 232–234, 236, 241, 243, 244
- green fluorescent protein, 232
- whole cell, 212, 230, 231
- biomimetic sensor, 82, 96, 202, 221, 223, 232, 234, 239, 241, 248
- biomimetic system, 201–262
- biomolecular interaction, 81, 243, 244
- biosensor, 92, 93, 201–204, 206–208, 211, 212, 215, 216, 218–225, 227–230, 232–239, 243, 244, 247, 263–265, 267, 268, 274–276, 279–283, 351, 354, 355
- bulk polymerization, 80, 107
- bulk polymer monolith, 89
- calcium zirconate, 322
- calixarenes, 117–200
- calixarene, 123, 127, 130, 132, 133, 136, 138, 139, 142–144, 147, 155, 156, 158, 164, 167, 169–176, 179–181, 222, 247
- calix[4]arene, 121, 124, 127, 129–131, 133, 134, 137–139, 141–144, 149–151, 153, 155–159, 161, 165, 167, 169–171, 173–175, 177, 181
- calix[6]arene, 123, 131, 134, 155, 172
- calix[8]arene, 132, 134

- calix[*n*]arene, 121–124, 128, 129, 132, 139, 152, 153
- conformation, 119, 121, 129–132, 134, 138, 144, 154, 165, 170, 174
- infrared spectra, 128
- nuclear magnetic resonance (NMR) spectra, 129, 172, 174
- physical properties, 48, 127, 201, 227, 265, 268, 356
- synthesis, 4, 7, 8, 27, 77, 81, 83–85, 88, 89, 100, 105, 107, 108, 117, 119, 120, 123–125, 132, 139, 144, 149–152, 155, 167, 173, 212, 225, 226, 233, 283, 305, 324, 335, 336, 361, 366, 368
- ultraviolet spectra, 128
- capacitance sensors, 354
- carbohydrate array, 230
- carbon dioxide sensor, 337–339
- carbon monoxide sensor, 37, 56
- carbon nanotubes, 228, 367, 368
- cell-based sensors, 238
- cerium oxide, 296, 343
- cesium, 53, 133, 134, 142, 144, 147
- chain-growth polymerization, 7
- CHEMFET, 57, 59, 266, 267, 280, 354
- chemical polymerization, 8, 47
- chemical recognition, 6, 79, 266, 282
- recognition cavities, 103
- recognition site, 46, 77, 80, 84, 103, 108, 147, 228, 229
- chemisorption-adsorption technique, 10
- chemoresistive sensor, 357
- chloroform, 17, 23, 32, 36, 42, 44, 45, 53, 58, 88, 124, 146–148, 180
- chromogenic material, 137, 143
- chromophoric heterocyclyl azocalix[4]arene, 153
- CO sensor. *See* carbon monoxide sensor
- CO₂ sensor. *See* carbon dioxide sensor
- colorimetric vesicles, 217
- conductometric sensors, 39, 100, 354, 356
- ammonia sensor, 31
- carbon dioxide sensor, 337–339
- carbon monoxide sensor, 37, 56
- hydrogen sensor, 291, 294, 324–326, 329, 331, 337
- nitric oxide sensor, 55
- volatile organic compounds, 23, 24, 32, 37, 40, 60, 360, 364, 365
- copper, 37, 99, 133, 151, 308, 316, 318, 329
- covalent imprinting, 81–83, 88, 89, 107, 108
- covalent interaction, 81, 82, 85, 101, 108, 233
- cross-linker, 83, 86–88, 99, 102
- CTO, 359–361
- CTO (titanium-substituted chromium oxide). *See* CTO
- CTO-based sensor, 360
- current-reversal mode, 316, 317
- debutylation, 126
- defect chemistry, 298, 304, 320, 332
- dendrimer-based sensor, 232
- deoxidation control, 308, 318
- diamond, 133, 273–277, 283
- dip coating, 10, 23
- ditopic molecular receptor, 175
- ditopic receptor, 135, 161, 170, 175
- DNA, 79, 221, 223, 225, 228, 232, 233, 236, 238, 276
- hybridization, 203, 227, 277
- sensing, 203, 229, 239–241, 243
- double calix[4]arene, 177
- dual probe, 139
- dummy molecule, 84
- electroactive sensing material, 156
- electrochemical cell, 6, 16, 51, 292, 293, 316, 336
- electrochemical gas sensor. *See* electrochemical sensor
- electrochemical polymerization, 8, 11, 34
- electrochemical sensor, 19, 28, 51, 53, 56, 82, 106, 135, 216, 327
- ammonia sensor, 31
- nitric oxide sensor, 55

- pH sensor, 21, 26, 27, 54, 266, 351, 354
polyvinyl chloride-based sensor, 52
electrodeposition, 12
electronic nose, 34, 41, 354, 355, 359, 362
electropolymerization, 9, 12, 82, 90, 100, 101, 203
emulsion polymerization, 89
enzyme, 9, 20, 80, 92, 96, 204, 205, 211, 212, 215, 218, 223–225, 231, 233, 237–239, 241
enzyme-based sensor, 223, 224
enzyme-embedded hydrogels, 211
enzyme immobilization, 211
- fiber optic sensor, 6, 23, 27, 80, 355
fluorescence, 21, 24, 98, 133, 136–138, 149, 154, 167, 172, 203, 206, 212, 222, 247, 283, 365, 367
dye, 20, 22, 23, 26, 27, 217, 225–227, 229–231
marker, 217, 226, 237
resonance energy transfer, 224, 282
fluorescence-doped vesicles, 217
fluoroionophore, 135, 140–142, 162, 163
functionalization of polymers, 13
- Ga₂O₃-based sensor, 360
gallium nitride
 applications, 274, 279
 properties, 274, 279
green fluorescent protein, 232
- H₂ sensor. *See* hydrogen sensor
HCl sensor, 23
heavy metal ion, 52, 142
humidity sensor, 16, 351, 355–357
hydrogel, 27, 46, 54, 87, 210–212, 221, 362, 365
 enzyme-embedded hydrogels, 211
 enzyme immobilization, 211
 hydrogel matrixes, 211
 swelling-responsive biosensor, 211
hydrogen, 3, 6, 8, 17, 29, 30, 33, 37, 54, 56, 57, 80, 88, 89, 101, 123, 128, 129, 131, 155, 161, 164, 167, 170–175, 205, 233, 266–268, 274, 278, 291, 292, 294, 313, 316, 320, 322, 324–332, 337
hydrogen sensor, 51, 291, 294, 324–326, 329, 331, 337, 355
- implantable biosensor, 236, 237
imprinting, 77–116
 control of, 92
 covalent, 80–83, 85, 88, 89, 91, 92, 101, 104, 107, 108
 cross-linker, 83, 86–88, 99, 102
 dummy molecule, 84
 in situ, 82, 90, 99, 100, 106
 initiator, 80, 83, 88
 matrix, 77, 81, 84–87, 91, 98, 99, 102, 103
 methods, 79, 80, 82, 86, 89, 96, 103, 105, 107
 molecular, 77–80, 82–84, 86–88, 91, 92, 96, 98, 101, 103–108
 monomer, 81, 83, 85–88, 99, 101
 noncovalent, 80–82, 91
 polymerization, 79–93, 100–102, 104, 105, 107, 108
 porogen, 88, 89, 91, 92, 101
 principles, 79, 93
 protocol, 89, 90, 107
 target molecule, 77, 82–84, 101, 105
imprint molecule, 79–82, 89, 90
In₂O₃-based sensors, 360
indium nitride, 280
infrared spectra, 128
in situ imprinted polymers, 82
in situ molecular imprinting, 82
integrated chemical sensor, 23
intracellular nanobiosensor, 230
in vivo biosensing, 204, 237
ion conductor, 291–350
 defect chemistry, 298, 304, 320, 332
 ionic conductivity, 292, 295, 296, 302, 304, 305, 324, 332, 333, 337

- mixed conductor, 325, 329
 oxygen ion-conducting solid electrolyte, 322
 proton conductor, 294, 320, 322, 326, 327, 329
 high-temperature, 319, 320, 343
 low-temperature, 291, 319, 331, 343
 superionic conductor, 292
 ionic conductivity, 16, 47, 51, 292, 295, 296, 302, 304, 305, 324, 332, 333, 337
 ionics, 319, 332
 ionophore, 46–48, 52, 53, 134–136, 140, 141, 150, 162, 163, 215, 220, 357
 ionophoric calix[4]arene, 134
 ion-selective electrode, 6, 10, 45, 46, 49, 50, 52, 53, 99, 106, 120, 133–136, 138–142, 147, 162, 163, 237, 351
 ion-sensitive field-effect transistor, 6, 120, 138
 iron, 18, 147, 227, 296, 319, 337, 339–344
 IR spectra. *See* infrared spectra

 lambda sensor, 308
 Langmuir-Blodgett film, 86, 181, 202, 207, 245–247
 of polymers, 11
 in biosensors, 244
 lanthanide, 142, 155
 layer-by-layer self-assembly, 11
 LB film. *See* Langmuir-Blodgett film
 LBL self-assembly. *See* layer-by-layer self-assembly
 ligand/receptor interactions, 214, 220, 244
 lipid, 207, 209, 213–222, 226, 229, 231, 234, 236, 241, 242, 244–247
 lipid bilayer, 213, 214, 216, 218, 220, 222, 229, 236, 241, 244
 liquid metals
 molten aluminum, 324–331
 molten copper, 318, 329
 molten iron, 296, 319, 339, 340, 343, 344
 molten steel, 318, 319
 process control, 340, 343
 hydrogen, 3, 6, 8, 17, 29, 30, 33, 37, 54, 56, 57, 80, 88, 89, 101, 123, 128, 129, 131, 155, 161, 164, 167, 170–175, 205, 233, 266–268, 274, 278, 291, 292, 294, 313, 316, 320, 322, 324–332, 337
 oxygen, 3, 6, 15, 22, 26, 32, 35, 39, 55, 56, 147, 156, 172, 217, 223, 231, 233, 274, 276, 278, 291–294, 296–299, 301, 304, 305, 308–322, 324–326, 329, 337, 339–341, 343, 344, 352, 357, 359, 360, 364, 365, 368
 sulfur, 3, 6, 17, 56, 123–125, 128, 129, 139, 147, 318, 319, 336, 337, 339–344
 low-temperature proton conductor, 331
 luminescent conjugated polymer, 205

 magnetic relaxation, 227
 magnetoresistive biosensor, 235
 mass-sensitive sensor, 356
 membrane, 10, 18, 19, 26, 43, 46–49, 52–58, 95, 96, 98–100, 104–106, 120, 133–136, 138, 141, 142, 150, 205, 207, 209, 221, 229–231, 234, 236–238, 244, 246, 247, 330, 352, 362
 artificial cell, 206
 bilayer lipid, 213
 biological, 201, 202, 204, 206, 210–219
 chemical, 210–212, 215
 hydrogel, 210–212
 enzyme immobilization, 211
 enzyme-embedded hydrogels, 211
 hydrogel matrixes, 211
 swelling-responsive biosensor, 211
 sol-gel matrix, 212, 219
 solid-supported membrane, 216
 mesoporous material, 368
 metallurgical sensor
 deoxidation control, 308, 318
 sulfur sensor for molten iron, 339, 340
 microfabrication, 93, 103, 203, 235, 238, 243
 MIP. *See* molecular imprinting polymer

- MIP-based chemical sensors
- advantages, 92
 - applications, 92, 93, 98, 103, 106
 - biomimetic sensor, 82, 96
 - capacitance sensor, 94
 - conductometric sensor, 100
 - detection principle, 93
 - electrochemical sensor, 82, 99, 106
 - mass-sensitive device, 96
 - optical sensor, 95, 98
 - quartz crystal microbalance (QCM), 95
 - quartz crystal microbalance (QCM biomimetic sensor, 82
 - quartz crystal microbalance (QCM) devices, 90
 - surface plasmon resonance spectroscopy, 98
- mixed conductor, 325, 329
- molecular biomimetics, 234
- molecular imprinting, 77–116, 228, 229
- molecular imprinting polymer, 78, 87, 94, 97, 108
- advantages, 80–82, 92, 100, 101, 106
 - applications, 79, 80, 82–84, 86, 88–91, 93, 98, 103, 106
 - bulk polymer monoliths, 89
 - chemical characteristics, 80, 88
 - heterogeneity of binding sites, 102
 - in situ* imprinted polymers, 82
 - morphology, 77, 86, 88, 101, 104, 107
 - nanostructurization, 103
 - porosity, 88, 96, 101, 102, 106
 - polymer-imprinted beads, 82, 83
 - preparation, 82, 86, 89, 99, 101, 102, 104, 105, 107
- molecular recognition, 21, 87, 88, 103, 105, 119, 206–208, 212, 216, 217, 221, 222, 235, 236, 243, 245
- molecular template, 79, 203
- Na β -alumina, 296, 332–337, 339, 340, 343
- Nafion, 10, 15, 16, 18–20, 22, 26, 49–51, 55–57, 291, 296, 319, 330, 331, 343, 352, 353, 356, 362, 364, 365
- nanobiosensor, 225, 228–230, 241, 248
- nanobiotechnology, 229
- nanocomposite, 18, 32
- advantages, 34, 367, 368
- nanofabrication, 103, 230, 235, 241, 243
- nanoparticle, 96
- gold, 8, 10, 36, 45, 47, 95, 100, 181, 215, 221, 224, 227, 229, 240–244, 264
 - magnetic, 129, 227, 235, 236
 - metal, 2, 5, 10, 15, 16, 22, 48, 52, 53, 60, 80–82, 94, 98, 99, 118, 133–144, 146–150, 153, 156–158, 160, 208, 215, 223, 226, 227, 234, 235, 240, 244, 266, 267, 272, 273, 276, 278, 279, 283, 292, 297, 311–313, 318–320, 325, 328, 332, 336, 339–341, 351–355, 357–361, 364–369
- nanopore, 105, 220
- Nasicon, 292, 332, 337, 339, 352, 356
- natural receptor, 77
- neutral anion receptor, 161, 165
- NH₃ sensor. *See* ammonia sensor
- nitric oxide sensor, 55
- NMR spectra. *See* nuclear magnetic resonance spectra
- noncovalent imprinting, 81, 82
- noncovalent interaction, 80–82, 120
- novel semiconductor materials, 263–290
- nuclear magnetic resonance spectra, 129, 172, 174
- nuclear waste management, 141
- O₂ sensor. *See* oxygen sensor
- optical sensor, 24, 27, 136, 142, 230, 362
- HCl sensor, 23
 - oxygen sensor, 26, 217, 233, 294, 308, 311–315, 317, 318, 329, 340, 341
 - pH sensor, 21, 26, 27, 54, 266, 351, 354
- organic semiconductor, 60, 351, 357, 363
- oxidative coupling polymerization, 8
- oxygen, 3, 6, 15, 22, 26, 32, 35, 39, 55, 56, 147, 156, 172, 217, 223, 231, 233, 274, 276, 278, 291–294, 296–299, 301, 304, 305, 308–322, 324–326, 329, 337, 339–341,

- 343, 344, 352, 357, 359, 360, 364, 365, 368
- oxygen ion-conducting solid electrolyte, 322
- oxygen sensor, 26, 314, 329, 338, 341
- air-fuel ratio, 294, 310, 311, 315
- current-reversal mode, 316, 317
- lambda sensor, 308
- p-tert*-butyl-tetrathiacalix[4]arene, 123–127, 129
- p-tert*-butyl-thiacalix[5]arene, 125
- p-tert*-butylcalix[4]arene, 123, 124, 127, 129, 131, 132, 149, 152, 180
- p-tert*-butylcalix[6]arene, 123, 124
- p-tert*-butylcalix[8]arene, 123, 124, 127, 131
- p-tert*-butylthiacalix[6]arene, 125
- p-tert*-butylthiacalix[8]arene, 125
- PDA. *See* polydiacetylene
- peptide, 79, 82, 84, 86, 94, 95, 206, 208, 209, 211, 215, 216, 218, 220, 221, 224, 234, 240, 241, 243, 244
- perovskite, 291, 296, 319–326, 343, 352
- pH sensor, 21, 26, 27, 54, 266, 351, 354
- phenomenological modeling, 369
- photopolymerization, 100, 101, 106
- photo-responsive ionophoric calix[4]arene, 134
- planar sensor, 51
- plasma polymerization, 9, 14
- platinum electrode, 12, 82, 100, 233, 294, 327, 328
- polyaniline-calixarene composite, 181
- polydiacetylene (PDA), 204–210, 215, 217–222, 231, 245–247, 352
- polymer, 1–76
- conducting, 3, 4, 6–9, 11–16, 21, 22, 26–34, 37–40, 46–48, 50, 54, 58, 60, 61
- deposition, 8–12, 14, 15, 18, 34, 36, 54
- by chemical modification, 9, 56
- by chemisorption-adsorption, 10
- by covalent attachment, 9
- by dip coating, 23
- by electrodeposition, 12
- by Langmuir-Blodgett film casting, 11
- by layer-by-layer self-assembly, 11
- by radio-frequency polymerization, 12
- by solvent evaporation, 10
- by spin coating, 44
- diffusion, 5, 6, 20, 22, 30, 32
- functionalization, 8, 13
- modification, 9, 10, 21, 23, 56
- by composition modification, 15
- by structure modification, 13
- by surface modification, 14, 15
- strategies, 13
- permeability, 6, 12, 26, 50
- properties, 2, 4–7, 12, 13, 15, 16, 20, 21, 23, 24, 26, 30, 32, 34, 40, 41, 45, 47, 48, 51, 57, 61
- stability, 4, 6, 12–14, 16, 20, 23, 26, 34, 40, 48, 50, 54, 55, 61
- synthesis, 4, 27
- by chain-growth polymerization, 7
- by chemical polymerization, 8
- by electrochemical polymerization, 34
- by oxidative coupling polymerization, 8
- by plasma polymerization, 9
- by ring-opening polymerization, 7
- by step-growth polymerization, 7
- polymer-based biosensor
- bacterial sensing, 206, 208, 209, 247
- colorimetric approaches, 209
- conductive polymer, 201–204, 353, 357
- DNA hybridization, 203, 227, 277
- DNA sensing, 203, 229, 239–241, 243
- luminescent conjugated polymer, 205
- molecular imprinting, 77–80, 82–84, 86, 92, 96, 98, 103, 104, 106, 107, 228, 229
- peptide, 79, 82, 84, 86, 94, 95, 206, 208, 209, 211, 215, 216, 218, 220, 221, 224, 234, 240, 241, 243, 244
- polymer-based sensor, 5, 13, 20, 40, 43, 45, 57, 61, 357
- polymeric calixarene, 143
- polymeric chemical sensor
- advantages, 20, 34, 39, 59, 60

- conductometric gas sensor, 27, 28
 - ammonia sensor, 31
 - carbon monoxide sensor, 37, 56
 - materials, 27, 32–34, 38, 39
 - problems, 27, 39–40
 - mechanism, 29, 31–33, 38, 40
 - volatile organic compounds, 32, 37, 40
- electrochemical sensor, 19, 28, 51, 53, 56
 - electrochemical gas sensors, 51, 55
 - ion-selective electrode, 45, 46, 49, 50, 52, 53
 - nitric oxide sensor, 55
 - pH sensor, 54
 - polyvinyl chloride–based sensor, 52
- fabrication, 20, 51, 61
- fiber optic sensor, 23, 27
- optical sensor, 20, 23, 24, 27
 - HCl sensor, 23
 - materials, 20, 23, 27
 - mechanism, 20–22
 - oxygen sensor, 26
 - pH sensor, 21, 26, 27
 - volatile organic compounds, 23, 24
- polymeric field-effect transistors
 - chemically sensitive field-effect transistor, 366
 - insulated-gate field-effect transistor, 57
- polypyrrole, 7, 8, 12, 14, 18, 19, 24, 26, 29, 31, 33–35, 37, 39, 49, 50, 57, 58, 86, 202–204, 362, 365
- polyvinyl chloride–based sensors, 52
- porogen, 91, 92, 101
 - function, 88, 89, 93, 98
 - solvent, 80, 81, 88–90, 100, 105
 - chloroform, 17, 23, 32, 36, 42, 44, 45, 53, 58, 88, 124, 146–148, 180
 - choice of, 81, 85–87
- porous semiconductor, 351
- positively charged anion receptor, 161
- potentiometric sensor, 45, 135, 232, 293, 294, 327
- precipitation polymerization, 89
- protein, 77, 80, 84, 86, 94–96, 105, 206–207, 211, 212, 215, 217, 219–225, 228, 230, 232–234, 236, 239, 241–245, 276
- protein receptor, 220
- proton conductor, 26, 294, 322, 326, 327, 329
 - high-temperature, 319, 320, 343
 - low-temperature, 291, 319, 331, 343
- QCM sensor. *See* quartz crystal microbalance sensor
- quantum dot, 211, 225, 281, 283
- quartz crystal microbalance sensor, 41, 45, 97, 98, 180
- radioactive wastes, 133
- radio-frequency polymerization, 12
- recognition site, 84, 147
- redox switch, 135
- reference electrode, 8, 46, 55, 56, 160, 293, 310, 312, 313, 318, 324–328, 336–340
- ring-opening polymerization, 7
- SAW sensor. *See* surface acoustic wave sensor
- self-assembled monolayer, 10, 100, 223, 242
- semiconductor, 5, 14, 29, 31, 42, 57, 58, 60, 202, 211, 225, 226, 241, 263–265, 267, 268, 270, 274, 275, 279, 280, 356, 359, 367, 369
 - advantages, 266, 277, 282, 283
 - applications, 264, 265, 269, 270, 271, 273–277, 279, 281–283
 - band gap, 271–273, 277, 279
 - conductivity, 264, 270, 272, 274, 277, 278, 281
 - surface chemistry, 265, 266, 269, 270, 276, 280, 282
- semiconductor-based nanostructure, 281
- semiconductor-based sensors
 - advantages, 266
 - CHEMFET, 266
 - parameters, 266
- sensing layer, 20, 36, 37, 39, 96, 367
- sensing membrane, 43, 46, 48, 54, 214
- sensor poisoning, 317
- SERS. *See* surface-enhanced Raman scattering

- SiC. *See* silicon carbide
- silicon carbide, 273–275, 278, 279, 283, 351, 352, 354
- properties, 277
- silicon dioxide sensor, 356
- sintering, 301, 302, 305, 307, 312, 324, 335
- SnO₂-based sensor, 358, 360
- SO₂ sensor. *See* silicon dioxide sensor
- soft lithographic technique, 14, 90
- sol-gel matrix, 208, 212, 219
- solid electrolyte, 2, 16, 45, 291–294, 296, 297, 305–308, 312–314, 317, 319, 320, 322–327, 329, 330, 332, 336–340, 343, 351, 355, 356, 363
- solid-supported membrane, 216
- solvent evaporation, 10
- space-charge effect, 265
- spin coating, 11, 44, 101, 106
- SPR. *See* surface plasmon resonance
- Sr β-alumina, 296, 332, 336, 337, 339–341, 344
- steel, 8, 12, 294, 308, 318, 319, 327, 339, 340, 343
- step-growth polymerization, 7
- sulfur, 3, 6, 17, 56, 123–125, 128, 129, 139, 147, 318, 319, 336, 337, 339–344
- sulfur sensor, 337, 339, 340, 342, 343
- superionic conductor, 292
- surface acoustic wave sensor, 40, 41, 44, 357
- surface-enhanced Raman scattering, 227, 231
- surface plasmon resonance, 23, 98, 214, 221, 233, 243, 351, 355, 359, 365
- surface plasmon resonance spectroscopy, 98
- surface potential, 32, 265–268, 270, 281
- swelling-responsive biosensor, 211
- synthetic receptor, 77, 220–222
- target molecule, 77, 81–84, 101, 105, 119, 232, 233, 235
- templating, 77–116
- tetrathiacalixarenes, 127
- thiacalixarenes, 120, 123, 129, 130, 132, 181
- three-way catalyst, 311
- transition metal ion, 135, 137–141, 147, 149, 153, 208
- ultraviolet spectra, 128, 144
- UV spectra. *See* ultraviolet spectra
- vesicle, 206–210, 213–222, 229, 234, 241, 242, 244, 245
- VOCs. *See* volatile organic compounds
- volatile organic compounds, 23, 24, 32, 37, 40, 60, 360, 364, 365
- WO₃-based sensors, 360
- yttria-stabilized zirconia, 293, 296, 300, 301, 317, 356, 363
- zirconia, 292, 293, 296, 297, 298, 301, 303, 306, 307, 313, 317, 324, 356, 363
- stabilized, 291, 294, 299, 300, 302, 304, 305, 308, 312, 318, 322, 340, 343
- zirconia-based solid electrolyte, 314
- cation diffusion, 301, 303
- fluorite structure, 297, 298

INDEX

- AC measurement, 43
- ADC. *See* analog-to-digital converter
- adsorbate, 25, 56, 60, 66, 156, 244, 334, 343, 344, 418
- adsorption, 56, 60, 343, 470
- adsorption, 4, 5, 7, 20, 22–25, 27, 29, 55–57, 59–61, 64, 66, 70, 74, 81, 91, 94–96, 133, 134, 140, 145, 149, 151, 155–157, 189–194, 196, 197, 201, 202, 211, 216, 217, 223, 231, 241, 243, 244, 250, 261, 269, 271, 272, 274, 275, 301, 322–324, 327, 331, 334, 342–345, 351, 356, 360, 362, 363, 379, 380, 393, 412–414, 423, 425, 427, 428, 463, 469, 503
- affinity measurement, 423, 424
- agglomeration, 80, 132
- AlN. *See* aluminum nitrate
- AlPO₄. *See* berlinite
- aluminum nitrate (AlN), 381, 382
 microfluidic channels, 382
 thin-film-based FBARs, 382
- aluminum phosphate (AlPO₄). *See* berlinite
- AMS. *See* Austrian Microsystems
- analog-to-digital converter, 40, 493
- anisotropic wet etching, 497
- ANN. *See* artificial neural network
- annealing, 64, 75, 79, 80, 86, 88, 96–98, 109, 118, 119, 125, 132, 139, 151, 155, 158–160, 214, 243, 267, 268, 300, 303
- antibody–antigen reaction, 380
- aromatic hydrocarbon, 466, 471
- artificial neural network, 50, 303, 305, 413, 429, 469
- AT-cut quartz, 385, 386, 388, 390, 396, 397, 405, 406, 425
- Au/Co₃O₄ catalyst, 280
- Austrian Microsystems, 490, 504
- Au/TiO₂ catalyst, 279
- automated detection, 447
- ball milling, 80
- band bending, 56, 64
- band gap, 67, 156, 194, 204, 209, 510
- barium titanate (BaTiO₃), 383, 448
- BaTiO₃. *See* barium titanate
- BAW. *See* bulk acoustic wave
- Behrndt, 378
- berlinite (aluminum phosphate, AlPO₄), 384
- biofilm, 380
- biomolecular detection, 493
- biosensor, 1, 3, 5, 7–10, 12, 15, 19, 315, 321, 324, 326, 328, 348, 360, 368, 377, 379–383, 389, 396, 416, 417, 421–425, 428, 493, 494
- boron implantation, 496
- breath analysis, 282
- Bruckenstein and Shay, 379
- BT-cut quartz, 385
- bulk acoustic wave (BAW), 471
- bulk leakage current, 205
- bulk micromachining, 32, 119, 121, 122, 488, 497
- calibration, 22, 32, 39, 44, 45, 48–50, 67, 117, 153, 154, 288, 313, 324, 343, 390, 474

- calixarene, 343, 345, 412, 459, 460, 462, 466
- calorimetric sensor, 5, 261, 266, 267, 269, 272, 283, 287–289, 292, 293, 312, 314, 490–492, 510
- cantilever, 5, 32, 244–249, 322–331, 333–338, 340, 342–352, 354–365, 367, 368, 383, 491, 492, 501, 503–507, 510
- microcantilever, 245, 249, 321–332, 335–338, 340, 342–344, 346, 348–351, 353–362, 364, 367, 368
- nanocantilever, 322, 345, 363, 364, 367
- cantilever-based sensor, 351, 360, 368
- cantilever bimorph sensor, 247, 249
- capacitance-type sensor, 229, 234, 255
- capacitive-coupled field-effect transistor. *See* CC-FET
- capacitive detection, 249, 335, 336, 507
- capacitive sensor array, 493
- carbon monoxide (CO), 11
- carbon nanotube (CNT), 413
- catalysis, 54, 59, 76, 94, 140, 293
- catalyst, 4, 31, 74, 81, 101, 112, 114, 115, 139, 140, 142, 147, 149, 193, 261, 266–268, 271–274, 276–280, 283, 287, 288, 290–296, 299–303, 305, 308, 313, 310, 359, 463
- Au/Co₃O₄, 280
- Au/TiO₂, 279
- film thickness, 277
- Pt/Al₂O₃, 280
- Pt/alumina, 277
- size, 268, 276, 277, 279
- catalytic activity, 27, 133, 272, 277, 287, 302
- catalytic combustion reaction, 272
- catalytic reaction, 65, 81, 84, 209, 213, 305, 464
- cavity length, 274
- CC-FET, 200
- CCD. *See* charge-coupled device
- cell-surface interactions, 380
- ceramic film, 342, 345
- ceramic integration, 267
- ceramic sensor, 78–80, 90, 111, 117
- CH₄. *See* methane
- charge-coupled device (CCD), 328
- chemical cross-linking, 349
- chemical solution deposition, 381
- chemical vapor deposition (CVD), 23, 25, 83, 91, 92, 109, 119, 125, 149, 206, 265, 381, 498
- chemiresistance effect, 58
- chemiresistor, 18–20, 28, 55, 64, 65, 70, 75, 77, 78, 102
- chemisorbed species, 56, 57
- chemisorption, 4, 5, 22, 30, 56, 60, 65, 66, 70, 94, 151, 190, 243, 343, 344, 364
- Christoffel, 378
- cluster analysis, 75, 475
- CMOS, 124, 126, 128, 188, 196, 205, 221, 234, 253, 265, 271, 276, 338, 347, 348, 350, 356, 485–487, 489–498, 500–511
- CMU CMOS MEMS, 498, 500, 502–504
- CNT. *See* carbon nanotube
- CO. *See* carbon monoxide
- coating material, 22, 239–241, 390, 411, 415, 457, 458, 463, 465, 467, 473
- colonic flora, 282
- combustion engine, 209, 211
- complementary metal oxide semiconductor. *See* CMOS
- composite resonator, 379, 403
- conducting polymer, 19, 20, 413, 429
- conductometric gas sensor, 8, 20, 54, 67, 70, 73, 88, 89, 99, 118, 126, 128, 129, 134, 138, 139, 149, 150, 153, 154, 156, 160, 161
- conductometric sensor, 9, 17, 53, 71, 96, 99, 105, 147, 160
- core-shell nanostructure, 138
- Curie, Pierre and Jacques, 378, 448
- CVD. *See* chemical vapor deposition
- cyclodextrin, 452, 453
- damping effect, 331, 332
- data processing, 3, 43, 45, 365
- DC measurement, 43, 270

- Debye length, 58, 61, 63, 64, 81, 100
- deep reactive-ion etching (DRIE), 395, 488, 497, 505
- deflection, 33, 245, 246, 249, 262, 323–328, 330, 333–335, 337, 338, 340, 342, 345, 351, 356, 358, 360, 362, 365
- dehumidifier, 282
- delay line, 449, 456, 464, 466, 469, 470, 508
- desorption, 20, 64, 66, 68, 74, 77, 81, 84, 94–96, 133, 140, 151, 190, 191, 216, 219, 223, 241, 242, 271, 300, 302, 305, 324, 331, 359, 412, 464
- dielectric excitation, 335
- differential scanning calorimetry, 312
- differential thermal analysis, 312
- diffusion, 23, 59, 65, 66, 68, 70, 75, 80, 94–96, 138, 148, 153–155, 193, 194, 197, 199, 209, 213, 217, 219, 222, 223, 241, 242, 250, 278, 292, 415, 456
- diffusor, 308, 309
- dissipative QCM-D technique, 379, 396
 - impulse excitation, 389
 - in situ* measurements, 377, 380, 423, 425
 - interfacial friction, 416, 418, 421
 - liquid measurement, 399
 - viscous shear friction, 421
- DNA, 322, 324, 342, 343, 346, 348, 360, 361, 364, 422, 493
- doping, 19, 20, 25, 27, 55, 68, 69, 79, 80, 84, 100, 108, 111, 112, 116, 117, 124, 138, 139, 141, 142, 144, 147, 154, 199, 206, 207, 265, 326, 339, 340, 458, 488
- DRIE. *See* deep reactive-ion etching
- drug discovery, 10, 12, 312
- dynamic mode, 245, 246, 322–324, 331, 360
- electret membrane, 250, 254
- electric field lines, 232
- electrochemical cell, 9, 65, 415, 474, 493
- electrochemical QCM (EQCM), 415, 428
- electrochemical sensor, 5, 8, 20, 22, 492, 493
- electronic filter, 508
- electronic nose, 8, 9, 66, 90, 364, 365, 382, 411, 412, 428, 429, 470
- electrophoretic deposition, 149
- electrospinning, 103
- electrostatic actuation, 335, 503, 504, 507
- electrostatic excitation, 335
- e-nose. *See* electronic nose
- enthalpy of combustion, 271
- epitaxy, 83, 124, 206
- EQCM. *See* electrochemical QCM
- etching, 32, 83, 109, 112, 113, 119, 121–124, 149, 198, 209, 234, 237, 238, 243, 247, 251, 268, 269, 272, 277, 337, 339, 341, 365, 395, 429, 450, 488, 490, 491, 493, 495–498, 500, 505, 508, 509
- etch stop, 491, 496
- ethanol, 13, 18, 24, 25, 68, 116, 144, 147, 149, 234, 250, 252–254, 275, 303, 305–307, 310, 354, 357, 462, 492, 507, 510
- explosion, 280, 308, 312
- explosives, 2, 322, 358, 359, 413, 462
- Fabry-Pérot interferometer, 274
- F_c-binding proteins, 348
- Fermi level, 56, 57, 59, 69, 140, 190, 191, 193, 194
- FET. *See* field-effect transistor
- FG-FET, 188, 189, 198, 200–202, 205–207, 211, 213, 214, 219, 220, 222, 223
- field-effect transistor, 5, 9, 61, 64, 188, 189, 194, 195, 197, 198, 200, 202, 203, 429
- figure of merit, 147, 264, 265
- film deposition techniques, 345
 - chemical vapor deposition (CVD), 23, 206, 265
 - low-pressure chemical vapor deposition (LPCVD), 498
 - plasma-enhanced chemical vapor deposition (PECVD), 92
 - radio-frequency (RF) magnetron sputtering, 276
- film thickness, 60, 83, 91, 92, 94–96, 132, 134, 242, 277, 403, 408, 412, 452, 453

- first-order sensor, 44
 flammable gas, 30, 114–116, 287
 flexible substrate, 237, 238, 252
 floating-gate field-effect transistor. *See* FG-FET
 flue gas sensors, 209
 force-field calculations, 460
 free carrier concentration, 60, 61
 Frenkel-Kontorova model, 419
 Freon-12, 353, 354
 Freundlich isotherm, 56, 64, 243
 fuel cell, 312
 Fullerene, 8, 21–25, 27

 GaAs, 29, 204, 212, 263, 466, 467, 494, 510
 gallium orthophosphate (GaPO_4), 383, 430
 GaP, 67, 69, 70, 72–74, 109, 113, 114, 123, 124, 139, 156, 194, 197–200, 204, 209, 232, 234, 235, 238, 245–247, 510
 GaPO_4 . *See* gallium orthophosphate
 gas adsorption, 7, 22, 23, 55, 56, 59, 60, 64, 91, 140, 189, 192, 202, 211, 503
 gas chromatography, 282, 350
 GAS-FET, 8
 gasoline, 68, 305, 312
 gas pump, 282
 gas-sensing devices, 161, 192
 gas sensing effects, 54
 gas-sensitive field-effect transistor. *See* GAS-FET
 gas sensor, 5, 7–9, 19, 20, 27, 31, 33, 44, 50, 53, 54, 60, 64, 65–67, 69–73, 75, 77–79, 81–84, 86–91, 93, 97–109, 111–119, 121, 122, 125, 126, 128, 129, 132, 133, 134, 138–141, 143–145, 147–154, 156, 157, 160, 161, 187–189, 198, 205, 209, 211, 214, 222, 223, 242–244, 264, 270, 272, 274, 276, 278–280, 282, 283, 287, 288, 292, 293, 299, 301–303, 305, 308–310, 312, 313, 315, 381, 382, 388, 410, 459, 463–466, 471, 487, 489, 490–492, 494, 496–499, 503–505, 507, 508, 510
 ceramic sensor, 78–80, 90, 111, 117
 high-temperature gas sensors, 67
 hot-wire sensors, 105, 114
 integrated gas sensor, 118, 499
 one-electrode sensor, 105, 107, 109–113, 115–117
 oxygen sensor, 7, 9, 23, 69
 pellistor, 5, 7, 105, 114–116, 118, 261, 267, 268, 273, 283, 287, 288, 290–294, 302, 303, 308
 planar sensors, 81–85
 solid electrolyte-based gas sensor, 65
 thick-film sensor, 82, 89, 90, 96, 131, 153
 thin-film sensor, 9, 90, 94, 96, 99, 131, 151
 gas sensor fabrication, 77, 96
 glucose, 2, 8, 12, 314, 322, 353, 362, 424, 460, 493
 grain size, 62–65, 79, 80, 90–92, 95, 97, 98, 109, 129–133, 142, 153, 154, 156–160

 H_2 . *See* hydrogen
 H_2O_2 . *See* hydrogen peroxide
 halogenated hydrocarbon, 459
 hazardous area, 280
 HCl. *See* hydrochloric acid
 HCN. *See* hydrogen cyanide
 heater, 20, 69, 78, 79, 81–83, 85, 88, 90, 100, 105, 107, 108, 112–115, 117, 119, 120, 122, 124, 144, 145, 147, 155, 222, 232, 244, 253, 266, 268, 272, 287, 288, 290, 291, 293–298, 300, 303, 496, 498
 herbicide, 2, 355
 HF. *See* hydrofluoric acid
 high-temperature gas sensors, 67
 high-temperature operation, 54, 66, 67, 203, 205
 Hooke's law, 329
 host-guest chemistry, 459, 475
 hot-wire sensor, 105, 114
 HSG-FET, 198–200, 202
 human breath, 13, 282
 humidity, 2, 8, 9, 18, 22, 67, 72, 94, 109, 110, 129, 148, 151, 155, 156, 187, 192, 211, 223, 230, 232, 234, 237, 238, 241, 243, 244, 247, 249, 250, 252–254, 278, 282,

- 292, 312, 356, 359, 381, 409, 411, 425,
454, 455, 458, 463, 464, 474, 508
- humidity effect, 156, 454, 458
- hybrid suspended-gate field-effect transistor. *See*
HSG-FET
- hydrocarbon, 2, 8, 13, 14, 29, 65, 116, 148, 194,
209, 212, 261, 283, 303, 342, 343, 360,
459, 466, 471
- hydrochloric acid (HCl), 11, 137, 458
- hydrofluoric acid (HF), 11, 71, 123, 353, 354,
508
- hydrogen, 8, 11, 14, 24, 69, 101, 116, 134, 149,
161, 189, 192–197, 209, 211–223, 239,
240, 247, 250, 254, 261, 268, 270, 273,
276–283, 294, 295, 300, 301, 303, 307,
312, 342, 351, 353, 355, 356, 358, 360,
361, 423, 455, 457, 459, 462, 464, 469,
474, 475
- hydrogen-bonding interactions, 239
- hydrogen cyanide (HCN), 353, 355, 472, 474
- hydrogen peroxide (H₂O₂), 12, 149, 314, 358,
361
- hydrogen (H₂) selectivity, 148, 282
- hydrogen sensor, 101, 196, 211, 213, 220, 223,
268, 278, 280, 281, 295, 303, 351
- hydrogen station, 278, 280–282
- immobilization, 348, 349, 425
- immunosensor, 379, 382
- impregnation, 134, 277
- impulse excitation, 389
- In₂O₃. *See* indium oxide
- indium oxide (In₂O₃), 18, 19, 25, 28, 66, 70–72,
91, 94, 102, 104, 107–111, 116, 129, 130,
132, 138, 142, 144, 148, 154, 156–160,
276, 463
- indium tin oxide (ITO), 113, 129
- injection molding, 342
- ink-jet spotting, 346
- integrated gas sensor, 118, 499
- interdigital transducer, 449
- interdigitated electrode sensor, 232
- interfacial friction, 410, 416, 418, 421
- interferometry, 328
- international standard, 280
- intrinsic carrier density, 204
- intrinsic fundamental noise, 330, 331
- ion implantation, 139
- ionic layer deposition, 149
- $I_{\text{ON}}/I_{\text{OFF}}$ ratio, 207
- ionosorption, 54
- isotherm, 56, 64, 191, 243, 469
- Freundlich isotherm, 243
- Temkin isotherm, 56
- Wolkenstein isotherm, 56
- ITO. *See* indium tin oxide
- Jazz Semiconductor, 505
- Jazz SiGe BiCMOS, 487, 504, 505
- junction isolation, 205, 206
- Kanazawa and Gordon, 379, 408
- Kelvin probe, 192, 202, 203, 215
- key–lock principle, 459
- kinetics, 20, 93, 94, 96, 98, 138, 140, 146, 151,
153, 211, 290, 365, 423, 425, 427, 456,
458, 462
- KOH etching. *See* potassium hydroxide etching
- La₃Ga₅SiO₁₄. *See* langasite
- lab-on-a-chip (LoC), 321, 322, 382, 472, 493
- langasite (La₃Ga₅SiO₁₄), 383
- langasite crystal microbalance, 383, 429
- laser ablation, 23, 91
- laser pulse deposition, 381
- Lawson, 378
- LCM. *See* langasite crystal microbalance
- lead zirconate titanate (PZT), 262–264, 266,
267, 272, 275, 358, 381–383, 448, 449
- LEL. *See* lower explosive limit
- length-to-thickness ratio, 336
- LiNbO₃. *See* lithium niobate
- linear solvation energy relationship (LSER), 457
- lipoprotein, 362

- Lippmann, Gabriel, 378, 448
 liquid measurement, 399
 LiTaO₃. *See* lithium tantalate
 lithium niobate (LiNbO₃), 383, 448
 lithium tantalate (LiTaO₃), 448
 LoC. *See* lab-on-a-chip
 long-term stability, 33, 45, 81, 91, 98, 108, 141, 223, 277, 279, 464
 loss modulus, 399
 lower explosive limit (LEL), 30, 288
 low-pressure chemical vapor deposition (LPCVD), 498
 low-temperature operation, 55
 LPCVD. *See* low-pressure chemical vapor deposition
 LSER. *See* linear solvation energy relationship
 Lundström FET, 189, 195, 196, 197, 221
 Lundström field-effect transistor. *See* Lundström FET
- 2-Mercaptoethanol, 353, 358
 Mason, 378, 384, 403
 mass resolution limitations, 330
 mass sensitivity, 249, 330, 364, 381, 382, 387, 397, 452
 Maxwell model, 398
 mechanical transducer, 363, 380
 membrane, 4, 7–9, 15, 17, 19, 20, 22, 23, 87, 119–123, 126, 135, 142, 145, 148, 149, 243–247, 249–251, 253–255, 264, 268, 269, 272, 276, 277, 293, 294, 298, 300, 357, 362, 382, 412, 413, 415–417, 422, 488, 491
 membrane bimorph sensor, 249, 251
 MEMS. *See* microelectromechanical system
 metal cluster, 140, 141
 metal ion, 2, 7, 74, 149, 343, 355, 356
 metal-organic chemical vapor deposition (MOCVD), 381
 metal oxide, 8, 17, 18, 19, 25–27, 50, 207, 232, 234, 265, 279, 350, 358, 413, 417, 429, 457, 458, 463, 485, 498
 indium oxide (In₂O₃), 18, 19, 25, 28, 66, 70–72, 91, 94, 102, 104, 107–111, 116, 129, 130, 132, 138, 142, 144, 148, 154, 156–160, 276, 463
 indium tin oxide (ITO), 113, 129
 perovskite, 55, 68–70, 262, 263
 tin oxide (SnO₂), 8, 18, 19, 28, 59, 60, 62, 65, 66, 68, 70–77, 79, 80–82, 84, 90–94, 97, 101, 102, 108–113, 116, 129–132, 137, 138, 140–144, 148–160, 267, 275, 276, 295, 300, 310, 463, 498
 titanium dioxide (TiO₂), 18, 19, 25, 27, 28, 55, 59, 67, 68, 70–72, 75, 104, 137–139, 141, 144, 279, 300, 310, 311, 463, 465
 tungsten oxide (WO₃), 18, 19, 28, 67, 70–72, 97, 129, 132, 138, 148, 459, 463–465, 467
 zinc oxide (ZnO), 381, 448, 509
 metal oxide–based sensor, 54
 metal oxide gas sensor operation, 54
 metal oxide–semiconductor field-effect transistor. *See* MOS-FET
 metallic film, 91, 149, 267, 330
 methane (CH₄), 2, 13, 18, 30, 69, 71, 77, 110, 116, 147–150, 152, 161, 274, 275, 282, 287, 288, 290, 299, 300, 302, 303, 305, 310, 464
 microbalance, 5, 19, 324, 349, 353, 377–380, 382, 383, 385–388, 390, 391, 393, 395, 398, 410, 429, 447, 471, 504
 microcantilever deflection detection methods, 324
 capacitive method, 327, 351
 charge-coupled device detection method, 328
 interferometry method, 328
 optical diffraction grating method, 328
 optical method, 325
 piezoelectric method, 328
 piezoresistive method, 326
 microcantilever excitation
 dielectric excitation, 335

- electrostatic excitation, 335
- piezoelectric excitation, 335
- resistive heating excitation, 335
- microcantilever functionalization
 - immobilization, 348, 349, 425
 - silanization, 342
 - surface functionalization, 342
- microdropping, 267, 346
- microelectromechanical systems (MEMS), 125,
 - 126, 268, 269, 292–294, 300, 302, 305, 312, 315, 321, 327, 351, 382, 429, 485–492, 494–498, 500–508, 510, 511
- microfabrication techniques, 488, 508
- micro-hotplate, 99, 118–121, 124, 125, 138,
 - 145, 151, 267, 268, 496–498
- micromachining, 31, 32, 67, 118, 119, 121–126,
 - 161, 292, 298, 337, 386, 395, 486–490, 496–498, 500, 501, 505, 511
 - anisotropic wet etching, 497
 - boron implantation, 496
 - bulk micromachining 32, 119, 121, 122, 488, 497
- CMOS technology, 126, 128, 188, 196,
 - 205, 234, 276, 338, 347, 348, 485–487, 489, 490, 493, 495, 496, 498, 500, 505, 508–511
- CMU CMOS MEMS, 498, 500, 502–504
- deep reactive-ion etching (DRIE), 395, 488, 497, 505
- etch stop, 491, 496
- etching, 32, 83, 109, 112, 113, 119, 121,
 - 122, 123, 124, 149, 198, 209, 234, 237, 238, 243, 247, 251, 268, 269, 272, 276, 277, 337, 339, 341, 365, 395, 429, 450, 488, 490, 491, 493, 495, 496, 497, 498, 500, 505, 508, 509
- Jazz SiGe BiCMOS, 504, 505
- NIST CMOS MEMS technology, 494–498
- photolithography, 81, 83, 90, 109, 113, 123,
 - 125, 234, 251, 338, 340, 395, 450, 488, 489
- post-CMOS micromachining, 490, 496, 505
 - reactive-ion etching (RIE), 234, 247, 277, 395, 429, 488, 491, 500, 501, 505, 508
 - surface micromachining, 32, 119, 121, 123, 124, 488, 489, 501
- micromachining technology, 67, 118, 122, 125,
 - 161, 487, 498, 501
- microstructure, 60, 61, 64, 68, 70, 80, 86, 87,
 - 91, 96, 141, 152, 247, 278, 488, 500
- miniaturization, 105, 118, 161, 245, 292, 321,
 - 326, 350, 355, 364, 367, 382, 394, 428, 473
- MISiC-FET, 189, 210
- missile storage and maintenance, 359
- MLP. *See* multiple-layer perceptrons
- MLR. *See* multivariate linear regression
- MOCVD. *See* metal-organic chemical vapor deposition
- molecular recognition, 4, 324, 360, 449, 457,
 - 461, 462, 466
- moment of inertia, 329, 332
- monolayer, 73, 74, 91, 103, 149, 159, 242, 251,
 - 269, 342, 345, 346, 348, 359, 364, 410, 417–419, 421, 425, 429, 457, 462, 463, 467, 469, 475
- monolithic integration, 119, 511
- MOS-FET, 9, 195, 196, 198–200, 206, 208,
 - 210, 212
- MOSIS, 494, 497, 508
- MQCM. *See* multichannel QCM
- multichannel QCM (MQCM), 392–394, 414,
 - 429
 - miniaturization and integration in arrays, 394
- multiple-layer perceptrons (MLP), 50
- multisensor array, 48, 51, 71, 81, 90, 103, 469
- multisensor environment, 39, 48, 49
- multivariate linear regression (MLR), 49
- myoglobin, 353, 362
- n*-well, 200, 491
- nanoarray, 28
- nanocomposite, 27, 243
- nanoelectromechanical systems (NEMS), 32,
 - 321, 322, 364

- nanoparticle, 157, 300, 360, 429
- nanorods, 25, 125, 381
- nanotips, 381
- nanotribology, 379, 416, 418, 429
- nanowire, 8, 102–104, 242, 243
- NEMS. *See* nanoelectromechanical systems
- nerve agent, 457, 504
- NIST CMOS MEMS technology, 494–498
- nitrogen oxide (NO_x), 2, 12, 18, 59, 65, 71, 113, 209, 212, 359, 463, 464
- noise, 39, 42, 43, 45, 126, 161, 188, 246, 251, 270, 272, 282, 313, 314, 326, 327, 330, 331, 340, 342, 351, 382, 504, 507
- noise equivalent power, 272
- NO_x. *See* nitrogen oxide
- on-chip integration, 335, 485, 486
- one-electrode sensor, 105, 107, 109–113, 115–117
- optical chemical sensor, 509, 510
- optical diffraction grating, 328
- organic vapor, 18, 22, 60, 145, 147, 231, 251, 457–459, 466, 467, 469
- organophosphorus, 469
- organosulfur, 469
- oxidizing gas, 28, 59
- oxygen sensor, 7, 9, 23, 69
- p-n* junction, 204, 206
- packaging, 1, 32, 98, 99, 118, 123, 128, 129, 148, 266, 305, 308, 309, 321, 351, 485, 486, 491, 492, 511
- paracyclophane, 460
- parallel plate, 229, 253, 254, 336
- parallel-plate sensors, 231
- partial least square, 49, 50
- PCA. *See* principal component analysis
- PCP. *See* principal components plot
- PCR. *See* principal component regression
- PDMS. *See* polydimethylsiloxane
- PECVD. *See* plasma-enhanced chemical vapor deposition
- pellistor, 5, 7, 105, 114–116, 118, 261, 267, 268, 273, 283, 287, 288, 290–294, 302, 303, 308
- permittivity sensor, 229–231
- perovskite, 55, 68–70, 262, 263
- perovskite oxide, 69, 263
- pH, 2, 5, 7, 8, 12, 14, 92, 334, 342, 359, 360, 419
- photodetector, 325, 326, 361, 510
- photoexcitation, 145
- photolithography, 81, 83, 90, 109, 123, 125, 234, 251, 338, 340, 395, 450, 488, 489
- physical sensor, 1, 3, 266
- piezoceramics, 383
- piezoelectric effect, 328, 378, 383–385, 448, 458
- piezoelectric excitation, 335
- piezoelectric material, 43, 328, 335, 384, 455, 509
- piezoelectric method, 328
- piezoresistive method, 326
- piezoresistor, 326, 338, 340, 504
- planar sensors, 81–85
- planar template, 135
- plasma-enhanced chemical vapor deposition (PECVD), 92
- PLS. *See* partial least square
- poisoning, 21, 31, 148, 155, 287, 288, 292, 301–303, 308
- Poisson equation, 64
- polydimethylsiloxane (PDMS), 87, 234, 249, 250, 273, 469
- polymer, 8, 9, 17, 19–21, 23, 27, 28, 87, 134, 135, 147, 213, 214, 230–234, 238–242, 244, 247–254, 263, 266, 272, 273, 300, 301, 311, 322, 337, 340–348, 356, 357, 359, 361, 362, 364, 365, 377, 379, 381, 383, 395, 399, 403, 410, 412–416, 422, 428, 429, 455, 457–459, 461, 462, 464, 466, 467, 469, 470, 472, 475, 485, 490–492, 503, 504, 507
- advantages of polymer-based sensors, 20
- conducting polymers, 19, 20, 413
- polymer coatings, 234, 377, 412, 414
- polymer membrane, 251, 272

- polysilicon, 200, 232, 238, 247, 253, 254, 268,
 270, 271, 295, 299, 359, 486, 488, 489,
 495, 496
- poly(vinylidene fluoride) (PVDF), 263, 264,
 273, 381, 383, 429
- porosity, 75, 80, 83, 95, 97, 114, 132, 134, 142,
 153, 154, 243, 302, 303, 460
- porous alumina, 242, 243
- porous silicon, 120, 122, 123, 242, 244
- porous silicon carbide, 242
- position-sensitive detector, 325, 328, 365
- post-CMOS micromachining, 490, 496, 505
- postprocessing, 232, 490, 491, 493, 496, 498,
 501, 502, 508–510
- potassium hydroxide etching (KOH etching),
 269
- potential barrier, 60, 61, 63, 140
- power consumption, 20, 43, 81, 82, 89, 90, 99,
 102, 105, 109, 111, 114, 116, 118, 119,
 124, 129, 152, 161, 188, 244, 245, 267,
 288, 292, 298, 299, 305, 315, 490
- PPR. *See* projection pursuit regression
- preconcentrator, 145–148, 470
- pressure-proof enclosure, 280
- principal component analysis (PCA), 252, 469
- principal components plot (PCP), 50
- principal component regression (PCR), 50
- projection pursuit regression, 50
- prostate-specific antigen, 361
- protective coating, 303
- protein, 15, 134, 135, 313, 314, 324, 346, 348,
 349, 353, 356, 361, 362, 379, 380, 395,
 416, 417, 422–425, 428
- protein adsorption, 380, 425
- PSA. *See* prostate-specific antigen
- PSD. *See* position-sensitive detector
- Pt/Al₂O₃ catalyst, 280
- Pt/alumina catalyst, 277
- PVDF. *See* poly(vinylidene fluoride)
- pyroelectric constant, 262
- pyroelectricity, 261–263, 280, 381
- pyroelectric material, 262, 263, 448
- lead zirconate titanate (PZT), 262–264, 266,
 267, 272, 275, 358, 381–383, 448, 449
- lithium tantalate (LiTaO₃), 18, 263, 266, 272,
 274, 275, 448, 449, 456, 470, 471
- PZT. *See* lead zirconate titanate
- QCM biosensor, 421, 422, 425
- affinity measurements, 423, 424
- antibody–antigen reactions, 380
- cell-surface interactions, 380
- deposited biofilms, 380
- immunosensor, 379, 382
- principle of biosensing, 380
- protein adsorption, 380, 425
- supported lipid membrane, 412
- QCM. *See* quartz crystal microbalance
- QCM-D technique, 379, 380, 395, 396, 421,
 424–426
- QCM electrode, 391
- QCM in tribology
- nanotribology challenges, 416
- superconductivity-dependent friction, 419
- surface corrugation, 419
- Q factor, 246, 324, 363, 379, 388, 389, 391,
 394, 397
- reciprocal, 379
- quartz, 5, 8, 18, 19, 22, 84, 135, 147, 262, 263,
 276, 335, 349, 353, 377–398, 401–407,
 409–412, 414–416, 418, 421–425, 427–
 430, 447–450, 452, 454, 455, 462–468,
 471, 497
- AT-cut crystal, 390, 391
- elastic stiffness, 384, 401
- natural, 378
- single crystal, 378, 386
- synthetic, 378
- quartz crystal microbalance (QCM), 353, 378,
 390, 395, 447, 471
- acoustical (mechanical) impedance, 403, 406
- acoustic parameters, 390
- analytical models, 379
- applications, 377–383, 385–389, 392, 394,

- 396, 402, 406, 409, 412, 413, 415–417, 422, 425, 426, 428–430
- basic principle, 380, 411
- coefficient of amplification, 411
- construction and stability, 387
- disadvantages, 397
- electrical impedance, 403, 404
- electrochemical QCM (EQCM), 415, 416, 425, 428, 430
- electronic circuitry, 389
- equivalent circuit models, 403
- fabrication, 381, 382, 386, 393, 395
- force-frequency and stress stability, 388
- Frenkel-Kontorova model, 419
- inherent sensitivity, 388
- mesa-shaped, 388, 392–394, 428
- multichannel QCM (MQCM), 392–394, 414, 429
- miniaturization and integration in arrays, 394
- pure mass loading, 411, 412
- Q factor, 246, 324, 363, 379, 388, 389, 391, 394, 397
- reciprocal, 379
- QCM resonance frequency, 406, 411
- unloaded, 387, 390, 391, 404, 405, 419
- shift in the resonance frequency, 379, 418
- soft materials, 398, 415, 421
- temperature stability, 382, 388
- Voight model, 398, 422
- quartz resonator, 378, 379, 382, 385, 388, 391–395, 397, 403–407, 409, 410, 423, 425, 429
- radio-frequency (RF), 112, 276, 381
- radio-frequency (RF) magnetron sputtering, 276
- Rayleigh, Lord, 378, 449
- Rayleigh-type SAW, 471
- reactive-ion etching (RIE), 234, 247, 277, 395, 429, 488, 491, 500, 501, 505, 508
- recovery rate, 41
- reducing gas, 18, 30, 59, 60, 64, 65, 68, 72, 74–76, 94, 109, 114, 116, 131, 140, 142, 161, 289–291
- resistive heating excitation, 335
- resolution, 17, 32, 33, 39, 42, 86–88, 90, 112, 125, 126, 206, 270, 271, 326, 330, 340, 348, 351, 353, 356, 362, 388
- resonance frequency, 230, 245, 324, 329–332, 336, 342, 346–348, 350, 356, 358, 363, 364, 378, 379, 385, 387–391, 394, 396, 397, 399, 402, 405–408, 410–412, 414, 415, 418, 419, 422, 425–427, 451, 452, 471, 504, 509
- resonant frequency, 245, 322, 323, 332, 337, 361, 391, 507, 508
- resonant membrane, 246, 251
- resonant microbeam, 503
- resonant operating mode, 329
- resonating cantilever, 249, 351, 492
- response rate, 139, 153
- response time, 15, 17, 22, 33, 39, 41, 65, 67, 69, 77, 82, 111, 119, 128, 129, 142, 150, 151, 154, 203, 221, 222, 231, 232, 242, 243, 247, 252, 253, 262, 289, 292, 305, 309, 355, 362, 452, 456, 462, 464, 466, 474, 491
- reverse leakage current, 204
- reversibility, 25, 68, 219, 239, 242, 358, 362, 448, 456, 457, 475
- RF. *See* radio-frequency
- RF magnetron sputtering. *See* radio-frequency magnetron sputtering
- rheotaxial growth and thermal oxidation, 91
- RIE. *See* reactive-ion etching
- rutile, 72, 73
- safety sensor, 189, 280
- saturation, 33, 39, 42, 215, 220, 357, 510
- Sauerbrey, Günter, 379, 387, 451
- Sauerbrey equation, 451, 452
- SAW. *See* surface acoustic wave
- SAW resonator. *See* surface acoustic wave (SAW) resonator

- Schottky diode, 18, 193, 194, 208–210, 212
- Schottky equation, 57
- screen printing, 83, 86, 87, 112, 149, 267, 300
- second-order sensor, 44
- Seebeck coefficient, 262, 264–266, 269, 270, 276
- selectivity, 4, 10, 19–22, 24, 39–41, 48–50, 66, 72, 77, 81, 102, 116, 119, 129, 139, 142, 145, 147–150, 153, 154, 161, 188, 193, 238–242, 247, 255, 272, 276, 279, 282, 296, 300, 301, 303, 305, 312, 315, 348, 359, 367, 411–413, 424, 456–460, 462, 464, 469–471, 473, 475, 488, 498, 510
- self-assembly, 100, 103, 346, 461
- semiconductor, 7, 9, 10, 11, 18, 21, 24, 25, 28, 53, 54, 56–61, 64, 67, 69, 72, 74, 75, 78, 105–116, 118, 124, 126, 129, 132, 133, 139–141, 148, 149, 188, 193–195, 197, 198, 202, 204, 234, 264, 265, 276, 288, 289, 350, 381, 413, 429, 463, 485, 486, 487, 488, 494, 505, 510
- GaAs, 29, 204, 212, 263, 466, 467, 494, 510
- GaP, 204
- SiC, 25, 204, 205, 209, 212, 242, 243, 311, 337
- sensing effect, 24, 25, 54, 213, 214
- sensing material, 4, 9, 15, 17, 18, 21, 24, 25, 28, 29, 42, 67, 71, 79, 87, 119, 138, 147, 148, 155, 223, 231, 239, 243, 298, 310, 355, 498
- sensing parameter, 39
- sensitivity, 4, 14, 15, 19, 21, 22, 25, 31–33, 39–42, 44, 48–50, 55, 58, 59, 61–65, 67, 68, 70–72, 74–77, 79, 81–82, 86, 89–91, 93, 96, 104, 105, 107–109, 111, 112, 114–116, 129, 132, 134, 138–141, 144, 147, 148, 151, 154, 156, 157, 160, 188, 193, 196, 200–202, 206, 210, 220, 229, 231, 232, 234, 238–240, 242–246, 249, 250, 252, 255, 262, 263, 275, 276, 279, 283, 289, 292, 293, 296, 300, 302, 303, 310, 312–314, 322–324, 326, 330, 331, 336–338, 340, 346, 348, 353–359, 361, 363, 364, 367, 368, 381, 382, 387, 388, 390–392, 394, 397, 413, 414, 416, 452, 456, 458, 460, 464–467, 469, 471, 474, 475, 498, 507
- sensor array, 49, 50, 66, 82, 100, 119–121, 128, 150, 230, 234, 238–240, 245, 255, 321, 337, 346, 351, 357, 365, 413, 469, 470, 493
- sensor selectivity, 119, 145, 147, 148, 153
- SG-FET, 9, 189, 196–199, 202, 211, 214, 220–222
- shear modulus, 386, 399, 401, 403, 404, 408, 411, 412, 414, 415, 425, 452
- signal analysis, 303
- signal processing, 1, 3, 16, 29, 31, 32, 40, 43, 48, 493, 507
- multisensor environment, 48, 49
- single sensor, 41, 48, 49
- signal sampling, 43, 45
- signal-to-noise ratio, 42, 340, 351, 452, 485
- silanization, 342, 462, 463
- silica gel, 282
- immunity to humidity, 282
- silicon-based microcantilever, 337
- silicon carbide-based field-effect transistor. *See* MISiC-FET
- silicon dioxide (SiO₂), 18, 19, 71, 85, 90, 102, 123, 142, 148, 195, 196, 200, 232, 234, 264, 269, 276, 277, 299, 303, 358, 360, 384, 465, 470, 486, 488, 493, 497, 495, 508
- silicon membrane, 250, 254
- silicon nitride (SiN), 206, 251, 269, 293, 322, 334, 340, 349, 356, 358, 360, 364, 486, 488
- silicon-on-insulator (SoI), 128, 205, 251
- SiN. *See* silicon nitride
- SiN membrane, 293
- SiO₂. *See* silicon dioxide
- smart sensor, 29, 31, 32, 43, 211, 469
- advantages, 29
- definition, 29
- SMR. *See* solidly mounted resonator

- SnO_2 . *See* tin oxide
 Sol. *See* silicon-on-insulator
 sol-gel, 79, 80, 83, 109, 130, 134, 262, 266, 343, 463
 solid electrolyte-based gas sensor, 65
 solidly mounted resonator (SMR), 381
 solid-state sensor, 25
 solid-state surface, 56
 solubility interactions, 239, 240
 sorption-induced effect, 343
 sorption model, 343, 345
 space-charge region, 206
 specific surface area, 79, 80, 132
 spill-over, 84, 140
 spray pyrolysis, 83, 91–93, 130, 131, 143, 157–159, 381
 spray pyrolysis deposition, 381
 spring constant, 245, 329–331, 336, 337, 365
 sputtering, 83, 90–92, 97, 102, 112, 113, 119, 130, 132, 139, 149, 214, 242, 243, 265, 267, 269, 276, 345, 382, 450, 457
 static mode, 322–324
 stoichiometry, 54, 55, 65, 66, 91, 97, 132
 Stoney's formula, 333
 storage modulus, 399
 structure control, 129
 sulfur, 13, 155, 302
 supported lipid membrane, 412
 surface acoustic wave (SAW), 8, 22, 447, 508
 Love mode, 381
 thickness shear mode, 379, 386, 390, 397, 429, 471
 surface acoustic wave (SAW) resonator, 403, 447, 449, 450, 452, 454, 455, 464, 466, 469, 470, 508
 surface charge region, 57, 64, 139
 surface coverage, 56, 57, 74, 145, 191, 211, 216–218
 surface electric potential, 57, 58
 surface functionalization, 15, 28, 342
 surface micromachining, 32, 119, 121, 123, 124, 488, 489, 501
 surface reaction, 54, 59, 66, 77, 84, 94, 114, 140, 153, 154, 209, 211, 216, 217
 surface stress, 244–247, 249, 251, 322–324, 332–334, 344, 345, 351, 360–362, 364
 surface stress transduction, 247
 suspended mass, 245
 suspended-gate field-effect transistor. *See* SG-FET
 target gas, 30, 31, 76, 98, 104, 105, 108, 147, 153, 154, 156, 189, 192, 193, 197, 201, 202, 211, 213, 214, 272, 279
 Temkin isotherm, 56
 temperature-controlled phase-transition FET. *See* TPT-FET
 temperature effect, 251
 temperature modulation, 69, 270, 292, 296, 310, 312, 315
 temperature programs, 303
 temperature resolution, 270, 271
 temperature uniformity, 120, 296
 tetramethylammonium hydroxide, 497
 TFBARs. *See* thin-film bulk acoustic resonators
 thermal conductivity, 7, 119, 124, 264–266, 270, 271, 276, 300, 301, 305, 311, 312
 thermal conductivity sensor, 301, 305
 thermal cycling, 117, 154
 thermal evaporation, 91, 101, 345
 thermal imaging, 271, 296, 297
 thermal modeling, 298
 thermal treatment, 86, 96, 97, 109, 157, 158
 thermocouple, 82, 262, 265, 270, 295, 311
 thermoelectric, 5, 8, 261–268, 270, 274–280, 282, 283, 295, 296, 310
 thermoelectric hydrogen sensor, 268, 278
 thermoelectricity, 262
 thermoelectric material, 264, 265, 266, 268, 276, 295
 SiGe, 264–268, 275, 276, 280, 487, 504, 505, 510
 ZnO, 7, 18, 19, 25, 26, 59, 70, 71, 80, 102, 109, 129, 142, 144, 148, 263, 264, 272,

- 328, 335, 381–383, 448, 449, 463, 465,
469, 470, 509
- thermoelectric sensor, 5, 261, 267, 274, 275,
278, 282, 283
- thermopile, 270, 271, 276, 295, 300, 301, 305,
310, 311, 313, 314
- thermopower, 270
- thick-film sensor, 82, 89, 90, 96, 131, 153
- thin-film bulk acoustic resonators (TFBARs),
381, 382
- thin-film sensor, 9, 90, 94, 96, 99, 131, 151
- thin-layer deposition, 337
- thiol chemistry, 342, 348
- THS. *See* thermoelectric hydrogen sensor
- Tiersten, 378
- tin oxide (SnO_2), 8, 18, 19, 28, 59, 60, 62, 65,
66, 68, 70–77, 79, 80–82, 84, 90–94, 97,
101, 102, 108–113, 116, 129–132, 137,
138, 140–144, 148–160, 267, 275, 276,
295, 300, 310, 463, 498
- TiO_2 . *See* titanium dioxide
- titanium dioxide (TiO_2), 18, 19, 25, 27, 28, 55,
59, 67, 68, 70–72, 75, 104, 137–139, 141,
144, 279, 300, 310, 311, 463, 465
- TLM. *See* transmission line model
- TMAH. *See* tetramethylammonium hydroxide
- toxic gas, 30
- TPT-FET, 211, 213, 214, 220–222
- transducer, 3–5, 20, 144, 187–189, 192–194,
197–200, 202, 203, 205, 211, 214, 223,
240, 251, 266, 267, 269, 270, 275, 283,
330, 344, 350, 351, 363, 364, 368, 380,
383, 385, 386, 413, 447, 449–452, 456,
489, 490, 492, 493, 495, 503, 508
- transducer film, 266
- transient response, 44, 93, 152
- transmission line model (TLM), 403–405
- transverse shear wave, 397
- tributyrin, 353, 359
- tungsten oxide (WO_3), 18, 19, 28, 67, 70–72,
97, 129, 132, 138, 148, 459, 463–465,
467
- vertical metal oxide–semiconductor field-effect
transistor. *See* vertical MOS-FET
- vertical MOS-FET, 206, 208
- VIBRIT, flexural piezoceramics, 383
- viscoelasticity, 388, 398, 408, 410
- compliance, 399, 407
- Maxwell model, 398
- shear modulus (storage modulus and loss
modulus), 399
- Voight model, 398, 422
- viscoelastic loading, 379
- viscoelastic properties, 410, 457
- viscous shear friction, 421
- VOCs. *See* volatile organic compounds
- Voight model, 398, 422
- volatile organic compounds (VOCs), 2, 13, 24,
28, 161, 230, 232, 234, 249, 272, 273, 312,
322, 356, 357, 413, 469, 470, 490
- voltage responsivity, 270
- Wheatstone bridge, 105, 114, 290, 291, 327,
336, 340, 351, 504
- Wheatstone bridge circuit, 291, 327, 336
- wide-gap material, 204, 205, 223
- wireless sensing, 161, 252
- WO_3 . *See* tungsten oxide
- Wolkenstein isotherm, 56
- work function, 18, 19, 140, 187–194, 196, 197,
199–203, 211, 213–223
- x-ray photoemission spectroscopy, 300
- Young's modulus, 245, 326, 329, 331, 332, 337
- Zener tunneling, 206, 207
- zeolite, 19, 29, 148, 301, 310, 354, 358, 359,
413, 458
- zero-order sensor, 44
- zinc oxide (ZnO), 7, 18, 19, 25, 26, 59, 70, 71,
80, 102, 109, 129, 142, 144, 148, 263, 264,
272, 328, 335, 381–383, 448, 449, 463,
465, 469, 470, 509
- nanoarray, 28

nanoparticle, 157, 300, 360, 429

nanorods, 25, 125, 381

nanotips, 381

nanowire, 8, 102–104, 242, 243

ZnO-functionalized QCM surfaces, 381

ZnO. *See* zinc oxide

INDEX

- μ -TAS. *See* micro total analysis system
- 2,4-D, 490
- absorption-based optical sensor, 360
- absorption-based sensor, 321, 324, 360
- gas analyzers of absorption type, 333
 - global remote control using absorption spectroscopy, 338
 - infrared absorption, 324
 - near-infrared absorption, 324
 - UV absorption, 330
- absorption spectroscopy, 324, 325, 332–334, 338, 352
- accuracy, 23, 31, 33, 47, 48, 59, 62, 73, 76, 101, 104, 105, 112, 113, 116, 142, 159, 297, 333, 334, 337, 338, 340, 344, 350, 390, 393, 406, 411, 430
- acetylcholine biosensor, 246
- acid–base reaction, 12
- acridinium derivative, 483
- adenosine sensor, 247
- adenosine triphosphate (ATP), 247–249, 265, 450
- sensor, 247
- Ag. *See* silver
- Ag⁺. *See* silver ion
- Al₂O₃. *See* aluminum oxide
- aliphatic amine, 492
- aluminum oxide (Al₂O₃), 36, 145, 173, 206–208, 211, 231, 247, 286, 373, 407
- ammonia (NH₃), 2, 9, 10, 12, 23, 29, 53, 55, 57, 74, 75, 144, 206, 208, 248, 251, 306, 325, 329, 330, 339, 346, 348, 360, 366, 367, 387, 401, 410, 427, 428, 433, 441, 442, 445
- ammonia sensor, 251, 306
- ammonium ion (NH₄⁺), 36, 145, 146, 239, 248
- amperometric gas sensor, 15, 17, 18, 41, 45–49, 53, 62, 67–70, 102, 104
- accuracy, 47, 48
 - potentiometric zirconia-based, 102
 - precision, 47, 48
 - range of linear response, 48
- amperometric sensor, 14, 15, 18, 20–22, 25–28, 32, 40, 46, 48, 49, 53, 59, 67, 68, 70, 76, 102–105, 127, 252
- amperometry, 5, 6, 24, 28, 39, 41, 127, 287–290, 488
- amphoteric site, 193
- aqueous electrolyte, 17, 24, 25, 27, 38, 39, 62, 72, 160, 208
- ATP. *See* adenosine triphosphate
- Au. *See* gold
- auxiliary electrode, 38, 41, 43, 47, 69, 290, 294
- avalanche breakdown, 212
- Ba. *See* barium
- back-side connected ISFET, 174
- barium (Ba), 64, 141, 142, 146, 151, 246, 492
- Bi. *See* bismuth
- biological reaction, 14

- biomolecule, 171–173, 177, 237, 238, 246, 347, 449, 451
 biosensor, 77, 171, 173, 177, 204, 237, 238, 242, 246–251, 263, 264, 290, 296, 297, 299, 302, 312, 380, 407, 408, 428, 435, 438, 447–449, 451, 452
 acetylcholine, 246
 iron (Fe^{3+}) ion, 242
 mercuric ion (Hg^{2+}), 242, 243
 BIOSPICE, 203
 bismuth (Bi), 158, 159, 289, 304
 breakdown voltage, 173, 212, 213, 227, 265
 buffer amplifier, 226, 227
 stages, 226

C–V curve, 177
 Ca. *See* calcium
 Ca^{2+} . *See* calcium ion
 cadmium (Cd), 146, 155, 236, 239–242, 265, 289, 304, 331, 436, 437, 443
 cadmium ion (Cd^{2+}), 146, 154–156, 234, 239, 241, 242, 263
 calcium (Ca), 126, 128, 134, 142, 150, 233, 234, 236, 240–242, 244, 263, 328, 437
 calcium ion (Ca^{2+}), 126, 147, 149, 150, 159, 233, 234, 236, 239–242, 263, 438
 calibration, 19, 47, 48, 51, 52, 61, 70, 72, 73, 138, 141, 159, 160, 240, 252, 253, 256–259, 297, 303, 348, 377, 380, 388, 391, 400, 420, 425, 427, 430, 431, 454, 495
 calibration plot, 159
 capacitance, 107, 173, 178, 180, 185, 193, 198–200, 202, 203, 213, 221, 223, 265, 266
 carbamate, 449, 489
 carbon dioxide (CO_2), 13, 17, 23, 25, 26, 28, 29, 46, 59, 60, 64, 68, 70, 75, 91, 95, 109, 113, 114, 116, 152, 172, 238, 252, 259, 306, 324, 325, 329, 330, 337, 339, 340, 341, 345, 346, 352, 360, 378, 386, 425, 428, 433, 438, 441, 453, 454, 487, 489
 carbon monoxide (CO), 2, 4, 9, 10, 11, 13, 14, 17, 23, 26, 27, 45–48, 50–52, 60, 64, 74–77, 91–93, 95, 96, 101, 103–105, 107, 108, 113, 114, 152, 251, 324, 325, 329, 330, 339, 378, 428, 443, 477, 488
 carrier accumulation, 182, 184, 185
 carrier depletion, 182, 184
 carrier inversion, 182, 184
 catalysis, 14, 291
 catalytic activity, 103
 catalyzed SE/gas reactions, 113
 cationic surfactant sensor, 240
 cavity ring-down (CRD) spectroscopy, 372, 377
 Cd. *See* cadmium
 Cd^{2+} . *See* cadmium ion
 cesium (Cs), 148, 149, 266
 channel aspect ratio, 213, 215
 charge, 3, 5–7, 9–11, 18, 22, 24, 34, 68, 92, 95, 127, 129, 135, 140, 149, 179, 181, 184, 186, 187, 189, 191–194, 196–198, 200–202, 212, 225, 233–235, 248, 267, 346, 349
 chemical oxygen demand, 488, 489
 chemical potential, 3, 35, 95, 194, 268
 chemiluminescence, 315, 316, 321, 347, 348, 360, 362, 421–423, 437, 448, 477, 478, 481, 482, 484–494
 chemical sensing, 477
 chemiluminescence sensing, 477–502
 application for water pollutants control, 485
 chemical oxygen demand, 488
 estrogens, 493
 fungoids, 494
 hydrogen peroxide, 488
 metals, 486
 nitrogen compounds, 491
 aliphatic amines and polyamines, 492
 nitrites and nitrates, 491
 nitroamines, 493
 pesticides and herbicides, 489
 2,4-D, 490
 carbamate insecticides, 489
 DDT, 490
 phenols, 491

- chemiluminescence reagents, 481
 acridinium derivatives, 483
 luminol, isoluminol, and analogs, 481
 peroxyoxalate chemiluminescence, 484
fundamentals, 478
 CL analysis, 478
 methodology of chemical analysis, 484
 outlook, 494–495
chemiluminescence sensor, 484–486, 491
chloride ion (Cl^-), 53, 128, 145, 153, 154, 172, 192, 193, 234, 244, 321, 322, 347, 348, 358, 422, 477–481, 484–495
chloride ISFET, 244
chromium ion (Cr^{6+}), 241
 Cl^- . *See* chloride ion
CMOS technology, 229
 readout circuits, 229
 CN^- . *See* cyanide ion
Co. *See* cobalt
CO. *See* carbon monoxide
 CO_2 . *See* carbon dioxide
cobalt (Co), 2, 4, 9, 10, 13, 14, 17, 23, 26, 45–48, 50–52, 60, 64, 74–77, 91–93, 95, 96, 101, 103–105, 107, 108, 113, 114, 152, 251, 324, 325, 329, 330, 339, 378, 410, 428, 443, 445, 477, 488
conductance, 7, 9, 38, 63, 173, 177, 185, 186, 215, 266
conductive polymer, 9, 11, 30, 407
conductivity, 1, 7–12, 22, 24, 28, 29, 33–39, 61–64, 71, 127, 132, 179, 208, 306, 407
conductometric gas sensor, 7, 8, 22
conductometric sensor, 7, 15, 22, 127
conductometry, 7, 24, 38, 306
control, 14, 19, 23, 55, 59, 63, 70, 71, 76, 105, 116, 117, 177, 208, 224, 231, 263, 264, 276, 277, 283, 285, 297, 304, 338, 342, 346, 347, 381, 399, 433, 434, 477, 478, 485, 486
copper (Cu), 42, 43, 69, 146, 153, 154, 241–243, 331, 348, 409, 411, 412, 437, 442
coulometry, 6, 287, 288
 Cr^{6+} . *See* chromium ion
CRD spectroscopy. *See* cavity ring-down spectroscopy
creatinine biosensor, 248
cross-sensitivity, 52, 74, 100, 101, 416, 425, 434
Cs. *See* cesium
Cu. *See* copper
 Cu^{2+} . *See* cupric ion
cupric ion (Cu^{2+}), 139, 146, 153, 154, 159, 236, 241, 242, 263, 437, 438, 486, 487
cyanide ion (CN^-), 127, 145, 155, 244, 410, 492
DDT, 490
detection limit, 22, 29, 40, 45, 68, 69, 127, 134, 153, 157, 158, 237, 240–245, 247–251, 290, 295, 298, 338, 339, 352, 377, 422, 436, 439, 442, 444, 449, 478, 486–490, 493
DIAL. *See* differential absorption LIDAR
diamond-like carbon (DLC), 208, 209, 266
different electrode equilibria, 92, 94, 118
differential absorption LIDAR (DIAL), 340–342
differential double-layer capacitance, 198, 199, 265
diffuse layer, 193, 198, 202, 204
diffuse-layer capacitance, 198
diffuse-layer model, 192
direct potentiometry, 141
DLC. *See* diamond-like carbon
DNA sensor, 248, 299, 448, 452
dopamine sensor, 248
double-layer model, 191, 193, 200
drift, 48, 51, 57, 61, 143, 159, 172, 173, 177, 204–207, 222, 255, 264, 265, 338, 344, 394, 402
 rate, 205
dual-gun magnetron sputtering, 208, 211
ED. *See* electrochemical detection
EGFET. *See* extended-gate FET
 readout circuit, 228
electrochemical detection (ED), 2, 29, 282, 283, 285, 290, 294, 295, 297, 299–302, 306

- electrochemical gas sensor, 1, 2, 7, 9, 15, 16, 23, 25, 27–31, 33–35, 42, 44, 49, 62, 67, 71, 72, 74–77, 91, 92
- analytical characteristics, 44, 45
- precision and accuracy, 47
 - selectivity, 46
 - sensitivity (lower detection limit), 45
 - stability, 48
- designs and materials, 23
- electrodes, 38
 - auxiliary electrode, 41
 - fabrication of electrodes, 43
 - materials for electrodes, 41
 - sensing electrodes, 38
 - characteristics for sensors with liquid electrolytes, 39
 - electrolytes, 24
 - ionic liquids for electrochemical gas sensors, 28
 - liquid electrolytes, 24
 - nonaqueous electrolytes, 27
 - polymer electrolytes, 33
 - solid electrolytes, 35
 - two-dimensional gas sensors with ionic liquids, 31
 - membranes, 38
- examples, 49
- H₂ sensors with liquid electrolytes, 49
 - H₂ sensors fabricated using polymer electrolytes, 53
 - characteristics, 53
 - methods to improve H₂ sensor performance, 59
 - high-temperature H₂ sensors, 62
- fundamentals, 15
- amperometric gas sensors, 15
 - conductometric gas sensors, 22
 - potentiometric gas sensors, 19
- market, 74, 75
- MEMS and nanotechnology in fabrication, 67–70
- electrochemical potential, 3, 43, 44, 95, 194, 268
- electrochemical sensing, 2, 275, 282, 285, 286
- microfluidic platforms, 282
 - designs and applications, 282
 - detection alternatives, 282
 - electrochemical detection (ED), 282
- electrochemical sensor, 2, 3, 7, 14, 17, 23–25, 31, 33–35, 40, 42–47, 53, 55, 67–72, 74–77, 125, 171, 235, 283, 285, 290, 312, 372, 485
- advantages, 76
 - applications, 70, 71, 76, 77
 - shortcomings, 76
- electrochemistry, 2, 3, 29, 30, 42, 77, 118
- electrochemistry for gas sensors, 2
- fundamentals, 2
 - conductivity/resistance and conductometry, 7
 - current, charge, and amperometry, 5
 - coulometry, 6
 - galvanometry, 6
 - voltammetry, 5
 - potential and potentiometry, 3
- electrode, 2–8, 12–25, 27, 29–33, 35, 38–51, 53–56, 58, 60–62, 65–70, 76, 77, 91, 92, 94–97, 99, 101–110, 114, 118, 126–131, 133–139, 141–160, 171–173, 175, 177, 179, 184, 200, 204, 207, 208, 221, 224–226, 228, 229, 231, 234, 235, 241, 249, 252–258, 260–262, 264–267, 281–292, 294, 295, 297–306, 370, 371, 382, 398, 452
- fabrication, 43, 44
 - glass, 128, 131, 144, 145, 152, 153, 155
 - heterogeneous solid-state, 131, 146
 - homogeneous solid-state, 131, 145
 - internal reference, 160
 - liquid membrane, 128, 131, 150, 152, 153, 155, 156, 158
 - materials of choice, 41–43
 - potential, 137
 - Procedure I, 137
 - Procedure II, 137, 138
 - preconditioning, 141
 - reference, 94, 95, 97

- selectivity, 136
- sensing, 91, 109, 118
- solid-state, 131, 150, 153, 158
- electrolyte, 2, 3, 5, 6, 8–15, 17–20, 22–25, 27–31, 33–49, 51, 53, 55, 56, 58, 61, 62, 64, 67–69, 71–73, 76, 77, 91, 95, 108, 114–116, 128, 132, 135, 155, 160, 175, 177, 191, 193, 198, 200, 203, 204, 208, 224, 234, 239, 252, 253, 255, 266, 305, 453
- aqueous, 17, 24, 25, 27, 38, 39, 62, 71, 72
- nonaqueous, 24, 27, 28
- polymer, 2, 9, 24, 27, 33–35, 40, 43, 53, 55, 61
- solid, 11, 13, 24, 27, 28, 33–37, 43, 62, 64, 68, 69, 71
- ellipsometry, 355
- EMF, 35, 57, 64–67, 95–97, 99–102, 112–114, 116, 135, 160, 236
- ENFET. *See* enzyme FET
- enhancement-mode FET, 179
- environmental monitoring, 68, 118, 263, 302, 312, 382, 433, 434, 486, 488
- enzyme FET (ENFET), 173, 249, 250, 266
- evanescent spectroscopic sensor, 365, 368
- extended-gate FET (EGFET), 175, 176, 180, 205, 210, 211, 228, 246, 265, 266
- extrinsic type of fiber optic chemical sensor, 364
- Fe³⁺. *See* iron ion
- Fermi level, 97, 181, 184, 186, 266
- FET. *See* field-effect transistor
- FET-based sensor, 127
- fiber Bragg grating, 366, 377, 416
- fiber optic chemical sensors, 311–476
 - absorption-based, 360
 - advantages, 380, 381
 - cavity ring-down (CRD) spectroscopy, 377
 - chemiluminescence-based, 347, 361
 - cladding-based, 363
 - classification, 360
 - disadvantages, 380
 - evanescent spectroscopic, 365, 368, 369
 - extrinsic type, 364
 - fiber Bragg grating, 366, 367, 377, 378, 416
 - fluorescence-based, 343, 360
 - hollow-core fiber-based, 378
 - hybrid intrinsic, 380
 - intrinsic, 364
 - microbent, 372
 - optical fiber, 356
 - optode, 370
 - photonic bandgap fiber, 379
 - refractometric, 362
 - surface plasmon resonance (SPR), 349, 374
 - surface-enhanced Raman scattering, 353, 372, 373
- field-effect transistor (FET), 29, 126, 127, 171, 173, 175–180, 229, 231, 239, 240, 242, 247, 250, 255, 266, 267, 285, 479
- FIM. *See* fixed interference method
- fixed interference method (FIM), 138, 236, 241
- flat-band voltage, 181, 186, 187, 267
- fluorescence, 314–316, 319, 321, 343–348, 352, 353, 360–362, 369, 370, 380, 382, 386, 387, 410, 411, 421–423, 425, 430, 434, 435, 441, 444, 448, 449, 451, 455, 477–479, 481, 484, 492
- fluorescence optical chemical sensor, 360
- fluoride (F⁻) ISFET, 244
- front-side connected ISFET, 174
- fuel-cell electrode technology, 39
- galvanometry, 6
- gas, 1–4, 6–20, 22–42, 44–58, 60–62, 64, 67–77, 91–98, 100–114, 116–118, 125, 171–173, 180, 206, 208, 209, 217, 235, 251, 252, 264, 288, 297, 298, 306, 319, 325–330, 333–342, 344, 346–348, 353, 364–367, 369, 377–381, 401, 410, 413, 426, 427, 429–431, 433, 439–445, 453, 480, 486, 491
 - oxidation, 9, 13
 - reduction, 9, 13
- gas concentration, 29, 47, 54, 102, 110, 334, 336, 381

- gas diffusion electrode (GDE), 26, 27, 39–42, 44, 47, 48, 58. *See also* fuel-cell electrode technology
- gas/electrode interactions, 12
- gas-phase decomposition, 98, 109
- gas sensor, 1–4, 7–10, 13–20, 22, 23, 25, 27–42, 44–49, 53, 55, 60–62, 64, 67–72, 74–77, 91–94, 96–98, 100–102, 104, 105, 108–112, 116–118, 173, 208, 251, 252, 326, 380, 431, 439
- hydrogen, 11, 12, 18, 19, 22, 28, 30, 32, 36, 38, 41, 45, 47, 49, 50, 51, 53–56, 58–60, 62–64, 68, 76
- two-dimensional, 8, 31, 32
- gas sensor application, 71
- parameters, 71
- calibration, 72
- humidity, 72
- pressure, 72
- sensor failure mechanisms, 73
- blocking mechanisms, 73
- poisoning mechanisms, 73
- sensor life, 74
- temperature, 71
- gate dielectric, 173, 177, 180, 191, 192, 205, 208, 210, 212, 215, 221, 254
- Gauss's law, 181
- GDE. *See* gas diffusion electrode
- glass electrode, 128, 131, 144, 145, 207, 234, 260–262, 265
- glucose biosensor, 249, 448
- glutamate biosensor, 249
- gold (Au), 8, 14, 25–27, 29, 31–33, 42, 43, 46, 47, 62, 64, 67, 68–70, 91, 93, 101–103, 156, 221–223, 255, 286–292, 298–300, 303, 304, 349, 351, 407, 408, 411, 412, 432, 437, 440, 441, 443
- Gouy-Chapman-Stern model, 173, 193, 198, 202
- gradual channel approximation, 189
- H₂. *See* hydrogen
- H₂ gas sensor, 36, 252
- H₂ sensor. *See* hydrogen sensor
- H₂O₂. *See* hydrogen peroxide
- H₂PO₄⁻. *See* phosphate ion
- hazardous pollutants, 101
- Helmholtz layer, 193, 198, 203, 204, 268
- Helmholtz plane, 192, 193, 266
- herbicide, 156, 489, 490
- herbicide 2,4-D, 490
- heterogeneous solid-state electrode, 131, 146
- Hg. *See* mercury
- Hg²⁺. *See* mercuric ion
- high-temperature H₂ sensor, 62, 66
- advantages, 62
- hollow-core fiber, 378
- homogeneous solid-state electrode, 131, 145
- hot embossing, 280, 287, 288
- HSPICE, 204
- humidity, 32, 34, 43, 61, 62, 68, 72–74, 101, 108, 117, 363, 367, 426, 427, 431, 433, 443–445
- hydrocarbon, 34, 69, 70, 330, 373
- hydrogen (H₂), 9–11, 12, 17–23, 25, 26, 28–30, 32, 34–36, 38, 40–43, 45, 47, 49–68, 72, 74–77, 91, 95, 104, 105, 133, 145, 151, 172, 194, 195, 201, 204, 206, 234, 236, 237, 242, 252, 267, 288, 291, 294, 297, 298, 332, 351, 389, 417, 440, 441, 443, 446–448, 481, 483, 484, 488, 490, 492
- hydrogen bonding, 11, 30, 417
- hydrogen peroxide (H₂O₂), 249, 286–288, 291, 294, 297, 298, 339, 446–448, 450, 477, 481, 483, 484, 487–490, 492, 493
- hydrogen sensor, 19, 22, 36, 38, 49, 51, 53, 56, 58, 59, 62, 63, 68, 76, 252
- immobilization, 173, 237, 244, 247, 248, 286–288, 382, 416–418, 420, 442, 484, 490
- immunosensor, 290, 291, 306, 449, 451, 490
- impedance-based gas sensor, 105, 118
- impedance-based sensor, 108
- impurities, 34, 45, 92, 134, 216, 217, 233, 255, 383, 414
- incremental methods, 141

- industrial applications, 71, 91, 92, 95, 101, 112
infrared (IR), 324–329, 331, 338, 340, 352–354,
373, 407, 413, 414, 430, 432
 spectroscopy, 324, 325, 328, 352, 430, 432
injection molding, 280, 281
insecticide, 264, 489, 490
integrated optical sensor (IOS), 324, 393–395,
399, 400
intercrystalline barrier, 92
interference, 31, 46, 75, 103, 125–127, 129, 137–
139, 142, 145, 149, 151–154, 157, 159,
160, 172, 235, 236, 241, 242, 314, 319,
325, 345, 354, 362, 366, 372, 391, 392,
401, 414, 415, 423, 431, 437, 442, 486, 491
interfering ion, 130, 136–140, 142–144, 150,
160, 235–237, 241, 242, 266
internal reference electrode, 136, 160
internal solution, 136, 160
intrinsic buffer capacity, 198, 267
ion exchange, 128, 133, 140, 236, 383, 395, 436
ion-exchange membrane, 40, 135, 157, 436
 potential, 135
ionic liquid, 14, 24, 28–32, 39, 76, 441
 electrochemical gas sensors, 28
 two-dimensional gas sensors, 31
ion implantation, 60, 206, 231, 244, 383, 395
ionophore, 128–135, 146–158, 160, 207, 233,
236, 238–241, 243–246, 411, 435
ion-selective electrode (ISE), 22, 126–131,
134–136, 141–144, 146, 148, 154, 159,
160, 172, 207, 231, 241, 266
ion-selective membrane, 128, 130, 134, 180,
231, 233, 239, 246
ion-sensitive field-effect transistor (ISFET),
171–175, 177–181, 188, 189, 191, 200,
203–208, 210, 212–231, 233–266, 285
IOS. *See* integrated optical sensor
IR. *See* infrared
iron ion (Fe^{3+}) biosensor, 152, 159, 241, 242, 487
ISE. *See* ion-selective electrode
 classification, 130, 131
 design, 128–130
 analyte recognition, 129
 membrane composition, 129
 sensing elements/ionophores, 128–129
 transducers/detecting system, 129
direct potentiometry, 141
experimental aspects, 141
 precautions, 144
 sources of error, 142
 diffusion, 143
 interferences, 142
 pH, 144
 potential drift, 143
 sample ionic strength, 143
 temperature, 143
incremental methods used, 141
literature, 144
 alkali metal ions, electrodes, 146
 Cs^+ -selective electrodes, 148
 K^+ -selective electrodes, 147
 Li^+ -selective electrodes, 146
 Na^+ -selective electrodes, 147
 Rb^+ -selective electrodes, 148
 alkaline earth metals, electrodes, 149
 Ba^{2+} -selective electrodes, 151
 Be^{2+} -selective electrodes, 149
 Ca^{2+} -selective electrodes, 150
 Mg^{2+} -selective electrodes, 149
 Sr^{2+} -selective electrodes, 150
 glass electrodes, 144
 heavy metals, electrodes, 151
 Ag^+ -selective electrodes, 154
 Bi^{3+} -selective electrodes, 158
 Cd^{2+} -selective electrodes, 155
 Co^{2+} -selective electrodes, 152
 Cu^{2+} -selective electrodes, 153
 Hg^{2+} -selective electrodes, 156
 Ni^{2+} -selective electrodes, 152
 Pb^{2+} -selective electrodes, 157
 UO_2^{2+} -selective electrodes, 158
 Zn^{2+} -selective electrodes, 154
 heterogeneous solid-state electrodes, 146
 homogeneous solid-state electrodes, 145

ISE (*continued*)

- maintenance and storage, 142
- potentiometric titrations, 142
- utility, 135

ISFET, 171–274

- adverse storage environment effects, 259
- applications and market, 263–264
- biasing, 225
- biotechnological process monitoring, 264
- buffer solutions, 256–259, 261
 - pH changes in ambient atmosphere, 259
- chloride ion (Cl^-), 234
- circuit models, 203
- creatinine, 248, 265
- design, 173, 175, 179, 204, 210, 212, 213, 215, 222, 224, 229, 235, 242, 248, 266
 - parameters and procedure, 210
 - specifications, 213
- deviation rate, 258
- encapsulation materials, 222
- fabrication process, 213–215
 - CHIP fabrication, 215
- fluoride (F^-), 244
- fluoride-ion, 234
- glucose, 172, 179, 249, 263, 264
- glutamate, 249, 251, 264, 267
- lactate, 172, 250
- light effects/sensitivity, 254
- measurements by the same or different ISFETs, 260
- malfunctions, 172, 262, 264
 - identification, 262
- penicillin, 250, 264, 267
- pH sensitivity, 191, 200
- readout circuit and instrumentation, 225
- storage in air, 257
- storage-time effects, 256
- triglyceride, 250
- trypsin, 250, 251
- urea, 172, 251
- use in soil analysis, evaluation, and agriculture, 264

- ISFET. *See* ion-sensitive field-effect transistor
- ISFET-based biosensor, 173, 204, 237, 263
- ISFET-based sensor, 203, 239, 244, 246
- ISFET–REFET combinations, 255
- isoluminol, 481

K. *See* potassium

K^+ . *See* potassium ion

lactate biosensor, 250

Langmuir-Blodgett film, 417

LAPS. *See* light-addressable potentiometric sensor

laser micromachining, 281

layer-by-layer nano self-assembly ISFET, 177

LDL. *See* lower detection limit

lead (Pb), 9, 31, 33, 68, 97, 110, 114, 116, 130, 143, 144, 146, 157, 158, 209, 210, 236, 241, 289, 294, 304, 331, 341, 405, 408, 430, 436

lead ion (Pb^{2+}), 146, 154, 157, 158, 234, 241, 242, 263, 408

leakage current, 207, 212, 254

Li. *See* lithium

LIDAR, 340–342

light-addressable potentiometric sensor (LAPS), 177, 178, 266

limit of detection, 19, 25–27, 59, 158, 160, 241, 246, 353, 437, 439, 448

linear range, 129, 154, 160, 200, 240–242, 245, 249, 401, 489

lipophilic additive, 131, 134, 233

liquid electrolyte, 19, 22, 24, 27–29, 33–35, 39, 49, 67, 71

liquid environment, 125, 126, 128, 130

liquid junction potential, 143, 160

liquid membrane electrode, 128, 131, 150, 152, 153, 155, 156, 158

lithium (Li), 2, 13, 15–17, 27, 28, 39, 45, 46, 53, 60, 68, 70, 92, 96, 126, 145–148, 210, 211, 236, 331, 383, 389, 398, 423, 424, 487–489, 491

long-term stability, 55, 66, 92, 96, 101, 110, 118, 175, 245, 246, 282, 432

- lower detection limit (LDL), 22, 29, 45, 69, 240, 290, 298
sensitivity, 45
- low-pressure chemical vapor deposition (LPCVD), 177, 208, 209, 217, 221, 266
- LPCVD. *See* low-pressure chemical vapor deposition
- luminol, 316, 347, 348, 448, 450, 477, 478, 481–483, 486, 488–494
- macroporous silicon, 175, 180
- magnesium (Mg), 36, 40, 41, 49, 50, 147, 150, 155, 239, 240, 243–246, 249, 251, 331, 441, 487, 491
- match potential method, 140
- matrix, 34, 41, 42, 92, 98–100, 110, 128, 129, 131–134, 142, 146, 148, 151, 154, 155, 157, 158, 233, 238, 244–246, 275, 343, 361, 405, 416, 417, 419, 420, 425, 428, 437, 439, 441, 443, 444, 447, 448, 450, 493
- membrane FET (MEMFET), 243, 266
- membrane potential, 129, 135, 136, 233–235
- membrane selectivity, 134, 235
- MEMFET. *See* membrane FET
- MEMS. *See* microelectromechanical systems
- mercuric ion (Hg^{2+}), 146, 151, 153, 154, 156, 157, 242, 243, 263, 437
- mercury (Hg), 6, 145, 156, 157, 243, 252, 304, 338, 340, 411, 422, 431, 436, 437, 492
- metal-oxide semiconductor field-effect transistor (MOSFET), 171–173, 175, 180, 181, 189, 191, 203, 204, 206, 210, 215, 228–231, 253, 254, 266
- methodology, 38, 135, 141, 173, 210, 212, 484
- Mg. *See* magnesium
- microbent chemical sensor, 372
- microelectromechanical systems (MEMS), 67, 76, 77, 109, 116, 221, 266, 400, 423
- microelectrode, 30, 68, 146, 153, 263, 294, 297, 301, 302, 305
- microfabrication, 67, 76, 173, 278–281, 283–285, 299, 306, 307, 324, 394
- microfluidic device, 285, 290–292, 294, 295, 297, 298, 300, 303, 307, 401, 420–422
- aptamer-based sensor, 302
- chemical sensor, 303
- conductometric sensor, 306
- configurations, 283
- DNA sensor, 299
- electrochemical detection (ED), 282
- electrochemical sensor, 283
- enzyme biosensor, 297
- future trends, 306
- immunosensor, 290
- potentiometric sensor, 305
- strengths, 306
- voltammetric sensor, 290
- weaknesses, 306
- microfluidic platforms, 275–310
- casting, 280, 281, 286
- fabrication, 277, 280, 283, 285, 306
- hot embossing, 280, 287, 288
- injection molding, 280, 281
- laser micromachining, 281
- microfabrication, 278, 280, 281, 283, 285, 299, 306, 307
- molding, 280, 281, 286–289
- polymer machining, 281
- microfluidics, 276, 285, 294, 306, 307, 312, 389
- micro total analysis system (μ -TAS), 275, 285
- mixed-potential gas sensor, 98
- mixed-potential sensor, 64, 99, 101, 118
- mixed-solution method (MSM), 136–138
- molecular recognition element, 312, 313, 319–321, 362, 370, 403, 408–411, 416, 417, 437
- MOSFET. *See* metal-oxide semiconductor field-effect transistor
- MOSFET operation, fundamentals
- channel conductance, 185
- concept, 180
- depletion- and enhancement-mode MOSFETs, 188
- flat-band and threshold voltages, 186

- MOSFET operation, fundamentals (*continued*)
- MOS capacitor, 173, 181–183, 185, 186
 - applied gate voltage, 181
 - capacitance, 185
 - zero gate voltage, 181
 - MOS transistor, 189, 206
 - static characteristics, 189
 - cutoff region, 191
 - linear region, 189
 - saturation region, 190
 - technology, 180
- MSM. *See* mixed-solution method
- Na. *See* sodium
- Na⁺. *See* sodium ion
- nanoparticle thin film, 177
- nanostructured oxide, 91, 109, 110
- nanotechnology, 67, 76, 77, 110, 307, 455
- near-infrared (NIR), 313, 319, 322, 324, 325, 327, 328, 330, 338, 346, 352, 353, 365, 430, 441, 454
 - spectroscopy, 324, 325, 328
- negative ion, 244
- Nernst equation, 20, 21, 35, 58, 95, 102, 135, 140, 160, 235, 306
- Nernstian behavior, 22, 92
- Nernstian response, 128, 135, 145, 148, 152, 153, 157, 158, 160, 180, 210, 234, 240–242
- NH₃. *See* ammonia
- NH₄⁺. *See* ammonium ion
- Ni. *See* nickel
- nickel (Ni), 42, 43, 56, 71, 152, 153, 181, 184, 186, 213, 266, 410, 445
- Nicolsky equation, 136, 138, 140
 - limitations, 139
- NIR. *See* near-infrared
- nitrate, 126, 144, 245, 263, 264, 267, 289, 305, 329, 491, 492
- nitrate ion (NO₃⁻), 30, 172, 236, 245
- nitrate (NO₃⁻) sensor, 245
- nitrite, 305, 409, 491, 492
- nitroamine, 493
- NO₃⁻. *See* nitrate ion
- noble metal, 42, 53, 54, 92, 99, 109, 221
- nonaqueous electrolyte, 24, 27, 28
- Non-Nernstian behavior, 58, 96, 97
- NO_x, 9, 91–93, 96, 97, 99, 101, 102, 104–110, 116, 117, 441
- O₂. *See* oxygen
- optical chemical sensor
 - absorption, 313
 - application, 433
 - anion sensing, 438
 - biomedical sensors, 452
 - gas sensing, 439
 - humidity sensing, 443
 - metal-ion sensing, 435
 - molecular sensors, 447
 - optical biosensors, 447
 - pH sensors, 434
 - vapor sensors, 445
 - chemiluminescence, 315
 - configuration, 321
 - fabrication, 400
 - fiber gratings, 415
 - fiber preparation, 414
 - fiber selection, 412
 - immobilization, 416
 - adsorption, 417
 - covalent bonding, 418
 - electrostatic attraction, 418
 - entrapment in polymeric structures, 419
 - interaction of reagent and support matrix, 419
 - Langmuir-Blodgett film, 417
 - optode in solution, 420
 - sol-gel procedure, 419
- light source, 318, 319, 321, 322, 326, 332, 334, 338–340, 344, 348, 352, 355, 362, 364, 370, 373, 377, 384, 385, 387, 391–393, 399, 401, 404, 422, 425
- optical components, 318, 320, 321, 328, 355, 394, 404, 406, 422, 423, 433, 438

- photoreceiver, 396, 430
- sensing materials, 407
 - colorimetric, 408
 - luminescent, 410
- surface plasmon resonance (SPR) probe design, 411
- uncontrolled intensity modulation, 406
- fluorescence, 314
- instrumentation, 318
- molecular recognition element, 320
- optical transduction principles, 312
- reflection, 317
- refraction, 317
- scattering of radiation, 316
- optical chemical sensor, integrated (IOS), 393
 - fabrication, 394–396, 399, 400
 - integrated optics (IO), 393–396, 398–400
 - materials, 394, 395, 400
- optical chemical sensors for flowing systems, 420
- optical chemical sensors for portable instruments, 429
- optical multiple-chemical sensing, 423
- optical planar waveguide chemical sensor (PWCS), 382
 - absorption-based, 387
 - application, 384, 385, 393, 394, 399, 400
 - fabrication, 400
 - fluorescence-based, 386
 - integrated optical sensor, 393
 - interferometric, 391
 - material, 382–384, 388, 389, 391, 393–397, 399, 400
 - refractometric, 388
- optode, 360, 365, 370, 371, 382, 387, 388, 404, 416, 419–421, 444
- optoelectronic nose, 425
- organic anion sensor, 246
- organic-based field-effect transistors, 179
- O-ring packaging, 223, 264
- oxidation, 6, 9, 11–14, 18, 19, 27, 29, 30, 39, 41, 45–47, 56, 58, 59, 66, 93, 96, 102, 109, 127, 142, 204, 208, 211, 215, 250, 265, 266, 281, 286–289, 295, 297, 302, 316, 347, 349, 412, 437, 445, 448, 449, 477, 478, 480, 483, 484, 486, 488–490, 493
- oxygen (O₂), 2, 4, 7, 9–11, 13, 14, 17–19, 23, 26, 29, 31, 38, 45, 56, 58, 60–62, 64, 68–71, 73–76, 91, 94–105, 108–110, 112–117, 133, 172, 206–209, 217, 249, 252, 255, 281, 325, 329, 339, 343, 346, 348, 386, 405, 410, 419, 423–425, 431, 433, 439, 440, 442, 444, 448, 450, 453–455, 481, 483, 488, 489
- oxygen probe, 112–116
- partial redox, 10, 11
- passivation, 208, 215
- Pb. *See* lead
- Pb²⁺. *See* lead ion
- PECVD. *See* plasma-enhanced chemical vapor deposition
- penicillin biosensor, 250
- peroxyoxalate, 316, 478, 484, 489, 491, 492
- pH, 126, 144, 145, 149, 154, 156, 157, 160, 171–173, 175, 177–179, 191, 194, 197, 198, 200–211, 225–229, 231, 234, 237, 238, 240, 242–244, 247–253, 255–265, 267, 277, 311, 324, 345, 360, 386, 387, 407–409, 418, 424, 427, 433–435, 437, 441, 445, 446, 449, 450, 453, 454, 492
- range, 177, 205, 207, 225, 226, 240, 265
- sensitivity, 173, 175, 179, 180, 191, 200, 206, 207, 210, 215, 221, 226, 240, 242, 246, 252, 253, 255, 261, 265
- sensor, 171–173, 175, 177, 204, 207, 210, 231, 234, 237, 244, 252, 263, 264
- fabrication, 171, 175
- pH/CO₂ sensor system, 252
- phosphate ion (H₂PO₄⁻), 246
- pH_{pzc}, 200, 201, 267
- pH-standard buffers, 256
- physical sorption, 8, 13
- planar technology, 153
- planar waveguide chemical sensor (PWCS), 323, 382, 383, 386–388, 391

- plasma-enhanced chemical vapor deposition (PECVD), 179, 208, 209, 211, 267
- plasticizer, 34, 131, 134, 154, 233, 243, 245, 246
- plug-type sensor, 92
- point of zero charge (pzc), 200, 201, 267
- polyamine, 492
- polymer, 2, 9, 11, 12, 20, 22, 24, 25, 27, 30, 33–36, 39, 40, 43, 53, 55–57, 60–62, 68, 131, 133, 134, 144, 147, 177, 179, 223, 233, 234, 238, 239, 244, 245, 247, 255, 265, 278, 280, 281, 286, 291, 294, 343, 344, 362, 363, 374, 379, 384, 389, 394, 395, 399, 404, 405, 407, 410, 413, 417–420, 423, 425, 427, 434–438, 443, 455, 484, 485
- conductive, 9, 11, 30
- polymer electrolyte, 2, 25, 27, 33–35, 40, 43, 53, 55, 61
- polymer machining, 281
- polymeric matrix, 129, 133, 244
- polymeric membrane, 129, 131, 134, 151, 241
- positive ion, 234, 239
- potassium (K), 2, 20, 34, 43, 44, 53, 125, 126, 145–150, 157, 158, 171, 184, 209, 213, 227, 228, 233, 234, 236, 239, 240–245, 251, 266, 299, 311, 328, 331, 332, 336, 338, 349, 388, 426, 427, 438, 453, 489, 491
- potassium ion (K⁺), 2, 20, 34, 43, 44, 53, 125, 126, 145–150, 171, 184, 209, 213, 227, 228, 234, 236, 239, 241–244, 251, 266, 311, 328, 331, 332, 336, 338, 349, 426, 427, 438, 453
- potentiometric gas sensor, 3, 4, 19, 20, 22, 61
- potentiometric selectivity coefficient, 136, 235, 241, 242, 266
- potentiometric sensor, 15, 19, 21, 22, 35, 57, 68, 76, 102, 103, 126–129, 147, 151, 153, 177, 252, 266, 305
- potentiometry, 3, 4, 13, 21, 24, 39, 41, 141, 142, 285
- direct, 141
- precision, 15, 18, 23, 47, 48, 56, 324, 377, 399, 431
- principles, 2, 3, 285, 290, 312, 394, 425, 430, 438, 448, 480
- probe deterioration, 114
- Procedure I, 137
- Procedure II, 137
- pulsed laser deposition, 153, 207, 209, 239
- PWCS. *See* planar waveguide chemical sensor
- pzc. *See* point of zero charge
- radiation, 223, 281, 313–320, 323, 325, 327, 328, 330, 334, 337, 338, 340, 346, 350, 352, 353, 361, 362, 370, 371, 373, 382, 387, 398, 413, 414, 416, 438, 455, 484
- Raman scattering, 352, 353, 372, 373, 455
- reagents, 74, 142, 277, 303, 305, 311, 312, 320, 328, 347, 362, 364, 370, 382, 408, 410, 417, 419, 420, 423, 437, 441, 447, 448, 477, 478, 480, 481, 484–486, 495
- recovery time, 100, 101, 108–110, 112
- reduction, 6, 9, 11–13, 18, 27, 29–32, 39, 43, 45, 46, 55, 56, 58, 62, 68, 92, 96, 101, 102, 127, 254, 286–288, 290, 291, 295, 301, 305, 313, 315, 395, 397, 438, 489, 491, 493
- reference electrode, 4, 6, 7, 13, 15, 17, 19, 20, 23, 25, 30, 41–43, 48, 51, 53, 54, 61, 62, 65, 68, 94, 126, 135, 136, 141, 143, 160, 171–173, 177, 200, 204, 207, 221, 224–226, 229, 231, 234, 252, 253, 255–258, 264, 265, 267, 290, 294, 297, 298, 301–306, 371
- problems, 255
- reference FET, 173
- reflection, 313, 314, 317, 318, 323, 328, 341, 349, 356, 359–362, 367, 369, 371, 377, 380, 383, 390, 397
- refraction, 317, 318, 362, 366, 368, 375, 383
- refractometric sensor, 362
- region ion-sensitive field-effect transistor (RISFET), 178, 179
- reproducibility, 29, 71, 101, 110, 112, 153, 157, 160, 238, 240, 251, 278, 337, 386, 400, 429, 480

- resistance, 7, 9, 22, 38, 106–108, 114, 116, 118, 127, 134, 155, 211, 222, 223, 226, 231, 262, 351, 384
- response time, 4, 9, 23, 27, 29, 38, 39, 44, 53–55, 59, 67, 68, 102, 148–150, 152–160, 207, 238–242, 246, 247, 250–252, 275, 312, 351, 370, 400, 403–405, 407, 420, 431, 441, 443–445, 447, 448
- RISFET. *See* region ion-sensitive field-effect transistor
- Ru. *See* rubidium
- rubidium (Ru), 17, 55, 99, 348, 439, 441, 450, 493
- selectivity coefficient, 128, 136–140, 142, 143, 145, 160, 173, 235–237, 241, 242, 266
- selectivity coefficient value, 138, 139, 242
- semiconductor, 2, 9, 10, 14, 72, 76, 92, 99–104, 109, 118, 155, 171, 178–182, 184, 186, 187, 211, 223, 233, 262, 265–268, 327, 337, 341, 393–395, 399–403
- sensing: gaseous interactions in, 7
- sensing electrode, 8, 12, 13, 15, 18, 20, 23, 25, 35, 38, 39, 41–45, 53, 61, 64, 66–68, 91, 109, 118, 179, 298, 305
- characteristics for sensors with liquid electrolytes, 39
- sensing mechanism, 14, 101, 102, 118, 393, 495
- sensor array, 7, 31, 32, 48, 68, 71, 77, 299, 304, 395, 423, 425, 426, 428, 429
- sensor failure mechanisms, 73
- sensor for dissolved oxygen, 252, 410
- sensor life expectancy, 74
- sensor operation, 23–25, 36, 38, 48, 92, 110, 113
- fundamentals, 92–98
- sensor performance, 37, 53, 55, 58–60, 109, 113, 386, 403, 407
- methods to improve, 59–62
- sensor technology, 53, 76, 112, 116, 117, 400, 434, 455
- separate-solution method (SSM), 136, 140, 150
- silicon dioxide (SiO₂), 145, 173, 175, 177, 179, 180, 181, 188, 193, 196, 206–210, 212–214, 217, 221–223, 233, 238, 239, 247, 249, 251, 267, 268, 357, 383, 394, 396, 440, 443
- silicon nitride, 173, 204, 206, 208, 211, 213, 217, 219, 221, 222, 267
- silicon oxynitrides, 206
- silver (Ag), 27, 31, 42, 43, 46, 51, 53, 54, 103, 128, 139, 145, 146, 153–157, 177, 207, 221, 224, 234, 243, 249, 252, 255, 263, 264, 289–291, 294, 297–299, 304–306, 331, 338, 349, 351, 353, 354, 373, 374, 383, 408, 411, 412, 432, 441, 445
- silver ion (Ag⁺), 27, 42, 43, 46, 51, 53, 54, 103, 139, 145, 146, 153–157, 177, 207, 221, 224, 234, 243, 249, 252, 255, 264, 290, 291, 294, 297–299, 304, 306, 331, 408, 412
- sintering, 98–100, 109, 110, 117
- conditions, 99
- SiO₂. *See* silicon dioxide
- SO₂. *See* sulfur dioxide
- SO₄²⁻. *See* sulfate ion
- sodium (Na), 8, 27, 70, 126, 143, 145–148, 150–152, 156, 172, 184, 212, 213, 223, 234–236, 239, 244, 266, 328, 331, 357–360, 367, 373, 383, 438, 453
- sodium ion (Na⁺), 8, 70, 126, 143, 145–148, 150, 152, 172, 184, 212, 213, 234–236, 239, 244, 266, 328, 331, 357–360, 373, 383, 438, 453
- sol-gel, 208, 209, 211, 239, 246, 286, 294, 389, 417, 419, 420, 435, 439, 441, 443, 445, 447, 450
- solid electrolyte, 11, 13, 24, 33, 35–37, 43, 62, 64, 68, 69, 71, 91, 108, 132
- solid-state electrode, 131, 145, 146, 150, 153, 221
- source follower circuit, 225, 226
- SPICE, 203, 204
- SPR. *See* surface plasmon resonance
- Sr. *See* strontium
- SSM. *See* separate-solution method
- stability, 19, 23, 28, 29, 32, 34, 36–38, 42, 43, 48, 53–55, 59, 62–64, 66, 67, 69, 76, 77,

- 92, 96, 101, 110, 116, 118, 133, 134, 146, 153, 175, 206, 207, 212, 222, 224, 225, 238, 239, 243, 245, 246, 251, 275, 282, 302, 312, 323, 340, 350, 384, 400, 404, 407, 412, 413, 416, 420, 432, 436, 456, 483, 484
- long-term, 92, 196, 101, 110, 118
- static ISFET model, 203
- Stern capacitance, 198, 202, 266
- strontium (Sr), 64, 150, 151, 288
- successive dilution, 160
- sulfate ion (SO_4^{2-}), 17, 29, 141, 142, 151, 154, 157, 236, 246
- sulfur dioxide (SO_2), 2, 14, 17, 23, 26, 28–30, 46, 47, 60, 74, 75, 92, 329, 339, 346, 427, 433, 443
- surface charge density, 196, 197
- surface chemistry, 95
- surface-enhanced Raman scattering, 353, 372, 373
- surface plasmon resonance (SPR), 1, 324, 349–352, 372, 374–377, 388, 390, 404, 407, 411, 412, 427, 432, 440, 443, 445, 449, 451
- surface potential, 177, 178, 182, 184, 195, 200, 226, 248, 253, 256, 268
- Ta_2O_5 . *See* tantalum pentoxide
- Ta_2O_3 gate ISFET–reference electrode assemblies, 256
- tantalum pentoxide (Ta_2O_5), 42, 173, 206–209, 222, 231, 242, 247, 249, 250, 256, 259, 264, 265, 383, 394, 395
- TAS. *See* total analysis system
- tertiary amines, 207
- thermal model, 204
- threshold voltage, 173, 187, 188, 191, 200, 203–206, 210, 212, 213, 215, 225, 226, 229, 231, 248, 253, 254, 258, 267
- titration, 142, 151, 155, 157, 158
- potentiometric, 142
- total analysis system (TAS), 275, 285
- TPB. *See* triple-phase boundary
- trace metals, 486
- transconductance, 173, 210, 213, 231, 266
- transcutaneous CO_2 sensor, 252
- triglyceride biosensor, 250
- triple-phase boundary (TPB), 41, 53, 95–97, 102, 110, 113, 240, 267
- trypsin biosensor, 250, 251
- two-dimensional gas sensor, 31
- types of gaseous interactions in sensing, 7
- gas/electrode interactions, 12
 - biological reaction, 14
 - catalysis and other gas interactions in sensing, 14
 - gas oxidation and reduction, 13
 - physical sorption, 13
 - gas/electrolyte interactions, 8
 - acid–base reaction, 12
 - gas oxidation and reduction, 9
 - hydrogen bonding, 11
 - partial redox, 11
 - physical sorption, 8
- U. *See* uranium
- ultraviolet (UV), 217, 223, 239, 245, 251, 281, 321, 329, 330, 332, 333, 338, 340, 352, 382, 389, 403, 412, 415, 416, 421, 430–432, 436, 492
- uranium (U), 38, 48, 156, 158, 251, 265, 266, 365, 491
- urea biosensor, 251
- UV. *See* ultraviolet
- voltammetry, 5, 6, 14, 125, 127, 285, 286, 288–290, 292, 304
- water pollutants, 477, 485, 486
- control, 477, 485
- YSZ. *See* yttria-stabilized zirconia
- yttria-stabilized zirconia (YSZ), 36, 37, 62, 64, 65, 67, 70, 91–95, 106–110, 112–114, 118

- zinc (Zn), 114, 154, 211, 328, 331, 407, 410, 437
- zirconia, 2, 37, 62, 64, 67, 91, 92, 94–97, 104, 106–110, 112–117
- zirconia-based sensor, 92, 95, 96, 98, 100, 102, 104–106, 110, 116–118
 - markets, 116, 117
- zirconia oxygen probe, 113
 - used in heat treatment industry, 113
 - three major factors affecting accuracy, 113–116
- zirconia sensor, 94, 95, 104, 106, 107, 109, 110, 112, 116
 - industrial applications, 112, 113
- Zn. *See* zinc