

Index

A

- A315 axial flow autoclave turbine, 123
- Acetic acid, 2
- Acetophenone
 - Deloxan AP II/1% Pd catalysis of, 102–103
 - Pd-catalyzed hydrogenation of, 99–100
- Acid value (AV), quality and control testing and, 330
- Active oxygen method, quality and control testing and, 341
- Activity. *See also* Catalysts
 - apparatus standardization, 352
 - of catalysts, 170–171, 351
 - of hydrogen, gas quality, 352
 - at low temperature, 352
 - of oil/hardening capacity/quality of oil, 351–352
 - purchase, 352
- Adsorption
 - catalyst deactivation and, 102
 - catalyst durability and, 172–173
 - and half-hydrogenated intermediate isomer, 165
 - of molecular hydrogen on catalyst surface, 164
 - and precautions/protection from oxidation, 136
 - quality and control testing
 - liquid-solid/adsorption chromatography, 347
- Advanced gas reactors, autoclave design, 128–129
- Agitation, effect on low *trans* hydrogenation, 306–307
- Alkali isomerization, quality and control testing and, 332–333
- Alkali neutralization, and cleansing of crude oil, 34
- Alkynes
 - Deloxan AP II/1% Pd catalysis and, 103
- Analysis
 - oil segregation
 - impurities, 134
- Anchovy/pilchard oils
 - hydrogenation methods
 - characteristics/FA range, 258, 263–265
 - higher melting/fully-saturated hardened oils, 257
 - normal hydrogenation, 265
 - two-stage hydrogenation, 265
- Anisidine value (AnV), quality and control testing and, 341
- Anode, electrocatalytic hydrogenation reaction of, 281
- Apparent volumetric reaction rate (r_{app})
 - substrate concentration and, 89–90
- Arachis* (peanut) oil
 - hydrogenation methods
 - characteristics/FA range, 208–210
 - higher melting/fully-saturated hardened oils, 212–213
 - iso-trans*-promoting hydrogenation, 212
 - iso-trans*-suppressive hydrogenation, 210–211
 - normal hydrogenation, 211–212
- Atomic absorption (AA)
 - spectrophotometry, quality and control testing and, 349
- Autoclave design
 - autoclave diameter, 130
 - current systems
 - advanced gas reactor, 128–129
 - loop reactor, 124–127
 - Lurgi system, 127–128
 - radial/axial flow, 118, 121–124
 - early systems, 116–120
 - flat-blade stirrers, 132
 - gas space, 130–131
 - ratio oil depth, 130
 - temperature control, 131–132
 - turbine agitator mixers, 132–133
 - vacuum, 129–130

- Autoclaves**
 batch (dead-end/circulating)
 hydrogenation and, 35–36
 consistent quality and, 48
 diameter, 130
 hydrogenation methods
 considerations, 273–274
 safety
 conforming features, 321
 opening, 322–324
 relative pressure levels, 322–323
 vent features/safety valves, 322
- B**
Bailey's Industrial Oil and Fat Products, 5
 Barcroft-Warburg Test, quality and control
 testing and, 342
 Batch (dead-end/circulating),
 hydrogenation process
 techniques, 35–36
 Batch reactors, 62–63
 dead-end autoclave and, 118–119
 energy conservation and, 138
 gas-liquid hydrogenation fat-hardening
 process
 temperature/pressure, 101
 Batch recycle reaction loop
 soybean oil with Raney nickel cathode
 Electrocatalytic hydrogenation,
 285–286
 Beef tallow
 hydrogenation methods
 characteristics/FA range, 196–198
 fully-hardened hydrogenation,
 198–201
 ultra-light hydrogenation, 198
 Binary fluid mixtures SC-H₂/Co₂ or SC-
 H₂/C₃H₈
 supercritical hydrogenation coupled
 processes
 FAME to fatty alcohols, 93–95
 GC profiles, 96–97
 Bipolar electrolyzers, 154
 Bleaching
 and cleansing of crude oil, 34
 filtration and, 142
 Bottini, Susana, 69
- Brignole, Esteban A., 69
 Brush, hydrogenation process techniques,
 38–39
 Bubble point line (BPL), of view cell in
 phase equilibria data, 65–66
 BUSS system, suspended catalysts and,
 37–38
- C**
 Calendaring, 140
 Capelin oil
 hydrogenation methods
 characteristics/FA range, 258,
 260–261
 Carbon, fatty acid chain length and, 2–3
 Carbon monoxide (CO)
 effect on catalyst of, 149–152
 shift reaction and, 156–157
 Carbon steel, facilities and, 133
 Carotene, 4
 Castor oil
 hydrogenation methods
 characteristics/FA range, 270–271
 hydrogenation, 271–273
 ricinoleic acid and, 2
 Catalysts
 acetophenone
 Pd-catalyzed hydrogenation,
 99–100
 action of, 14–15
 activity, 170–171, 351
 and adsorption of molecular hydrogen,
 164
 apparatus
 standardization, 352
 catalytic metals/classes, 178
 chromatography, 352–353
 CO effect on, 149–152
 coke buildup in, 106
 commercial
 Engelhard, 183–184
 nickel, 183, 183–184
 suppliers, 184–187
 copper, 177–178
 critical fluid gas-liquid/liquid-catalyst
 interface
 insufficient H₂ at surface, 100–101

- deactivation
 - gas-liquid hydrogenation fat-hardening process, 101–102
 - definition
 - tests in general, 351
 - Deloxan AP II/1% Pd
 - acetophenone, 102–103
 - dilatations, 353–354
 - durability/poisoning and, 171–174
 - filterability and, 169
 - general overview (speed/course), 14–15
 - hydrogen
 - gas quality, 352
 - hydrogen dispersion and, 9–12
 - hydrogenation facility and conditions of, 111
 - hydrogenation methods
 - general overview, 274, 276–277
 - induction/fatigue/poisoning, 15–17
 - low *trans* hydrogenation
 - via catalyst switching strategy, 311–312
 - nanoparticles
 - SC-CO₂, 103
 - necessary characteristics for heterogeneous, 169
 - nickel catalysts
 - commercial, 183
 - consumption/poisoning, 362
 - enhancement, 176
 - general overview, 176
 - historical aspects, 160–161
 - induction and, 16
 - isomer formation, 159
 - modified, 309, 311
 - pore diameters of, 28–30
 - recovery, 182–183
 - trans*-promoting/reusable, 145
 - noble metals/other, 178–179
 - oils
 - hardening capacity/quality, 351–352
 - passivation, 174–175
 - polysiloxane-supported noble metal cyclohexene to cyclohexane, 102
 - pretreatment to diminish poisons, 135–137
 - production
 - dry reduction, 179–181
 - recovery, 182–183
 - storage, 182
 - wet reduction, 181
 - productivity
 - Deloxan polysiloxane-supported Pd/Pt, 80–81
 - purchase
 - low, 352
 - Raney nickel/other nickel, 176
 - reuse of, 145
 - selectivity and, 175–176
 - spent, 45–46
 - split of reaction mixture into phases
 - minimum pressure, 89–90
 - stabilization, 174–175
 - supercritical hydrogenation coupled processes
 - lipase/chromium-free catalysts, 92–93
 - temperature
 - low, 352
- Cathode, electrocatalytic hydrogenation reaction of, 281
- Cell voltages, security and, 155–156
- Center-point system, oil segregation and, 135
- Chromatography, 352–353
- Chromium-free catalysts
 - supercritical hydrogenation coupled processes
 - basic apparatus, 92–93
 - binary fluid mixtures SC-H₂/Co₂ or SC-H₂/C₃H₈, 95–96
 - GC profiles, 96–97
- Chueh-Prausnitz approximation sunflower oil hydrogenation pressure/temperature, 80
- Circulating systems
 - hydrogen distribution and, 112–113
 - hydrogenation process techniques and, 36
- Cis* isomer configuration
 - configuration change to *trans* isomer formation, 159–160
 - defined, 3
 - Deloxan polysiloxane-supported Pd/Pt catalysts and, 80–81

- Cis* isomer configuration (*continued*)
and impact of double bonds on
hydrogenation, 30–31
isomerization (general overview) and, 6–7
from linoleic acid, 166–168
- Cis-trans* equilibrium, isomer formation
and, 162
- Citric acid, and precautions/protection
from oxidation, 137
- Cleansing of crude oil
considerations, 277
degumming, 34
- Clear point, quality and control testing
and, 335
- Cloud point
quality and control testing and, 336
- Coconut oil
hydrogenation methods
characteristics/FA range, 201–202
normal hydrogenation/full
saturation, 202–203
ultra-light hydrogenation, 202
as triglyceride, 1
- Coke buildup in catalysts, 106
- Color
hydrogenation and, 34
quality and control testing and,
349–350
- Commercial catalyst suppliers, 184–187
and purchases, 180–181
- Complete fusion/melting point/clear
point/FAC melting point, quality
and control testing and, 335
- Compressed water, hydrogenation in,
103–104
- Congel point, quality and control testing
and, 336
- Consecutive flow reactor, schematic, 88
- Construction materials, facilities and, 133
- Continuous (fixed-bed) catalyst,
hydrogenation process
techniques, 36–37
- Continuous hydrogenation, 127–128
energy conservation and, 138
- Continuous (suspended) catalyst,
hydrogenation process
techniques, 37–38
- Controlling autoclaves, 146–147
- Converter autoclave design, 116–118
- Copper catalysts. *See also* Catalysts
general overview, 177–178
historical aspects, 177–178
hydrogenation
composition curves of linoleic esters,
23–24
light hydrogenation
color/flavor/odor, 39
positional isomerisation and, 160
- Cottonseed oil
hydrogenation
initial/final oil concentrations, 22–23
hydrogenation methods
characteristics/FA range, 203–205
higher melting/fully-saturated
hardened oils, 206–207
iso-trans-suppressive hydrogenation,
204–205
normal hydrogenation, 205–206
- Coupled process
supercritical hydrogenation
lipase/chromium-free catalysts, 92–93
- Critical fluids
equipment
advantage of continuous, 61–62
batch reactors, 62–63
continuous internal recycle, 63–64
membrane reactors, 63–65
reactor options, 60–61
fundamentals, 53–55
gas-liquid hydrogenation fat-hardening
process
temperature/pressure, 101
historical aspects
pressure variability, 49–50
hydrogenation reactions in, 56–59
low *trans* hydrogenation and, 306
oleochemical synthesis
FAMES to fatty alcohol mixtures, 85
phase equilibria studies
of Bottini-Brignole-Perada-Peters-
Rovetto, 69
EOS, 68
FAMES, 68
thermodynamics, 67

- pressure-temperature, 63–64
 - supercritical. *See* Supercritical fluid hydrogenation
 - Crossfields & Sons Ltd., 160–161
 - Current efficiency, electrocatalytic hydrogenation reaction of, 282–283
 - Cyclic ethers, Deloxan AP II/1% Pd catalysis and, 103
 - Cyclization/polymerization
 - general overview, 357–358
 - hydrogenation process techniques, 41–43
 - Cyclohexene to cyclohexane hydrogenation
 - polysiloxane-supported noble metal catalysts, 102
- D**
- Dead-end/circulating
 - hydrogen quality and, 151–152
 - hydrogenation process techniques, 35–36
 - Degumming
 - and cleansing of crude oil, 34
 - Deloxan AP II/1% Pd hydrogenation
 - acetophenone, 102–103
 - space-time yields with, 86
 - Detergent-range alcohols, 85
 - Dew point line (DPL), of view cell in
 - phase equilibria data, 65–66
 - Differential thermal analysis (DTA), quality and control testing and, 338
 - Dilatations, general overview, 353–354
 - Dilatations/solid-fat index, quality and control testing and, 336–337
 - Discontinuous hydrogenation, 127
 - Double bond
 - adsorption and sulfur-containing catalysts, 46
 - cyclization/polymerization and, 41
 - impact on hydrogenation of, 30–31
 - linkage to catalyst atoms, 5–8
 - selectivity II (S_{II}) and, 31
 - Drop/flow/pour points, quality and control testing and, 336
 - Dry reduction, catalyst production and, 179–181
 - DuPont facility (North Carolina), 107
 - Durability/poisoning, catalysts and, 171–174
- E**
- Eckey method, quality and control testing and, 342
 - Economics
 - continuous (suspended) hydrogenation and, 38
 - copper catalysts and, 39
 - hydrogenation and, 1
 - hydrogenation facilities and, 111
 - oil segregation and, 133–134
 - Edible oils. *See* Electrocatalytic hydrogenation
 - Efficiency
 - electrocatalytic hydrogenation
 - solid polymer electrolyte (SPE) reactor, 295
 - Electrical equipment
 - safety and, 327
 - Electrocatalytic hydrogenation
 - low-*trans* spread oils via blending
 - soybean oil (partially hydrogenated), 304
 - reactions
 - anode, 281
 - cathode, 281
 - current efficiency, 282–283
 - extent of hydrogenation/selectivities, 284
 - overall olefinic organic compound, 281
 - power consumption (PC), 283
 - production rate (PR), 283
 - side, 281–282
 - trans* FA isomers, 284
 - solid polymer electrolyte (SPE) reactor
 - efficiency/cell voltage, 291
 - efficiency/selectivity, 295
 - FA profiles for canola/cotton seed oil, 293
 - FA profiles for soybean oil, 291–292
 - schematic, 289–290

- Electrocatalytic hydrogenation (*continued*)
 temperature, 293–294
trans isomer content for canola/
 cotton seed oil, 293
trans isomer content/IV for soybean
 oil, 291–292
 water as anode/oil as cathode, 290
 soybean oil (partially hydrogenated)
 FA composition/chemical and
 physical analysis, 301–302
 IV properties, 303
 low-*trans* spread oils via blending,
 304
 odor intensity scores, 301–302
 solid fat content/temperature, 303
trans FA/stearic acid content,
 303–304
 soybean oil with H₂ gas
 FA profiles with modified Pd
 catalyst cathode, 299–300
 materials/operating conditions for
 SPE reactor, 297
 production rate (PR)/power
 consumption for PEM reactor,
 299–300
 selectivity, 298
 temperature, 295, 297–298
 soybean oil with Raney nickel cathode
 batch recycle reaction loop, 285–
 286
 current density/electrolyte oil
 content, 286–287
 drawbacks, 288–289
 FA profiles/*trans* isomer content,
 286–288
 initial experiments, 284–285
 radial reactor, 287–288
 schematic, 285
 solid polymer electrolyte (SPE)
 reactor, 288–289
- Electrolytic hydrogen
 bipolar electrolyzers and, 154
 quality and, 152–153
 unipolar electrolyzers, 153
- Energy conservation, facilities and,
 137–138
- Engelhard catalysts, 183–184
- Entrainment
 circulation system gas space and, 112
 and precautions/protection from
 oxidation, 136
- Epoxides, Deloxan AP II/1% Pd catalysis
 and, 103
- Equations of state (EOS)
 FAMEs, 68
- Equipment
 autoclave design
 turbines of agitators, 114–115
 autoclaves
 conforming features, 321
 opening, 322–324
 relative pressure levels, 322–323
 vent features/safety valves, 322
 hydrogenation facilities
 autoclave systems, 118, 121–129
 gas recirculators, 111
 heat exchangers, 111
 oil filters, 111
 turbines of autoclave agitators, 114–
 115, 118, 120–124
- Essential fatty acids
 fatty-acid isomerism, 357
 general overview, 356–357
 geometric isomerism, 357
 optical isomerism, 357
 positional isomerism, 357
- Ester value (EV), quality and control
 testing and, 330
- Extent of hydrogenation/selectivities,
 electrocatalytic hydrogenation
 reaction of, 284
- F**
- FAC melting point
 quality and control testing and, 335
- Facilities
 autoclave
 controlling, 146–147
 emptying, 147
 filling, 145–146
 autoclave design
 current (advanced gas reactor),
 128–129
 current (loop reactor), 124–127

- current (Lurgi system), 127–128
- current (radial/axial flow), 118, 121–124
- early systems, 116–120
- flat-blade stirrers, 132
- gas space, 130–131
- ratio oil depth/autoclave diameter, 130
- temperature control, 131–132
- turbine agitator mixers, 132–133
- vacuum, 129–130
- catalysts
 - handling/economy, 143–145
 - construction material, 133
 - energy conservation, 137–138
 - filtration, 138–142
 - general considerations, 111–112
 - hydrogen distribution
 - circulation systems, 112–113
 - dead-end systems, 113–114
 - limitation of uses, 115–116
 - mixed dead-end circulation systems, 114–115
 - oil protection, 135–137
 - oil segregation, 133–135
- Fatigue
 - catalyst action and, 15–17
- Fatty acid methyl esters (FAMES)
 - packed bed reactor
 - Cu-Cr catalysts, 87–88
- Fatty acid methyl esters (FAMES)
 - phase behavior and, 68
- Fatty acid methyl esters (FAMES)
 - supercritical hydrogenation coupled processes
 - binary fluid mixtures SC-H₂/Co₂ or SC-H₂/C₃H₈, 93–97
 - chromium-free catalyst, 97–98
 - SFR-SFR sequential reaction GC profile, 97–98
 - SFR-SFR sequential reaction scheme, 93–95
- Fatty acids
 - chain length/unsaturation and, 2–4
 - general overview, 1–2
 - hydrogenation
 - composition curves of linoleic esters, 23–24
- Fatty acids (FAs)
 - cyclization/polymerization and, 357–358
 - essential FAs, 356–357
 - FA composition/chemical and physical analysis
 - soybean oil (partially hydrogenated), 301–302
 - FA profiles with modified Pd catalyst cathode
 - soybean oil with H₂ gas, 299–300
 - hydrogenation methods
 - autoclave considerations, 273–274
 - catalysts, 274, 276–277
 - cleansing, 277
 - temperature/pressure, 274–276
 - nomenclature, 354–356
 - quality and control testing
 - hydroxy fatty acids, 343
 - soybean oil
 - Raney nickel cathode (electrocatalytic hydrogenation), 286–288
 - solid polymer electrolyte (SPE) reactor, 291–292
 - structural isomerism
 - geometric, 357
 - optical, 357
 - positional, 357
- Fatty alcohols. *See also* Fatty acid methyl esters (FAMES)
 - commercial production of, 85
 - methyl palmitate
 - supercritical n-butane model study, 91–92
 - sequential/two-step reaction conversion
 - soybean oil, 93–94
 - substrate concentration
 - reaction rates, 102
 - supercritical hydrogenation coupled processes
 - lipase/chromium-free catalysts, 92–93
 - SFR-SFR sequential reaction scheme, 93–94
 - uses, 85
- Filling autoclaves, 145–146

- Filter cloth, 140–141
 - Filterability, catalysts and, 169
 - Filtration
 - autoclave filtering, 147
 - facilities and, 138–142
 - and filterability of catalysts, 169
 - Fire point
 - quality and control testing and, 343
 - Fish liver oils
 - hydrogenation methods
 - characteristics/FA range, 258, 261
 - hydrogenation, 262
 - Fish oils
 - hydrogenation
 - selectivity II (S_{II}) and, 31
 - Fixed-bed (continuous) catalyst
 - hydrogenation process techniques, 36–37
 - and space–time yields with Deloxan AP II/1% Pd, 86
 - Flash, hydrogenation process techniques, 38–39
 - Flash point, quality and control testing and, 343
 - Flat-blade stirrers, autoclave design and, 132
 - Flavor, light hydrogenation and, 38–39
 - Flow reactors. *See also* Reactors
 - reduction of ketone moieties
 - alcohol dehydrogenase on hydrophilic polymer, 104
 - Formic acid, 2
 - Free fatty acids (FFAs)
 - quality and control testing and, 329–330
 - SFF for, 99
 - Friedrich, John P., 107–108
 - Fuel OD contamination
 - quality and control testing and, 344
 - Fully-saturated/high melting hardened oils
 - hydrogenation methods
 - cottonseed oil, 206–207
 - general overview, 47
 - groundnut (*Arachis*/peanut) oil, 212–213
 - linseed oil, 214
 - marine oils (anchovy/pilchard oils), 257
 - marine oils (herring oil), 260
 - marine oils (sardine/menhaden oils), 258, 266–269
 - palm oil, 224
 - rapeseed (colza) oil, 246
 - rapeseed oil, 235
 - sunflower oil, 251
- G**
- Gas chromatography (GC)/gas-liquid chromatography (GLC), quality and control testing and, 345–346
 - Gas reactors, advanced, autoclave design, 128–129
 - Gas space, autoclave design and, 130–131, 130–131
 - Gas spectrometry-mass spectrometry (GC-MS), quality and control testing and, 348
 - Gauze weave, filtration and, 139–140
 - Gel permeation chromatography (GPC), quality and control testing and, 347
 - Geometrical isomerisation, *cis*
 - configuration change to *trans*, 160
 - Glass capillary chromatography, quality and control testing and, 347
 - Glossary, 351–365
 - Glycerol, structure of, 2
 - Göteborg, Sweden research plant, 107–108
 - Grapeseed oil
 - hydrogenation methods
 - characteristics/FA range, 207
 - normal/*iso-trans*-promoting hydrogenation, 208
 - Green chemistry
 - historical aspects of research, 109
 - supercritical fluid hydrogenation
 - lipase/chromium-free catalysts for coupled process, 92–94
 - Groundnut (*Arachis*/peanut) oil
 - hydrogenation methods
 - characteristics/FA range, 208–210
 - higher melting/fully-saturated hardened oils, 212–213

- iso-/trans*-promoting hydrogenation, 212
- iso-/trans*-suppressive hydrogenation, 210–211
- normal hydrogenation, 211–212
- Groundnut oil
 - hydrogenation
 - initial/final oil concentrations, 22
- Guhr, kieselguhr and, 179
- H**
- Handling fats/oils, consistent quality and, 47–48
- Hardening
 - capacity, 351–352
 - flavors
 - avoidance of off flavors, 361
 - origin, 360–361, 360–361
 - order of reaction, 358
 - reaction rates, 358
 - reactions
 - order of, 358
 - rates, 358
 - single-stage, 358–359
 - order of, 358–359
 - switch point and, 359
 - techniques, 359–360, 359–360
 - two-stage, 359
- “Hardening of Unsaturated Fats, Fatty Acids, or Fatty Acid Esters” (patent), 105
- Hardening studies. *See* Vegetable oil hardening studies
- Hardening vessel autoclave design, 116–118
- Härröd Research AB (Sweden), 107–108
- Harshaw Catalysts, 46
- Haskel gas booster compressor, 93
- Heat of reaction
 - implications of, 5
- Herring oil
 - hydrogenation methods
 - characteristics/FA range, 257–259
 - higher melting/fully-saturated hardened oils, 260
 - iso-/trans*-promoting hydrogenation, 260
 - normal hydrogenation, 259–260
 - two-stage hydrogenation, 259
 - High melting/fully-saturated hardened oils
 - hydrogenation methods
 - cottonseed oil, 206–207
 - general overview, 47
 - groundnut (*Arachis*/peanut) oil, 212–213
 - linseed oil, 214
 - marine oils (anchovy/pilchard oils), 257
 - marine oils (herring oil), 260
 - marine oils (sardine/menhaden oils), 258, 266–269
 - palm oil, 224
 - rapeseed (colza) oil, 246
 - rapeseed oil, 235
 - sunflower oil, 251
- High-performance liquid chromatography (HPLC), quality and control testing and, 347
- High pressure hydrogenation, fatty alcohol production and, 85
- Hoecat, 184
- Holmboe oil spray, 118–119
- Horiuti-Polanyi mechanism
 - isomer formation
 - nickel-catalyzed reaction, 159–160
- Hydrazine (N_2H_4), and hydrogenation sans catalysts, 32
- Hydrocarbon chain, defined, 2
- Hydrocarbon reforming, quality and, 156–157
- Hydrogen
 - activity of, 352
 - concentration on catalyst surface, 166–168
 - electrolytic, 152–153
 - general safety and, 317–319
 - hydrocarbons
 - reforming, 156–157
 - ignition (safety problem), 320–321
 - impact of availability, 90
 - impact on selectivity, 27–28
 - isomer formation
 - mechanism, 163–168
 - leaks in (safety problem), 320
 - leaks out (safety problem), 319–320

- Hydrogen (*continued*)
 purchase of, 157–158
 receipt by road/rail, 326
 requirements, 158
 storage
 high-pressure stores, 326
 low-pressure stores, 324–325
 used to clear oil/catalyst autoclave lines
 (undesirable), 115–116
- Hydrogen circulating systems
 hydrogenation process techniques and,
 36
- Hydrogen content
 FAME to fatty alcohols
 binary fluid mixtures SC-H₂/Co₂ or
 SC-H₂/C₃H₈, 95–96
- Hydrogen distribution
 circulation systems, 112–113
 dead-end systems, 113–114
 general overview, 9–12
 limitation of uses, 115–116
 mixed dead-end circulation systems,
 114–115
- Hydrogen pressure, general overview,
 12–13
- Hydrogenation. *See also* Electrocatalytic
 hydrogenation; Hydrogenation
 methods
 catalyst action
 general overview, 14–15
 induction/fatigue/poisoning, 15–17
 in compressed water, 103–104
 continuous, 127–128
 cyclohexene to cyclohexane
 polysiloxane-supported noble metal
 catalysts, 102
 discontinuous, 127
 economic value, 1
 European posttreatment, 142
 factors affecting, 31
 fatty acids
 chain length/unsaturation, 2–4
 general overview, 1–2
 hydrogen dispersion, 9–12
 hydrogen pressure, 12–13
 impact of double bonds on, 30–31
 isomer formation
 general overview, 159–160
 historical aspects, 160–163
 mechanism, 163–168
 isomerization (general overview) of,
 5–9
 methylated sunflower oil, 88
 nonfat components (general overview)
 of, 4–5
 order of reaction, 17
 other routes, 32–33
 reaction of, 5
 selectivity
 estimation of, 21–27
 meaning, 17–18
 miscellaneous, 20–21
 operation of, 27–30
 selectivity I (S_I), 18–19
 selectivity II (S_{II}), 19
 specific isomerization (S_I), 19
 triglyceride selectivity (S_I), 19–20
 supercritical
 patents involving, 104–106
 switch point and, 359
 temperature, 12–13
 three-dimensional phase equilibria
 FAME, 88
 triglycerides (general overview) of, 1–2
- Hydrogenation facility. *See* Facilities
- Hydrogenation methods
 beef tallow
 characteristics/FA range, 196–198
 fully-hardened hydrogenation,
 198–201
 ultra-light hydrogenation, 198
 castor oil
 characteristics/FA range, 270–271
 hydrogenation, 271–273
 cleansing of oils prior to, 192–194
 coconut oil
 characteristics/FA range, 201–202
 normal hydrogenation/full
 saturation, 202–203
 ultra-light hydrogenation, 202
 cottonseed oil
 characteristics/FA range, 203–205
 higher melting/fully-saturated
 hardened oils, 206–207

- iso-/*trans**-suppressive hydrogenation, 204–205
- normal hydrogenation, 205–206
- fat/oil variability and, 189–190
- fatty acids (FAs)
 - autoclave considerations, 273–274
 - catalysts, 274, 276–277
 - cleansing, 277
 - temperature/pressure, 274–276
- grapeseed oil
 - characteristics/FA range, 207
 - normal/*iso-/*trans**-promoting hydrogenation, 208
- groundnut (*Arachis*/peanut) oil
 - characteristics/FA range, 208–210
 - higher melting/fully-saturated hardened oils, 212–213
 - iso-/*trans**-promoting hydrogenation, 212
 - iso-/*trans**-suppressive hydrogenation, 210–211
 - normal hydrogenation, 211–212
- lard and, 194–196
- linseed oil
 - characteristics/FA range, 213–214
 - higher melting hardened oils, 214
 - two-stage hydrogenation, 215
- maize (corn oil)
 - characteristics/FA range, 215–216
 - normal/*iso-/*trans**-promoting hydrogenation, 216–217
 - normal versus low-temperature hydrogenation, 217
- marine oils
 - characteristics/FA range, 252–254
- marine oils (anchovy/pilchard oils)
 - characteristics/FA range, 258, 263–265
 - higher melting/fully-saturated hardened oils, 257
 - normal hydrogenation, 265
 - two-stage hydrogenation, 265
- marine oils (capelin oil)
 - characteristics/FA range, 258, 260–261
- marine oils (fish liver oils)
 - characteristics/FA range, 258, 261
 - hydrogenation, 262
- marine oils (general)
 - hydrogenation, 254–258
- marine oils (herring oil)
 - characteristics/FA range, 257–259
 - higher melting/fully-saturated hardened oils, 260
 - iso-/*trans**-promoting hydrogenation, 260
 - normal hydrogenation, 259–260
 - two-stage hydrogenation, 259
- marine oils (sardine/menhaden oils)
 - higher melting/fully-saturated hardened oils, 258, 266–269
 - normal hydrogenation, 269
 - two-stage hydrogenation, 268–269
- marine oils (whale/seal/sea elephant oils)
 - characteristics/FA range, 258, 262–263
 - hydrogenation, 263
- olive oil
 - characteristics/FA range, 217–218
 - hydrogenation, 218–219
- palm-kernel oil
 - characteristics/FA range, 224–225
 - fractionation, 226–227
 - melting point/SFI, 225–226
 - normal hydrogenation, 226–227
- palm oil
 - characteristics/FA range, 219–222
 - higher melting/fully-saturated hardened oils, 224
 - iso-/*trans**-promoting hydrogenation, 223–224
 - normal hydrogenation, 222–223
- process control, 190–192
- rapeseed (colza) oil
 - hardened/winterized, 243
 - higher melting/fully-saturated hardened oils, 246
 - iso-/*trans**-promoting hydrogenation, 245–246
 - iso-/*trans**-suppressive hydrogenation, 243–244
 - normal hydrogenation, 244–245
 - two-stage hydrogenation, 242–243

Hydrogenation methods (*continued*)

- rapeseed oil
 - characteristics/FA range, 227–232
 - higher melting/fully-saturated hardened oils, 235
 - iso-/trans*-promoting hydrogenation, 235
 - iso-/trans*-suppressive hydrogenation, 233
 - low-temperature hydrogenation, 232–233
 - normal hydrogenation, 233–234
 - two-stage hydrogenation, 235
- rice bran oil
 - characteristics/FA range, 235–237
- safflower oil
 - characteristics/FA range, 237–238
- sesame oil
 - characteristics/FA range, 238–240
- soybean oil
 - characteristics/FA range, 240–242
 - low-temperature hydrogenation, 242
- sunflower oil
 - characteristics/FA range, 246–248
 - higher melting/fully-saturated hardened oils, 251
 - iso-/trans*-promoting hydrogenation, 251
 - iso-/trans*-suppressive hydrogenation, 249–250
 - low-temperature hydrogenation, 248–249
 - normal hydrogenation, 250
 - two-stage hydrogenation, 250–251
- teaseed/tomato seed/oleic-linoleic class oils
 - characteristics/FA range, 251
- technical oils (soap-making)
 - hydrogenation, 278
- “Hydrogenation of Substrate and Products Manufactured According to the Process” (patent), 105
- Hydrogenation process techniques
 - batch (dead-end/circulating), 35–36
 - brush, 38–39
 - continuous (fixed-bed), 36–37
 - continuous (suspended), 37–38
 - cyclization/polymerization, 41–43
 - flash, 38–39
 - higher melting/fully-saturated hardened oils, 47
 - iso-/trans*-promoting, 44–46
 - iso-/trans*-suppressive, 40–41
 - low-temperature, 40
 - normal, 41
 - process techniques
 - batch (dead-end/circulating), 35–36
 - brush, 38–39
 - consistent quality, 47–48
 - continuous (fixed-bed), 36–37
 - continuous (suspended), 37–38
 - cyclization/polymerization, 41–43
 - flash, 38–39
 - higher melting/fully-saturated hardened oils, 47
 - iso-/trans*-promoting, 44–46
 - iso-/trans*-suppressive, 40–41
 - low-temperature, 40
 - normal, 41
 - requirements, 33–34
 - touch, 38–39
 - two-stage, 43–44
 - ultra-light, 38–39
 - touch, 38–39
 - two-stage, 43–44
 - ultra-light, 38–39
- Hydroxy fatty acids, quality and control testing and, 343

I

- Ignition, safety and, 320–321
- Impurities. *See also* Quality
 - circulation distribution system and, 113
 - classes of, 149
 - fixed-bed catalyst and, 36–37
 - oil segregation and, 134
- “In situ Mitigation of Coke Buildup in Porous Catalysts by Pretreatment of Hydrocarbon Feed to Reduce Peroxides and Oxygen Impurities” (patent), 106

- Incipient fusion, quality and control testing and, 335
- Induction, catalyst action and, 15–17
- Industrial plants, supercritical fluid hydrogenation and, 107
- Internal recycle reactor, 63–64
- Iodine Value (IV)
and activity of catalysts, 170–171, 351
defined, 362
electrocatalytic hydrogenation soybean oil (partially hydrogenated), 303
and hydrogen concentration on catalyst surface, 166–168
and hydrogen requirements, 158
low *trans* hydrogenation and, 307, 309–310
quality and control testing and, 330–331
- Iron, quality and, 152
- Isco SFX-2-10 extractor module, 93
- Iso-1 trans*-promoting hydrogenation
grapeseed oil, 208
groundnut (*Arachis*/peanut) oil, 212
maize (corn oil), 216–217
marine oils (herring oil), 260
palm oil, 223–224
process techniques, 44–46
rapeseed (colza) oil, 245–246
rapeseed oil, 235
SFC curve and, 45
sunflower oil, 251
- Iso-1 trans*-promotive, hydrogenation process techniques, 44–46
- Iso-1 trans*-suppressive, hydrogenation process techniques, 40–41
- Isomerization (general overview)
hydrogenation and, 5–9
- Isomers
formation during hydrogenation
general overview, 159–160
historical aspects, 160–163
mechanism, 163–168
trans FA isomers
electrocatalytic hydrogenation reaction, 284
- Isothorone to trimethylcyclohexanone hydrogenation
SC-CO₂, 106
- K**
- Kieselguhr, as silica source, 179–180
- Kirschner values, quality and control testing and, 344
- L**
- Lard, hydrogenation methods for, 194–196
- Laser pyrolysis
quality and control testing and, 348
- Lauric oils
facilities
separate handling, 134
- Leaks in, safety and, 320
- Leaks out, safety and, 319–320
- Light
odor/flavor/color and, 38–39
and precautions/protection from oxidation, 136
- Linoleate (L), hydrogenation and, 22
- Linoleic acid
adsorbed *trans* isomer of, 165–166
- Linoleic acid selectivity
isomer formation
general overview, 18
historical aspects, 162
sunflower seed oil, 166–168
- Linolenate (Ln)
hydrogenation of, 22
- Linolenic acid (triunsaturate)
isomer formation
historical aspects, 162
selectivity II (S_{II}) and, 19
- Linseed oil
hydrogenation
initial/final oil concentrations, 22
hydrogenation methods
characteristics/FA range, 213–214
higher melting hardened oils, 214
two-stage hydrogenation, 215
- Lipase catalysts, supercritical
hydrogenation coupled processes, 92–93

- Liquid chromatography (LC)/liquid-liquid chromatography/partition chromatography, quality and control testing and, 346–347
- Liquid-solid/adsorption chromatography, quality and control testing and, 347
- Loop reactor, autoclave design, 124–127
- Low-temperature, hydrogenation process techniques, 40
- Low *trans* hydrogenation
 - and catalysts for reduced *trans* FAs, 309
 - effects of agitation on, 306–307
 - effects of pressure on, 307–308
 - effects of temperature on, 306–307
 - general overview/historical aspects, 305–306
 - low IV oils and, 307, 309–310
 - modified nickel catalysts for, 309, 311
 - via catalyst switching strategy, 311–312
- Lurgi system
 - autoclave design, 127–128
- M**
- Maize
 - hydrogenation
 - initial/final oil concentrations, 22
- Maize (corn oil)
 - hydrogenation methods
 - characteristics/FA range, 215–216
 - normal/*iso*-/*trans*-promoting hydrogenation, 216–217
 - normal versus low-temperature hydrogenation, 217
- Marine oils
 - facilities
 - separate handling, 134–135
 - hydrogenation methods
 - characteristics/FA range, 252–254
- Marine oils (anchovy/pilchard oils)
 - hydrogenation methods
 - characteristics/FA range, 258, 263–265
 - higher melting/fully-saturated hardened oils, 257
 - normal hydrogenation, 265
 - two-stage hydrogenation, 265
- Marine oils (capelin oil)
 - hydrogenation methods
 - characteristics/FA range, 258, 260–261
- Marine oils (fish liver oils)
 - hydrogenation methods
 - characteristics/FA range, 258, 261
 - hydrogenation, 262
- Marine oils (general)
 - hydrogenation methods
 - hydrogenation, 254–258
- Marine oils (herring oil)
 - hydrogenation methods
 - characteristics/FA range, 257–259
 - higher melting/fully-saturated hardened oils, 260
 - iso*-/*trans*-promoting hydrogenation, 260
 - normal hydrogenation, 259–260
 - two-stage hydrogenation, 259
- Marine oils (sardine/menhaden oils)
 - hydrogenation methods
 - higher melting/fully-saturated hardened oils, 258, 266–269
 - normal hydrogenation, 269
 - two-stage hydrogenation, 268–269
- Marine oils (whale/seal/sea elephant oils)
 - hydrogenation methods
 - characteristics/FA range, 258, 262–263
 - hydrogenation, 263
- Mass spectrometry (MS), quality and control testing and, 348
- Melting point
 - quality and control testing and, 335
- Melting tests
 - quality and control
 - cloud point, 336
 - complete fusion/melting point/clear point/FAC melting point, 335
 - congeal point, 336
 - differential thermal analysis (DTA), 338
 - dilatations/solid-fat index, 336–337
 - drop/flow/pour points, 336
 - incipient fusion, 335
 - SFC over temperature range, 335

- slip melting point, 335
- solid-fat content (SFC) determined by NMR, 337–338
- titer, 336
- Wiley melting point, 336
- Membrane-Electrode-Assembly (MEA), 289
- Membrane reactors, 63–65
- Menhaden/sardine oils
 - hydrogenation methods
 - higher melting/fully-saturated hardened oils, 258, 266–269
 - normal hydrogenation, 269
 - two-stage hydrogenation, 268–269
- Methane, as common impurity, 149
- Methanol, feedback into SFR process, 92, 94
- Methyl palmitate
 - phase behavior and, 68
 - supercritical n-butane model study, 91–92
- Mixed triglyceride, 2
- Multiple syringe pump system
 - FAME to fatty alcohols
 - binary fluid mixtures SC-H₂/Co₂ or SC-H₂/C₃H₈, 94–95
- N**
- N-butane model study, and hydrogenation of methyl palmitate, 91–92
- Nanoparticles with catalytic activity
 - hydrogenation and, 103
 - research and, 107
- National Center for Agricultural Utilization Research, 107
- Neat fatty acids, versus FAMEs, 99
- Nickel-catalyst poisons, as minor component of fats/oils, 4
- Nickel catalysts. *See also* Catalysts
 - commercial, 183
 - consumption/poisoning, 362
 - enhancement of, 176
 - general overview, 176
 - hydrogenation
 - historical aspects, 160–161
 - induction and, 16
 - isomer formation and, 159
 - modified for low *trans* hydrogenation, 309, 311
 - pore diameters of, 28–30
 - recovery and, 182–183
 - trans*-promoting/reusable, 145
- Nickel concentration, and hydrogenation rates at different stirring speeds, 14–15
- Nitriles, Deloxan AP II/1% Pd catalysis and, 103
- Nitrobenzenes, Deloxan AP II/1% Pd catalysis and, 103
- Nitrogen
 - as common impurity, 149
 - and precautions/protection from oxidation, 137
- Noble metals, catalysts and, 178–179
- Nonfat components (general overview), 4–5
- Normal, hydrogenation process techniques, 41
- Northern Regional Research Center (NRRC), 107, 175
- Novozym SP 435, 97–98
- Nysosel, 183–184
- O**
- Odor
 - light hydrogenation and, 38–39
- Odor intensity scores
 - electrocatalytic hydrogenation
 - soybean oil (partially hydrogenated), 301–302
- Off flavors, *trans* plus terminal aldehyde/ketone group and, 9
- Oil protection, facilities and, 135–137
- Oil segregation, facilities and, 133–135
- Olefinic organic compound
 - electrocatalytic hydrogenation reaction of, 281
- Oleic-linoleic class oils
 - hydrogenation methods
 - characteristics/FA range, 251
- Olive oil
 - hydrogenation methods
 - characteristics/FA range, 217–218
 - hydrogenation, 218–219

- Order of reaction, 17
- Oven/Schaal Test, quality and control testing and, 342
- Oxidation. *See also* Rate of oxidation catalysts
 stabilization/passivation, 174
 precautions/protection from, 136–137
 storage of catalysts and, 182
- Oxidation and stability testing
 quality and control
 2-thiobarbituric acid (TBA) test, 342
 anisidine value (AnV), 341
 fire point, 343
 flash point, 343
 mechanism, 339
 Oven/Schaal Test, 342
 peroxide value (PV), 340
 Quality Test, 342
 Rancimat Test, 341–342
 relevance, 338–339
 significance of oxidation tests, 340
 smoke point, 343
 specifications of present state/
 resistance to further, 340
 Spectrometric Test, 342–343
 Swift Test/Swift Life/active oxygen
 method, 341
 Sylvester Test/Barcroft-Warburg
 Test/Eckey method, 342
- Oxidized oil, as catalyst poison,
 135–137
- Oximes, Deloxan AP II/1% Pd catalysis
 and, 103
- Oxo process, fatty alcohol production
 and, 85
- Oxygen
 impurities and, 151
 safety and, 317–320
- P**
- Packed bed reactor
 FAME
 Cu-Cr catalysts, 87–88
- Palm-kernel oil
 hydrogenation methods
 characteristics/FA range, 224–225
 fractionation, 226–227
 melting point/SFI, 225–226
 normal hydrogenation, 226–227
- Palm oil
 hydrogenation methods
 characteristics/FA range, 219–222
 higher melting/fully-saturated
 hardened oils, 224
iso-trans-promoting hydrogenation,
 223–224
 normal hydrogenation, 222–223
- Passivation, catalysts, 174–175
- Patents, 104–106, 109
- Peanut oil
 hydrogenation methods
 characteristics/FA range, 208–210
 higher melting/fully-saturated
 hardened oils, 212–213
iso-trans-promoting hydrogenation,
 212
iso-trans-suppressive hydrogenation,
 210–211
 normal hydrogenation, 211–212
- Pereda, Selva, 69
- Peroxide value (PV), quality and control
 testing and, 340
- Peroxides, and precautions/protection
 from oxidation, 137
- Phase equilibria studies
 of Bottini-Brignole-Perada-Peters-
 Rovetto, 69
 EOS and, 68
 FAMES and, 68
 thermodynamics and, 67
 view cell, 65–66
- Phenols, Deloxan AP II/1% Pd catalysis
 and, 103
- Phospholipids, poisoning action of, 173
- Pigments and hydrogenation, 4
- Pilchard/anchovy oils
 hydrogenation methods
 characteristics/FA range, 258,
 263–265
 higher melting/fully-saturated
 hardened oils, 257
 normal hydrogenation, 265
 two-stage hydrogenation, 265

- Poisoning. *See also* Catalysts; Nickel catalysts
catalyst action and, 15–17
catalysts and, 171–174
and hydrogen concentration on catalyst surface, 165
nickel consumption and, 362
- Polenske values, quality and control testing and, 344
- Polishing filters, 142
- Polybromides, quality and control testing and, 331
- Polymer formation, upon hydrogenation, 43
- Polymorphs, 364–365
- Polysiloxane-supported noble metal catalysts
continuous flow reactors
SC-CO₂, 102
- Polyunsaturation, as preliminary to hydrogenation, 41
- Pore diameters, of nickel catalyst, 28–30
- Positional isomerisation
geometrical isomerisation and, 160
triglycerides and, 363–364
- Power consumption (PC)
electrocatalytic hydrogenation reaction of, 283
- Pressure
autoclave safety
relative pressure levels, 322–323
effect on low *trans* hydrogenation, 307–308
filtration control and, 141
and hydrogenation in compressed water, 104
hydrogenation methods, 274–276
and moisture content of saturated gas, 149–150
and phase behavior for reactant feed/product flow, 65–66
and split of reaction mixture into phases, 89–90
substrate concentration
reaction rates, 102
- Process techniques. *See* Hydrogenation process techniques
- Production rate (PR)
electrocatalytic hydrogenation reaction of, 283
- Production rate (PR)/power consumption for PEM reactor
electrocatalytic hydrogenation
soybean oil with H₂ gas, 299–300
- Propane
as supercritical fluid
amine-containing substrates, 103
- Propionic acid, 2
- Purchase, 352
- ## Q
- Quality
bipolar electrolyzers and, 154
classes of impurities, 149
CO and, 149–152
consistence in, 47–48
electrolytic hydrogen and, 152–153
hydrocarbon reforming and, 156–157
and hydrogen requirements, 158
moisture content of saturated gas
temperature/pressure, 149–152
and purchase of hydrogen, 157–158
security and, 155–156
steam iron hydrogen and, 152
unipolar electrolyzers and, 153
water supply and, 154
- Quality and control
classification of tests, 329
melting
cloud point, 336
complete fusion/melting point/clear point/FAC melting point, 335
congeal point, 336
differential thermal analysis (DTA), 338
dilatations/solid-fat index, 336–337
drop/flow/pour points, 336
incipient fusion, 335
SFC over temperature range, 335
slip melting point, 335
solid-fat content (SFC) determined by NMR, 337–338
titer, 336
Wiley melting point, 336

Quality and control (*continued*)

miscellaneous

- atomic absorption (AA)
 - spectrophotometry, 349
- color values, 349–350
- fuel OD contamination, 344
- gas chromatography (GC)/gas-liquid chromatography (GLC), 345–346
- gas spectrometry-mass spectrometry (GC-MS), 348
- gel permeation chromatography (GPC), 347
- glass capillary chromatography, 347
- high-performance liquid chromatography, 347
- hydroxy fatty acids, 343
- laser pyrolysis, 348
- liquid chromatography (LC)/liquid-liquid chromatography/partition chromatography, 346–347
- liquid-solid/adsorption chromatography, 347
- mass spectrometry (MS), 348
- Reichert-Meissl/Polenske/Kirschner values, 344
- thin-layer chromatography, 347
- oxidation and stability
 - 2-thiobarbituric acid (TBA) test, 342
 - anisidine value (AnV), 341
 - fire point, 343
 - flash point, 343
 - mechanism, 339
 - Oven/Schaal Test, 342
 - peroxide value (PV), 340
 - Quality Test, 342
 - Rancimat Test, 341–342
 - relevance, 338–339
 - significance of oxidation tests, 340
 - smoke point, 343
 - specifications of present state/resistance to further, 340
 - Spectrometric Test, 342–343
 - Swift Test/Swift Life/active oxygen method, 341
 - Sylvester Test/Barcroft-Warburg Test/Eckey method, 342

- saponifiable matter
 - acid value (AV), 330
 - ester value (EV), 330
 - FFA(%), 329–330
 - saponification value (SV), 330
 - unsaponifiable matter (%), 330

unsaturation

- alkali isomerization, 332–333
- iodine value (IV), 330–331
- polybromides, 331
- refractive index (n'_D), 333–334
- trans* index, 331–332
- Quality Test, quality and control testing and, 342

R

- Radial/axial flow
 - autoclave design, 118, 121–124
- Radial reactor
 - soybean oil
 - Raney nickel cathode (electrocatalytic hydrogenation), 287–288
- Rancimat Test, quality and control testing and, 341–342
- Raney nickel
 - catalysts and, 176
- Raney nickel cathode (electrocatalytic hydrogenation)
 - soybean oil
 - batch recycle reaction loop, 285–286
 - current density/electrolyte oil content, 286–287
 - drawbacks, 288–289
 - FA profiles/*trans* isomer content, 286–288
 - initial experiments, 284–285
 - radial reactor, 287–288
 - schematic, 285
 - solid polymer electrolyte (SPE) reactor, 288–289
- Rapeseed (colza) oil
 - hydrogenation methods
 - hardened/winterized, 243
 - higher melting/fully-saturated hardened oils, 246

- iso/trans*-promoting hydrogenation, 245–246
 - iso/trans*-suppressive hydrogenation, 243–244
 - normal hydrogenation, 244–245
 - two-stage hydrogenation, 242–243
- Rapeseed oil
- continuous partial hydrogenation of methylated, 90–91
 - and deodorization following alkali neutralization, 4
 - hydrogenation methods
 - characteristics/FA range, 227–232
 - higher melting/fully-saturated hardened oils, 235
 - iso/trans*-promoting hydrogenation, 235
 - iso/trans*-suppressive hydrogenation, 233
 - low-temperature hydrogenation, 232–233
 - normal hydrogenation, 233–234
 - two-stage hydrogenation, 235
- Rate of oxidation, degree of unsaturation/temperature on, 136
- Ratio oil depth, autoclave design and, 130
- Reaction
- of hydrogenation, 5
 - order of, 17
- Reaction rates
- circulation system control of, 112
 - isomer formation
 - historical aspects, 163
 - loop hydrogenation reactor and, 126
 - patents and, 105
- Reactions
- electrocatalytic hydrogenation
 - anode, 281
 - cathode, 281
 - current efficiency, 282–283
 - extent of hydrogenation/selectivities, 284
 - overall olefinic organic compound, 281
 - power consumption (PC), 283
 - production rate (PR), 283
 - side, 281–282
 - trans* FA isomers, 284
 - hydrogenation
 - mechanism, 164
 - reforming, 156
 - shift, 156
- Reactors, 88
- advantage of continuous, 61–62
 - batch, 62–63
 - consecutive, 88
 - continuous internal recycle, 63–64
 - membrane, 63–65
 - packed bed reactor
 - Cu-Cr catalysts, 87–88
 - Robinson-Mahoney type-reactor, 63
 - trickle bed reactor
 - space-time yields with Deloxan AP II/1% Pd, 86
- Recovery
- catalyst production and, 182–183
- Reduction
- low *trans* hydrogenation
 - strategies, 305–306
- Reduction, wet/dry, catalyst production and, 179–181
- Refractive index (n_D^{20}), quality and control testing and, 333–334
- Refractometer
- activity apparatus standardization and, 352
 - consistent quality and, 48
- Reichert-Meissl/Polenske/Kirschner values, quality and control testing and, 344
- Research
- supercritical fluid hydrogenation, 106–109
- Rice bran oil
- hydrogenation methods
 - characteristics/FA range, 235–237
- Ricinoleic acid, 2
- Robinson-Mahoney type-reactor, 63
- ## S
- Safety/security
- autoclaves
 - conforming features, 321
 - opening, 322–324
 - relative pressure levels, 322–323
 - vent features/safety valves, 322

- Safety/security (*continued*)
 common precautions
 ignition, 320–321
 leaks in, 320
 leaks out, 319–320
 equipment and, 316–317
 hydrogen and, 317–319
 hydrogen receipt by road/rail, 326
 hydrogen storage
 high-pressure stores, 326
 low-pressure stores, 324–325
 personnel and, 316
 static charges/electrical equipment, 327
- Safflower oil
 hydrogenation methods
 characteristics/FA range, 237–238
- Saponifiable matter tests
 quality and control
 acid value (AV), 330
 ester value (EV), 330
 FFA(%), 329–330
 saponification value (SV), 330
 unsaponifiable matter (%), 330
- Saponification value (SV)
 quality and control testing and, 330
- Sardine/menhaden oils
 hydrogenation methods
 higher melting/fully-saturated
 hardened oils, 258, 266–269
 normal hydrogenation, 269
 two-stage hydrogenation, 268–269
- Saturates. *See also* Fully-saturated/high melting hardened oils
 hydrogenation
 conditions promoting, 45
- SC-CO₂
 historical aspects of research, 109
- SC/Co₂
 supercritical hydrogenation coupled processes
 acetophenone, 99
- SC-H₂/Co₂ or SC-H₂/C₃H₈, binary fluid mixtures
 supercritical hydrogenation coupled processes
 FAME to fatty alcohols, 93–95
 GC profiles, 96–97
- Schaal/Oven Test
 quality and control testing and, 342
- Sea elephant/whale/seal oils
 hydrogenation methods
 characteristics/FA range, 258, 262–263
 hydrogenation, 263
- Seal/sea elephant/whale oils
 hydrogenation methods
 characteristics/FA range, 258, 262–263
 hydrogenation, 263
- Security. *See also* Safety/security
 hydrogen migration/deterioration and, 155–156
- Segregation. *See* Oil segregation
- Selectivity. *See also* Nickel catalysts
 to assess different hydrogenation results, 81
 and available hydrogen, 27–28
 catalyst durability and, 172
 catalysts and, 175–176
 continuous (suspended) hydrogenation and, 38
 defined, 362–363
 electrocatalytic hydrogenation
 solid polymer electrolyte (SPE) reactor, 295
 soybean oil with H₂ gas, 298
 estimation of, 21–27
 isomer formation
 historical aspects, 161–162
 meaning, 17–18
 miscellaneous, 20–21
 operation of, 27–30
 reactions
 Electrocatalytic hydrogenation, 284
 selectivity I (S_I), 18–19
 selectivity II (S_{II}), 19, 25–27
 selectivity (S_I), 19
 selectivity (S_r), 19–20
 specific isomerization (S_i), 19
 triglyceride selectivity (S_t), 19–20
 Venturi jet and BUSS system, 38
- Selectivity I (S_I)
 classification of, 363

- general overview, 18–19
- hydrogenation
 - SCI-temperature curves, 23–25
- Selectivity II (S_{II})
 - calculation of, 25–27
 - classification of, 363
 - general overview, 19
- Selectivity ratio (SR), 19
- Selectivity (S_i)
 - classification of, 363
 - general overview, 19
- Selectivity (S_T)
 - classification of, 363
 - general overview, 19–20
- Sequential reaction scheme
 - conversion %, 99
- SFR-SFR
 - GC profiles, 97–98
 - GC profiles with Novozym SP 435, 97–98
- Sesame oil
 - hydrogenation methods
 - characteristics/FA range, 238–240
- SFC curve, iso-/trans-promoting
 - hydrogenation and, 45
- SFC over temperature range
 - quality and control testing and, 335
- SFR-SFR sequential reaction scheme
 - supercritical hydrogenation coupled processes
 - GC profiles, 97–98
 - GC profiles with Novozym SP 435, 97–98
 - vegetable oil to fatty alcohol, 93–94
- Shunt reactions, 162–163
- Side, electrocatalytic hydrogenation
 - reaction of, 281–282
- Side-mounted propellers of storage tanks, 48
- Silica
 - catalysts
 - dry reduction, 179–180
- Silt, 136
- Simple triglyceride, defined, 1
- Single-phase systems
 - catalytic performance in, 67
 - continuous partial hydrogenation of methylated rapeseed oil, 90–91
- Slip melting point, quality and control testing and, 335
- Smoke point
 - quality and control testing and, 343
- Soap-making oils
 - hydrogenation methods
 - hydrogenation, 278
- Solid-fat content (SFC) determined by NMR
 - quality and control testing and, 337–338
- Solid Fat Content (SFC), *trans* isomerisation and, 161
- Solid fat content/temperature electrocatalytic hydrogenation
 - soybean oil (partially hydrogenated), 303
- Solid fat index (SFI)
 - hydrogenation
 - catalyst selectivity, 25–26
 - iso/trans*-suppressive hydrogenation and, 40–41
 - and low-sulfur catalysts, 44
- Solid polymer electrolyte (SPE) reactor electrocatalytic hydrogenation
 - efficiency/cell voltage, 291
 - efficiency/selectivity, 295
 - FA profiles for canola/cotton seed oil, 293
 - FA profiles for soybean oil, 291–292
 - Raney nickel cathode and soybean oil, 288–289
 - temperature, 293–294
 - trans* isomer content for canola/cotton seed oil, 293
 - trans* isomer content/IV for soybean oil, 291–292
 - water as anode/oil as cathode, 290
- Solubility (product/substrate)
 - substrate concentration and, 102
- Soybean oil
 - catalysts
 - selectivity, 175–176
 - copper catalysts and, 177–178

Soybean oil (*continued*)

- electrocatalytic hydrogenation with H₂ gas
 - FA profiles with modified Pd catalyst cathode, 299–300
 - materials/operating conditions for SPE reactor, 297
 - production rate (PR)/power consumption for PEM reactor, 299–300
 - selectivity, 298
 - temperature, 295, 297–298
- fatty alcohol
 - sequential/two-step reaction conversion, 93–94
- hydrogenation
 - initial/final oil concentrations, 22
- hydrogenation methods
 - characteristics/FA range, 240–242
 - low-temperature hydrogenation, 242
- partially hydrogenated
 - FA composition/chemical and physical analysis, 301–302
 - IV properties, 303
 - low-*trans* spread oils via blending, 304
 - odor intensity scores, 301–302
 - solid fat content/temperature, 303
 - trans* FA/stearic acid content, 303–304
- Raney nickel cathode (electrocatalytic hydrogenation)
 - batch recycle reaction loop, 285–286
 - current density/electrolyte oil content, 286–287
 - drawbacks, 288–289
 - FA profiles/*trans* isomer content, 286–288
 - initial experiments, 284–285
 - radial reactor, 287–288
 - schematic, 285
 - solid polymer electrolyte (SPE) reactor, 288–289
- solid polymer electrolyte (SPE) reactor
 - efficiency/cell voltage, 291
 - efficiency/selectivity, 295–296

- FA profiles for canola/cotton seed oil, 293
- FA profiles for soybean oil, 291–292
 - temperature, 293–294
 - trans* isomer content for canola/cotton seed oil, 293
 - trans* isomer content/IV for soybean oil, 291–292
 - water as anode/oil as cathode, 290
 - trans*-isomer content of, 176
- Spe-ed unit, 93
- Specific isomerization (S_p), selectivity and, 19
- Spectrometric Test, quality and control testing and, 342–343
- Stability. *See* Oxidation and stability
- Stabilization, catalysts, 174–175
- Stainless steel coils, facilities and, 133
- Static charges/electrical equipment, safety and, 327
- Steam iron hydrogen
 - quality and, 152
- Stearic acid
 - hydrogenation properties
 - SBO stearic acid content vs. IV value, 74–75
- Stearic acid content
 - electrocatalytic hydrogenation soybean oil (partially hydrogenated), 303–304
- Stills for water, 154
- Storage, catalyst production and, 182
- Storage of fats/oils
 - consistent quality and, 47–48
 - and precautions/protection from oxidation, 136–137
- Styrene, hydrogenation in compressed water of, 104
- Subcritical fluid hydrogenation, importance of, 50–53
- Substrate concentration, and split of reaction mixture into phases, 89–90
- Sulfur, 4
 - and adsorbed double bonds, 46
 - catalysts and, 44

- Sunflower oil
- hydrogenation
 - HPLC pump, 63
 - methylated, 88
 - hydrogenation methods
 - characteristics/FA range, 246–248
 - higher melting/fully-saturated hardened oils, 251
 - iso-1 trans*-promoting hydrogenation, 251
 - iso-1 trans*-suppressive hydrogenation, 249–250
 - low-temperature hydrogenation, 248–249
 - normal hydrogenation, 250
 - two-stage hydrogenation, 250–251
- Sunflower seed oil
- isomer formation
 - linoleic acid selectivity, 166
- Supercritical fluid extraction (SFE)
- Supercritical fluid fractionation (SFF)
- for high purity FFAs, 99
- Supercritical fluid hydrogenation
- coupled processes
 - lipase/chromium-free catalysts, 92–93
 - electrochemical synthesis, 84–85
 - FAME
 - two-phase/single-phase reaction rate differences, 82
 - importance of, 50–53, 70–71
 - lipid substrates
 - FAME to fatty alcohols, 82
 - palm oil in near-critical/supercritical conditions
 - IV as function of H₂/triglyceride ratio and time, 83–84
 - IV as function of reaction temperature and residence time at constant H₂ concentration, 84–85
 - IV/reaction rates as function of variables, 82–84
 - patents involving, 104–106
 - productivity
 - Deloxan polysiloxane-supported Pd/Pt catalysts, 80–81
 - propane
 - amine-containing substrates, 103
 - properties
 - SBO and CO₂/H₂, 71
 - SBO and pure H₂, 71–72
 - SBO at high temperatures, 72–73
 - SBO percent *trans* FA vs. IV value, 74
 - SBO reaction time vs. IV value, 73
 - SBO SFI vs. temperature, 76–77
 - SBO stearic acid content vs. IV value, 74–75
 - SBO vs. margarine/shortening basestocks, 75–76
 - rapiseed FAME in near-critical/supercritical conditions
 - reaction rate/*trans* FA formation, 82
 - research and, 106–109
 - SBO percent *trans* FA using binary mixtures of CO₂/H₂
 - properties, 77–78
 - rate constants, 78
 - split of reaction mixture into phases, 89–90
 - sunflower oil hydrogenation
 - Pd/C catalyst in propane, 80
 - triglyceride distribution
 - pressure increase, 79
 - “Supercritical Hydrogenation” (patent), 105
 - Suppliers of commercial catalysts, 184–187
 - Surface area
 - importance
 - activity of catalysts, 170–171
 - Suspended (continuous) catalyst, hydrogenation process techniques, 37–38
 - Swift Life, quality and control testing and, 341
 - Swift Test/Swift Life/active oxygen method, quality and control testing and, 341
 - Sylvester Test/Barcroft-Warburg Test/Eckey method, quality and control testing and, 342
- T**
- “Tacke” (patent), 105
 - Teaseed/tomato seed/oleic-linoleic class oils
 - hydrogenation methods
 - characteristics/FA range, 251

- Technical oils (soap-making)
 hydrogenation methods
 hydrogenation, 278
- Temperature
 activity at low temperature, 352
 autoclave design
 controlling, 131–132
 and critical effects for reaction, 13
 effect on low *trans* hydrogenation,
 306–307
 electrocatalytic hydrogenation
 solid polymer electrolyte (SPE)
 reactor, 293–294
 soybean oil (partially hydrogenated),
 303
 soybean oil with H₂ gas, 295, 297–298
 electrocatalytic hydrogenation with
 H₂ gas
 soybean oil, 295
- FAME to fatty alcohols
 binary fluid mixtures SC-H₂/Co₂ or
 SC-H₂/C₃H₈, 95
 and hydrogen concentration on catalyst
 surface, 164–165
 hydrogen dispersion and, 9–12
 hydrogenation
 batch (dead-end/circulating),
 35–36
 hydrogen scarcity, 42–43
 impact of miscibility of hydrogen/
 substrates, 67
 sulfur-poisoned supported catalysts, 46
 two-stage, 43–44
 hydrogenation and, 12–13
 and hydrogenation in compressed
 water, 104
 hydrogenation methods
 considerations, 274–276
 isomer formation
 mechanism, 163
 and moisture content of saturated gas,
 149–150
 and normal hydrogenation, 41
 and phase behavior for reactant feed/
 product flow, 65–66
 supercritical fluid hydrogenation
 SBO properties, 72–73
 wet reduction and, 181
- Thermodynamics. *See also* Temperature
 phase behavior and, 67
- Thin-layer chromatography, quality and
 control testing and, 347
- 2-Thiobarbituric Acid (TBA) test,
 quality and control testing and,
 342
- Thioglucosides
 sulfur and, 4
- Three-dimensional phase equilibria
 hydrogenation
 FAME, 88
- “Three Stage Processes for the Separation
 of Supercritical or Near-critical
 Mixtures” (patent), 106
- Titer
 quality and control testing and,
 336
- Tomato seed oil
 hydrogenation methods
 characteristics/FA range, 251
- Touch
 hydrogenation process techniques,
 38–39
- Trans* fatty acid
 hydrogenation properties
 SBO percent *trans* FA vs. IV value,
 74
- Trans* fatty acid isomers
 cottonseed oil/canola oil
 solid polymer electrolyte (SPE)
 reactor, 293
 electrocatalytic hydrogenation
 soybean oil (partially hydrogenated),
 303–304
 electrocatalytic hydrogenation reaction
 of, 284
 electrocatalytic hydrogenation
 reactions
 reactions, 284
 soybean oil
 Raney nickel cathode
 (electrocatalytic hydrogenation),
 286–288
 solid polymer electrolyte (SPE)
 reactor, 291–292

- Trans* hydrogenation. *See* Low *trans* hydrogenation
- Trans* index
 quality and control testing and, 331–332
- Trans* isomer configuration
 configuration change to *cis* isomer formation, 159–160
 geometrical isomerisation and, 161–162
 from linoleic acid, 166–168
- Trans* isomer configurations
 defined, 3
 and impact of double bonds on hydrogenation, 30–31
 isomerization (general overview) and, 6–7
 normal hydrogenation and, 41
 promoting
 hydrogenation process techniques, 44–46
 specific isomerization (SI) and, 19
 sulfur-poisoned supported catalysts and, 46
 texture and, 18
- Trans* isomer content
 soybean oil
 Raney nickel cathode (electrocatalytic hydrogenation), 286–288
- Trans* isomerization, Deloxan polysiloxane-supported Pd/Pt catalysts and, 80–81
- Transesterification. *See* SFR-SFR sequential reaction scheme
- Transport limitation, split of reaction mixture into phases, 89–90
- Trickle bed reactor, 63
 patents and, 105
 and space-time yields with Deloxan AP II/1% Pd, 86
- Triglycerides
 activity of catalysts
 surface area, 171
 general overview, 1–2
 isomer formation
 reaction, 159
 polymorphs and, 364–365
 positional isomers and, 363–364
 selectivity (S_p), 19–20
 shunt reactions and, 162–163
- Tristearins (S_3), selectivity (S_T) and, 20–21
- Triunsaturate linolenic acid, selectivity II (S_{II}) and, 19
- Turbines agitator mixers, autoclave design and, 132–133
- Turbines of autoclave agitators, 114–115, 118, 120–124
- Two-stage hydrogenation
 hydrogenation process techniques, 43–44
 linseed oil and, 215
 marine oils (anchovy/pilchard oils) and, 265
 marine oils (herring oil) and, 259
 marine oils (sardine/menhaden oils) and, 268–269
 rapeseed oil and, 235, 242–243
 reaction rates and, 67
 sunflower oil and, 250–251
- ## U
- Ultra-light hydrogenation
 beef tallow and, 198
 coconut oil and, 202
 process techniques, 38–39
 techniques, 38–39
- Ultraviolet light, and precautions/protection from oxidation, 136
- Unipolar electrolyzers, quality and, 153
- United States Department of Agriculture, Northern Regional Research Center (NRRC), 107, 175
- Unsaponifiable matter (%), quality and control testing and, 330
- Unsaturation
 controlling degree of, 104
 cyclization/polymerization and, 41–43
 selectivity
 nickel catalyst, 31

Unsaturation tests

quality and control

- alkali isomerization, 332–333
- iodine value (IV), 330–331
- polybromides, 331
- refractive index (n'_D), 333–334
- trans* index, 331–332

V

Vacuum, autoclave design and, 129–130

Vegetable oil hardening studies

- and control of degree of unsaturation, 104
- free tallow FA in Sc-CO₂, 81
- productivity
 - conventional Ni catalysts with supercritical propane, 81

Venturi jet

- loop hydrogenation reactor and, 124–125
- suspended catalysts and BUSS system, 38

Viscosity

productivity

- Deloxan polysiloxane-supported Pd/Pt catalysts, 80–81

Voltages. *See* Cell voltages

W

Warp, filtration and, 139

Washing/drying, and cleansing of crude oil, 34

Water

- hydrogenation in compressed water, 103–104
- quality and, 154

Wet reduction

- catalyst production and, 181
- catalysts
 - durability/poisoning, 174

Whale/seal/sea elephant oils

- hydrogenation methods
 - characteristics/FA range, 258, 262–263
 - hydrogenation, 263

Wilbuschewitsch oil spray/mixing jet, 116–117

Wiley melting point, quality and control testing and, 336

Z

Ziegler process, fatty alcohol production and, 85

Zosel patents, 105