

Index

A

- Acetone extracts, 144
- Adducts
 - equilibria, 274
 - urea dewaxing, 271
- Aniline Point, 9
- API Base Stock Categories, 15
- API Engine Oil Classification, 18

B

- Base Oils, 2
- Base Stocks
 - annual volumes, 1
 - API definition, 2
 - API classification, 15
 - classification, 2
 - composition, 12
 - processing steps, 4
 - properties, 6

BASF

- Refined paraffins process, 348–350
- White Oil process, 339, 343

Boiling Points, 37

- composition, 37–41
 - effect of aromatic saturation, 38–39
- BP Cat Dewaxing process, 282–289
- mordenite-based catalysts, 284
 - naphthenic lubes, 284
 - paraffinic lubes, 287

Branched paraffins, pour points, 32, 40

Brookfield viscosity, 10

C

- Carbon type distributions, 10, 75–79
- Cat Dewaxing
 - BP, 282–289
 - Chevron, 306–310
 - Mobil, 293–306
- Chemical conversion process, 4
- Chemical separation process, 4
- Chevron
 - Cat Dewaxing, 306–310
 - Isodewaxing, 313–317, 317–327
 - Oxidator BN, 197–200
 - Richmond Plant, 194–200

Clay Treating

- compositional changes, 164–168
- lubes finishing, 155
- nitrogen removal, 163, 129–131

Cloud Point, 7

Color, 7

Conversion processes, 7

Cresylic Acid, 142

D

Density, 6

DILCHILL process, 150–153

E

ExxonMobil

- free carbon index, 362
- GTL plant, 356, 360
- hydrocracking, 200–203
- MSDW dewaxing, 313
- MWI dewaxing, 313
- Raffinate hydroconversion, 201–204

F

Fischer-Tropsch process, 355–359

Flash Point, 8

G

Group III base stocks, 205–219

GTL base stocks, 358–362

H

HDA, 223–245

HDN, 250–253

HDS, 245–250

- effect on stability, 111–123
- Imperial Oil studies, 158–165

Hydrocracking, 171–219

Hydrofinishing

- aromatic ring changes, 158–162
- benefits, 156
- compositional changes, 164–168
- extraction severity, 164–168

- nitrogen removal, 162
- Tia Juana Light, 158–162
- thiophenic ring changes, 158–162
- Hydroisomerization, 312–331
 - comparison with solvent dewaxing, 316
 - introduction, 312
 - model compounds, 321
 - yields, 316
- Hydroprocessing,
 - chemistry of, 223–259

I

- IFP technology, 172–176
- Induction times,
 - GTL base stocks, 364
 - oxidation stability, 102–123
- iso-Paraffins,
 - boiling points, 40
 - pour points, 32–34
 - viscosities, 27–28
- ISO Viscosity system, 16

L

- Lubes finishing
 - clay treating, 154–155
 - hydrofinishing, 154–68

M

- Methyl-substituted paraffins
 - boiling points, 40
 - pour points, 32–34
 - viscosities, 27–28
- Miscibility, 149
- Mobil cat dewaxing, 293–306
- Mobil MLDW, 293–306
- Mobil MSDW, 313
- Mordenite zeolite, 284

N

- n-d-M method, 76–79
- Noack volatility, 8
- Nitrobenzene, 142
- Nitrogen compounds, 14,
 - hydrodenitrication, 250–253
 - effect on color stability, 162–163,
 - effect on oxidation stability, 127
- N-Methylpyrrolidone(NMP), 142, 147
- NMR Spectroscopy,
 - ¹³C applications, 93
 - Base stock properties, 96

- development, 88–90
- Fischer-Tropsch base stocks, 362
- petroleum pitch, 90
- wax, 90–93

O

- Optimum aromaticity, 111–123
- Oxidation stability
 - aromatics, effect of, 111–123
 - composition, 123–137
 - induction times, 102–120
 - mechanism, 100–102
 - oxygen uptake, 102–111
 - peroxides, 100–102, 117–120
 - sulfur compounds, 111–123
 - UV absorption, 132–136

P

- Paraffins, pour points, 31
- Petro-Canada plant, 189–192
- Phenol, 142
- Polycyclic aromatics
 - formation of, 242–245
 - lubes stability, 183–184
 - saturation of, 233
 - white oils, 335, 345
- Pour points
 - effect of composition, 29–36
 - branched paraffins, 31–35
 - measurement, 29–30
 - specification, 7
 - wax in gas oils, 34–36
- Process modeling, 258

R

- Raffinate, 69, 143
- Raffinate hydroconversion, 201–204
- Refined waxes, 348–351
- Refractive index, 9
- Refractivity intercept, 82

S

- Saturates, effect on oxidation, 125–126
- Separation processes, 4
- Shell processes, 184–189
- Solvent dewaxing
 - development, 148–149
 - membrane technology, 153
 - paraffin distributions, 150–151
 - process, 148–154

Solvent extraction

- hydrocracker feed preparation, 183,
- process, 141–148
- Raffinate Hydroconversion, 200
- Shell Hybrid process, 186
- solvents, 142
- stabilization, 210, 183
- thermal diffusion results, 69

Sulfur compounds

- effect on oxidation, 111–123
- hydrodesulfurization, 245

Sulfur Dioxide, 142**Sun Oil plant, Yabacoa, 180–184****T****Thermal Diffusion**

- basis, 63–66
- hydrocracked base stocks, 69–70
- solvent refined base stocks, 67–68
- VI distributions, 67–71

U**Urea dewaxing**

- adduct formation, 271
- commercial applications, 279
- comparison with solvent dewaxing, 288
- Edeleanu process, 280
- pour point profile, 277
- VI profile, 278

V**VI – see Viscosity Index****VI droop, 176–179****Viscosity**

- composition, 24–29
- cycloparaffins, 26–29
- empirical units, 23–24
- iso-paraffins, 27
- measurement, 21–24
- paraffins, 24–25

systematic units, 22–23

variation with temperature, 57

Viscosity grades, 16**Viscosity Gravity Constant, 9****Viscosity Index**

- alternatives, 57
- aromatics composition, 60–63, 68
- ASTM D567, 48
- ASTM D2270, 48–54
- base stock life, 125
- composition, 58–63
- condensed multi-ring cycloparaffins, 69
- cycloparaffin composition, 60–63
- Dean and David results, 43
- development, 43–57
- effect of paraffin structure, 321
- paraffin composition, 58–60

Viscosity Gravity Constant, 79**Volatility, 8****W****Wax**

- carbon number, 269
- composition, 266
- distribution, 270

White Oils

- 1st stage hydrotreatment, 340
- 2nd stage hydrotreatment, 340
- acid treatment, 337
- description, 335
- Food Grade, 335–336
- hydrotreatment, 337
- polynuclear aromatics, 336, 345–348
- product composition, 341
- Technical Grade, 335–336

Z**Zeolites**

- Mordenite, 284
- pore sizes, 295–302
- selectivity, 294, 298
- ZSM-5 channel structure, 295