

# Index

- Abrasion, 129, 153–155
- Additives:
- classification of, 472
  - importance of, 471–472
- Alumina trihydrate, 203
- Antiblocking agents, 472–473
- Antimony mercaptides, 291
- Antimony oxide, 140
- as pigment, 44–45
  - in flame retardance, 203
- Antioxidants:
- amine, 12–14
  - for condensation polymers, 30–32
  - for polyolefins, 27–29
  - for styrenics, 29–30
  - mobility of, 7–9
  - oxidation products of, 6–7
  - phenolic, 5–7
  - primary, 4–5
  - secondary, 9–12
  - selection of, 23–26
  - sources of, 33
  - testing of, 26–27
- Antistatic agents:
- function of, 473–476
  - sources of, 478
  - testing of, 476–477
  - types of, 477–478
- Asbestos fibers, 122, 144
- Basic lead carbonate, 278
- Biocides:
- as insecticides, 497
  - as rodent repellants, 497
- [Biocides]
- characteristics of, 496
  - in marine applications, 497–498
  - need for, 491–492
  - sources of, 492
  - types of, 495–497
- Biodeterioration:
- mechanisms of, 492–495
  - susceptibility to, 494
  - test methods, 498–499
  - test microorganisms, 494
- Blowing agents:
- activators for, 489–490
  - incorporation of, 490
  - inorganic, 483–485
  - organic, 485–489
- Carbon black, 143–144
- Carbon fibers, 122
- Cellular foam:
- chemically blown, 482–483
  - mechanical, 479–480
  - physically blown, 480–482
  - test methods for, 490–491
  - types of, 478–479
- Chromium oxides, 46
- Citrate esters, 428–429
- Color:
- factors affecting, 80–87
  - measurement of, 72–77
  - metamerism, 77–78
- Color matching:
- colorimeter measurement, 88–89
  - visual, 78–80

- Coupling agents:  
  addition of, 96–97  
  filler interaction with, 105–106  
  grafting of, 102–104  
  in polyolefins, 100–102  
  in styrenics, 104–105  
  in vinyl, 98–100  
  literature on, 106  
  mechanism of, 95–96  
  polymer interaction with, 97–98
- Degradation of halogenated polymers,  
  274–277
- Dibasic lead phosphite, 281
- Dibasic lead phthalate, 281–282
- Dibasic lead stearate, 283
- Dyes, 35–36
- Filled polymers:  
  diffusion in, 165–166  
  mechanics of, 156–158  
  moduli of, 160–164  
  stress-strain properties of, 164–165
- Fillers:  
  as extenders, 127  
  classification of, 126–127  
  color of, 144–145  
  current usage of, 168  
  dispersability of, 151–153  
  effects on processing, 155–156  
  hardness of, 153–155  
  packing of, 158–160  
  particle size of, 147–149  
  quality control of, 166–167  
  refractive index of, 145–147  
  rheology in plastisols, 158  
  surface area of, 149–151  
  surface treatment of, 151  
  whether to use, 125–126
- Flame retardants:  
  bromine containing, 187–196  
  chlorine containing, 198–199  
  in blends, 239–244  
  in epoxy resins, 255–256  
  in polyacrylates, 248–249  
  in polyamides, 244–248  
  in polybutylene terephthalate, 235–238
- [Flame retardants]  
  in polycarbonate, 230–232  
  in polyesters, 256  
  in polyethylene, 218–224  
  in polypropylene, 207–217  
  in PPO, 230–232  
  in styrenics, 224–230  
  in urethanes, 256  
  in vinyl, 249–255  
  market for, 266–269  
  mechanism of action, 174–178  
  phosphorus containing, 201–202  
  sources of, 270–271  
  usage summary, 197
- Flame tests:  
  cone calorimeter, 184–185  
  Federal Method 5903, 183–184  
  flame spread, 182–183  
  Motor Vehicle Safety Standard, 183  
  Ohio State heat release, 184  
  oxygen index, 179–180  
  UL94, 180–182
- Formulations:  
  blow molding, 460  
  calendering, 462–463  
  extrusion, 459, 461  
  injection molding, 464  
  thermoforming, 465
- Glass beads, 121–122
- Glass fibers:  
  compounding with, 119–121  
  fabrication of, 112–114  
  level of, 116–117  
  limitations in use of, 111–112  
  properties of, 115  
  reinforcement with, 107–111  
  sizings for, 118–119
- Hydrotalcite, 14–15
- Impact modification:  
  acetals, 343–344  
  engineering resins, 345–351  
  polyamides, 337–340  
  polycarbonate, 344–345  
  polypropylene, 335  
  PVC, 336–337

- [Impact modification]
  - styrenics, 336
  - thermoplastic polyesters, 340–343
- Impact modifiers:
  - commercial sources, 331–334
  - effect on properties, 351–358
  - product designations, 356
- Impact strength:
  - characterization of, 315–327
  - improvement of, 313–315
- Impact tests:
  - falling dart, 322–325
  - Izod, 316–321
- Iron oxides, 45–46, 142
- Kaolin clay, 130–131
- Lead stabilizers:
  - coprecipitated, 282
  - mechanism of action of, 277, 283–284
  - safe use of, 284–285
- Limestone, 128–130
- Lubricants:
  - action of, 363–365
  - aliphatic alcohols as, 377–378
  - amides as, 378–379
  - analysis and selection of, 384–387
  - esters as, 379–381
  - fatty acids as, 375–377
  - internal vs external, 365, 370–371
  - multifunctional, 387–389
  - stearates as, 381–384
  - summary of usage, 389–390
  - testing of, 366–369
  - waxes as, 371–375
- Magnesium hydroxide, 206
- Metal deactivators, 14–16
- Mixed metal stabilizers:
  - action of, 292–294
  - anions in, 296
  - bridged structures in, 293–294
  - epoxides in, 298
  - organophosphites in, 298–299
  - powder vs. liquid, 296–298
  - replacement of cadmium in, 294–295
  - role of alkaline earth metal in, 295–296
- Molybdenum smoke suppressants,
  - 264–265
- Monomeric aliphatic plasticizers, 425–426
- Optical brighteners:
  - analysis of, 404–405
  - commercial products, 417
  - in cellulosics, 415
  - in polyacetals, 415–416
  - in polyamides, 412–413
  - in polycarbonates, 414–415
  - in polyesters, 409–411
  - in polyolefins, 405–407
  - in PAN, 411–412
  - in PVC, 407–408
  - in styrenics, 408–409
  - in thermoplastic urethanes, 413–414
  - incorporation of, 404
  - lightfastness of, 400–401
  - migration of, 401
  - use with antidegradants, 403–404
  - use with pigments, 401–403
- Optical brightening:
  - effects on heat resistance, 399
  - mechanism of, 394–398
  - use in plastics, 399
- Organic fibers, 122–123
- Organotin stabilizers:
  - action of, 291–292
  - carboxylates, 288–289
  - mercaptides, 289–291
  - sulfur-bridged, 290
  - synthesis of, 286–288
- Oxidation:
  - effect of strain on, 8
  - initiation of, 3–4
  - mechanism of, 2–4
  - propagation of, 3–4
  - thermodynamics of, 1–2
- Phosphate esters, 427–428
- Phosphites:
  - as secondary antioxidants, 9–12
- Phthalate esters, 422–424

**Pigments:**

- azo, 55–64
- blooming, 85
- carbon black, 47–50
- classification of, 43–47
- current usage, 89–91
- dispersions of, 37–38, 87
- fluorescent, 68–69
- heat stability of, 82–83
- metallic, 50–52
- metallic sally, 52–55
- migration resistance, 83–84
- organic, 55–67
- particle size of, 38
- pearlescent, 68
- phthalocyanine, 65
- selection of, 81–82
- strength of, 41–43
- toxicity of, 69–71
- use of, 36–37
- weatherability, 84–85

**Plasticization, mechanism of, 419–420****Plasticizers:**

- applications, 431–432
- bibliography, 437
- compatibility, 420–421
- efficiency, 421
- formulations with, 434–435
- health concerns, 432–434
- permanence, 421
- properties of, 421–422
- relation of structure to properties, 422–430
- suppliers of, 436

**Polymeric plasticizers, 426–427****Processing aids:**

- effect on elasticity, 447–455
- effect on fusion, 441–443
- effect on melt viscosity, 455–456
- effect on rheology, 445–447
- function of, 439–440
- in extrusion, 458–459
- in PVC, 440–445
- sources of, 466
- summary of usage, 467
- types of, 456–458

**Red phosphorus, 257–260****Reodorants:**

- sources of, 500
- test methods, 500–501
- use of, 499

**Secondary plasticizers, 430–431****Silica:**

- fumed, 139–140
- precipitated, 136–139

**Silicates, 139****Slip additives, 472–473****Smoke density:**

- additives to decrease, 260–267
- measurement of, 185–187

**Solubility parameters. 384–385****Stabilization of flexible PVC:**

- calendered and extruded products, 307–309
- use of liquids, 305–306
- use of powders, 305
- wire and cable, 309–310

**Stabilization of PVC, steps in, 276–277****Stabilization of rigid PVC:**

- film and sheet, 302–303
- molded products, 303–304
- pipe, 300–302
- siding and profile, 302

**Talc, 131–136****Tetrabasic lead sulfate, 280****Thiodipropionates, 9–12****Titanium dioxide, 43–44, 141–142****Toughening of thermoplastics:**

- effect of glass transition, 326–327
- interaction with polymer, 327–331

**Tribasic lead sulfate, 279–280****Trimellitate esters, 424–425****Ultraviolet light absorbers:**

- benzophenone, 17–18
- benzotriazole, 18–19
- fillers as, 16–17
- hindered amine, 21–23
- miscellaneous, 19–21

**Zinc borate, 263–264****Zinc hydroxystannate, 265****Zinc oxide, 140–141**