

Subject Index

- Acrylonitrile-butadiene-styrene copolymer, 11,
52, 54, 74, 105, 122, 246, 302, 321,
336, 340, 354, 465
- Adhesion of materials, 338
- Air intake manifolds, 154, 184, 222, 256
- Alpha 1 machine, 344
- Arm rests, 257
- Autoclave vacuum molding, 287
- Automotive parts, 219
- Axiomatic design, 101
 - customer domain, 144
 - design parameters, 138, 144
 - functional requirements, 137, 144
 - independence axiom, 144
 - information axiom, 144
 - process variables, 138, 144
 - uncoupled, decoupled designs, 146
- Azdel™, 266
- Bellows, flexible and rigid, 258
- Bezel, TV, 75
- Birefringence, 398
- Blends, 294
- Blow molding
 - advanced, 230
 - appliance conduits, 256
 - decoration, 239
 - deep draw, 235
 - mechanism, 239
 - future applications, 255
 - inserts, 255
 - multimaterial, 253
 - parison positioning
 - moving mold, 249
 - robotic, 251
 - suction, 252
 - tiltable table, 249
- press blowing, 243
- processing conditions, 233
- resins, 232
- three-dimensional, 247
 - double wall, 234
 - injection molding comparison, 231
 - products, 233
- Bumper, 348
- Bumper beam, 299, 385
- Bumper fascia, 209, 257
- Caskets, 368
- Cell growth, 121
- Cells
 - open, 99
 - structure, 98, 101
- Cellulose acetate, 400
- Chair, 218
- Chest of drawers, 245
- Chopping boards, 245
- Clamp force, 202
- Class A finish, 218, 224
- Clutch pedal, 33
- Coextrusion, 294
- Coinjection molding, 41, 332, 364
- Compact discs, 399
- Compression molding, 282
 - matched metal, 287
 - melt application, 359
- Concurrent engineering, 457, 468
- Conduits, 241
- Container, 429, 432
 - insulated, 249

- Controlled density molding, 223
- Costs
 - avoiding, 463
 - optimizing, 463
 - understanding, 461
- Crack formation, 405
- Cut-N-Shoot, 391

- Darcy's Law, 274, 372
- Design guidelines, gas-assisted injection molding, 33
- Diaphragm molding, 287
- Die side injection, 221, 222
- Diffusion, 106
- Dual molding, 195, 220
- Ducts, 247

- Electronic enclosures, 224
- Environmental stress cracking resistance, 320
- Epoxy, 368

- Feedblock, 299
- Fiber, impregnation, analysis, 273
- Fiber reinforced composites, fiber lengths, 260, 262
- Fibers
 - glass, 263
 - reinforcing, 368
 - carbon, 263, 271
- Filler tube, gasoline, 253
- Filter plates, 210
- Finite element analysis, 412, 414, 419, 421, 429, 446
 - rib, 446
- Fittings, 220
- Fixtures, 219
- Fluoropolymers, 97, 131
- Food contact, 330
- Fountain flow, 401
- Fuel rails, 220
- Furniture, 219, 220, 224
 - office, 246
- Fusible core molding, 221
 - automation, 180
 - bismuth-tin alloy, 155
 - core casting, 158
 - core deformation, 165
 - core melting, 175
 - costs, 183
 - heat transfer, 166
 - mold design, 161
 - mold filling simulation, 162
 - process optimization, 160
 - runner systems, 163
 - sand cores, 153
 - soluble cores, 153
 - temperature profile, 170
 - thermosets, 175
 - tin-cadmium alloy, 155
 - alloy cycle, 179

- Gas-assisted injection molding
 - advantages, 6, 44
- Gas channel design, 35
 - channel geometry, 84
 - clutch pedal, 33
 - coinjection, 40
 - computer aided engineering
 - benefits, 63
 - data input, 68
 - mathematical formulation, 64
 - state of art, 62
 - continuous pressure generation, 3, 21
 - delay time, 56
 - design guidelines, 35, 82
 - discontinuous pressure generation, 3, 19
 - equipment suppliers, 19
 - fractional fill, 86
 - gas injection into mold, 12
 - gas injection module, 26
 - gas injection through nozzle, 11
 - gas injection time, 56
 - gas pressure, 52
 - gas recovery, 21
 - injection sequence, 13
 - liquid injection, 217
 - local increased wall thickness, 7, 34
 - mechanical properties, 31
 - melt temperature, 54
 - mold design, 26
 - mold filling, 49
 - panel shaped molding, 6
 - patents and licensing, 41
 - prefilled volume fraction, 52
 - primary gas penetration, 48
 - problematic conventional molding, 9
 - problems, 59
 - process cycle, 47

- processing conditions, 52, 68
- quality, 38
- rod-shaped molding, 6, 34
- secondary gas penetration, 48, 88
- shrinkage
 - gas pressure level, 18
 - gas pressure time, 18
 - polymer grade, 18
- troubleshooting, 39
- wall thickness
 - mold temperature, 16
 - polymer type, 17
 - reinforcement, 17
- warpage, 29
- Gelling number, 375
- Glass transition temperature, 111
- Handle, 3, 219
- Heat transfer, simulation, 166, 167, 375, 415
- Hele-Shaw flow, 375
- Henry's law, 109, 123
- Hood, automotive, 351, 383
- Hydrocarbon barrier, 315
- Hydroforming, 287
- Impingement mixing, 370
- Induction heating, 176, 294
- Injection molding
 - high pressure, 195
 - high speed, 196
 - press assisted, 357
- Injection-compression molding
 - sequential, 346, 360
 - simultaneous, 351, 355
 - vertical, 360
- Injection-stamping process, 348
- In-mold coating, 287, 360
- Just in time, 203
- Keyboard cover, 10
- Kinetic models, 371
- Kozeny-Carmen equation, 274
- Lamellar injection molding
 - advantages, 296
 - compositional uniformity, 302, 305
 - cycle time, 309
 - dimensional stability, 317
 - feedblock, 299
 - gate and runner design, 308
 - hydrocarbon barrier, 315
 - layer multiplication, 296
 - layer uniformity,
 - optical clarity, 317
 - permeability, 294, 303, 312
 - process reproducibility, 311
 - recycling, 31
 - rheological matching, 310
 - structure-property relationship, 303
 - temperature resistance, 323
 - tie layers, 309
 - wall thickness, 308
- Laminate molding, 195, 211
- Leaf spring, 446
- Lean molding
 - achieving change, 479
 - analysis software, 471, 477
 - compatibility issues, 455
 - costs and rewards, 475. *See Costs*
 - definition, 455
 - faster/better/cheaper, 460
 - implementation, 454, 470
 - manufacturing system, 472
 - mold builder, 455
 - molder, 455
 - monitoring benefits, 482
 - optimizing systems/components, 454
 - over-the-wall engineering, 457
 - problem avoider/solver/optimizer, 459
 - process and structure redesign, 476
 - product designer, 455
 - raw material supplier, 455
 - simulation. *See Simulation*
 - attitudes, 464
 - early work, 464
 - skills and responsibilities, 475
 - warpage, minimizing, 469
- Liftgate, automotive, 376
- Liquid crystalline polymer, 302
- Liquid gas assist, 195
- Lofting, 279
- Low pressure molding
 - characteristics, 194
 - cycle time, 198
 - enabled processes, 195
 - hydraulics, 205
 - materials, 199

- Low pressure molding (*continued*)
 melt temperature, 198
 mold design, 203
 plastication, 205
 pressure profile, 197
 shrinkage and warpage, 199
- Manifolds, 220
- Microcellular plastics
 advantages, 99
 batch processing, 125, 127
 cell growth, 121, 139
 continuous processing, 133
 extrusion, 134, 138
 definition, 97
 gas concentration
 crystallinity, 113
 glass transition temperature, 113
 mechanical properties, 113
 gas solubility-temperature-pressure, 125
 history, 94
 mechanical properties, 132
 microstructure, 103
 physical properties
 fatigue life, 142
 hardness, 142
 thermal conductivity, 141
 skin layer, 133
 supermicrocellular, 120, 121
 thermodynamic instability, 125
See Cells; Nucleation
- Migration of polymer, 209
- Mold design
 expanding core, 29
 gas-assisted injection molding, 26
 gating, 28
 multicavity molds, 27
 spillover cavities, 29
 undercuts, 27
- Molecular orientation, 398
- Multimaterial, blow molding, 253
- Multimaterial multicolor, 332, 364
- Multimaterial multiprocess
 adhesion of materials, 338
 advantages, 332
 Alpha 1 machine, 344
 commercial products, 352
 distortion, 341
 equipment, configurations, 342
 interface, 336
 sliding, 341
 plastic-metal composites, 354
 process sequence, 336
 shrinkage, 336
 thermal expansion, 335
- Multipoint volume injection control, 195, 207
- Multistation mold, 195, 202, 219
- Nucleation, 116
 competition with growth, 134
 crystalline and amorphous, 118
 heterogeneous, 103
 homogeneous, 104
 pressure drop rate, 136
- Orientation distribution function, 409
- Orientation/warpage prediction
 compression molding, 404
 converging flow, 413
 fiber orientation, 404, 415, 439
 finite element analysis, 412, 414, 419, 421, 429, 442, 446
 orientation distribution function, 409
 planar orientation, 408, 411
 property change with cure, 438
 reacting plate, 434
 residual stresses, 415
 modeling, 415, 417, 419
 sandwich beam, 421
 simulation
 box, 429, 432
 leaf spring, 446
 rib, 446
 test specimen, 433
 specific heat, 427
 specific volume, 426
 spring-forward effect, 434, 439, 440
 thermal conductivity, 428
 thermal strain, 439
 thermal stress-strain modeling, 438
 thermomechanical behavior, 414, 423, 451
 truck fender, simulation, 412, 442
- Overmolding, 220, 221, 333
 two shell, 222
- Over-the-wall engineering, 457

- Pallet, 346
- Panel
 - air conditioner, 247
 - automotive, 210, 215, 369
 - interior door, 357
 - blow molding vs. steel, 244
 - freezer, 73
 - water resistant, 227
- Peak melting temperature, 285
- Permeability, gas, 294, 303, 312
- Pipe fitting, 465
- Planter pots, 464
- Planters, 241
- Plating, automotive part, 465
- Polyamide, 11, 52, 54, 154, 164, 169, 174, 233, 263, 269, 302, 315, 317
- Poly(butylene terephthalate), 11, 209, 263, 267, 302, 310, 320, 323, 336, 340
- Polycarbonate, 11, 52, 54, 122, 209, 263, 302, 305, 310, 317, 320, 323, 340, 399
- Polyester, 323, 368
- Polyester, low shrink, 443
- Poly(etherarylketone), 174, 189
- Poly(etheretherketone), 263
- Polyethylene, 11, 105, 121, 122, 127, 130, 233, 242, 245, 263, 277, 294, 302, 304, 315
- Poly(ethylene-co-vinyl alcohol), 294, 302, 304
- Poly(ethylene 2, 6-naphthalene dicarboxylate), 325
- Poly(ethylene sulfide), 174
- Poly(ethylene terephthalate), 104, 105, 108, 111, 113, 118, 122, 129, 263, 265, 302, 315, 317
- Poly(methylmethacrylate), 111, 129, 302, 305, 317, 400
- Poly(methylpentene), 104, 105, 120, 122
- Poly(oxymethylene), 174, 354
- Poly(phenylene ether), 174, 245, 294
- Poly(phenyleneoxide), 11, 340
- Poly(phenylene sulfide), 263
- Polypropylene, 11, 56, 74, 96, 174, 200, 205, 211, 218, 220, 225, 233, 255, 264, 266, 267, 276, 277, 283, 285, 302, 315, 317, 336, 425
 - specific heat, 427
 - specific volume, 426
 - thermal conductivity, 428
- Polystyrene, 11, 95, 105, 123, 128, 141, 233, 245, 294, 302, 400
 - specific heat, 427
 - specific volume, 426
 - thermal conductivity, 428
- Poly(styrene-co-acrylonitrile), 315
- Poly(styrene-co-maleic anhydride), 302
- Polysulfone, 263
- Polyurethane, 96, 255, 302, 321
- Poly(vinylchloride), 105, 111, 122, 263, 340, 465
- Pool side products, 368
- Preform, 368
- Preforming, 387
- Pressure-volume-temperature, 423
- Programmable Powered Preform Process, 389
- Pultrusion, 265, 269, 271
- Pump
 - aircraft fuel, 189
 - automotive water, 187
- Race tracking, 385
- Reactive liquid molding
 - air conveying of fiber, 388
 - bladder preforming, 392
 - directed fiber, 388
 - economics, 391
 - efficient preform/fabrication, 369
 - faster reacting systems, 369
 - flexible resin transfer molding, 392
 - flow distribution, 392
 - kinetic models, 371
 - mixing activated, 386
 - mold vent location, 376
 - multiprocess preforming, 390
 - preforming, 387
 - simulation, 373
 - lift gate, 394
 - thermally activated, 386
 - variable injection rate, 392
- Recrystallization peak temperature, 285
- Recycling, 311, 333
- Refractive index, 398
- Resin transfer molding, 368, 386
- Reynolds number, 374
- Rheology, reacting materials, 372
- Rubber, thermoplastic, 205
- Rubber pad molding, 287

- Sanitary ware, 368
- SCRIMP, 393
- Seat, 211, 216
- Self-clamping mold, 195, 204
- Sheet molding compound, 96, 132, 289, 404, 420, 439
- Shell core molding, 195, 220
- Shipping cases, 241
- Shrinkage, gas-assisted injection molding, 18
- Simulation
 - combined with experience, 467
 - process change, 470
 - understanding tool, 466
- Simulation of mold filling
 - attitudes, 464
 - early work, 464
- Sink, 216
- Sink marks, gas-assisted injection molding, 2
- Slurry deposition, 267, 272, 389
- Spoilers, 257
- Spring-forward effect, 434, 439
- Stress-optical rule, 424
- Structural reaction injection molding, 386
- Styrene-acrylonitrile copolymer, 11, 302, 340
- Supercritical carbon dioxide, 110

- Table top, 7, 34, 224, 225
- Tait equation, 425
- Telephone booth, 353
- Tennis racquet, 155, 186
- Textiles, laminate molding, 211
- Thermal expansion, 334
- Thermoformable mat, 387
- Thermoforming, 281
- Thermoplastic cellular molding, 223
- Thermoplastic elastomer, 11

- Thermoplastic polyurethane, 11
- Thermoplastic sheet composites
 - commingling, 270, 271
 - coweaving, 270, 271
 - direct part forming, 279
 - fast compression molding, 282
 - film stacking, 265
 - melt impregnation by extrusion, 256, 272
 - melt phase stamping, 281
 - powder impregnation, 269
 - pultrusion
 - thermoplastic, 265, 271, 286
 - thermoset, 269
 - slurry deposition
 - lofting, 279
 - sheet consolidation, 278
 - solid-state stamping, 282
 - solvent impregnation, 264
 - thermoplastic vs. thermoset, 261
- Transfer molding, 294
- Truck fender, 412, 442

- Vacuum-assisted resin injection, 368
- Valves, 154, 220, 223
- Variable density molding, 195
- Vent, air, 354
- Viscoelastic behavior, 430

- Warpage
 - gas-assisted injection molding, 29
 - minimizing, 469
- Water meters, 154
- Weber number, 108
- Williams-Landel-Ferry equation, 431
- Window channel, 90
- Window frames, 224