
Index

- Aceto-acetic esters (acetylacetoxy),
36–38
- Acrylate (methacrylate), 23, 36, 37,
48, 50–52, 54, 60, 63, 64,
154–157, 222, 242, 243, 245,
249, 254, 293, 294, 341, 351,
375, 377, 378, 391, 406, 407,
411, 412, 428, 438, 439,
457
- Adiabatic temperature rise, 138,
175–180, 257–260, 270, 278
- Aging, 420–422, 429, 433, 440, 447,
456, 462, 464, 465
accelerated, 441, 452, 464
chemical, 422, 423, 465
humid, 421–423
hydrolytic, 433, 440
index, 446
photochemical, 421
physical, 126, 127, 129, 130, 166,
326, 345, 350, 352, 357, 358,
369, 371, 383, 422, 423, 465
radiochemical, 421
- [Aging]
thermal, 421, 446, 447, 454, 457,
459–462, 465
- Alkoxysilane condensation, 35, 75,
114, 213–216
- Amine reactions with
acid, 10, 12
cyclic anhydride, 10, 13, 17
epoxy (*see* Epoxy reactions)
isocyanate, 11, 18, 19, 23
ketone, 10
- Amino resins, 10, 32
- Anelasticity, 357
- Antiplasticization, 289, 298, 299,
334–336, 344, 346
- Argon's theory, 361, 364–366, 369
- Arrhenius law (number), 121, 124, 137,
140, 141, 258, 297, 339, 346,
347, 425, 449, 462, 463, 465
- Bismaleimide (BMI), 13, 17, 39, 128,
171, 294, 310, 365, 404, 453

- Block copolymers, 224, 239, 241–244, 405, 412, 414
- Blocked isocyanate, 21, 58
- Boltzmann's law/principle, 312, 325, 336
- Bowden's theory, 361, 365, 369
- Branching units/joints, 72, 82, 130, 208, 309
- B-stage formulation, 136
- Carboxy-terminated poly(butadiene-co-acrylonitrile) (CTBN), 227, 228, 230, 397, 398, 400, 405, 411, 413
- Cascade substitution, 74
- Castor oil, 231
- Cavitation, 391, 392, 396, 397, 399–401, 407–411, 414, 415, 422
- Ceiling temperature, 121, 446, 448, 452
- Chain scission, 423, 434–437, 440–442, 446, 454, 456, 460–462, 465
- Char formation, 134, 140, 141, 255, 273, 454, 461
- Chemical-controlled reaction, 150, 165, 168
- Cloud-point curve (CPC), 49, 134, 227, 230–236
- Clusters, 50, 192–194, 213, 215, 216, 222, 223, 306, 410
- Cohesive energy density (CED), 282, 284, 288, 290–294, 299, 300, 326–331, 334, 383, 426
- Cole-Cole plot, 341–344
- Compliance, 296, 325, 337, 338, 341, 343, 377, 382, 432
- Conductivity
 - ionic/electrical, 197, 199–203, 432
 - thermal, 182, 252, 256, 267, 268, 273, 276, 277, 376, 379, 380
- Constitutional repeating unit (CRU), 1, 8, 230, 283, 284, 287, 291, 292, 299–301, 303, 305–307, 309, 426
- Conversion-temperature-transformation diagram (CTT), 120, 134–139, 254, 279
- Core-shell (CS)
 - particles, 223, 224, 241–243, 390, 406–411, 414, 415
 - toughened networks (*see* Modified thermosets)
- Crack
 - appearance, 390, 392, 440, 444
 - arrest, 354, 356, 395
 - branching, 413
 - bridging, 393, 396, 397, 399, 400, 404–406, 413, 415
 - deflection, 395, 410, 413
 - front, 394, 414
 - (-front) pinning, 394, 404, 414
 - growth-rate, 381
 - initiation, 354, 377, 381, 383, 390, 395, 440
 - jump, 393
 - length, 355, 381, 382
 - opening displacement, 383
 - propagation, 354–356, 375, 381–383, 390, 392, 394, 395, 411, 412, 414, 445
 - resistance, 382, 403
 - tip, 355, 372, 383, 394, 395, 408
 - (-tip) blunting, 371, 375, 380, 394
- Crankshaft motion, 294, 298
- Craze, crazing, 358, 371, 383, 384, 392, 408, 409
- Craze-like structure, 358, 408
- Creep, 127, 297, 299, 325, 326, 330, 336, 398, 432
- Critical
 - composition/point/transition, 68, 70, 234, 235, 237, 398, 403, 404, 406, 415
 - conversion, 71
 - elastic strain energy release rate, 354–356, 371–377, 394–396, 398–401, 403, 406, 409, 413, 414
 - exponent, 191–194
 - gelation ratio, 89, 90, 94, 212

- [Critical]
 region, 189, 190
 stress intensity factor, 355, 356,
 371–375, 382, 383, 389, 403,
 404, 410, 411, 413
- Croiding, 408, 409, 411, 415
- Crosslink, 4, 215, 283, 301–303,
 305–308, 314, 358, 384, 410,
 459, 465
- definition, 72, 82, 103, 113, 213,
 306
- density (concentration), 52, 74, 82,
 91, 95, 98, 99, 103, 104, 113,
 191, 206, 222, 282, 287,
 300–302, 305, 313, 371, 427
- experimental determination, 315,
 316, 465
- fluctuations, 207, 208, 213, 221,
 300, 306, 309, 310, 313, 340,
 351, 375
- influence of termination
 mechanism on, 113, 114
- influence on properties, 5, 74, 121,
 123, 130, 284, 287–290, 293,
 299, 301, 302, 305–311,
 316–319, 323, 328, 334, 335,
 340, 344, 346, 347, 351, 358,
 361, 366, 367, 369, 372, 373,
 375, 399, 400, 459
- modification, 366, 367, 400, 410,
 423
- formation, 7, 98, 99
- functionality, 74, 92, 98, 99, 113,
 213, 302, 305–307, 313, 373, 435
- physical, 2, 50, 309, 384
- relationship with EANC's, 73, 82,
 91, 99, 104, 114, 305
- Crosslinked microparticles (CMP),
 221–224, 241, 245, 414
- Cyanate esters, 4, 11, 38, 100,
 127–129, 131, 132, 168, 169,
 255, 405, 406
- Cyclic anhydride, reaction with
 alcohol, 10, 13, 14
 amine (*see* Amine reactions with)
 epoxy (*see* Epoxy reactions)
- Cyclotrimerization, 38, 100–104, 131,
 132, 167–169
- Dangling chains/bonds (*see* Pendant
 chains/bonds)
- Deformation (mechanism), 357, 358,
 378, 389, 390, 415
- Degradation, 1, 2, 120, 134, 135–138,
 140, 141, 248, 252, 258, 267,
 291, 315, 316, 345, 423, 434,
 436, 437, 440, 441, 447, 452,
 453, 457–463
- Dendrimers, 223, 224, 241, 245
- Density (packing), 282, 286–289, 292,
 299, 327, 330, 343
- Devitrification, 2, 122, 126, 129, 134,
 141, 255, 279, 372, 431
- Di Benedetto's equation, 131
- Dicyanodiamide (Dicy), 27, 29, 134,
 213, 369, 409, 411
- Dielectric permittivity/properties, 5,
 122, 169, 186, 197, 199, 201,
 202, 255, 296, 297, 343, 346,
 432
- Diethylene glycol bis(allyl carbonate)
 (DADC or CR39), 63, 253
- Diffusion
 characteristic time of, 422, 429
 coefficient, 423, 428–430, 453
 -controlled hydrolysis, 434, 440, 441
 -controlled oxidation, 451, 452, 463
 -controlled polymerization, 5, 44,
 140, 150, 154, 156–158,
 165–169, 217
 solvent, water, 422, 423, 428, 432
- Diffusivity, thermal, 257, 275, 461
- Dilatation bands, 358, 408
- Dipoles, 197, 198, 255
- Dissipation band/peak/spectrum (*see*
 also Loss factor/tangent), 298,
 309, 331, 333, 336, 338, 339,
 341, 345
- Doolittle's constant/relationship, 317,
 346
- Double-bond reactivity, 218–220

- Elastically active network chain
(EANC), 73, 74, 82, 83, 91, 92,
99, 104, 114, 213, 301, 306,
307, 312, 435, 436, 442, 443,
461, 465
- Elasticity (rubber), 5, 187–189, 283,
311–315, 317, 344, 357, 384,
435, 436
- Embrittlement, 326, 384, 421, 435, 454,
456, 457, 460, 465
- Emulsifier, 239, 407
- Endlife criterion, 434, 435, 440, 446,
457, 462–465
- Epoxy formulation/resin, 1, 4, 25, 26,
127, 129, 130, 132–134, 226,
230, 245, 249, 251, 405, 421
- Epoxy network
 α -transition, 339
antiplasticization, 334, 335
Argon's theory, 365
 β -transition, 298, 339, 340, 358
Bowden's theory, 365
chain stiffness, 300–305
Cole-Cole plots, 342, 344, 345
crosslink density, 300–305, 310,
311, 335
degradation, 452, 454, 455,
459–462
density, 284–289
Eyring's theory, 363
Fatigue, 382, 383
formation, 83, 87, 89, 92, 141,
188–192, 194–203, 211, 212,
222, 263
fracture, fracture energy, 371–374,
376, 377, 400
free volume, 317, 318
front factor, 315
glass transition temperature,
300–305, 310, 311, 335
homogeneity, 206, 207, 211–213,
309, 310, 351
hydrophilicity, 425–428
impact properties, 378, 379
modified/toughened, 226, 227, 231,
232, 237–244, 340, 341, 376,
[Epoxy network]
[modified/toughened] 377, 390,
395–402, 404–407, 409–414
modulus, 289, 328, 331, 335, 342,
366
packing density, 287, 289, 290, 293,
294
plasticization, 431
Poisson's ratio, 330, 332–334
relaxation map, 325
thermal expansion, 290, 316, 401
von Mises criterion, 360, 361
water diffusion, 430
WLF constants, 317
yielding, yield stress, 366–370
- Epoxy reactions
homopolymerization, 52, 54–56, 84,
88, 105, 148, 150, 153, 213, 222,
253
with amide, 241, 464
with amine, 11, 24, 26, 27, 57, 58, 84,
88, 146, 148–153, 164–167,
170–172, 188–192, 213
with cyclic anhydride, 57–59, 128,
158–164
with isocyanate, 11, 19, 30
- Expansion
coefficient, 121–123, 126, 127, 290,
317, 346, 391, 401, 430
thermal, 290, 299, 316, 317
- Eyring's theory, 361–365, 369, 378, 383
- Failure (mechanism, strain, time-to-),
371, 375–381, 393, 446, 456, 457
- Fatigue, 356, 379–384, 389, 403, 409,
411, 412, 414
- Fick's law, 428, 429
- Flex parameter, 300–303
- Flory-Huggins' model/equation, 230,
237
- Flory-Stockmayer's theory/model, 74,
75, 192, 193
- Fracture, 5, 127, 206, 298, 299, 326,
350, 351, 353, 354, 356, 357,
371, 373–375, 377–379, 381,

- [Fracture]
383, 389, 392–397, 404, 406,
407, 409, 413, 414, 439, 440,
457, 465
- Fracture toughness (energy), 121, 226,
371, 374, 377, 384, 391, 393,
395, 397, 399, 400, 402–404,
406, 409, 411, 412, 414, 415,
445, 456
- Fragment approach, 5, 75, 97
- Free volume, 124–127, 157, 167–169,
282, 288, 299, 301, 306, 308,
309, 317, 318, 343, 346, 361,
362, 372, 425, 430, 459
- Functionality-average functionality,
96
- Gas permeability, 122, 453
- Gel, 2, 3, 82, 83, 88, 98, 119, 150, 192
effect, 45, 156, 217
fraction, 72, 74
physical, 2, 70
structure, 72, 73
- Gelation, 5, 31, 67, 68, 70, 71, 88–90,
93–96, 98, 110, 115, 116, 119,
120, 134–136, 140, 141, 151,
154, 165, 173, 186, 188, 190,
193–195, 199, 201, 212, 213,
220, 221, 234, 249–251, 253,
268, 269, 279
- Gel conversion/point/time, 7, 62,
68–72, 79, 87–90, 93, 94, 96, 98,
102, 110, 112, 115, 116, 119,
120, 134, 139, 140, 158, 160,
165, 186–194, 199–201, 207,
210–213, 221, 234, 236, 238,
270, 276, 309
- Glass transition (temperature), 2, 4, 5,
119–134, 165, 169, 186, 188,
199, 203, 211, 227, 238, 242,
245, 254, 266, 282, 283, 294,
297–311, 318, 323, 324, 327,
334, 335, 339, 340, 342,
345–347, 362, 367, 369–374,
376, 380, 383, 384, 389, 391,
[Glass transition (temperature)]
396, 399–403, 405, 409, 410,
412–414, 430–432, 440, 454,
457, 459, 462, 463
hysteresis, 126
- Glassy (vitreous) state, 4, 7, 71,
119–123, 125–127, 129, 131,
134–136, 138, 141, 166, 186, 253,
254, 262, 282–284, 287, 289,
290, 294, 295, 297, 299, 312,
313, 316, 318, 324, 326, 330,
337, 344, 347, 357, 362, 365,
366, 378, 392, 406, 407, 414,
431, 465
- Glycerophthalic (glyptal) resins, 14
- Griffith's energy criterion, 354, 355
- Havriliak-Nagami's model, 343–345
- Heat capacity, 121–123, 126, 127, 131,
138, 175, 256, 267, 269, 273, 276
- Heat deflection temperature (HDT),
121, 389
- Heat of reaction (polymerization), 2,
52, 129, 130, 135, 136, 138, 139,
174, 175, 182, 250, 252–254,
256, 264, 267, 274
- Henry's law, 424, 450
- Hybrid (composites, networks), 3, 35,
36, 390, 414
- Hydrolysis, 420, 422, 423, 433–435,
438–440, 442–445, 451, 465
- Hydrostatic pressure, 324, 350,
357–359, 361, 383, 396, 401
- Hyperbranched polymers, 223, 224,
241, 245, 401, 402
- Impact
energy, 376
fast, 283
modifier, 241
properties, 363, 376, 378
resilience, 378
resistance, 284, 378, 379, 389, 456
strength, 376, 378, 409, 415

- [Impact]
 test, characterization, conditions,
 356, 376–379, 399
- Inhomogeneities, 5, 71, 186, 206–215,
 217, 218, 220–223, 300, 309,
 340, 341, 351, 366, 374, 375,
 384
- Initiator, 7, 41, 42, 50, 52–58, 61, 62,
 106, 107, 109, 111, 127, 154,
 156–158, 160, 161, 164, 238,
 253
- Interaction parameter, 230–232, 234,
 315
- Interfacial adhesion, 239, 242, 390,
 392, 393, 400–402, 404–406,
 409, 410, 413, 414
- Intermolecular energy potential, 326,
 327, 329
- Intramolecular cycles/reactions, 27, 48,
 49, 71, 72, 74–76, 79, 92–94, 97,
 104, 108, 110, 115, 154, 171,
 206, 213, 215, 219–222
- Isoconversional method, 149, 153, 164
- Kamal's equation, 147
- Kambour's law, 364, 367, 432
- Kitawaga's theory, 365, 366, 369
- KWW model, 297, 337, 345, 347
- Lifetime, 43, 380, 381, 383, 420, 421,
 435, 437, 439, 446, 450, 452,
 461–464
- Linear elastic fracture mechanics
 (LEFM), 354–356, 440
- Liquid-crystalline polymers, 412
 nematic-isotropic transition, 4
- Living (controlled) polymerization,
 44–46, 67, 105, 158
- Loss (damping, dissipation) factor/
 tangent, 122, 123, 188–192,
 195–197, 201, 254, 255, 296,
 298, 310, 329, 330, 334, 337,
 338, 344
- Lower critical solution temperature
 (LCST), 231, 232, 234, 238
- Macosko-Miller's model, 75, 93
- Melamine-formaldehyde resin, 4, 29,
 32–34, 37
- Microgels, 49, 71, 110, 154, 173, 207,
 220, 221, 223, 224, 300, 414
- Modified (toughened) thermosets/
 polymer networks, 5, 186,
 226–247, 340, 355, 356, 358,
 371, 379, 389
- core-shell particles-, 406–411
- rubber-, 5, 120, 134, 249, 340,
 389–403, 409, 413–415
- thermoplastic-, 5, 120, 134, 255,
 340, 389, 393, 403–406, 413,
 414
- Modulus, 336, 337, 358, 366, 379,
 390, 393, 394, 403, 412, 414,
 415, 440
- bulk, 289, 292, 294, 323, 326–329,
 347, 392, 426, 427
- complex, 188, 296, 317, 337, 341,
 343, 344
- elastic, 34, 68, 69, 72, 74, 99, 100,
 189, 226, 311
- engineering, 323, 324
- equilibrium, 187, 193, 315, 342
- glassy, 313, 334, 336, 340, 342
- loss, dissipation, 122, 123, 188–194,
 201, 337, 344
- relaxation, 317, 325
- rubbery, 313–315, 342, 344, 347, 421,
 437
- secant, 311
- shear, 188–192, 313, 323, 329, 330,
 333, 347, 364, 365, 369, 392,
 435, 437
- storage, 122, 123, 188–194, 201, 337,
 344
- tangent, 313
- tensile, 289, 323, 330–332, 335,
 347
- ultrasonic, 289, 293, 328, 335, 426
- Young's, 121, 313, 330, 335, 352,
 355, 398, 401, 413
- Monte-Carlo simulation, 75, 104
- Mooney-Rivlin's equation, 314, 360

- Nanostructured networks, 223, 243
Nucleation-growth mechanism, 235
- Osmotic cracking, 423, 439, 440, 444, 445
- Oxidation, 415, 420, 447–453, 455, 457, 458, 460, 461, 463, 464
- Paris' law, 381, 382, 411, 412
- Particle size, 221, 237–239, 241, 245, 392, 394, 398–400, 402, 404–407, 409, 411
- Pendant chains/bonds, 48, 49, 71–74, 83, 91, 113, 148, 157, 219, 221, 283, 290, 300, 307–309, 351, 435, 437, 439, 442–444
- Percolation model, 192–194, 201
- Perez's model, 343–345
- Phase diagram, 227, 230–236, 404, 406
- Phenolic resins, 1, 4, 10, 29, 30, 34, 70, 88, 127, 255, 258, 298, 306, 340, 371, 459, 461
 novolacs, 31, 32, 88, 94, 95, 127, 133, 273, 276–278
 resols, 32, 70, 270, 272, 374, 375
 rubber-modified, 226
- Plasticization, 298, 308, 309, 334, 335, 340, 341, 351, 383, 389, 414, 425, 430–432, 465
- Poisson's ratio, 121, 323, 330, 332–334, 347, 352, 362, 401
- Polyamide, 10, 62
 as toughening agent, 241, 405
 - imide, 2
 synthesis, 12, 60, 406
- Polyester (saturated), 10, 12, 13, 36, 52, 54, 62, 96, 213, 215, 232, 316, 401, 402, 412
- Polyimide, 4, 10, 39, 129, 241, 298, 330, 340, 403, 405, 425, 427, 446, 448, 453, 461
- Polynadimide, 40, 298, 307
- Polysiloxane, 10, 34–36, 411, 412, 425, 427
- Polyurea, 11, 22, 23
- Polyurethane, 193, 194, 258, 261
 backbone, 52, 54, 341
 foams, 22, 23
 network formation, 129, 148, 175–180, 195, 211, 213, 215, 216, 351
 reaction injection molding (RIM), 22, 23, 250
 structure-property relationships, 300, 306, 367, 372
 synthesis, 11, 18, 22, 23, 50, 52, 195, 222
 ureas, 23, 250
- Poly(vinyl acetate) (PVAc), 50, 229, 232, 236, 340, 341, 402
- Preformed particles, 227, 241, 245, 389, 397, 405, 406, 411, 415
- Prepregs, 27, 226, 250, 263–265
- Processing (reactive), 2, 248, 249
 autoclave molding, 249, 250, 263
 bulk molding compound (BMC), 226, 250
 casting, 60, 63, 249, 273
 coating, 34, 71, 249, 250
 compression molding, 250
 electron beam cure (EB), 52, 253, 254, 279
 filament winding, 249, 251
 foaming, 23, 174, 249, 250, 253, 268–272
 injection molding, 2, 250
 microwave cure, 255, 279
 pultrusion, 249, 251
 reaction injection molding (RIM), 22, 60, 174, 250, 258, 278
 resin transfer molding (RTM), 62, 250
 sheet molding compound (SMC), 50, 226
 shell molding (Croning process), 249, 250, 272–278
 ultraviolet cure (u.v.), 23, 41, 51–55, 64, 253, 254, 279
 x-ray cure, 41, 253, 254

- Rabinowitch's model, 166
- Reaction heat (*see* Heat of reaction)
- Reaction-induced phase separation, 49, 50, 71, 108, 120, 134, 158, 172, 186, 212, 213, 216, 221, 222, 227, 232–236, 238, 239, 242, 245, 248, 255, 374, 391, 398, 401–406, 412, 413, 415
- Reactive liquid polymers (RLP), reactive liquid rubbers, 227, 228, 230, 391, 397, 398, 402, 403, 409, 413–415
- Reactivity ratio, 18, 26, 47, 49, 51, 65, 86, 89, 90, 148, 152, 157, 171–173, 177, 211
- Refractive index, 65, 122, 209, 407
- Relaxation (*see also* Transition), 126, 127, 173, 211, 264, 294–299, 311, 317, 325, 326, 330, 336, 339, 343, 345, 363, 369
- dielectric, 197, 199
- enthalpy, 129
- mechanical (stress), 196, 297
- secondary, 294, 347, 369, 375, 378, 379, 383, 384, 400
- spectrum, 194, 222, 294, 297, 337, 339, 342, 343, 347
- time, 2, 120, 167, 194, 294, 295, 297, 326, 341, 342, 344
- Robertson's theory, 361, 364, 366
- Rouse's model, 194
- Rubbery state, 4, 73, 74, 99, 119–125, 129, 135, 137, 147, 154, 186, 191, 199, 282, 283, 295, 306, 310–318, 324, 332, 344, 347, 362, 406–408, 414, 437
- Shrinkage, 2, 49, 50, 63, 65, 223, 402
- Sol (fraction), 2, 3, 68, 69, 72, 74, 81–83, 91, 98, 100, 103, 188, 207, 210–212, 309, 351
- Sol-gel (chemistry, process), 3, 35, 213, 215, 216
- Solubility parameter, 231, 291, 294, 299, 315, 426
- Specific heat (*see* Heat capacity)
- Spinodal demixing, 235
- Stochastic branching process, 74
- Stockmayer's equation, 110
- Strain hardening, 352
- Stress field (concentration), 249, 264, 353–356, 358, 371, 372, 374, 384, 390–392, 395, 399, 401, 408, 414, 433
- Styrene-divinylbenzene network, 48, 306, 427
- Substitution effect, 18, 26, 74–76, 86, 88, 89, 92, 93, 95, 97, 108, 119, 148, 157, 176, 177
- Swelling, 2, 283, 314, 315, 362, 431, 432, 465
- Tetraethoxysilane (TEOS), 35, 114, 115
- Thermal stability, 63, 446, 448, 452, 454, 457, 458
- Thermolysis, 448–450, 452, 453
- Time-temperature equivalence (superposition) principle, 124, 317–319, 326, 338, 345, 347, 376, 446
- Time (frequency)-temperature map, 282, 283, 296, 319, 325, 339, 345
- Time-temperature-transformation diagram (TTT), 120, 134, 139–142, 310
- Topological restrictions, 133
- Torsional braid analysis (TBA), 188, 189, 338
- Toughened network (*see* Modified network)
- Transition (*see also* Relaxation), 295–297
- α -, 123, 254, 295, 309, 324, 325, 334, 336, 339–343, 346
- β -, 295, 297–299, 318, 325, 328, 329, 331, 333, 334, 336, 339–343, 346, 357, 369, 375, 378, 379, 383, 384

- [Transition]
 ductile-brittle, 283, 356, 357, 361, 363, 364, 371, 378, 384, 391, 407, 415, 439
 glass (*see* Glass transition)
 secondary (subglass), 292, 295, 297, 299, 328–332, 339, 340, 346, 347, 375
 sol-gel, 3
 Tresca's criterion, 358–361
 Trommsdorff's effect, 45, 156, 217
- Unsaturated polyester (UP), 1, 4, 49, 51, 71, 110, 127, 129, 251
 bulk molding compound (BMC), 226
 crosslinking agent, 63
 low-profile, 50, 226, 232, 236, 340, 402
 low-shrink, 50, 232, 241, 402
 modified, 226, 231–233, 236, 242, 340, 402, 403
 network formation/properties, 148, 157, 172–174, 221, 222, 284–287, 289, 293, 294, 298, 306, 309, 315, 317, 318, 325, 330–333, 340, 341, 351, 365, 371, 425, 427, 428, 430, 431, 435, 444, 459, 460
 oligomer synthesis, 14–16
 sheet molding compound (SMC), 50, 226, 250
 structure-property relationship, 436–440
 thickening, 50
 Upper critical solution temperature (UCST), 227, 230–235, 238
- Urea-formaldehyde resin (UF), 1, 4, 10, 29, 32–34, 72
- Van der Waals, 2, 287, 290, 310, 327
- Vinyl-divinyl polymerization, 48, 67, 69, 108, 113, 148, 154
- Vinyl ester resin (VE), 51, 129, 231, 251, 254, 284, 287, 288, 293, 294, 298, 315, 328, 331–333, 340, 371, 402, 403, 406, 409, 425–427, 431, 435, 438, 439
- Viscosity, 3, 44, 50, 52, 62, 68–71, 187–189, 192, 193, 197, 201, 202, 217, 220, 221, 223, 227, 238, 242, 245, 250, 251, 258, 268, 270, 279, 317, 336, 364, 401–404, 406, 407, 411, 415
- Vitrification, 7, 65, 119, 120, 122, 125, 126, 129, 134–141, 146, 147, 151, 154, 156, 160, 164, 165, 167, 169, 186, 188, 194, 195, 199, 201, 231, 232, 234, 249, 253–255, 258, 262, 266, 267, 279, 335
- von Mises' criterion, 358–361, 396
- Water
 (ab)sorption, 422, 423, 425, 428, 430, 432, 433, 445, 465
 desorption, 345, 433, 462
 heat of dissolution, 425
 solubility, 424, 427
- WLF equation, 121, 124, 167, 168, 317, 318, 340, 346, 347, 360, 364
- Wöhler's curve, 381
- Yielding, 5, 127, 350–353, 356–358, 361–366, 369, 371, 374, 378, 383, 389–392, 396, 397, 399, 409, 411, 414, 415, 432
- Yield stress, 121, 299, 352, 353, 357–359, 361, 363–375, 378, 383, 389, 391, 396, 398, 399, 403, 410, 414, 415, 432, 433