

Index

- (Benzylamido) dimethyl
(tetramethyl- ζ -5-cyclopentadienyl) silanetitanium dichloride, 35
- (Ethylamido)-(tetramethyl- ζ -5-cyclopentadienyl)-methylenetitanium dichloride, 35
- (Methyamido)-(tetramethyl- ζ -5-cyclopentadienyl)-1,2-ethanediylzirconium dichloride, 35
- (Methylamido)-(tetramethyl- ζ -5-cyclopentadienyl)-1,2-ethanediyltitanium dichloride, 35
- (Phenylphosphido) dimethyl (tetramethylzirconium dibenzyl, 35
- (tert-Butylamido) dimethyl-(tetramethyl- ζ -5-cyclopentadienyl) silanetitanium dichloride, 35
- (tert-Butylamido)-(tetramethyl- ζ -5-cyclopentadienyl)-1,2-ethanediyltitanium dichloride, 35
- (tert-Butylamido)-(tetramethyl- ζ -5-cyclopentadienyl)-1,2-ethanediylzirconium dichloride, 35
- 1,2-Propylene oxide, 22
- 1,3,5,7,10-Pentaoxacyclodecane, 38
- 1,3,5,7-Tetraoxacyclononane, 38
- 1,3-Dioxane, 22
- 1,3-Dioxepane, 22, 39
- 1,3-Dioxolane, 22
- 1,4-Butanediol, 26
- 1,4-Dioxane, 22
- 1,6-Hexamethylene-di(N,N-ethylene urea), 39
- 11-Molybdo-1-vanadophosphoric acid, 24
- 1-Epoxyethyl-3,4-epoxycyclohexane, 28
- 2,2-Dimethyl-4-methylene-1,3-dioxolane, 27
- 2-Ethyl hexanoic acid, 25
- 2-Methylene-1,3-dioxepane, 27
- 4-Amino-2,2,6,6-tetramethylpiperidine, 34
- 4-Ethyl-1,3-dioxolane, 37
- 4-Isopropyl dioxolane, 37
- 4-Methyl-1,3-dioxolane, 37
- 4-Methylene-1,3-dioxolane, 27
- 4-Phenyl-1,3-dioxolane, 37
- Ablation vapor, 314, 315
- Acetic anhydride, 39
- Acid, 286, 288–291, 294
- Acid-catalyzed dehydration, 27
- Acidolysis, 264, 265, 270, 279
- Additive, 9–10, 13
- Agglomeration, 346, 347, 355, 366, 369
- Aggregation, 339, 341–343, 353, 370, 373, 386

- Aging, 261, 263
Alkali, 286, 292
Aluminium, 292
Aluminium oxide, 369
Aluminium Tri Hydroxide, 77
Amorphous phase, 243
Anhydride,
 acetic, 286
 propionic, 286
Anionic polymerization, 29, 31
Anisotropic growth,
 transcrystallization, 178, 185
Anisotropy, 109
Antennas, 303, 306, 312
Antioxidants, 54, 44
Antistatic agents, 79
Application, 2, 7–8, 11–12
Arc plasma, 314
Arc resistance, 315
ASHLENE®, 229
Automotive, 1, 7, 11–12, 286, 288
Automotive industry, 153, 156
Autoxidative scission, 264, 265
Avrami, 68
- Bacteria, 295
Bentonite, 340, 349, 350, 352,
 355, 376, 380
Bioaccumulation, 238
Biocompatibility, 343, 344, 385
Biofilm, 295
Biorenewable, 327
Bis(1,2-dimethylcyclopentadienyl)
 titanium dichloride, 35
Bis(1,2-dimethylcyclopentadienyl)
 titanium diphenyl, 35
Bis(cyclopentadienyl)hafnium
 dichloride, 35
Bis(cyclopentadienyl)hafnium
 dimethyl, 35
Bis(cyclopentadienyl)titanium
 diphenyl, 35
Bis(cyclopentadienyl)vanadium
 dichloride, 35
Bis(cyclopentadienyl)zirconium
 dichloride, 35
Bis(cyclopentadienyl)zirconium
 diphenyl, 35
Bis(cyclopentadienyl)zirconium
 monomethylmonochloride, 35
Bis(ethylcyclopentadienyl)zirconium
 dichloride, 35
Bis(methylcyclopentadienyl)zirconium
 dichloride, 35
Bis(pentamethylcyclopentadienyl)
 zirconium dichloride, 35
Blend, 376–381
Blow molding, 121
Boemite alumina, 376
Brittle-ductile transitions, 380
Burning, 267–270
- Calcium carbonate, 380
Carbon black, 328–329, 333, 370, 55,
 61, 74
Carbon fiber, 339, 345, 370
Carbon nanofibers, 336, 339, 341, 355,
 375, 380
Carbon nanotubes, 13, 333, 336, 337,
 338, 341, 353, 356, 363, 373
Carbon nanotubes (CNT), 288
Catalysts, 24
Cationic polymerization, 31
Compliance constant, 216
Chalking, 267
Chemical degradation, 250
Chemical interaction, 286
Chemical resistance table, 289–291
Chlorine, 286
Chloropropanol, 25
Circuit breakers, 313–315
Cleaning, 294
CNFs, 355, 360, 378, 380
CNTs, 332–334, 336–338, 341, 350,
 352–355, 363, 373–375, 385
Coefficient of thermal
 expansion, 260
Collocated meshes, 232

- Color, 266–267
- Color stability, 294
- Combustion, 269–270
- Commercialization, 4, 7
- Compatibilizer, 233
- Composites, 153–155, 159, 160
- Compression molding, 124
- Conductivity, 308, 321, 322
- Congeners, 238
- Consumer goods, 11–12
- Consumption, 6, 10–12
- Copolymer, 153, 154, 157, 159
- Copper, 292, 293, 370–372
- Creep, 341, 355, 377–380
- Crystal,
 - morphology, 173–178, 182
 - structure and properties of polymorphs, 165–172
- Crystal structure analysis, 195
- Crystal welding, 128
- Crystalline morphology, 112
- Crystalline phase, 244
- Crystallinity, 7, 257, 301, 307, 323, 327, 337, 341, 344–346, 347, 348, 350–354, 366, 373, 163, 165, 172–173, 181, 184–185
- Crystallinity Ratio, 242
- Crystallite modulus, 219
- Crystallization, 342, 345, 349–355, 374
- Crystallization behavior, 111
- Crystallization from polymer melt, 121
- Cumene hydroperoxide, 26
- Cyclic ether, 5
- Cyclic formaldehyde oligomers, 37
- Cyclic formals, 25
- Cyclic ketene acetals, 27
- Cyclopentadienylzirconium trichloride, 35
- Deactivators, 34
- Decomposition, 261–263, 266–267, 270
- Degradation, 286, 291, 292, 294, 328–329
- Dehydrogenation, 23
- Delrin, 229
- Dentistry, 294
- Depolymerization, 264–265, 278
- Devolatilization, 40
- Die-drawing, 135, 136
- Dielectric, 321–327
- Dielectric constant, 302, 303, 305
- Dielectric loss, 303, 305
- Dielectric Spectroscopy, 304, 308, 312, 340, 379
- Dimensional stability, 267
- Dimethylsilyldi cyclopentadienylzirconium dimethyl, 35
- Dioxolane, 34
- Diphenylmethane diisocyanate, 233
- Dipole-dipole interactions, 206
- Discoloration, 266–267, 271
- Dispersion, 332–335, 337–339, 341–344, 352, 355, 362, 364, 376, 377
- Division of markets, 12–13
- DMA, 347, 348–349, 365, 378
- Double screw extrusion, 117
- DSC, 348, 349, 352–354, 363
- Dyes, 72
- Dynamic thermogravimetry, 45
- ECC, 205
- Elastic constant, 216
- Electrical, 321, 323, 327
- Electrical conductivity, 336, 337, 373–375, 86
- Electrical industry, 153, 157
- Electron diffraction, 203
- Electronic industry, 153, 157
- Electronics, 11
- Electrospinning, 131, 181–182
- Electrostatic, 321

- Elongation at break, 337, 344, 355, 377, 381
- Elvax®, 46
- End capping (acetylation), 263
- Endcapping, 40
- Engineering thermoplastic, 1–2, 7
- Enthalpy, 259
- Environmental stress cracking (ESC), 291, 292
- Epichlorhydrin, 39
- Ethylene oxide, 286, 22
- Ethylenimine, 39
- EVA, 380
- Exfoliation, 237
- Extended chain crystal (ECC), 111, 132, 142
- Fancy goods, 153, 157, 154–155
- Fatigue Properties, 249
- FCC, 205
- Filler particles,
 - micro-sized Fe, 308–311
 - nano-sized alumina, 313
 - nano-sized fluorohectorite clay, 312
- Fillers, 82
- Finishing, 139
- Fire resistance, 362
- Flame, 268–270
- Flame retardant, 268, 270
- Flame retardants, 75
- Flash point, 268
- Flexural modulus, 287
- Fluorohectorite, 340, 380
- Folded chain crystal (FCC), 132, 142
- Food, 295
- Formaldehyde, 1–4, 6, 8, 264, 266–268, 286, 22
- Formic acid, 266–267
- Fracture Properties, 247
- Friction coefficient, 365–372, 385
- Friction-wear characteristics, 42
- Fuel, 267, 270
- Fuel cell, 293
- Fullerene, 341, 365, 366, 367
- Fungi, 295
- Gas permability, 89
- Generalized Newtonian model, 232
- Glass fibers (GF), 260–261, 267, 287, 288, 291
- Glass transition, 304, 305, 342, 347, 242, 231
- Glass transition (T_g), 257–258
- Glycerol monooleate, 230
- Glycerol monostearate, 230
- Grade, 2, 9–13
- Graphite, 334, 335, 341, 370, 372
- Hashin-Shtrikman bounds, 311
- HDPE, 380
- Heat conductivity, 83, 84
- Heat Deflexion Temperatur (HDT), 261
- Heat Release Rate (HRR), 270
- Hemiacetal, 263–265
- Heterogenous nucleation agent, 43
- Highly-oriented POM, 134
- High-performance POM fibers, 129, 130
- High-velocity compaction, 128
- Hindered Amine Stabilizers, 62
- Homopolymer, 321, 329, 153, 154, 159
- Hydrolysis, 264–265, 287
- Hydroperoxide, 265
- hydroperoxides, 280, 281
- Hydroperoxides decomposers, 54
- Hydrostatic extrusion, 119, 120, 135
- Hydroxyapatite, 343, 344, 351, 353, 354, 356, 364
- Hydroxybenzophenones, 60

- Hydroxybenzotriazole, 61
 Hydroxyl-terminated POM, 263
- Ignition temperature, 268
- Impact, 10–11, 13
 Impact modified, 260–261, 267, 287
 Impact modifier, 65
 Impact strength, 345, 346, 376, 377, 380
- Implant, 294
- Infrared spectra, 204, 207
- Initial decomposition temperature (IDT), 292
- Injection molding, 109
- Insects, 295
- Insoluble, 286
 insulation, 322, 327,
- Interfacial interactions, 335, 336, 338, 348, 352, 356, 359, 369
- Ionomers, 45
- Isothermal crystallization, 207
- Isotropic growth, spherulite, 171, 173, 176–178, 180, 184–186
- Joint venture, 5–6, 9, 12
- Kinetic parameters, 58
- Lamellar twisting, 122
- Latex, 377, 378
- Lattice dynamical theory, 193
- Lewis acid sites, 26
- Limiting Oxygen Index, 76
- Linear compressibility, 217
- Linseed oil, 230
- Lithium, 291
- LNP Lubricomp, 229
- Loss factor, 322–326
- Loss modulus (E''), 258
- Lubricants, alkali based soap, 292
 perfluorether oil, 291
 poly- α -olefin (PAO), 291
 silicone oil, 291
- Lubricating agents, 80
- Machining, 138, 139
- Magnetic, 322, 327
- Major consumer, 11
- Manufacturer, 7–9, 12
- Market share, 7, 9
- Mechanical, 322, 327–328
- Mechanical engineering, 156,,
 Mechanical properties, 181–186
- Medical applications, 153, 158, 159
- Melt blowing, 123, 124
- Melt extrusion, 116
- Melt flow rate, 231
- Melt spinning, 130, 131
- Melting temperature, Melting temperature (T_m), 257, 259
- Metaformaldehyde, 24
- Metal ion, 292
- Methyl stearyl formal, 39
- Methylene chloride, 24
- Methylphosphinedicyclopenta dienzylzirconium dimethyl Bis(indenyl) titanium diphenyl, 35
- Microfibrillar morphology, 131
- Micro-injection molding, 112
- Micromechanical Modeling, 245
- Microstructure, orientation, 171, 181–182, 184–186
 POM blends, 179–181
- Microwave, 321, 323, 325–327
- Mineral filler (MF), 260–261
- Modulus, 345, 346, 347, 355, 373, 242
- Modulus of elasticity (Young's modulus), 258
- Molar mass, 264, 271
- Molecular dynamics, 342, 343, 386
- Molecular mobility, 302, 306

- Molecular weight, 333, 335,
344, 354, 385
- Molecular weight distribution, 328
- Molybdenum disulfide,
364, 365, 367
- Montmorillonite, 332, 350, 351
- Morphology, 341, 342, 344, 345,
349, 351, 353, 355, 364,
370, 371, 383, 386
- Moth, 205
- MWCNTs, 337, 341, 372
- Nanoballs, 364, 367
- Nanocomposites, 153, 159, 160, 43
- Nanofibers, 131
- Nanosilica, 338, 339, 345,
351, 365, 370
- Nitrous fumes, 288
- Nondepletive sampling, 238
- Non-isothermal crystallization, 215
- Notched impact strength, 233
- Nucleating, 344, 349–353, 386
- Nucleating agent, 67
- Onset decomposition
temperature (T_d), 261–262
- Optical property, 329
- Orientation, 133, 134
- Oxidation, 280
- Oxidizing agent, 286, 288
- Oxygen index, 268–269
- Oxygen induction time, 44
- Partial discharge (PD)
technique, 317
- Patent, 4–5
- Peak mass loss rate (DTG_{max}),
261–262
- Pentamethylcyclo
pentadienylzirconium
trichloride, 35
- Percolation threshold, 308–310
- Permastat[®], 236
- Peroxide, 288, 290
- Phase,
amorphous, 265
change, 257
crystalline, 258–259
- Phase separation, 342, 343, 345, 348
- Phenolic antioxidants, 55
- Photothermal oxidation, 282
- Pigments, 72
- Plastic solid waste, 136
- Plasticization effect, 288
- Plumbing, 286
- Poly(amide) 6, 42
- Poly(dimethyl siloxane), 37
- Poly(methyl phenyl siloxane), 37
- Polyacetal, 1–2, 4–6, 12, 263
- Polyalkylene glycol, 292
- Polyethylene, 380
- Polyformal, 1
- Polyfunctional epoxides, 27
- Polymer,
backbone, 257, 263–264, 267, 269
blockcopolymer, 1, 6–7
copolymer (POM-C), 1, 5–7, 9,
257–261, 263, 266–167, 271
homopolymer (POM-H), 1, 4–9,
13, 257–261, 263–264,
266–267, 271
terpolymer, 1, 7
- Polymer fuel tanks, 237
- Polymeric acetal, 22
- Polymerization, 1–4, 6–7, 9
- Polyolefin, 269
- Polyolefins, 380
- Polyoxides, 269
- Polyoxymethylene (POM), 21
- Polyurethane, 359, 360, 376–378,
380, 66
- POM copolymers, 164–165, 172, 37
- Pomalux[®], 236
- POSS, 332, 335, 341–343, 347–348,
352, 355, 361–362
- Preparation methods,
- Price, 10
- Processing aids, 90

- Production, 6–7, 12–13
- Properties, 1–3, 7–9, 12
- Propylene oxide, 26
- PTFE, 335, 351, 352, 365, 366, 369, 370, 371
- Pyrolysis, 137
- Quality factor, 303
- Radical, 286, 328–329
- Radici*, 236
- Raman spectra, 204, 219
- Reactive blending, 43
- Recycling, 136
- Relaxation, 257–258, 263
- Relaxation processes,
 - α -relaxation, 304
 - β -relaxation, 305
 - γ -relaxation, 305
- Renewable, 327
- Resistivity, 327
- Resorcinol-formaldehyde resin, 235
- Rheological properties, 376
- Roll-drawing, 133
- Rolling, 125, 126
- Roughness, 294
- Row nucleated structures, 111, 121
- Rule-of-mixtures, 308, 311
- Self-heating, 129
- Semicrystalline, 1
- Shish-kebab morphology, 111, 112
- Sintering, 126, 127
- Small-angle X-ray scattering, 207
- Sodium, 290, 292
- Solid-state extrusion, 118
- Solubility, 57
- Solvent, 292
 - 1,1,1,3,3,3-hexafluoro-2-propanol (HFIP), 286
 - dimethylformamide, 286
 - ethanol, 288, 290
 - fuel, 286–288, 291–293
 - gasoline, 288, 292
 - hexafluoroacetone sesquihydrate, 286
 - isooctane, 288
 - methanol, 287–289
 - N-methyl-pyrrolidone, 286
 - p-chlorophenol-tetra chloroethane, 286
 - phenylmethanol, 286
 - toluene, 288
 - γ -butyrolactone, 286
- Soybean oil, 230
- Specific heat, 260
- Spherulite, 345, 349–351, 353, 373, 374, 380
- Spherulite crystals, 43
- Spinning, 129
- Steam sterilization, 270–271
- Stearic acid, 230
- Sterilization, 294, 295
- Stiffness, 258, 261
- Storage modulus (E'), 258
- Strength,
 - tensile, 291
 - ultimate, 287
- Stress distribution, 219
- Stress-induced crystallization, 134
- Sulfur dioxide, 288
- Superdrawn POM fibers, 134
- Surface,
 - polarity, 293
 - tension, 293
 - treatment, 294
- Surlyn*, 46
- SWCNTs, 338, 341, 363
- Swelling, 287
- Synchrotron, 196
- Tait equation, 229
- Temperature jump, 207
- Temperature of Deflexion under Flexural Loading (TDFL), 261
- Tensile drawing, 136

- Tensile modulus, 130
Tensile strength, 261, 267–268, 345, 373, 376, 233
Terminators, 34
Tetrahydrofuran, 22, 26
Thermal analysis,
 differential scanning calorimetry (DSC), 259
 dynamic mechanical analysis (DMA), 258
 thermogravimetric analysis (TGA), 261–263
Thermal conductivity, 260, 370, 372, 373
Thermal cycling, 82
Thermal oxidation, 286
Thermal stability, 4–5, 7–8, 263, 266–267, 269, 333, 336, 347, 356, 359–364, 385
Thermally stimulated depolarization currents (TSC), 304
Thermogravimetric analysis (TGA), 292
Thermo-oxidative degradation, 263, 266
Thermoplastic, 321
Titanium dioxide, 346, 73
Toughness, 288, 335, 340, 341, 347, 354, 355, 376, 377, 380, 233
Transition dipole moment, 206
Triazine, 61
Tribochemical reaction, 372
Tribological properties, 365–372, 87, 235
Triethylammonium hydrogen triflate, 36
Trifluoromethanesulfonic acid, 36
Triglyme, 34
Trimerization of formaldehyde, 24
Trioxane, 5–7, 286
Trioxane Trimer of formaldehyde, 22
Twin-screw extruder, 45
UL 94, 269–270
Ultimate mechanical property, 216
Unital*, 236
Unzipping, 264–265, 286
UV absorber, 60, 62
Vanadyl hydrogenphosphate hemihydrate, 24
Vibrational spectroscopy, 193
Vicat softening temperature, 261
Viscosity, 335, 377, 378
Volatility, 56
Water,
 agressive, 286
 cold, 287
 drinking, 286, 287
 hot, 287
Water Absorption, 235
Wear, 365–372
Weiner bounds, 311
Wettability, 293
Whisker, 203, 205
Whiskers, 235
Wide--angle neutron diffraction, 198
Wide-anlge X-ray diffraction, 207
X-ray scattering, 193
Yellowing, 57
Young's modulus, 84, 217
Zinc, 292
Zinc chloride, 286
Zinc oxide, 292, 346
Zirconium dioxide, 345, 369
 in situ polymerization, 333, 334, 340, 345, 368
 mechanical mixing, 332
 melt blending, 333, 340, 342, 345, 352, 356, 364, 376, 377, 380
 solid mechanochemical, 333, 334, 386