

Index

- Abrasive wear, 234
- ABS *see* Acrylonitrile-butadiene-styrene...
- Absorption of light, 8
- Absorption of radiation, 368, 370
- Acids, chemical properties, 9, 395
- Acrylonitrile-butadiene-styrene (ABS) polymer, 24, 470
- Activation energy in self-diffusion, 285
- Adhesive wear, 234
- Adiabatic heating and creep, 302
- Aeroplanes:
 - airframes, 301–2
 - mechanical properties, 5
 - wing fatigue, 187–8
- Alkalis, 9, 365
- Allotropes, 268
- Alloys:
 - aluminium, 178–9, 258
 - ductility, 121, 133–4
 - ferrous, 465–6
 - metals, 134
 - solution hardening, 129
 - steel heat treatment, 467–8
 - strength, 121
 - temperature, 302–3
 - titanium, 214–15
- Aluminium:
 - alloys, 178–9, 258
 - bike frames, 462–4
 - components cost, 431
- Amorphous metal alloys (AMAs), 362
- Amorphous structures, 60, 65
- Anisotropy, 57–8, 358
- Anodizing, 393
- Anti-ferro-magnets, 354
- Archard wear constant, 229–30
- Archimedes' principle, 49
- ASM Materials Handbook*, 2
- Aspect ratio in open die forging, 418–19
- Asperities in friction, 232
- Atoms, 69, 252–3
 - packing, 59–62
 - ceramics, 62
 - glasses, 62–3
 - metals, 59–62
 - polymers, 63
- Attribute limits on charts, 95
- Backbones in polymers, 64
- Ball bearing race hardening, 442–3
- Bar charts:
 - embodied energy, 490–1
 - hydrocarbons consumption, 481
 - material property charts, 22–3
 - process-economic batch size, 431
 - process-mass range, 415
 - process-roughness bar charts, 423
 - process-section thickness, 416
 - process-tolerance, 422
 - shape-process, 420
- 'Barrelling', 418–19
- Barrier coatings (heat), 265–6
- Beams:
 - clamping, 88
 - elastic bending, 84–6
 - floors, 102–3
 - light stiff, 93
 - plastic bending, 144
 - shape effects, 152–3
 - vibration modes, 88
 - weight, 92–4
 - yielding, 142–4
- Bearings (friction and wear), 235–40
- Bending:
 - design, 104–6
 - stiffness of section shapes, 94
 - strength-limited design, 141–62
- Bi-metal cells, 399–400
- Bi-metal strip thermal properties, 261–2
- Bicycles:
 - frames, 462–4
 - strategy, 38
- Body-centred cubic stacking, 60
- Bohr, Niels, 354

- Boltzmann, Ludwig, 253
- Bond stiffness, 66–7
- Bottle openers, 32–3
- Boundary-layer lubrication, 235
- Brake disks, 238–40, 465–6
- Brass, 69
- Brittleness, 165, 175–6
- Brunel, Isambard Kingdom, 2
- Bubble charts, 22–3
- Buckling of columns and plate, 87
- Buildings materials cost, 101–2
- Bulk modulus, 51, 73

- Cables, 332
- Cans, 466–7
- Carbon dioxide emissions and footprint, 484
- Carbon steel, 466–7
- Carbon-reinforced polymers (CFRP), 101
- Cars, 466–7
- Case studies:
 - ball bearing race hardening, 442–3
 - bending design, 104–6
 - ceramic plug insulator shaping, 434–6
 - ceramics, 468–72
 - con-rods for high performance engines, 213–16
 - corkscrew levers, 154
 - cost of buildings materials, 101–2
 - couplings, 154–5
 - cracks, 217–18
 - crash barriers, 495–7
 - cushions and padding, 102–4
 - designing for fracture, 218–20
 - fail-safe design, 211–13
 - ferrous alloys, 465–6
 - foams, 102–4
 - forensic fracture mechanics, 209–11
 - glass, 468–72
 - hinges, 154–5
 - levers for corkscrews, 99–101
 - metal rolling, 157–8
 - metals-overview, 464–5
 - pressure vessels, 209–11
 - rail cracking, 216–17
 - resonance avoidance, 104
 - springs, 156–7
 - steel connecting rod shaping, 437–40
 - steel radiator joining, 440–2
 - thermoplastic CD case shaping, 436–7
 - vibration, 104
- Cast iron brake disks, 465–6
- Casting aluminium components cost, 431
- CD cases, 40–1, 436–7
- Ceramics:
 - atom packing, 62
 - ceramic matrix composites, 69
 - classification, 14–17
 - creep resistance, 293–4
 - defects, 119–21
 - microstructure, 452–3
 - plug insulator shaping, 434–6
 - processing, 468–72
 - stress-strain curves, 53, 113
- CES software:
 - computer-aided design, 98–9
 - computer-aided information management, 24–6
 - conductors, 341–3
 - corrosion, 406–7
 - cost model, 433–4
 - dielectrics, 341–3
 - environmental issues, 501
 - fatigue, 202
 - fractures, 183–4, 224–5
 - friction and wear, 243
 - heat, 271–4
 - high temperatures, 308–9
 - insulators, 341–3
 - magnetic properties, 364–6
 - manufacturing, 445–7
 - optical properties, 384–5
 - organizing materials and processes, 26–8, 77–9
 - plasticity, yielding and ductility, 138–9
 - science exploration, 138–9
 - stiffness-limited design, 109
 - strength-limited design, 161–2
- CFRP *see* Carbon-reinforced polymers
- Characteristics of materials, 1–11
- Charts:
 - computer-aided design, 98–9
 - creep behavior, 281–2
 - dielectric loss vs strength, 320
 - electrical properties, 317–20
 - electrical resistivity vs strength, 319
 - electrical resistivity vs thermal properties
 - conductivity, 318
 - embodied energy in structural design, 491–2
 - endurance limits, 194–5
 - European cars 2005, energy consumption vs fuel economy, 494

- fracture toughness vs yield strength, 468–9
- friction and wear, 229–31
- indices, 95–8
- limits, 95–8
- magnetic properties, 351–3
- modulus vs embodied energy, 492
- refractive index vs dielectric constant, 374
- refractive index vs reflectance, 374–5
- remanence vs coercive field, 351–2
- saturation magnetization vs susceptibility, 352–3
- specific strength vs specific modulus property, 471
- strength (950C) vs density, 283–4
- strength vs embodied energy, 492, 497
- stress vs temperature, 299
- thermal conductivity, 252, 318
- thermal properties, 249–51
- yield strength, 116–18, 468–9
- see also* Bar charts
- Chemical properties, 8–9
- Circular shafts and elastic torsion, 86–7
- Clamping of beams, 88
- Classification:
 - materials, 14–18
 - processes, 20–2
 - shape, 419–20
- Cleavage fracture, 175–6
- Closed packed hexagonal stacking, 59
- Clutches and friction, 238–40
- CMCs *see* Ceramic matrix composites
- Coefficient of friction, 228–30
- Cohesive energy in crystals and glasses, 66–8
- Color, 379–80
- Columns, 87, 142
- Compatibility in joining materials, 424
- Composites, 472–4
 - modulus and density, 69–71
 - strength and toughness, 179–80
- Compression, elastic, 83–4
- Compressive crushing strength, 115
- Computer-aided design, 2–3, 98–9
- Computer-aided information management, 24–6
- Computer-aided process selection in manufacturing, 432–4
- Con-rods for high performance engines, 213–16
- Concentration gradients diffusion, 285–6
- Conceptual design, 31
- Conduction (electrical), 7–8
- Conductivity (thermal properties), 6
- Conductors, 311–44
- Connecting-rods for high performance engines, 213–16
- Constraints in matching materials and design, 35, 38
- Consumption of materials, 480–3
- Contact stress, 147–8
- Continuous use temperature (CUT), 276
- Conversion factors, 498
- Copper alloys, 135
- Corkscrews:
 - corked bottle openers, 32–3
 - levers, 40, 99–101
 - levers strength, 154
 - selection of materials, 100–1
- Corrosion, 387–407
 - alkalis, 395
 - cells, 398–400
 - crevice, 402
 - fighting, 401–4
 - ions, 396–7
 - organic solvents, 395–6
 - pH, 396–7
 - selective, 401
 - water, 395
- Cost:
 - buildings materials, 101–2
 - casting aluminium components, 431
 - CES software, 433–4
 - materials, 94–5, 153
 - models, 428–34
 - shaping processes, 427–32
- Couplings, elastic, 154–6
- Cracks:
 - crack tip plastic zone, 170–2
 - fatigue damage, 195–6
 - fatigue loading, 192–4
 - fracture-limited design, 204–5, 217–18
 - lengths of fractures, 172
- Cranks, 467–8
- Crash barriers, 495–7
- Creep:
 - adiabatic heating, 302
 - creep modulus of PMMA, 293–4
 - damage and fracture, 280–1
 - diffusion, 284–8
 - fracture, 291–2
 - polymers, 293, 294–5
 - power-law creep, 290–1, 298

- Creep: (*continued*)
 - relaxation, 302–4
 - resistance in design, 296–7
 - resistance in materials, 293–6
 - strength at 950C, 283–4
 - strength and density, 283–4
 - testing and curves, 278–80
- Crevice corrosion, 402
- Cross-section, section shapes, 84–5
- Cross-section area in three section shapes, 84–5
- Crushing (strength-limited design), 141–62
- Crystals:
 - cohesive energy, 66–8
 - crystallite polymers, 65
 - defects, 120
 - lattices, 61
- Cubic zirconia, 374
- Curves (creep), 278–80
- Cushions, modulus of foams, 102–4
- CUT *see* Continuous use temperature
- Cutlery, 465, 468
- Cyclic loading, 185–202

- Damage by creep, 280–1
- Damping, 186–7, 195
- Defects:
 - crystals, 120
 - dislocations, 120–1
 - grain boundaries, 120–1
 - metals and ceramics, 119–21
- Deflections, stiffness, 106–7
- Deformation mechanism diagrams, 291–2
- Deformation processing in metals, 456–7
- Degradation, 387–407
- Degrees of freedom in section shapes, 106
- Density:
 - creep strength, 283–4
 - density-modulus bubble chart, 23
 - modulus, 48–51, 69–73
 - properties, 4–5
 - relative, 102–3
 - science, 58–69
 - stiffness and weight, 47–80
 - stress, strain and moduli, 48–51
- Design:
 - conceptual, 31
 - constraints, 35
 - creep resistance, 296–7
 - design-limiting properties, 9–10
 - electrical properties, 331–8
 - flow chart, 31
 - fracture-limited design, 218–20
 - materials and process information, 34–5
 - process, 30–5
 - requirements, 30
 - shape, 35
 - strategic thinking, 29–46
- Development of materials, 3
- Dielectric properties:
 - behavior, 325–6
 - breakdown, 326–7
 - breakdown potential, 312, 316
 - dielectric constant, 7–8, 312, 314, 373–4
 - dielectric constant-refractive index chart, 373–4
 - light, 377–9
 - loss, 312, 316, 326
 - loss and microwave heating, 334
 - loss and radomes, 324–5, 334–5
 - loss and stealth technology, 334
 - loss and strength, 319–20
 - materials, 311–44
 - properties, 314–17
 - strength, 316
- Differential thermal properties expansion, 259
- Diffuse reflection, 369–70
- Diffusion:
 - concentration gradient, 285–6
 - creep, 284–8
 - flow, 288–9
 - heat, 262–3
 - intermixing, 287
 - liquids and non-crystalline solids, 288
 - thermal properties, 6
- Dilatation, 52
- Dipole (magnetic), 354
- Dislocations:
 - climb, 290–1
 - defects, 120–1
 - dislocation strength/yield strength ratio, 132–3
 - forces, 125
 - lattice resistance, 126
 - line tension, 125–6
 - plastic flow, 122–4
 - slip planes, 124
- Dispersion (precipitate strengthening), 129, 130–1
- Displacement-limited design (fracture-limited design), 208
- Documentation, 39, 412–13

- Domains, magnetic, 355–8
- Doping of materials for optical use, 380–1
- Ductility, 111–39
 - alloys, 133–4
 - definition, 114
 - ductile-to brittle transition, 177
 - fractures, 176–7
 - processes, 20
 - properties, 4
 - strength, 118–26
- Durability, 387–407

- E-relative cost chart, 96
- E charts, 96–7
- Eco-design, selection of materials, 493–7
- Einstein, Albert, 251
- Elastic bending of beams, 84–6
- Elastic compression, 83–4
- Elastic couplings, 154–6
- Elastic deflection of beams, 85
- Elastic design indices, 89–95
- Elastic extension, 83–4
- Elastic hinges, 154–6
- Elastic limits, 115
- Elastic moduli:
 - elastomers, 68–9
 - properties, 4
 - stiffness and weight, 47–80
- Elastic section modulus, 143
- Elastic torsion of circular shafts, 86–7, 145
- Elasticity, 111–39
 - energy, 54–5
 - meaning, 48
 - properties, 4
 - standard solutions, 82–8
- Elastomers:
 - classification, 14–17
 - elastic moduli, 68–9
 - microstructure, 453–4
 - processing, 470–2
- Electrical properties:
 - behavior, 312
 - charts, 317–20
 - conduction, 7–8
 - conductivity, 320–2
 - design, 331–8
 - insulation, 7–8, 332–3
 - materials, 7–9
 - plugs, 332
 - resistance, 322–5
 - resistivity, 319
 - resistivity vs elastic limits charts, 319
 - resistivity vs thermal conductivity chart, 318
- Electro luminescence, 380
- Electrochemical corrosion, 402
- Electromagnetic radiation, 368–9
- Electromagnetic waves, 375–6
- Electrostriction, 317
- Elongation, 114
- Embodied energy:
 - definition, 484–5
 - materials bar chart, 490–1
 - structural design chart, 491–2
- Embrittlement, 178
- End-of-life potential, 486
- Endurance limits:
 - charts, 194–5
 - endurance limit-tensile strength chart, 194
 - fatigue, 190–1
 - high strength metals, 215
- Energy:
 - consumption, 489–90
 - energy release rate, 168–70
 - fuels, 498
 - life cycles, 483–4
 - transport systems, 498
- Energy consumption vs fuel economy chart,
 - European cars 2005, 494
- Energy-limited design and fractures, 207
- Engineering materials consumption, 480–1
- Environment, 479–502
- European cars 2005:
 - energy consumption, 494–5
 - fuel economy, 494–5
 - unladen weight, 494–5
- Exercises:
 - character of materials, 10
 - conductors, insulators and dielectrics, 339–41
 - corrosion, 405
 - cyclic loading, 199–201
 - dielectrics, 339–41
 - environmental issues, 499–500
 - family trees, 26–7
 - flex, sag and wobble, 107–8
 - fracture-limited design, 221–3
 - fractures and toughness, 182–3
 - friction and wear, 241–2
 - heat, 270

- Exercises: (*continued*)
- high temperatures, 305–7
 - history of materials, 10
 - insulators, 339–41
 - magnetic properties, 364–6
 - manufacturing, 476–7
 - manufacturing processes, 445
 - matching material to design, 74–6
 - matching material to design, 44–5
 - optical properties, 383–4
 - strength parameters, 137–8
 - strength-limited design, 159–60
 - toughness, 182–3
 - wear, 241–2
- Expansion coefficients, 6, 247–8, 250
- Extension (elastic), 83–4
- Face-centred cubic (FCC) stacking, 59
- Fail-safe design, 211–13
- Family trees, 13–28
- Faraday, Michael, 315
- Fatigue, 187–04
- cracking, 195–6
 - ratio, 197
 - resistance, 196–8
- FCC *see* Face-centred cubic...
- Fermi, Enrick, 376
- Fermi levels, 376
- Ferry-magnetic materials, 355
- Ferro-electric materials, 320, 329–31, 337–8
- Ferro-magnetic materials, 355
- Ferro magnets, 7
- Ferrous alloys, 465–6
- Fiber composites, 472
- Fighting corrosion, 401–4
- Finishing:
- levels, 410–111, 421
 - see also* Surface treatment
- Flame retardants, 394
- Flammability, characterization, 388–90, 393–4
- Flexibility in design, 81–110
- Floors, 101–3
- Flow chart design, 31
- Flow and diffusion, 288–9
- Fluorescence, 380
- Flywheels *see* Spinning disks
- Foams, 71–3, 472–3
- Forces and dislocations, 125
- Forensic fracture mechanics, 209–11
- Fracture properties, 163–84
- crack lengths, 172
 - creep, 280–1
 - fracture toughness, 165–8
 - fracture toughness vs modulus chart, 172–3
 - fracture toughness vs strength chart, 172–4
 - fracture toughness vs yield strength chart, 468–9
 - fracture-limited design, 204–25
 - toughness, 4
- Fractures:
- modulus vs toughness chart, 172–3
 - strength vs toughness charts, 172–4
 - yield strength vs toughness, 468–9
- Free energy of oxidation, 390–2
- Free radicals, 394
- Free variables, 37
- Fresh water, 397–401
- Fresnel's construction, 373
- Friction, 227–43
- brakes and clutches 238–40
 - charts, 229–31
 - clutches, 228–30, 238–40
 - coefficient, 228–30
 - materials, 235–40
 - open die forging, 418–19
 - physics, 231–4
 - sliding, 233
- Fuels, energy contents, 498
- Galvanized iron, 403
- Gas-phase reactions, 393–4
- Gears, 467–8
- Geometry, joining, 424
- Glasses:
- atom packing, 62–3
 - classification, 14–17
 - cohesive energy, 66–8
 - microstructure, 452–3
 - processing, 468–72
 - temperature, 246
- Goodman's Law, 191–2
- Grain boundaries, 120–1, 132–3
- Grain structure evolution, 457–8
- Growth of consumption, 481–3
- Gyroscopes *see* Spinning disks
- Hard magnetic behavior, 8–9
- Hard magnetic devices, 351, 360–1

- Hardness:
 - hardening of materials, 131–2
 - scales, 116
 - test, 115
- HAZ *see* Heat-affected zone
- Heat, 245–72
 - capacity, 6–7, 247, 251–2, 257–8
 - diffusion, 262–3
 - exchangers, 264–5
 - heat-affected zone, 459
 - metals treatment, 458–9
 - sinks, 41–2, 333
 - storage heaters, 266–7
- High strength metals, 215
- High temperatures, 275–309
 - creep behavior, 278–84, 290–3
 - pipe work, 297–8
- High-cycle fatigue, 188–90, 196
- Hinges, bendy design, 105, 154–6
- History of materials, 1–11
- Hooke’s law, 52
- Hot processing in powder compaction, 459–60
- Hybrid materials, 15–18, 472–4
- Hydrocarbons consumption, 480–1
- Hydrodynamic lubrication, 235–6
- Hydrolysis reactions, 397–8
- Hydrostatic pressure, 50–1
- Hysteresis:
 - curves, 349–50
 - hard magnets loops, 360–1
 - soft magnets loops, 359
- I-beams, 466–7
- Impure water, 397–401
- Index of refraction, 371
- Indices:
 - charts, 95–8
 - elastic design, 89–95
 - fracture-safe design, 205–9
 - yield limited design, 149–53
- Information and magnetic storage, 361–2
- Information management, 24–6
- Initiation-controlled fatigue, 188
- Injection molding, record, 25
- Injectors for diesel engines, 337–8
- Inkjet printers, 335
- Insulation, 311–44
 - electrical, 7–8, 332–3
 - thermal properties walls and barrier coatings, 265–6
- Intermixing and diffusion, 287
- Interstitial solid, 120–1
- Ionization in electrochemical reactions, 397–8
- Ions and corrosion, 396–7
- Iron (galvanized), 403
- Joining:
 - attributes and origins, 423–6
 - joint geometry and mode of loading, 424–5
 - joints thermal properties, 261
 - physical limits, 425–6
 - processes, 18–19, 20–2, 459–60
 - selection of materials, 410–11
- Joists (floor), 101
- Joule, James, 168
- K_c-E chart, 208–9
- Kevlar, 474
- Kinetics, 390–1
- Laminates, 474
- Laser hardening, 460–1
- Lattice points, 61
- Lattice resistance and dislocations, 126
- Lever for corkscrews, 99–101
- Life cycles of materials, 483–4
- Light, *see also* Optical properties...
- Light and dielectric materials, 377–9
- Light and materials response, 8
- Limiting oxygen index (LOI), 389
- Limits in charts, 95–8
- Line tension and dislocations, 125–6
- Linear temperature dependence, 276–8
- Linear thermal properties expansion coefficients, 247–8, 250
- Liquids and diffusion, 288
- Loading:
 - load-limited design and fractures, 206–7
 - modes, 49, 82
 - stress, 48
- Lodestone, 346
- LOI *see* Limiting oxygen index
- Lorentz force, 357
- Lorentz, Hendrik, 357
- Low-alloy steel, 465
- Low-carbon steel, 465
- Low-cycle fatigue, 188, 190–2, 196
- Lubrication, friction and wear, 235–40

- Magnetic properties, 7–9
 - anisotropy, 358
 - charts, 351–3
 - definition, 346–9
 - dipole, 354
 - induction, 346
 - information storage, 361–2
 - materials, 345–66
 - measurement, 349–51
 - physics, 353–8
 - read/write heads, 362
 - vacuum, 346–8
- Manufacturing:
 - constraints, 424–5
 - materials and process information, 31
 - processes, 31, 409–48
- Market need and design process, 30
- Martensite, 467–8
- Materials:
 - compatibility matrix, 414
 - consumption, 480–3
 - cost, 94–5, 153
 - design and strategic thinking, 29–46
 - fracture toughness, 167–8
 - life cycles, 483–4
 - material selection/process selection coupling, 413–14
 - radiation, 368–73
 - resisting creep selection, 295–6
 - springs, 156–8
 - volume, 153
- Maximum service temperature, 5–7, 246, 276, 282
- Mechanical loss coefficient in damping, 195
- Mechanical properties, 4–5
- Mechanics of fracture, 165–8
- Melting temperature, 246
- Metals:
 - alloys, 134
 - atom packing, 59–62
 - classification, 14–17
 - creep resistance, 293–4
 - defects, 119–21
 - deformation processing, 456–7
 - heat treatment, 458–9
 - metal casting and solidification, 455–6
 - metal matrix composites, 69
 - microstructure, 451–2
 - overview of processing, 464–5
 - photons, 377
 - rolling, 157–8
 - strength-toughness trade-off, 178–80
 - strengthening, 127–9
 - stress-strain curves, 53, 113
 - transparency, 376–7
- Microchips, heat sinks, 41–2
- Microstructures, 450–62
- Microwave heating, 334
- Miner's rule of cumulative damage, 192
- Minimum mass design, 495
- Minimum service temperature, 246, 276
- Mixtures of atoms, 69
- MMCs *see* Metal matrix composites
- Mode of loading, 49, 82, 424–5
- Models, cost, 428–32
- Modulus:
 - bar chart, 23
 - density, 69–73
 - dilatation, 52
 - foams, 102–4
- Modulus-density bubble chart, 23
- Modulus-density chart, 56–7
- Modulus-embodied energy chart, 492
- Modulus-relative cost chart, 57
- Modulus-strength chart, 117–18
- Molding, polymers, 20
- 'Mushy zone' (alloys), 417
- Mylar film, 134
- Micromesh, 393

- Non-crystalline solids, 288
- Non-linear temperature dependence, 276–8
- Nylon, 134

- Objective function equations, 90, 92
- Objectives in matching materials and design, 38
- Opaque materials, 369
- Open die forging, 418–19
- Openers (corked bottles), 32–3
- Optical properties:
 - design, 7–9, 381–2
 - materials for devices, 367–85
 - optical fibers, 382
 - optical quality materials, 369
 - physics, 375–81
- Organic solvents:
 - chemical properties, 9
 - corrosion, 395–6
 - solubility parameters, 403–4
- Organization of processes, 18–21
- Original design of materials, 30–1

- Oxidation, 387–407
 - chemical properties, 9
 - definition, 388
 - measurement, 388–9
 - mechanisms, 390–2
 - resistance, 392–5
- Padding and modulus of foams, 102–4
- Paints, 427
- Panels:
 - objective function equations, 92
 - weight, 91–2, 150–2
 - yielding, 142–4
- Paramagnetic materials, 354
- Particulate composites, 472–4
- Pauli exclusion principle, 321
- PE *see* Polyethylene
- Pellets with embodied energy (PET) production, 484–8
- PET *see* Pellets with embodied energy (PET)...
- pH and corrosion, 396–7
- Phases in microstructure, 454–5
- Phosphorescence, 380
- Photo-conductivity, 381
- Photo-degradation, 394–5
- Photons, 375, 377
- Physics:
 - friction and wear, 231–5
 - optical properties, 375–81
 - thermal properties, 251–7
- Piezo-electric materials, 320, 327–8, 335
- Pipework and high temperatures, 297–8
- Planck's constant, 376
- Plane bearings, 237
- Plasticity, 111–39
 - elastic hinges, 154–5
 - metal rolling, 157–8
- Plastics:
 - bags, process-property interaction, 22
 - flow, 122–4, 126
 - hinges, 144
 - process-property interaction, 22
 - recycling, 487–9
 - section modulus, 144
 - strain, 113
 - work, 114
- Plate buckling, 87
- Plugs (electric), 332, 434–6
- PMCs *see* Polymer matrix composites
- PMMA creep modulus, 293–4
- Poisson's ratio, 54
- Polyethylene (PE), 21–2, 64
- Polymers:
 - atom packing, 63
 - classification, 14–17
 - consumption, 480
 - creep, 293–5
 - flammability, 393–4
 - hinges and springs, 156
 - Kevlar, 474
 - microstructure, 453–4
 - molding, 20, 456–7
 - plastic flow, 126
 - polymer matrix composites, 69
 - processing, 470–2
 - strength and toughness, 179–80
 - strengthening, 134–5
 - stress-strain curves, 53, 113
- Polypropylene (PP), 64, 65, 179–80
- Polystyrene (PS), 64, 374
- Polytetrafluoroethylene (PTFE), 64, 237
- Polyvinyl chloride (PVC), 64
- Powder compaction, 459–60
- Powder processing, 459–60
- Power-law creep, 290–1, 298
- PP *see* Polypropylene
- Precipitate strengthening, 129, 130–1
- Pressure vessels and fractures, 209–11
- Primary shaping, 18–19
- Process-economic batch size bar chart, 431
- Process-mass range bar chart, 415
- Process-property interaction, 21–2
- Process-roughness bar charts, 423
- Process-section thickness bar chart, 416
- Process-tolerance bar chart, 422
- Processing energy, 484–5
- Processing properties, 449–78
- Product design, 29–46
- Product disposal phase
- Product manufacture phase, 493–4
- Product materials, 29–46
- Product specification, 29–46
- Product use phase, eco-design, 494–5
- Production phase, eco-design, 493
- Proof stress, 112
- Propellers, 402
- Properties:
 - charts, 14, 22–4, 172–4
 - materials, 4–9
 - walls, 265–6

- Propagation controlled fatigue, 188
- PS *see* Polystyrene
- PTFE *see* Polytetrafluoroethylene
- PVC *see* Polyvinyl chloride
- Pyre-electric materials, 320, 328–9, 335–8
- ‘Quench and temper’ process, 459, 467
- Radiation by materials, 368–73
- Radomes and dielectric loss, 334–5
- Rail cracking and fractures, 216–17
- Random substitutional solid solutions, 129–30
- Ranking:
 - indices on charts, 95–8
 - selection for manufacturing processes, 412
 - strategy, 39
- Records of materials, 24
- Recycling, 486–9
- Redesign:
 - CD case, 40–1
 - design process, 31–2
 - transformer cores, 42–3
- Reduction (chemical properties), 9
- Reflection, 8, 368, 381–2
- Refraction:
 - definition, 8, 371
 - dielectric constant, 373–4
 - optical design, 381–2
 - optical properties, 8
 - refractive index, 373–5
 - refractive index vs reflectance chart, 374–5
- Relaxation of creep, 302–4
- Remanence (magnetism), 7, 348, 351–2
- Remanence vs coercive field chart, 351–2
- Requirements of design, 30
- Resistance:
 - creep, 293–6
 - fatigue, 196–8
 - oxidation, 392–5
- Resistivity (electrical), 7–8, 313–14, 318
- Resolution of stress, 132–3
- Resonance, 104, 186–7
- Reynolds, Osborne, 236
- Rolling bearings, 237–8
- Rolling of metals, 157–8
- Ropes, 472
- Roughness tolerances, 421–3
- S-N curves, 189, 214–15
- Sacrificial anodes, 402–3
- Sag of materials, 81–110
- Salt water properties, 9
- Sandwich panels, 474
- Saturation magnetization, 8, 352–3
- Scrap recycling, 486
- Screening:
 - attribute limits on charts, 95
 - selection for manufacturing processes, 412
 - strategy, 38
- Screw dislocation, 123–4
- Second moments, section shapes, 84–5
- Second moments of three section shapes, 84–5
- Secondary processes, 18–20
- Section shapes:
 - bending stiffness, 94
 - cross-section area and second moments, 84–5
 - flexural degrees of freedom, 106
- Section thickness, 415–19
- Selection:
 - manufacturing processes, 410–13
 - materials
 - for corkscrew levers, 100–1
 - for eco-design, 493–7
 - materials processes, 413–14
 - materials to resist creep, 295–6
 - processes, 413–14
- Selective corrosion, 401
- Shafts:
 - elastic torsion, 145
 - etorsion, 86–7
 - yielding, 144–6
- Shape:
 - beams, 152–3
 - design, 35
 - shape-memory, 268
 - strength of beams, 153
 - super elastic materials, 268
- Shaping:
 - attributes and origins, 414–23
 - characteristics, 419–23
 - cost, 427–32
 - primary, 18–19
 - processes, 20–1
 - selection of materials, 410–11
 - shape-process chart matrix, 420
 - stiffness, 94–5
- Shear modulus, 51, 73
- Shear strain, 52
- Shear stress, 50
- Ship’s propellers, 402

- Shot peening, 198
- Silicon carbide, 62
- Single atomic bonds, 118–19
- Sintering, 459–60
- Size (physical limits for shaping), 415–19
- Sliding friction, 233
- Slip planes, 124, 128
- Small objects shaping, 419
- Snell's Law, 371
- Soft magnetic devices, 8–9, 350–1, 358–60
- Solid solutions, 69
- Solidification in metal casting, 455–6
- Solubility parameters of organic solvents, 403–4
- Solution hardening, 129–30
- Specific heat, 247
- Specific stiffness, 90–1
- Specific strength, 50, 471
- Specular reflection, 369–70
- Spinning disks, 146–7
- Springs materials, 156–8
- Stainless steels, 393, 465, 468
- Standard reduction potential, 397–9
- Stealth technology, 334
- Steel connecting rod shaping, 437–40
- Stiffness, 47–80
 - bonds, 67
 - limited deflections, 106–7
 - science, 58–69
 - shaping, 94–5
 - specific, 90–1
 - stiffness-limited design, 81–110
- Stimuli strain, 56
- Storage heaters, 266–7
- Stoves, 393
- Strategic thinking, materials and design, 29–46
- Strength:
 - alloys ductility, 133–4
 - corkscrew levers, 154
 - definition, 48
 - dielectric loss, 319–20
 - ductility, 118–26
 - electrical properties resistivity, 319
 - fractures, 164–5
 - manipulation, 127–35
 - maximum service temperature, 282
 - metals strengthening, 127–9
 - polymers toughness, 179–80
 - strength (950C) vs density chart, 283–4
 - strength and limited design, crushing and bending, 141–62
 - strength vs density chart, 116–17, 151
 - strength vs embodied energy chart, 492, 497
 - strength-toughness trade-off in metals, 178–80
- Stress, 49–51
 - concentrations, 148–9
 - contact, 147–8
 - intensity, 165–8
 - resolution, 132–3
 - stress-free strain, 55–6
 - stress-strain curves, 52–4
 - metals, 113
 - single atomic bond, 118–19
 - stress-temperature charts, 299
- Structured data for records, 25
- Substitutional solid solution, 120–1
- Sulfur dioxide emissions, 484
- Super-elastic materials, 268
- Surface energy toughness, 174–8
- Surface engineering, 460–2
- Surface stress and shot peening, 198
- Surface tension of liquid metal, 416–17
- Surface treatment, 18–19, 20–1, 426–7
- Susceptibility chart, 352–3
- Taxonomy of materials, 17, 21
- TBC *see* Thermal properties barrier coatings
- Temperature:
 - alloys, 302–3
 - dependence, 276–8
 - gradients, 263
 - high, 275–309
 - materials to resist creep, 296
 - service, 246
- Tensile strength, 112, 164
- Tensile stress, 49–51
- Tesla, Nikola, 347
- Testing:
 - creep, 278–80
 - toughness, 165–6
- Thermal properties:
 - actuation, 260–2
 - barrier coatings, 300–1
 - buffers, 267–8
 - characteristics, 5–7
 - charts, 249–51, 252
 - conduction, 333–4
 - conductivity, 6, 318
 - charts, 248–50
 - manipulation, 257–8
 - physics, 255–7

Thermal properties: (*continued*)

- yield strength, 250–1
 - diffusivity, 6–7, 249–50
 - electrical insulation, 333–4
 - energy, 253
 - expansion, 254–5, 257
 - gradients, 262–4
 - imaging, 335–8
 - physics, 251–7
 - sensing, 260–2
 - shock resistance, 263
 - stress, 259–62
 - thermoplastics, 436–7
 - thermosets, 66
- Thin objects shaping, 419
- Tie-rods:
- design, 90–1
 - objective function equations, 90
 - weight, 89–91, 149–50
 - yielding, 142
- Titanium alloy S-N curve, 214–15
- Tolerance and roughness, 421–3
- Tools, 467–8
- Torsion in shafts, 86–7
- Total internal reflection, 371–2, 382
- Toughness:
- energy release rate, 168–70
 - fractures, 164–5, 176–7
 - test, 165
- Transformer cores redesign, 42–3
- Translation:
- heat sinks, 42
 - manufacturing processes, 411
 - strategy, 37, 39–43
- Translucent materials, 369
- Transmission of radiation, 368, 370
- Transparent materials, 369
- Transparent metals, 376–7
- Transport systems energy requirements, 498
- Tribology, 228–9
- Tungsten carbide, 62
- Turbine blades, 298–300
- UL *see* Underwriters Laboratory (UL) ...
- Ultraviolet absorption, 394–5
- Underwriters Laboratory (UL) rating, 389–90
- Unit cells, 60–2
- Unstructured data, records, 25
- UV radiation, 9

Vibration:

- atoms, 252–3
 - beams, 88
 - damping coefficient, 186–7
 - resonance avoidance, 104
- Vickers test (hardness), 115
- Viscous flow, 277–8, 416–17
- VOCs *see* Volatile organic compounds
- Volatile organic compounds (VOCs), 403
- Volume, materials, 153
- Volumetric strain *see* Dilatation

Water:

- chemical properties, 9
 - corrosion, 395
 - fresh and impure, 397–401
- Water molecule dipole moment, 326
- Watt, James, 331
- Wear, 235–40
- adhesive, 234
 - charts, 229–31
 - hardness chart, 230–1
 - materials, 239–40
 - physics, 234–5
 - wear rate, 228–31
- Weight, 47–80
- beams, 92–4
 - panels, 91–2
 - tie-rods, 89–91, 149–50
- Welding, 22, 459–61
- Wind tunnels, 266–7
- Wings of aeroplanes, 5, 187–8
- Wobble and stiffness-limited design, 81–110
- Work of fracture, 164
- Work hardening, 112, 129, 131–2

Yield strength, 164

- definition, 112
 - dislocation strength, 132–3
 - properties, 4
 - thermal conductivity, 250–1
- Yielding, 111–39
- shafts, 144–6
 - yield limited design, indices, 149–53
- Young's modulus, 51–2, 55, 73, 118

Zircon, 374