

CEMENT AND LIME MANUFACTURE

VOL. XXXV. No. 2

MARCH, 1962

Price 1s. 6d. Annual subscription 9s.
(\$1.75 in Canada and U.S.A.)

GRINDING
MEDIA
INFORMATION

USED AND RECOMMENDED BY

No. 1

"CRETOLIDS"

(Reg. No. 573298)

have been specially produced by us to meet the requirements of manufacturers for producing cement of extreme fineness. They have proved highly successful in finishing-mills without any cooling devices and, as with all our other types of grinding media, the wear-and-tear cost of "Cretoids" is infinitesimal. Free working samples are available on application.

THE WORLD'S LEADING CEMENT MAKERS


The comprehensive range of grinding media supplied by us and our unique experience in the cement industry in practically every country of the world enable us to give expert advice and to supply a type of grinding media that will provide the answer to any grinding problem.

HELIPERS LTD PHONE: GLOUCESTER 51402
GRAMS: HOLPERS, GLOUCESTER
PREMIER WORKS
GLOUCESTER

STEIN

Refractories

For Rotary Cement Kilns



STEIN MAG C
*The Basic Lining for
 Rotary Cement Kilns*

*Photograph by courtesy of the
 Billingham Division of ICI.*

STEIN MAG C offers

- * High resistance to clinker attack.
- * Forms clinker coating quickly.
- * High retention of coating during kiln shut-downs.
- * Excellent for oil firing.

From our range of High Alumina bricks and Firebricks we can also supply the correct type of Refractory to suit all zones in Rotary Cement Kilns.





Our long-standing experience with Cement Kiln Refractories is available to all users on request.

JOHN G. STEIN & CO. LTD., Bonnybridge, Scotland. Tel: Banknock 255 (4 lines) 361 & 362

Introducing the **FULLER GLASS BAG FILTER**

- as the solution to your hot dust problems
- a vital new weapon in industry's fight against hot corrosive dust and fumes
- broad temperature operation up to 600 deg. F. is permissible with siliconised fibre-glass cloth
- no creasing or fatigue to bags
- no moving parts or hazards to personnel




Sonic cleaning by low frequency vibrations at safe energy levels.

Write for full details to Dept. E.6.,
123 VICTORIA STREET, LONDON, S.W.1
Telephone TATe Gallery 0637

Constantin
(ENGINEERS) LIMITED

SOLE LICENSEES OF FULLER CO.,
CATASAUQUA, Pa., U.S.A. FOR THE
MANUFACTURE AND SALE OF FULLER
EQUIPMENT IN GREAT BRITAIN

These figures mean
**SUSTAINED HIGH-EFFICIENCY
 DUST PRECIPITATION**



CARRIBEAN CEMENT CO. JAMAICA	0.088 grains/ft ³ *
AUSTRALIAN CEMENT LTD. GEELONG	0.006 grains/ft ³
A.P.C.M. LTD. BEVANS WORKS	0.001 grains/ft ³

* (Stack emissions measured during official acceptance tests)

Over 70 electro-precipitator units have been individually designed
 and built by Lodge-Cottrell for the cement industry throughout
 the world, thus preventing air pollution from cement kilns.

The experience we have gained is at your disposal.

LODGE-COTTRELL LTD

George Street Parade, Birmingham 3.
 and at London, Brussels, Calcutta, Johannesburg, Sydney, Toronto.

MEMBER COMPANY



SIMON ENGINEERING LTD

"IT'S THE FINISH
THAT COUNTS"



Take that new SANDEX, for instance. It's a decorative finish that stands up to really severe conditions. Economical and very tough. It's been tested for *ten years*, too—under actual working conditions! That certainly gives it the go-ahead!

Then there's SNOWCEM. Nothing in this class of work comes near Super Snowcem's price and ease of application. Customers know the name... in fact it *pays* you to use it.

And in both cases, if you meet problems, you can always turn to the special technical service which the Blue Circle people operate.

SANDEX decorative finish

has amazing obliterative power. One coat gives good coverage with any colour. It is extremely tenacious even on bituminous surfaces. It is touch-dry and impervious to rain in minutes. There are 3 finishes—matt, textured and trowel. It is unaffected by lime bloom. There is a range of 21 colours in bold and pastel shades. It comes ready-mixed—ready to use and can be applied by brush or spray. Sandtex is the most economical long-term finish available.

SUPER SNOWCEM

is a waterproof cement paint made with a base of Snowcrete, the British white Portland Cement. It is supplied in powder form in free containers from 7lb to 112lb and requires only the addition of water to prepare it for use. When applied to suitable surfaces it provides a hard durable finish which resists the penetration of damp—will not rub, flake or peel off and may be washed.

For further information please write to:

THE CEMENT MARKETING COMPANY LIMITED, PORTLAND HOUSE, TOTHILL STREET, LONDON, SW1
Telephone: TATe Gallery 3456 - G. & T. EARLE LTD., HULL - Telephone: Hull 26121
THE SOUTH WALES PORTLAND CEMENT & LIME CO. LTD., PENARTH, GLAMORGAN
Telephone: Penarth 57301-4

Selling Organisations of The Associated Portland Cement Manufacturers Ltd.





**ALL
HAND FORGED**

BALLS FOR BALL AND TUBE MILLS

**STEEL
GRINDING BALLS**

In High Carbon and Chrome Steel
1" - 6" Diameter

**DESIGNED TO
GRIND FASTER,
LAST LONGER,
NEVER BREAK,
NEVER LOSE SHAPE**

*Also makers of fine hand-forged tools
for QUARRY and MINE*

F. J. BRINDLEY & SONS (SHEFFIELD) LTD.


CENTRAL HAMMER WORKS, SHEFFIELD, 1.

Phone and Grams: Sheffield 24201/2

Powder, Particles or Pieces ...

**TOTALLY ENCLOSED AND DUST FREE
NO ABRASION OF PLANT
OR OF MATERIALS HANDLED
LOW POWER CONSUMPTION**

VIBRATORY CONVEYORS




*a revolutionary method of
CONVEYING, feeding, mixing
and proportioning*

A remarkable method of conveying chemicals, ashes, coal and other materials, giving efficient dust-free transportation, extremely economical to operate and to maintain.

OWL ENGINEERING SUPPLIES LTD., Kirkstall Rd. Leeds 3 A MEMBER OF THE



**complete
electrification schemes
for the
CEMENT INDUSTRY**



FROM PLANNING TO COMMISSIONING UNDER A SINGLE CONTRACT


'ENGLISH ELECTRIC'

ELECTRICAL PLANT DIVISION · STAFFORD


PS.44

The English Electric Company Limited, English Electric House, Strand, London, W.C.2

See our exhibits on!STAND D 6, ELECTRICAL ENGINEERS EXHIBITION, Earls Court, March 20th—24th



POLYSIUS



WE INSTALL
CEMENT WORKS
ALL OVER
THE WORLD

POLYSIUS Ltd. / ASCOT, BERKS.

NI-HARD
NI-HARD
NI-HARD
NI-HARD

is increasingly being used
 by manufacturers in
 all parts of the world

**grinding
 media**

in all sizes
 and **MILL
 LININGS**

**ALSO SUPPLIED
 IN
 WHITE
 IRON**

more and more
CEMENT manufacturers
 are realising that NI-HARD GRINDING MEDIA have wearing
 qualities far greater than those of steel.

Let us send you our
 leaflet and prices, which will show
 how costs can be **GROUND** down to a minimum.

WYE FOUNDRY Co. LTD.

WILLENHALL, STAFFS, ENGLAND. TEL: WILLENHALL 65541/2 (2 lines)

The largest kilns in the world

COMPLETE CEMENT FACTORIES

•
Crushing, grinding, drying,
burning plants for all kinds of minerals




PHOTO PARIS MATIN

Alhandra cement factory (Portugal). View of the kiln (167.5 m x 4.8/5.3 m - 1600 T/day)

SAG - PARIS - 2022



FIVES LILLE - CAIL

7, rue Montalivet, PARIS (8^e) - Tél. : ANJou 92-01 et 32-40

LOW COST CRUSHING BY

IMPACT

Coking
coal

Iron
ore

Stowing
Material

Middlings

Slag


Limestone

Potash

Salt

Gypsum


High tonnage throughput with reduction ratios as high as 100 : 1 with some materials is possible with the Joy-Hazemag Impact Crusher. Choose from a range of 20 sizes—from 3 to 500 tons per hour capacity. Small, compact Joy-Hazemag Crushers offer low capital and operating costs—give efficient and economical crushing for a wide range of materials. Write for booklet giving full details and specification.



The Joy-Hazemag breaks material by impingement—uses less power and less space than conventional crushers. The principle? Material enters crusher against chain curtain, controlling feed rate—is flung violently against impact plates in crusher by fast-rotating blow bars mounted on rotor. Result? Material hitting impact plates—and itself—breaks up along natural lines of cleavage or weakness. Gives uniform, well cubed product of great strength. Selectivity reduces mixed materials—separates coal ores from stone, metal from slag, etc.

JOY-HAZEMAG *Impact* CRUSHERS

JOY-SULLIVAN LIMITED · GALLYWHITE LANE · DRONFIELD · NR. SHEFFIELD



“LOMA” FURNACE

The illustration shows a “LOMA” duplex, oil-fired FURNACE (no refractories) serving “LOESCHE” MILL engaged in grinding a mixture of limestone, anthracite and coke at the rate of 35 tons per hour with an average moisture of 4% and a maximum of 7%. 32,000 cu. ft. of air per minute at a temperature of 175°F. after the Mill. Entrance temperature about 400°F. Fuel is Bunker C oil. MILL fed by “LOESCHE” all-enclosed ROTARY FEEDER.

Also Feeders, Disc Pelletisers, Short and Medium Distance Pneumatic Conveyors.

DELO (ENGINEERS) LTD.

138 Borough High Street,
LONDON, S.E.1.

Tel: Hop 0085/6

Telegrams:

“CLAYCOMP, LONDON, S.E.1.” (INLAND)

“CLAYCOMP, LONDON.” (OVERSEAS)

Plants for making:

ASBESTOS CEMENT PIPES & SHEETS

WHITE CEMENT

SLAG CEMENT

PRESTRESSED CONCRETE

RAILWAY SLEEPERS

ASBESTOS CEMENT ENGINEERING CO.

P.O. BOX 34.649 Hauptstrasse 26, VADUZ, LIECHTENSTEIN, SWITZERLAND

PICKFORD HOLLAND MAGNECON BRICKS

used at the new
PLYMSTOCK PLANT
of Associated
Portland Cement Manufacturers
Ltd.

MAGNECON is the most widely used Basic Refractory Lining Brick in the world for lining Hot Zones of Rotary Cement Kilns

MAGNECON is used in Rotary Kilns of all sizes, up to the largest diameters

MAGNECON Bricks are manufactured in Great Britain by Pickford, Holland & Co., Ltd. by arrangement with Canadian Refractories Ltd. of Montreal

Pickford, Holland & Co. Ltd.

381 FULWOOD ROAD, SHEFFIELD, 10

Telephone: 33921

YOUR GRINDING CAN BE DONE ECONOMICALLY

From the experience gained in this field British 'Rema' manufacture two types of grinding plant both giving fine particles of almost any organic or inorganic material economically. The first consists of either a ball mill, ring roll mill or disintegrator followed by a classifier, cyclone and fan. The second plant being the ball mill, ring roll mill, pinned disc mill or disintegrator working in conjunction with an air separator. We shall be pleased to discuss your grinding problems, please fill in the request form.

BRITISH

REMA

To British 'Rema' Manufacturing Co. Ltd., One Industry Road, Sheffield, 9:
Please send data on "Grinding Plants" to:—

NAME

POSITION.....

FIRM

ADDRESS

BR48/CLM


**BRITISH 'REMA' MANUFACTURING
CO. LTD.**

PROPRIETORS: EDGAR ALLEN & CO. LTD.

ONE INDUSTRY ROAD • SHEFFIELD 9

Telephone: 42721/2

NOVO super 70 brand



A HIGH ALUMINA REFRACTORY FOR HARD DRIVEN FURNACES

From the table of properties it is immediately apparent that Novo 70 is a super refractory in the class of new materials available to furnace designers and operators. The high alumina content, in a tight, fine-grained structure of low porosity, provides a larger safety factor in applications where thermal shock, slag attack and abrasion are operational factors.

Al ₂ O ₃	over 75%
P.C.E.	Cone 36 (1790°C)
*Porosity	24-26%
*R.U.L.	5% subsidence at 1680°C
*C.C.S.	8,000-10,000 lb/sq. in.
P.L.C.	2 hrs. at 1600°C-nil

*Morgan Marshall Abradability Index below 100.

*Figures relate to standards and certain other shapes.

Novo Super 70 is particularly recommended for soaking pit and reheating furnace hearth and side wall construction, open hearth furnace uptakes, rotary kiln linings. Our technical staff will be pleased to advise on the applications of all our refractories.

BONNYBRIDGE SILICA & FIRECLAY



BONNYBRIDGE, SCOTLAND.


Telephone: Bonnybridge 227

Telegrams: "Silica" Bonnybridge



PLYMSTOCK

production capacity 220,000 tons of cement a year



NIAGARA

plays its part at Plymstock

This totally enclosed single deck Niagara screen installed at the Plymstock works of Associated Portland Cement Manufacturers Ltd. is one of four screens carrying out various grading duties throughout the plant. The enclosure as shown is specially designed for use with cement and gives exhaust connections for keeping air pollution to a minimum. The screen handles 100 tons per hour of finished cement, ensuring the extraction of oversize particles before passing forward to bulk loading plant.

Whether the material to be screened is dry, tacky or damp there is a Niagara that will tackle it with maximum efficiency and minimum maintenance.

NIAGARA SCREENS AND PLANT LTD.

Straysfield Road, Clay Hill, Enfield, Middlesex

Telephone: ENfield 6622



HIGH EFFICIENCY FABRIC DUST COLLECTORS FOR CEMENT KILN GASES

Tilghman's Limited, who specialize in high efficiency fully automatic fabric type Dust Collectors for cleaning gases at high temperatures, can now confidently offer a unit for cleaning rotary Cement Kiln waste gases at temperatures up to 600°F., considerably cheaper than present conventional methods with constant high collecting efficiency.


The collector houses tubular fabric sleeves made of a special silicone treated fibre-glass filter cloth. The excess dust is removed by a gentle collapsing of the tubes operated by a small fan in conjunction with simple plate dampers. The plants are simple to operate and fully automatic.

Good results being obtained abroad on these plants have been confirmed by tests carried out by one of the leading British Cement Manufacturers. These plants gave a collecting efficiency in excess of 98.6%, there being no real visible discharge to the atmosphere.

For further details contact:-

Tilghman's Limited

**BROADHEATH ALTRINCHAM CHESHIRE
LONDON OFFICE: 1 CHESTER ST. S.W.1**



For higher outputs with only one operator The Haver ROTARY Packer with or without pre-compacting for cement, lime, slag, plaster, etc., etc.

THE **HAVER ROTO PACKER**

Developed to meet arduous present day requirements.


Offers peak outputs of up to 110 TPH with eight spouts and one operator or 75-90 TPH with six spouts.

U.K. Representatives:-

CONTINENTAL ENGINEERING CO. LTD., London Road, Ascot, Berks.

Tel. No: Winkfield Row 395

At PLYMSTOCK WORKS



MIRRLEES IMO PUMPS
provide
Fuel Oil Supply
to the kilns

Steady flow, without pulsation or turbulence makes Mirrlees Imo Pumps especially suitable for Fuel Oil Burner Supply. Their reliability and compactness fits them for many other oil supply and transfer duties.



MIRRLEES (Engineers) LTD

EARL HAIG ROAD, HILLINGTON, GLASGOW, S.W.2

A Member of the Mirrlees Watson Group

Bet
your
boots
on




PEARSON refractories!


E. J. & J. PEARSON LIMITED · FIREBRICK WORKS · STOURBRIDGE

260-1

300 000 long tons/year




100 000 long tons/year




Vertical shaft kilns and
homogenising plants
in modern cement works

50-300 000 long tons/year

100 000 long tons/year



L. DE ROLL SA ZURICH/SWITZERLAND



A NAME AS
FAMILIAR AS CEMENT
ITSELF

F.L. SMIDTH & CO

You are invited to take advantage of our world-wide experience by consulting us regarding any problem connected with the manufacture of cement.

F.L. SMIDTH & CO. LTD.

105, PICCADILLY, LONDON, W.1.

Telephone: Grosvenor 4100.

Telegrams and cables:

Folasmith London.

CEMENT AND LIME MANUFACTURE

PUBLISHED ALTERNATE MONTHS.

PRICE 1s. 6d. A COPY

ANNUAL SUBSCRIPTION 9s. POST FREE
\$1.75 IN CANADA AND U.S.A

PUBLISHED BY
CONCRETE PUBLICATIONS LIMITED
14 DARTMOUTH STREET, LONDON, S.W.1

TELEPHONE: WHITEHALL 4681.
TELEGRAPHIC ADDRESS:
CONCRETIUS, PEARL, LONDON.

PUBLISHERS OF
"CONCRETE & CONSTRUCTIONAL ENGINEERING"
"CONCRETE BUILDING & CONCRETE PRODUCTS"
"CEMENT & LIME MANUFACTURE"
"THE CONCRETE YEAR BOOK"
"CONCRETE SERIES" BOOKS.

VOLUME XXXV. NUMBER 2.

MARCH, 1962





The Preparation and Chemistry of Expanding Cements.

By S. K. Chopra and Mohan Rai*.

SEVERAL mixtures have been described⁽¹⁾ for expanding cements by mixing calcium sulphate and calcium aluminate with ordinary Portland cement. The preparation of these cements is based on earlier work by H. Lafuma⁽²⁾ that the so called sulpho-alumina clinker is not an anhydrous calcium sulpho-aluminate though more recent work by A. Klein and G. E. Troxell⁽³⁾ indicates the contrary. Since the theory of expansive action is not fully understood and the raw materials are of variable nature, the writers have examined some of the methods of preparation with a view to determining their suitability. The composition, expansive characteristics and strengths of different trial expanding cements are recorded in detail elsewhere⁽⁴⁾, but the principal results are discussed in the following.

Cement of Series K.

P. P. Budnikov and Z. S. Kosuireva⁽⁵⁾ prepared an expanding cement by mixing ordinary Portland cement with an expanding agent consisting of a 1 : 1 mixture of calcium sulphate and dried hydration products of lime and calcined kaolin. The following reactions are believed to take place:—



*Central Building Research Institute, Roorkee, U.P. India.

TABLE I.—POTENTIAL OXIDE COMPOSITION OF TYPICAL EXPANDING CEMENTS (Expanding agent; Portland cement=1:3).

Constituents per cent.	Commer. cement	Group K			Group S			Group B			Group H		
		K1	K2	K3	S1	S2	S3	B1	B2	B3	H1	H2	H3
SiO ₂	19.42	21.40	21.11	20.80	22.31	22.18	22.59	19.50	19.50	18.78	18.55	18.38	18.55
Al ₂ O ₃	8.80	7.32	6.94	6.73	7.81	7.64	8.98	9.50	10.75	6.58	9.80	9.72	9.51
Fe ₂ O ₃	2.60	2.07	2.12	2.03	1.94	1.84	1.87	3.37	3.69	2.61	3.63	3.60	3.86
CaO	61.60	56.80	56.60	56.43	56.37	56.90	53.38	51.93	51.18	56.78	55.35	55.15	55.55
MgO	1.70	0.63	0.63	0.63	1.13	1.08	1.28	0.63	0.63	0.63	0.64	0.63	1.25
SO ₃	5.70	5.73	6.47	7.04	6.46	6.46	7.46	8.10	7.04	4.95	7.64	8.24	7.13
Loss on ignition	1.90	5.55	5.64	5.70	3.48	3.48	3.92	7.00	7.18	7.36	4.05	4.04	4.13

TABLE II.—EXPANSION AND COMPRESSIVE STRENGTH OF TYPICAL EXPANDING CEMENTS (Pastes of normal consistency)

Sample	Expansion (per cent.)						Compressive strength (lb. per sq. in.)	
	3 days	7 days	10 days	14 days	28 days	7 days	28 days	
K1	0.29	0.37	0.37	0.38	0.38	4140	6540	
K2	0.24	0.37	0.39	0.41	0.42	3850	6450	
K3	0.28	0.38	0.42	0.46	0.48	3700	5870	
KI	0.33	0.35	0.35	0.36	0.36	5940	7010	
KII	0.33	0.37	0.37	0.37	0.38	5170	6760	
KIII	0.28	0.38	0.42	0.44	0.44	4790	7140	
SI	0.20	0.30	0.37	0.49	0.80	3010	3900	
S2	0.18	0.29	0.36	0.46	0.86	3200	4820	
S3	0.15	0.21	0.26	0.34	0.64	3540	4370	
B1	0.19	0.29	0.35	0.45	0.80	3650	5550	
B2	0.15	0.25	0.33	0.41	0.86	3900	5270	
B3	0.14	0.23	0.29	0.38	0.80	3960	7030	
H1	2.13	3.10	3.11	3.11	3.11	5710	8520	
H2	1.10	2.03	2.31	2.31	2.31	6650	8560	
H3	1.02	1.80	1.83	1.84	1.84	—	—	

H1) 6hrs. in water
H2) at 70°C. plus
normal water
H3) curing at 27°C.

According to these investigators, the disruptive internal stresses are excluded because the hardening is not due to the reaction of tetracalcium aluminate ($4\text{CaO}\cdot\text{Al}_2\text{O}_3\cdot 12\text{H}_2\text{O}$) with calcium sulphate but rather mainly to the reaction of calcium sulphate and dicalcium aluminate ($2\text{CaO}\cdot\text{Al}_2\text{O}_3\cdot\text{aq}$). This statement is not borne out by the results of the writers' investigations. For example, the differential thermal and X-ray powder analysis of the hydration products of the first reaction showed the presence of higher calcium aluminates besides dicalcium aluminate and calcium silicate hydrates as envisaged in equation (A). In fact $4\text{CaO}\cdot\text{Al}_2\text{O}_3\cdot\text{aq}$ was found to be present in the largest quantity. This is in agreement with the findings of earlier investigators⁽⁶⁾ of this reaction. The presence of a small quantity of unreacted $\text{Ca}(\text{OH})_2$ showed that the reaction (A) did not proceed to completion within the recommended period of storing. This is understandable as the reaction is pozzolanic. In view of these results it was thought of interest to mix all the constituents, that is calcined kaolin, lime, gypsum and ordinary Portland cement, in a dry state and use this mixture as an expanding cement. After standardizing the quality and fineness of the various constituents, their optimum proportions were determined by trial, and were found to be the same as for the expanding cement prepared by the original method⁽⁶⁾. The corresponding data for the two series of the expanding cements (TABLES I and II) show that the results are comparable. However, the strengths of the cements K1, K2 and K3 are lower than the strengths of KI, KII and KIII respectively because the aluminates and silicate hydrates formed by the reaction of lime with kaolin do not contribute towards the strength and, in this method, their cementing property is lost during grinding. The three advantages which would result from the modified method (that is by mixing dry predetermined quantities of the various constituents) are a saving in equipment and energy required for lime and kaolin reaction, eliminating the processes of grinding and drying of the hydration products of the reaction (A), and eliminating the danger of carbonation which is inherent in the process.

Cement of Series S.

Suitable mixtures of super-sulphated cement and ordinary Portland cement have been suggested for use as expanding cements⁽⁹⁾. Indian slags contain a relatively higher alumina content⁽⁷⁾ (17 to 25 per cent.) and when activated with lime were found to result in the formation of calcium silicate hydrate and tetra-calcium aluminate hydrate. Therefore, a mixture of ordinary Portland cement, granulated slag, lime and gypsum in different proportions was tried as an expanding cement on the lines mentioned above. The expansion of these cements continued even beyond twenty-eight days. As a result of failures of attempts to arrest expansion, it may be concluded that a true expanding cement using slag as an alumina-bearing substance is not practicable. The compressive strengths of these cements are also poor compared with those of Portland cement. F. Keil and F. Gille observed⁽⁸⁾ that the addition of 10 per cent. of high-alumina cement to a mixture of Portland cement, granulated slag and gypsum stabilized

the expansion within fourteen days. The writers find that the expansion could be stabilized even within seven days by adding 15 per cent. of high-alumina cement. However, in such mixtures it is difficult to accept the view that high-alumina cement acts as a stabilizer.

Cement of Series B.

The use of a mixture of bauxite and calcium sulphate in place of sulpho-aluminate clinker has also been suggested⁽²⁾. Cements were, therefore, prepared as described in the foregoing. While the composition of cement B3 is approaching that of the commercial expanding (Lossier) cement⁽²⁾, the expansion is much less. An increase in SO_3 content to 7.04 and 8.1 per cent. respectively increased the overall expansion of the cements but the expansion could not be arrested within any reasonable period of curing. Any further increase in SO_3 content resulted in the disintegration of the samples.

With the exception of the cement B3, the two other cements showed expansion at twenty-eight days almost double that at fourteen days. Hydro-thermal treatment of the specimens on the lines suggested by Russian investigators⁽¹⁰⁾ stabilized the expansion within the first seven days, but the treatment did not give reproducible results even when calcined bauxite was used in the above mixtures. Since strict control was exercised over the quality of the constituents, the mixing, making, curing and testing of the specimens, the lack of reproducibility shows that the expansive action for this series of the cements is very sensitive and hence shows inconsistent behaviour.

Cement of Series H.

Some trials were also made to prepare "self-stressing cement" according to the Russian method⁽¹⁰⁾. A mixture of ordinary Portland cement, gypsum and high-alumina cement in the proportions of 74:14:12 (trial cement H1) gave the best results. The initial curing in water of the specimens at various temperatures for six hours confirmed the optimum temperature to be 70 deg. C. The highest expansions were obtained in the cement containing Portland cement clinker having a mineralogical composition of tricalcium silicate (C_3S)48, dicalcium silicate (C_2S)27, tricalciumaluminate (C_3A)11, and tetra-calcium aluminoferrite (C_4AF)8 per cent. The expansion of cements H2 and H3 in which Portland cement clinkers of lower C_3S content (42 and 38 per cent. respectively) were used resulted in less expansion. The cement H1 had an expansion of 3.1 per cent. and a strength of about 8500 lb. per square inch at twenty-eight days.

With the exception of the cements H1, all others failed to give the desired expansions or reproducibility. Since the samples of gypsum and Portland cement used in the various mixtures were of the same quality the only other materials of variable nature were the alumina-bearing substances such as kaolin, slag and bauxite. The quantity of mixing water could be another variable. These two variables are probably responsible for the different rates of dissolution of the various constituents and lack of reproducibility of the expansive characteristics

of the cements. When high-alumina cement was used as a source of the aluminates in preparing the Russian-type cement, the reproducibility was as good as claimed for commercial expanding (Lossier) cement. Therefore, it may be concluded that the preparation of the expanding agents by thermal treatment is probably better than by simple mechanical mixing.

The chemistry and mechanism of the expansion of the Russian-type cement have been studied⁽¹⁰⁾ extensively which is not the case with other expanding cements, not even M. Lossier's cement, the oldest of this type. The latest studies of calcium sulpho-aluminate admixtures for expanding cements by A. Klein and G. E. Troxell⁽³⁾ show the presence of a new compound not precisely identified, but which most likely is an anhydrous calcium sulpho-aluminate. This is contrary to the earlier observations of H. Lafuma⁽²⁾. Another contradictory result reported by the former investigators show that the sulpho-aluminate clinker of maximum expansive characteristics in mixtures with slag and Portland cement has a free calcium-oxide (CaO) content of about 19 per cent. In view of this the chemistry of M. Lossier's cement needs re-examination. It is quite probable that in the presence of such a high quantity of lime, ettringite may be formed entirely in a fine powder form and very little in crystalline form by the dissolution of the aluminate and reaction with calcium sulphate in solution as visualized by M. E. Perre⁽¹¹⁾. This is supported by the observation, that on hydration of the cement K₃ prepared by the method of P. P. Budnikov and Z. S. Kosuireva⁽⁵⁾, ettringite was formed both in crystalline and powder form as in M. Lossier's cement, but when cement KIII, prepared by the modified method and containing 7.2 per cent. of free lime, was hydrated, ettringite was formed mostly in the form of powder.

Though there is evidence^{(5) (9) (11)} that both forms of ettringite lead to expansion, either no attempt has been made, or it has been difficult to estimate, the relative amounts of the two forms with a view to correlating them with the magnitude of the expansion. The role of the stabilizer is also not clearly understood. Therefore, it is felt that further information on these matters is necessary to indicate a method of preparing expanding cement on a more rational basis.

In conclusion, the writers acknowledge the help of Dr. N. K. Patwardhan in preparing this article which is published by the permission of the Director, Central Building Research Institute, Roorkee, India.

REFERENCES

- (1).—F. M. LEA and C. H. DESCH, "Chemistry of Cement and Concrete," pp. 446-447.
- (2).—H. LAFUMA.—"Expansive Cement." Proceedings Third International Symposium on Chemistry of Cement, London, 1952, pp. 581-597.
- (3).—A. KLEIN and G. E. TROXELL.—"Studies of Calcium Sulpho-aluminate Mixtures for Expansive Cements." Proc. A.S.T.M. Vol. 58 (1958), pp. 986-1007.
- (4).—MOHAN RAI & S. K. CHOPRA.—"An Investigation on Expanding Cements." Proceedings 48th Session of Indian Science Congress. (1961).
- (5).—P. P. BUDNIKOV and Z. Z. KOSUIREVA.—"Sulpho-aluminate: A Positive Factor in Expanding Cement" (Sulfaluyminat Kak Polozhitelnui factor pripolu-

cheniirasshiryayushchevosya tsementa). Dokladi Akademii Nauk. U.S.S.R. (1948), pp. 681-4 (L.C. No. 489. B.R.S., U.K.).

(6).—GIOVANNI MALQUORI.—“Portland Pozzolana Cement.” Fourth International Symposium on the Chemistry of Cement. 1960, pp. 21-28.

J. CHAPPELLE.—“Reactions of Calcium Sulphate and Lime with Slags and Pozzolanas,” *Revue Mat. Construct. et Travaux*, pp. 231-42 (1958).

(7).—S. K. CHOPRA and KISHAN LAL.—“Sulphate Activation of Low Lime and High-alumina Slags.” *J. Sci. Industr. Res.*, Vol. 20D, No. 6, pp. 218-223, June 1961.

(8).—F. KEIL & F. GILLE.—“Sound and Unsound Expansion of Cement containing Blastfurnace Slag due to Calcium Sulphate.” *Zement-Kalk-Gips*. 1949, pp. 148-52. (L.C. No. 489. B.R.S., U.K.).

(9).—V. V. MIKHAILOV.—“New Development in Self-stressed Concrete.” World Conference on Prestressed Concrete. San Francisco. (1957), pp. 25-1 to 25-12.

(10).—V. V. MIKHAILOV.—“Stressing Cement: the Mechanism of Self-stressing Concrete Regulation.” Fourth International Symposium on the Chemistry of Cement. (1960).

(11).—M. E. PERRE.—“Ciments Sans Retraint; Ciments Expansifs.” Conference du Centre de Perfectionnement-Technique, Vol. 2, April, 1944, pp. 26-34; *Cement & Lime Manufacture*, July 1947.

Classification of Technical Literature.

THE third edition of the Abridged English Edition of “Universal Decimal Classification” (B.S.1000A : 1961), which is issued under the auspices of the International Federation for Documentation, was published recently by the British Standards Institution (price 60s.; obtainable from the Institution).

The references to cement and lime are as follows:—

Asbestos-cement: 666.858; 691.328.5	Gypsum: 666.84
Cements: 666.94	Lime industry: 666.92
Building material: 691.54/56 (cement); 691.51 (lime)	Refractory: 666.76

Proposed New British Standards for Special Cements.

THE preparation of new Standards for two types of special cements has been commenced by the British Standards Institution.

MASONRY CEMENT.—The Standard will probably include requirements for composition, fineness, soundness and setting time based on B.S. No. 12, “Portland cement.” Tests for water retentivity, plasticity, and workability or air entrainment may be included and will, as far as possible, be similar to those at present being prepared for a Standard for methods of testing. Strength testing will also be included.

SULPHATE-RESISTING PORTLAND CEMENT.—The Standard will be based upon B.S. No. 12. In the absence of any direct tests for sulphate resistance, this property will be controlled by specifying the composition of the cement.

A New Rotary Dry-process Kiln in Gt. Britain*.

THE new plant installed at the Plymstock works of the Associated Portland Cement Manufacturers Ltd., includes a rotary kiln using the Humboldt dry-process method for the first time in this country. The preparation of the raw meal and the Humboldt pre-heater were described in the previous issue of this journal.

The Kiln.

The kiln (*Fig. 10*) is a Vickers-Armstrong oil-fired rotary kiln of all-welded construction and is 178 ft. long and 12 ft. 6 in. diameter. The total weight of the kiln, including the refractory lining, is about 620 tons. The kiln, which is in a steel frame building (*Fig. 11*), lies at an inclination of 3 in 100, and rotates at a maximum speed of 1.4 r.p.m. It has a rated capacity of 600 tons of clinker per day. The operating temperature is about 2600 deg. F. The driving unit is adjacent to the feed-end of the kiln and comprises a 9-h.p. variable-speed motor, a triple-reduction spur gear-box, and a Twiflex flexible coupling. The lining of the kiln comprises refractory blocks, with steel face-plates in the burning zone; these special blocks




Fig. 10.—Kiln House, Plymstock Works.

*Continued from January 1962.




Fig. 11.—The Kiln during Installation.




Fig. 12.—Clinker Storage Silo.

were made by Canadian Refractories Ltd., of Montreal. The remainder of the lining was provided by General Refractories Ltd.

Heavy fuel-oil is delivered by road tankers which discharge into a small receiving tank. The oil is pumped by one of two Mirlees pumps to an insulated main storage tank which has a capacity of 600 tons. The receiving tank and the main storage tank are heated by steam coils to maintain the temperature of the oil at 120 deg. F. Oil is supplied by gravity from the main storage tank to the firing floor of the kiln, where it passes through a Duplex suction filter to one of two Mirlees constant-volume pumps, and thence to a Simplex oil-fuel steam-heater or to a stand-by electrical heater, where the temperature is raised to 230 deg. F. Oil is fed to the kiln through a 2½-in. pipe equipped with an atomising firing nozzle, which receives oil at 500 lb. per square inch and controls the quantity of oil burned. The surplus is returned to the oil-supply pipe. The oil pipes are contained in a 7-in. diameter jacket-pipe which has a 2-in. refractory lining and through which the primary air is passed. The primary air is supplied by a Keith Blackman fan capable of delivering 2100 cu. ft. of air at 22 to 23 in. water-gauge.

The burner and primary-air pipe is adjustable in position and is suspended from an overhead runway-beam so that rapid withdrawal from the kiln is possible.

Cooler.

The clinker is discharged from the kiln into a Fuller grate-cooler 41 ft. long by 7 ft. wide. A fan is provided for blowing cold air and another fan for the recirculating air for the second pass. The cooler is capable of cooling 700 tons of clinker per day down to a temperature of 150 deg. F. Clinker from the cooler is conveyed by a drag-chain conveyor to a catenary conveyor which has a vertical rise of 102 ft. at a maximum inclination of 63 deg. The clinker can be passed directly to a 1000-ton silo (*Fig. 12*) at the feed-end of the cement grinding mill, or it can be transported by belt-conveyors to the store.

Grinding.

Clinker is drawn from one of the two outlets from the storage silo by belt-feeders which discharge on to a band-conveyor on which the material is transported to the cement grinding mill (*Fig. 13*).

Gypsum is delivered to Plymouth by boat and conveyed by road to the gypsum store within the storage building, where it is loaded by the overhead crane into a mild steel hopper from which it is conveyed to a 100-ton bin over the grinding mill. Gypsum is supplied from the bin by means of a constant-speed belt-feeder, the quantity being regulated by a weir-gate.

The cement grinding mill, which was supplied by Messrs. Vickers-Armstrong (Engineers) Ltd., is 8 ft. 4½ in. diameter and 45 ft. 1½ in. long. The total operating weight is about 170 tons, which includes a total charge of 73 tons of grinding media. The drum has four sections. In the first, that is the section at the feed-end, there are 20½ tons of 3-in. to 3½-in. steel balls; in the second, 14½ tons of 1½ to 1¾-in. balls; in the third, 23 tons of ¾, 1 and 1¼-in. balls; and in the fourth section, that is at the driving and discharge end, there are 14½ tons of ½-in. by ½-in. and ⅝-in. by ⅝-in. Slugs.




Fig. 13.—Inlet End of Cement grinding Mill.

The mill rotates at 20.5 r.p.m. and is driven by a 1200-h.p. motor through a double-reduction gear. Cooling is by means of water sprayed on the rotating drum. When grinding ordinary Portland cement, the mill has an output of about 25 tons per hour. Dust-collecting units are connected to all transfer points of the conveyor system at the feed-end of the mill.

Storage.

From the outlet of the grinding mill the cement is carried by a short screw-conveyor, and thence by a central discharge elevator 76 ft. high, to an overhead belt-conveyor 284 ft. long, extending from the cement grinding-mill building to the top of a new 35-ft. diameter storage silo. The cement is discharged directly into this silo or, by a system of Air-slides, into one of the four older silos. Provision is made for dust extraction at all transfer points over the storage silos as elsewhere. Storage for the old works was in one silo of 3500-tons capacity and four silos each of 450-tons capacity. The new 2500-ton reinforced concrete silo increases the total storage capacity to about 7800 tons.

Packing.

Cement is transferred from the storage silos by Air-slides and screw-conveyors to a central discharge elevator, and then to a rotary screen over a surge hopper. A pneumatic feeder delivers the cement to a Fluxo twelve-spout packer, capable



Fig. 14.—Water Tower. (End of Kiln House on the right.)

of filling paper bags at the rate of 120 tons per hour. The filled bags are discharged on to a laminated conveyor, then by chute to a belt-conveyor, from which they are taken off by a plough to the lorry-loading bays.

The loading bay for bulk cement is incorporated in the packing plant. From the discharge of the elevator, an Air-slide delivers the cement to a Niagara screen which ensures that no lumps or extraneous matter remain in it. The cement is dropped into a steel hopper fitted with air-extraction equipment for delivery through pipe chutes into tanker lorries. This hopper is for ordinary Portland cement, and nearby there is a 30-ton hopper for rapid-hardening cement.

Instrumentation.

The instruments necessary for the operation of the raw-meal grinding plant and the kiln and preheater plant have been grouped on two panels in pressurised cabins near the raw-grinding mill and on the kiln firing-floor respectively.

Other Buildings.

A new single-storey building constructed with precast concrete frames spanning 50 ft. is provided for offices, main store, fitting and blacksmith's shops, and welding shop. The building, which is seen to the left of the kiln house in *Fig. 14*, is 182 ft. long and 22 ft. high to the eaves. The store building for lubricants and grease is at

one end of the main store building. There is also a subsidiary store building close to the packing plant in which supplies of cement products not manufactured at the Plymstock works are stored; this building is 106 ft. long and 50 ft. wide.

Acknowledgements.

The principle civil engineering contractors are Messrs. Richard Costain Ltd.; included in their work are a concrete access road, the workshop and stores building, a sub-station, four 28-ft. diameter raw-meal silos, the 35-ft. diameter cement silo 85 ft. high, the kiln house and cooler pit, the clinker silo, the clinker grinding-mill building, and the packing and loading building. This firm also designed and constructed the Humboldt building which is a ten-storey reinforced concrete structure 168 ft. high.

The reinforced concrete water-tower (*Fig. 14*) and some ancillary structures were constructed by Messrs. James Miller & Partners Ltd. The water-pipe and air equipment were supplied and installed by Messrs. Barrett & Wright Ltd. Some of the ancillary buildings are constructed of precast concrete frames supplied by Messrs. Hewlitt of Cranleigh and Wrexham.

Messrs. Constantin (Engineers) Ltd., supplied the Fuller grate cooler, the F. H. Air-slide conveyors and the raw-meal blending plant.

The new Plymstock works were designed by the owners, the Associated Portland Cement Manufacturers Ltd. This firm also erected the main mechanical plant. The Company work closely with the Town and Country Planning authorities and a landscaping scheme is in progress.

The Determination of the Loss on Ignition.

WHEN a cement has been burned under reducing conditions or if it contains slag, the loss on ignition may include the effects of the oxidation of sulphides, carbides or carbon. If heating is carried out in a stream of argon, the carbon dioxide and water vapour may still bring about some degree of oxidation, and alkali or sulphur may be lost at higher temperatures. A procedure designed to minimise these errors was described by Mr. K. BLEHER in a recent number of "Zement-Kalk-Gips."

The sample of cement is placed in a platinum boat in a quartz tube, with a thermo-couple beside the boat. Argon is introduced at one end of the tube and, after passing through the tube, it is led through a U-tube containing silica-gel or magnesium perchlorate. A bubble-counter is included in the absorption tube. The quartz tube is heated by an electric wire connected to a rheostat. The tube should be heated up to about 200 deg. C. within ten minutes, and then quickly up to 800 to 830 deg. C. and held at this temperature for fifteen minutes. The rate of flow of the argon should be 6 ml. per minute. These indications apply to a charge of about 350 mg. in a platinum boat 30 mm. long, 3 mm. high and 4 mm. wide. Metallic iron should first be removed by means of a magnet.

Cement Industry in America. North America.

U.S.A.—A new cement works is being erected in Houston, Texas, for the McDonough Co. Production may begin during the latter part of 1962. The works will employ about one hundred men. The annual productive capacity will be 250,000 tons. The Fuller Co. are supplying the principal equipment including a 450-ft. rotary kiln of 12-ft. diameter, a 2,000-h.p. clinker grinding mill, a 1,500-h.p. raw-material grinding mill, the conveyors and the dust collectors.

Construction is in hand for doubling the capacity of the works of the Arkansas Cement Corporation at Foreman, Arkansas, to 466,000 tons per annum. A kiln 450 ft. long and 12 ft. in diameter and a ball mill are to be supplied by Messrs. F. L. Smidth & Co.

The Huron Portland Cement Division intends to double the capacity of the cement works at Alpena, Michigan, during the next fourteen years. The installation of a new rotary kiln which will increase the annual capacity of these works from 2,000,000 to 2,350,000 tons is nearing completion. The kiln is 460 ft. long and 15 ft. in diameter. An ocean-going oil tanker, the "Huron," is to be converted into a cement and coal carrier. Having a capacity of 9,150 tons, this vessel will be the largest cement carrier on the Great Lakes.

Two wet-process rotary kilns with the largest capacity in the United States are to be supplied to the newly formed Atlantic Cement Co. Each of the kilns will be 580 ft. long and 20 ft. in diameter and will be capable of producing 833,000 tons of cement a year. Other equipment for this new plant includes a gyratory crusher for primary crushing, three 13-ft. by 36-ft. two-compartment ball-mills for grinding dry cement, two 13-ft. by 40-ft. ball-mills, each with two compartments, for wet grinding the raw materials. Production is expected to start in 1963. Facilities will be provided on the Hudson River capable of accommodating ocean-going vessels. The site of 2,000 acres is reported to have a reserve of limestone capable of supplying the requirements of the works for more than one hundred years.

The Louisville Cement Co. is establishing a cement works near Logansport, Indiana. The site of the works and the limestone deposits occupy 700 acres. A 12-ft. rotary kiln 425 ft. long will probably be installed and will have an initial annual capacity of 165,000 tons. Production will commence probably early in 1963. The Company also operates a works at Speed, Inc., with an annual capacity of 750,000 tons.

The expansion of the Lehigh Portland Cement Company's works at Mitchell, Indiana, was completed by the end of 1961. Work commenced in 1959 with the installation of two new kilns which began operation in January 1960. Storage, raw-material plant, transport facilities, a mill building and thirty concrete silos for storage of cement, were then installed.

The Oklahoma Cement Corporation, Pryor, Oklahoma, expects to double the capacity of its works, the cost of the project being about \$5,000,000. It is intended to double the grinding capacity by the addition of a new raw mill,



Location of Cement Works in U.S.A. (Western States).

convert the existing mill to a finishing mill as well as a raw mill, install a second kiln 11-ft. diameter and 375 ft. long, and construct a 1,330-ton concrete kiln feed tank. Storage capacity for cement is to be increased to about 50,000 tons. (The foregoing reports are from "Pit & Quarry.")

The Phoenix Cement Co., of Clarkdale, Arizona, are to complete their installation with an additional rotary kiln, which will increase the annual capacity by 133,000 tons to 430,000 tons.

In the U.S.A. there are currently about 172 Portland cement works either in production or in the course of construction. Of these, 102 are wet-process plants and 69 are dry-process plants. One works manufactures cement by both processes. There is additionally one plant where grinding only is done. The locations of these works are shown on the maps on this page and page 31, which are based on a more comprehensive map issued by Pit & Quarry Publications. The key to the map is as follows. Solid circle: Manufacturing works in production.

(Continued on page 32)

In goes yet another

ROTARY KILN LINING



Illustration shows details of Jack assembly

—by

STEETLEY

who are themselves rotary kiln operators and have a unique experience in design, manufacture and practical use of bricks to suit all conditions. For ordinary Portland Cement practice the choice is either Magnesite/Chrome or Serpex 'S' bricks, both developed after much research and practical experience of rotary kiln lining problems. For white cements which must be burned at high temperatures on chrome-free brickwork, Steetley provide a spinel bonded magnesite brick designed to withstand the most arduous conditions prevailing.

*Send for special brochure—
"Rotary Cement Kiln
Refractory Linings"*

THE STEETLEY REFRACTORY BRICK CO. LTD.

WORKS AT—

NORMANBY
near MIDDLESBROUGH


OUGHTIBRIDGE
near SHEFFIELD

STEETLEY
near WORKSOP

BRASSINGTON
DERBYSHIRE

All enquiries to The Steetley Refractory Brick Co. Ltd., Oughtibridge nr Sheffield. Tel: Oughtibridge 2311

HUMBOLDT



design build and extend
Cement Works
using the
**HUMBOLDT
PREHEATER**

91 This system is job-proved by plants operating throughout the world.

Ask for expert advice and literature

KLÖCKNER-HUMBOLDT-DEUTZ AG·KÖLN

Phone: 6711
Telex: 08873410

WERK HUMBOLDT



NOTES.—1. Works at Thomaston (Maine) not shown.
 2. The twelve works in Pennsylvania not named are as follows: Bath, Bethlehem, Cementon, Coplay, Egypt, Evansville, Fogelsville, Martins Creek, Nazareth, Northampton, Sandt's-Eddy and Stockertown.

Location of Cement Works in U.S.A. (Eastern States).

Open circle: Works in the course of construction. Cross: Grinding plant only. Triangle: Distribution centres. The states of Hawaii (where there are one dry-process and one wet-process works) and Alaska (where there are no cement works) are omitted from this survey.

Canada.—The annual productive capacity at the end of 1960 was 8,750,000 tons. The excess capacity was 3,052,141 tons, that is 53·6 per cent. of the 1960 production. The industry operated at 68 per cent. of its actual capacity and production was 5,697,859 tons, which is the lowest since 1956, and 9 per cent. below that of 1959. The year 1960 was the first since 1947 in which the cement industry had not achieved record production. Exports, most of which were to the U.S.A., increased by 3 per cent. of the value of the cement produced. About one-third of the production is used in the precast concrete and ready-mixed concrete industries. (This report is from "Pit & Quarry".)

There are currently in production in Canada eighteen Portland cement works of which fifteen are wet-process plants and three are dry-process plants. Additionally there are two plants which grind only.

Mexico.—Cement production in 1960 reached a record of about 3,000,000 tons. Imports amounted to less than 5,000 tons. The existing works of Cementos Atoyac, S.A., will be demolished when the new works now under construction has been completed. Capacity of the new works will be more than 300 tons per day, it is reported in "Pit & Quarry."

There are currently in Mexico twenty-four Portland cement works, either in production or in the course of construction. At least twenty of these works are dry-process plants.

West Indies and Central America.

Bahamas.—It is reported that the Government has passed a bill which will enable Portland cement to be produced on a large scale in the Freeport area. The Bahamas Cement Co. will invest up to 50,000 dollars in the project and will be granted a monopoly for a period of twelve years. The estimated cost of the plant and equipment is 30,000,000 dollars.

The Caribbean Cement Corporation intends to install a third kiln at their Rockfort works at a cost of £2,500,000. The plan has yet to be approved by the Government.

Dominican Republic.—A new cement works having a capacity of from 250 to 500 tons daily is to be established alongside the harbour at Barahona where there are large supplies of raw materials.

Puerto Rico.—There are currently two Portland cement works in Puerto Rico, both of which are wet-process plants.

Jamaica.—The Caribbean Cement Co., Ltd., is undertaking an expansion programme which is estimated to cost £3 000 000 and will double the output.

Barbados.—A new company, the West Indian Cement Ltd., has been formed to manufacture cement on the island.



FIRST KILN SECTION DELIVERED for giant new Blue Circle plant at Westbury

Vickers-Armstrongs are supplying the complete kiln installation and three grinding mills for the Blue Circle Group's new Westbury Cement works.

A GIANT TAKES SHAPE

This first section of the massive new kiln was delivered during January 1962. Built at Vickers-Armstrongs Barrow works, it is 14 ft. 6 in. in diameter by 38 ft. in length. When complete, the cement kiln at Westbury will measure 450 ft. in length! The plant's capacity will be 800 tons daily.

Vickers are fully equipped for the design and manufacture of complete cement plants as well as individual kilns, mills and ancillary equipment. For your special needs, call in

VICKERS



When temperatures run high . . .

"It's the Devil's own job finding a brick that won't crack up over 1600° Centigrade—and resist, really resist, slag attack."

"Quite a proposition."

"It's a necessity—also this brick has to be suitable for a multitude of applications."

"—the glass producers and high temperature kiln people, you mean—"

"Indeed yes, and we in the Steel Industry need these bricks for burner blocks, soaking pits, and reheating furnaces—everywhere where the operating conditions are really severe."

"So it must have low spalling tendency and very high mechanical strength. It's a super duty brick you need. And I'd suggest the Consett High Grade Alumina brick—it meets all the requirements we've mentioned."

"Didn't know you were a refractories expert."

"I'm not. The experts are at Consett Iron Company. They've got a whole range of refractories. Consett 341—that's their number."

"Thanks. I'll ring them at once."



CONSETT IRON CO. LTD.

CONSETT · COUNTY DURHAM

Telephone: Consett 341 (12 lines) Telegrams: Steel Phone Consett


London Office: NORFOLK HOUSE, 7, LAURENCE POUNTNEY HILL, E.C.4.

Telephone: Mansion House 7975




Patent Applications for Making Cement.

Low alkali content cement is produced by first drying the raw material in alkali free gases from a rotary kiln 1 and/or external gases such as hot air in a chamber 5, then heating the dried material in chamber 6 with the alkali containing waste gases from the kiln and finally calcining the material in the rotary kiln. The granular raw material from hopper 3 is fed in a thin layer by a conveyer grate 2 through the chamber 5 which is supplied with hot air from a cooler 8, then through chamber 6 which is supplied with hot gases from the kiln 1. Calcining is



effected in the rotary kiln 1 and the calcined clinker is cooled on an endless belt 8 which is divided into two chambers by a movable flap 9, and supplied with cold air via pipe 12. The waste gases from chamber 6 are electrically filtered to remove alkali and dust and may be circulated to the drying chamber and/or grinding apparatus. Alkali dust is separated from the preheated granules by a sieve mounted at the discharge end of the grate 2 and the preheated chamber 6 may contain stationary or movable rakes. The separated dust is collected in a collecting chamber below the grate 2.—No. 874,818. Polysius G.m.b.H.

Cement raw material, lime, ore or similar raw materials are calcined, burned or sintered during movement on or over a gas-permeable support while gases effecting the calcination etc., pass through the material and the support, all the raw material forming a layer in contact with the support being covered by one or more layers consisting of return material, with or without fuel. In Fig. 1 cold nodules of raw material of about 10 to 20 mm. in size and 15% water content are fed on to a traveling grate 2 from a hopper 9 and are immediately covered by a mixture of fuel 12 and return material 13 from a hopper 14. The fuel is ignited by a burner 16 in an ignition zone 15 and the bed passes under a casing 17 while a fan (not shown)



draws hot air therefrom through bed and grate and away by a pipe 22, causing the combustion to penetrate further into the layer as the bed moves. Cold air is drawn from the atmosphere down through the bed into compartment 21, thereby cooling the bed and passing as hot air into the casing 17 by a pipe 18. At the discharge end of the grate a blade 23 divides the bed into layers 25*a* and 25*b*, the division coinciding with or lying above the original division of the bed. A transverse conveyer 26 carries the upper layer away as finished product while layer 25*a* is passed as return layer by hopper 27, conveyer 28 and elevator 29 and finally into hopper 14. In the ignition zone 15 temperatures of the upper surface of the bed, boundary between the layers, and surfaces in contact with the grate are about 1400°C., 500°C. and 30°C. the temperature of the boundary becoming about 1400°C. where the casing 17 ends. In the cooling zone heat is carried further into the lower layer by the downwardly passing, cold atmospheric air, so that the upper surface of the bed close to the drum 4 is at a very low temperature whereas the grate may be at the maximum permissible temperature of 700°C. If the point of division of the bed by blade 23 lies above that of the original layers, so that part of the final product is used as return material, the blade may be displaced toward the feed end of the grate, thus allowing shortening of the latter. Two blades instead of one may be used to provide two return layers if desired. *Fig. 1* may be modified by preheating the fresh layer before it becomes covered by return material. In another form of apparatus intended for use with irregularly shaped raw material unmixed with fuel, conveyer shoes are connected through slots in a stationary grate to a horizontal beam which is continually reciprocated so that the shoes carry material with them on the forward stroke but slide beneath it during the return stroke. Fuel is burnt above the grate in two flames which may have joint or separate sources of air for their combustion.—No. 860,791. A.S., F. L. Smidth & Co.

Cement Production in the United Kingdom in 1961.

ACCORDING to statistics issued by the Ministry of Works, cement production in 1961 in the United Kingdom was 14,000,000 tons compared with 13,000,000 tons in 1960, an increase of 7 per cent. Deliveries in 1961 were 13,500,000 tons, an increase of 10 per cent. compared with 1960. In the first ten months of 1961, almost 196,000 tons of cement were imported, nearly double the amount imported in the corresponding period of 1960, and exports in the same period fell from 859,000 to 615,000 tons, a decrease of 28 per cent.


Dust in Factories.

IN amendment (No. 2, issued September 1961) to the Booklet No. 8 of the Safety, Health and Welfare New Series, "Toxic Substances in Factory Atmospheres," the maximum permitted content of Portland cement dust is given as 50 (millions of particles per cubic foot of air based on impinger samples counted by light-field methods) or 1766 particles per c.c. of air. This quantity is several times greater than the permitted amount of other silicate dusts.

New Approach to Hot Zone Linings

**FIRED DOLOMITE BRICK
LININGS PROVED SUCCESSFUL**

GR '341' FIRED DOLOMITE BRICKS



BASIC FACTS ON A BASIC BRICK

Full scale trials in the hot zones of Portland Cement Kilns have proved the success of GR '341' Dolomite bricks. Equivalent life to magnesia based bricks has been established. These bricks quickly develop and retain a protective clinker coating. Lower thermal conductivity values give a reduction in shell temperatures, and as a result the heat losses of linings made from these new bricks are much lower than with magnesite. Greater thermal efficiency, promoted by lower conductivity, makes GR '341' a more economical proposition.

HOT FACE: 1500 C

Lining Thickness	C COOL FACE (THEORETICAL)			
	GR '341'		MAGNESITE	
	Uncoated	Coated	Uncoated	Coated
6"	365	265	395	295
7"	355	255	380	280
9"	330	230	375	275



THE
GENEFAX GROUP
for everything
in refractories.

Consult

GENERAL REFRACTORIES LTD.

GENEFAX HOUSE · SHEFFIELD 10 · TEL: SHEFFIELD 31113

We shall be pleased to provide specialist advice and supervision of the installation of linings if required.

EDGAR ALLEN LIME BURNING PLANT

This is a 180 ft. rotary kiln producing 7 tons of burnt lime per hour, in Israel. The burnt lime is used in cement manufacture and Edgar Allen & Co. Ltd. can also manufacture cement plants as complete "turnkey" jobs. The burnt lime can be hydrated for mortar or, on the other hand, used as a fertilizer. The Engineering Dept. of Edgar Allen also manufacture crushing and grinding machinery and ball mills to suit all applications.



EDGAR ALLEN & CO. LIMITED

IMPERIAL STEEL WORKS · SHEFFIELD 9

To EDGAR ALLEN & CO. LTD., SHEFFIELD 9 ENG 36/CLM
Please post data on 'Rotary Kilns' to:—

NAME

POSITION

FIRM

ADDRESS