

# CEMENT AND LIME MANUFACTURE

VOL. XXXV No. 5

SEPTEMBER, 1962

Price 1s. 6d. Annual subscription 9s.  
(\$1.75 in Canada and U.S.A.).

FULLER

*Airmerge*

SYSTEM

*Blending and storage  
silos at the new  
Plymstock works for  
A.P.C.M. Limited.*

## *The successful blending system for dry process plants*

Perfect blending of the raw material supply to the preheater in a dry process cement plant is absolutely essential—and the Fuller Airmerge system ensures this homogeneous supply. The quadrant blending method using Fuller equipment not only produces an accurately blended mix, even with materials of different bulk density and fineness, but does so at a high rate of output at a very low power cost. When a continuously reliable supply of carefully blended materials helps towards an optimum output of cement from the plant, then Fuller Airmerge equipment is essential—and our engineers and laboratories are at your disposal to design the most effective system for your plant.

**CONSTANTIN (ENGINEERS) LTD.**  
123 Victoria St., London, S.W.1  
Tel.: Tate Gallery 0637

*Sole Licenses of Fuller Co., Catasauqua, Pa.,  
U.S.A., for the manufacture and sale of Fuller  
equipment in U.K.*

**CONSTANTIN**

# STEIN

## *Refractories*

### For Rotary Cement Kilns



**STEIN MAG C**  
*The Basic Lining for  
Rotary Cement Kilns*

*Photograph by courtesy of the  
Billingham Division of ICI.*

#### **STEIN MAG C offers**

- \* High resistance to clinker attack.
- \* Forms clinker coating quickly.
- \* High retention of coating during kiln shut-downs.
- \* Excellent for oil firing.

From our range of High Alumina bricks and Firebricks we can also supply the correct type of Refractory to suit all zones in Rotary Cement Kilns.



*Our long-standing experience with Cement Kiln Refractories is available to all users on request.*

**JOHN G. STEIN & CO. LTD.** Bonnybridge, Scotland. Tel: Banknock 255 (4 lines) 361 & 362

**GRINDING  
MEDIA  
INFORMATION**

**No. 1**

**"CRETOIDS"**  
(Reg. No. 573298)

have been specially produced by us to meet the requirements of manufacturers for producing cement of extreme fineness. They have proved highly successful in finishing-mills without any cooling devices and, as with all our other types of grinding media, the wear-and-tear cost of "Cretoids" is infinitesimal. Free working samples are available on application.

**USED AND RECOMMENDED BY**

**THE WORLD'S LEADING CEMENT MAKERS**

The comprehensive range of grinding media supplied by us and our unique experience in the cement industry in practically every country of the world enable us to give expert advice and to supply a type of grinding media that will provide the answer to any grinding problem.


**HELIPERS LTD** PHONE: GLOUCESTER 51402  
GRAMS: HOLPERS, GLOUCESTER  
**PREMIER WORKS**  
**GLOUCESTER**

# ERECTION

OVERHAUL

CONTRACTORS  
TO THE  
CEMENT  
INDUSTRY

MAINTAIN



ROTARY KILNS.  
MILLS & CRUSHERS.  
COMPLETE PLANTS.  
ELECTRICAL PLANT.  
TRANSPORT EQUIPMENT.

# CONTACT

**INSTALLATION &  
MANUFACTURING CONTRACTORS  
LTD**

27 CHURCH ST.,  
WEST HARTLEPOOL.  
HARTLEPOOL 5308.

HIGH ST.,  
WARE, HERTS.  
WARE 3302.

**POLYSIUS**

WE INSTALL  
CEMENT WORKS  
ALL OVER  
THE WORLD

**POLYSIUS Ltd. / ASCOT, BERKS.**

TEL: WINKFIELD ROW 395-6-7  
TELEX 84102

The advertisement features a stylized world map background with a wavy, textured pattern. A central photograph, framed in a dark, rounded rectangle, shows an industrial cement plant with large cylindrical silos and various structures. The Polysius logo is positioned in the upper right quadrant, and a circular callout box is located in the lower center. At the bottom, a dark horizontal band contains the company name, and a separate box provides contact information.

For  
higher  
outputs  
with  
only one  
operator  
The Haver  
ROTARY  
Packer with or  
without pre-  
compacting for  
cement, lime,  
slag, plaster,  
etc., etc.

THE  
**HAVER ROTO PACKER**


Developed to meet  
arduous present day requirements.

Offers peak outputs of up to 110 TPH with eight  
spouts and one operator or 75-90 TPH with six spouts.

*U.K. Representatives:-*

**CONTINENTAL ENGINEERING CO. LTD., London Road, Ascot, Berks.**

*Tel. No: Winkfield Row 395*



**ECONOMICAL  
CONTRIBUTIONS  
TO EFFICIENCY IN  
CEMENT MAKING**

*grinding  
media*

**NI-HARD  
AND  
WHITE  
IRON**  
for exceptional  
wearing qualities

More and more cement manufacturers are realising that "NI-HARD" has wearing qualities from two to five times greater than those of steel, depending on the material being ground, and is a quality material that saves money and time.

*mill  
linings*

"NI-HARD", which is made with the aid of modern mechanical plant, is the ideal material for the production of grinding media and mill linings for cement manufacture. We shall be pleased to make castings to your own specification and produce patterns to your designs. Please ask for our illustrated leaflet giving proof of the many uses of "Ni-Hard and White Iron". We also manufacture wear-resisting castings for many applications in gas works, shot-blasting, coke crushing, mining machinery, etc.

***Wye Foundry***  
COMPANY · LIMITED

**WILLENHALL, STAFFS.** Telephone: Willenhall 65541/2 (2 lines)



**ALL  
HAND FORGED**

**BALLS FOR BALL AND TUBE MILLS**

**STEEL  
GRINDING BALLS**  
In High Carbon and Chrome Steel  
1" - 6" Diameter

**DESIGNED TO  
GRIND FASTER,  
LAST LONGER,  
NEVER BREAK,  
NEVER LOSE SHAPE**

*Also makers of fine hand-forged tools  
for QUARRY and MINE*

**F. J. BRINDLEY & SONS (SHEFFIELD) LTD.**  
CENTRAL HAMMER WORKS, SHEFFIELD, 1.  
*Phone and Grams: Sheffield 24201/2*

A "CONCRETE SERIES" BOOK

**CEMENT CHEMISTS' AND WORKS MANAGERS'  
HANDBOOK**

By W. WATSON, B.Sc., and Q. L. CRADDOCK, M.Sc.

**SECOND EDITION REVISED  
1962**

The revisions include

**Cement Specifications of World**  
brought up to date to 1961.

**Latest British and American methods of testing**

All the data required for the manufacture, chemistry and testing of cement, which were given in the preceding edition, are retained and include

Weights and volumes of slurry. Standard sieves (British and foreign).  
Capacities of tanks and kilns. Kiln data. Fan horse-power.  
Volumes, weights and densities of gases. Raw mixtures. Heat balance, etc.


234 pages. Numerous Tables.

Price 25s.; by post 26s. 3d. 5.50 dollars in Canada and U.S.A.

**CONCRETE PUBLICATIONS LTD.**  
14 DARTMOUTH STREET, LONDON, S.W.1



*These figures mean*  
**SUSTAINED HIGH-EFFICIENCY  
 DUST PRECIPITATION**



CARRIBEAN CEMENT CO. JAMAICA .....	0.088 grains/ft <sup>3</sup> *
AUSTRALIAN CEMENT LTD. GEELONG.....	0.006 grains/ft <sup>3</sup>
A.P.C.M. LTD. BEVANS WORKS .....	0.001 grains/ft <sup>3</sup>

\* (Stack emissions measured during official acceptance tests)

Over 70 electro-precipitator units have been individually designed  
 and built by Lodge-Cottrell for the cement industry throughout  
 the world, thus preventing air pollution from cement kilns.

The experience we have gained is at your disposal.

**LODGE-COTTRELL LTD**

George Street Parade, Birmingham 3,  
 and at London, Brussels, Calcutta, Johannesburg, Sydney, Toronto.

MEMBER COMPANY



SIMON ENGINEERING LTD



# ROTARY DISC FEEDER

*British Patent No. 769603*

for controlled, infinitely-variable volumetric measurements to close limits of many kinds of crushed and ground materials such as cement raw material, limestone, gypsum, coal, etc.

- Operates safely.
- Handles very moist materials
- Offers immediate response to automatic regulation
- Is airtight and therefore suitable for use in grinding installations operating under vacuum or pressure conditions.

**DELO (ENGINEERS) LTD.**  
138 Borough High Street  
LONDON, S.E.1. Tel: Hop 0085/6

Also Drying Furnaces, Disc Granulators, Short and Medium Distance Pneumatic Conveyors

*Plants for making:*

**ASBESTOS CEMENT PIPES & SHEETS**

**WHITE CEMENT**

**SLAG CEMENT**

**PRESTRESSED CONCRETE**

**RAILWAY SLEEPERS**

**ASBESTOS CEMENT ENGINEERING CO.**


P.O. BOX 34.649 Hauptstrasse 26, VADUZ, LIECHTENSTEIN, SWITZERLAND

# LOW COST CRUSHING BY

# IMPACT




High tonnage throughput with reduction ratios as high as 100 : 1 with some materials is possible with the Joy-Hazemag Impact Crusher. Choose from a range of 20 sizes—from 3 to 500 tons per hour capacity. Small, compact Joy-Hazemag Crushers offer low capital and operating costs—give efficient and economical crushing for a wide range of materials. Write for booklet giving full details and specification.



The Joy-Hazemag breaks material by impingement—uses less power and less space than conventional crushers. The principle? Material enters crusher against chain curtain, controlling feed rate—is flung violently against impact plates in crusher by fast-rotating blow bars mounted on rotor. Result? Material hitting impact plates—and itself—breaks up along natural lines of cleavage or weakness. Gives uniform, well cubed product of great strength. Selectivity reduces mixed materials—separates coal/ores from stone, metal from slag, etc.

## JOY-HAZEMAG *Impact* CRUSHERS

JOY-SULLIVAN LIMITED · GALLYWHITE LANE · DRONFIELD · NR. SHEFFIELD



## Our basic Special Magnesite ANKRAL Bricks

Due to their extremely high refractoriness our basic Special Magnesite ANKRAL bricks bring about considerable advantages in

### HIGH-CAPACITY LIME SHAFT KILNS

ANKRAL-lined shaft kilns operate very economically for the following reasons :

- Forced operation is possible.
- No incrustations, hence regular kiln operation without standstills.
- Lower number of intermediate repairs and greater total lining life.
- Increased throughput.
- Improved quality of the production.
- Simpler kiln maintenance.

Our technical service comprises all phases from the preparation of a complete lining proposal to detailed engineering advice for construction, starting-up and operational running.

General Sales Office

Refractory Products Limited  
Basle 2, St. Albanvorstadt 94  
Switzerland

Representative for the U.K.


**JOHN LE BOUTILLIER LTD.**  
3, REGENT STREET, LONDON, S.W.1  
Telephone: TRA 5005



# VEITSCHER MAGNESITWERKE

A CTIEN - GESELLSCHAFT, VIENNA - AUSTRIA

**complete  
electrification schemes  
for the  
CEMENT INDUSTRY**




**POWER GENERATION  
SWITCHGEAR  
TRANSFORMERS  
FUSEGEAR  
CONTROL GEAR  
MOTORS  
CABLES AND WIRING**

**FROM PLANNING TO COMMISSIONING UNDER A SINGLE CONTRACT**

**'ENGLISH ELECTRIC'**

**ELECTRICAL PLANT DIVISION · STAFFORD**



*Designers of complete  
Cement Works and  
manufacturers of  
machinery for the  
cement industry*

**F. L. SMIDTH & CO. LTD.**

105 PICCADILLY - LONDON W.1 - Telephone: Grosvenor 4100 - Telegrams and Cables: Folasmidth London

# CEMENT AND LIME MANUFACTURE

PUBLISHED ALTERNATE MONTHS.

PRICE 1s. 6d. A COPY

ANNUAL SUBSCRIPTION 9s. POST FREE  
\$1.75 IN CANADA AND U.S.A

PUBLISHED BY  
CONCRETE PUBLICATIONS LIMITED  
14 DARTMOUTH STREET, LONDON, S.W.1

TELEPHONE: WHITEHALL 4581.  
TELEGRAPHIC ADDRESS:  
CONCRETIUS, PARL, LONDON.

PUBLISHERS OF  
"CONCRETE & CONSTRUCTIONAL ENGINEERING"  
"CONCRETE BUILDING & CONCRETE PRODUCTS"  
"CEMENT & LIME MANUFACTURE"  
"THE CONCRETE YEAR BOOK"  
"CONCRETE SERIES" BOOKS.

VOLUME XXXV, NUMBER 5.

SEPTEMBER, 1962

## A New Cement Works in Saudi Arabia.

THE new cement works for the Saudi Cement Co., in the Province of El Hasa, Saudi Arabia, commenced operating early this year (as reported in this journal for May last). The works, general views of which are shown in *Figs. 1* and *2*, has a capacity of 300 tons per day. A plan of the works is shown in *Fig. 3*. There is one dry-process rotary kiln, fired by natural gas, and provision is made for installing another. The works, which is situated on a level site 430 ft. above sea level is about 80 miles west of the port of Dammam on the Persian Gulf. It is connected to Dammam by the 4-ft. 8½-in. gauge Saudi Government Railway and a main road.

The locality is such that day temperatures in the summer range from 100 to




Fig. 1.—General View of Works (Looking West).




Fig. 2.—General View of Works (Looking East).




Fig. 3.

125 deg. F., falling by about 40 deg. F. at night. The highest humidity is in July and August. Winds are moderate, but sand-storms occur generally in April and May. Rainfall, which averages 3 in. a year, occurs in the winter. Water is obtained from a bore-hole 110 m. (360 ft.) deep and is supplied to a water tower of 33,000 gallons capacity by a submerged pump. The tank of the tower comprises two compartments, one for drinking water for the works and houses of the staff, and the other for the circulating system in the works.

Electricity is generated at the works in a power station having a capacity of 600 k.v.a. at 0.8 power-factor and contains four pressure-charged 9-cylinder four-stroke 1750-b.h.p. sets running at 300 r.p.m. and using white diesel oil. Current is generated at 6000 volts 3-phase 50 cycles. The mill motors operate on 6000 volts, other motors on 380 volts, and lighting and other single-phase circuits on 220 volts. Two small generating sets, which were used during construction are retained as auxiliaries. The cooling water and lubricating oil are cooled in air-blast coolers.






Fig. 4.—The Kiln.

#### Raw Materials.

**LIMESTONE.**—The part of the quarry being worked at present is 600 metres (660 yards) from the works, which is built on a limestone deposit. The limestone is of medium hardness and of constant quality having about 88 per cent. of  $\text{CaCO}_3$ . It is drilled by wagon drills, blasted, and loaded by a  $2\frac{1}{2}$ -cu. yd. 54-R.B. diesel-operated shovel into 9-cu. yd. Mercedes dumpers in which it is transported to the crushing plant at the works. It is discharged into a hopper and is fed by a 1.2 m. (42-in.) apron-feeder to a primary jaw-crusher which reduces the pieces of stone to 150 mm. (6 in.). To obtain optimum loading, the speed of operation of the feeder, which is variable, is linked to the power taken by the crusher. The crushed stone is carried by a belt-conveyor and fed to a secondary Symons No. 4 cone crusher which reduces it to a size at which 95 per cent. passes through a 32-mm. ( $1\frac{1}{4}$ -in.) screen. It is then conveyed either to the store or direct to the mill bunkers.

The store structure, which is seen in *Figs. 1* and *2* and is shown on the plan in *Fig. 3*, contains an overhead crane of 25-m. (82 ft. 6 in.) span and provided with a  $2\frac{1}{2}$ -cu. yd. grab, which serves the stocks of raw material, clinker and gypsum and the respective mill bunkers which are within the store structure.

**CLAY.**—The clay deposit is located 14 km. (about 9 miles) from the works and is on the railway. There is an overburden of lime-marl 6 m. (20 ft.) thick which is drilled, blasted, and loaded by a 22-R.B. diesel-operated shovel into 9-cu. yd. dumpers for removal to a tip. The clay bed is 10 m. (33 ft.) thick. The clay is hard and compact and contains 28 to 30 per cent. of moisture. It is dug by another 22-R.B. diesel-operated shovel and also loaded into 9-cu. yd. dumpers. The pieces are up to 250 mm. (10 in.) in size but occasional pieces are as large as 500 mm. (20 in.) cube.

The dumpers run on to a loading ramp at the railway and discharge into

50-ton tipping railway wagons, which have compressed-air mechanism for tipping to either side; they were originally used on harbour construction. On arrival at the works, the clay is tipped into a grab-hopper which is situated at the east end of the main store structure. The hopper is served by the grab-crane in the store, by which the clay is transferred to the store or direct to the hopper of the clay crusher. A roll crusher reduces the clay to 25 mm. (1 in.) and it then passes through a "Rapid" drier; this equipment consists of a chamber with rapidly rotating impellers at the bottom, which repeatedly throw the material into a stream of hot gas in the chamber until the moisture is reduced to 6 to 8 per cent. Heat is provided by natural gas. The dried clay is then transferred by a belt-conveyor and elevators to the store. The system is provided with multi-cyclone dust collectors.

IRON OXIDE.—Iron ore of 90 per cent. purity is brought by road from a local source. It is crushed in the limestone crushing plant and delivered to the store or mill bunker.

#### Grinding and Blending of Raw Material.

The raw materials, which have a moisture content up to 8 per cent., are ground in a Polysius double-rotator mill and classifier to a fineness giving a residue of not more than 8 per cent. on a 170-mesh screen. The mill is 2.8 m. (9 ft. 2 in.) in diameter and is 8.5 m. (28 ft.) long, and is driven through girth gears and a reduction gearbox by a 630-kw. 6000-volt motor. The output is 28 tons per hour. Heat for drying in the mill and classifier is obtained either from a gas-fired furnace or the flue gas from the kiln. The purge from the system is cleaned in a fabric bag filter.

The raw meal is conveyed by screw-conveyors and elevators to the blending




Fig. 5.—Feed-end House and Chimney.

silos, which are six 440-ton concrete silos 6.1 m. (20 ft.) in diameter and 14 m. (46 ft.) high. The silos, which are seen to the left-centre in *Fig. 1*, are equipped with the Polysius pneumatic system for mixing, and with screw-conveyors and elevators for re-circulation. The blended meal is stored in another silo (*Fig. 5*) which is 9.5 m. (31 ft.) in diameter and 14 m. (46 ft.) high, and from this it is extracted by a drag-link conveyor and elevated to the kiln-feed hopper. The feed is extracted from the hopper by a variable speed Redler conveyor and delivered into a double paddle mixer, where water is added as necessary to dampen the meal before discharge into the kiln.

### **Burning.**

The Polysius rotary kiln (*Fig. 4*) is 3.2 m. (10 ft. 6 in.) in diameter and 90 m. (295 ft.) long, and is supported on five bearings with thrust rollers at the central bed and the adjacent bed. It is operated by a 90-kw. slip-ring motor, with rotor-assistance speed control, through a reduction box equipped with barring gear driven by a petrol engine for emergency use. The flue gas is cleaned in a multiple-cyclone dust collector and discharged by an induced draught fan to a steel chimney (*Fig. 5*).

The kiln is fired with natural gas having a calorific value of 1550 B.t.u. per cu. ft. gross (1425 B.t.u. per cu. ft. net). The gas, which is preheated, is discharged through a dual-purpose burner which can also operate with white diesel oil in an emergency. The gas for the kiln and for drying the raw material is supplied, through the 200 mm. (8-in.) pipeline seen in the foreground of *Fig. 2*, from the Arabian Oil Co.'s (ARAMCO) gas-oil separation plant at Shedgum 11 km. (7 miles) from the works. The gas enters the pipeline through regulating and metering equipment at a pressure of about 50 lb. per sq. in., and emerges at the works through an oil and water separator at about 20 lb. per sq. in.

The clinker is cooled in a Fuller-629 inclined cooler, the breaker of which discharges into vibrating conveyors which carry the clinker horizontally to an inclined belt-conveyor, with an automatic-weigher, to the store.

All instruments and motor controls for the kiln are located on a control board with mimic panels which gives central manual control of the plant.

### **Grinding, Storing and Packing.**

The gypsum, which is delivered by road from a source 125 km. (78 miles) from the works, is a hard crystalline material and is reduced in a hammer crusher to a size such that 90 per cent. passes through a 25-mm. (1 in.) screen. From the crusher, it is conveyed to a bin in the main store. The clinker and gypsum are ground in an open-circuit three-chamber Polysius compound mill, 2.2 m. (7ft. 3 in.) in diameter and 13 m. (42 ft. 7 in.) long, fitted with a girth gear and pinion driven by a 630-kw. 6000-volt motor through a reduction box with barring gear. The mill is ventilated through an automatic bag-filter. The output is 18 tons per hour with a residue of not more than 5 per cent. on a 170-mesh.

The cement is taken by screw-conveyors under the main store and then by elevators to the three concrete silos (seen at the left of *Fig. 2*), which are 9.5 m.

(31 ft.) in diameter and 19.7 m. (95 ft.) high. It is taken from the bottom of the silos by Polysius extraction equipment and by means of screw-conveyors it is taken to the packing plant. Here it is elevated to a screen and the hopper of the four-spout packer, which is provided with a dust collector, and where it is packed into paper bags for despatch by rail or road. The packing plant is seen on the extreme left of *Fig. 2*.

### Buildings.

The buildings housing the plant are of reinforced concrete. The climate requires open buildings as exemplified by the firing and feed-end buildings. Since the ground is capable of bearing over 4 tons per sq. ft., the work of constructing the foundations was simple. A workshop fully equipped with machine tools and a 3-ton overhead crane, and an air-conditioned laboratory and offices are also provided.

The senior staff are European and for them there is a housing estate with suitable amenities; the houses can just be discerned in the background of *Fig. 4*.

The works were designed and constructed under the supervision of Henry Pooley (Consulting Engineers). The plant for the preparation of the raw material, the kiln, and the grinding mills were supplied by Polysius G.m.B.H. The main electrical equipment was supplied by Siemens-Schuckertwerke A.G., and the complete power plant by M.A.N.A.G. The civil engineering work was carried out by Mist Concrete Development Co., S.A.E., of Cairo.

---

### False Set.

IN a paper entitled "Quick and False Set in Portland Cement" by W. C. Hansen [reprinted from "A.S.T.M. Materials Research & Standards," October 1961, and issued by the National Ready Mixed Concrete Association (U.S.A.)], the information in the papers presented at the Fourth International Symposium on the Chemistry of Cement is reviewed. False set is defined as the stiffening produced by the crystallization of gypsum in the cement paste and quick set as the stiffening produced by the reactions of  $C_3A$  and  $C_4AF$  with water. Some cements containing dehydrated gypsum may not show false set until aeration reduces the rate at which  $C_3A$  reacts with  $CaSO_4$ . It is shown that some cements may develop quick set by aeration, reducing the ability of  $C_3S$  to release  $Ca(OH)_2$  to the solution to control the reactions of  $C_3A$  and  $C_4AF$  with water.

---

### Cement Industry in South Africa.

**Transvaal.**—The works at Slurry of the Pretoria Cement Co., Ltd, has been converted from a wet-process plant to a highly instrumented efficient dry-process plant having a daily capacity of about 1,400 tons. The new plant incorporates two new raw-mills each 19 ft. 6 in. long and 9 ft. 6 in. diameter, six 500-ton blending silos, two 485-ft. kilns of about 12-ft. diameter, and two cement mills each having an output of 32 tons per hour.



---

# STEETLEY

*Improved*

## Rotary Kiln Lining Blocks

**NOW  
ABSOLUTELY  
GUARANTEED  
for  
ACCURACY  
OF TAPER  
LOW POROSITY  
EASY BRICKING**




- Guaranteed dead accuracy of taper.
- Combination of bricks will turn any desired circle to fit the burning zone of a rotary kiln.
- This introduces the bonded type of brick construction, with its increased mechanical strength of the lining, resulting in extra lining life.
- Easier and quicker bricking.
- Colour key enables bricks to be easily recognised when fitting combination of bricks for ring.
- Steel jointing plates attached to individual bricks if requested.
- Can be supplied in Mag. 90 or Mag-Chrome qualities at highly competitive prices.

*Technical information on request.*

**SIZES AVAILABLE**

- 9" x 4½"/? x 6" CROWN
- 9" x 4½"/? x 3" CROWN BONDER
- 7" x 4½"/? x 6" CROWN
- 7" x 4½"/? x 3" CROWN BONDER



### THE STEETLEY REFRACTORY BRICK CO LTD

**WORKS AT:**      NORMANBY      |      OUGHTIBRIDGE      |      STEETLEY      |      BRASSINGTON  
                          near MIDDLESBROUGH      |      near SHEFFIELD      |      near WORKSOP      |      DERBYSHIRE

*All enquiries to: The Steetley Refractory Brick Co. Ltd. Oughtibridge near Sheffield      Tel: Oughtibridge 2311*

## BOOKS ON CEMENT

### CEMENT CHEMISTS' AND WORKS MANAGERS' HANDBOOK

By W. WATSON, B.Sc., and Q. L. CRADDOCK, M.Sc.

Revised 1962

234 pages. Price 25s, by post 26s 3d. In Canada and U.S.A., 5.50 dollars.

Cement specifications of the world (1961).

Dimensions of standard sieves. Weights and volumes of slurry. Capacities of tanks and kilns. Gas volumes per ton of clinker. Kiln data. Fan horse-power. Volumes and weights of gases from kilns. Density of exit gases. Density of gases in kilns. Proportioning and chemical control of raw mixes. Heat balance.

Conversion tables (English-metric and metric-English)—Pressures. Density and concentration. Heat, work, energy and calorific values. Specific surface. Air passing through pipes: rate of flow.

Properties of substance, compounds, and alloys. Solubilities of gases in water. Specific gravities of hydrochloric, sulphuric and nitric acids at 15 deg. C. Specific gravity, degrees Twaddell and degrees Baumé. Conversion of hydrometer readings to specific gravity. Weights of substance. Tension of aqueous vapour. Density and volume of water at different temperatures. Weights of sheet metal. Weights of water vapour and dry air in saturated air at different temperatures. Calibration of pyrometers. Heat units. Combustion data. Freezing mixtures. Evaporative power. Calorific power and carbon value.

Standard solutions and bench reagents. Chemical tables: atomic weights, gravimetric factors, conversion of weights and precipitates. Chemical analysis of argillaceous and calcareous materials, coal and coke, gypsum, and cement.

Tests: Setting, consistency, fineness, soundness, strength; revised to 1961.

### PORTLAND CEMENT

By SIR CHARLES DAVIS

Reprinted 1948

340 pages. Price 30s, by post 31s 9d. In Canada and U.S.A., 6.80 dollars.

DEVELOPMENT OF PORTLAND CEMENT MANUFACTURE.

RAW MATERIALS: Estimation and Analysis. Proportioning and Preparation. Preliminary Crushing and Grinding. Transporting.

BURNING: Intermittent, Chamber, Batchelor, Continuous, Dietsch, Hoffman, Aalborg, Stein, and Schneider kilns. Rotary kilns. Coolers. Linings. Coal firing and mills. Quality of coal. Control of Rotary kilns. Instruments. Reactions in Burning. The Heat Balance in Rotary kilns. Waste-heat Boilers. Coal Grinding. CLINKER GRINDING: Ball, tube, and compound mills. Open and closed circuits.

DUST COLLECTION: Mechanical, washing and electrostatic apparatus.

POWER FOR CEMENT WORKS. PACKING AND DESPATCH. SAMPLING AND TESTING.

CHEMISTRY OF CEMENT: Composition of Portland cement. Uncombined lime. Chemical analyses. Effect of fuel ash, Silica, lime, and alumina. Ferric oxide and alumina. Magnesia, Sulphuric anhydride. Insoluble residue. Loss on ignition. Sulphur. Potash and soda. Carbon dioxide.

SETTING AND HARDENING: Control of setting time. "False" set. Determination of setting time. High-alumina cement. Normal consistency. FINENESS: Sieving. Fine grinding. Cementitious value of fine and coarse grains. Elutriators. CONSTANCY OF VOLUME: U.S.A. tests. Le Chatelier test. "Cold plunge" test. Faija test.

STRENGTH: Differences in tensile test results. Standard tests. Testing machines. Growth of strength. Compression and Transverse Tests.

---

The foregoing books are in the "Concrete Series" published by  
**CONCRETE PUBLICATIONS LTD.**

---

### WORLD CEMENT DIRECTORY

An International Directory of the Cement Industry.

Published (in English) by **Cembureau**. Price 75s, by post 77s 3d.

The data are up to date to the beginning of 1960 and are presented in tables and maps giving size, location and ownership of cement works in about a hundred countries; names and addresses of the operating companies and of their works; number and type of kilns; method of manufacture; productive capacity; types and trade names of cements manufactured.

### REVIEW OF PORTLAND CEMENT STANDARDS OF THE WORLD—1961

Published (in English) by **Cembureau**. Price 25s, by post 25s 9d.


Data brought up to date to June, 1961; specified requirements of 42 countries; Chemical and physical requirements; strengths; tests.

---

*The foregoing books are obtainable, at the prices stated, from*

**CONCRETE PUBLICATIONS LTD.**  
14, DARTMOUTH ST., LONDON, S.W.1.

---



Radio Times Hulton Picture Library

## Horse-sense

claims a dictionary definition  
of 'plain, robust sense'

... but the dictionary offers  
little help in defining

## Know-how

which might be described  
as 'horse-sense allied to  
experience'

### IN MORE THAN FIFTY YEARS

as manufacturers of **electric motor control gear**,

Allen West & Co Ltd have developed a  
specialist 'know-how', backed by intensive  
programmes of testing and research.

*For all industrial, traction, and marine applications,  
the acknowledged symbol of service and reliability is*




**ALLEN WEST**

**ALLEN WEST & CO LTD BRIGHTON ENGLAND** · Telephone: Brighton 66666 · Telegrams: Control, Brighton

*Engineers and Manufacturers of Electric Motor Control Gear and Switchgear*

SUBSIDIARY COMPANIES IN CANADA, SOUTH AFRICA AND RHODESIA · AGENCIES THROUGHOUT THE WORLD



## **FINAL KILN SECTION ARRIVES -for new giant Blue Circle plant at Westbury**

Vickers-Armstrongs have supplied the complete kiln installation and three grinding mills for the Blue Circle Group's new Westbury Cement works.

### **THE GIANT COMPLETED**

The massive kiln, built at Vickers-Armstrongs Barrow works, is 450 ft. in length. Capacity of the plant is 800 tons daily.

*Vickers are fully equipped for the design and manufacture of complete cement plants as well as individual kilns, mills and ancillary equipment. For your special needs call in*

# **VICKERS**



## Specifications for Portland Cement.

TABLES giving the requirements regarding the strengths of Portland cement in accordance with standard specifications of certain countries were given in this journal for July last; these tables (*Table III*) are concluded on pages 80 to 82 in the present number. Tables for Chemical Composition (*Table I*) and Setting Time and Soundness (*Table II*) were published in this journal for May last. The data is up to date to 1961. The notes in the following apply to *Table III* (Strengths). TYPES OF CEMENT.—Abbreviations denote the various types of cement as follows: H.S., high strength; L.H., low heat; S.R.-L.H., moderate sulphate resistant and low heat; S.R., sulphate resistant; R.H., rapid hardening; O., ordinary; A.E., air entrained.

---

### The Cement Industry in the East.

**Cambodia.**—A Chinese aid project is the construction of a cement works at Kampot; work is due to start this year.

**Thailand.**—The Siam Cement Co., is to build a new cement works in South Thailand which will produce 250,000 metric tons annually, and which will be the third of this Company's works. The annual production of the two existing works is 700,000 metric tons.

Provisional quantities of the production of cement in Thailand in 1961 are 802,000 metric tons compared with 543,000 metric tons in 1960.

**Indonesia.**—The Cresik cement works, which recently produced its five-millionth bag of cement, has commenced operation of a third kiln. The annual output is expected to increase from 275,000 tons to 375,000 tons. It is stated that the annual requirement of the country is 1,000,000 tons. Present regular supplies amount to 800,000 tons, including 300,000 tons which are imported.

**Japan.**—Cement production increased from 17,269,000 tons in 1959 to 22,539,000 tons in 1960 when there were forty-six works with a total of 169 kilns in operation. The productive capacity was 2,350,000 tons monthly. It is reported in "Cement, Lime & Gravel," that 85 of the kilns are dry process, 21 are wet process (short), 30 are wet process (long), 23 are Lepol kilns, and there are ten shaft kilns. Nearly half the kilns have been in use for more than twenty years. In 1960, the amount of cement exported was 1,632,000 tons, an increase of 12 per cent. on the previous year. Home sales were 21,930,000 tons, an increase of 28 per cent.

**Malaya.**—A new works, having an initial annual capacity of 180,000 tons and an eventual capacity of 240,000 tons, began operation recently at Singapore.

**Pakistan.**—In the January number of this journal, reference was made to new cement works to be installed at Manghopir and Gharibwal. The works at the former place will have a capacity of 500 tons daily and will operate on the dry process. The works at Gharibwal will operate on the wet process and will have a capacity of 1,200 tons daily. The consulting engineers for both works are Henry Pooley (Consulting Engineers).

TABLE III.—STRENGTH OF PORTLAND CEMENT (Continued from July.)

(For Notes see page 79.)

Country	Type of Cement	Tensile Strength Age of specimen in days				Bending Strength Age of specimen in days				Compressive Strength Age of specimen in days				Remarks
		1	3	7	28	3	7	28	1	3	7	28		
Spain	O.1	—	—	—	—	384 27	611 43	—	—	—	1337 94	2133 150	—	1500g. sand : 500g. cement : 250g. water
	O.2	—	—	—	—	526 37	796 56	—	—	—	2375 167	3555 250	—	
	R.H.	—	—	—	—	469 33	640 45	910 64	—	—	2545 179	4977 350	—	
	S.R.	—	—	—	—	384 27	611 43	—	—	—	1337 94	2133 150	—	
Sweden	O.	—	—	—	—	427* 30*	640* 45*	924* 65*	—	—	2275* 160*	3697 260	5972 420	Bending strength at 1 day is (427*/30*) Bending and compressive at 90 days: (924*/65*) and (5972/420)
	R.H.	—	—	—	—	853* 60*	924* 65*	—	—	2275* 160*	4835 340	5972 420	—	
	L.H.	—	—	—	—	—	427 30	711 50	—	—	2275* 160*	4124 290	—	
Switzerland	O.	—	—	—	—	—	711 50	924 65	—	—	—	4266 300	5688 400	
	R.H.	—	—	—	—	782 55	924 65	1067 75	—	—	5261 370	6968 490	8390 590	
Taiwan	O.	—	149	275	338	—	—	—	—	—	853 60	1771 125	2986 210	
	M.S.R./ M.L.H. }	—	10.5	19.0	24.0	—	—	—	—	—	711 50	1493 105	2986 210	
	R.H.	275 19.0	382 26.5	—	—	—	—	—	—	1286 90	2489 175	—	—	

Turkey	O.	—	313 22	384 27	—	—	—	4267 300	4978 350	Tensile and compressive at 28 days combined wet and dry storage: (455/32) and (5688/400)
	R.H.	—	384 27	484 34	—	—	—	—	6045 425	Ditto (597/42) and (7466/525)
Uruguay	O.	—	—	—	—	—	—	2133 150	—	—
	R.H.	—	—	—	—	—	1565 110	4400 310	—	—
U.S.A. A.S.T.M. and A.A.S.H.O. Standards. Federal require- ments similar except where noted	O.	—	150 11	275 19	350 25	—	—	1200 84	2100 148	3500 246
	M.S.R.	—	125	250	325	—	—	1000†	1800†	3500†
	M.L.H.	—	9	18	23	—	—	70†	127†	246†
	R.H.	275 19	375 26	—	—	—	—	1700 120	3000 211	—
L.H.	—	—	175 12	300 21	—	—	—	800 56	2000 141	—
	S.R.	—	—	250 18	325 23	—	—	1500 105	3000 211	—
O.(A.E.)	—	—	—	—	—	—	—	900 63	1500 105	2800 197
	M.S.R./ M.L.H. (A.E.)	—	—	—	—	—	—	750† 53†	1400† 98†	2800† 197†
(A.E.)	—	—	—	—	—	—	1100 77	2200 155	—	—
R.H. (A.E.)	—	—	—	—	—	—	1300 91	2500 176	—	—

TABLE III.—STRENGTH OF PORTLAND CEMENT (Concluded.)

(For Notes see page 79.)

Country	Type of Cement	Tensile Strength			Bending Strength			Compressive Strength			Remarks			
		Age of specimen in days			Age of specimen in days			Age of specimen in days						
		1	3	7	28	3	7	28	1	3	7	28		
U.S.S.R.	300	—	—	213	284	—	—	—	—	—	2844	4266		
				15	20						200	300		
	400	—	—	228	270	—	—	—	—	—	2702	3982		
				16	19	23					190	280	400	
Venezuela	500	—	—	284	327	—	—	—	—	—	3697	5404		
				20	23	27					260	380	500	
	600	—	—	313	384	—	—	—	—	—	4266	6399		
				22	27	32					300	450	600	
Yugoslavia	O.	—	—	156	284	—	—	—	—	—	910	1806		
				11	20	25					64	127	211	
	S.R./L.H.	—	—	128	256	—	—	—	—	—	754	1507		
				9	18	23					53	106	211	
	O.1	—	—	—	—	—	356	498	—	—	1422	2133		
							25	35			100	150		
	O.2	—	—	—	—	—	427	640	—	—	2275	3555		
							30	45			160	250		
	O.3	—	—	—	—	—	569	782	—	—	3555	4977		
							40	55			250	350		
	R.H.	—	—	—	—	—	498	640	853	—	2844	4977		
							35	45	60		200	350	450	

2:75 : 1 mortar for compressive test

## Production Control with Closed-circuit Television Systems.

SEVERAL cement works use closed-circuit television to aid in the control of one or more stages in production. A simple example is the closed-circuit television system installed recently in the dry-process works of the British Columbia Cement Co., at Bamberton, near Victoria, British Columbia, and by means of which there is centralised control of some of the operations concerned with the raw material. The installation reduces labour costs and increases efficiency. For an initial expenditure of about £3000 on the installation, it is claimed that a saving of about £5300 in wages is effected annually.

The installation comprises two cameras, which are focused on the two storage bins, each 80 ft. by 10 ft. and which relay to a 17-in. monitor screen on the control panel of the dry-mill. Each bin contains 800 tons of crushed stone and the operator is able to see the level of the stone in each bin. With this information, he can cause a travelling tripper to move to enable stone to be fed into any of the five compartments into which each bin is divided, and so add stone where it is needed. He can also control the belt-conveyor which is over the bins and is 150 ft. above the control floor. Both cameras are mounted on antenna rotators (*Fig. 1*) which can be moved by the operator who can thus see a complete picture of each bin. The camera which covers the upper bin is mounted in the roof of the mill,




Fig. 1.




Fig. 2.

30 ft. above the bin (*Fig. 2*). The other camera is at normal eye-level and about 25 ft. to one side of the lower bin. These comprehensive sitings and the rotating mountings are necessary because during trials it was found that cameras in a fixed central position relayed pictures that were misleading to the operator, since they could cover only about half of each bin. A problem in the installation was to place the cameras at the optimum distance from each bin to obtain an overall picture of the level of the stone instead of an unsatisfactory picture of a part of the bins. To get the necessary coverage of the upper bin, it was necessary to raise the roof of the mill building by 12 ft. The lighting is arranged so that irregular shadows fall on the stone (*Fig. 3*), thus ensuring that the contents of the bins are shown in detail on the monitor screen; uniform lighting destroys the shading of the stone as seen in the picture. Light from outside the mill has to be obstructed because, on bright days, errant light patterns can seriously disrupt the image shown on the monitor screen. To give sufficient light for the cameras to operate at maximum efficiency, the upper bin has a battery of twelve R40 300-watt flood lamps arranged along the bin in pairs of lights at six equidistant points. The layout is identical for the lower bin but, because this is naturally darker, there are three flood lamps at each point.

Although the television system usually works continuously, the crushers operate only when crushed stone is required. One minute after the crushers are switched on, a tape-recorder automatically broadcasts over loud-speakers a warning to workers to stand clear. After another minute, and without any further manual movement, the crushing plant begins to work. The television

equipment used at this works was supplied by the General Electric Company of Canada.

A more complicated closed-circuit television network operates at the works of the Permanente Cement Co., Waianae, Hawaii. Three systems comprising six cameras and eight monitor screens give the operators of the materials handling, the foremen, the mill operators, and the chemists current information about progress at various stages of manufacture. One system is a single camera mounted above the primary jaw crusher and transmitting to a monitor screen on the control panel of the secondary crusher. Therefore the operator can see any stone that is too large and which might subsequently prevent the even flow of stone to the secondary crushing station, and he can take immediate action to re-establish continuity. In the kiln area, a system of three cameras relays to a treble-monitor control panel where one man supervises the three operations at this stage. A Dage heavy-duty camera in a dust-proof housing gives an overall picture of the kiln. Another camera is permanently focused on the chain-and-sprocket drive and shows any fault in this equipment which might hinder the smooth exit of clinker from the kiln. Any overflow of the clinker from the discharge conveyor appears on the third monitor screen. The mill operators and the chemists responsible for proportioning the feed to the mills are served by the third system, which comprises two Dage heavy-duty cameras. These are protected by dust-proof housings and are mounted over the conveyors carrying the basalt, gypsum



Fig. 3.



Fig. 4.

and silica sand from the storage silos to the mills. Consequently the operators and chemists may check the conveyors periodically to ensure that the passage of the materials is unhindered.

A network of eight closed-circuit television cameras and ten monitor screens has been operating for two years at the works of the Dundee Cement Co., Michigan, U.S.A., and is part of the highly automated production control system at this works. When first opened the works had a production of 1,000,000 tons a year. Only 110 workers on production and fifty other employees are required. The works (*Fig. 4*) occupies about  $1\frac{1}{2}$  acres of a 30-acre site adjacent to 1600 acres of land suitable for quarries. Coal arriving by rail is pulverised at the works. The limestone and clay slurry contains 33 per cent. of water. Two slurry mills, which are claimed to be the largest in the world, work in series and reduce the particles to such size that 80 per cent. passes a 200-mesh. The operating of the two rotary kilns, which are each 460 ft. long and from 15 ft. to 16 ft. 6 in. in diameter, is supervised from a central control room. Clinker is discharged from the kilns at 2000 deg. F. and is cooled to 200 deg. F. in a horizontal air-quenching cooler 60 ft. by 10 ft. The cement from three cement-grinding mills and separators is pumped into eight storage silos, each of which is 150 ft. high and has a capacity of 5000 tons. There are also twelve 1250-ton silos for special cements.

The television systems permit complete control of the manufacturing and despatching operations at this works. The operator of the secondary crusher, for example, can remain near his control panel (*Fig. 5*) and simultaneously view on the screens the inlet and outlet of the crusher at the quarry, the reclaimed material in the tunnel beneath the stockpile, and the raw-material conveyor discharging into the bunker in the main part of the works. From a screen in the sales office, the clerk can record the weight of lorries which are loading at the packing house and prepare





Fig. 5.

documents so that they are ready when the lorry arrives at the sales office. The cameras and five of the monitoring sets were supplied by the General Electric Company of America. The other five monitoring sets, which were manufactured by the Conrac Company and have larger screens, are on the mill control-panel and in the sales office. Initially there was deterioration of the electronic components, high maintenance costs, and unsatisfactory pictures. These defects were found to be due to such causes as fluctuations of voltage, inadequate co-axial cable, and insufficient lighting. Since these faults were rectified, it is said that excellent results have been obtained and that maintenance costs have been reasonable.

Particulars of the installation at the works of the Permanente Cement Co., are abstracted from a recent number of "Pit and Quarry." The description of the installations at the works of the British Columbia Cement Co., and the Dundee Cement Co., is based on information contributed by MR. LEO WALTER. Reference should also be made to the number of this journal for May 1959 in which a television installation at the works of the California Portland Cement Co., is described.

---

#### Conference of the Silicate Industry.

THE Seventh Conference of the Silicate Industry will be held in Budapest from June 4 to 7, 1963. The meeting is organized by the Scientific Society of the Silicate Industry and by the Central Institute of Building Material Research of Hungary. The address of the Secretariat is Seventh Conference of the Silicate Industry, Executive Committee, Budapest, V., Szabadság tér 17.

The subjects of interest to cement manufacturers include automation, new types of refractories, thermal reactions of clay minerals, problems of rotary kilns, high-magnesia Portland cement, the hydration of cements, and drilling and blasting in quarries. The official languages of the Conference are English, German, Russian and Hungarian.

## Research on Cement in Great Britain.

IN addition to the research carried out continuously by the several cement manufacturers in Great Britain, many investigations are proceeding, either independently or in conjunction with manufacturers, at the Building Research Station and by the Cement & Concrete Association. Some of these investigations, particulars of which are abstracted from the Annual Reports for 1961 issued by both these bodies, are described in the following.

### Reactions in the Lime-silica-water System.

Work in progress on the  $\text{CaO-SiO}_2\text{-H}_2\text{O}$  system includes an investigation, by the Association, of the nature of the hydrated calcium silicates by methods of inorganic and physical chemistry as distinct from crystallographical methods. The two types of structure proposed for the calcium-silicate hydrates thought to be formed in cement-water pastes correspond essentially to a tobermorite-like structure of meta-silicate chains linked by calcium ions and hydrogen bonds, and an ortho-silicate structure built up of individual  $\text{SiO}_4$  tetrahedra. The evidence for the former is derived largely from X-ray diffraction data, and that for the latter from the reactivity of cement gels towards acids. Investigations tending to support the latter proposal include the following.

Measurement of the rate at which equilibrium is established between calcium silicate hydrates and lime solutions.

Observation of the effect of pH and  $\text{SiO}_2$  concentration in solution on the crystallinity of calcium-silicate hydrates.

Measurement of  $\text{Ca}^{2+}$ -ion mobility as the C/S ratio is changed in calcium-silicate-hydrate preparations.

Observation of the structure of dehydration products of calcium-silicate hydrates.

A very rapid adjustment of silica concentration in the aqueous phase in contact with Taylor's  $\text{CSH}(\text{I})$  after sudden dilution has been found and suggests that the silica present in the crystals of  $\text{CSH}(\text{I})$  is in a more readily available form than infinite meta-silicate chains. When the composition of the  $\text{CSH}(\text{I})$  is below C/S of about unity, the composition of the equilibrium aqueous phase does not adjust itself so readily, possibly because the presence of meta-silicate chain species in the solution phase itself causes delay in reaching final equilibrium; or it may be that the solid-phase structure changes fundamentally near  $\text{C/S} = 1$  and below this value includes meta-silicate chains in the crystal structure. Both factors may operate.

Other experimental evidence bearing on the crystal structure of  $\text{CSH}(\text{I})$  has been obtained from the conditions under which it is precipitated in a crystalline form. Sodium-silicate solution and calcium nitrate solution on mixing give well crystallised  $\text{CSH}(\text{I})$  when the sodium-silicate solution is either of high pH or of low concentration in silica, both tobermorite and  $\text{CSH}(\text{I})$  have been reported from dehydration experiments. On dehydrating natural tobermorite at 700 deg. C.,  $\beta\text{CS}$  ( $\beta$  Wollastonite containing meta-silicate chains) is formed. On dehy-



**DON'T LET REFRACTORIES PROBLEMS GET YOU DOWN**

Not much point in sitting there with a load on your mind. Turn the problem of selection of refractories over to Consett Iron Company Limited.

In all probability we have already met—and solved—your particular difficulty. If not, then nearly a century of manufacturing experience and research by Consett are at your service.

Get on to Consett and relax, knowing that your problem is in the right hands.



**CONSETT** IRON COMPANY  
LIMITED

CONSETT · COUNTY DURHAM. Telephone: Consett 341. Telegrams: Steel  
Consett Telex. Telex: 53172.

# The largest kilns in the world

## COMPLETE CEMENT FACTORIES

Crushing, grinding, drying,  
burning plants for all kinds of minerals




PHOTO PARIS MATI

*Alhandra cement factory (Portugal). View of the kiln (167.5 m x 4.8/5.3 m - 1600 T/day)*

SAG - PARIS - 2022



# FIVES LILLE - CAIL

7. rue Montalivet, PARIS (8<sup>e</sup>) - Tél. : ANJou 22-01 et 32-40

drating CSH(1) at 700 deg. C.,  $\beta\text{C}_2\text{S}$  (dicalcium silicate containing  $\text{SiO}_4$  ortho-silicate ions) is formed. An ortho-silicate hydrated compound might be expected to produce an ortho-silicate anhydrous compound; further experiments are in hand.

Work is now in progress on the kinetics of the lime take-up by CSH. Radio-isotope exchange results indicate a considerable reduction in calcium ion mobility at low C/S ratios. A relationship between calcium ion mobility and rate of lime take-up should exist.

### X-ray Diffractometry.

Investigations utilising X-ray diffractometry are proceeding at the laboratories of the Building Research Station and the Cement & Concrete Association. The technique is similar to normal powder X-ray diffraction, but instead of recording the spectrum by means of photographic film a direct record of scattered intensity is obtained by means of a suitable counter and associated circuit. The main difficulties are the small size of specimen (with consequent sampling errors), the varying X-ray reflections obtained with components which differ slightly from one cement to another, and confusion arising from the overlapping of reflections from the many components present.

The role of minor constituents in modifying the behaviour of the major hydraulic constituents of Portland cement is being studied at the Building Research Station, because such work is necessary if the chemistry of cement is to be fully understood and an optimum quality of manufacture maintained. For example, though a high proportion of alite (tri-calcium silicate solid solution) in the clinker has always been associated with the development of high strength, some cements containing a very high proportion of alite may have low strength. This may be caused by the solution of minor constituents in the solid alite. Although the alite phase is essentially  $3\text{CaO}\cdot\text{SiO}_2$ , it normally contains a little MgO and a trace of  $\text{Al}_2\text{O}_3$  substituting for CaO.


An unsolved problem of cement chemistry is how to determine the mutual solid-solution limits for the major cementing phases, and investigations are proceeding at the Station by means of quantitative X-ray diffractometry. Pure mixtures of cement composition are synthesized and, after a known heat-treatment, are analysed on the diffractometer; the data obtained from the counter are fed to a computer which analyses the results in terms of the composition of the components in the mixture.

Because of the importance of sulphate-resisting cement and the necessity of a standard specification, attention is being paid to the estimation of low contents of  $\text{C}_3\text{A}$  in cements. This work is being done at the Station by a research fellow appointed by the Associated Portland Cement Manufacturers Ltd.


Quantitative X-ray diffractometric analysis of cement has become a routine method for the examination of cements at the Association's laboratories. It is clear that the anhydrous cement compounds require further study. The precise quantitative information which the method provides enables small differences in the compounds to be detected and it now appears that each of the four




(a)



(b)



(c)



(d)

**Fig. 1.—Electron Micrographs of Tobermorite.**

principal compounds can contain small amounts of alien oxides which may alter their crystal structure. Even if there is no structural change, the fact that the compounds can have a variable composition means that calculations of the compound composition of cement from elemental analyses and the traditional two, three and four oxide systems can only be approximate. These small inclusions change the crystal symmetry of alite so that triclinic  $C_3S$  becomes monoclinic alite. In the case of belite, a high temperature  $C_2S$  phase becomes stabilised at room temperature. In the case of  $C_3A$  the effect is merely a change in unit cell size; this change and the capacity for take-up of other oxides is being studied. So far  $Fe_2O_3$  and  $SiO_2$  have been examined and work on the effect of  $MgO$  and alkalis is in progress. There seems to be no alteration of crystal symmetry ( $C_3A$

**OUR  
DRYERS  
ARE**

gentle

British 'Rema' pneumatic dryers are particularly suitable for small materials easily damaged by breakage or overheating.

The particles are separated and swept by hot gases giving a rapid transfer of moisture from the material to the air stream.

Drying plant is manufactured for many different products and we supply plant up to the largest sizes. Please fill in



the request form to gain all the information you require.

BR 49/CLM

To BRITISH 'REMA' MANUFACTURING CO. LTD.  
ONE INDUSTRY ROAD, SHEFFIELD 9

Please post data on "British Rema Dryers" to:—

Name .....

Position .....

Firm .....

Address .....

**BRITISH 'REMA' MANUFACTURING CO. LTD.,**  
A Subsidiary of EDGAR ALLEN & CO. LTD.  
**ONE INDUSTRY ROAD, SHEFFIELD 9**  
Telephone: 42721/2

Review of

**PORTLAND CEMENT  
STANDARDS  
OF THE WORLD**

**1961**

♦

**Published in English**

by

**CEMBUREAU**  
(SWEDEN)

♦

**Data brought up to date (with revisions) to June, 1961.**

Specified requirements of forty-two countries.

Chemical and physical requirements.

Strengths.

Tests.

Essential work of reference for manufacturers and exporters of cement, cement chemists, and contractors with overseas projects.

96 pages

♦

**Price 25s.; by post 25s. 9d.**

**Distributed in British Isles**

by

**CONCRETE PUBLICATIONS LTD**  
**14, DARTMOUTH ST., LONDON, S.W.1.**

# Powder, Particles or Pieces . . .



*a revolutionary method of  
CONVEYING, feeding, mixing  
and proportioning*

TOTALLY ENCLOSED AND DUST FREE  
NO ABRASION OF PLANT  
OR OF MATERIALS HANDLED  
LOW POWER CONSUMPTION

## VIBRATORY CONVEYORS

A remarkable method of conveying chemicals, ashes, coal and other materials, giving efficient dust-free transportation, extremely economical to operate and to maintain.

**OWL ENGINEERING SUPPLIES LTD., Kirkstall Rd. Leeds 3 A MEMBER OF THE**



**Bet  
your  
boots  
on**



## PEARSON refractories!

**E. J. & J. PEARSON LIMITED · FIREBRICK WORKS · STOURBRIDGE**



being cubic) and the changes in cell size are small.  $\text{Fe}_2\text{O}_3$  causes an expansion of the unit cell as expected if Al are replaced by Fe atoms. A decrease in cell size is caused by the inclusion of  $\text{SiO}_2$ , which is expected if Si replaces Al.

### Mineralogical Studies.

The hydration products formed at various stages in the setting of cement have been studied, at the Building Research Station, using X-ray diffraction differential thermal analysis, and infra-red spectrometry. Most information has been obtained by a combination of thermal analysis and X-ray diffraction, both methods being necessary because, in the early stages of setting, the products of reaction are poorly crystallised and do not give clear diffraction patterns. An extensive investigation has been made into the setting of high-alumina cement at various temperatures and there is more understanding of the reaction which causes the cement to lose strength under moist warm conditions. A similar investigation is being made of the setting of supersulphate slag cement, recently introduced as a British product.

An E.M.6 electron microscope, which has been installed at the Station, is capable of a resolution of  $7\text{-}10\text{\AA}$ , and has been primarily used for the study of the products of cement hydration. Examination of calcium-silicate hydrates has revealed structures that are generally in accord with electron micrographs, but high-resolution investigations have shown that some supposed differences between the various forms are not, in fact, real. Pictures of the calcium silicate hydrate particles from a set commercial Portland cement show that tobermorite can co-exist in many of its habits in one sample. High-resolution pictures (*Fig. 1*) have shown much more detail than hitherto and this may result in a better understanding of the mechanism of the setting of cements.

At (*a*) in *Fig. 1*, the typical twisted shape of the crimped foils of tobermorite gel is clearly seen. Fibrous tobermorite, from a set cement, is shown at (*b*); the crystals are produced by precipitation from solution. The widths of the thin wispy fibres at the end of a crystal of fibrous tobermorite shown at (*c*) are only about  $100\text{\AA}$ . At (*d*) is shown tobermorite from a sample of hydrated tricalcium silicate; the crystals, which exhibit an outer rim of tobermorite, were formed by topochemical reaction, tricalcium silicate being replaced by calcium-silicate hydrate.

---

### Cement Industry in New Zealand.

As part of a transport modernisation programme developed by Wilsons (N.Z.) Portland Cement Ltd., new loading and unloading facilities have been installed at the works at Portland, near Auckland. This company is the largest manufacturer of cement in New Zealand and produces about 300,000 tons annually. The works is situated adjacent to Whangarei Harbour, from where cement is shipped in bulk in the Company's cement carrier M.V. "John Wilson" (see this journal for July 1961) and delivered to coastal towns in New Zealand where it is unloaded into silos and later transported by road to inland areas. The harbour is very silted so that, to obtain sufficient depth of water for the vessel, a 4000 ft. wharf has been constructed.

### Refractories in Kilns.

RECENT major developments in kilns have resulted in greater production with a reduction of costs. Kilns are longer, the diameters tend to be greater, the intake of fuel has increased, and liquid fuels are being used. Conditions in the clinkering zones of many kilns are now such that it has been necessary to replace traditional refractories by bricks of greater chemical resistance. This matter is discussed in a paper entitled "New Approach to Portland Cement Kiln Refractory Problems" by H. Parnham, which is given in "Edgar Allen News" for May 1962.

### Publication Received.

"PROJETO DE UM FORNO ROTATIVO DE CIMENTO." By J. F. de Assumpção Santos. (In Portuguese; published in Sao Paulo, 1961.) This book of about 100 pages describes the fundamental computations related to a particular wet-process rotary kiln, the dimensions of which are calculated from the thermodynamical data of a mixture of clay from Aratú, Bahia, and limestone from Pindoba, Sergipe, in north-eastern Brazil. The fuel is a typical bunker C oil, the chemical composition and other properties of which are known. The horse-power requirements are based on selected, but generally accepted, formulae.

#### MISCELLANEOUS ADVERTISEMENTS

##### SCALE OF CHARGES

*Situations Wanted, 3d. a word; minimum 7s. 6d. Situations Vacant, 4d. a word; minimum 10s. Box number 1s. extra. Other miscellaneous advertisements, 4d. a word; 10s. minimum. Advertisements must reach this office by the 5th of the month of publication.*

#### "CONCRETE SERIES"

### BOOKS ON CEMENT and CONCRETE

For a complete catalogue giving prices in sterling and dollars, send a postcard to:—

**Concrete Publications Limited**  
14 Dartmouth Street, London, S.W.1

**CHECK MOISTURE CONTENT ON SITE**  
in less than 3 minutes with

### THE "SPEEDY" MOISTURE TESTER

Fully portable · Over 23,000 in use · £29.10s. complete

Write for leaflet to:

**THOMAS ASHWORTH & CO. LTD.**  
Dept. CE2, Sycamore Avenue, BURNLEY, LANCs.

The Proprietors of Patent No. 813084 for "Manufacture of High Early-strength Cements from Granulated Blast Furnace Slags" desire to secure commercial exploitation by Licence or otherwise in the United Kingdom.

Replies to

**H. N. & W. S. SKERRETT**  
24 Temple Row ● Birmingham 2.

#### INTERNATIONAL DICTIONARY OF CONCRETE

Compiled by STUVO (Amsterdam) in conjunction with F.I.P.

A vocabulary of upwards of 1300 terms used in the reinforced and prestressed concrete industries.

Equivalent terms given in **English, French, German, Dutch, Italian, Spanish and Russian.**

Price 6os. By post 61s. 4d. In Canada and U.S.A., 9 dollars.

Obtainable from


**CONCRETE PUBLICATIONS LTD., 14 DARTMOUTH STREET,  
LONDON, S.W.1.**

# New Approach to Hot Zone Linings

**FIRED DOLOMITE BRICK  
LININGS PROVED SUCCESSFUL**

# GR'341'

**FIRED DOLOMITE  
BRICKS**



### BASIC FACTS ON A BASIC BRICK

Full scale trials in the hot zones of Portland Cement Kilns have proved the success of GR '341' Dolomite bricks. Equivalent life to magnesia based bricks has been established. These bricks quickly develop and retain a protective clinker coating. Lower thermal conductivity values give a reduction in shell temperatures, and as a result the heat losses of linings made from these new bricks are much lower than with magnesite. Greater thermal efficiency, promoted by lower conductivity, makes GR '341' a more economical proposition.

HOT FACE: 1500 C				
Lining Thickness	C COOL FACE (THEORETICAL)			
	GR '341'		MAGNESITE	
	Uncoated	Coated	Uncoated	Coated
6"	365	265	395	295
7"	355	255	380	280
9"	330	230	375	275




*Consult*  
**GENERAL REFRACTORIES LTD.**  
GENEFAX HOUSE · SHEFFIELD 10 · TEL: SHEFFIELD 31113

*We shall be pleased to provide specialist advice and supervision of the installation of linings if required.*


THE  
GENEFAX GROUP  
*for everything  
in refractories.*

260-1

300000 long tons/year



100000 long tons/year




Vertical shaft kilns and  
homogenising plants  
in modern cement works

50-300000 long tons/year

**DE ROLL**

100000 long tons/year



**L. DE ROLL SA ZURICH/SWITZERLAND**