

# CEMENT & LIME MANUFACTURE

VOL. XXXIX. No. 4

JULY, 1966

Price 1s. 6d. per Copy.  
Annual subscriptions: Inland 9s. post free.  
Overseas 11s. 6d. including postage.  
Canada and U.S.A. 2.15 dollars incl. post.

GRINDING  
MEDIA  
INFORMATION

USED AND RECOMMENDED BY


**"CRETIDS"**

Reg. No. 573298  
have been specially produced by us to meet the requirements of manufacturers for producing cement of extreme fineness. They have proved highly successful in finishing-mills without any cooling devices and, as with all our other types of grinding media, the wear-and-tear cost of "Cretoids" is infinitesimal. Free working samples are available on application.

THE WORLD'S LEADING CEMENT MAKERS

The comprehensive range of grinding media supplied by us and our unique experience in the cement industry in practically every country of the world enable us to give expert advice and to supply a type of grinding media that will provide the answer to any grinding problem.

**HELIPEDS LTD** PHONE: GLOUCESTER 51402  
GRAMS: HOLPERS, GLOUCESTER  
**PREMIER WORKS  
GLOUCESTER**



# HAVER ROTO PACKER

Complete packing and loading plants with ROTO PACKERS or our in-line packers with or without pre-compacting device including all conveying, screening, dust-collecting and loading equipment for lorries, wagons and ships.

Furthermore:  
Vibrating screens, laboratory screens with test sieves, electro-magnetic feeders, wire cloth of all metals.


More than 2500 Haver Packing Machines in operation all over the world

**HAVER & BOECKER**

4740 OELDE Westfalen · Germany

U.K. Representatives:- **CONTINENTAL ENGINEERING CO. LTD.**, London Road, Ascot, Berks.  
Tel. No: Winkfield Row 2011

# FULLER-DRACCO GLASS CLOTH FILTERS FOR THE CEMENT INDUSTRY



- \* For completely dust-free cement production both kilns and clinker coolers should have Fuller-Dracco Glass-Bag filters.
- \* Fuller-Dracco Glass-Bag filters assure virtually 100% dust collection from hot gases.
- \* Glass bags withstand continuous temperatures of up to 550°F.
- \* Reverse air and sonic cleaning prolong bag life.
- \* Bag-houses can be designed for vacuum or pressure operation and for any capacity.
- \* The largest suction type Glass Cloth Collector in the world is a Dracco installation handling 350,000 c.f.m. dry process kiln gas.

Glass cloth gas cleaning has proved the most effective means of trapping hot dust in cement plants and Fuller's extensive experience in designing and developing Glass-Bag Dust Collectors for many applications makes us best qualified to build your next collecting system.

Fuller-Dracco Glass-Bag dust collectors operate at intake temperatures of up to 550°F without pre-cooling and we can offer a variety of bag cleaning techniques to suit your operating requirements. Bag-houses are tailor-made to suit individual applications and cost requirements. The glass bags incorporate Fuller's modern fabricating techniques to ensure maximum service life.



RADNOR HOUSE · LONDON ROAD · NORBURY  
LONDON · S.W.16      ☎ POLLARDS 9571



105 rue Lafayette  
PARIS 10<sup>e</sup> ☎ 526 91.29




Sancho el Sabio 28  
SAN SEBASTIAN ☎ 18442

Licenses of FULLER CO. U.S.A.




PNEUMATIC CONVEYORS · BLENDING SYSTEMS  
DUST COLLECTORS · COOLERS · CONTROL EQUIPMENT



DOPOL kiln  
with raw mat-  
erial preheater

# POLYSIUS


POLYSIUS  
engineers  
advise you  
to choose



Long kiln for wet and dry process

## The correct kiln for every raw material

LEPOL kiln with preheater for granulated and small-size material




**POLYSIUS GMBH**  
4723 Neubeckum,  
West Germany.  
Telefon: (02525) 711  
Telegramme: Polysius Neubeckum  
Telex: 0892 893

**POLYSIUS LTD.**  
London Road,  
Ascot, Berks.  
Telephone: Winkfield Row 2011  
Cables: Polysius Ascot  
Telex: 84 102

**POLYSIUS S.A.R.L.**  
13 Rue Auber,  
Paris IXe(Frankreich), France  
Tél: Paris-Richelieu 87 49  
Télégrammes: Polysius Paris  
Telex: 21602

Matosinhos Cement Factory  
(Brazil)



all over the world ...

the cement industry  
relies on


**FIVES LILLE-CAIL**

S. A. AU CAPITAL DE 61.032.000 DE F. R. C. SEINE 54 B 2384  
7 RUE MONTALIVET PARIS 8<sup>e</sup> - ANJ. 22.01, 32.40





**REFRACTORIES** in world-wide demand...



... ferrous and non-ferrous metals,  
glass, cement—the heat-using industries  
of more than 60 countries throughout  
the world constantly rely on  
Stein refractories for  
long life service.

**STEIN** *Refractories*

*Our Technical Sales Department is available to  
you on all refractory problems.*

ANTICIPATE THE NEEDS OF INDUSTRY.

**JOHN G. STEIN & CO. LTD., BONNYBRIDGE, SCOTLAND. Tel: Banknock 255 (4 lines) 381 & 382**

## " CONCRETE SERIES " BOOKS

Detailed particulars of the books in the " Concrete Series " will be sent on request.

In the following list, the dates are the year of publication of the edition in print in Spring 1966.

Prices in Canada and U.S.A. are given in dollars in brackets.

### BOOKS FOR THE CEMENT INDUSTRY

**Cement Chemists' and Works Managers' Handbook.** WATSON and CRADDOCK. 1965. 234 pp. 30s.; by post 31s. 9d. (\$7.50.)

**How to Make Good Concrete.** WALSH. 1955. 108 pp. 8s.; by post 8s. 10d. (\$1.90.)  
**Concrete Finishes and Decoration.** CHILDE. 1963. 144 pp. 18s.; by post 19s. (\$4.50.)

### OTHER BOOKS ON CONCRETE AND ALLIED SUBJECTS

**Concrete Construction Made Easy.** TURNER and LAKEMAN. 1958. 115 pp. 6s.; by post 6s. 9d. (\$1.50.)

**Concrete Construction.** REYNOLDS. New edition in preparation.

**Concrete Formwork Designer's Handbook.** GILL. 1960. 160 pp. 15s.; by post 16s. (\$3.50.)

**Basic Reinforced Concrete Design.** REYNOLDS. 1962. Vol. I. 264 pp. Vol. II. 224 pp. Each volume (sold separately) 24s.; by post 25s. 3d. (\$6.00.)

**Engineering Mathematics (Modern Developments).** DOUGLAS with TURNER. 1964. 224pp. 63s.; by post 66s. (\$15.75.)

**Theory and Practice of Structural Design Applied to Reinforced Concrete.** ERIKSEN. 1953. 402 pp. 25s.; by post 26s. 6d. (\$5.50.)

**Explanatory Handbook on the B.S. Code of Practice for Reinforced Concrete.** SCOTT, GLANVILLE and THOMAS. 1965. 20s.; by post 21s. 6d. (\$5.00.)

**Reinforced Concrete Designer's Handbook.** REYNOLDS. 1965. 358 pp. 20s.; by post 21s. 9d. (\$5.00.)

**Examples of the Design of Reinforced Concrete Buildings.** REYNOLDS. 1959. 266 pp. 12s. 6d.; by post 13s. 10d. (\$3.00.)

**Reinforced Concrete Members subjected to Bending and Direct Force.** BENNETT. New edition in preparation.

**Formwork for Concrete Structures.** WYNN and MANNING. 1965. 388 pp. 50s.; by post 53s. (\$12.50.)

**Prestressed Concrete.** MAGNEL. 1954. 354 pp. 20s.; by post 21s. 6d. Customers in America should obtain the American edition from McGraw-Hill Book Company, Inc., New York 36.

**Guide to the B.S. Code of Practice for Prestressed Concrete.** WALLY and BATE. 1961. 104 pp. 12s. 6d.; by post 13s. 6d. (\$3.00.)

**Design and Construction of Reinforced Concrete Bridges.** LEGAT, DUNN and FAIRHURST. New edition in preparation.

**Reinforced Concrete Reservoirs and Tanks.** GRAY and MANNING. 1960. 190 pp. 12s.; by post 13s. (\$2.80.)

**Concrete Water Towers, Bunkers, Silos and other Elevated Structures.** GRAY and MANNING. 1964. 312 pp. 36s.; by post 38s. (\$9.00.)

**Reinforced Concrete Chimneys.** TAYLOR and TURNER. 1960. 80 pp. 12s.; by post 13s. (\$2.80.)

**Introduction to Concrete Work.** CHILDE. 1961. 120 pp. 4s.; by post 4s. 9d. (\$1.00.)

**Elementary Guide to Reinforced Concrete.** LAKEMAN. 1950. 95 pp. 6s.; by post 6s. 9d. (\$1.50.)

**Introduction to Prestressed Concrete.** ABELES. Vol. 1: 1964. 379 pp. 60s.; by post 62s. (\$15.00.) Vol. 2: 1966. 347 pp. 72s.; by post 74s. (\$15.00.)

**Prestressed Concrete Designer's Handbook.** ABELES and TURNER. 1962. 294 pp. 28s.; by post 29s. 6d. (\$7.00.)

**Ultimate Load Theory Applied to the Design of Reinforced and Prestressed Concrete Frames.** BAKER. 1956. 96 pp. 18s.; by post 19s. (\$4.00.)

**Continuous Beam Structures.** SHEPLEY. 1962. 128 pp. 12s.; by post 13s. (\$3.00.)

**Statically-Indeterminate Structures.** GARTNER. 1957. 128 pp. 18s.; by post 19s. (\$4.00.)

**Analysis of Structures.** SMOLIRA. 1955. 176 pp. 18s.; by post 19s. (\$4.00.)

**Nomograms for the Analysis of Frames.** RYGOL. 1957. 58 pp. text and 26 nomograms. 18s.; by post 19s. (\$4.00.)

**Arch Design Simplified.** FAIRHURST. 1954. 64 pp. 12s.; by post 13s. (\$2.80.)

**Influence Lines for Thrust and Bending Moments in the Fixed Arch.** ERIKSEN. 1955. 27 pp. 4s.; by post 4s. 8d. (\$1.00.)

**Design of Non-Planar Roofs.** TERRINGTON and TURNER. 1964. 108 pp. 15s.; by post 16s. (\$3.75.)

**Arch Ribs for Reinforced Concrete Roofs.** TERRINGTON. 1956. 28 pp. 4s.; by post 4s. 8d. (\$1.00.)

**Design of Pyramid Roofs.** TERRINGTON. 1956. 20 pp. 4s.; by post 4s. 8d. (\$1.00.)

**Design of Prismatic Structures.** ASHDOWN. 1958. 87 pp. 9s.; by post 10s. (\$2.10.)

**Design and Construction of Foundations.** MANNING. 1961. 231 pp. 24s.; by post 25s. 3d. (\$6.00.)

**Raft Foundations: The Soil-Line Method.** BAKER. 1965. 148 pp. 15s.; by post 16s. (\$3.75.)

**Deep Foundations and Sheet-piling.** LEE. 1961. 260 pp. 20s.; by post 21s. 3d. (\$5.00.)

**Reinforced Concrete Piling and Piled Structures.** WENTWORTH-SHEILDS, GRAY and EVANS. 1960. 149 pp. 18s.; by post 19s. (\$4.00.)

**Foundation Failures.** SZEGHY. 1961. 140 pp. 20s.; by post 21s. (\$5.00.)

**Concrete Products and Cast Stone.** CHILDE. 1961. 320 pp. 18s.; by post 19s. 9d. (\$4.50.)

**Moulds for Cast Stone and Concrete Products.** BURREN and GREGORY. Designs for garden ware. 1957. 96 pp. 6s.; by post 6s. 9d. (\$1.50.)

**Estimating and Costing Precast Concrete Products and Cast Stone.** FIELDER. 1963. 138 pp. 16s.; by post 17s. (\$4.00.)

**Concrete Farm Structures.** PENNINGTON. 1954. 156 pp. 12s.; by post 13s. (\$2.80.)

### CONCRETE YEAR BOOK 1966

CONCRETE PUBLICATIONS LTD., 60 BUCKINGHAM GATE, LONDON, S.W.1



# Cement plant turnkey projects by Vickers

## Reliability

To be economic the production of portland cement must be a continuous uninterrupted process. All of Vickers equipment, whether a component or a complete plant is designed and made to ensure reliable, continuous and profitable plant operation.

World demand for cement continues to rise, bringing with it the requirement for more manufacturing plant—extensions to existing works, complete installations. More and more, particularly with developing countries, the requirement is for turnkey projects, complete plants ready for operation as soon as the labour force moves in.

Vickers is uniquely placed to meet any requirement for cement-making machinery. A special Division, devoted exclusively to the Industry, is composed of experienced chemists, designers and engineers, backed by world-renowned engineering facilities.


## A Complete Service

Experienced design engineering teams are available to travel to any part of the world to discuss projects on the spot. The closest liaison is maintained with all leading cement producers, keeping Vickers abreast of world cement market trends and requirements.

## Manufacture and Design

The works are at Barrow-in-Furness, Lancashire, England, whilst other engineering and manufacturing facilities are available at Vickers works and associates in Australia, Canada, India, South Africa and Vickers licensee in Spain. Full advantage is taken of this engineering capacity, enabling kilns and grinding mills of the largest capacity and rating so far in use anywhere in the world to be offered to customers. Up to the present day Barrow Works alone has made and delivered over a hundred and twenty kilns and a hundred and fifty grinding mills.

A specialist staff of chemists and engineers is concerned with the development and application of new equipment and techniques, many of which have been initiated by Vickers.



## Construction, Operation and Labour

Construction and commissioning on site is carried out under the surveillance of Vickers engineers, and local labour employed during this period can be trained to operate the factory.

## World-Wide Experience and Service

Vickers have been producing specialised machinery for the cement and allied industries for over forty-five years. Equipment has been supplied to leading manufacturers in many parts of the world and an extensive service network has been built up. Plants operating in Australia, Belgium, Canada, Ceylon, Hong Kong, India, Mexico, New Zealand, Rumania, South Africa, Zambia, have all provided experience in meeting varying conditions of operation.

## Further information

For further information please contact the Cement Machinery Division (Sales), Vickers House, Millbank Tower, Millbank, London SW1. Telephone: TATE Gallery 7777. Cables: Vickers London.

Technical queries to

**VICKERS**  
LIMITED

Cement Machinery Division  
Engineering Group  
Vickers-Armstrongs  
Barrow Engineering Works  
Barrow-in-Furness Lancs England  
Tel: Barrow 3366. Ext 129



FOR BALL AND  
TUBE MILLS

IN HIGH  
CARBON  
OR CHROME  
STEEL

from

1" - 6" Diameter



DESIGNED TO GRIND FASTER.  
LAST LONGER. NEVER BREAK.  
NEVER LOSE SHAPE.  
ALL HAND FORGED.


ALSO FINE HAND  
FORGED TOOLS FOR  
QUARRY AND MINE.



**F. J.  
Brindley  
& Sons (SHEFFIELD)  
Ltd.**

**CENTRAL HAMMER WORKS, ACRES HILL LANE, POOLE ROAD,  
DARNALL, SHEFFIELD 9.**

Tel: Sheffield 49663/4 Grams: 49663/4



## ROTARY DISC FEEDER

British Patent No. 769603

for controlled, infinitely-variable volumetric-measurements to close limits of many kinds of crushed and ground materials such as cement raw material, limestone, gypsum, coal, etc.


- Operates safely.
- Handles highly hygroscopic and sticky materials.
- Offers immediate response to automatic regulation.
- Is airtight and therefore suitable for use in grinding installations operating under vacuum or pressure conditions.

**DELO (ENGINEERS) LTD.**

138 Borough High Street  
LONDON, S.E.1. Tel: Hop 0085/6  
Telegrams: OLED, LONDON, S.E.1


Also Drying Furnaces, Disc  
Granulators, Pneumatic Conveyors

# MILLS FOR THE CEMENT INDUSTRY



1200 H.P. THREE CHAMBER GRINDING MILL RUNNING IN SELF-ALIGNING WATER COOLED OIL CASCADE LUBRICATED MAIN TRUNNION BEARINGS, PATENT FABRICATED STEEL ENDS AND SHELL LINED WITH MARTENSITIC NI-HARD LINERS.

PATENT 'H' TYPE MARTENSITIC NI-HARD SHELL LINERS FOR BALL, ROD AND TUBE MILLS. BRINELL HARDNESS UP TO 650. STANDARD PATTERNS AVAILABLE. OTHER TYPES TO CUSTOMERS OWN DESIGNS TO SUIT EXISTING MILLS CAN ALSO BE SUPPLIED.



*Other Products include:—*

- Rotary Kilns, Coolers and Dryers.
- Apron, Table, and Scraper Feeders.
- Slurry Pumps and Slurry Mixers.



**ERNEST NEWELL & COMPANY LIMITED  
MISTERTON VIA DONCASTER, ENGLAND**

*Cables:* Newells, Misterton, Notts, England      *Telephone:* Misterton 224-225

*MEMBER OF THE HADFIELDS GROUP OF COMPANIES*

*A name as familiar  
as cement itself*



You are invited to take advantage of our world-wide experience by consulting us regarding any problem connected with the manufacture of cement.

**F.L. SMITH & CO. LTD.**

**105 PICCADILLY,**

**LONDON, W.1**

Telephone: Grosvenor 4100 Telegrams and cables: Folasmith London

---

# CEMENT AND LIME MANUFACTURE

PUBLISHED ALTERNATE MONTHS.

PRICE 1s. 6d. A COPY

ANNUAL SUBSCRIPTION 9s. POST FREE  
\$1.75 IN CANADA AND U.S.A

PUBLISHED BY  
CONCRETE PUBLICATIONS LIMITED  
60 BUCKINGHAM GATE, LONDON, S.W.1

TELEPHONE: VICTORIA 0705/6.  
TELEGRAPHIC ADDRESS:  
CONCRETIUS, PARL, LONDON.

PUBLISHERS OF  
"CONCRETE & CONSTRUCTIONAL ENGINEERING"  
"CONCRETE BUILDING & CONCRETE PRODUCTS"  
"CEMENT & LIME MANUFACTURE"  
"THE CONCRETE YEAR BOOK"  
"CONCRETE SERIES": BOOKS.

VOLUME XXXIX NUMBER 4

JULY, 1966

## The New Weardale Cement Works.

THE new works (*Fig. 1*) which has been established by The Associated Portland Cement Manufacturers Ltd., at Eastgate-in-Weardale, County Durham, was formally opened last month. The works is situated on the north bank of the River Wear (*Fig. 2*) some 20 miles west of Durham City. The quarry from which the raw materials are obtained is about  $\frac{1}{2}$  mile south of the river and at a level about 450 ft. higher than the works; it is seen on the hill in the background of *Fig. 1*. Connection between the works and quarry is by means of a new road negotiating the southern escarpment of the valley. Materials are transferred from the quarry to the works by means of a totally-enclosed conveying system. Construction of the works, which has an annual productive capacity of 600,000 tons, commenced in December 1963 and the first kiln was lit in June 1965; the second kiln was lit in October last.

Because of the low moisture content of the raw materials, the semi-dry process has been adopted. A flow-chart of the complete process will be given in the continuation of this article in the next issue of this journal.





Fig. 1.—General View of Works and Quarry.

C

ห้องสมุด กรมวิทยาศาสตร์  
31 ส.ค. 2509




**Fig. 2.**  
**Plan of Environs**  
**of the Works and**  
**Quarry.**

A general plan and elevation of the structures at the quarry are shown in *Fig. 3.*


**Preparation of Raw Meal**

**EXCAVATING.**—Limestone and shale are excavated from different parts of the same quarry. There are deposits of high and low carbonate limestone, and three grades of stone are excavated, crushed and stored to facilitate correct blending in subsequent processes. At present the top soil is being transported to spoil heaps.



**Fig. 3.—Plan and Elevation of Structures at Quarry.**


Fig. 4.  
Discharging  
Limestone  
into  
Crusher.



After drilling and blasting, the limestone and shale are excavated by two 7I-RB  $3\frac{1}{2}$ -cu. yd. electrically-operated excavators and one 54-RB  $2\frac{1}{2}$ -cu. yd. diesel excavator. These machines load the material into 18-cu. yd. Foden dumpers. A 24-RB diesel excavator fitted with drop-ball equipment is used for breaking up oversized boulders. The material is transported in the dumpers to the crushing plant where it is discharged into an intake hopper, which is at the same level as the quarry floor, and thence onto screening rolls so that any material of small size, which is usually low in carbonate, is separated from the higher carbonate larger stones. This screening operation also relieves the crushers of stone requiring no reduction, and the screenings are conveyed to the low-carbonate stone in the storage compound. Crushing of the larger material is effected by a double slugger roll crusher having two rolls 62 in. in diameter and 49 in. wide, running at 60 r.p.m. Each is driven by a 100-h.p. motor giving a peripheral speed of about 1,000 ft. per minute. *Fig. 4* shows limestone being tipped from a dumper onto a drop-bar feeder and passing thence to the roll crusher in the foreground. The operator is stationed in a cabin overlooking the plant for the successive stages of feeding, screening and crushing.

**STORAGE OF CRUSHED STONE.**—The crushed and screened stone is delivered from an elevated conveyor into a covered compound of 6,000 tons capacity


**Fig. 5.**  
**Conveyor**  
**to**  
**Raw-meal**  
**Mills.**



equipped with an overhead electric travelling grab-crane to facilitate distribution of stone. A subway below the floor of the compound is provided for the recovery of the stone as required for the subsequent grinding process. Apron-feeders with electronic weigh-scales are provided in the subway to proportion the feed of each grade of stone in predetermined ratios. The feeders discharge onto a belt-conveyor (*Fig. 5*) leading to the raw mill building which, like the store, is just below the level of the quarry floor.

**GRINDING RAW MEAL.**—The high-carbonate limestone as excavated contains about 90 per cent. of calcium carbonate and less than 2 per cent. of moisture.

**Fig. 6.**  
**“Aerofall”**  
**Mill.**








Fig. 7.—“Double Rotator” Mills.

It is blended with low-carbonate stone which usually occurs in smaller pieces and has a greater moisture content. The moisture content of the shale may be as high as 20 per cent. The moisture content of the combined materials is often in excess of 5 per cent., but is dependent on the weather. A combined drying and grinding plant is therefore provided, and comprises a 23-ft. “Aerofall” mill (*Fig. 6*) driven by an 1,800-h.p. English Electric motor, and two “Double-Rotator” mills driven by 1,200-h.p. G.E.C. motors. The “Aerofall” mill is charged with the coarsely-crushed material for the grinding action, but some steel media are also added for this purpose. The mill is swept by a stream of hot air from an oil-fired heater which dries the material and conveys the ground material to four-stage classifying equipment. Oversized material discharged by the classifiers is split so that part of it is returned to the “Aerofall” mill for further grinding and the remainder to the re-grinding mills. The latter (*Fig. 7*) are arranged for closed-circuit grinding with two turbo-separators of 4.5 m. diameter, and driven by the 100-h.p. motors. A feature of the “Aerofall” mill, which is the third installed by the A.P.C.M. Ltd., for the simultaneous grinding and drying of the hard mountain limestone of the north country, is the feed-regulation system. By a combination of sonic and weigh-feed controls, the supply to the mill of a sufficient quantity of coarse limestone to act as a grinding charge is ensured.

The moisture liberated from the raw limestone and shale is extracted from the

**Fig. 8.**  
**Interior of**  
**Conveyor**  
**Tunnel from**  
**Quarry**  
**to**  
**Works.**



grinding circuit by bleeding off some of the circulating air through an Andrews fabric filter plant having a capacity of 50,000 cu. ft. per minute. The oil-fired air heater is automatically controlled to maintain a suitable differential between the temperature and dew-point of the discharged gases.


CONVEYING.—The raw meal is transferred from the raw grinding system to the main works by a 42-in. trough-conveyor (*Fig. 8*) which follows, so far as possible, the general downward slope of the side of the valley, the inclination of the belt being up to 15 deg., that is a slope of about 1 in.  $3\frac{3}{4}$ . A low belt-speed and the provision of a sealed aluminium cover obviate air entrainment on the fluffy surface of the fine dried powder materials. Near the main works the conveyor crosses a road, a railway and the river, the conveyor gantry in this section being supported on tee-headed precast concrete columns (*Fig. 9*).

#### THE WORKS

A general view of the works is illustrated in *Fig. 1*. In the foreground of *Fig. 9* is seen the end of the covered raw-meal conveyor from the quarry. A plan of the works together with other diagrammatic views is shown in *Fig. 10*. The principal operations at the works include the further treatment of the raw meal, the burning, cooling and grinding processes, and the batching and despatch of the finished cement.

#### Treatment of Raw Meal

BLENDING AND STORAGE.—The raw meal is discharged from the covered conveyor into the boot of a bucket-elevator, 145-ft. centres, which in turn discharges



**Fig. 9.**  
**Exterior of**  
**Conveyor**  
**from**  
**Quarry to Works.**

into one of three reinforced concrete blending silos (*Fig. 9*) the capacity of each being about 900 tons. The overflow from the first silo passes into the other two. Blending is effected by a Fuller continuous quadrant blending plant which utilises aeration pads covering the floors of the cylindrical silos. The pads in each silo are grouped into four quadrants and operated through a time-controlled selection valve. Compressed air is directed mainly into one of the four quadrants resulting in a high degree of aeration in the meal above it compared with the meal above the other three quadrants. The difference in the degrees of aeration and the corresponding alteration in density causes convection currents within the contained meal with consequent blending which eradicates variations in the carbonate content. The meal is transferred from the three blending silos by means of bottom discharge into any of five storage silos, each of which have a capacity of about 1,450-tons.

**NODULISING.**—From the base of the storage silos the prepared meal is transferred at a controlled rate, by means of pneumatic extraction conveyors screw-conveyors and elevators to the granulators or nodulisers, which are 13 ft 1 in. in diameter and two of which are installed for each of the two kilns. The nodulisers are inclined rotating pans in which the meal is mixed with water in automatically proportioned amounts of from 12 to 14 per cent. The rotation of








Fig. 10.—Plan and Elevations



the Weardale Cement Works.


Fig. 11.  
Side  
View  
of  
Nodulisers.



the pan causes the moistened meal to form into pellets or nodules. Two views of the nodulisers are shown in *Figs. 11* and *12*.

Each noduliser is driven by a 50-h.p. motor (*Fig. 12*). In the pan, a traversing scraping arm is provided to prevent the building up of damp powder on the working

Fig. 12.  
Rear  
View  
of  
Noduliser.



# AT THE HOT HEART OF WEARDALE

Brief note to Top Management :  
Blair characteristics : skill—competitive-  
ness—highly mobile labour force—ad-  
vanced mechanical handling technique  
—experience in all types of refractory  
installations large and small — compre-  
hensive service in North and North East.


S. G. Blair & Co. Ltd., Lesley House, Broadway,  
Bexleyheath, Kent. Bexleyheath 5696/7691.  
Grams : Refcon, Dartford.

The refractory installation by S. G. Blair & Co. Ltd. the specialist constructors in this field



# we sell the best dust valves you can buy!

As a major manufacturer of world renowned dust collection equipment, we know you can't get high performance from a dust collector without getting high performance from the dust valves connected to the hoppers so we produce our own high performance dust valves—and use them ourselves—and sell them to others. If you need the best dust valves you can buy to get the highest efficiency out of your dust collection system, settle for OURS.



**OURS**—The type R-1 motorized tipping valve with features not available with gravity-operated tipping valves: positive time cycle motorized operation; gravity free-flow flushing features; gravity return assuring positive valve seating without pressure closure that guarantees non-jamming. It operates in positive pressure installations up to 5in. W.G. (with special valves available rated for 30in. W.G.), and negative pressure installations up to 40in. W.G. And like all the dust valves we sell, the R-1 continues to operate efficiently at temperatures up to 750°F.

**OURS**—The gravity operated tipping valve—ideal for sealing dust collector hoppers operating under negative pressure (0-6 in. W.G.) when handling dry free-flowing material. The air lock principle of this valve is achieved by the use of two flap closures that operate alternately, permitting the collected dust to pass out of the hopper without pressure loss. The rugged cast iron construction and the unique hinged design of the valve plate assures a perfect seal.

**OURS**—The floating seal dust valve, for operation when handling abrasive materials, particularly at high temperature. The "revolving door" principle is a familiar one for dust valves and dust feed regulators. But it took Western Precipitation to transform a "familiar" item into a "special" one, by using a carefully machined cast iron "Floating Seal" of controlled hardness. A perfect metal-to-metal seal is continuously maintained, for, as the cast iron seal slowly wears, its weight keeps it in intimate contact with the rotor.

We sell the best dust valves you can buy. Not the cheapest . . . but the best value for money and exactly the right unit for your application, in six, eight and ten inch sizes. That's a big claim and one we are prepared to back all the way. Ask us to prove it, but first, may we send you a copy of our technical bulletin on Valves?

Ask your Secretary to write for a copy.



**WESTERN PRECIPITATION**

division of Joy Trading Corporation.


7 HARLEY STREET, LONDON, W.1.

Telephone: Langham 7711

Manufacturers of electrical precipitators · mechanical dust collectors · gas scrubbers and high temperature filters



**Fig. 13.**  
**Control**  
**Panel**  
**for**  
**Blending**  
**and Distribution**  
**of**  
**Raw**  
**Meal.**



surface. The maximum capacity of each noduliser is to convert into nodules 31 to 37 tons of raw meal per hour. Feed regulation is by means of Richardson weighers coupled to Honeywell pneumatic controllers which are in turn linked by ratio-controllers to Fischer & Porter water-flow controls. The blending, storage and conveying of the raw meal to the nodulisers is controlled from a console (*Fig. 13*) at which the successive processes are depicted diagrammatically.

### **The Kilns**

Two kilns are installed and each is combined with a "Lepol" preheating grate and a "Recupol" cooler. The kiln house (*Fig. 14*) is of precast concrete frame construction with walls of concrete blocks.

The accompanying illustrations (*Figs. 14 to 17*) show various views of the kiln plant. The hood of the "Lepol" grate is shown in *Fig. 15*, and a general view of one half of the kiln house is seen in *Fig. 16*. The firing end of the kiln with the control panel and closed-circuit television for viewing the raw-meal nodulising is shown in *Fig. 16*. A clearer view of the firing end is seen in *Fig. 17*.

**GRATE PREHEATER.**—Nodules from the nodulisers pass onto the preheating grate through which pass the hot gases from the kiln. In so doing, the nodules are dried and heated to the calcining temperature before entering the kiln. Each




Fig. 14.—The Kiln House.

grate is 12 ft. 10 in. wide, the distance between the centres of the end-shafts being 95 ft. Each grate is driven by a  $25\frac{5}{8}$ -h.p. variable-speed motor through quadruple reduction gears. The gases pass twice through the grate and the bed of nodules thereon. After the first passage, the gases from the preheating end of the grate are subjected to cyclonic cleaning prior to being returned for the second pass for drying the incoming nodules from the noduliser.

**THE KILNS.**—Each of the two kilns, which are inclined at a slope of  $3\frac{1}{2}$  in 100 has a central cylindrical part 155 ft. long and of 12-ft. 10-in. internal diameter. The overall length, including the coned inlet and outlet ends, is 196 ft. 6 in. Each kiln is supported on three tyres having an outside diameter of 16 ft. 1 in. and face width of 2 ft. 1 in. The shells were delivered with the tyres mounted on the appropriate sections. Each tyre is carried on twin rollers having bearings of 20 in. diameter and is supported on a reinforced concrete pier. Hydraulic thrust gear is provided on two of the tyres which impart a small longitudinal oscillating movement.

The shells of the kilns are of mild steel plate [B.S. 1501 (151 Grade B).] All shop and site joints are welded. The thickness of the shell is  $1\frac{1}{8}$  in. at the sintering zone and increases to  $1\frac{3}{8}$  in. under the tyres, and is  $1\frac{1}{4}$  in. at the girth-gear. The thick-



### **WADDINGTON-BENOTO BORED PILES FOR A.P.C.M. NEW WORKS AT WEARDALE, CO. DURHAM**

Benoto EDF.55 Rig boring foundation piles for Granulator, Lepol Grate, Kiln Piers and Cooler Housings in the second phase of the Weardale development. The structures in the background comprising similar units in the first phase were also founded on Waddington-Benoto piles.

**A.WADDINGTON & SON LTD**

Civil Engineering Contractors, North Circular Road, London, N.W.10.

Choose an  
**AEROFALL MILL**  
 and  
**SAVE ON CAPITAL AND  
 OPERATING COSTS**  
**OF CRUSHING AND GRINDING**

— study the economics

**Capital cost**

Equipment costs can show a reduction of up to 20%.  
 Installation costs can show a reduction of up to 50%.

**Operating costs**

**LABOUR** Only one operator is needed to supervise a plant with as many as six mills.

**MAINTENANCE** Virtually limited to lubrication and planned replacement of liners.

**POWER** Reductions in power consumption.

All these savings are inherent in the design and operation of the Aerofall mill system. This comprises a complete crushing, grinding and classifying plant which accepts run-of-mine or primary crusher product as feed, and in a single operation reduces it to a ground product ready for the process plant.

*Associated Portland Cement Manufacturers Limited now use Aerofall mills at three works in the U.K. for the manufacture of cement raw meal—details are listed below.*

<b>ORE</b>	Hard limestone plus shale	<b>POTENTIAL CAPACITY</b>	In excess of 4,000 tons per day per mill
<b>MOISTURE CONTENT</b>	Average 5%	<b>GRIND</b>	35% minus 170 mesh
<b>MILL</b>	One 23 ft. dia. Aerofall mill at each of three works	<b>MEDIA STEEL WEAR</b>	0.17 lb./ton
<b>LOCATION</b>	Cauldon, Staffordshire, England. Dunbar, East Lothian, Scotland. Weardale, Co. Durham, England.	<b>POWER (Total primary grinding including auxiliaries)</b>	16.0 kWh per ton
<b>FEED</b>	Minus 9 in.		

*Write for brochure entitled 'Aerofall Mills' describing the range and applications of this versatile system.*

**ASHMORES**  
**PROCESS EQUIPMENT DIVISION**

Ashmore, Benson, Pease & Company Limited,  
 South Works, Stockton-on-Tees, England.  
 Telephone: Stockton 65171 Telex: 58570

MEMBER OF THE DAVY-ASHMORE GROUP

DAVY/1002




Fig. 15.—Hood of "Lepol" Grate.

ness of the refractory lining is 7 in. Each kiln is driven by a 180/52-h.p. 960/280-r.p.m. variable-speed electric motor which gives a rotational speed to the kiln of 1.1 to 0.37 r.p.m. The drive is through a straight spur-gear with a tooth face  $17\frac{3}{4}$  in. wide. To prevent the risk of distortion of the shell in the event of a power failure, an auxiliary diesel drive is fitted to each kiln. Under these emergency conditions, the kiln would rotate at 2.5 revolutions per hour while contraction due to cooling was taking place.

**GRATE COOLER.**—The clinker falls from each kiln into a "Recupol" horizontal grate cooler. The width of the grate is 6 ft. 9 in. and the length between the centres of the shaft is 61 ft. 2 in. As the bed of hot clinker moves forward along the surface of the grate, air at atmospheric temperature is blown under and through the bed, and thence passes in controllable proportions to the kiln as secondary air for combustion. Air is also distributed to the coal mill as drying and primary air. Air surplus to these requirements is exhausted to atmosphere through electrostatic precipitators. The grit and dust collected in the precipitator is passed to the conveying system into which each cooler discharges. The main drive of the cooler is a 25/8-h.p. 1440/480-r.p.m. electric motor interchangeable with that of the preheater grate.

**FIRING PLANT.**—The kilns are fired by pulverised coal. About 2,000 tons of

Fig. 16.  
Control  
Panel  
and  
Firing  
End  
of  
Kiln.



coal, which is delivered by road, are consumed each week. Until required, the coal is retained in a covered store, of some 2,200 tons capacity, and is then trans-





Fig. 17.— Firing End of Kiln.



**Consett**  
**ROTACON Bricks**

**THE Hot Zone Lining  
 for ROTARY CEMENT KILNS !**

Specially developed for Portland Cement Kilns by Consett Iron Co. Ltd. ROTACON possesses all the important characteristics necessary in a basic liner brick. ROTACON bricks build up a sound coating rapidly and withstand kiln shut-downs without spalling. They are not subject to chemical attack at high operating temperatures and will not disintegrate from thermal contraction. *The ideal basic lining for the production of Portland Cement.*

**ROTACON BRICKS SAVE MONEY  
 BY INCREASED KILN AVAILABILITY**




**CONSETT IRON CO. LTD.**  
**CONSETT · COUNTY DURHAM**

Telephone: Consett 3411      Telex: 53172



## Simple in construction, unequalled in performance



### **MIAG double - shaft hammer crusher "TITAN"**

crushes in one single operation up to 800 t/h of limestone as well as minerals of similar kind to a grain size smaller than 25 mm


Insensible to tramp irons contained in the feeding material

Favourable specific power requirement

Perfect operation safety

Good possibilities of maintenance and observation for all building sections

Shortest installation and disassembly period of the wear parts



**MIAG**

BRAUNSCHWEIG / Germany

Agency for Great Britain  
**INDUSTRIAL EQUIPMENT CO.**  
(N.I.) Ltd.  
58, Howard St. Belfast



ferred to the coal mills (Fig. 19) for pulverisation. It is blown into the kilns by the firing fans. A "P.H.I./M.P.S. 100" coal-drying and grinding plant, having an output of 7 tons per hour, is provided. The mill, with its separator, is pressurised by the adjacent firing fan which has a capacity of 9,500 cu. ft. per minute at 300 deg. F. and which is driven by a 125-h.p. motor. Each coal mill is driven by a 100-h.p. motor.

*To be continued.*

---

### **Investigations of the System $C_3A-N_8CA_3$ in System C-A-N.**

A PAPER entitled "Data on the binary system  $3CaO \cdot Al_2O_3 - Na_2O \cdot 8CaO \cdot 3Al_2O_3$  within the system  $CaO - Al_2O_3 - Na_2O$ ." by K. E. Fletcher, H. G. Midgley and A. E. Moore, was published in the "Magazine of Concrete Research," December, 1965. A summary of the contents of the paper is as follows.

Conwicke and Day have shown that partial solid solution occurs in the system  $C_3A - NC_8A_3$  at temperatures below the liquidus. Their results indicate a marked similarity between the X-ray powder diffraction data for a preparation containing more than 3.0 per cent  $Na_2O$  and the data given by Moore for a new phase in Portland cements. The investigation now described was almost complete when Conwicke and Day's paper was published. It generally confirms their results but gives more information on the solid solution.

The author's conclusions read as follows.

The solid solution of  $Na_2O$  in  $C_3A$  has been investigated. In preparations made at 1,350 deg. C., it was confirmed that  $Na_2O$  replaced  $CaO$ . The sodium calcium aluminate formed at the limit of solid solution has the composition of 91.0 mol per cent.  $C_3A$ , 9.0 mol per cent.  $N_3A$ . This compound has been indexed on an orthorhombic system with cell dimensions  $a = 15.314$ ,  $b = 15.394$ ,  $c = 15.137$  Å. For preparations containing up to 2 per cent.  $Na_2O$  there is a slight contraction of the lattice dimension of the cubic  $C_3A$ ; between 2 per cent and 4 per cent.  $Na_2O$  a mixture of cubic and orthorhombic forms is found and at 4 per cent  $Na_2O$  a single orthorhombic form occurs. Further solid solution causes a slight modification of the orthorhombic lattice dimension until the limit of solid solution is reached with 6 per cent.  $Na_2O$ . The X-ray diffraction pattern obtained when the phase contains between 4 per cent. and 6 per cent.  $Na_2O$  agrees well with that given by Moore for a new phase in Portland cements which is concluded to be a new  $C_3A$  phase in which additional oxides,  $Na_2O$ ,  $K_2O$ ,  $MgO$  or even  $Fe_2O_3$  or traces of  $TiO_2$ , had lowered the symmetry from cubic to orthorhombic. It cannot, however, be concluded that the new phase is stabilised solely by  $Na_2O$  since the analyses of Moore appear to preclude the possibility of even 4 per cent.  $Na_2O$  being retained in the new phase in some of the cements investigated.

---

## The Associated Portland Cement Manufacturers Ltd.

THE following information is abstracted from the Chairman's Statement made at the Annual General Meeting of The Associated Portland Cement Manufacturers Ltd., held in London last month.

WITH the second kiln at the Westbury works<sup>1</sup> and the new works at Weardale<sup>2</sup> commencing operation by October last, the year 1966 was started with nearly 1,000,000 tons of extra productive capacity. By the end of 1966, a further 1,250,000 tons will be available from the works at Dunbar, Dunstable, Ipswich<sup>3</sup> and Plymouth, and the installation of a new works at Cookstown, Northern Ireland, will be in hand.

Once again, associated companies overseas experienced record sales.

Associated Portland Cement Manufacturers (Australia) Ltd., which company has three works in New South Wales and one works in Victoria, achieved record production and sales. A new kiln of 300,000-tons annual capacity is being installed at Maldon works in New South Wales, and planning of further expansion in Victoria is proceeding.

Ocean Cement & Supplies Ltd., British Columbia, had a successful year, and a new kiln of 300,000-tons annual productive capacity is being installed at the works on Vancouver Island.

Keenly competitive conditions were experienced in Malaya, and productive capacity is in excess of demand, but Malayan Cement Ltd., sold its entire production.

Mexico experienced a slight fall in sales. The new 300,000-ton kiln at the Atotonilco works will be in production in the near future.

The Golden Bay Cement Co., Ltd., and Waitomo Portland Cement Ltd., in New Zealand, again produced record results, and both the ships carrying bulk-cement were fully employed. Another kiln to produce 160,000 tons annually is being brought into production at the Tarakohe works.

The works of White's South African Portland Cement Co., Ltd., operated to capacity and sales reached a new high level. Expansion is in progress, a new 300,000-ton kiln being in the course of installation at the Lichtenburg works. The East African Portland Cement Co., Ltd., and the British Standard Portland Cement Co., Ltd., recorded gratifying results, and with the stable political situation in Kenya, trade has been good. A new 300,000-ton kiln is being installed in the Mombasa works of the British Standard Co., and an additional bulk-cement ship has been ordered to deal with the increasing export trade of that Company. The new 130,000-ton works<sup>4</sup> in Tanzania is nearing completion. In Rhodesia, The Salisbury Portland Cement Co., Ltd., maintained its position. Since the Unilateral Declaration of Independence, the Company's trade, which includes

---

1.—See this journal for March and May 1966, and page 76 of the current number.

2.—See page 59 of the current number.

3.—See page 76 of the current number.

4.—See page 75 of the current number.



## MAXIMUM PROFITABILITY— TROUBLE-FREE OPERATION

We are specialists in the design and construction of high-efficiency Lime Hydrating Plants. Sturtevant Plants continuously produce hydrate of guaranteed quality, are fully automatic in operation and have full dust suppression. Only two operatives are required, including bagging-off. Sturtevant Plants have in-built safeguards against breakdown, and accurately classify hydrate by air separators. They are in use all over the world.

*Write or telephone for full details.*

# STURTEVANT


**STURTEVANT ENGINEERING CO. LTD.**  
ENGINEERED PROJECTS DIVISION

Sturtevant House, Highgate Hill, London, N.19

Telephone: ARChway 0233 Telegrams: Sturtevant, London, Telex



*Designers and manufacturers of plant for Drying, Pneumatic Conveying, Gas Cleaning, Lime Hydrating, Vacuum Cleaning, Batching and Blending, Formulation of Insecticides and Material Classification.*



**Complete Plants  
for manufacturing**

**ASBESTOS CEMENT  
PIPES and SHEETS..**

PRESSURE PIPES

DOWN PIPES

CORRUGATED

AND FLAT

SHEETS



**ASBESTOS CEMENT ENGINEERING CO.**  
 AEULESTRASSE 772, VADUZ - LIECHTENSTEIN  
 Switzerland . P.O. Box 34,722.

... Production, delivery,  
 service and (if required)  
 finance for complete  
 installations, large or small.

Installations complètes pour la  
 fabrication des tuyaux haute et  
 basse pression et des plaques  
 planes et ondulées en amiant-  
 ciment.

Production, livraison, service et  
 (si désiré) financement des  
 installations complètes grandes  
 ou petites.

**AGENTS REQUIRED**

**FOR ALL BAGS  
 AND SACKS · ANY  
 MATERIAL · ANY SIZE**

TPE portable stitching machines

TPE static stitching machines

TPE high-speed heat sealers for  
plastic bags

TPE automatic sack lifters

**FREE DEMONSTRATIONS**  
 of these and TPE's many other  
 profit-earners

*Write today for details*

**THE THAMES PACKAGING  
 EQUIPMENT CO.**

Dept. CLM, 28 City Rd., London, E.C.1,  
 England. Tel: MONarch 7387/8.  
 Grams: Pakitup London E.C.1.

(Props: The Thames Sack & Bag Co. Ltd.)

**MISCELLANEOUS ADVERTISEMENTS**

**SCALE OF CHARGES  
 FOR  
 MISCELLANEOUS  
 ADVERTISEMENTS**

5s. per line (average seven  
 words per line).

For use of Box Number, allow  
 two lines.

Minimum £1 for not more  
 than four lines.

**DISPLAYED ADVERTISEMENTS**

45s. per single column inch.

Advertisements must reach this journal at 60  
 Buckingham Gate, London, S.W.1. by the 1st  
 of the month of publication.

**FOR SALE**

OVER 30,000 "SPEEDY" MOISTURE TESTERS  
 now in use, for accurately measuring moisture content  
 in cement, lime, gravel, etc. Non-electric. Easily operated  
 by unskilled workmen. Full details of "SPEEDY" from  
 THOMAS ASHWORTH & CO. LTD., CG7, Sycamore  
 Avenue, Burnley, Lancs.

**PUBLICATIONS**

**THE MARKETING OF LIME**  
 by K. K. Roy

An authoritative reference work detailing  
 clearly proven marketing techniques adopted  
 by lime manufacturers all over  
 the world. Price 15s.

**INTERTRADE PUBLICATIONS**  
 (INDIA) PRIVATE LIMITED  
 55 Gariahat Road, Calcutta 19, India.

**"CONCRETE SERIES"**  
**BOOKS ON CONCRETE**  
 AND ALLIED SUBJECTS

see page viii.


**CONCRETE PUBLICATIONS, Ltd.**  
 60 Buckingham Gate, London, S.W.1

IT WILL PAY YOU TO MAKE  
 YOUR REQUIREMENTS KNOWN  
 THROUGH THE CLASSIFIED  
 ADVERTISEMENT COLUMNS OF  
**CEMENT AND LIME  
 MANUFACTURE**

exports to Zambia, has increased. Further measures have been taken to rationalise the industry in Rhodesia. Good results were achieved by the Nigerian subsidiary. The full output of the works of the West African Portland Cement Co., Ltd., was sold, and capacity is being raised to 500,000 tons a year. Notwithstanding disturbed political conditions in the Western Region, where the works is located, the Company surpassed all previous records. Politics adversely affected trade in Ghana. The clinker grinding plant, which is being managed for the Government in that country, operated intermittently.

Asland Asociada, S.A. has taken over four existing works in Spain. The new kiln at Cordoba has been brought into operation, and measures are in hand to increase output at the Moncada Works, near Barcelona. It is also planned to build a large new works in the Barcelona area.

### New Cement Works.



**Tanzania.**—The accompanying illustration shows part of the crushing plant at the cement works of the Tanganyika Portland Cement Co., Ltd., at Wazo Hill, near Dar-es-Salaam, Tanzania. The Commonwealth Development Finance Co., Ltd. (CDFC) contributed some £440,000 towards the establishment of this works, which will have an annual productive capacity of 130,000 tons, and in which The Associated Portland Cement Manufacturers Ltd., have an interest.

*Continued on page 76*

### New Cement Works

*Continued from page 75.*



**Claydon, Suffolk.**—The illustration above shows the erection in progress of the steelwork for a coal hopper for the new 500-ft. kiln at the A.P.C.M. works at Claydon, near Ipswich. Main civil engineering contractors: Mitchell Construction Co., Ltd. Suppliers of 60-ft. jib crane: Pointer Contracting Ltd.

**Westbury, Wiltshire.**—A description of the recently-opened extension to the A.P.C.M. works at Westbury, a general view of which is shown below, was given in the number of this journal for March and May 1966.




# GR 341

## Fired Dolomite

### for Rotary Cement Kiln Lining

#### 7 IMPORTANT FEATURES OF GR 341 FIRED DOLOMITE BRICKS

- Chemically resistant to Portland cement.
- Have a natural tendency to pick up and maintain a protective clinker coating in the clinkering zone.
- Resist clinker ring formation in the cooler sections of the kiln.
- Excellent volume stability.
- Low thermal conductivity.
- High resistance to thermal shock.
- Resistant to hydration.



Full particulars from:

## GENERAL REFRACTORIES LTD

GENEFAX HOUSE · SHEFFIELD 10 · TEL: SHEFFIELD 31113

# PLANET HUNWICK ALITE

a complete range of lining blocks for cement & lime kilns

send for full details of these grades

HUNWICK magnesite-chrome

ALITE high alumina

PLANET abrasion resistant



**PRICE-PEARSON (SALES) LIMITED** STOURBRIDGE WORCS.



A member of the Price-Pearson Refractories Group