

# CEMENT & LIME MANUFACTURE

VOL. XXXIX. No. 5

SEPTEMBER, 1966

Price 1s. 6d. per Copy.  
Annual subscriptions: Inland 9s. post free.  
Overseas 11s. 6d. including postage.  
Canada and U.S.A. 2.15 dollars incl. post.

GRINDING  
MEDIA  
INFORMATION

USED AND RECOMMENDED BY

**"CRETIDS"**

Reg. No. 573298  
have been specially produced by us to meet the requirements of manufacturers for producing cement of extreme fineness. They have proved highly successful in finishing-mills without any cooling devices and, as with all our other types of grinding media, the wear-and-tear cost of "Cretoids" is infinitesimal. Free working samples are available on application.

THE WORLD'S LEADING CEMENT MAKERS

The comprehensive range of grinding media supplied by us and our unique experience in the cement industry in practically every country of the world enable us to give expert advice and to supply a type of grinding media that will provide the answer to any grinding problem.


**HELIPERS LTD** PHONE: GLOUCESTER 51402  
GRAMS: HOLPEBS, GLOUCESTER  
**PREMIER WORKS**  
**GLOUCESTER**





# STEIN *Refractories*

In Spain: building a cement kiln  
with Stein Refractories



## FOR CEMENT KILNS

... offer maximum efficiency through high resistance to clinker attack, quick clinker coating, and high retention of coating during kiln shut-downs.

STEIN MAG CKL · MAG CK · STEIN 70 · STEIN 63  
NETTLE DA and THISTLE  
are proved refractories for lining the various  
zones of cement kilns.

*You are invited to consult our  
world-wide experience on all cement kiln refractory problems.*

**JOHN G. STEIN & CO. LTD. BONNYBRIDGE, SCOTLAND. Telephone: Banknock 255 (4 lines) 361 & 362**

# This broom lasts 5 times longer



## THE NEW JARRATT WITH **WEBRONZE** FILLING

It's a tough brush the new Jarratt with the Webronze filling. Webronze—a polypropylene, designed to resist abrasion—to give five times the wear of natural fibres and to really sweep deep—shifts all the dirt—quickly. Webronze—the filling unaffected by climatic conditions, easy to clean, clogging matter falls away in water.

COMPARE THE PRICE



**102'6** PER DOZ.  
**ORDER NOW**

Less factor discount.  
Quantity discounts on application.  
Ref: 13 W.B., 13" double stave hole  
stock, 16x5 Knots.


**JARRATT**

**BRUSHES**

WEBB JARRATT & CO. LTD., TOWNSEND ROAD, CHESHAM, BUCKS.

TELEPHONE: 2181






DOPOL kiln  
with raw material preheater

# POLYSIUS




POLYSIUS  
engineers  
advise you  
to choose



Long kiln for wet and dry process

## The correct kiln for every raw material

LEPOL kiln with preheater for granulated and small-size material




**POLYSIUS GMBH**  
4723 Neubeckum,  
West Germany.  
Telefon: (02525) 711  
Telegramme: Polysius Neubeckum  
Telex: 0892 893

**POLYSIUS LTD.**  
London Road,  
Ascot, Berks.  
Telephone: Winkfield Row 2011  
Cables: Polysius Ascot  
Telex: 84 102

**POLYSIUS S.A.R.L.**  
13 Rue Auber,  
Paris 1Xe (Frankreich), France  
Tél: Paris-Richelieu 87 49  
Télégrammes: Polysius Paris  
Telex: 21602

**Confidence of the Customer – Characteristic of Success**

---



**KLÖCKNER-HUMBOLDT-DEUTZ AG · KÖLN**






### **Thanks to its advantages the HUMBOLDT preheater**

stands for the prototype equipment which determines a new trend in developing the new economic dry procedure for the production of cement.

Every 4th order for a HUMBOLDT preheater plant is placed as a subsequence of favourable experience made with the same equipment in the past. We project and build complete cement works operating by the dry procedure, wet procedure and with HUMBOLDT electrostatic precipitators reaching maximum capacities in accordance with the requirements of modern practice.



K 597 H

Matosinhos Cement Factory  
(Brazil)



all over the world ...

the cement industry  
relies on

**FIVES LILLE-CAIL**

S. A. AU CAPITAL DE 61.032.000 DE F. R. C. SEINE 54 B 2384  
7 RUE MONTALIVET PARIS 8<sup>e</sup> - ANJ. 22.01, 32.40





# HOWDEN

at

## *Wilson's (NZ) Portland Cement Portland, New Zealand*

**T**O handle and treat the gases from a Vickers-Armstrong 30/35-ton per hour Wet Process Cement Kiln at Portland, Northland, in New Zealand, a Howden Lurgi dry electro-precipitator has been installed, followed by a Howden induced-draught fan.

The waste gases from the kiln are conveyed to the twin-section mild-steel cased precipitator, which has trough-shaped hoppers with enclosed screw conveyors for dust removal.

The precipitator operating voltage is supplied by two Silicon Transformer Rectifiers, each rated at 500 mA/60 kV output, with Automatic Voltage Control equipment to maintain maximum de-dusting efficiency.

The precipitator and fan are designed to handle gas volumes up to 214,000 CFM at 250°C at a suction of 7.5 inches WG. The designed efficiency of the precipitator is 96.67%.

**JAMES HOWDEN AND COMPANY LTD**  
195 SCOTLAND STREET, GLASGOW C.5



## MAXIMUM PROFITABILITY— TROUBLE-FREE OPERATION

We are specialists in the design and construction of high-efficiency Lime Hydrating Plants. Sturtevant Plants continuously produce hydrate of guaranteed quality, are fully automatic in operation and have full dust suppression. Only two operatives are required, including bagging-off. Sturtevant Plants have in-built safeguards against breakdown, and accurately classify hydrate by air separators. They are in use all over the world.

*Write or telephone for full details.*

# STURTEVANT

**STURTEVANT ENGINEERING CO. LTD.**  
ENGINEERED PROJECTS DIVISION

Sturtevant House, Highgate Hill, London, N.19


Telephone: ARChway 0233



*Designers and manufacturers of plant for Drying, Pneumatic Conveying, Gas Cleaning, Lime Hydrating, Vacuum Cleaning, Batching and Blending, Formulation of Insecticides and Materials Classification.*




# MILLS FOR THE CEMENT INDUSTRY



1200 H.P. THREE CHAMBER GRINDING MILL RUNNING IN SELF-ALIGNING WATER COOLED OIL CASCADE LUBRICATED MAIN TRUNNION BEARINGS, PATENT FABRICATED STEEL ENDS AND SHELL LINED WITH MARTENSITIC NI-HARD LINERS.

PATENT 'H' TYPE MARTENSITIC NI-HARD SHELL LINERS FOR BALL, ROD AND TUBE MILLS. BRINELL HARDNESS UP TO 650. STANDARD PATTERNS AVAILABLE. OTHER TYPES TO CUSTOMERS OWN DESIGNS TO SUIT EXISTING MILLS CAN ALSO BE SUPPLIED.



*Other Products include:—*


Rotary Kilns, Coolers and Dryers.  
Apron, Table, and Scraper Feeders.  
Slurry Pumps and Slurry Mixers.

**NEWELLS**  
MISTERTON

**ERNEST NEWELL & COMPANY LIMITED  
MISTERTON VIA DONCASTER, ENGLAND**

Cables: Newells, Misterton, Notts, England Telephone: Misterton 224-225

MEMBER OF THE HADFIELDS GROUP OF COMPANIES



# ROTARY DISC FEEDER

*British Patent No. 769603*

for controlled, infinitely-variable volumetric-measurements to close limits of many kinds of crushed and ground materials such as cement raw material, limestone, gypsum, coal, etc.

- Operates safely.
- Handles highly hygroscopic and sticky materials.
- Offers immediate response to automatic regulation.
- Is airtight and therefore suitable for use in grinding installations operating under vacuum or pressure conditions.

**DELO (ENGINEERS) LTD.**  
138 Borough High Street  
LONDON, S.E.1. Tel: Hop 0085/6  
Telegrams: OLED, LONDON, S.E.1

Also Drying Furnaces, Disc  
Granulators, Pneumatic Conveyors

**HAND**

**FORGED**

**STEEL**

FOR BALL AND  
TUBE MILLS

IN HIGH  
CARBON  
OR CHROME  
STEEL

from

1" - 6" Diameter

**GRINDING**

**BALLS**

DESIGNED TO GRIND FASTER.  
LAST LONGER. NEVER BREAK.  
NEVER LOSE SHAPE.  
ALL HAND FORGED.

ALSO FINE HAND  
FORGED TOOLS FOR  
QUARRY AND MINE.

**F. J.  
Brindley  
& Sons (SHEFFIELD)  
Ltd.**

CENTRAL HAMMER WORKS, ACRES HILL LANE, POOLE ROAD,  
DARNALL, SHEFFIELD 9. Tel: Sheffield 49663/4 Grams: 49663/4



An 'ENGLISH ELECTRIC' 250 h.p. 735 r.p.m. d.c. motor driving the rotary kiln at the Rhoose Works of the Aberthaw and Bristol Channel Portland Cement Company Ltd., Glamorgan. A 300 h.p. motor generator set and 57 motors totalling 2,366 h.p. were also supplied under this contract.

For industrial drives or complete electrification schemes for the cement industry, contact

- TRANSFORMERS
- SWITCHGEAR
- FUSEGEAR
- CONTROL GEAR
- MOTORS
- POWER GENERATION

# 'ENGLISH ELECTRIC'

**LARGE INDUSTRIAL MACHINES DIVISION, STAFFORD**

The English Electric Company Limited, English Electric House, Strand, London, W.C.2.



*A name as familiar  
as cement itself*



You are invited to take advantage of our world-wide experience by consulting us regarding any problem connected with the manufacture of cement.

**F.L. SMIDTH & CO. LTD.**

**105 PICCADILLY,**

**LONDON, W.1**

Telephone: Grosvenor 4100 Telegrams and cables: Folasmith London

---

# CEMENT AND LIME MANUFACTURE

PUBLISHED ALTERNATE MONTHS.

PRICE 1s. 6d. A COPY

ANNUAL SUBSCRIPTION 9s. POST FREE  
\$1.75 IN CANADA AND U.S.A

PUBLISHED BY  
CONCRETE PUBLICATIONS LIMITED  
60 BUCKINGHAM GATE, LONDON, S.W.1

TELEPHONE: VICTORIA 0705/6.  
TELEGRAPHIC ADDRESS:  
CONCRETIUS, PEARL, LONDON.

PUBLISHERS OF  
"CONCRETE & CONSTRUCTIONAL ENGINEERING"  
"CONCRETE BUILDING & CONCRETE PRODUCTS"  
"CEMENT & LIME MANUFACTURE"  
"THE CONCRETE YEAR BOOK"  
"CONCRETE SERIES": BOOKS.

VOLUME XXXIX NUMBER 5

SEPTEMBER, 1966

## The New Weardale Cement Works.\*

IN the number of this journal for July last, a description was given of the quarrying operations, the preparation of the raw meal, and the firing section of the new works recently opened by The Associated Portland Cement Manufacturers Ltd., at Weardale, Co. Durham. In the following the processes subsequent to burning are described. Flow-diagrams for each of the sections of the plant from the quarry to the despatch section are given in *Fig 25* (pages 84 and 85).

### Auxilliary Kiln Plant.

ELECTROSTATIC PRECIPITATORS.—Each bed of nodules on the preheating grates absorbs a high proportion of the dust entrained in the gases leaving the kiln. The dust remaining in the gases is extracted by electrostatic precipitators (*Fig. 18*) before the waste gases are discharged via the final fan into the base of the 400-ft. reinforced concrete chimney.

Each of the precipitators, which were supplied by the Western Precipitation Division of Joy Sullivan Ltd., is of the plate type and comprises two chambers arranged in parallel and individually capable of taking the full flow of gas in the event of a fault occurring in the other chamber. The plates, which are of 16-gauge mild steel and are placed 9 in. apart, are interspersed with electrodes of 0.1055-in. diameter plough-steel wire placed at intervals in the direction of flow of the gas. Pneumatic rappers are provided for the plates and the electrodes. High-tension uni-directional current is supplied by totally enclosed silicon rectifier-transformer units equipped with automatic voltage controls of the transistomatic type. Castell locking of the isolators, earthing switches and all entries into the precipitator makes access impossible until isolation and earthing has been carried out.

INSTRUMENTATION AND CONTROL.—Automatic control of the Lepol semi-dry process plant is more complicated than in the case of a wet process. The principle adopted is to control some of the more important variables to pre-determined

\* Continued from July 1966.

C

ห้องสมุด กรมวิทยาศาสตร์  
- 8 พ.ย. 2509






Fig. 18.—Electrostatic Precipitators for Kilns.





Fig. 19.  
Kiln  
Instrument  
Panel.





**Fig. 20.—Clinker Storage Silos.**

levels. This control, coupled with weight control of the nodule input, tends to make some of the disturbing factors affecting the equilibrium of the burning process more uniform.

The variables controlled are the exit temperature of the coal mill, the input of cooler-air, the over-grate pressure balance of the Lepol grate, and the kiln-hod pressure. These controlled variables are recorded together with a number of the other temperatures and pressures throughout the system. Instruments and electric controls are situated in a common cubicle on panels which include mimic diagrams of each kiln and alarm annunciator panels.

The electric control panels are quite separate from the instrument panels, thus avoiding any risk of confusion between the wiring circuits which work on different voltages.

Honeywell Servotronic movements are used to make records of the prime variables in a row across a single wide chart, each instrument having a separate band of the chart with its appropriate scale. The whole of the records are thus obtained on one piece of paper which simplifies daily removal and scrutiny for control purposes. The instruments in the raw-meal preparation section are arranged similarly. The wide-chart opening can be seen clearly in *Fig. 19* which shows the kiln instrument panel.

### Clinker Conveying and Storage.

The clinker grate-coolers are fitted with hammer breakers which reduce oversize pieces of clinker and these then pass with the fine clinker through a drag-chain conveyor onto either of two Clarke-Chapman steel-trough catenary conveyors. Each conveyor has a designed capacity of 200 tons per hour, at a speed of 50 ft. per minute, which greatly exceeds the output from the two kilns, and thus allows for any surge in the discharge. Below the outlets from the coolers, the conveyors are horizontal for a length of 70 ft. Thereafter they are inclined at 5 deg. while passing along a subway below the works road. Following this section, one conveyor is inclined at  $17\frac{1}{4}$  deg. and the other at 36 deg. so as to discharge into separate steel distribution hoppers which are arranged for transfer of the clinker into the silos of the grinding mill or to a reserve store. Conveying to the silos is effected by two Bagshawe inclined bucket-elevators having a vertical lift of 65 ft. followed by two 15 in. Redler drag-chain conveyors each 129 ft. long.

The silos are of steel and are 30 ft. in diameter and 55 ft. high. There are eight silos, installed in two rows of four each, having a total capacity of 1,000 tons. Three of each group of four silos are allocated for storing clinker, the remaining one in each group being for storing gypsum. The clinker silos are shown in *Fig 20*.

The gypsum is delivered by road, the vehicles discharging into a hopper at ground level. By means of a short belt-conveyor, the gypsum is fed into one




Fig. 21.—Cement Grinding Mills.



**Fig. 22.—Electrostatic Precipitators at Cement Grinding Mills.**

of the aforementioned bucket-elevators and drag-chain conveyors while clinker is being handled by the other. The clinker and gypsum are extracted from the bases of the silos by Howe-Richardson extractors which discharge onto four belts, one on each side of the two rows of silos, feeding four cement mills. Weighers are combined with the gypsum extractors. Each belt has a Howe-Richardson weigher giving the combined weight of clinker and gypsum. This weigher is linked with the gypsum extractor-weigher by a controller set to give the required ratio of gypsum to clinker whatever the rate of feed to the mill.

#### **Grinding and Cement Storage.**

**GRINDING.**—Four cement mills are installed in two pairs (*Fig. 21*) in the building which also contains the drive motors and reduction gears.



The mills have shells 45 ft. long and of 8 ft.  $4\frac{1}{2}$  in. internal diameter. They are supported at both ends on white-metal self-aligning trunnion bearings of 3 ft. diameter, with provision for longitudinal expansion at the feed end of the mill. Each mill is divided internally into two chambers by a steel grid diaphragm. The feed-end chamber is lined with manganese steel plates and the following chamber is lined with NI-hard plates with helically-pitched ridges constituting a "classifying" lining. The chambers are loaded with steel grinding media of various sizes. Each mill shell is placed under suction by a fan through an electrostatic precipitator, a pair of which are seen in the background of *Fig. 21* and more clearly in *Fig. 22*. The dust discharges into the main flow of cement from the mill. Each mill is driven by an A.E.I. 1,200-h.p. 3.3-k.v. auto-synchronous induction motor coupled to a double-reduction divided-drive locked-train gearbox transmitting through a speed reduction of 750 to 20.5 r.p.m. The output shaft of the gearbox is coupled by two flexible couplings and a torsion shaft to a flange on the outlet trunnion journal of the mill.

Cement leaving each mill is passed over a totally enclosed Niagara vibrating screen with a single deck 30 in. by 60 in. Any particles of broken media are extracted, and cement then falls to the inlet of a 7-in. Fuller-Kinyon pump. The






Fig. 23—Bag-packing Plant.



**Fig. 24.—Bulk-loading Plant for Road Vehicles.**


air required for the pumps is provided by a Hick-Hargreaves rotary compressor. Delivery pipes 5 in. in diameter extend from the mill house and up the exterior of the cement silos to appropriate distribution junctions and valves in the housings over the cement silos.

**STORAGE.**—The cement is stored in eight reinforced concrete silos, each of 2,100 tons capacity, installed adjacent to the packing and loading plants. Extraction from each silo is by means of three pneumatic conveyors feeding to either of two 24-in. screw-conveyors between the two rows of four silos. Extraction air, together with that exhausted by the pipe-lines of the Fuller-Kinyon pumps, is passed through filter bags provided in the housings over silos. Following the two screw-conveyors, two elevators of the central discharge type lift the cement for transfer by pneumatic conveyors. Thus cement from any silo can arrive at positions suitable for bagging or despatch in bulk by road or rail. Screens are interposed at each terminal point of the mechanical handling system as a protection against any extraneous matter entering the system,




RAWMEAL PLANT

\* INDICATES DUST EXTRACTION PLANT FITTED



COAL PLANT



KILN



CLINKER AND GYPSUM STORAGE AND GRINDING PLANT

Fig. 25.—Cement Works





Weardale : Flow Diagram.




**Fig. 26.—Works Main Substation.**

**BAGGING AND DESPATCH IN BULK.**—For packing bags, an eight-spout Haver & Boecker packer (*Fig. 23*) is installed. This plant has a capacity of filling 1-cwt. paper bags at the rate of 110 tons per hour. The filled bags are discharged on to a 24-in. flat belt-conveyor which, by means of ploughs, can distribute either to one of the three retractable belt-conveyors, supplied by Messrs. J. Darnley Taylor, Ltd., for loading lorries, or on to a turntable from which they are taken by sack-barrows to rail box-wagons.

For bulk loading, the cement is passed into three elevated hoppers (*Fig. 24*) from which vehicles standing below can be loaded quickly.

Rail bulk-wagons stand on a weighbridge while they are being loaded from pneumatic conveyors. All the loading points are fitted with dust-collection equipment returning the collected cement into the respective loading hoppers.

Most of the output of this works is dispatched in bulk in block trains composed of "Presflo" wagons, many of which are owned by A.P.C.M. Ltd. Some special light-alloy cylindrical tank wagons (*Fig. 20*) are also provided. The trains proceed to distribution and packing depots at various places in the North of England. For shunting, rail traffic is handled by a diesel-hydraulic Vanguard locomotive of 175 h.p. The works sidings are, however, laid out for use by British Rail locomotives so that assembled trains of empty and filled wagons can be easily



# FIRTH BROWN

**steel and alloy  
iron castings**

**Firth Brown  
castings have  
been supplied  
to the Weardale  
Cement Works**



**FIRTH BROWN LIMITED**  
Sheffield  
England.

**Steel Foundry:**  
Scunthorpe, Lincs.  
Tel. 2208/9.




# AT THE HOT HEART OF WEARDALE

Brief note to Top Management :  
Blair characteristics : skill—competitive-  
ness—highly mobile labour force—ad-  
vanced mechanical handling technique  
—experience in all types of refractory  
installations large and small — compre-  
hensive service in North and North East.

S. G. Blair & Co. Ltd., Lesley House, Broadway,  
Bexleyheath, Kent. Bexleyheath 5696/7691.  
Grams : Refcon, Dartford.

The refractory installation by S. G. Blair & Co. Ltd. the specialist constructors in this field



handled into and out of the works, thereby ensuring a speeding turn-round of traffic.

#### Water and Power.

**WATER SUPPLY.**—Water for nodulising and cooling machinery is obtained from surface drainage and by extraction from the nearby River Wear. All water is stored primarily in two interconnected concrete-lined ponds of 100,000 and 160,000 gallons capacity. Circulation is effected by three, and one standby, centrifugal pumps through two 9-in. low-level mains into a 20,000-gallon header tank situated in the top of the granulator building. The pressure of water at any part of the works is therefore practically constant. All cooling water, together with storm water, is returned by the works drainage system to the ponds. By arrangement with the Wear and Tees River Board, supplementary water is taken from the River Wear by a separate smaller pump, and surplus water which may be collected at times is passed into the river. Water for drinking purposes, canteen, laboratories and the like, is obtained from a separate water main connected to the local water authority's supply.

**DRAINAGE.**—A complete soil drainage system is installed at the works and connected to a sewage treatment plant.

**POWER SUPPLY.**—The supply of electricity from the North Eastern Electricity Board is fed into duplicate 66/20 k.v./15 m.v.a. transformers installed in a substation adjacent to the main entrance to the works. From this point, 20-k.v. underground cables feed two A.E.I. 20/3·3 k.v. transformers located in the works main substation (*Fig. 25*). Each is rated at 6/7·5 m.v.a. and each is fitted with manually-operated off-load tap-changing having steps of  $\pm 2\frac{1}{2}$  per cent. and  $\pm 5$  per cent., delta-star wound, incorporating Bucholz and winding temperature protection. Power is received and distributed from the main substation at 3·3 k.v. using Whipp & Bourne air-break circuit-breakers rated 150 mVA, each breaker being solenoid-operated from either a rectifier or battery source of 110 volts d.c.

In addition to the main substation, three other substations have been established, namely, one at the Aerofall mill, crusher and kiln. The Aerofall mill and crusher substations are on the hillside. The former is fed via duplicate feeders about  $\frac{1}{2}$  mile long and comprising two three-core 0·3-sq. in. cables, which are underground except where they cross the road, river and railway by means of the conveyor gantry. The medium voltage distribution system is derived from eleven 3·3 k.v. 433-v. hermetically-sealed transformers supplied by London Transformer Products Ltd. Three of these transformers are installed in the main substation, three in the Aerofall mill substation, and one in the crusher substation. All these transformers are of 750 k.v.a. The remaining four are of 1,000 k.v.a. and are installed in the kiln substation which is located near the kiln plant. All these eleven transformers are fitted with manually-operated off-load tap-changing switches with  $\pm 2\frac{1}{2}$  per cent. and  $\pm 5$  per cent. settings, and are suitable for parallel operation within their group. Whipp & Bourne medium-voltage switchgear is installed, and comprises spring-operated air-break circuit-breakers for the incoming and bus-section duties, together with outgoing fused-switch units.

The 3.3-k.v. motors are controlled by air-break circuit-breakers incorporating P. & B. Gold M4A relays. The 415-v. drives are grouped into multi-starter boards using Baldwin & Francis air-break contactors. Automatic synchronising equipment is fitted to the Salient-pole synchronous motors driving the 1,800-h.p. and 1,200-h.p. mills.

Centralised control consoles equipped with semi-graphic mimics, indicator lamps, alarm and monitoring devices and the like are provided to operate all the plant drives.

#### **Acknowledgements.**

The design of the works was undertaken by the Central Engineering Department and Northern Area Engineering Office of The Associated Portland Cement Manufacturers Ltd. The consulting engineers for the civil engineering work at the quarry were Messrs. Oscar Faber & Partners.

The main civil engineering contractors were Tarmac Civil Engineering Ltd., and Mitchell Construction Co., Ltd.; the work undertaken by the latter firm also included the construction of the 400-ft. concrete chimney. The piled foundations were installed by Messrs. A. Waddington & Son Ltd. The main contractors for the administration building, which has an area of 12,000 sq. ft. and is of conventional construction, were Messrs. G. Stephenson (Builders & Contractors) Ltd. This building was erected in four months. The precast concrete components for the coal store, mill and grinder building, the garage at the quarry, and the buildings for the general stores and fitting shop were supplied and erected by Messrs. F. & D. M. Hewitt Ltd. The structural steel work, amounting to over 1,000 tons, for the limestone stores, crusher house, Aerofall mill house and other works at the quarry was supplied and erected by Messrs. Wright Anderson & Co., Ltd.

In addition to the various suppliers of auxilliary plant named in the foregoing description of the works, the following firms were concerned with the supply of the plant. The Lepol kiln plant, the Recupol coolers, the regrind mills and the turbo-air-separators were supplied by Polysius Ltd. The Aerofall mill was supplied by Messrs. Ashmore Benson, Pease & Co., Ltd., and the 1,200-h.p. cement mills by Vickers Armstrong (Engineering) Ltd. The mechanical erection was carried out by Messrs. Ashmore Benson, Pease & Co., Ltd., Staffordshire Public Works Co., Ltd., and Installation & Manufacturing Contractors Ltd. The electrical installations were by Messrs. H. J. Couzens Ltd.

---

#### **Brochure Received.**

**Fives Lille-Cail and the Cement Industry.**—A 56-page booklet describing the operation of four factories of the Fives Lille-Cail organisation, which undertakes all manufacturing operations of plant for the cement and other industries, from making the steel to assembling the plant. The descriptions relating to cement plant apply to grinding and burning and auxiliary plant, and are illustrated by examples of plant installed at various works throughout the world.






### **WADDINGTON-BENOTO BORED PILES FOR A.P.C.M. NEW WORKS AT WEARDALE CO. DURHAM**

Benoto EDF.55 Rig boring foundation piles for Granulator, Lepol Grate, Kiln Piers and Cooler Housings in the second phase of the Weardale development. The structures in the background comprising similar units in the first phase were also founded on Waddington-Benoto piles.

**A.WADDINGTON & SON LTD**

Civil Engineering Contractors, North Circular Road, London, N.W.10.



— study the economics

#### Capital cost

Equipment costs can show a reduction of up to 20%.  
Installation costs can show a reduction of up to 50%.

#### Operating costs

**LABOUR** Only one operator is needed to supervise a plant with as many as six mills.

**MAINTENANCE** Virtually limited to lubrication and planned replacement of liners.

**POWER** Reductions in power consumption.

All these savings are inherent in the design and operation of the Aerofall mill system. This comprises a complete crushing, grinding and classifying plant which accepts run-of-mine or primary crusher product as feed, and in a single operation reduces it to a ground product ready for the process plant.

*Associated Portland Cement Manufacturers Limited now use Aerofall mills at three works in the U.K. for the manufacture of cement raw meal—details are listed below.*

<b>ORE</b>	Hard limestone plus shale	<b>POTENTIAL CAPACITY</b>	In excess of 4,000 tons per day per mill
<b>MOISTURE CONTENT</b>	Average 5%	<b>GRIND</b>	35% minus 170 mesh
<b>MILL</b>	One 23 ft. dia. Aerofall mill at each of three works	<b>MEDIA STEEL WEAR</b>	0.17 lb./ton
<b>LOCATION</b>	Cauldon, Staffordshire, England. Dunbar, East Lothian, Scotland. Weardale, Co. Durham, England.	<b>POWER (Total primary grinding including auxiliaries)</b>	16.0 kWh per ton
<b>FEED</b>	Minus 9 in.		

*Write for brochure entitled 'Aerofall Mills' describing the range and applications of this versatile system.*

**ASHMORES**  
PROCESS EQUIPMENT DIVISION

Ashmore, Benson, Pease & Company Limited,  
South Works, Stockton-on-Tees, England.  
Telephone: Stockton 65171 Telex: 58570

MEMBER OF THE DAVY-ASHMORE GROUP

## Heat Generated in the Hardening of Magnesite Cement.

AN important study by the U.S. National Bureau of Standards provides what is thought to be the first published figures on the amount of heat generated in the setting of magnesium-oxychloride cement. Formed by the action of concentrated magnesium-chloride solution on active magnesium oxide, cements of this type are extensively used in industry, but they generate much more heat in the process of hardening than does ordinary Portland cement, and this may in some applications cause serious difficulties. The heat evolved by a large mass of magnesium-oxychloride cement could easily raise the temperature to well above 100 deg. C. Being a good conductor of electricity, this cement is particularly suitable for non-sparking flooring in works manufacturing explosives and the operating theatres of hospitals. Other applications include floors of office buildings, stores, ships and railway carriages. Because it absorbs neutrons more effectively than does Portland cement, it is also used for the heavy protective walls required in atomic-energy work. Although well established, some users of magnesite cement report unfavourable results. The mechanisms of the difficulties that have arisen are not well understood, but it is likely that some instances of unsatisfactory performance have resulted from non-uniform methods of preparation and application. No generally accepted standard specification for the preparation and application of magnesium-oxychloride cement have yet been adopted in the U.S.A. (There is in Great Britain, a British Standard Code of Practice CP204, "Insitu Floor Finishes," which includes a section on magnesium-oxychloride flooring; a revised edition of this Code was published recently.)

In the Bureau's study, nine representative commercial magnesite cements were investigated and, in addition, some laboratory-mixed pastes consisting only of magnesium oxide ( $MgO$ ), magnesium chloride ( $MgCl_2$ ) and water, in various proportions, were also investigated.

The heat generated in the commercial cements during the first eighteen hours of hardening, during which time heat generation is substantially complete, was found to be about 190 calories per gramme of magnesium oxide. For the laboratory-made pastes of various proportions, a wide range of values was obtained, varying from 135 to 320 calories per gramme of magnesium oxide. The low heats of hardening measured for some of these pastes support the conclusion of previous investigators that free  $MgO$  may remain in such pastes.

Three different calorimetric procedures were adopted. The heats of hardening of the laboratory pastes, which contained no inert or filler material, were determined indirectly by a heat-of-solution method similar to that used for Portland cement. The heat of solution of a sample of the hardened paste was determined in hydrochloric acid (2.00 normal). Using similar HCl solutions, the heat of solution of the magnesia and the heat of dilution of the magnesium-chloride solution used in preparing the paste were also determined. The difference between the sum of these last two values and the heat of solution of the hardened sample is the heat evolved during the hardening of the paste. This indirect heat-of-solution method



used for the laboratory pastes, requires that the materials be soluble in the acid and that the paste be analysed chemically.

To determine the heats of hardening of the commercial cements, two direct methods were used. In the first, samples of the cement were allowed to harden in corked vacuum flasks while their internal temperatures were recorded. Electrical calibration of the flasks permitted the heat evolved by the cement to be calculated from the recorded temperatures. Because the cement in the vacuum flasks reached temperatures up to 100 deg. C., a second set of direct measurements was made in a Lerch conduction calorimeter. In this apparatus, the heat generated by the cement flows over a calibrated path into a water-bath at constant temperature. Because of the more rapid flow of heat from the specimen, the Lerch equipment permits the cement to harden at lower temperatures than do the vacuum flasks; the temperatures reached by the cement in this instrument were only a few degrees above the temperature of the room. The path of the flow of heat was a brass tube, one end of which was in contact with the cement and the other end of which was maintained at the temperature of the water bath. Resistance thermometers attached to the tube permitted the temperature drop along the tube to be recorded. From the recorded differences of temperature and from the electrical calibration of the instrument, it was possible to calculate the amount of heat evolved by the cements.

---

### British Standard for Sulphate-resisting Portland Cement.

A NEW British Standard B.S.4027, "Sulphate-resisting Portland Cement", was issued recently.\* The specification is based on experience gained in the sixteen years which have elapsed since sulphate-resisting cements were first manufactured.

The physical requirements for sulphate-resisting Portland cement are identical with those for ordinary Portland cement, as specified in B.S.12, except that finer grinding is required. A direct test of resistance to sulphates can only be achieved by prolonged storage of specimens in sulphate solutions, and thus is not suitable for a standard test. It is known, however, that Portland cement has a considerable degree of resistance to sulphates if the content of tricalcium aluminate does not exceed  $3\frac{1}{2}$  per cent., and this limit has therefore been included in the new Standard.

In addition to fineness and chemical composition, the Standard stipulates the requirements regarding manufacture, sampling, manufacturer's certificates, marking, and the use of the cement in tropical climates. The compressive strength, setting time and soundness are specified. Appropriate methods of test are given in appendices.

Details of the requirements of the Standard are given in the following.

**FINENESS.**—The fineness is to be such that the specific surface is not less than 2,500 sq. cm. per gramme.


**CHEMICAL COMPOSITION.**—The lime-saturation factor is to be not greater than 1.02 and not less than 0.66 when calculated from the expression

---

\*Obtainable from the British Standards Institution, 2 Park Street, London, W.1. (Price 10s).

# we sell the best dust valves you can buy!

As a major manufacturer of world renowned dust collection equipment, we know you can't get high performance from a dust collector without getting high performance from the dust valves connected to the hoppers so we produce our own high performance dust valves—and use them ourselves—and sell them to others. If you need the best dust valves you can buy to get the highest efficiency out of your dust collection system, settle for OURS.



**OURS**—The type R-1 motorized tipping valve with features not available with gravity-operated tipping valves: positive time cycle motorized operation; gravity free-flow flushing features; gravity return assuring positive valve seating without pressure closure that guarantees non-jamming. It operates in positive pressure installations up to 5in. W.G. (with special valves available rated for 30in. W.G.), and negative pressure installations up to 40in. W.G. And like all the dust valves we sell, the R-1 continues to operate efficiently at temperatures up to 750°F.

**OURS**—The gravity operated tipping valve—ideal for sealing dust collector hoppers operating under negative pressure (0-6 in. W.G.) when handling dry free-flowing material. The air lock principle of this valve is achieved by the use of two flap closures that operate alternately, permitting the collected dust to pass out of the hopper without pressure loss. The rugged cast iron construction and the unique hinged design of the valve plate assures a perfect seal.

**OURS**—The floating seal dust valve, for operation when handling abrasive materials, particularly at high temperature. The "revolving door" principle is a familiar one for dust valves and dust feed regulators. But it took Western Precipitation to transform a "familiar" item into a "special" one, by using a carefully machined cast iron "Floating Seal" of controlled hardness. A perfect metal-to-metal seal is continuously maintained, for, as the cast iron seal slowly wears, its weight keeps it in intimate contact with the rotor.

We sell the best dust valves you can buy. Not the cheapest . . . but the best value for money and exactly the right unit for your application, in six, eight and ten inch sizes. That's a big claim and one we are prepared to back all the way. Ask us to prove it, but first, may we send you a copy of our technical bulletin on Valves?

Ask your Secretary to write for a copy.



**WESTERN PRECIPITATION**

division of Joy Trading Corporation.

7 HARLEY STREET, LONDON, W.1.

Telephone: Langham 7711

Manufacturers of electrical precipitators · mechanical dust collectors · gas scrubbers and high temperature filters



# **Consett**


## **ROTACON Bricks**

### **THE Hot Zone Lining for ROTARY CEMENT KILNS !**

Specially developed for Portland Cement Kilns by Consett Iron Co. Ltd. ROTACON possesses all the important characteristics necessary in a basic liner brick.

ROTACON bricks build up a sound coating rapidly and withstand kiln shut-downs without spalling. They are not subject to chemical attack at high operating temperatures and will not disintegrate from thermal contraction. *The ideal basic lining for the production of Portland Cement.*

**ROTACON BRICKS SAVE MONEY  
BY INCREASED KILN AVAILABILITY**



**CONSETT IRON CO. LTD.**  
**CONSETT · COUNTY DURHAM**

Telephone: Consett 3411      Telex: 53172





$$\frac{(\text{CaO}) - 0.7(\text{SO}_3)}{2.8(\text{SiO}_2) + 1.2(\text{Al}_2\text{O}_3) + 0.65(\text{Fe}_2\text{O}_3)}$$

The symbols in brackets refer to the percentage (by weight of total cement) of the oxide, excluding any contained in the insoluble residue.

The tricalcium-aluminate content  $C_3A$  is to be not greater than 3.5 per cent. when calculated from the expression  $2.65(\text{Al}_2\text{O}_3) - 1.69(\text{Fe}_2\text{O}_3)$ . The symbols have the same significance as for the lime-saturation factor.

The percentages of  $\text{Al}_2\text{O}_3$  and  $\text{Fe}_2\text{O}_3$  are determined by methods described in the Standard. If the result of this calculation is below 3 per cent., the cement is deemed to comply with the requirements without a repeat determination. If the result is above 3 per cent., the determination is to be repeated from the beginning. If both the results are at or below 3.5 per cent., the cement is deemed to comply with the requirements. If one of the two results is above 3.5 per cent., the determination is to be carried out a third time and, if two out of the three results are at or below 3.5 per cent., the cement is deemed to comply with the requirements. If two out of the three results are above 3.5 per cent., the cement is deemed not to comply with the requirements.

Results of the tricalcium-aluminate determination which differ by more than 0.2 per cent. from the laboratory average result, are to be discarded and the determinations repeated. If agreement is still not reached, the cement is to be retested in accordance with the foregoing procedure by an agreed independent laboratory, and the results then obtained are to be accepted.

The weight of magnesia is not to exceed 4.0 per cent.

The content of total sulphur in the cement, expressed as  $\text{SO}_3$  is not to exceed 2.5 per cent.

The total loss on ignition is not to exceed 3 per cent. for cement to be used in temperate climates or 4 per cent. for cement to be used in tropical climates.

**COMPRESSIVE STRENGTH.**—The average compressive strength of three mortar cubes or of three concrete cubes are to be as for ordinary Portland cement.

**SETTING TIME.**—The initial setting time is to be not less than 45 minutes, and the final setting time not more than 10 hours.

**SOUNDNESS.**—The cement, when tested for soundness by the method described in the Standard is to have an expansion not exceeding 10 mm. If the cement fails to comply with this requirement, a further test is to be made using another portion of the same sample after it has been aerated by being spread out to a depth of 3 in. (76 mm.) at a relative humidity of 50 to 80 per cent. for a total period of 7 days; the expansion of this aerated sample is not to exceed 5 mm.

**CEMENT IN TROPICAL CLIMATES.**—The temperatures specifically mentioned in the methods of test are applicable to temperate climates. Cement intended for use in tropical climates may be tested at temperatures exceeding 68 deg. F. (20 deg. C.) but not exceeding 95 deg. F. (35 deg. C.).

**Note.**—The Blue Circle Group have published a revised data sheet relating to sulphate-resisting Portland cement and having special reference to the new British Standard.

### Pozzolan Cements in India.

A publication, entitled "Special Report No. 1—Pozzolan Clays of India: Their Industrial Exploitation & Use in Engineering Works," was issued recently by the Indian Central Road Research Institute (Copies are obtainable at Rs. 13.00 per copy from the Director, Central Road Research Institute, New Delhi-20, India). One section of this 300-page book deals with pozzolan cements. After dealing with the method of production of this material in other countries, the Report continues with an examination of suitable materials available in India and gives an account of the extent to which pozzolan cements are made in that country.

A number of deposits of very reactive clay yielding pozzolanas with lime reactivity of at least 2,000 lb. per sq. in. have been located, and work connected with the development of special pozzolana cements has been undertaken at the Institute. Results show that by using highly reactive "surkhi"\* to replace 20 per cent. of the cement in a mortar or concrete, a pozzolan cement is obtained which has the same early-strength properties as the corresponding ordinary cement and has higher chemical resistance. Experience indicates the necessity of inter-grinding pozzolana and cement clinker to produce pozzolan cement in preference to the current method of mixing the pozzolana with the cement and aggregates when making concrete, and in preference to the establishment of blending centres to achieve the unsatisfactory task of mixing dry cement and pozzolana.

The only example in India of large-scale manufacture (about 100 tons per day) of clay pozzolana carried out under controlled calcination has been at Bhakra dam in the Punjab. The pozzolana plant was associated with a 400-ton-per-day cement plant producing together 500 tons of pozzolan cement per day. The procedure was as follows.

The raw shale was first reduced to  $\frac{3}{4}$ -in. size. It was calcined in a rotary kiln at 1400 to 1600 deg. F. (760 to 870 deg. C.) and remained to soak at this temperature for two hours in a refractory-lined 15-ton soak pit. This operation was found to improve calcination. The material was then carried on a drag-chain conveyor and cooled on the way to the grinding unit by a spray of water limited in volume to keep the material dry enough for grinding. The calcined material was ground to a specific surface of 4500 sq. cm. per gramme (Blaine).

The shale deposits at Bhakra contain bands of sandstone, siltstone and overburden mixed with the shales. During excavation, the sandstone and overburden could be rejected but the siltstones were thoroughly intermixed with the shales. They were, however, removed to a great extent by hand-picking off the raw-feed belt, but about 3 to 6 per cent. was always left in the shale. From the point of view of pozzolan activity, this amount of siltstone was found to be deleterious. The raw shale as excavated was a mixture of dust and lumps. Before feeding it into the kiln, the lumps were reduced to  $\frac{3}{4}$ -in. in a jaw-crusher. Calcination and grinding were greatly affected by the condition of the raw material, granular material

---

\*Until recently, "surkhi" was the term applied to crushed brickbats. A superior material is now prepared by calcining selected clays rich in reactive materials.

# HAVER AUTOMATIC PACKING MACHINES

In-line packers: series BB and BBV

rotary packers: ROTO series R and RV

Outputs up to 110 l.p.h. with one operator

Pre-compacting of cement (shorter bags)

Vertical bag-drop


Automatic bag push-off

Complete packing and loading plants

More than 2500 HAVER Packing Machines  
in operation all over the world

**HAVER & BOECKER**

4740 OELDE Westfalen  
— Germany —




U. K. Representatives:-

**CONTINENTAL ENGINEERING CO. LTD.**

London Road, Ascot, Berks. · Tel. No: Winkfield Row 2011



## Simple in construction, unequalled in performance



### **MIAG double - shaft hammer crusher "TITAN"**

crushes in one single operation up to 800 t/h of limestone as well as minerals of similar kind to a grain size smaller than 25 mm


Insensible to tramp irons contained in the feeding material

Favourable specific power requirement

Perfect operation safety

Good possibilities of maintenance and observation for all building sections

Shortest installation and disassembly period of the wear parts



**MIAG**

BRAUNSCHWEIG / Germany

Agency for Great Britain  
**INDUSTRIAL EQUIPMENT CO.**  
(N. I.) Ltd.  
58, Howard St. Belfast

being easier to handle during calcination than the dust. The shale acquired pozzolanic activity only when it was calcined at the previously stated temperatures for about two hours. The kiln was an oil-fired rotary kiln 100 ft. long which dealt with about  $5\frac{1}{2}$  tons of material per hour. The temperature at the firing end was about 1700 deg. F. The kiln rotated at 1 r.p.m., at which speed, and due to the inclination of the kiln, it took about 58 minutes for the material to travel from one end to the other. The temperature of the material at the discharge end was about 1600 deg. F. The temperatures in the kiln and soak pit were recorded by radiation-type pyrometers and thermocouples. The oil consumption in the kiln was about 8 to 10 gallons per ton of material.

The calcined material, after being cooled, was stored in a 1100-ton silo. The grinding mills were of two types and three in number. One was a 20 ft. by 5 ft. double-compartment ball-mill, capable of grinding about 2.5 tons of material per hour to the required fineness. The first compartment contained large balls which did most of the disintegration. The second compartment contained smaller media which pulverised by attrition. The second type of ball-mill of which there were two, was a single-compartment type 10 ft. by 5 ft. and used "cylpebs" as grinding media. Before being fed into the ball-mills, the material was disintegrated in hammer-mills. Each ball-mill had a hammer-mill attached to it. However, the hammer-mills were found to be unsuitable for this operation since the hammer, sieves and corrugated lining plates were easily worn out and had to be replaced frequently. The average output was about 2.5 tons of material per hour. The total maximum output in a day from the three ball-mills was about 120 tons. The ground pozzolana was stored in silos from which it was taken by lorries to a batching plant where the pozzolana was batched with the other materials to produce pozzolana concrete.

The foregoing process for preparing pozzolana could, up to the stage of grinding, be adopted for a cement works producing pozzolana cement. In this case, the calcined pozzolana could be interground with cement clinker in the proper proportions to yield pozzolana cement conforming to the Indian Standard Specification No. 1489-1962.

---

#### Rotary Kilns of Large Capacity.

A KILN having a capacity of 3,000 tons per day is to be added to the eight kilns existing at the Obourg cement works in Belgium. The diameter of the new kiln will be 7 m. (23 ft.) to 6.25 m. (20 ft. 6 in.), and the length will be 202 m. (663 ft.). Two other large kilns of 165-m. (541 ft.) length having capacities of 1,400 and 1,600 tons per day were installed at this works in 1953 and 1954 respectively. A kiln 167.5 m. (about 550 ft.) long, also having a daily productive capacity of 1,600 tons, was installed in the 1960's in the works at Alhandra, Portugal. Other large kilns include one of 1,700/2,000-tons daily capacity in the United Arab Republic, and one of 2,500-tons capacity in the Atchinsk works in the U.S.S.R.

All the foregoing large kilns were supplied by the Fives Lille-Cail organisation of France.

The welded shells of the largest kilns are made of open-hearth steel having different mechanical properties for different sections of the shell. The tensile strength of the steel for the heaviest sections and for the burning zone is 42 to 50 k.g. per sq. mm. (27 to 32 tons per sq. in.), that of the remaining part being 37 to 44 kg. per sq. mm. (23.5 to 28 tons per sq. in.).

---

### **Combined Sulphur and Cement Production.**

A NEW thermal method of processing sulphur, which combines the production of sulphur with that of cement and which has been developed successfully in laboratory tests, is to be tried out on a commercial scale at the Golezow cement works in Poland. Clay is added to the limestone remaining after the sulphur has been extracted, and the resulting mixture is used for the production of the cement.

---

### **A New Concrete Journal.**

THE recent formation of The Concrete Society is an important event in the development of the concrete industry in Britain and, in particular, in the life of our contemporary journal "Concrete & Constructional Engineering," which, during the past sixty years or so has always aimed to represent the activities of all aspects of the cement and concrete industry—design, construction research, materials, plant and equipment. When the then un-established Concrete Society decided that it would have to issue a journal for its members, it was felt that there was no need for two journals having this same aim and it was natural, in the best interest of the industry, for some form of collaboration to be considered.

It has therefore been decided that, from the end of this year, "Concrete & Constructional Engineering" will cease to be published as such, as will also "Structural Concrete," the journal of the Reinforced Concrete Association. In their place, commencing in January 1967, Concrete Publications Ltd. will publish, on behalf of the Concrete Society, a new journal entitled simply "CONCRETE" which will incorporate "Concrete & Constructional Engineering" and "Structural Concrete," and will be the journal of the Concrete Society. The new journal, which will be of the international A4 size, will give news of the Society, report on its activities, publish its papers and reports, and will include some of the well-known features of "Concrete & Constructional Engineering" such as the articles on theoretical and practical design.

All members of the Concrete Society will receive copies of CONCRETE, but for non-members in the U.K. and abroad, the charge will be four shillings per copy (plus postage).

The prepaid subscription rate will be 50s. (9 dollars in Canada and U.S.A.) per annum including postage. Readers of "Cement & Lime Manufacture" who are not members of the Concrete Society and wish to subscribe to the new journal should communicate with the Publishers (not the Society) at 60 Buckingham Gate, London, S.W.1. Specimen copies of the new journal will be available in January.



# Cement plant turnkey projects by Vickers

World demand for cement continues to rise, bringing with it the requirement for more manufacturing plant—extensions to existing works, complete installations. More and more, particularly with developing countries, the requirement is for turnkey projects, complete plants ready for operation as soon as the labour force moves in.

Vickers is uniquely placed to meet any requirement for cement-making machinery. A special Division, devoted exclusively to the Industry, is composed of experienced chemists, designers and engineers, backed by world-renowned engineering facilities.


## A Complete Service

Experienced design engineering teams are available to travel to any part of the world to discuss projects on the spot. The closest liaison is maintained with all leading cement producers, keeping Vickers abreast of world cement market trends and requirements.

## Manufacture and Design

The works are at Barrow-in-Furness, Lancashire, England, whilst other engineering and manufacturing facilities are available at Vickers works and associates in Australia, Canada, India, South Africa and Vickers licensee in Spain. Full advantage is taken of this engineering capacity, enabling kilns and grinding mills of the largest capacity and rating so far in use anywhere in the world to be offered to customers. Up to the present day Barrow Works alone has made and delivered over a hundred and twenty kilns and a hundred and fifty grinding mills.

A specialist staff of chemists and engineers is concerned with the development and application of new equipment and techniques, many of which have been initiated by Vickers.



## Construction, Operation and Labour

Construction and commissioning on site is carried out under the surveillance of Vickers engineers, and local labour employed during this period can be trained to operate the factory.

## World-Wide Experience and Service

Vickers have been producing specialised machinery for the cement and allied industries for over forty-five years. Equipment has been supplied to leading manufacturers in many parts of the world and an extensive service network has been built up. Plants operating in Australia, Belgium, Canada, Ceylon, Hong Kong, India, Mexico, New Zealand, Rumania, South Africa, Zambia, have all provided experience in meeting varying conditions of operation.

## Reliability

To be economic the production of portland cement must be a continuous uninterrupted process. All of Vickers equipment, whether a component or a complete plant is designed and made to ensure reliable, continuous and profitable plant operation.


## Further information

For further information please contact the Cement Machinery Division (Sales), Vickers House, Millbank Tower, Millbank, London SW1. Telephone: TATE Gallery 7777. Cables: Vickers London.

Technical queries to

**VICKERS**  
LIMITED

Cement Machinery Division  
Engineering Group  
Vickers-Armstrongs  
Barrow Engineering Works  
Barrow-in-Furness Lancs England  
Tel: Barrow 3366. Ext 129



**Complete Plants  
for manufacturing**

**ASBESTOS CEMENT  
PIPES and SHEETS..**

**PRESSURE PIPES**

**DOWN PIPES**

**CORRUGATED**

**AND FLAT**

**SHEETS**



**ASBESTOS CEMENT ENGINEERING CO.**  
**AEULESTRASSE 772, YADUZ - LIECHTENSTEIN**  
 Switzerland . P.O. Box 34,722.

... Production, delivery, service and (if required) finance for complete installations, large or small.

Installations complètes pour la fabrication des tuyaux haute et basse pression et des plaques planes et ondulées en amiante-ciment.

Production, livraison, service et (si désiré) financement des installations complètes grandes ou petites.

**AGENTS REQUIRED**

**MISCELLANEOUS ADVERTISEMENTS**

**SCALE OF CHARGES  
FOR  
MISCELLANEOUS  
ADVERTISEMENTS**

5s. per line (average seven words per line).

For use of Box Number, allow two lines.

Minimum £1 for not more than four lines.

**DISPLAYED ADVERTISEMENTS**

45s. per single column inch.

Advertisements must reach this journal at 60 Buckingham Gate, London, S.W.1. by the 1st of the month of publication.

**FOR SALE**

"SPEEDY" MOISTURE TESTER gives an accurate measurement of the moisture content in cement, lime, gravel, etc., in 3 minutes. Unskilled workmen can easily operate this non-electric and portable instrument. Over 30,000 "SPEEDYS" now in use. Full descriptive literature available from THOMAS ASHWORTH & CO. LTD., CG8, Sycamore Avenue, Burnley, Lancs.

**FOR ALL BAGS  
AND SACKS · ANY  
MATERIAL · ANY SIZE**

**TPE portable stitching machines**

**TPE static stitching machines**

**TPE high-speed heat sealers for plastic bags**

**TPE automatic sack lifters**

**FREE DEMONSTRATIONS  
of these and TPE's many other  
profit-earners**

*Write today for details*

**THE THAMES PACKAGING  
EQUIPMENT CO.**

Dept. CLM, 28 City Rd., London, E.C.1,  
 England. Tel: MONarch 7387/8.  
 Grams: Pakitup London E.C.1.

(Props: The Thames Sack & Bag Co. Ltd.)

**"CONCRETE SERIES"**

**BOOKS ON CONCRETE**

For complete list of books on cement, concrete,  
 and allied subjects send postcard to


**CONCRETE PUBLICATIONS, Ltd.**

**60 Buckingham Gate, London, S.W.1**

# GR 341 Fired Dolomite for Rotary Cement Kiln Lining

## 7 IMPORTANT FEATURES OF GR 341 FIRED DOLOMITE BRICKS

- Chemically resistant to Portland cement.
- Have a natural tendency to pick up and maintain a protective clinker coating in the clinkering zone.
- Resist clinker ring formation in the cooler sections of the kiln.
- Excellent volume stability.
- Low thermal conductivity.
- High resistance to thermal shock.
- Resistant to hydration.




**SYSTEM  
CaO-MgO**  
AFTER HANKIN & MERWIN

Full particulars from:

# GENERAL REFRACTORIES LTD

GENEFAX HOUSE · SHEFFIELD 10 · TEL: SHEFFIELD 31113





# PLANET HUNWICK ALITE

a complete range of lining blocks for cement & lime kilns

send for full details of these grades  
HUNWICK magnesite-chrome  
ALITE high alumina  
PLANET abrasion resistant



**PRICE-PEARSON (SALES) LIMITED** STOURBRIDGE WORCS.



A member of the Price-Pearson Refractories Group