


CEMENT & LIME MANUFACTURE

VOL. XLI. No. 2

MARCH, 1968

Price 1s. 6d. per Copy.
Annual subscriptions: Inland 9s. post free.
Overseas 11s. 6d. including postage.
Canada and U.S.A. 1.80 dollars incl. post.



HAVER ROTO PACKER

Complete packing and loading plants with ROTO PACKERS or our in-line packers with or without pre-compacting device including all conveying, screening, dust-collecting and loading equipment for lorries, wagons and ships.

Furthermore:
Vibrating screens, laboratory screens with test sieves, electro-magnetic feeders, wire cloth of all metals.

More than 2500 Haver Packing Machines in operation all over the world

HAVER & BOECKER

4740 OELDE Westfalen - Germany

U.K. Representatives:- **CONTINENTAL ENGINEERING CO. LTD.**, London Road, Ascot, Berks.
Tel. No: Winkfield Row 20 11

FULLER-DRACCO GLASS CLOTH FILTERS FOR THE CEMENT INDUSTRY



- * For completely dust-free cement production both kilns and clinker coolers should have Fuller-Dracco Glass-Bag filters.
- * Fuller-Dracco Glass-Bag filters assure virtually 100% dust collection from hot gases.
- * Glass bags withstand continuous temperatures of up to 550°F.
- * Reverse air and sonic cleaning prolong bag life.
- * Bag-houses can be designed for vacuum or pressure operation and for any capacity.
- * The largest suction type Glass Cloth Collector in the world is a Dracco installation handling 350,000 c.f.m. dry process kiln gas.

Glass cloth gas cleaning has proved the most effective means of trapping hot dust in cement plants and Fuller's extensive experience in designing and developing Glass-Bag Dust Collectors for many applications makes us best qualified to build your next collecting system.

Fuller-Dracco Glass-Bag dust collectors operate at intake temperatures of up to 550°F without pre-cooling and we can offer a variety of bag cleaning techniques to suit your operating requirements. Bag-houses are tailor-made to suit individual applications and cost requirements. The glass bags incorporate Fuller's modern fabricating techniques to ensure maximum service life.

CONSTANTIN
(ENGINEERS) LTD.

RADNOR HOUSE · LONDON ROAD · NORBURY
LONDON · S.W.16 ☎ 01-764 9571

ECONSTANTIN
S.A.

105 rue Lafayette
PARIS 10^e ☎ 526 91.29

CONSTANTIN
ESPAÑOLA S.A.

Sancho el Sabio 28
SAN SEBASTIAN ☎ 18442

Licenses of FULLER CO. U.S.A.

GATX



PNEUMATIC CONVEYORS · BLENDING SYSTEMS
DUST COLLECTORS · COOLERS · CONTROL EQUIPMENT

GRINDING MEDIA INFORMATION

USED AND RECOMMENDED BY

"CRETIDS"

Reg. No. 573298

have been specially produced by us to meet the requirements of manufacturers for producing cement of extreme fineness. They have proved highly successful in finishing-mills without any cooling devices and, as with all our other types of grinding media, the wear-and-rear cost of "Cretoids" is infinitesimal. Free working samples are available on application.

THE WORLD'S LEADING CEMENT MAKERS


The comprehensive range of grinding media supplied by us and our unique experience in the cement industry in practically every country of the world enable us to give expert advice and to supply a type of grinding media that will provide the answer to any grinding problem.

HELPEBS LTD PHONE: GLOUCESTER 24051
GRAMS: HOLPEBS, GLOUCESTER
PREMIER WORKS
GLOUCESTER

Ask Vickers about cement making plant

You'll get the right answers...

wherever you are



With over 45 years experience of manufacture for the cement and allied industries, Vickers are uniquely equipped to meet all plant and machinery requirements — from a single kiln or mill installation right up to complete production plants. Write or telephone for information about our facilities and our world-wide service.


VICKERS

Complete Wet or Dry Process Plants Grinding Mills Kilns Ancillary Equipment

VICKERS LIMITED ENGINEERING GROUP CEMENT MACHINERY DIVISION (SALES) VICKERS HOUSE MILLBANK TOWER
MILLBANK LONDON SW1 01-828 7777 Technical enquiries: CEMENT MACHINERY DIVISION
VICKERS LTD ENGINEERING GROUP V-A ENGINEERING WORKS BARROW-IN-FURNESS LANCS BARROW-IN-FURNESS 3366

CM63A

HUMBOLDT offer something new in the range of lime shaft furnace construction:



A furnace type which has successfully been built for the past seven years.

HP 7/67

New is that we have taken over the design, construction and sales of a furnace type which up to now had been built by the Friedrich-Siemens, Industrieofenbau GmbH, Düsseldorf. It is the cross flow kiln - Röchling system. A lime shaft furnace which has successfully been sold in all parts of the world during the past seven years.

Now, through Klöckner-Humboldt-Deutz AG, this furnace system is further available to the construction, steel and chemical industries. If you have any problems in the field of lime shaft furnace construction, con-

sult us and we shall answer with a completely new HUMBOLDT product - with a gas or oil operated cross flow kiln, Röchling system.

HUMBOLDT design and build: Dressing plants for mineral-bearing raw materials, smelting works cement factories, plants for the chemical and fertilizer industries, automatic control systems, special centrifugal pumps and steel constructions. Humboldt Works, Telephone Köln 82 31, Telex 088 73501.




HUMBOLDT

KLÖCKNER-HUMBOLDT-DEUTZ AG · KÖLN



The cleanest and most efficient way to convey fine, dry solids is through a pipe

with a push from the CALLOW-DUCON FLUO/veyor



The Callow systems now incorporate the Callow-Ducon Fluo/veyor System which is one of the most advanced developments in dense phase pneumatic conveying of fine dry solids . . . such as plastic powders, cement, hydrated lime, fly ash, pulverised coke and coal, silica dust and fillers.

There are no moving parts . . . no screws, agitating nozzles or pressure-consuming orifices. Air volume and pressure requirements are low. The Fluo/veyor comes complete with compressor unit and controls.

Conventional dilute-phase systems can also be designed to meet your individual requirements.

For further information, contact:-




CALLOW ENGINEERING LTD

Pioneer Specialists in Pneumatic Conveying

SKELMERSDALE, LANCASHIRE, ENGLAND
Telephone: TAWD VALE 3321 (5 lines)

A MEMBER OF THE WESTON-EVANS GROUP

Matosinhos Cement Factory
(Brazil)



all over the world ...

the cement industry
relies on
FIVES LILLE-CAIL



7 RUE MONTALIVET PARIS 8^e - ANJ. 22.01, 32.40

solve your dust collection problems


with the Multiclone[®] Dust Collector

—proved in over 4,000 installations!

Multiclone, with its small diameter multi-tube design, means greater compactness, better adaptability, higher efficiency, and less maintenance. In every industry, the **Multiclone** offers the economy of unit construction with the adaptability of custom-built design. Long and narrow . . . square . . . short and wide . . . the **Multiclone** can be made to fit YOUR installation requirements.

APPLICATIONS. The **Multiclone** has been successfully applied to dust collection problems in many industries, including power, cement, chemical, coal and rock products.


[®] *Multiclone is a registered trade mark*



with Western Precipitation Dust Valves


—the best you can buy!

These valves all operate efficiently at temperatures up to 750°F and are available in six, eight and ten inch sizes.




THE TYPE R-1 MOTORIZED TIPPING VALVE

. . . positive time cycle motorized operation; gravity free-flow flushing features; gravity return assuring positive valve seating without pressure closure that guarantees non-jamming.



THE GRAVITY OPERATED TIPPING VALVE

. . . ideal for sealing dust collector hoppers operating under negative pressure (0–6 ins. W.G.) when handling dry free-flowing material.



THE FLOATING SEAL DUST VALVE

. . . for operation when handling abrasive materials particularly at high temperature.

Western Precipitation, the world leaders in dust control, are manufacturers of cottrell electrical precipitators, mechanical dust collectors, gas scrubbers, high temperature bag filters and dust valves. Write for more information about any of the above products to:



WESTERN PRECIPITATION

division of Joy Trading Corporation, 7 Harley Street, London W.1.
Tel: Langham (01-580) 7711. Telex: 23704. Cables: Joyloader London.


W.P.6

universal

Drives for the largest pumps, compressors, fans, mills, mixers and crushers for any application in any industry.

international

Complete factory electrification including the generation of power anywhere in the world.




LARGE
INDUSTRIAL
MACHINES
DIVISION,
BRADFORD, 3
Tel: 65221

250 hp 735 rpm dc motor
driving the rotary kiln
at the Rhoose Works of the
Aberthaw and Bristol Channel
Portland Cement Company Ltd.,
Glamorgan.

Never too big – or too small – for

**ENGLISH
ELECTRIC**





FOR BALL AND TUBE MILLS IN HIGH CARBON OR CHROME STEEL from 1" to 6" diam.

All hand forged to grind faster, last longer, never break and never lose shape.


Also fine hand forged tools for quarry and mine.

BRINDLEY

F. J. BRINDLEY & SONS (SHEFFIELD) LTD.

CENTRAL HAMMER WORKS,
ACRES HILL LANE, POOLE RD.,
DARNALL, SHEFFIELD 9.

Tel: Sheffield 49663/4 Grams: 49663/4



ROTARY DISC FEEDER

British Patent No. 769603

for controlled, infinitely-variable volumetric-measurements to close limits of many kinds of crushed and ground materials such as cement raw material, limestone, gypsum, coal, etc.


- Operates safely.
- Handles highly hygroscopic and sticky materials.
- Offers immediate response to automatic regulation.
- Is airtight and therefore suitable for use in grinding installations operating under vacuum or pressure conditions.

DELO (ENGINEERS) LTD.

138 Borough High Street
LONDON, S.E.1. Tel: 01-407 0085/6
Telegrams: OLED, LONDON, S.E.1

Also Drying Furnaces, Disc
Granulators, Pneumatic Conveyors

ROTARY KILNS WITH RAW MATERIAL PREHEATERS (S.F.A.C. Process)



**SCHNEIDER
CREUSOT**



**EQUIPMENT FOR CEMENT PLANTS
DRY PROCESS AND WET PROCESS**

SOCIÉTÉ DES FORGES ET ATELIERS DU CREUSOT
DÉPARTEMENT DE LA MÉCANIQUE

15, Rue Pasquier - 75 - Paris 8^e - Téléphone (1) 256-77.22
Adr. télégr.: Forgeac Paris 123 - Télex Monetoy 27 776



*A name as familiar
as cement itself*



You are invited to take advantage of our world-wide experience by consulting us regarding any problem connected with the manufacture of cement.

F.L. SMIDTH & CO. LTD.

P.O. BOX NO. 137, 17 LANSDOWNE ROAD, CROYDON. CR9 2JT.
Telephone: MUNICIPAL 5555. Telex No: 264021. Telegrams & Cables: Folasmidth Croydon

CEMENT AND LIME MANUFACTURE

PUBLISHED ALTERNATE MONTHS

PRICE 1s. 6d. A COPY

ANNUAL SUBSCRIPTION 9s. POST FREE
\$1.80 IN CANADA AND U.S.A

PUBLISHED BY
CONCRETE PUBLICATIONS LIMITED
60 BUCKINGHAM GATE, LONDON, S.W.1

TELEPHONE : 01-834-0705.
TELEGRAPHIC ADDRESS :
CONCRETIUS, PARL, LONDON.

ALSO PUBLISHERS OF
"CONCRETE"
"CONCRETE BUILDING & CONCRETE PRODUCTS"
"CEMENT & LIME MANUFACTURE"
"THE CONCRETE YEAR BOOK"
"CONCRETE SERIES": BOOKS

VOLUME XLI NUMBER 2

MARCH, 1968

Reaction Products at Early Ages of C_3A and of C_3AH_6 with Calcium Sulphate.

By J. H. P. VAN AARDT* and S. VISSER*.

AS THE reaction products of C_3A ** and of C_3AH_6 with sulphate are the same at equilibrium, and as C_3A in Portland cement causes expansion while apparently no distress is encountered with a similar quantity of C_3AH_6 , it seems justifiable to assume that the expansion or distress is due to intermediate metastable reaction products or the formation of such phases before equilibrium is reached. It is with this in mind that the reactions at very early ages of C_3A and of C_3AH_6 with gypsum were investigated.

Experiments

C_3A was prepared by repeated burning at 1370 deg. C. and crushing of a mixture of pure $CaCO_3$ and Al_2O_3 . The material was ground to pass a 325-mesh sieve before being used in the experiments, C_3AH_6 was prepared by autoclaving C_3A at 150 lb. per sq. in. for two hours. Precautions were taken to exclude CO_2 . Some solid was filtered off at various intervals and X-ray diagrams were prepared while the reaction mixture was kept at the required temperature in a humid nitrogen atmosphere. All X-ray diffraction work was carried out with copper $K\alpha$ radiation.


Reaction Mixtures

1.— C_3A (1.35g.) or C_3AH_6 (1.89g.) was reacted with $Ca(OH)_2$ (0.37g.) in water (100g.) or in saturated lime water [100g. plus 0.2g. $Ca(OH)_2$] at 5 deg. C. and 25 deg. C.

*National Building Research Institute, Council for Scientific and Industrial Research, Pretoria, S. Africa.

**The symbols are: C=CaO, A= Al_2O_3 , H= H_2O .

จัดพิมพ์ โดยกรมวิชาการ
20 มี.ค. 2511



(a). $C_3A(1.35g.)$ and $Ca(OH)_2(0.37g.)$ or $C_3AH_6(1.89g.)$ and $Ca(OH)_2(0.37g.)$ reacted at 5 deg. C. in saturated lime solution [water (100g.) plus $Ca(OH)_2(0.20g.)$; $CaSO_4 \cdot 2H_2O(0.86g.)$] and mixture kept at 25 deg. C.

(b). $C_3AH_6(1.89g.)$ and $Ca(OH)_2(0.37g.)$ reacted at 25 deg. C. in saturated lime solution [water (100g.) plus $Ca(OH)_2(0.16g.)$; $CaSO_4 \cdot 2H_2O(0.86g.)$] added after one week and mixture kept at 25 deg. C.

(c). $C_3A(1.35g.)$ and $Ca(OH)_2(0.37g.)$ reacted at 25 deg. C. in saturated lime solution [water (100g.) plus $Ca(OH)_2(0.16g.)$; $CaSO_4 \cdot 2H_2O(0.86g.)$] added after one week and mixture kept at 25 deg. C.

Fig. 1.—X-ray Diffractograms of Calcium Sulpho-aluminates.




Fig. 2.—X-ray Diffractograms of Calcium Sulpho-aluminates.

2.— $\text{CaSO}_4\cdot 2\text{H}_2\text{O}$ (0.86g.) or $3\text{CaSO}_4\cdot 2\text{H}_2\text{O}$ (2.58g.) were added to the suspensions above and kept at 25 deg. C.

3.— C_3A (1.35g.) or C_3AH_6 (1.89g.) was reacted with $\text{Ca}(\text{OH})_2$ (0.37g.) and $\text{CaSO}_4\cdot 2\text{H}_2\text{O}$ (0.86g.) or $3\text{CaSO}_4\cdot 2\text{H}_2\text{O}$ (2.58g.) in water (100g.) at 25 deg. C.

4.— C_3A (1.35g.) or C_3AH_6 (1.89g.) was reacted with $\text{CaSO}_4\cdot 2\text{H}_2\text{O}$ (0.86g.) or $3\text{CaSO}_4\cdot 2\text{H}_2\text{O}$ (2.58g.) in water (100g.) or in saturated lime water [100g. plus 0.16 $\text{Ca}(\text{OH})_2$] at 25 deg. C.

Discussion

REACTION MIXTURE 1.—It has been recorded in a previous publication¹ that

(i) A compound with d-spacings 10.6Å, 5.3Å was observed when C_3A and $\text{Ca}(\text{OH})_2$ or C_3AH_6 and $\text{Ca}(\text{OH})_2$ were reacted in water at 5 deg. C.


(ii) A compound with d-spacings 8.2Å, 4.1Å was observed when C_3AH_6 and $\text{Ca}(\text{OH})_2$ were reacted in water at 25 deg. C.; and

(iii) Both compounds were present when C_3A and $\text{Ca}(\text{OH})_2$ were reacted in water at 25 deg. C.

Some C_3AH_6 and $\text{Ca}(\text{OH})_2$ were always present in the reaction mixtures kept at 25 deg. C. When saturated $\text{Ca}(\text{OH})_2$ water was used identical reaction products


1.—VAN AARDT, J. H. P. and VISSER, S. "Some reactions of Tricalcium-aluminate-hexahydrate at medium temperatures." *Cem. Lime Mf.*, vol. XL, No. 1, January 1967.

were formed and $\text{Ca}(\text{OH})_2$ was detected in the mixtures kept at 5 deg. C. REACTION MIXTURE 2.—The addition of one mole of sulphate to the 10.6Å compound produced a phase with d-spacings 9.6Å, 4.77Å at early ages, that is one hour to seven days (see *Fig. 1a*). This substance changed to a phase with d-spacings 8.9Å, 4.4Å at equilibrium. When three moles of sulphate were added, only the 9.6Å compound and $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ were observed at one hour; the equilibrium phase was ettringite. The presence of excess $\text{Ca}(\text{OH})_2$ tended to retard the reaction rate. In brief:



One mole of sulphate added to the 8.2Å compound, produced a phase with d-spacings 8.5Å, 4.23Å and ettringite: gypsum was also present at an early age, that is, one hour, but was not detected at seven days (see *Fig. 1b*). The 8.5Å compound changed to ettringite and finally at equilibrium the 8.9Å compound was observed; the change from ettringite to 8.9Å appeared to pass through the 9.6Å substance. When three moles of sulphate were added the 8.5Å phase and gypsum were observed at one hour; the equilibrium phase was ettringite. The presence of $\text{Ca}(\text{OH})_2$ tended to retard the reaction rate.

In brief:



In the presence of gypsum, a suspension containing both the 10.6Å and 8.2Å compounds gave the intermediate phases 9.6Å and 8.5Å at early ages (see *Fig. 1c*) REACTION MIXTURE 3.—In this experiment the reactants were all added at once; C_3A and CaSO_4 rapidly formed ettringite; the latter then reacted with more calcium aluminat to form the 9.6Å compound within one day. C_3AH_6 reacted with the CaSO_4 to again produce ettringite; in this instance the ettringite was only slowly changed to the 9.6Å substance. The equilibrium phase was again the 8.9Å compound in both instances. Three moles of sulphate gave only ettringite at early ages while unreacted sulphate and aluminat were present.

REACTION MIXTURE 4.—With one mole of sulphate and C_3A the 9.6Å-phase was predominant after one day (see *Fig. 2a*), but with C_3AH_6 , ettringite was predominant (see *Fig. 2b*); at later ages both suspensions contained the 9.6Å-compound. In the presence of saturated $\text{Ca}(\text{OH})_2$ solutions, the 8.9Å-phase was detected at equilibrium. Ettringite was the only phase observed when three moles of gypsum were added to the aluminates.

Conclusions

It has been shown (reaction mixture 2) that if sulphate was added to suspensions of C_3A and $\text{Ca}(\text{OH})_2$ or C_3AH_6 and $\text{Ca}(\text{OH})_2$ that were kept for seven days at

5 deg. C before the addition of the sulphate, similar calcium sulpho-aluminates were observed, but if similar experiments were made at 25 deg. C, the reactions followed different courses to the same equilibrium phases, which are either the 8.9Å-calcium sulpho-aluminate, ettringite or a mixture of these two calcium sulpho-aluminates, depending on whether one mole or less, three moles, or one to three moles, of gypsum are used, respectively. The new phases at 9.6Å for C_3A and sulphate and 8.5Å for C_3AH_6 and sulphate, and the fact that C_3AH_6 tends to produce ettringite immediately while C_3A goes through the 9.6Å phase, may provide a lead to a precise explanation of sulphate expansion phenomena in Portland cement containing medium to high percentages of C_3A . This may also offer an explanation for the discrepancies sometimes observed in the relationship between C_3A content and sulphate susceptibility of a Portland cement.

New Cement Works in Nigeria

TWO NEW cement works have been established recently in Nigerian territories, namely at Ukpilla and Calabar. Both works are described briefly in the following.

UKPILLA WORKS

THE NEW cement works at Ukpilla, about 120 miles north-east of Benin City in Mid-western Nigeria, has been built for the Ukpilla Cement Co. Ltd., by a consortium comprising Friedrich Krupp of Rheinhaussen, which firm supplied the main mechanical equipment, Continho Caro & Co. of Hamburg, and Philipp Holzman, the civil engineering contractors. Electrical equipment was supplied by Brown-Boveri. The works, the daily productive capacity of which is 500 tons of ordinary Portland cement, operates on the dry process, with a Krupp suspended-dust preheater and rotary kiln. A plan of the works is shown in *Fig. 1*, a general view is shown in *Fig. 2*, and a view of the workshops and stores are shown in *Fig. 3*. The illustrations in *Figs. 2* and *3* on page 26 are reproduced from photographs supplied by the Krupp organisation. *Fig. 1* is given on pages 24 and 25.

Raw Material

A limestone quarry is being developed about 2 miles from the works. The stone is won by drilling and blasting and is loaded by a 1.3 cu. m. Demag diesel shovel into Aveling-Barford 15-ton dumpers for transport to the works, where it is discharged into a ground hopper. It is then fed by an apron-feeder into a hammer-crusher, where the stone is reduced in size from 800 mm. to 25 mm. The crushed product is conveyed by belt, with a throw-off carriage, to the storage hall.

Clay is dug in the neighbourhood of the works by contractors who deliver it to the works, where it is crushed by a roll-crusher and dried in a Rapid drier fired by oil. From the drier, the material is discharged into the storage hall.

Provision is made to receive and handle a third component material available locally, if such is required.





Fig. 1.—Plan of Cement

Preparation of Raw Material

The storage hall for the raw materials, clinker and gypsum is 130 m. long by 25 m. wide and is served by a travelling crane of 8-tons capacity. Concrete hoppers for each material are provided in the hall. The raw-material hoppers are equipped with feeder-weighers, with automatic control, which feed a correctly proportioned mixture on to a belt-conveyor by means of which it is transported to the raw-materials mill.

The raw-materials mill is a single-chamber tube-mill, which operates on closed circuit and is 6.5 m. long and 3.0 m. in diameter. The drying of the material to 0.5-per cent. moisture content is completed in the mill by hot flue gases from



Works at Ukpilla, Nigeria.

the kiln. The purge from the closed circuit passes to an electrostatic precipitator on the kiln outlet. The product, after grinding, is taken to the blending and storage silos by pneumatic trough-conveyors and a pneumatic elevator.

There are three blending silos each of which is of 5-m. diameter and is equipped with air-agitation equipment. They are mounted on the top of a storage silo of 13-m. diameter. The silos are constructed of reinforced concrete, and the structure has an overall height of about 45 m.

The finished raw meal is extracted from the silo and elevated pneumatically to the kiln feeder-weigher from which it is taken to the feed-point of the kiln by a trough-conveyor and bucket-elevator.




Fig. 2.—General View of Ukpilla Works, Nigeria.

Burning

The kiln plant comprises a Krupp counterflow preheater, about 60 m. high, with two cyclones and three chambers, a rotary oil-fired kiln 48 m. long and 3.45 m. in diameter, and a Fuller inclined-grate cooler. D.C. motors are used for obtaining variable speed for both the kiln and the induced-draught fan. The exit gases are finally cleaned in a Walther electrostatic precipitator.

The cooled clinker is transferred to the storage hall by a bucket-tray conveyor and a drum-weigher.




Fig. 3.—Workshop and Stores, Ukpilla Works.

Grinding, Storing and Packing

Clinker and gypsum are extracted from the hoppers in the storage hall by weigher-feeders with automatic proportioning control, and taken to the mill on a belt-conveyor. The mill, which is 8.5 m. long and 3.0 m. in diameter, has two chambers and works on closed circuit, the purge being cleaned in an Intensive filter containing 136 stockings. The mill-drive is a 920-kw. motor operating through a girth-gear and a reduction gear-box.

The finished cement is transferred to a single concrete silo 13 m. in diameter and 32 m. high. Sliding formwork was used in the construction of the structure and the blending and raw-meal silos.

The cement is packed into 50-kg. paper bags by two Haver & Boecker three-spout packers each equipped with retractable conveyors for loading lorries.

The works is equipped with the usual laboratory, workshop and office facilities. Living quarters for the supervisory staff have been built about two miles from the works.


CALABAR WORKS

THE OTHER new cement works in Nigeria is at Calabar and was officially opened in February 1967. The works was planned and built by Salzgitter Industriebau G.m.b.H., and Deutsche Industrielagen Fritz Werner G.m.b.H., of West Germany, the civil engineering contractors being the Monier Construction Co., of Port Harcourt, Nigeria. The designed annual productive capacity of clinker is 100,000 tonnes, part of which would be despatched as clinker.

The works, a plan of which is given in *Fig. 5*, operates on the wet process and is situated on the northern outskirts of Calabar on the bank of the Calabar River, where a deep-water berth has been constructed for loading clinker and packed cement into sea-going vessels. *Fig. 5* is given on page 28. Some views of the works are shown in *Figs. 4, 6 and 7*.

The raw materials, limestone and shale, are won from a quarry about 20 miles to the east of the works. A road had to be constructed from the works and passes through areas of dense bush, forests with trees more than 50 ft. high, over deep swamps and the River Kwa, the crossing of which required a bridge

Fig. 4.—Calcinator House and Raw Meal Silos at Calabar Works.






Fig. 5.—Plan of
Cement Works
at
Calabar,
Nigeria.

Fig. 6. — Calcinator House, Kiln and Quarry Dumpers at Calabar Works.



900 ft. long. The materials are transported, as dug, to the works by a fleet of sixteen dumpers and are there crushed to mill-size in a Miag-Titan hammer-crusher.

The raw materials, clinker and gypsum are stored in a main materials store, which is served by two overhead cranes. They are ground wet to produce slurry,

Fig. 7. — Materials Store (showing Clinker Conveyor to Wharf) at Calabar Works.



in a Miag open-circuit compound mill. There are two concrete silos with air-agitation equipment for blending, and two storage silos for the finished slurry.

The slurry is burned in a kiln plant comprising a Miag calcinator, a Miag rotary kiln, and a Fuller inclined-grate cooler. The flue-gases are cleaned in a multi-cyclone separator.

The clinker is ground in an open-circuit Miag compound mill, from which the cement is pumped to the two concrete silos.

The packing plant is on the river-side wharf. The cement is pumped from the silos to the hoppers at the packing plant by Fuller Kinyon pumps. The silos are about 750 ft. from and some 60 ft. above the wharf. The cement is packed by two two-spout Haver & Boecker packers into 50-kg. paper bags for loading on to lorries or into vessels berthed alongside.

Clinker for shipment in bulk is extracted from the storage hall through openings in the floor, and falls on to a belt-conveyor, equipped with a weigher, in a tunnel beneath the floor on which it is transported to the wharf, where it is discharged by means of a boom direct into the holds of berthed vessels.

The works was shown in a British news-reel on B.B.C. Television in November last. Unfortunately, some damage was sustained during the recent fighting and the works is now shut down.

The Cement Industry in Kenya

WITH REFERENCE to the note in the November 1967 number of this journal, the Bamburi Portland Cement Co. Ltd., of Mombasa, have informed this journal that the Bamburi works are referred to as belonging to the British Standard Portland Cement Co. Ltd. The latter Company is now known as the Bamburi Portland Cement Co. Ltd. In December last, a new Humboldt preheater and rotary kiln, with a guaranteed output of 750 tons per day, came into operation and, in the same month, a new bulk-carrying ship "Cementia" arrived in Mombasa to join her sister ship "Bamburi," giving additional carrying capacity for deliveries in the Indian Ocean area. During December, the Company sold a total of 26,916 tons of cement.

Separating Effect and Efficiency of Classifiers

IN THE article in the January number of this journal on the "Separating Effect and Efficiency of Classifiers," by DR. R. RUEGG, the formula at the bottom of page 8

$$\sigma_M = 1/(1-u_4)$$

should be given the serial number (6), and the reference to formula (5) near the bottom of page 10 should be to this formula (6).

The second term in formula (3) should be $\frac{F \cdot f}{A \cdot a}$

The symbols z and Σ in the text have the same significance respectively ε s the symbol γ in Fig. 3, and the symbol Σ in Table II and Fig. 6.

Refractory Gunite Lining of Lime Shaft-kiln

THE WEST'S vertical shaft-kiln at the lime works of Limestone Products Ltd., at Abergele, North Wales, has a capacity of 70 tons per day and is oil-fired by the Catagas system. It is in continuous operation permitting only one annual shut-down period, during which it is necessary to repair the refractory brick lining owing to erosion in the critical area in the burning zone. For this work West's (Manchester) Ltd., the constructors of the kiln, recommended Steetley Chambers Ltd., to be consulted and the latter firm suggested monolithic repairing. The process proposed and carried out was applying by the guniting method, "Gunolith L.I.", an aluminosilicate material. The repair, which was carried out over the




Fig. 1.
Vertical Shaft
Lime Kiln at
Abergele.



Fig. 2.—Burning Zone of Vertical Lime Kiln at Abergele.

badly worn areas, gave a lining with a low iron content, high density and a good abrasability index, suitable for working temperatures up to 1500 deg. C.

The accompanying illustrations show, in *Fig 1*, a general view of the kiln at Abergele and, in *Fig. 2*, the burning zone of the kiln when partly re-lined; a further application of the gunite lining is required to bring the lining to its correct profile.

Previous experience with gunite linings has shown that the degree of wear was no greater than with brick linings, and the benefits derived from the speedier work of the repairing of the lining are considerable. None of the existing worn brickwork needs to be taken out since the gunite is applied directly on to it, the thickness depending on the amount of wear of the brick lining. The time taken to reline the shaft-kiln at Abergele was reduced by 60 per cent. It is also claimed that the cost of materials was reduced by 25 per cent., since expensive bricks of special shapes were not required.



Consett

ROTACON Bricks

**THE Hot Zone Lining
for ROTARY CEMENT KILNS!**

Specially developed for Portland Cement Kilns by Consett Iron Co. Ltd. ROTACON possesses all the important characteristics necessary in a basic liner brick.

ROTACON bricks build up a sound coating rapidly and withstand kiln shut-downs without spalling. They are not subject to chemical attack at high operating temperatures and will not disintegrate from thermal contraction. *The ideal basic lining for the production of Portland Cement.*

**ROTACON BRICKS SAVE MONEY
BY INCREASED KILN AVAILABILITY**



CONSETT IRON CO. LTD.
CONSETT · COUNTY DURHAM

Telephone : Consett 3411

Telex : 53172





If this is your problem

Stein Two-Taper System is the solution



In two-taper construction, two sizes of bricks are used, one with "fast" and one with "slow" taper, easily identified by different colours and supplied in the correct ratio to suit a given kiln diameter.

Two-taper construction has the advantages—

- Linings do not have to be tailor-made giving quicker delivery from the manufacturer.
- Brick stocks are simplified and reduced—just vary the ratio of tapers for the different sizes of kilns in the plant.
- If kiln shell irregularities are encountered through re-lining, the ratio can be altered as required using proportionately more "fast" or "slow" tapers to maintain a tight build to the shell and at the same time, ensuring that all joints are radial.

As major suppliers to Rotary Cement Kilns in the United Kingdom and Exporters to Cement Plants throughout the World, we would be pleased to advise on and quote for your requirements from our comprehensive range of Rotary Cement Kiln Refractories.

For further details please consult our Technical Service Department.

JOHN G. STEIN & CO. LTD., BONNYBRIDGE, SCOTLAND. TEL: BANKNOCK 255 (4 LINES) 361 & 362

STEIN
Refractories

ANTICIPATE THE NEEDS OF INDUSTRY

The Cement Industry in the United Kingdom

Extension of Rugby Cement Works

THE NEW extension of the Rugby Portland Cement Co.'s works at Rugby is now proceeding and comprises mainly the installation of a new kiln. The site of the new kiln is an old quarry which has been filled, and therefore it is necessary to provide foundation piles extending down to the rock of the quarry floor to support the plant. The foundations will have to resist considerable lateral thrust from the movement and operations of the kiln and, to withstand this, inclined pressure-grouted piles of the M.V. system will be used. There will be forty-two of these piles, each 18 in. square and 83 ft. long ; the inclination will be 45 deg.

For supporting vertical loads, twenty vertical Hochstrasser-Weisepiles, 4 ft. in diameter and 112 ft. long will be provided.

The piles of both systems are being installed by Economic Foundations Ltd.

Extension of Southerham Works

EASTWOODS CEMENT LTD., one of the companies of the Rugby Portland Cement Co. Ltd., has applied for planning permission for extensions adjacent to the works at Southerham, near Lewes, Sussex. The proposals include the erection of a chimney 400 ft. high; the neighbouring Mount Caburn, a local beauty spot, is 488 ft. high. Excavation of the chalk is proposed up to the 350-ft. contour. The net area of the two quarries, Southerham Quarry and Machine Bottom Quarry, would be about 145 acres.

The new works comprise, in addition to the chimney, a kiln and kilnhouse, an electrostatic precipitator, a materials store, cement mill house, cement silos, and packing and loading plant, together with ancillary offices, stores, laboratory and railway sidings.

A new raw-materials plant proposed for Machine Bottom Quarry will comprise crushing plant, washmills, screening plant, slurry storage basins and pumphouse.

It is understood that the extraction rate from the new quarry could reach 500,000 tons of chalk a year.

A secondary application seeks to establish a 52-acre clay working, together with vehicle loading plant and repair shop, on land adjoining Ripe railway crossing. This is a completely new works.


Silo for White Cement

BECAUSE WHITE structural concrete is becoming increasingly popular, The Cement Marketing Company has recently installed a silo for storing white Portland cement, "Snowcrete," at the depot at Northenden, Manchester. Special road tankers are reserved for transporting this material direct from the depot to the sites.

Cement Silos, Ipswich

THE CONSTRUCTION of the reinforced concrete cement storage silos in *Fig. 1* was completed early this year at Mason's Works, near Ipswich, which is one of the works of The Associated Portland Cement Manufacturers Ltd. The silos, each of

Fig. 1.—Cement Silos, Ipswich.



which has a capacity of 2,000 tons, are supported 40 ft. above the ground on an entablature the slab of which is carried on concrete columns 3 ft. square. Due to difficult ground conditions at the site, where the strata comprises filling overlying putty chalk, which becomes harder with increase in depth, it was necessary to provide a piled foundation. A total of 108 Frankipiles, each of 90-ton capacity, support the columns and extend to depth of 60 to 70 ft.


The consulting engineers were Messrs Oscar Faber & Partners, the contractors being The Mitchell Construction Co., Ltd.

Sulphuric-acid and Cement Plant at Whitehaven

THE ILLUSTRATION in *Fig. 2* shows the five kilns, which are now on stream producing sulphuric acid at the rate of over 1,000 tons per day, at the Whitehaven works of Marchon Products Ltd. An equal quantity of cement is produced at the same time. The operation is independent of imported sulphur since it is based on the anhydrite process, the raw material for which is mined from Marchon's own mine on the site at Whitehaven.

Mobile Pre-Crushing Units


with



MIAG Double-Shaft Hammer Crusher «TITAN»

on undercarriage of
Messrs. Weserhütte Otto Wolff G.m.b.H.

are crushing up to 1000 t/h of limestone as well as minerals of similar kind to a grain size smaller than 25 mm in one operating process




MIAG

BRAUNSCHWEIG/Germany

AGENCY FOR GREAT BRITAIN

INDUSTRIAL EQUIPMENT CO. (N.I.) Ltd., 58, Howard St. Belfast



**Complete Plants
for manufacturing**

**ASBESTOS CEMENT
PIPES and SHEETS..**

PRESSURE PIPES

DOWN PIPES

CORRUGATED

AND FLAT

SHEETS



ASBESTOS CEMENT ENGINEERING CO.
AEULESTRASSE 772, VADUZ - LIECHTENSTEIN
Switzerland. P.O. Box 34,722.

... Production, delivery, service and (if required) finance for complete installations, large or small.

Installations complètes pour la fabrication des tuyaux haute et basse pression et des plaques planes et ondulées en amiant-cimenté.

Production, livraison, service et (si désiré) financement des installations complètes grandes ou petites.

AGENTS REQUIRED

MISCELLANEOUS ADVERTISEMENTS

SCALE OF CHARGES

FOR

MISCELLANEOUS ADVERTISEMENTS

5s. per line
(average seven words per line).

For use of Box Number,
allow two lines.

Minimum £1
for not more than four lines.

DISPLAYED ADVERTISEMENTS

45s. per single column inch.

Advertisements must reach the offices of this journal at 60 Buckingham Gate, London, S.W.1, by the 1st of the month of publication.

FOR SALE

The "SPEEDY" Moisture Tester—a simple, efficient method of testing moisture content in sand, soil, clay, etc., in three minutes. Portable, non-electric—over 37,000 "SPEEDYS" in use. Full details from Thomas Ashworth & Co., Ltd., Dept. CLM, Sycamore Avenue, Burnley, Lancashire.

BOUND VOLUMES OF "CEMENT AND LIME MANUFACTURE"

BINDING cases for annual volumes of "Cement and Lime Manufacture" can be supplied in cloth-covered boards lettered in gold on the spine with the title, volume number, and year of publication. Copies for binding should be sent post paid to Concrete Publications Ltd., 60 Buckingham Gate, London, S.W.1.

When possible, missing numbers will be supplied at the published price to make up incomplete sets, but as many of the numbers published during the past few years are not available it is advisable to ask the Publishers whether they have the numbers required before sending incomplete sets.

The cost of cloth-covered lettered cases is 15s. for each volume. The cost of supplying a case and binding a volume is 25s. including packing and carriage.

EQUIPMENT FOR SALE

2 Aerial Ropeways installations (Bleichert - Leipzig) and two cable cranes for the limestone transport :

One of the installations has a loading capacity of 100 tons/hour with carrying cables 1,320 m. long and an 18-mm. pulling cable 2,750 m. long; speed 2.3 m./second.

This installation has 37 wagonnets in good condition and 18 which need to be repaired—the loading capacity of these wagonnets being 910 kg. When loaded these wagonnets weigh 1,320 kg. each.

The second installation has a loading capacity of 84 tons/hour with an aerial rope 490 m. long and a pulling cable of 1,000 m. long.

This installation has 25 wagonnets with a loading capacity of 700 kg. Its average loading capacity is 120 wagonnets per hour.

The two cable cranes of 260 m. and 280 m. are equipped with carrying cables of 260 to 625 m.

We have also some spare parts and spare cables in good condition

Box 2021, Cement and Lime Manufacture, 60, Buckingham Gate, London, S.W.1.




Fig. 2.—Kilns at Whitehaven.

Transport of Clinker

SPECIAL TRAINS have been arranged by the London Midland Region of British Rail to convey cement clinker in bulk from Whitehaven to Wishaw and Coatbridge in Scotland. The clinker, which is a by-product of the process for making sulphuric acid at the chemical plant of Marchon Products Ltd., is despatched in train loads to Scotland by the Cement Marketing Co., Ltd. Road vehicles bring the clinker from the works to the loading site at Whitehaven where it is tipped into a hopper and transferred by conveyor belts to the rail wagons. Two special trains run each week to Coatbridge and consist of forty-two wagons each having a capacity of 16 tons, giving a total train load of 640 tons. Originally one train, carrying about 700 tons of clinker in 26-ton capacity tipper wagons, was despatched each week to Wishaw. With the improved discharge facilities now completed at Wishaw, modified 30-ton hopper wagons are being used on this service and an average of two trains is run each week. The carriage of cement clinker from Whitehaven is eventually planned to reach a total of 200,000 tons per annum.

Cookstown Works, Northern Ireland

WITH REFERENCE to the article in the number of this journal for January 1968, describing some aspects of the new cement works for The Associated Portland Cement Manufacturers Ltd., at Cookstown, Northern Ireland, it should be mentioned that the design and supply of the rotary kiln and Lepol grate preheater, granulator plant and conveying equipment, the regrind mill and ancillaries for raw-meal preparation have been carried out by Polysius Ltd. This equipment is for the semi-dry process and is similar to the equipment installed by Polysius Ltd., at other works of The Associated Portland Cement Manufacturers Ltd., at Caudon, Dunbar and Weardale.

Pitstone Works, Bucks

IN THE description of the new works of the Tunnel Portland Cement Co., Ltd.,

at Pitstone, Bucks., the size of the kiln house was given as 1,800 ft. by 500 ft. These are the overall dimensions of the entire works.

Cement Industry Abroad

U.S.S.R.—It has been announced that the Soviet Union, which is reported to have been leading the world in cement production during the past few years, has now taken first place in the world for exports of cement. These exports have increased by more than five times during the past seven years, and it is expected that, in 1968, about 2,300,000 tons, which is a record amount, will be exported. The exports are to twenty-one countries, but mainly to Africa and Asia. Deliveries to Latin America are expected to start shortly, Brazil having already bought 150,000 tons with possible further purchases to follow. White cement for facing buildings is supplied to southern countries. In 1966, Hungary commenced importing cement from the U.S.S.R., and exports to the Netherlands and possibly to Italy will commence this year.

Yugoslavia.—The Dalmacija Cement Company, the largest cement producing organisation in Yugoslavia, is extending its works at Prvoborac near Split, and has placed an order with the Humboldt division of Klöckner-Humboldt-Deutz A.G. (KHD), for the new plant. The plant will comprise a Humboldt preheater for a rotary kiln 64 m. long and 4·2 m. in diameter, as well as the raw material and clinker mills with the corresponding precipitators and dust-collecting systems. When the new plant is complete (production is expected by the end of 1969), the Dalmacija Cement Company will attain an annual output of 1,100,000 tons of cement.


The Dalmacija Cement Company had installed a Humboldt preheater in its Partizan works as long ago as 1956.

Eire.—It was announced last month that Cement Ltd., the sole cement manufacturing concern in Eire, had increased its annual sales by 15 per cent. in the year ending September 30, 1967. The total value of cement sold was £8,710,000. For the current year, exports are a little uncertain and there will be added competition in this field when the new works of The Associated Portland Cement Manufacturers Ltd., is in operation at Cookstown.

Publisher's Note

THIS NUMBER of "Cement & Lime Manufacture" is the first to be printed by Fleetway Printers in succession to Cornwall Press Ltd., the latter firm, which has now ceased business, had printed this journal since 1930.

"**my** in a grate big tube corld a kiln witch
daddy goes round and round. Inside their
makes are a lot of speshul briks corld
siment refractrees becors it gets
 very hot. My daddy says the
 best refractrees are made by
 a general who must be very
 clever nearly as clever as my
 daddy who makes siment"



548

There is much more than mere cleverness behind the excellence of GR products, like years of experience, extensive research, the selection and blending of the right raw materials, care, craftsmanship and other things too numerous to mention—but you can't expect a little girl to know all that, can you? And she has forgotten to mention

Spinella AC

the GR basic refractory that plays such an important part in the cement industry today.

Send for Spinella AC data sheet.

**General
Refractories**



Genefax House, Tapton Park Road,
Sheffield S10 3FJ Telephone: 0742 31118

PLANET HUNWICK ALITE

a complete range of lining blocks for cement & lime kilns

send for full details of these grades


HUNWICK magnesite-chrome

ALITE high alumina

PLANET abrasion resistant



PRICE-PEARSON (SALES) LIMITED STOURBRIDGE WORCS.



A member of the Price-Pearson Refractories Group

2 0 115 231